

Experiment 2: Supplementary Analyses

2023-02-24

Contents

Setup	1
Without <i>Other</i> Responses	3
Model 1: Condition w/o <i>Other</i> Responses	3
Odds Ratios: Intercept	4
Odds Ratios: Last vs First+Full	4
Odds Ratios: Last Only	5
Odds Ratios: First and Full Only	6
Model 2: Condition * Name Gender w/o <i>Other</i> Responses	7
Quadratic Name Gender Rating	8
Model 3: Quadratic	8
Participant Gender	9
Setup/Data Summary	9
Model 4: Condition * Participant Gender	10
Interaction	12
Model 5: Condition * Name Gender * Participant Gender	14
Gender Rating Centering	15
Model 6: Gender Rating Recentered	16

Setup

Variable names:

- Experiment: exp2__
- Data (_d_)
 - d = main df
 - FF = First + Full Name conditions only
 - noOther = just *he* and *she* responses

- subjGender = participant gender
- Models (`_m_`)
 - cond = effect of Condition (Last vs First+Full)
 - nameGender = effects of Condition (First vs Full) and Name Gender Rating
 - FF = dummy coded with First + Full Name conditions as 0, Last Name condition as 1
 - L = dummy coded with Last Name condition as 0, First + Full Name conditions as 1
 - quad = quadratic effect of Gender Rating
 - subjGender = participant gender
 - recentered = center name gender rating by scale (at 4)

Load data and select columns used in model. See `data/exp2_data_about.txt` for more details.

```
exp2_d <- read.csv("../data/exp2_data.csv",
                  stringsAsFactors=TRUE) %>%
  rename("Participant" = "SubjID", "Item" = "NameShown") %>%
  select(Participant, SubjGenderMale, Condition, GenderRating,
         Item, Male, Female, Other)
str(exp2_d)
```

```
## 'data.frame': 9457 obs. of 8 variables:
## $ Participant : Factor w/ 1351 levels "Exp2_P1","Exp2_P10",...: 501 501 501 501 501 501 501 14 14 ...
## $ SubjGenderMale: int 1 1 1 1 1 1 1 0 0 0 ...
## $ Condition : Factor w/ 3 levels "first","full",...: 1 1 1 1 1 1 1 1 1 ...
## $ GenderRating : num 5.59 4.22 2.12 6.73 3.61 4.73 1.21 6.24 4.39 2.61 ...
## $ Item : Factor w/ 105 levels "Ashley","Ashley Cook",...: 51 91 18 60 87 55 63 1 47 29 ...
## $ Male : int 1 1 0 1 1 0 1 0 0 1 ...
## $ Female : int 0 0 1 0 0 1 0 1 1 0 ...
## $ Other : int 0 0 0 0 0 0 0 0 0 0 ...
```

Center gender rating for names: Original scale from 1 to 7, with 1 as most masculine and 7 as most feminine. Mean-centered with higher still as more feminine.

```
exp2_d %<>% mutate(GenderRatingCentered =
  scale(GenderRating, scale = FALSE))
```

Set contrasts for name conditions.

```
contrasts(exp2_d$Condition) = cbind(
  "last vs first/full" = c(.33, .33, -0.66),
  "first vs full" = c(-.5, .5, 0))
contrasts(exp2_d$Condition)
```

```
##      last vs first/full first vs full
## first      0.33      -0.5
## full      0.33      0.5
## last     -0.66      0.0
```

Subset for gender rating effects (First and Full conditions only).

```
exp2_d_FF <- exp2_d %>% filter(Condition != "last")
exp2_d_FF$Condition %<>% droplevels()
contrasts(exp2_d_FF$Condition) = cbind(
  "first vs full" = c(-.5, .5)) #add contrast back
contrasts(exp2_d_FF$Condition)
```

```
##           first vs full
## first           -0.5
## full            0.5
```

Without *Other* Responses

The first supplementary analysis tests if excluding OTHER responses (3.72% of total responses) affects the pattern of results.

```
sum(exp2_d$Other)
```

```
## [1] 352
```

```
sum(exp2_d$Other)/length(exp2_d$Other)
```

```
## [1] 0.03722111
```

Exclude *other* responses.

```
exp2_d_noOther <- exp2_d %>% filter(Other == 0)
exp2_d_FF_noOther <- exp2_d_FF %>% filter(Other == 0)
```

Model 1: Condition w/o *Other* Responses

Effect of Name Condition (first name, last name, full name) on likelihood of a *female* response, as opposed to a *male* response, with *other* responses excluded. Participant and Item are again included as random intercepts, with items defined as the unique first, last and first + last name combinations.

```
exp2_m_cond_noOther <- glmer(
  Female ~ Condition + (1|Participant) + (1|Item),
  data = exp2_d_noOther, family = binomial)
summary(exp2_m_cond_noOther)
```

```
## Generalized linear mixed model fit by maximum likelihood (Laplace
## Approximation) [glmerMod]
## Family: binomial ( logit )
## Formula: Female ~ Condition + (1 | Participant) + (1 | Item)
## Data: exp2_d_noOther
##
##           AIC          BIC    logLik deviance df.resid
##    8950.7    8986.3  -4470.3   8940.7      9100
##
```

```
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -2.8774 -0.4708 -0.3082  0.5527  4.7451
##
## Random effects:
##   Groups      Name      Variance Std.Dev.
##   Participant (Intercept) 0.1024   0.320
##   Item         (Intercept) 1.7798   1.334
## Number of obs: 9105, groups: Participant, 1322; Item, 105
##
## Fixed effects:
##
##              Estimate Std. Error z value Pr(>|z|)
## (Intercept)      -0.7854     0.1505  -5.220 1.79e-07 ***
## Conditionlast vs first/full   1.9225     0.3423   5.616 1.96e-08 ***
## Conditionfirst vs full      -0.2003     0.3441  -0.582   0.561
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##              (Intr) Cvfrs/
## Cndtnvfirst/ -0.170
## Cndtnfrstvf -0.361 -0.241
```

No differences.

Odds Ratios: Intercept

```
exp(get_intercept(exp2_m_cond_no0ther))
```

```
## [1] 0.4559352
```

```
exp(-get_intercept(exp2_m_cond_no0ther))
```

```
## [1] 2.193294
```

0.45x less likely to recall as female overall (or: 2.19x more likely to recall as male/other overall), $p < .001$

Odds Ratios: Last vs First+Full

```
exp2_m_cond_no0ther %>% tidy() %>%
  filter(term == "Conditionlast vs first/full") %>%
  pull(estimate) %>% exp()
```

```
## [1] 6.838129
```

6.84x more likely to use *she* in First + Full compared to Last (or: 6.84x times more likely to use *he* and *other* in Last than in First + Full), $p < .001$

Odds Ratios: Last Only

Dummy code with Last Name as 0, so that intercept is the Last Name condition only.

```
exp2_d_noOther %<>% mutate(Condition_Last = case_when(
  Condition == "first" ~ 1,
  Condition == "full" ~ 1,
  Condition == "last" ~ 0))
exp2_d_noOther$Condition_Last %<>% as.factor()
```

```
exp2_m_L_noOther <- glmer(
  Female ~ Condition_Last + (1|Participant) + (1|Item),
  data = exp2_d_noOther, family = binomial)
summary(exp2_m_L_noOther)
```

```
## Generalized linear mixed model fit by maximum likelihood (Laplace
## Approximation) [glmerMod]
## Family: binomial ( logit )
## Formula: Female ~ Condition_Last + (1 | Participant) + (1 | Item)
## Data: exp2_d_noOther
##
##      AIC      BIC   logLik deviance df.resid
##  8949.0   8977.5 -4470.5   8941.0     9101
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -2.8705 -0.4718 -0.3082  0.5518  4.7752
##
## Random effects:
##  Groups      Name      Variance Std.Dev.
## Participant (Intercept) 0.1024   0.320
## Item          (Intercept) 1.7849   1.336
## Number of obs: 9105, groups: Participant, 1322; Item, 105
##
## Fixed effects:
##              Estimate Std. Error z value Pr(>|z|)
## (Intercept)    -2.0543    0.2923  -7.027 2.11e-12 ***
## Condition_Last1  1.8558    0.3293   5.636 1.74e-08 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##              (Intr)
## Condtm_Lst1 -0.888
```

```
exp(get_intercept(exp2_m_L_noOther))
```

```
## [1] 0.1281845
```

```
exp(-get_intercept(exp2_m_L_noOther))
```

```
## [1] 7.801258
```

0.13x times less likely to recall as female in the Last Name condition (or: 7.80x more likely to recall as male in the Last Name condition), $p < .001$

Odds Ratios: First and Full Only

Dummy code with First and Full Name as 0, so that intercept is average for these two conditions.

```
exp2_d_noOther %<>% mutate(Condition_FF = case_when(
  Condition == "first" ~ 0,
  Condition == "full" ~ 0,
  Condition == "last" ~ 1))
exp2_d_noOther$Condition_FF %<>% as.factor()
```

```
exp2_m_FF_noOther <- glmer(
  Female ~ Condition_FF + (1|Participant) + (1|Item),
  data = exp2_d_noOther, family = binomial)
summary(exp2_m_FF_noOther)
```

```
## Generalized linear mixed model fit by maximum likelihood (Laplace
## Approximation) [glmerMod]
## Family: binomial ( logit )
## Formula: Female ~ Condition_FF + (1 | Participant) + (1 | Item)
## Data: exp2_d_noOther
##
##      AIC      BIC   logLik deviance df.resid
##  8949.0   8977.5 -4470.5   8941.0     9101
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -2.8705 -0.4718 -0.3082  0.5518  4.7752
##
## Random effects:
##  Groups      Name      Variance Std.Dev.
## Participant (Intercept) 0.1024   0.320
## Item          (Intercept) 1.7849   1.336
## Number of obs: 9105, groups: Participant, 1322; Item, 105
##
## Fixed effects:
##              Estimate Std. Error z value Pr(>|z|)
## (Intercept)   -0.1985    0.1517  -1.308   0.191
## Condition_FF1 -1.8558    0.3293  -5.635 1.75e-08 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##              (Intr)
## Conditn_FF1 -0.460
```

```
exp(get_intercept(exp2_m_FF_noOther))
```

```
## [1] 0.8199412
```

```
exp(-get_intercept(exp2_m_FF_noOther))
```

```
## [1] 1.2196
```

0.82x times less likely to recall as female in the First and Full Name conditions (or: 1.22x more likely to use *he* in the First and Full Name conditions), $p=.17$

Model 2: Condition * Name Gender w/o *Other* Responses

Effects of Name Condition (first name, full name) and the first name's Gender Rating (centered, positive=more feminine) on the likelihood of a *female* response as opposed to a *male* response, with *other* responses excluded. In Experiment 2, the Last Name condition does not include any instances of the gendered first name, so it is not included here. Participant and Item are again included as random intercepts.

```
exp2_m_nameGender_noOther <- glmer(
  Female ~ Condition * GenderRatingCentered + (1|Participant) + (1|Item),
  data = exp2_d_FF_noOther, family = binomial)
summary(exp2_m_nameGender_noOther)
```

```
## Generalized linear mixed model fit by maximum likelihood (Laplace
## Approximation) [glmerMod]
## Family: binomial ( logit )
## Formula: Female ~ Condition * GenderRatingCentered + (1 | Participant) +
## (1 | Item)
## Data: exp2_d_FF_noOther
##
##      AIC      BIC    logLik deviance df.resid
## 6599.9   6640.3  -3294.0   6587.9     6195
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -2.8767 -0.6104 -0.2386  0.6019  4.2441
##
## Random effects:
## Groups      Name      Variance Std.Dev.
## Participant (Intercept) 0.02864  0.1692
## Item          (Intercept) 0.13866  0.3724
## Number of obs: 6201, groups: Participant, 897; Item, 83
##
## Fixed effects:
##
##              Estimate Std. Error z value
## (Intercept)    -0.12585    0.05754  -2.187
## Conditionfirst vs full    -0.19186    0.11493  -1.669
## GenderRatingCentered      0.78391    0.03496  22.423
## Conditionfirst vs full:GenderRatingCentered -0.06121    0.06855  -0.893
##
##              Pr(>|z|)
## (Intercept)      0.0287 *
## Conditionfirst vs full    0.0951 .
## GenderRatingCentered    <2e-16 ***
## Conditionfirst vs full:GenderRatingCentered  0.3719
## ---
```

```
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##      (Intr) Cndtvf GndrRC
## Cndtnfrstvf -0.344
## GndrRtngCnt -0.058 -0.013
## Cvfll:GndRC -0.011 -0.052 -0.293
```

Compared to the main analysis including *other* responses, the intercept has a larger p-value, the difference between the First and Full Name conditions is no longer trending, and the Name Gender Rating is the same.

Quadratic Name Gender Rating

The second supplementary analysis tested the effect of squared name gender rating, such that larger values meant names with stronger gender associations (masc or fem), and smaller values meant names with weaker gender associations.

```
exp2_d_FF %<>% mutate(GenderRatingSquared = GenderRatingCentered^2)
```

Model 3: Quadratic

No quadratic effects.

```
exp2_m_nameGender_quad <- glmer(
  Female ~ Condition*GenderRatingCentered + Condition*GenderRatingSquared +
    (1|Participant) + (1|Item),
  data = exp2_d_FF, family = binomial)
summary(exp2_m_nameGender_quad)

## Generalized linear mixed model fit by maximum likelihood (Laplace
## Approximation) [glmerMod]
## Family: binomial ( logit )
## Formula:
## Female ~ Condition * GenderRatingCentered + Condition * GenderRatingSquared +
## (1 | Participant) + (1 | Item)
## Data: exp2_d_FF
##
##      AIC      BIC   logLik deviance df.resid
##  6779.2   6833.2  -3381.6   6763.2     6313
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -2.8991 -0.6319 -0.2351  0.6235  4.4716
##
## Random effects:
## Groups      Name             Variance Std.Dev.
## Participant (Intercept) 0.1137    0.3372
## Item          (Intercept) 0.1409    0.3754
## Number of obs: 6321, groups: Participant, 903; Item, 83
##
```



```
## Fixed effects:
##
##              Estimate Std. Error z value
## (Intercept)    -0.13892    0.08064  -1.723
## Conditionfirst vs full    -0.25775    0.16129  -1.598
## GenderRatingCentered      0.77906    0.03558  21.895
## GenderRatingSquared     -0.01296    0.01963  -0.661
## Conditionfirst vs full:GenderRatingCentered -0.06125    0.06977  -0.878
## Conditionfirst vs full:GenderRatingSquared  0.01120    0.03921   0.286
##
##              Pr(>|z|)
## (Intercept)      0.0849 .
## Conditionfirst vs full    0.1100
## GenderRatingCentered    <2e-16 ***
## GenderRatingSquared      0.5089
## Conditionfirst vs full:GenderRatingCentered  0.3800
## Conditionfirst vs full:GenderRatingSquared  0.7752
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##              (Intr) Cndtvf GndrRC GndrRS Cvf:GRC
## Cndtnfrstvf -0.375
## GndrRtngCnt -0.164  0.052
## GndrRtngSqr -0.687  0.258  0.168
## Cvfll:GndrRC  0.058 -0.165 -0.306 -0.087
## Cvfll:GndrRS  0.258 -0.688 -0.083 -0.331  0.175
```

Participant Gender

Setup/Data Summary

The third supplementary analysis looks at participant gender: if male participants show a larger bias to recall the character as male than non-male participants.

Participants entered their gender in a free-response box.

```
exp2_d %>% group_by(SubjGenderMale) %>%
  summarise(total = n_distinct(Participant)) %>%
  kable()
```

SubjGenderMale	total
0	569
1	694
NA	88

For this analysis, we exclude participants who did not respond (N=88). Because there are not enough participants to create 3 groups, we compare male to non-male participants. Male participants (N=694) are coded as 1, and female (N=566), nonbinary (N=2), and genderqueer (N=1) participants are coded as 0.

Summary of responses by condition and participant gender:

```
exp2_d_subjGender <- exp2_d %>%
  filter(!is.na(SubjGenderMale)) %>%
  mutate(ResponseAll = case_when(
```

```

Male == 1 ~ "Male",
Female == 1 ~ "Female",
Other == 1 ~ "Other"))

exp2_d_subjGender %>%
  group_by(Condition, ResponseAll, SubjGenderMale) %>%
  summarise(n = n()) %>%
  pivot_wider(names_from = ResponseAll,
              values_from = n) %>%
  rename("ParticipantGender" = "SubjGenderMale") %>%
  mutate(ParticipantGender = case_when(
    ParticipantGender == "0" ~ "Non-male",
    ParticipantGender == "1" ~ "Male")) %>%
  mutate(Female_MaleOther = Female / (Male+Other),
         Female_Male = Female / Male) %>%
  kable(digits = 3)

```

Condition	ParticipantGender	Female	Male	Other	Female_MaleOther	Female_Male
first	Non-male	693	609	21	1.100	1.138
first	Male	784	847	14	0.911	0.926
full	Non-male	601	609	43	0.922	0.987
full	Male	734	893	32	0.794	0.822
last	Non-male	170	1146	91	0.137	0.148
last	Male	212	1223	119	0.158	0.173

Participant gender is mean centered effects coded, comparing non-male participants to male participants.

```

exp2_d_subjGender$SubjGenderMale %<>% as.factor()
contrasts(exp2_d_subjGender$SubjGenderMale) = cbind("NM_M" = c(-.5, .5))
contrasts(exp2_d_subjGender$SubjGenderMale)

```

```

## NM_M
## 0 -0.5
## 1 0.5

```

Subset First and Full conditions.

```

exp2_d_FF_subjGender <- exp2_d_subjGender %>% filter(Condition != "last")
exp2_d_FF_subjGender$Condition %<>% droplevels()
contrasts(exp2_d_FF_subjGender$Condition) =
  cbind("first vs full" = c(-.5, .5)) #add contrast back
contrasts(exp2_d_FF_subjGender$Condition)

```

```

## first vs full
## first -0.5
## full 0.5

```

Model 4: Condition * Participant Gender

Effect of Name Condition (first name, last name, full name) and Participant Gender (non-male vs male) on likelihood of a *female* response, as opposed to a *male* response or *other* response. Participant and Item are again included as random intercepts.

```

exp2_m_cond_subjGender <- glmer(
  Female ~ Condition * SubjGenderMale + (1|Participant) + (1|Item),
  data = exp2_d_subjGender, family = binomial)
summary(exp2_m_cond_subjGender)

## Generalized linear mixed model fit by maximum likelihood (Laplace
## Approximation) [glmerMod]
## Family: binomial ( logit )
## Formula: Female ~ Condition * SubjGenderMale + (1 | Participant) + (1 |
## Item)
## Data: exp2_d_subjGender
##
##      AIC      BIC    logLik deviance df.resid
## 8549.0    8605.6  -4266.5   8533.0     8833
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -3.6665 -0.4635 -0.2879  0.5557  4.6794
##
## Random effects:
## Groups      Name      Variance Std.Dev.
## Participant (Intercept) 0.1828   0.4275
## Item          (Intercept) 1.8258   1.3512
## Number of obs: 8841, groups: Participant, 1263; Item, 105
##
## Fixed effects:
##
##              Estimate Std. Error z value
## (Intercept)      -0.85062    0.15276  -5.568
## Conditionlast vs first/full      2.02308    0.34754   5.821
## Conditionfirst vs full      -0.20021    0.34946  -0.573
## SubjGenderMaleNM_M      -0.12522    0.06205  -2.018
## Conditionlast vs first/full:SubjGenderMaleNM_M -0.41779    0.14249  -2.932
## Conditionfirst vs full:SubjGenderMaleNM_M      0.09225    0.14019   0.658
##
##              Pr(>|z|)
## (Intercept)      2.57e-08 ***
## Conditionlast vs first/full      5.84e-09 ***
## Conditionfirst vs full      0.56669
## SubjGenderMaleNM_M      0.04357 *
## Conditionlast vs first/full:SubjGenderMaleNM_M 0.00337 **
## Conditionfirst vs full:SubjGenderMaleNM_M      0.51051
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##              (Intr) Cvfrs/ Cndtvf SGMNM_ Cvf/:S
## Cndtnvfrst/ -0.170
## Cndtnfrstvf -0.359 -0.240
## SbjGndMNM_M -0.022  0.001 -0.002
## Cvf/:SGMNM_  0.003 -0.023 -0.001 -0.196
## Cvf:SGMNM_M -0.002 -0.001 -0.024 -0.002 -0.001

```

- Male participants are less likely to recall the character as female overall, but this is not significant after correction for multiple comparisons.

- The interaction between Condition (Last vs. First + Full) and Participant Gender is significant.

Interaction

Dummy code to get the Participant Gender effect just for First and Full Name conditions.

```
exp2_d_subjGender %<>% mutate(Condition_FF = case_when(
  Condition == "first" ~ 0,
  Condition == "full" ~ 0,
  Condition == "last" ~ 1))
exp2_d_subjGender$Condition_FF %<>% as.factor()

exp2_m_cond_FF_subjGender <- glmer(
  Female ~ Condition_FF*SubjGenderMale + (1|Participant) + (1|Item),
  data = exp2_d_subjGender, family = binomial)
summary(exp2_m_cond_FF_subjGender)
```

```
## Generalized linear mixed model fit by maximum likelihood (Laplace
##   Approximation) [glmerMod]
##   Family: binomial   ( logit )
## Formula: Female ~ Condition_FF * SubjGenderMale + (1 | Participant) +
##   (1 | Item)
##   Data: exp2_d_subjGender
##
##      AIC      BIC    logLik deviance df.resid
##  8545.7   8588.2  -4266.8   8533.7     8835
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -3.7198 -0.4648 -0.2879  0.5527  4.6970
##
## Random effects:
##   Groups      Name      Variance Std.Dev.
## Participant (Intercept) 0.1832   0.4281
## Item          (Intercept) 1.8318   1.3535
## Number of obs: 8841, groups: Participant, 1263; Item, 105
##
## Fixed effects:
##
##              Estimate Std. Error z value Pr(>|z|)
## (Intercept)      -0.22873    0.15432  -1.482  0.138294
## Condition_FF1      -1.95738    0.33433  -5.855  4.78e-09 ***
## SubjGenderMaleNM_M -0.26325    0.07015  -3.753  0.000175 ***
## Condition_FF1:SubjGenderMaleNM_M  0.41378    0.14108   2.933  0.003357 **
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##              (Intr) Cn_FF1 SGMNM_
## Conditn_FF1 -0.461
## SbjGndMNM_M -0.028  0.015
## C_FF1:SGMNM  0.014 -0.023 -0.497
```

Then dummy code to get the participant gender effect just for Last Name condition.

```

exp2_d_subjGender %<>% mutate(Condition_L = case_when(
  Condition == "first" ~ 1,
  Condition == "full" ~ 1,
  Condition == "last" ~ 0))
exp2_d_subjGender$Condition_L %<>% as.factor()

exp2_m_cond_L_subjGender <- glmer(
  Female ~ Condition_L*SubjGenderMale + (1|Participant) + (1|Item),
  data = exp2_d_subjGender, family = binomial)
summary(exp2_m_cond_L_subjGender)

## Generalized linear mixed model fit by maximum likelihood (Laplace
## Approximation) [glmerMod]
## Family: binomial ( logit )
## Formula: Female ~ Condition_L * SubjGenderMale + (1 | Participant) + (1 |
## Item)
## Data: exp2_d_subjGender
##
##      AIC      BIC    logLik deviance df.resid
## 8545.7   8588.2  -4266.8   8533.7     8835
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -3.7198 -0.4648 -0.2879  0.5527  4.6970
##
## Random effects:
## Groups      Name      Variance Std.Dev.
## Participant (Intercept) 0.1832   0.4281
## Item          (Intercept) 1.8318   1.3535
## Number of obs: 8841, groups: Participant, 1263; Item, 105
##
## Fixed effects:
##
##              Estimate Std. Error z value Pr(>|z|)
## (Intercept)      -2.1861     0.2967  -7.367 1.75e-13 ***
## Condition_L1       1.9574     0.3344   5.854 4.80e-09 ***
## SubjGenderMaleNM_M  0.1505     0.1224   1.230 0.21876
## Condition_L1:SubjGenderMaleNM_M -0.4138     0.1411  -2.933 0.00336 **
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##      (Intr) Cnd_L1 SGMNM_
## Conditin_L1 -0.887
## SbjGndMNM_M -0.021  0.019
## C_L1:SGMNM_  0.019 -0.023 -0.868

```

- Beta for subj gender in First + Full: -0.26325
- Beta for subj gender in Last: 0.1505 NS

→ Male participants were less likely to recall the referent as female than non-male participants in the First and Full Name conditions. No participant gender difference in the Last Name condition.

Model 5: Condition * Name Gender * Participant Gender

Effects of Name Condition (first name, full name), the first name's Gender Rating (centered, positive=more feminine), and Participant Gender (non-male vs. male) on the likelihood of a *female* response as opposed to *male* or *other* responses. In Experiment 2, the Last Name condition does not include any instances of the gendered first name, so it is not included here.

```
exp2_m_nameGender_subjgender <- buildmer(
  formula = Female ~ Condition * GenderRatingCentered * SubjGenderMale +
    (1|Participant) + (1|Item),
  data = exp2_d_FF_subjGender, family = binomial,
  buildmerControl(direction = "order", quiet = TRUE))
summary(exp2_m_nameGender_subjgender)
```

```
## Generalized linear mixed model fit by maximum likelihood (Laplace
## Approximation) (p-values based on Wald z-scores) [glmerMod]
## Family: binomial ( logit )
## Formula: Female ~ 1 + GenderRatingCentered + SubjGenderMale + Condition +
##           GenderRatingCentered:SubjGenderMale + GenderRatingCentered:Condition +
##           SubjGenderMale:Condition + GenderRatingCentered:SubjGenderMale:Condition +
##           (1 | Item) + (1 | Participant)
## Data: exp2_d_FF_subjGender
##
##           AIC           BIC    logLik deviance df.resid
##    6256.0      6322.8   -3118.0   6236.0     5870
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -3.3843 -0.6313 -0.2289  0.6377  4.3983
##
## Random effects:
##  Groups      Name          Variance Std.Dev.
## Participant (Intercept) 0.09857  0.3140
## Item         (Intercept) 0.14889  0.3859
## Number of obs: 5880, groups: Participant, 840; Item, 83
##
## Fixed effects:
##                                     Estimate
## (Intercept)                        -0.15983
## GenderRatingCentered                 0.80814
## SubjGenderMaleNM_M                  -0.22830
## Conditionfirst vs full              -0.20337
## GenderRatingCentered:SubjGenderMaleNM_M -0.14941
## GenderRatingCentered:Conditionfirst vs full -0.05830
## SubjGenderMaleNM_M:Conditionfirst vs full  0.12761
## GenderRatingCentered:SubjGenderMaleNM_M:Conditionfirst vs full -0.11630
##                                     Std. Error
## (Intercept)                        0.06058
## GenderRatingCentered                 0.03677
## SubjGenderMaleNM_M                  0.06826
## Conditionfirst vs full              0.12106
## GenderRatingCentered:SubjGenderMaleNM_M 0.04500
## GenderRatingCentered:Conditionfirst vs full 0.07191
## SubjGenderMaleNM_M:Conditionfirst vs full 0.13645
```

```

## GenderRatingCentered:SubjGenderMaleNM_M:Conditionfirst vs full    0.08997
##                                                                    z value
## (Intercept)                                                         -2.63817
## GenderRatingCentered                                                21.98051
## SubjGenderMaleNM_M                                                  -3.34465
## Conditionfirst vs full                                              -1.67990
## GenderRatingCentered:SubjGenderMaleNM_M                            -3.31991
## GenderRatingCentered:Conditionfirst vs full                        -0.81074
## SubjGenderMaleNM_M:Conditionfirst vs full                           0.93524
## GenderRatingCentered:SubjGenderMaleNM_M:Conditionfirst vs full    -1.29269
##                                                                    Pr(>|z|)
## (Intercept)                                                         0.008
## GenderRatingCentered                                                0.000
## SubjGenderMaleNM_M                                                  0.001
## Conditionfirst vs full                                              0.093
## GenderRatingCentered:SubjGenderMaleNM_M                            0.001
## GenderRatingCentered:Conditionfirst vs full                        0.418
## SubjGenderMaleNM_M:Conditionfirst vs full                           0.350
## GenderRatingCentered:SubjGenderMaleNM_M:Conditionfirst vs full    0.196
##                                                                    Pr(>|t|)
## (Intercept)                                                         0.008336 **
## GenderRatingCentered                                                < 2e-16 ***
## SubjGenderMaleNM_M                                                  0.000824 ***
## Conditionfirst vs full                                              0.092977 .
## GenderRatingCentered:SubjGenderMaleNM_M                            0.000900 ***
## GenderRatingCentered:Conditionfirst vs full                        0.417513
## SubjGenderMaleNM_M:Conditionfirst vs full                           0.349664
## GenderRatingCentered:SubjGenderMaleNM_M:Conditionfirst vs full    0.196119
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##          (Intr) GndrRC SGMNM_ Cndtvf GRC:SG GRC:Cvf SGMNvf
## GndrRtngCnt -0.062
## SbjGndMNM_M -0.092 -0.010
## Cndtnfrstv -0.329 -0.013 -0.017
## GRC:SGMNM_M -0.011 -0.147 -0.126  0.024
## GndrRtC:Cvf -0.011 -0.276  0.021 -0.056 -0.033
## SGMNM_M:Cvf -0.018  0.022  0.010 -0.094 -0.036 -0.003
## GRC:SGMNMvf  0.024 -0.035 -0.035 -0.011 -0.003 -0.144 -0.127

```

- Male participants are less likely to recall the character as female overall. This matches the results of the interaction in the condition-only model.
- The interaction between participant gender and first name gender rating is significant. Smaller effect of name gender rating in male participants.
- Interaction with Condition, three-way interaction with Name Gender and Condition n.s.

Gender Rating Centering

The first name gender ratings aren't perfectly centered, partially because mostly-feminine/somewhat-masculine names are much less common than mostly-masculine/somewhat-feminine names.

```
mean(exp2_d$GenderRating, na.rm = TRUE)
```

```
## [1] 4.22436
```

Does it make a difference if we center it on 4, the mean of the scale, instead of 4.22, the mean of the items?

```
exp2_d_FF %<>% mutate(GenderRating4 = GenderRating - 4)
```

Model 6: Gender Rating Recentered

```
exp2_m_recenter <- glmer(
  Female ~ Condition * GenderRating4 + (1|Participant) + (1|Item),
  data = exp2_d_FF, family=binomial)
summary(exp2_m_recenter)
```

```
## Generalized linear mixed model fit by maximum likelihood (Laplace
## Approximation) [glmerMod]
## Family: binomial ( logit )
## Formula: Female ~ Condition * GenderRating4 + (1 | Participant) + (1 |
## Item)
## Data: exp2_d_FF
##
##      AIC      BIC    logLik deviance df.resid
## 6775.6   6816.1  -3381.8   6763.6     6315
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -2.9386 -0.6285 -0.2404  0.6240  4.3729
##
## Random effects:
## Groups      Name                Variance Std.Dev.
## Participant (Intercept) 0.1137     0.3372
## Item         (Intercept) 0.1414     0.3760
## Number of obs: 6321, groups: Participant, 903; Item, 83
##
## Fixed effects:
##                                     Estimate Std. Error z value Pr(>|z|)
## (Intercept)                       -0.35142    0.05961  -5.896 3.73e-09 ***
## Conditionfirst vs full              -0.20833    0.11889  -1.752  0.0797 .
## GenderRating4                      0.78323    0.03506  22.338 < 2e-16 ***
## Conditionfirst vs full:GenderRating4 -0.06596    0.06862  -0.961  0.3365
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##              (Intr) Cndtvf GndrR4
## Cndtnfrstvf -0.329
## GenderRtng4 -0.195  0.025
## Cvfll:GndR4  0.028 -0.186 -0.297
```

Here, the absolute value of the beta estimate for the intercept is again larger for the intercept (-0.35 vs -0.18) but the same for the condition effect (-0.21 vs -0.22).