

# Bayesian inference of an individual-based mutualistic network

03\_03

## Net 03\_03

```
library(BayesianNetworks)
library(network.tools)
library(tidyverse)
theme_set(theme_minimal())
options(mc.cores = 4)
```

## Data

Load dataset and sampling effort per individual plant:

```
web <- readr::read_csv(here::here("data/nets_raw", paste0(params$net, "_int.csv"))) |>
  arrange(ind)
```

```
## Rows: 14 Columns: 14
## -- Column specification -----
## Delimiter: ","
## dbl (14): ind, Turdus_chiguanco, Turdus_amaurochalinus, Turdus_rufiventris, Mimus_triurus, Turdus_ni,
##
## i Use 'spec()' to retrieve the full column specification for this data.
## i Specify the column types or set 'show_col_types = FALSE' to quiet this message.
```

```
mat <- as.matrix(web[, -1])
mat <- apply(mat, c(1,2), as.integer)
rownames(mat) <- web$ind
```

```
# create numeric vector of sampling effort for each plant with names = plant id
effort <- readr::read_csv(here::here("data/nets_attr", paste0(params$net, "_attr.csv"))) |>
  select(ind, starts_with("se_")) |>
  filter(ind %in% web$ind) |>
  arrange(ind)
```

```
## Rows: 14 Columns: 13
## -- Column specification -----
## Delimiter: ","
## chr (3): site_type, fruit_type, fruit_color
## dbl (10): ind, crop, neigh_n_fruits, neigh_fruiting_sp, neigh_and_focal_n_fruits, DBH_cm, height_cm,
##
## i Use 'spec()' to retrieve the full column specification for this data.
## i Specify the column types or set 'show_col_types = FALSE' to quiet this message.
```

```

## If there is only one column with sampling effort, use it:
if (!net %in% c("15_01", "18_01", "18_02", "20_01", "21_01", "21_02")) {
  effort <- effort |>
    pull(starts_with("se_"), name = "ind")
}

# Otherwise, select sampling effort column in some specific nets:
if (net == "15_01") {
  effort <- effort |>
    pull(se_cam_days, name = "ind")
}

if (net %in% c("18_01", "18_02", "20_01")) {
  effort <- effort |>
    mutate(se_bc_months = se_bc_days/30) |>
    pull(se_bc_months, name = "ind")
}

if (net %in% c("21_01", "21_02")) {
  effort <- effort |>
    pull(se_obs_h, name = "ind")
}

## Some nets may require adjusting of the count data or effort values
## Insert that here eg.
# if (params$net == "01_01") {
#   mat <- round(mat/10)
#   mat <- apply(mat, c(1,2), as.integer)
# }

stopifnot(identical(length(effort), nrow(mat)))
stopifnot(identical(names(effort), rownames(mat)))

summary(as.numeric(mat))

```

```

##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##      0.000   0.000   0.000   2.632   1.500  46.000

```

```

if (max(mat) > 500) {
  stop("More than 500 counts in some cell(s)")
}

summary(effort)

```

```

##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##         4         4         4         4         4         4

```

```


if (max(effort) > 500) {
  stop("Sampling effort > 500 for some plants")
}

```

## Bayesian inference of network structure

```
dt <- prepare_data(mat, sampl.eff = effort)

plot_prior(params$beta)
```



```
fit <- fit_model(dt,
  refresh = 0,
  beta = params$beta,
  model = params$model,
  # max_treedepth = 15,
  # init = function() list(r = runif(1, 0, 20000)),
  iter_warmup = params$iter,
  iter_sampling = params$iter,
  thin = 4 * params$iter / 1000)
```

```
## Running MCMC with 4 parallel chains...
##
## Chain 2 finished in 10.9 seconds.
## Chain 4 finished in 10.9 seconds.
## Chain 3 finished in 11.2 seconds.
## Chain 1 finished in 11.4 seconds.
##
## All 4 chains finished successfully.
```

```
## Mean chain execution time: 11.1 seconds.  
## Total execution time: 11.5 seconds.
```


```
get_seed(fit)
```

```
## [1] 790355651
```


```
check_model(fit, data = dt)
```

```
## Processing csv files: C:/Users/frodr/AppData/Local/Temp/RtmpkDNfRE/varying_preferences-202406241405-  
##  
## Checking sampler transitions treedepth.  
## Treedepth satisfactory for all transitions.  
##  
## Checking sampler transitions for divergences.  
## No divergent transitions found.  
##  
## Checking E-BFMI - sampler transitions HMC potential energy.  
## E-BFMI satisfactory.  
##  
## Effective sample size satisfactory.  
##  
## Split R-hat values satisfactory all parameters.  
##  
## Processing complete, no problems detected.
```

Preference (r) parameter: prior (dark grey) vs posterior (light grey) distrib



## Log posterior across chains



## Posteriors


Get posterior distributions:

```
post <- get_posterior(fit, dt)
head(post)
```

```
## # A tibble: 6 x 11
## # Groups:   Animal, Plant [6]
##   Plant Animal      .chain .iteration .draw connectance preference plant.abund animal.abund int.pr
##   <chr> <chr>      <int>      <int> <int>      <dbl>      <dbl>      <dbl>      <dbl>      <dbl>
## 1 31   Turdus_chigu~    1          1     1         0.319      257.      0.0782      0.135      1
## 2 32   Turdus_chigu~    1          1     1         0.319      257.      0.0387      0.135      1
## 3 33   Turdus_chigu~    1          1     1         0.319      257.      0.00682     0.135     0.15
## 4 34   Turdus_chigu~    1          1     1         0.319      257.      0.197       0.135      1
## 5 35   Turdus_chigu~    1          1     1         0.319      257.      0.0667      0.135      1
## 6 36   Turdus_chigu~    1          1     1         0.319      257.      0.0129      0.135     0.07
```

Mean edge probability:

```
plot_interaction_prob(post)
```





## Generate predicted visits for each pairwise interaction


```
post.counts <- predict_counts(fit, dt)
```

Compare observed and predicted visits by the model:

```
p <- plot_counts_pred(post.counts, sort = FALSE)
o <- plot_counts_obs(mat, sort = FALSE, zero.na = FALSE)
library(patchwork)
p + o
```




```
plot_counts_pred_obs(post.counts, dt)
```



```
plot_counts_pred_obs(post.counts, dt, byplant = TRUE, scales = "free")
```





```
saveRDS(post.counts, here::here(paste0("data/nets_post/", params$net, "_post_counts.rds")))
```