

Bayesian inference of an individual-based mutualistic network

15_01

Net 15_01

```
library(BayesianNetworks)
library(network.tools)
library(tidyverse)
theme_set(theme_minimal())
options(mc.cores = 4)
```

Data

Load dataset and sampling effort per individual plant:

```
web <- readr::read_csv(here::here("data/nets_raw", paste0(params$net, "_int.csv"))) |>
  arrange(ind)
```

```
## Rows: 26 Columns: 12
## -- Column specification -----
## Delimiter: ","
## chr (1): ind
## dbl (11): Cervus_elaphus, Vulpes_vulpes, Meles_meles, Genetta_genetta, Oryctolagus_cuniculus, Dama_d...
##
## i Use 'spec()' to retrieve the full column specification for this data.
## i Specify the column types or set 'show_col_types = FALSE' to quiet this message.
```

```
mat <- as.matrix(web[, -1])
mat <- apply(mat, c(1,2), as.integer)
rownames(mat) <- web$ind
```

```
# create numeric vector of sampling effort for each plant with names = plant id
effort <- readr::read_csv(here::here("data/nets_attr", paste0(params$net, "_attr.csv"))) |>
  select(ind, starts_with("se_")) |>
  filter(ind %in% web$ind) |>
  arrange(ind)
```

```
## Rows: 29 Columns: 16
## -- Column specification -----
## Delimiter: ","
## chr (4): ind, fruit_type, fruit_color, seeds_per_fruit
## dbl (12): crop_y2, d1_cm, d2_cm, x, y, fruit_d1_mm, fruit_d2_mm, fruit_d1_sd, fruit_d2_sd, se_cam_da...
```

```

##
## i Use 'spec()' to retrieve the full column specification for this data.
## i Specify the column types or set 'show_col_types = FALSE' to quiet this message.

## If there is only one column with sampling effort, use it:
if (!net %in% c("01_01", "01_02", "02_01", "02_02", "02_03", "10_01", "11_01",
               "15_01", "18_01", "18_02", "20_01", "21_01", "21_02")) {
  effort <- effort |>
    pull(starts_with("se_"), name = "ind")
}

# Otherwise, select sampling effort column in some specific nets:
if (net == "10_01") {
  effort <- effort |>
    mutate(se_cam_days = se_cam_h/24) |>
    pull(se_cam_days, name = "ind")
}

if (net == "11_01") {
  effort <- effort |>
    mutate(se_cam_months = se_cam_days/30) |>
    pull(se_cam_months, name = "ind")
}

if (net == "15_01") {
  effort <- effort |>
    mutate(se_cam_months = se_cam_days/30) |>
    pull(se_cam_months, name = "ind")
}

if (net %in% c("18_01", "18_02", "20_01")) {
  effort <- effort |>
    mutate(se_bc_months = se_bc_days/30) |>
    pull(se_bc_months, name = "ind")
}

if (net %in% c("21_01", "21_02")) {
  effort <- effort |>
    pull(se_obs_h, name = "ind")
}

# For Pistacia and Juniperus, use constant sampling effort
if (net %in% c("01_01", "01_02", "02_01", "02_02", "02_03")) {
  effort <- rep(10, nrow(mat))
  names(effort) <- web$ind
}

## Some nets may require adjusting of the count data or effort values
# if (net %in% c("01_01", "01_02", "02_01", "02_02", "02_03")) {
#   mat <- mat/10 # divide counts by 10 to make modelling feasible
#   mat[mat > 0 & mat < 1] <- 1 # don't miss rare counts
#   mat <- round(mat)
#   mat <- apply(mat, c(1,2), as.integer)
# }

```

```
stopifnot(identical(length(effort), nrow(mat)))
stopifnot(identical(names(effort), rownames(mat)))
```

```
# summary(mat)
summary(as.numeric(mat))
```

```
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##      0.000   0.000   0.000   1.073   0.750   36.000
```

```
# if (max(mat) > 1000) {
#   stop("More than 1000 counts in some cell(s)")
# }
```

```
summary(effort)
```

```
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##      1.022   2.671   3.390   4.397   6.505   8.795
```


```
if (max(effort) > 500) {
  stop("Sampling effort > 500 for some plants")
}
```

Bayesian inference of network structure

```
dt <- prepare_data(mat, sampl.eff = effort)

plot_prior(params$beta)
```

Prior probability for r (preference) parameter with beta = 0.01



```
fit <- fit_model(dt,
  refresh = 0,
  beta = params$beta,
  model = params$model,
  # max_treedepth = 15,
  # init = function() list(r = runif(1, 0, 20000)),
  iter_warmup = params$iter,
  iter_sampling = params$iter,
  thin = 4 * params$iter / 1000)
```

```
## Running MCMC with 4 parallel chains...
##
## Chain 4 finished in 20.0 seconds.
## Chain 1 finished in 20.3 seconds.
## Chain 2 finished in 20.3 seconds.
## Chain 3 finished in 20.9 seconds.
##
## All 4 chains finished successfully.
## Mean chain execution time: 20.4 seconds.
## Total execution time: 21.0 seconds.
```


```
get_seed(fit)
```


```
## [1] 2131503473
```

```
check_model(fit, data = dt)
```

```
## Processing csv files: C:/Users/frodr/AppData/Local/Temp/Rtmp4CoIrr/varying_preferences-202406251207-  
##  
## Checking sampler transitions treedepth.  
## Treedepth satisfactory for all transitions.  
##  
## Checking sampler transitions for divergences.  
## No divergent transitions found.  
##  
## Checking E-BFMI - sampler transitions HMC potential energy.  
## E-BFMI satisfactory.  
##  
## Effective sample size satisfactory.  
##  
## Split R-hat values satisfactory all parameters.  
##  
## Processing complete, no problems detected.
```

Preference (r) parameter: prior (dark grey) vs posterior (light grey) distribut





Posteriors


Get posterior distributions:

```
post <- get_posterior(fit, dt)
head(post)
```

```
## # A tibble: 6 x 11
## # Groups:   Animal, Plant [6]
##   Plant   Animal   .chain .iteration .draw connectance preference plant.abund animal.abund int.pr
##   <chr>   <chr>     <int>    <int>  <int>    <dbl>    <dbl>    <dbl>    <dbl>    <dbl>
## 1 Jmac001 Cervus_ela~     1         1      1      0.531     320.    0.0381    0.237 1 e+
## 2 Jmac002 Cervus_ela~     1         1      1      0.531     320.    0.149     0.237 1.20e-
## 3 Jmac003 Cervus_ela~     1         1      1      0.531     320.    0.0936    0.237 6.52e-
## 4 Jmac004 Cervus_ela~     1         1      1      0.531     320.    0.0214    0.237 1 e+
## 5 Jmac005 Cervus_ela~     1         1      1      0.531     320.    0.0635    0.237 1 e+
## 6 Jmac006 Cervus_ela~     1         1      1      0.531     320.    0.0435    0.237 1 e+
```

Mean edge probability:

```
plot_interaction_prob(post)
```




Generate predicted visits for each pairwise interaction


```
post.counts <- predict_counts(fit, dt)
```

Compare observed and predicted visits by the model:


```
p <- plot_counts_pred(post.counts, sort = FALSE)
o <- plot_counts_obs(mat, sort = FALSE, zero.na = FALSE)
library(patchwork)
p + o
```



```
plot_counts_pred_obs(post.counts, dt)
```

```
plot_counts_pred_obs(post.counts, dt, byplant = TRUE, scales = "free")
```



```
saveRDS(post.counts, here::here(paste0("data/nets_post/", params$net, "_post_counts.rds")))
```