



**3rd ICTG 2016**

**04-07 September 2016, Guimarães, Portugal**



University of Minho  
School of Engineering



GEO-INSTITUTE



# Some effects of fiber addition on the behavior of clean sands under cyclic loadings

**Jorge Hernán Flórez Gálvez<sup>1</sup>, Lucas Festugato<sup>1</sup>**

*1. Universidade Federal do Rio Grande Do Sul, Porto Alegre - Brazil*





## Introduction

- Fiber adding for improve the mechanical behavior of soils;
- Characterization of positive effects under static loading conditions;
- Possibility of using this technique for ground improvement in cyclic loading situations:
  - Wind generators;
  - Seismic events;
  - Tidal effects;
- Limited knowledge about the behavior of these material that conditions.



# 3<sup>rd</sup> ICTG 2016

04-07 September 2016, Guimarães, Portugal



University of Minho  
School of Engineering



GEO-INSTITUTE




## Objective

- Evaluate the effect of fiber addition in a sand, when submited to monotonic and cyclic loading, in two conditions: no fiber and, with 0.5% of fiber in weight. To study the effect of compaction, the sand samples were tested in two different void ratio.




## Materials

### 1. Sand - Source: Osorio, Southern Brazil



Index	Value
$g_s$	26,2 kN/m <sup>3</sup>
$C_u$	2,0
$C_c$	1,1
$D_{10}$	0,11 mm
$D_{50}$	0,20 mm
$e_{min}$	0,6
$e_{max}$	0,9





## Materials

### 2. Fiber: Polypropilene

- Diameter: 0,1 mm
- Length: 50 mm
- Density: 0,91
- Secant modulus: 10 GPa
- Tensile Strength: 200 MPa

- Distilled water







## Experimental program

- Monotonic Triaxial tests (CD)

- Fiber: 0,5 % (constant)
- Water: 10 % (constant)
- Effective confining pressures: 20, 100 and 200 kPa
- Number of tests: 6


- Cyclic Triaxial tests (CU)

- Fiber: 0,5 % (constant)
- Water: 10 % (constant)
- Effective initial confining pressure: 100 kPa
- Number of tests: 12
- Frequency: 0.1 Hz
- Loading path: Sinusoidal
- Deviatoric stresses:  $\pm 20$  to  $\pm 100$  kPa



## Molding conditions

- Sand — Water – Fiber
- Moist tamping (3 layer)
- Sample size:
  - Diameter = 10 cm
  - Height = 20 cm
- Moisture content: 10%










## Results – Monotonic triaxial tests

Void ratio: 0,75

No - fiber

0,5% fiber









## Results – Cyclic triaxial tests

Void ratio	$\sigma_D$ (kPa)	$N_f$	
		0,5% fiber	No-fiber
0.75	$\pm 20$	635	234
0.75	$\pm 40$	14	6
0.75	$\pm 60$	3	1



## Results – Cyclic triaxial tests



- Evolution of pore pressure
- Accumulation of permanent deformation





## Results – Cyclic triaxial tests

- Degradation of moduli of elasticity
- Cyclic stress ratio



$\diamond e = 0,75$     $\diamond e = 0,75$  (0,5% fiber)



## Conclusions

For shear strength parameters, the post-breaking effect in the case with fiber addition, is an increase of strength due to fiber elongation, but this do not have, apparently, any effect in the volumetric strains.

The contribution of fibers is more effective for the higher void ratio, which is the condition with less deformation, delaying the fibers response.

Improvement due to the addition of fibers is not limited to increase in the maximum number of cycles:

Conservation of moduli of elasticity by controlling the accumulation of permanent deformations.

Preservation of test specimens even after liquefaction is reached.



## References

- Consoli, N. C., Casagrande, M. D. T., & Coop, M. R. (2005). Effect of Fiber Reinforcement on the Isotropic Compression Behavior of a Sand. *Journal of Geotechnical and Geoenvironmental Engineering*. [http://doi.org/10.1061/\(ASCE\)1090-0241\(2005\)131:11\(1434\)](http://doi.org/10.1061/(ASCE)1090-0241(2005)131:11(1434))
- Diambra, A. (2010). *Fibre reinforced sands: Experiments and constitutive modelling* (Dissertation (Doctor of Philosophy)). University of Bristol, Bristol.
- Festugato, L. (2011). *Comportamento de hidratação e resposta cisalhante cíclica de resíduo de mineração cimentado reforçado com fibras* (Tese (Doutorado em Engenharia)). Programa de Pós-Graduação em Engenharia Civil, Universidade Federal do Rio Grande do Sul, Porto Alegre.
- Festugato, L., Consoli, N. C., & Fourie, A. (2015). Cyclic shear behaviour of fibre-reinforced mine tailings. *Geosynthetics International*, 22(2), 196–206. <http://doi.org/10.1680/gein.15.00005>
- Ladd, R. S. (1978). Preparing Test Specimens Using Undercompaction. *Geotechnical Testing Journal*, 1(1), 16–23. <http://doi.org/10.1520/GTJ10364J>
- Maher, M. H., & Ho, Y. C. (1993). Behavior of Fiber-Reinforced Cemented Sand Under Static and Cyclic Loads. *Geotechnical Testing Journal*. <http://doi.org/10.1520/GTJ10054J>
- Maher, M. H., & Woods, R. D. (1990). Dynamic Response of Sand Reinforced with Randomly Distributed Fibers. *Journal of Geotechnical Engineering*, 116(7), 1116–1131. [http://doi.org/10.1061/\(ASCE\)0733-9410\(1990\)116:7\(1116\)](http://doi.org/10.1061/(ASCE)0733-9410(1990)116:7(1116))





# 3<sup>rd</sup> ICTG 2016

04-07 September 2016, Guimarães, Portugal



University of Minho  
School of Engineering



## Acknowledgments

