

Auditable Multi-Context Quantum Orchestration on IBM Heron

Protein Comparison, Controlled K-Ablations, and Open-Instance Scale Evidence

Dr. Ilan Kreitmann

Quantum Polycontextural Computing (QPC)

readytogo@quantumpolycontextural.ai · quantumpolycontextural.ai

June 2026

Abstract. Quantum Polycontextural Computing (QPC) is a hardware-agnostic orchestration layer that maps multiple labelled problem contexts onto one gate-model execution on commercial superconducting QPUs. We report three auditable hardware studies on IBM Heron (`ibm_fez` , `ibm_marrakesh`) under the IBM Open plan, each with published job identifiers and JSON artifacts: (i) a 46-qubit mastoparan-I folding pilot compared to a published trapped-ion BF-DCQO energy reference (-8.70); QPC Tier-D repair reaches -9.74 in one pass with eight recoverable job IDs; (ii) a controlled K-ablation on 16 qubits where polycontextural $K=4$ fits held-out Wang–Busemeyer joint statistics better than a matched $K=1$ control (bootstrap one-sided $p < 0.0005$ on total-variation and KL); (iii) thirteen Runtime jobs demonstrating co-resident multi-context layouts from $4 \times 39Q$ through 24 contexts in six cluster submissions. A supplementary transjunction ON vs OFF ablation at $3 \times 26Q$ shows bridge-local inter-context correlators

increase by $|\Delta| > 0.05$ when ring coupling is enabled, after QPC readout mitigation on bridge qubits only; full-width correlators do not separate conditions. We state limitations explicitly: QPC is not a new QPU; protein and cognition results are selective comparisons, not universal advantage claims; open-instance entropy alone does not signature the architecture.

Keywords: multi-context orchestration, IBM Quantum, auditable benchmarks, transjunction coupling, quantum chemistry pilot

1. Introduction

Enterprise and research workloads often require several scenarios at once—risk views, cost and carbon constraints, supply-chain hypotheses, or multiple experimental conditions. Mainstream gate-model stacks typically serialize these as separate circuits or flatten them into a single Boolean narrative per run. **Quantum Polycontextural Computing (QPC)** is an orchestration and logical-architecture layer that keeps multiple formal contexts co-resident on one chip width where the layout permits, coupled by transjunction gates when the workload requires cross-context structure.

This note is deliberately narrow: an 8–12 page hardware evidence summary with honest scope, not a complete theory monograph nor a claim of a new quantum processor. Every headline result below is tied to (a) a defined metric, (b) a stated baseline or control, and (c) verifiable IBM Quantum Runtime job IDs.

What we claim.

- QPC can plan, submit, and archive multi-context workloads on IBM Heron 156Q-class devices with reproducible JSON schemas and public job IDs.
- On three independent lines—published folding energy, controlled K-ablation on empirical joints, and bridge-local coupling metrics—we report comparisons where the metric and baseline are explicit.

What we do not claim.

- QPC does not replace IBM Quantum, Qiskit, or hardware vendors.
- High shot entropy or unique outcome counts from deep circuits are not unique signatures of QPC.
- We do not assert human-cognitive mechanisms, universal quantum advantage, or that no other architecture could match our pilots.

2. Methods

2.1 Context layouts and transjunctions

A **context** is a labelled register block on the device graph with its own morphogrammatic evolution. **Transjunctions** are two-qubit bridges linking aligned qubits across context boundaries. The orchestrator emits a single QASM submission per cluster job when contexts are co-resident.

2.2 Software stack

Runs use Qiskit Runtime SamplerV2 on IBM Open (open-instance). A QPC noise reducer is enabled where documented. Artifacts use versioned JSON schemas (qpc_benchmark_v1, qpc_coupling_ablation_v2, protein and QQ archives).

3. Experiment I — Mastoparan I vs published BF-DCQO

Sequence IDWKKLLDAAKQIL (mastoparan I) on **46 qubits** on ibm_fez. Published reference $E_{\text{ref}} = -8.698$ (IonQ/Kipu BF-DCQO, arXiv:2604.26861). Eight Runtime jobs merged in qpc_protein_ALL_REFINED_v2.json.

Tier	Best energy	Role
A — raw	+13.5	Direct pool
B — geometry filter	+13.5	Constraints
C — light consensus	−0.32	Partial repair
D — repair pool	−9.74	Primary headline
E — refined consensus	+16.48	Alternate path
E_{ref} (published)	−8.70	External ceiling

Table 1. Mastoparan I energy tiers (IBM Fez).

Full report: [QPC_PROTEIN_IDWKK_FEZ.html](#)

4. Experiment II — QPC-QQ K-ablation

16 qubits, K=1 vs K=4, Wang–Busemeyer Clinton–Gore joints. Parameters from order-blind marginals only; joints held out for evaluation. 18 SamplerV2 jobs on `ibm_fez` , 4096 shots.

K	TV _{AB}	TV _{BA}	TV _{mean}
1 (control)	0.2815	0.3216	0.3015
2	0.2672	0.2491	0.2582
4 (polycontextural)	0.2479	0.2541	0.2510

Table 2. Hardware K-ablation (May 2026). Bootstrap $n=2000$: mean $TV(K=1)-TV(K=4)=+0.0505$, 95% CI $[+0.0359, +0.0655]$, one-sided $p=0$.

Report: [QPC_QQ_PILOT_REPORT.html](#)

5. Experiment III — Open-instance scale

Thirteen Runtime jobs (512 shots, May 2026): To1 4×39Q (`d8atngdmd1s73b8p4fg`), To2 12×13Q, To3–To4 clusters on Marrakesh, To5 24 contexts in six jobs. Establishes orchestration reach and audit trails—not, alone, architectural discrimination.

Report: [QPC_OPEN_INSTANCE_BENCHMARKS.html](#)

6. Supplement — Coupling ON vs OFF

Matched 3×26Q = 78Q, 1024 shots. Bridge-local ICC with readout mitigation:

		Δ full-	Δ bridge
--	--	---------	----------

Backend	Coupled job	width ICC	ICC (mit.)
ibm_fez	d8fh39ralsvc7391oe30	−0.0033	+0.0640
ibm_marrakesh	d8fi333alsvc7391pvag	−0.0048	+0.0690

Report: [QPC_COUPLING_ABLATION.html](#)

7. Discussion and data availability

Job IDs and JSON schemas are the reproducibility contract. Overview: [qpc_highlights_report.html](#). Scripts in site release: `qpc_protein_idwkk_fez.py`, `scripts/run_qpc_coupling_ablation.py`.

References

1. Wang & Busemeyer, *J. Math. Psychol.* 50 (2006) — quantum cognition dataset.
2. IonQ/Kipu BF-DCQO, arXiv:2604.26861 (2026) — mastoparan E_{ref} .
3. QPC public reports, [quantumpolycontextural.ai](#) (2026).
4. IBM Quantum Heron, [quantum.ibm.com](#).

To submit on arXiv: compile `arxiv/qpc_hardware_note.tex` → PDF, or print this page (File → Print → Save as PDF). See `docs/QPC_ARXIV_SUBMISSION_CHECKLIST.md`.

