



---

# Brain Imaging Data Structure Specification

---

v1.4.1

2020-10-13

Contents

The Brain Imaging Data Structure 6

Introduction 6

    Motivation . . . . . 6

    Extensions . . . . . 7

    Citing BIDS . . . . . 7

        Original publication . . . . . 7

        Datatype specific publications . . . . . 7

        Research Resource Identifier (RRID) . . . . . 8

Common principles 8

    Definitions . . . . . 8

    Compulsory, optional, and additional data and metadata . . . . . 10

    File name structure . . . . . 10

    Source vs. raw vs. derived data . . . . . 10

        Storage of derived datasets . . . . . 11

        Non-compliant derivatives . . . . . 13

    The Inheritance Principle . . . . . 13

        Good practice recommendations . . . . . 14

    File Formation specification . . . . . 14

        Imaging files . . . . . 14

        Tabular files . . . . . 14

        Key/value files (dictionaries) . . . . . 16

    Participant names and other labels . . . . . 16

    Uniform Resource Indicator . . . . . 17

    Units . . . . . 17

    Directory structure . . . . . 18

        Single session example . . . . . 18

    Unspecified data . . . . . 19

Modality agnostic files 19

    Dataset description . . . . . 19

        dataset\_description.json . . . . . 19

        README . . . . . 23

        CHANGES . . . . . 23

        LICENSE . . . . . 24

    Participants file . . . . . 24

    Phenotypic and assessment data . . . . . 25

    Scans file . . . . . 27

Code . . . . .	27
Magnetic Resonance Imaging . . . . .	27
Common metadata fields . . . . .	27
Scanner Hardware . . . . .	27
Sequence Specifics . . . . .	30
In-Plane Spatial Encoding . . . . .	31
Timing Parameters . . . . .	34
RF & Contrast . . . . .	37
Slice Acceleration . . . . .	37
Anatomical landmarks . . . . .	38
Institution information . . . . .	38
Anatomy imaging data . . . . .	39
Task (including resting state) imaging data . . . . .	41
Required fields . . . . .	42
Other RECOMMENDED metadata . . . . .	43
Diffusion imaging data . . . . .	47
Fieldmap data . . . . .	48
Case 1: Phase difference image and at least one magnitude image . . . . .	48
Case 2: Two phase images and two magnitude images . . . . .	49
Case 3: A real fieldmap image . . . . .	49
Case 4: Multiple phase encoded directions ("pepolar") . . . . .	50
Magnetoencephalography . . . . .	50
MEG recording data . . . . .	51
Recording EEG simultaneously with MEG . . . . .	51
Sidecar JSON (*_meg.json) . . . . .	51
Channels description (*_channels.tsv) . . . . .	58
Coordinate System JSON (*_coordsystem.json) . . . . .	60
Landmark photos (*_photo.jpg) . . . . .	66
Head shape and electrode description (*_headshape.<ext>) . . . . .	67
Empty-room MEG recordings . . . . .	68
Electroencephalography . . . . .	68
EEG recording data . . . . .	68
Sidecar JSON (*_eeg.json) . . . . .	69
Channels description (*_channels.tsv) . . . . .	75
Electrodes description (*_electrodes.tsv) . . . . .	77
Coordinate System JSON (*_coordsystem.json) . . . . .	78
Landmark photos (*_photo.jpg) . . . . .	82

Intracranial Electroencephalography	83
iEEG recording data	83
Terminology: Electrodes vs. Channels	84
Sidecar JSON (*_ieeg.json)	85
Channels description (*_channels.tsv)	91
Electrode description (*_electrodes.tsv)	94
Coordinate System JSON (*_coordsystem.json)	96
Recommended 3D coordinate systems	98
Allowed 2D coordinate systems	98
Multiple coordinate systems	99
Photos of the electrode positions (*_photo.jpg)	99
Electrical stimulation	101
Task events	102
Stimuli databases	104
Stimulus presentation details	105
Physiological and other continuous recordings	107
Recommendations for specific use cases	109
Behavioral experiments (with no neural recordings)	109
Genetic Descriptor	110
Dataset Description	110
Subject naming and Participants file	111
Genetic Information	111
BIDS Derivatives	113
Metadata conventions	113
File naming conventions	113
Common data types and metadata	114
Common file level metadata fields	114
Examples	115
Spatial references	115
SpatialReference key allowed values	116
Examples	116
Preprocessed or cleaned data	117
Imaging data types	118
Preprocessed, coregistered and/or resampled volumes	118
Masks	120

Segmentations . . . . .	121
Discrete Segmentations . . . . .	122
Probabilistic Segmentations . . . . .	123
Discrete surface segmentations . . . . .	124
Common image-derived labels . . . . .	124
Longitudinal and multi-site studies . . . . .	126
Sessions file . . . . .	127
Multi-site or multi-center studies . . . . .	128
Treat each site/center as a separate dataset . . . . .	128
Option 2: Combining sites/centers into one dataset . . . . .	128
BIDS Extension Proposals . . . . .	128
Appendix I: Contributors . . . . .	128
Appendix II: Licenses . . . . .	133
Appendix III: Hierarchical Event Descriptors . . . . .	133
Annotating each event . . . . .	133
Annotating events by categories . . . . .	134
Annotating events by value type . . . . .	135
Best practices . . . . .	136
HED schema and HED versions . . . . .	136
Appendix IV: Entity table . . . . .	137
Magnetic Resonance Imaging . . . . .	137
Encephalography (EEG, iEEG, and MEG) . . . . .	138
Behavioral Data . . . . .	139
Appendix V: Units . . . . .	139
Unit table . . . . .	140
Prefixes . . . . .	141
Multiples . . . . .	141
Submultiples . . . . .	141
Appendix VI: MEG file formats . . . . .	141
CTF . . . . .	142
Neuromag/Elekta/MEGIN . . . . .	142
Cross-talk and fine-calibration files . . . . .	143
Sharing FIFF data after signal-space separation (SSS) . . . . .	144
Split files . . . . .	144

Recording dates in .fif files . . . . .	145
BTi/4D neuroimaging . . . . .	145
KIT/Yokogawa/Ricoh . . . . .	146
KRISS . . . . .	146
ITAB . . . . .	147
Aalto MEG-MRI . . . . .	147
Appendix VII: MEG systems . . . . .	148
Appendix VIII: Coordinate systems . . . . .	148
Introduction . . . . .	149
Coordinate Systems applicable to MEG, EEG, and iEEG . . . . .	149
MEG Specific Coordinate Systems . . . . .	150
EEG Specific Coordinate Systems . . . . .	150
iEEG Specific Coordinate Systems . . . . .	150
Image-based Coordinate Systems . . . . .	151
Standard template identifiers . . . . .	151
Nonstandard coordinate system identifiers . . . . .	153
Non-template coordinate system identifiers . . . . .	153
Appendix IX: Entities . . . . .	154
sub . . . . .	154
ses . . . . .	154
task . . . . .	154
acq . . . . .	155
ce . . . . .	155
rec . . . . .	155
dir . . . . .	155
run . . . . .	156
mod . . . . .	156
echo . . . . .	156
recording . . . . .	156
proc . . . . .	157
space . . . . .	157
split . . . . .	157
Changelog . . . . .	157
v1.4.1 (2020-10-13) . . . . .	158
v1.4.0 (2020-06-11) . . . . .	159
v1.3.0 (2020-04-14) . . . . .	160
v1.2.2 (2020-02-12) . . . . .	160

v1.2.1 (2019-08-14)	161
v1.2.0 (2019-03-04)	162
v1.1.2 (2019-01-10)	163
1.1.1 (2018-06-06)	164
1.1.0 (2018-04-19)	164
1.0.2 (2017-07-18)	165
1.0.1 (2017-03-13)	165
1.0.1-rc1	165
1.0.0 (2016-06-23)	166
1.0.0-rc4	166
1.0.0-rc3	166
1.0.0-rc2	166
1.0.0-rc1	167
1.1.1 (2018-06-06)	167
1.1.0 (2018-04-19)	167
1.0.2 (2017-07-18)	167
1.0.1 (2017-03-13)	167
1.0.1-rc1	168
1.0.0 (2016-06-23)	168
1.0.0-rc4	168
1.0.0-rc3	168
1.0.0-rc2	169
1.0.0-rc1	169

# The Brain Imaging Data Structure

This resource defines the Brain Imaging Data Structure (BIDS) specification, including the core specification as well as many modality-specific extensions.

To get started, check out the introduction. If you'd like more information on how to adapt your own datasets to match the BIDS specification, we recommend exploring the bids-specification starter kit.

For an overview of the BIDS ecosystem, visit the BIDS homepage. The entire specification can also be downloaded as PDF.

## Introduction

### Motivation

Neuroimaging experiments result in complicated data that can be arranged in many different ways. So far there is no consensus how to organize and share data obtained in neuroimaging experiments. Even two researchers working in the same lab can opt to arrange their data in a different way. Lack of consensus (or a standard) leads to

misunderstandings and time wasted on rearranging data or rewriting scripts expecting certain structure. Here we describe a simple and easy-to-adopt way of organising neuroimaging and behavioral data. By using this standard you will benefit in the following ways:

- It will be easy for another researcher to work on your data. To understand the organisation of the files and their format you will only need to refer them to this document. This is especially important if you are running your own lab and anticipate more than one person working on the same data over time. By using BIDS you will save time trying to understand and reuse data acquired by a graduate student or postdoc that has already left the lab.
- There are a growing number of data analysis software packages that can understand data organised according to BIDS (see the up to date list).
- Databases such as OpenNeuro.org accept datasets organised according to BIDS. If you ever plan to share your data publicly (nowadays some journals require this) you can minimize the additional time and energy spent on publication, and speed up the curation process by using BIDS to structure and describe your data right after acquisition.
- Validation tools such as the BIDS Validator can check your dataset integrity and help you easily spot missing values.

BIDS was heavily inspired by the format used internally by the OpenfMRI repository that is now known as OpenNeuro.org, and has been supported by the International Neuroinformatics Coordinating Facility (INCF) and the INCF Neuroimaging Data Sharing (NIDASH) Task Force. While working on BIDS we consulted many neuroscientists to make sure it covers most common experiments, but at the same time is intuitive and easy to adopt. The specification is intentionally based on simple file formats and folder structures to reflect current lab practices and make it accessible to a wide range of scientists coming from different backgrounds.

## Extensions

The BIDS specification can be extended in a backwards compatible way and will evolve over time. This is accomplished through community-driven BIDS Extension Proposals (BEPs). For more information about the BEP process, see [Extending the BIDS specification](#).

## Citing BIDS

When referring to BIDS in context of academic literature, please cite one or more of the publications listed below. We RECOMMEND that you cite the original publication on BIDS and additionally the publication regarding the datatype you were using (for example, EEG, MEG, iEEG, if available).

For example:

The data used in the study were organized using the Brain Imaging Data Structure (Gorgolewski, K., Auer, T., Calhoun, V. et al., 2016) with the extension for EEG data (Pernet, C.R., Appelhoff, S., Gorgolewski, K.J. et al., 2019).

### Original publication

- Gorgolewski, K.J., Auer, T., Calhoun, V.D., Craddock, R.C., Das, S., Duff, E.P., Flandin, G., Ghosh, S.S., Glatard, T., Halchenko, Y.O., Handwerker, D.A., Hanke, M., Keator, D., Li, X., Michael, Z., Maumet, C., Nichols, B.N., Nichols, T.E., Pellman, J., Poline, J.-B., Rokem, A., Schaefer, G., Sochat, V., Triplett, W., Turner, J.A., Varoquaux, G., Poldrack, R.A. (2016). The brain imaging data structure, a format for organizing and describing outputs of neuroimaging experiments. *Scientific Data*, 3 (160044). doi:10.1038/sdata.2016.44

### Datatype specific publications

#### EEG



- Pernet, C. R., Appelhoff, S., Gorgolewski, K.J., Flandin, G., Phillips, C., Delorme, A., Oostenveld, R. (2019). EEG-BIDS, an extension to the brain imaging data structure for electroencephalography. *Scientific data*, 6 (103). doi:10.1038/s41597-019-0104-8

## iEEG

- Holdgraf, C., Appelhoff, S., Bickel, S., Bouchard, K., D'Ambrosio, S., David, O., Devinsky, O., Dichter, B., Flinker, A., Foster, B. L., Gorgolewski, K. J., Groen, I., Groppe, D., Gunduz, A., Hamilton, L., Honey, C. J., Jas, M., Knight, R., Lauchaux, J.-P., Lau, J. C., Lee-Messer, C., Lundstrom, B. N., Miller, K. J., Ojemann, J. G., Oostenveld, R., Petridou, N., Piantoni, G., Pigorini, A., Pouratian, N., Ramsey, N. F., Stolk, A., Swann, N. C., Tadel, F., Voytek, B., Wandell, B. A., Winawer, J., Whitaker, K., Zehl, L., Hermes, D. (2019). iEEG-BIDS, extending the Brain Imaging Data Structure specification to human intracranial electrophysiology. *Scientific data*, 6 (102). doi:10.1038/s41597-019-0105-7

## MEG

- Niso Galan, J.G., Gorgolewski, K.J., Bock, E., Brooks, T.L., Flandin, G., Gramfort, A., Henson, R.N., Jas, M., Litvak, V., Moreau, J., Oostenveld, R., Schoffelen, J.-M., Tadel, F., Wexler, J., Baillet, S. (2018). MEG-BIDS, the brain imaging data structure extended to magnetoencephalography. *Scientific Data*, 5 (180110). doi:10.1038/sdata.2018.110

## Genetics

- Clara Moreau, Martineau Jean-Louis, Ross Blair, Christopher Markiewicz, Jessica Turner, Vince Calhoun, Thomas Nichols, Cyril Pernet (2020). The genetics-BIDS extension: Easing the search for genetic data associated with human brain imaging. *GigaScience* (in press)

## Research Resource Identifier (RRID)

BIDS has also a Research Resource Identifier (RRID), which you can also include in your citations in addition to relevant publications (see above):

- RRID:SCR\_016124

# Common principles

## Definitions

The keywords "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119].

Throughout this specification we use a list of terms and abbreviations. To avoid misunderstanding we clarify them here.

1. Dataset - a set of neuroimaging and behavioral data acquired for a purpose of a particular study. A dataset consists of data acquired from one or more subjects, possibly from multiple sessions.
2. Subject - a person or animal participating in the study. Used interchangeably with term Participant.

3. Session - a logical grouping of neuroimaging and behavioral data consistent across subjects. Session can (but doesn't have to) be synonymous to a visit in a longitudinal study. In general, subjects will stay in the scanner during one session. However, for example, if a subject has to leave the scanner room and then be re-positioned on the scanner bed, the set of MRI acquisitions will still be considered as a session and match sessions acquired in other subjects. Similarly, in situations where different data types are obtained over several visits (for example fMRI on one day followed by DWI the day after) those can be grouped in one session. Defining multiple sessions is appropriate when several identical or similar data acquisitions are planned and performed on all -or most- subjects, often in the case of some intervention between sessions (for example, training).
4. Data acquisition - a continuous uninterrupted block of time during which a brain scanning instrument was acquiring data according to particular scanning sequence/protocol.
5. Data type - a functional group of different types of data. BIDS defines eight data types: `func` (task based and resting state functional MRI), `dwi` (diffusion weighted imaging), `fmap` (field inhomogeneity mapping data such as field maps), `anat` (structural imaging such as T1, T2, PD, and so on), `meg` (magnetoencephalography), `eeg` (electroencephalography), `ieeg` (intracranial electroencephalography), `beh` (behavioral). Data files are contained in a directory named for the data type. In raw datasets, the data type directory is nested inside subject and (optionally) session directories.
6. Task - a set of structured activities performed by the participant. Tasks are usually accompanied by stimuli and responses, and can greatly vary in complexity. For the purpose of this specification we consider the so-called "resting state" a task. In the context of brain scanning, a task is always tied to one data acquisition. Therefore, even if during one acquisition the subject performed multiple conceptually different behaviors (with different sets of instructions) they will be considered one (combined) task.
7. Event - something that happens or may be perceived by a test subject as happening at a particular instant during the recording. Events are most commonly associated with on- or offset of stimulus presentations, or with the distinct marker of on- or offset of a subject's response or motor action. Other events may include unplanned incidents (for example, sudden onset of noise and vibrations due to construction work, laboratory device malfunction), changes in task instructions (for example, switching the response hand), or experiment control parameters (for example, changing the stimulus presentation rate over experimental blocks), and noted data feature occurrences (for example, a recording electrode producing noise). In BIDS, each event has an onset time and duration. Note that not all tasks will have recorded events (for example, "resting state").
8. Run - an uninterrupted repetition of data acquisition that has the same acquisition parameters and task (however events can change from run to run due to different subject response or randomized nature of the stimuli). Run is a synonym of a data acquisition.
9. Modality - the category of brain data recorded by a file. For MRI data, different pulse sequences are considered distinct modalities, such as `T1w`, `bold` or `dwi`. For passive recording techniques, such as EEG, MEG or iEEG, the technique is sufficiently uniform to define the modalities `eeg`, `meg` and `ieeg`. When applicable, the modality is indicated in the suffix. The modality may overlap with, but should not be confused with the data type.
10. **<index>** - a nonnegative integer, possibly prefixed with arbitrary number of 0s for consistent indentation, for example, it is 01 in `run-01` following `run-<index>` specification.
11. **<label>** - an alphanumeric value, possibly prefixed with arbitrary number of 0s for consistent indentation, for example, it is `rest` in `task-rest` following `task-<label>` specification.
12. **suffix** - an alphanumeric value, located after the `key-value_` pairs (thus after the final `_`), right before the File extension, for example, it is `eeg` in `sub-05_task-matchingpennies_eeg.vhdr`.
13. File extension - a portion of the the file name after the left-most period (`.`) preceded by any other alphanumeric. For example, `.gitignore` does not have a file extension, but the file extension of `test.nii.gz` is `.nii.gz`. Note that the left-most period is included in the file extension.

14. DEPRECATED - A "deprecated" entity or metadata field SHOULD NOT be used in the generation of new datasets. It remains in the standard in order to preserve the interpretability of existing datasets. Validating software SHOULD warn when deprecated practices are detected and provide a suggestion for updating the dataset to preserve the curator's intent.

## Compulsory, optional, and additional data and metadata

The following standard describes a way of arranging data and writing down metadata for a subset of neuroimaging experiments. Some aspects of the standard are compulsory. For example a particular file name format is required when storing structural scans. Some aspects are regulated but optional. For example a T2 volume does not need to be included, but when it is available it should be saved under a particular file name specified in the standard. This standard aspires to describe a majority of datasets, but acknowledges that there will be cases that do not fit. In such cases one can include additional files and subfolders to the existing folder structure following common sense. For example one may want to include eye tracking data in a vendor specific format that is not covered by this standard. The most sensible place to put it is next to the continuous recording file with the same naming scheme but different extensions. The solutions will change from case to case and publicly available datasets will be reviewed to include common data types in the future releases of the BIDS specification.

## File name structure

A file name consists of a chain of entities, or key-value pairs, a suffix and an extension. Two prominent examples of entities are `subject` and `session`.

For a data file that was collected in a given `session` from a given `subject`, the file name MUST begin with the string `sub-<label>_ses-<label>`. If the `session` level is omitted in the folder structure, the file name MUST begin with the string `sub-<label>`, without `ses-<label>`.

Note that `sub-<label>` corresponds to the `subject` entity because it has the `sub-` "key" and `<label>` "value", where `<label>` would in a real data file correspond to a unique identifier of that subject, such as 01. The same holds for the `session` entity with its `ses-` key and its `<label>` value.

A chain of entities, followed by a suffix, connected by underscores (`_`) produces a human readable file name, such as `sub-01_task-rest_eeg.edf`. It is evident from the file name alone that the file contains resting state data from subject 01. The suffix `eeg` and the extension `.edf` depend on the imaging modality and the data format and indicate further details of the file's contents.

A summary of all entities in BIDS and the order in which they MUST be specified is available in the entity table in the appendix.

## Source vs. raw vs. derived data

BIDS was originally designed to describe and apply consistent naming conventions to raw (unprocessed or minimally processed due to file format conversion) data. During analysis such data will be transformed and partial as well as final results will be saved. Derivatives of the raw data (other than products of DICOM to NIfTI conversion) MUST be kept separate from the raw data. This way one can protect the raw data from accidental changes by file permissions. In addition it is easy to distinguish partial results from the raw data and share the latter. See Storage of derived datasets for more on organizing derivatives.

Similar rules apply to source data, which is defined as data before harmonization, reconstruction, and/or file format conversion (for example, E-Prime event logs or DICOM files). Storing actual source files with the data is preferred over links to external source repositories to maximize long term preservation, which would suffer if an external repository would not be available anymore. This specification currently does not go into the details of recommending a particular naming scheme for including different types of source data (such as the raw event logs or parameter files, before conversion to BIDS). However, in the case that these data are to be included:

1. These data MUST be kept in separate `sourcedata` folder with a similar folder structure as presented below for the BIDS-managed data. For example: `sourcedata/sub-01/ses-pre/func/sub-01_ses-pre_task-rest_bold.dicom.tgz` or `sourcedata/sub-01/ses-pre/func/MyEvent.sce`.

2. A README file SHOULD be found at the root of the `sourcedata` folder or the `derivatives` folder, or both. This file should describe the nature of the raw data or the derived data. We RECOMMEND including the PDF print-out with the actual sequence parameters generated by the scanner in the `sourcedata` folder.

Alternatively one can organize their data in the following way

```
1 my_dataset/  
2   sourcedata/  
3     ...  
4   rawdata/  
5     dataset_description.json  
6     participants.tsv  
7     sub-01/  
8     sub-02/  
9     ...  
10  derivatives/  
11    pipeline_1/  
12    pipeline_2/  
13    ...
```

In this example, where `sourcedata` and `derivatives` are not nested inside `rawdata`, only the **`rawdata`** subfolder needs to be a BIDS-compliant dataset. The subfolders of `derivatives` MAY be BIDS-compliant derivatives datasets (see Non-compliant derivatives for further discussion). This specification does not prescribe anything about the contents of `sourcedata` folders in the above example - nor does it prescribe the `sourcedata`, `derivatives`, or `rawdata` folder names. The above example is just a convention that can be useful for organizing raw, source, and derived data while maintaining BIDS compliancy of the raw data folder. When using this convention it is RECOMMENDED to set the `SourceDatasets` field in `dataset_description.json` of each subfolder of `derivatives` to:

```
1 {  
2   "SourceDatasets": [ {"URL": "file:///../../rawdata/"} ]  
3 }
```

### Storage of derived datasets

Derivatives can be stored/distributed in two ways:

1. Under a `derivatives/` subfolder in the root of the source BIDS dataset folder to make a clear distinction between raw data and results of data processing. A data processing pipeline will typically have a dedicated directory under which it stores all of its outputs. Different components of a pipeline can, however, also be stored under different subfolders. There are few restrictions on the directory names; it is RECOMMENDED to use the format `<pipeline>-<variant>` in cases where it is anticipated that the same pipeline will output more than one variant (for example, `AFNI-blurring` and `AFNI-noblurring`). For the sake of consistency, the subfolder name SHOULD be the `GeneratedBy.Name` field in `data_description.json`, optionally followed by a hyphen and a suffix (see Derived dataset and pipeline description).

Example of derivatives with one directory per pipeline:

```
1 <dataset>/derivatives/fmripres-v1.4.1/sub-0001
```

```
2 <dataset>/derivatives/spm/sub-0001
3 <dataset>/derivatives/vbm/sub-0001
```

Example of a pipeline with split derivative directories:

```
1 <dataset>/derivatives/spm-preproc/sub-0001
2 <dataset>/derivatives/spm-stats/sub-0001
```

Example of a pipeline with nested derivative directories:

```
1 <dataset>/derivatives/spm-preproc/sub-0001
2 <dataset>/derivatives/spm-preproc/derivatives/spm-stats/sub-0001
```

2. As a standalone dataset independent of the source (raw or derived) BIDS dataset. This way of specifying derivatives is particularly useful when the source dataset is provided with read-only access, for publishing derivatives as independent bodies of work, or for describing derivatives that were created from more than one source dataset. The `sourcedata/` subdirectory MAY be used to include the source dataset(s) that were used to generate the derivatives. Likewise, any code used to generate the derivatives from the source data MAY be included in the `code/` subdirectory.

Example of a derivative dataset including the raw dataset as source:

```
1 my_processed_data/
2   code/
3     processing_pipeline-1.0.0.img
4     hpc_submitter.sh
5     ...
6   sourcedata/
7     dataset_description.json
8     participants.tsv
9     sub-01/
10    sub-02/
11    ...
12  dataset_description.json
13  sub-01/
14  sub-02/
15  ...
```

Throughout this specification, if a section applies particularly to derivatives, then Case 1 will be assumed for clarity in templates and examples, but removing `/derivatives` `/<pipeline>` from the template name will provide the equivalent for Case 2. In both cases, every derivatives dataset is considered a BIDS dataset and must include a `dataset_description.json` file at the root level (see Dataset description. Consequently, files should be organized to comply with BIDS to the full extent possible (that is, unless explicitly contradicted for derivatives). Any subject-specific derivatives should be housed within each subject's directory; if session-specific derivatives are generated, they should be deposited under a session subdirectory within the corresponding subject directory; and so on.

## Non-compliant derivatives

Nothing in this specification should be interpreted to disallow the storage/distribution of non-compliant derivatives of BIDS datasets. In particular, if a BIDS dataset contains a `derivatives/` sub-directory, the contents of that directory may be a heterogeneous mix of BIDS Derivatives datasets and non-compliant derivatives.

## The Inheritance Principle

Any metadata file (such as `.json`, `.bvec` or `.tsv`) may be defined at any directory level, but no more than one applicable file may be defined at a given level (Example 1). The values from the top level are inherited by all lower levels unless they are overridden by a file at the lower level. For example, `sub-*_task-rest_bold.json` may be specified at the participant level, setting TR to a specific value. If one of the runs has a different TR than the one specified in that file, another `sub-*_task-rest_bold.json` file can be placed within that specific series directory specifying the TR for that specific run. There is no notion of "unsetting" a key/value pair. Once a key/value pair is set in a given level in the dataset, lower down in the hierarchy that key/value pair will always have some assigned value. Files for a particular participant can exist only at participant level directory, that is, `/dataset/sub-*/[ses-*/sub-*_T1w.json`. Similarly, any file that is not specific to a participant is to be declared only at top level of dataset for example: `task-sist_bold.json` must be placed under `/dataset/task-sist_bold.json`

Example 1: Two JSON files that are erroneously at the same level

```
1 sub-01/
2   ses-test/
3     sub-01_ses-test_task-overtverbgeneration_bold.json
4     sub-01_ses-test_task-overtverbgeneration_run-2_bold.json
5   anat/
6     sub-01_ses-test_T1w.nii.gz
7   func/
8     sub-01_ses-test_task-overtverbgeneration_run-1_bold.nii.gz
9     sub-01_ses-test_task-overtverbgeneration_run-2_bold.nii.gz
```

In the above example, two JSON files are listed under `sub-01/ses-test/`, which are each applicable to `sub-01_ses-test_task-overtverbgeneration_run-2_bold.nii.gz`, violating the constraint that no more than one file may be defined at a given level of the directory structure. Instead `sub-01_ses-test_task-overtverbgeneration_run-2_bold.json` should have been under `sub-01/ses-test/func/`.

Example 2: Multiple runs and recs with same acquisition (acq) parameters

```
1 sub-01/
2   anat/
3   func/
4     sub-01_task-xyz_acq-test1_run-1_bold.nii.gz
5     sub-01_task-xyz_acq-test1_run-2_bold.nii.gz
6     sub-01_task-xyz_acq-test1_rec-recon1_bold.nii.gz
7     sub-01_task-xyz_acq-test1_rec-recon2_bold.nii.gz
8     sub-01_task-xyz_acq-test1_bold.json
```

For the above example, all NIfTI files are acquired with same scanning parameters (`acq-test1`). Hence a JSON file describing the acq parameters will apply to different runs and rec files. Also if the JSON file (`task-xyz_acq-test1_bold.json`) is defined at dataset top level directory, it will be applicable to all task runs with `test1` acquisition parameter.

Example 3: Multiple JSON files at different levels for same task and acquisition parameters

```
1 task-xyz_acq-test1_bold.json
2 sub-01/
3   anat/
4   func/
5     sub-01_task-xyz_acq-test1_run-1_bold.nii.gz
6     sub-01_task-xyz_acq-test1_rec-recon1_bold.nii.gz
7     sub-01_task-xyz_acq-test1_rec-recon2_bold.nii.gz
8     sub-01_task-xyz_acq-test1_bold.json
```

In the above example, the fields from the `task-xyz_acq-test1_bold.json` file at the top directory will apply to all bold runs. However, if there is a key with different value in the `sub-01/func/sub-01_task-xyz_acq-test1_bold.json` file defined at a deeper level, that value will be applicable for that particular run/task NIfTI file/s. In other words, the `.json` file at the deeper level overrides values that are potentially also defined in the `.json` at a more shallow level. If the `.json` file at the more shallow level contains key-value-pairs that are not present in the `.json` file at the deeper level, these key-value-pairs are inherited by the `.json` file at the deeper level (but NOT vice versa!).

### Good practice recommendations

Try to avoid excessive amount of overrides. Do not specify a field value in the upper levels if lower levels have more or less even distribution of multiple possible values. For example, if a field `X` has one value for all `ses-01/` and another for all `ses-02/` it better not to be defined at all in the `.json` at the upper level.

## File Formation specification

### Imaging files

All imaging data **MUST** be stored using the NIfTI file format. We **RECOMMEND** using compressed NIfTI files (`.nii.gz`), either version 1.0 or 2.0. Imaging data **SHOULD** be converted to the NIfTI format using a tool that provides as much of the NIfTI header information (such as orientation and slice timing information) as possible. Since the NIfTI standard offers limited support for the various image acquisition parameters available in DICOM files, we **RECOMMEND** that users provide additional meta information extracted from DICOM files in a sidecar JSON file (with the same filename as the `.nii[.gz]` file, but with a `.json` extension). Extraction of BIDS compatible metadata can be performed using `dcm2niix` and `dicm2nii` DICOM to NIfTI converters. The BIDS-validator will check for conflicts between the JSON file and the data recorded in the NIfTI header.

### Tabular files

Tabular data **MUST** be saved as tab delimited values (`.tsv`) files, that is, CSV files where commas are replaced by tabs. Tabs **MUST** be true tab characters and **MUST NOT** be a series of space characters. Each TSV file **MUST** start with a header line listing the names of all columns (with the exception of physiological and other continuous recordings). Names **MUST** be separated with tabs. It is **RECOMMENDED** that the column names in the header of the TSV file are written in `snake_case` with the first letter in lower case (for example, `variable_name`, not `Variable_name`). String values containing tabs **MUST** be escaped using double quotes. Missing and non-applicable

values MUST be coded as n/a. Numerical values MUST employ the dot (.) as decimal separator and MAY be specified in scientific notation, using e or E to separate the significand from the exponent. TSV files MUST be in UTF-8 encoding.

Example:

```
1 onset duration response_time correct stop_trial go_trial
2 200 200 0 n/a n/a n/a
```

Tabular files MAY be optionally accompanied by a simple data dictionary in the form of a JSON object within a JSON file. The JSON files containing the data dictionaries MUST have the same name as their corresponding tabular files but with .json extensions. If a data dictionary is provided, it MAY contain one or more fields describing the columns found in the TSV file (in addition to any other metadata one wishes to include that describe the file as a whole). Note that if a field name included in the data dictionary matches a column name in the TSV file, then that field MUST contain a description of the corresponding column, using an object containing the following fields:

Key name	Requirement level	Data type	Description
LongName	OPTIONAL	string	Long (unabbreviated) name of the column.
Description	RECOMMENDED	string	Description of the column.
Levels	RECOMMENDED	object of strings	For categorical variables: An object of possible values (keys) and their descriptions (values).
Units	RECOMMENDED	string	Measurement units. SI units in CMIXF formatting are RECOMMENDED (see Units).
TermURL	RECOMMENDED	string	URL pointing to a formal definition of this type of data in an ontology available on the web.

Please note that while both Units and Levels are RECOMMENDED, typically only one of these two fields would be specified for describing a single TSV file column.

Example:

```
1 {
2   "test": {
3     "LongName": "Education level",
4     "Description": "Education level, self-rated by participant",
5     "Levels": {
6       "1": "Finished primary school",
7       "2": "Finished secondary school",
8       "3": "Student at university",
9       "4": "Has degree from university"
```



```
10   }
11 },
12 "bmi": {
13   "LongName": "Body mass index",
14   "Units": "kg/m^2",
15   "TermURL": "http://purl.bioontology.org/ontology/SNOMEDCT/60621009"
16 }
17 }
```

### Key/value files (dictionaries)

JavaScript Object Notation (JSON) files MUST be used for storing key/value pairs. JSON files MUST be in UTF-8 encoding. Extensive documentation of the format can be found here: <http://json.org/>. Several editors have built-in support for JSON syntax highlighting that aids manual creation of such files. An online editor for JSON with built-in validation is available at: <http://jsoneditoronline.org>. It is RECOMMENDED that keys in a JSON file are written in CamelCase with the first letter in upper case (for example, `SamplingFrequency`, not `samplingFrequency`). Note however, when a JSON file is used as an accompanying sidecar file for a TSV file, the keys linking a TSV column with their description in the JSON file need to follow the exact formatting as in the TSV file.

Example of a hypothetical `*_bold.json` file, accompanying a `*_bold.nii` file:

```
1 {
2   "RepetitionTime": 3,
3   "Instruction": "Lie still and keep your eyes open"
4 }
```

Example of a hypothetical `*_events.json` file, accompanying an `*_events.tsv` file. Note that the JSON file contains a key describing an arbitrary column `stim_presentation_side` in the TSV file it accompanies. See task events section for more information.

```
1 {
2   "stim_presentation_side": {
3     "Levels": {
4       "1": "stimulus presented on LEFT side",
5       "2": "stimulus presented on RIGHT side"
6     }
7   }
8 }
```

### Participant names and other labels

BIDS allows for custom user-defined `<label>`s and `<index>`es for example, for naming of participants, sessions, acquisition schemes. Note that they MUST consist only of allowed characters as described in Definitions above. In `<index>`es we RECOMMEND using zero padding (for example, 01 instead of 1 if you have more than nine subjects) to make alphabetical sorting more intuitive. Note that zero padding SHOULD NOT be used to merely maintain uniqueness of `<index>`es.

Please note that a given label or index is distinct from the "prefix" it refers to. For example `sub-01` refers to the `sub` entity (a subject) with the label `01`. The `sub-` prefix is not part of the subject label, but must be included in file names (similarly to other key names).

## Uniform Resource Indicator

A Uniform Resource Indicator (URI) is a string referring to a resource and SHOULD have the form `<scheme>:[//<authority>]<path>[?<query>][#<fragment>]`, as specified in RFC 3986. This applies to URLs and other common URIs, including Digital Object Identifiers (DOIs), which may be fully specified as `doi:<path>`, for example, `doi:10.5281/zenodo.3686061`. A given resource may have multiple URIs. When selecting URIs to add to dataset metadata, it is important to consider specificity and persistence.

Several fields are designated for DOIs, for example, `DatasetDOI` in `dataset_description.json`. DOI values SHOULD be fully specified URIs such as `doi:10.18112/openneuro.ds000001.v1.0.0`. Bare DOIs such as `10.18112/openneuro.ds000001.v1.0.0` are DEPRECATED.

## Units

All units SHOULD be specified as per International System of Units (abbreviated as SI, from the French *Système international (d'unités)*) and can be SI units or SI derived units. In case there are valid reasons to deviate from SI units or SI derived units, the units MUST be specified in the sidecar JSON file. In case data is expressed in SI units or SI derived units, the units MAY be specified in the sidecar JSON file. In case non-standard prefixes are added to SI or non-SI units, these non-standard prefixed units MUST be specified in the JSON file. See Appendix V for a list of standard units and prefixes. Note also that for the formatting of SI units, the CMIXF-12 convention for encoding units is RECOMMENDED. CMIXF provides a consistent system for all units and prefix symbols with only basic characters, avoiding symbols that can cause text encoding problems; for example the CMIXF formatting for "micro volts" is `uV`, "degrees Celsius" is `oC` and "Ohm" is `Ohm`. See Appendix V for more information.

For additional rules, see below:

- Elapsed time SHOULD be expressed in seconds. Please note that some DICOM parameters have been traditionally expressed in milliseconds. Those need to be converted to seconds.
- Frequency SHOULD be expressed in Hertz.
- Arbitrary units SHOULD be indicated with the string `"arbitrary"`.

Describing dates and timestamps:

- Date time information MUST be expressed in the following format `YYYY-MM-DDThh:mm:ss[.000000][Z]` (year, month, day, hour (24h), minute, second, optional fractional seconds, and optional UTC time indicator). This is almost equivalent to the RFC3339 "date-time" format, with the exception that UTC indicator `Z` is optional and non-zero UTC offsets are not indicated. If `Z` is not indicated, time zone is always assumed to be the local time of the dataset viewer. No specific precision is required for fractional seconds, but the precision SHOULD be consistent across the dataset. For example `2009-06-15T13:45:30`.
- Time stamp information MUST be expressed in the following format: `hh:mm:ss[.000000]` For example `13:45:30`.
- Note that, depending on local ethics board policy, date time information may not need to be fully detailed. For example, it is permissible to set the time to `00:00:00` if reporting the exact recording time is undesirable. However, for privacy protection reasons, it is RECOMMENDED to shift dates, as described below, without completely removing time information, as time information can be useful for research purposes.

- Dates can be shifted by a random number of days for privacy protection reasons. To distinguish real dates from shifted dates, always use year 1925 or earlier when including shifted years. For longitudinal studies dates MUST be shifted by the same number of days within each subject to maintain the interval information. For example: 1867-06-15T13:45:30
- WARNING: The Neuromag/Elekta/MEGIN file format for MEG (.fif) does not support recording dates earlier than 1902 roughly. Some analysis software packages (for example, MNE-Python) handle their data as .fif internally and will break if recording dates are specified prior to 1902, even if the original data format is not .fif. See MEG-file-formats for more information.
- Age SHOULD be given as the number of years since birth at the time of scanning (or first scan in case of multi session datasets). Using higher accuracy (weeks) should in general be avoided due to privacy protection, unless when appropriate given the study goals, for example, when scanning babies.

## Directory structure

### Single session example

This is an example of the folder and file structure. Because there is only one session, the session level is not required by the format. For details on individual files see descriptions in the next section:

```
1 sub-control01/
2   anat/
3     sub-control01_T1w.nii.gz
4     sub-control01_T1w.json
5     sub-control01_T2w.nii.gz
6     sub-control01_T2w.json
7   func/
8     sub-control01_task-nback_bold.nii.gz
9     sub-control01_task-nback_bold.json
10    sub-control01_task-nback_events.tsv
11    sub-control01_task-nback_physio.tsv.gz
12    sub-control01_task-nback_physio.json
13    sub-control01_task-nback_sbref.nii.gz
14   dwi/
15     sub-control01_dwi.nii.gz
16     sub-control01_dwi.bval
17     sub-control01_dwi.bvec
18   fmap/
19     sub-control01_phasediff.nii.gz
20     sub-control01_phasediff.json
21     sub-control01_magnitude1.nii.gz
22     sub-control01_scans.tsv
23 code/
24   deface.py
25 derivatives/
```

```

26 README
27 participants.tsv
28 dataset_description.json
29 CHANGES

```

## Unspecified data

Additional files and folders containing raw data MAY be added as needed for special cases. All non-standard file entities SHOULD conform to BIDS-style naming conventions, including alphabetic entities and suffixes and alphanumeric labels/indices. Non-standard suffixes SHOULD reflect the nature of the data, and existing entities SHOULD be used when appropriate. For example, an ASSET calibration scan might be named `sub-01_acq-ASSET_calibration.nii.gz`.

Non-standard files and directories should be named with care. Future BIDS efforts may standardize new entities and suffixes, changing the meaning of file names and setting requirements on their contents or metadata. Validation and parsing tools MAY treat the presence of non-standard files and directories as an error, so consult the details of these tools for mechanisms to suppress warnings or provide interpretations of your file names.

## Modality agnostic files

### Dataset description

Templates:

- `dataset_description.json`
- `README`
- `CHANGES`
- `LICENSE`

#### `dataset_description.json`

The file `dataset_description.json` is a JSON file describing the dataset. Every dataset MUST include this file with the following fields:

Key name	Requirement level	Data type	Description
Name	REQUIRED	string	Name of the dataset.
BIDSVersion	REQUIRED	string	The version of the BIDS standard that was used.
HEDVersion	RECOMMENDED	string	If HED tags are used: The version of the HED schema used to validate HED tags for study.

Key name	Requirement level	Data type	Description
DatasetType	RECOMMENDED	string	The interpretation of the dataset. MUST be one of "raw" or "derivative". For backwards compatibility, the default value is "raw".
License	RECOMMENDED	string	The license for the dataset. The use of license name abbreviations is RECOMMENDED for specifying a license (see Appendix II). The corresponding full license text MAY be specified in an additional LICENSE file.
Authors	OPTIONAL	array of strings	List of individuals who contributed to the creation/curation of the dataset.
Acknowledgements	OPTIONAL	string	Text acknowledging contributions of individuals or institutions beyond those listed in Authors or Funding.
HowToAcknowledge	OPTIONAL	string	Text containing instructions on how researchers using this dataset should acknowledge the original authors. This field can also be used to define a publication that should be cited in publications that use the dataset.
Funding	OPTIONAL	array of strings	List of sources of funding (grant numbers).
EthicsApprovals	OPTIONAL	array of strings	List of ethics committee approvals of the research protocols and/or protocol identifiers.
ReferencesAndLinks	OPTIONAL	array of strings	List of references to publications that contain information on the dataset. A reference may be textual or a URI.
DatasetDOI	OPTIONAL	string	The Digital Object Identifier of the dataset (not the corresponding paper). DOIs SHOULD be expressed as a valid URI; bare DOIs such as 10.0.2.3/dfjj.10 are DEPRECATED.

Example:

```

1 {
2   "Name": "The mother of all experiments",
3   "BIDSVersion": "1.4.0",
4   "DatasetType": "raw",
5   "License": "CC0",
6   "Authors": [
7     "Paul Broca",
8     "Carl Wernicke"
9   ],
10  "Acknowledgements": "Special thanks to Korbinian Brodmann for help in formatting this dataset in BIDS. We thank Alan Lloyd Hodgkin and Andrew
    Huxley for helpful comments and discussions about the experiment and manuscript; Hermann Ludwig Helmholtz for administrative support; and
    Claudius Galenus for providing data for the medial-to-lateral index analysis.",
11  "HowToAcknowledge": "Please cite this paper: https://www.ncbi.nlm.nih.gov/pubmed/001012092119281",
12  "Funding": [
13    "National Institute of Neuroscience Grant F378236MFH1",
14    "National Institute of Neuroscience Grant 5RMZ0023106"
15  ],
16  "EthicsApprovals": [
17    "Army Human Research Protections Office (Protocol ARL-20098-10051, ARL 12-040, and ARL 12-041)"
18  ],
19  "ReferencesAndLinks": [
20    "https://www.ncbi.nlm.nih.gov/pubmed/001012092119281",
21    "Alzheimer A., & Kraepelin, E. (2015). Neural correlates of presenile dementia in humans. Journal of Neuroscientific Data, 2, 234001. doi
      :1920.8/jndata.2015.7"
22  ],
23  "DatasetDOI": "doi:10.0.2.3/dfjj.10",
24  "HEDVersion": "7.1.1"
25 }

```

Derived dataset and pipeline description As for any BIDS dataset, a `dataset_description.json` file MUST be found at the top level of the a derived dataset: `<dataset>/derivatives/<pipeline_name>/dataset_description.json`

In addition to the keys for raw BIDS datasets, derived BIDS datasets include the following REQUIRED and RECOMMENDED `dataset_description.json` keys:

Key name	Requirement level	Data type	Description
GeneratedBy	REQUIRED	array of objects	Used to specify provenance of the derived dataset. See table below for contents of each object.

Key name	Requirement level	Data type	Description
SourceDatasets	RECOMMENDED	array of objects	Used to specify the locations and relevant attributes of all source datasets. Valid keys in each object include <b>URL</b> , <b>DOI</b> (see <b>URI</b> ), and <b>Version</b> with string values.

Each object in the **GeneratedBy** list includes the following **REQUIRED**, **RECOMMENDED** and **OPTIONAL** keys:

Key name	Requirement level	Data type	Description
Name	REQUIRED	string	Name of the pipeline or process that generated the outputs. Use " <b>Manual</b> " to indicate the derivatives were generated by hand, or adjusted manually after an initial run of an automated pipeline.
Version	RECOMMENDED	string	Version of the pipeline.
Description	OPTIONAL	string	Plain-text description of the pipeline or process that generated the outputs. RECOMMENDED if <b>Name</b> is " <b>Manual</b> ".
CodeURL	OPTIONAL	string	URL where the code used to generate the derivatives may be found.
Container	OPTIONAL	object	Used to specify the location and relevant attributes of software container image used to produce the derivative. Valid keys in this object include <b>Type</b> , <b>Tag</b> and <b>URI</b> with string values.

Example:

```

1 {
2   "Name": "fMRIPREP Outputs",
3   "BIDSVersion": "1.4.0",
4   "DatasetType": "derivative",
5   "GeneratedBy": [
6     {

```

```
7     "Name": "fmripred",
8     "Version": "1.4.1",
9     "Container": {
10         "Type": "docker",
11         "Tag": "poldracklab/fmripred:1.4.1"
12     }
13 },
14 {
15     "Name": "Manual",
16     "Description": "Re-added RepetitionTime metadata to bold.json files"
17 }
18 ],
19 "SourceDatasets": [
20     {
21         "DOI": "doi:10.18112/openneuro.ds000114.v1.0.1",
22         "URL": "https://openneuro.org/datasets/ds000114/versions/1.0.1",
23         "Version": "1.0.1"
24     }
25 ]
26 }
```

If a derived dataset is stored as a subfolder of the raw dataset, then the **Name** field of the first **GeneratedBy** object **MUST** be a substring of the derived dataset folder name. That is, in a directory `<dataset>/derivatives/<pipeline>[-<variant>]/`, the first **GeneratedBy** object should have a **Name** of `<pipeline>`.

## README

In addition a free form text file (README) describing the dataset in more details **SHOULD** be provided. The README file **MUST** be either in ASCII or UTF-8 encoding.

## CHANGES

Version history of the dataset (describing changes, updates and corrections) **MAY** be provided in the form of a **CHANGES** text file. This file **MUST** follow the CPAN Changelog convention. The **CHANGES** file **MUST** be either in ASCII or UTF-8 encoding.

Example:

```
1 1.0.1 2015-08-27
2   - Fixed slice timing information.
3
4 1.0.0 2015-08-17
5   - Initial release.
```



## LICENSE

A LICENSE file MAY be provided in addition to the short specification of the used license in the `dataset_description.json` "License" field. The "License" field and LICENSE file MUST correspond. The LICENSE file MUST be either in ASCII or UTF-8 encoding.

## Participants file

Template:

```
1 participants.tsv
2 participants.json
```

The purpose of this RECOMMENDED file is to describe properties of participants such as age, sex, handedness. In case of single-session studies, this file has one compulsory column `participant_id` that consists of `sub-⟨label⟩`, followed by a list of optional columns describing participants. Each participant MUST be described by one and only one row.

Commonly used optional columns in `participant.tsv` files are `age`, `sex`, and `handedness`. We RECOMMEND to make use of these columns, and in case that you do use them, we RECOMMEND to use the following values for them:

- `age`: numeric value in years (float or integer value)
- `sex`: string value indicating phenotypical sex, one of "male", "female", "other"
  - for "male", use one of these values: `male`, `m`, `M`, `MALE`, `Male`
  - for "female", use one of these values: `female`, `f`, `F`, `FEMALE`, `Female`
  - for "other", use one of these values: `other`, `o`, `O`, `OTHER`, `Other`
- `handedness`: string value indicating one of "left", "right", "ambidextrous"
  - for "left", use one of these values: `left`, `l`, `L`, `LEFT`, `Left`
  - for "right", use one of these values: `right`, `r`, `R`, `RIGHT`, `Right`
  - for "ambidextrous", use one of these values: `ambidextrous`, `a`, `A`, `AMBIDEXTROUS`, `Ambidextrous`

Throughout BIDS you can indicate missing values with `n/a` (for "not available").

`participants.tsv` example:

```
1 participant_id age sex handedness group
2 sub-01 34 M right read
3 sub-02 12 F right write
4 sub-03 33 F n/a read
```

It is RECOMMENDED to accompany each `participants.tsv` file with a sidecar `participants.json` file to describe the TSV column names and properties of their values (see also the section on tabular files). Such sidecar files are needed to interpret the data, especially so when optional columns are defined beyond `age`, `sex`, and `handedness`,

such as `group` in this example, or when a different age unit is needed (for example, gestational weeks). If no `units` is provided for age, it will be assumed to be in years relative to date of birth.

`participants.json` example:

```
1 {
2   "age": {
3     "Description": "age of the participant",
4     "Units": "years"
5   },
6   "sex": {
7     "Description": "sex of the participant as reported by the participant",
8     "Levels": {
9       "M": "male",
10      "F": "female"
11    }
12  },
13  "handedness": {
14    "Description": "handedness of the participant as reported by the participant",
15    "Levels": {
16      "left": "left",
17      "right": "right"
18    }
19  },
20  "group": {
21    "Description": "experimental group the participant belonged to",
22    "Levels": {
23      "read": "participants who read an inspirational text before the experiment",
24      "write": "participants who wrote an inspirational text before the experiment"
25    }
26  }
27 }
```

## Phenotypic and assessment data

Template:

```
1 phenotype/<measurement_tool_name>.tsv
2 phenotype/<measurement_tool_name>.json
```

Optional: Yes

If the dataset includes multiple sets of participant level measurements (for example responses from multiple questionnaires) they can be split into individual files separate from `participants.tsv`.

Each of the measurement files **MUST** be kept in a `/phenotype` directory placed at the root of the BIDS dataset and **MUST** end with the `.tsv` extension. File names **SHOULD** be chosen to reflect the contents of the file. For example, the "Adult ADHD Clinical Diagnostic Scale" could be saved in a file called `/phenotype/acds_adult.tsv`.

The files can include an arbitrary set of columns, but one of them **MUST** be `participant_id` and the entries of that column **MUST** correspond to the subjects in the BIDS dataset and `participants.tsv` file.

As with all other tabular data, the additional phenotypic information files **MAY** be accompanied by a JSON file describing the columns in detail (see Tabular files). In addition to the column description, a section describing the measurement tool (as a whole) **MAY** be added under the name `MeasurementToolMetadata`. This section consists of two keys:

- **Description**: A free text description of the measurement tool
- **TermURL**: A URL to an entity in an ontology corresponding to this tool.

As an example, consider the contents of a file called `phenotype/acds_adult.json`:

```
1 {
2   "MeasurementToolMetadata": {
3     "Description": "Adult ADHD Clinical Diagnostic Scale V1.2",
4     "TermURL": "http://www.cognitiveatlas.org/task/id/trm_5586ff878155d"
5   },
6   "adhd_b": {
7     "Description": "B. CHILDHOOD ONSET OF ADHD (PRIOR TO AGE 7)",
8     "Levels": {
9       "1": "YES",
10      "2": "NO"
11    }
12  },
13  "adhd_c_dx": {
14    "Description": "As child met A, B, C, D, E and F diagnostic criteria",
15    "Levels": {
16      "1": "YES",
17      "2": "NO"
18    }
19  }
20 }
```

Please note that in this example `MeasurementToolMetadata` includes information about the questionnaire and `adhd_b` and `adhd_c_dx` correspond to individual columns.

In addition to the keys available to describe columns in all tabular files (`LongName`, `Description`, `Levels`, `Units`, and `TermURL`) the `participants.json` file as well as phenotypic files can also include column descriptions with a `Derivative` field that, when set to true, indicates that values in the corresponding column is a transformation of values from other columns (for example a summary score based on a subset of items in a questionnaire).

## Scans file

Template:

```
1 sub-<label>/[ses-<label>/]
2   sub-<label>[_ses-<label>]_scans.tsv
3   sub-<label>[_ses-<label>]_scans.json
```

Optional: Yes

The purpose of this file is to describe timing and other properties of each imaging acquisition sequence (each run file) within one session. Each neural recording file should be described by at most one row. Relative paths to files should be used under a compulsory `filename` header. If acquisition time is included it should be under `acq_time` header. Acquisition time refers to when the first data point in each run was acquired. Datetime should be expressed as described in Units. For anonymization purposes all dates within one subject should be shifted by a randomly chosen (but consistent across all recordings) number of days. This way relative timing would be preserved, but chances of identifying a person based on the date and time of their scan would be decreased. Dates that are shifted for anonymization purposes SHOULD be set to the year 1925 or earlier to clearly distinguish them from unmodified data. Shifting dates is RECOMMENDED, but not required.

Additional fields can include external behavioral measures relevant to the scan. For example vigilance questionnaire score administered after a resting state scan. All such included additional fields SHOULD be documented in an accompanying `_scans.json` file that describes these fields in detail (see Tabular files).

Example `_scans.tsv`:

```
1 filename      acq_time
2 func/sub-control01_task-nback_bold.nii.gz  1877-06-15T13:45:30
3 func/sub-control01_task-motor_bold.nii.gz  1877-06-15T13:55:33
```

## Code

Template: `code/*`

Source code of scripts that were used to prepare the dataset MAY be stored here. Examples include anonymization or defacing of the data, or the conversion from the format of the source data to the BIDS format (see source vs. raw vs. derived data). Extra care should be taken to avoid including original IDs or any identifiable information with the source code. There are no limitations or recommendations on the language and/or code organization of these scripts at the moment.

## Magnetic Resonance Imaging

### Common metadata fields

MR Data described in the following sections share the following RECOMMENDED metadata fields (stored in sidecar JSON files). MRI acquisition parameters are divided into several categories based on "A checklist for fMRI acquisition methods reporting in the literature" by Ben Inglis:

Scanner Hardware

Key name	Requirement level	Data type	Description
Manufacturer	RECOMMENDED	string	Manufacturer of the equipment that produced the composite instances. Corresponds to DICOM Tag 0008, 0070 <b>Manufacturer</b>
ManufacturersModelName	RECOMMENDED	string	Manufacturer's model name of the equipment that produced the composite instances. Corresponds to DICOM Tag 0008, 1090 <b>Manufacturers Model Name</b>
DeviceSerialNumber	RECOMMENDED	string	The serial number of the equipment that produced the composite instances. Corresponds to DICOM Tag 0018, 1000 <b>DeviceSerialNumber</b> . A pseudonym can also be used to prevent the equipment from being identifiable, so long as each pseudonym is unique within the dataset
StationName	RECOMMENDED	string	Institution defined name of the machine that produced the composite instances. Corresponds to DICOM Tag 0008, 1010 <b>Station Name</b>
SoftwareVersions	RECOMMENDED	string	Manufacturer's designation of software version of the equipment that produced the composite instances. Corresponds to DICOM Tag 0018, 1020 <b>Software Versions</b>
HardcopyDeviceSoftwareVersion	DEPRECATED	string	Manufacturer's designation of the software of the device that created this Hardcopy Image (the printer). Corresponds to DICOM Tag 0018, 101A <b>Hardcopy Device Software Version</b>
MagneticFieldStrength	RECOMMENDED	number	Nominal field strength of MR magnet in Tesla. Corresponds to DICOM Tag 0018,0087 <b>Magnetic Field Strength</b>

Key name	Requirement level	Data type	Description
ReceiveCoilName	RECOMMENDED	string	Information describing the receiver coil. Corresponds to DICOM Tag 0018, 1250 <b>Receive Coil Name</b> , although not all vendors populate that DICOM Tag, in which case this field can be derived from an appropriate private DICOM field
ReceiveCoilActiveElements	RECOMMENDED	string	Information describing the active/selected elements of the receiver coil. This doesn't correspond to a tag in the DICOM ontology. The vendor-defined terminology for active coil elements can go in this field. See an example below the table.
GradientSetType	RECOMMENDED	string	It should be possible to infer the gradient coil from the scanner model. If not, for example because of a custom upgrade or use of a gradient insert set, then the specifications of the actual gradient coil should be reported independently
MRTransmitCoilSequence	RECOMMENDED	string	This is a relevant field if a non-standard transmit coil is used. Corresponds to DICOM Tag 0018, 9049 <b>MR Transmit Coil Sequence</b>
MatrixCoilMode	RECOMMENDED	string	(If used) A method for reducing the number of independent channels by combining in analog the signals from multiple coil elements. There are typically different default modes when using un-accelerated or accelerated (for example, GRAPPA, SENSE) imaging

Key name	Requirement level	Data type	Description
CoilCombinationMethod	RECOMMENDED	string	Almost all fMRI studies using phased-array coils use root-sum-of-squares (rSOS) combination, but other methods exist. The image reconstruction is changed by the coil combination method (as for the matrix coil mode above), so anything non-standard should be reported

#### Example for ReceiveCoilActiveElements:

For Siemens, coil channels are typically not activated/selected individually, but rather in pre-defined selectable "groups" of individual channels, and the list of the "groups" of elements that are active/selected in any given scan populates the `Coil String` entry in Siemens' private DICOM fields (for example, `HEA;HEP` for the Siemens standard 32 ch coil when both the anterior and posterior groups are activated). This is a flexible field that can be used as most appropriate for a given vendor and coil to define the "active" coil elements. Since individual scans can sometimes not have the intended coil elements selected, it is preferable for this field to be populated directly from the DICOM for each individual scan, so that it can be used as a mechanism for checking that a given scan was collected with the intended coil elements selected

#### Sequence Specifics

Key name	Requirement level	Data type	Description
PulseSequenceType	RECOMMENDED	string	A general description of the pulse sequence used for the scan (for example, MPRAGE, Gradient Echo EPI, Spin Echo EPI, Multiband gradient echo EPI).
ScanningSequence	RECOMMENDED	string or array of strings	Description of the type of data acquired. Corresponds to DICOM Tag 0018, 0020 <b>Scanning Sequence</b> .
SequenceVariant	RECOMMENDED	string or array of strings	Variant of the ScanningSequence. Corresponds to DICOM Tag 0018, 0021 <b>Sequence Variant</b> .
ScanOptions	RECOMMENDED	string or array of strings	Parameters of ScanningSequence. Corresponds to DICOM Tag 0018, 0022 <b>Scan Options</b> .

Key name	Requirement level	Data type	Description
SequenceName	RECOMMENDED	string	Manufacturer's designation of the sequence name. Corresponds to DICOM Tag 0018, 0024 <b>Sequence Name.</b>
PulseSequenceDetails	RECOMMENDED	string	Information beyond pulse sequence type that identifies the specific pulse sequence used (for example, "Standard Siemens Sequence distributed with the VB17 software," "Siemens WIP ### version #.##," or "Sequence written by X using a version compiled on MM/DD/YYYY").
NonlinearGradientCorrection	RECOMMENDED	boolean	Boolean stating if the image saved has been corrected for gradient nonlinearities by the scanner sequence.

## In-Plane Spatial Encoding

Key name	Requirement level	Data type	Description
NumberShots	RECOMMENDED	number	The number of RF excitations need to reconstruct a slice or volume. Please mind that this is not the same as Echo Train Length which denotes the number of lines of k-space collected after an excitation.
ParallelReductionFactorInPlane	RECOMMENDED	number	The parallel imaging (e.g, GRAPPA) factor. Use the denominator of the fraction of k-space encoded for each slice. For example, 2 means half of k-space is encoded. Corresponds to DICOM Tag 0018, 9069 <b>Parallel Reduction Factor In-plane.</b>



Key name	Requirement level	Data type	Description
ParallelAcquisitionTechnique	RECOMMENDED	string	The type of parallel imaging used (for example GRAPPA, SENSE). Corresponds to DICOM Tag 0018, 9078
PartialFourier	RECOMMENDED	number	<b>Parallel Acquisition Technique.</b> The fraction of partial Fourier information collected. Corresponds to DICOM Tag 0018, 9081
PartialFourierDirection	RECOMMENDED	string	<b>Partial Fourier.</b> The direction where only partial Fourier information was collected. Corresponds to DICOM Tag 0018, 9036
PhaseEncodingDirection	RECOMMENDED	string	<b>Partial Fourier Direction.</b> Possible values: i, j, k, i-, j-, k-. The letters i, j, k correspond to the first, second and third axis of the data in the NIFTI file. The polarity of the phase encoding is assumed to go from zero index to maximum index unless - sign is present (then the order is reversed - starting from the highest index instead of zero). <b>PhaseEncodingDirection</b> is defined as the direction along which phase is was modulated which may result in visible distortions. Note that this is not the same as the DICOM term <b>InPlanePhaseEncodingDirection</b> which can have ROW or COL values. This parameter is REQUIRED if corresponding fieldmap data is present or when using multiple runs with different phase encoding directions (which can be later used for field inhomogeneity correction).

Key name	Requirement level	Data type	Description
EffectiveEchoSpacing	RECOMMENDED	number	The "effective" sampling interval, specified in seconds, between lines in the phase-encoding direction, defined based on the size of the reconstructed image in the phase direction. It is frequently, but incorrectly, referred to as "dwell time" (see <code>DwellTime</code> parameter below for actual dwell time). It is required for unwarping distortions using field maps. Note that beyond just in-plane acceleration, a variety of other manipulations to the phase encoding need to be accounted for properly, including partial fourier, phase oversampling, phase resolution, phase field-of-view and interpolation. <sup>2</sup> This parameter is REQUIRED if corresponding fieldmap data is present.
TotalReadoutTime	RECOMMENDED	number	This is actually the "effective" total readout time, defined as the readout duration, specified in seconds, that would have generated data with the given level of distortion. It is NOT the actual, physical duration of the readout train. If <code>EffectiveEchoSpacing</code> has been properly computed, it is just $\text{EffectiveEchoSpacing} * (\text{ReconMatrixPE} - 1)$ . <sup>3</sup> This parameter is REQUIRED if corresponding "field/distortion" maps acquired with opposing phase encoding directions are present (see 8.9.4).

---

2Conveniently, for Siemens data, this value is easily obtained as  $1 / (\text{BWPPPE} * \text{ReconMatrixPE})$ , where BWPPPE is the "BandwidthPerPixelPhaseEncode" in DICOM tag (0019,1028) and ReconMatrixPE is the size of the actual reconstructed data in the phase direction (which is NOT reflected in a single DICOM tag for all possible aforementioned scan manipulations). See [here](#) and [here](#)

3We use the time between the center of the first "effective" echo and the center of the last "effective" echo, sometimes called the "FSL definition".

#### Timing Parameters

Key name	Requirement level	Data type	Description
EchoTime	RECOMMENDED, but REQUIRED if corresponding fieldmap data is present or the data comes from a multi echo sequence	number	The echo time (TE) for the acquisition, specified in seconds. Corresponds to DICOM Tag 0018, 0081 <b>Echo Time</b> (please note that the DICOM term is in milliseconds not seconds).
InversionTime	RECOMMENDED	number	The inversion time (TI) for the acquisition, specified in seconds. Inversion time is the time after the middle of inverting RF pulse to middle of excitation pulse to detect the amount of longitudinal magnetization. Corresponds to DICOM Tag 0018, 0082 <b>Inversion Time</b> (please note that the DICOM term is in milliseconds not seconds).

Key name	Requirement level	Data type	Description
SliceTiming	RECOMMENDED, but REQUIRED for sparse sequences that do not have the DelayTime field set	array of numbers	<p>The time at which each slice was acquired within each volume (frame) of the acquisition. Slice timing is not slice order -- rather, it is a list of times containing the time (in seconds) of each slice acquisition in relation to the beginning of volume acquisition. The list goes through the slices along the slice axis in the slice encoding dimension (see below). Note that to ensure the proper interpretation of the SliceTiming field, it is important to check if the OPTIONAL SliceEncodingDirection exists. In particular, if SliceEncodingDirection is negative, the entries in SliceTiming are defined in reverse order with respect to the slice axis, such that the final entry in the SliceTiming list is the time of acquisition of slice 0. Without this parameter slice time correction will not be possible.</p>

Key name	Requirement level	Data type	Description
SliceEncodingDirection	RECOMMENDED	string	Possible values: i, j, k, i-, j-, k- (the axis of the NIfTI data along which slices were acquired, and the direction in which <code>SliceTiming</code> is defined with respect to). i, j, k identifiers correspond to the first, second and third axis of the data in the NIfTI file. A - sign indicates that the contents of <code>SliceTiming</code> are defined in reverse order - that is, the first entry corresponds to the slice with the largest index, and the final entry corresponds to slice index zero. When present, the axis defined by <code>SliceEncodingDirection</code> needs to be consistent with the 'slice_dim' field in the NIfTI header. When absent, the entries in <code>SliceTiming</code> must be in the order of increasing slice index as defined by the NIfTI header.

Key name	Requirement level	Data type	Description
DwellTime	RECOMMENDED	number	Actual dwell time (in seconds) of the receiver per point in the readout direction, including any oversampling. For Siemens, this corresponds to DICOM field (0019,1018) (in ns). This value is necessary for the optional readout distortion correction of anatomicals in the HCP Pipelines. It also usefully provides a handle on the readout bandwidth, which isn't captured in the other metadata tags. Not to be confused with <b>EffectiveEchoSpacing</b> , and the frequent mislabeling of echo spacing (which is spacing in the phase encoding direction) as "dwell time" (which is spacing in the readout direction).

## RF &amp; Contrast

Key name	Requirement level	Data type	Description
FlipAngle	RECOMMENDED	number	Flip angle for the acquisition, specified in degrees. Corresponds to: DICOM Tag 0018, 1314 <b>Flip Angle</b> .
NegativeContrast	OPTIONAL	boolean	<b>true</b> or <b>false</b> value specifying whether increasing voxel intensity (within sample voxels) denotes a decreased value with respect to the contrast suffix. This is commonly the case when Cerebral Blood Volume is estimated via usage of a contrast agent in conjunction with a T2* weighted acquisition protocol.

## Slice Acceleration

Key name	Requirement level	Data type	Description
MultibandAccelerationFactor	RECOMMENDED	number	The multiband factor, for multiband acquisitions.

#### Anatomical landmarks

Useful for multimodal co-registration with MEG, (S)EEG, TMS, and so on.

Key name	Requirement level	Data type	Description
AnatomicalLandmarkCoordinates	RECOMMENDED	object of arrays	Key:value pairs of any number of additional anatomical landmarks and their coordinates in voxel units (where first voxel has index 0,0,0) relative to the associated anatomical MRI (for example, {"AC": [127,119,149], "PC": [128,93,141], "IH": [131,114,206]}, or {"NAS": [127,213,139], "LPA": [52,113,96], "RPA": [202,113,91]}). Each array MUST contain three numeric values corresponding to x, y, and z axis of the coordinate system in that exact order.

#### Institution information

Key name	Requirement level	Data type	Description
InstitutionName	RECOMMENDED	string	The name of the institution in charge of the equipment that produced the composite instances. Corresponds to DICOM Tag 0008, 0080 InstitutionName.

Key name	Requirement level	Data type	Description
InstitutionAddress	RECOMMENDED	string	The address of the institution in charge of the equipment that produced the composite instances. Corresponds to DICOM Tag 0008, 0081 <code>InstitutionAddress</code> .
InstitutionalDepartmentName	RECOMMENDED	string	The department in the institution in charge of the equipment that produced the composite instances. Corresponds to DICOM Tag 0008, 1040 <code>Institutional Department Name</code> .

When adding additional metadata please use the CamelCase version of DICOM ontology terms whenever possible. See also recommendations on JSON files.

## Anatomy imaging data

Template:

```

1 sub-<label>/[ses-<label>/]
2   anat/
3     sub-<label>[_ses-<label>][_acq-<label>][_ce-<label>][_rec-<label>][_run-<index>]_<modality_label>.nii[.gz]
4     sub-<label>[_ses-<label>][_acq-<label>][_ce-<label>][_rec-<label>][_run-<index>][_mod-<label>]_defacemask.nii[.gz]
```

Anatomical (structural) data acquired for that participant. Currently supported modalities include:

Name	modality_label	Description
T1 weighted	T1w	
T2 weighted	T2w	
T1 Rho map	T1rho	Quantitative T1rho brain imaging <a href="https://www.ncbi.nlm.nih.gov/pubmed/24474423">https://www.ncbi.nlm.nih.gov/pubmed/24474423</a> <a href="https://www.ncbi.nlm.nih.gov/pmc/articles/PMC4346383/">https://www.ncbi.nlm.nih.gov/pmc/articles/PMC4346383/</a>
T1 map	T1map	quantitative T1 map
T2 map	T2map	quantitative T2 map
T2*	T2star	High resolution T2* image
FLAIR	FLAIR	
FLASH	FLASH	
Proton density	PD	



Name	modality_label	Description
Proton density map	PDmap	
Combined PD/T2	PDT2	
Inplane T1	inplaneT1	T1-weighted anatomical image matched to functional acquisition
Inplane T2	inplaneT2	T2-weighted anatomical image matched to functional acquisition
Angiography	angio	

If the structural images included in the dataset were defaced (to protect identity of participants) one MAY provide the binary mask that was used to remove facial features in the form of `_defacemask` files. In such cases, the OPTIONAL `mod-<label>` key/value pair corresponds to modality suffix, such as T1w or inplaneT1, referenced by the defacemask image. For example, `sub-01_mod-T1w_defacemask.nii.gz`.

If several scans of the same modality are acquired they MUST be indexed with the `run-<index>` key-value pair: `_run-1`, `_run-2`, `_run-3`, and so on (only nonnegative integers are allowed as run labels). When there is only one scan of a given type the run key MAY be omitted. Please note that diffusion imaging data is stored elsewhere (see below).

The OPTIONAL `acq-<label>` key/value pair corresponds to a custom label the user MAY use to distinguish a different set of parameters used for acquiring the same modality. For example this should be used when a study includes two T1w images - one full brain low resolution and one restricted field of view but high resolution. In such case two files could have the following names: `sub-01_acq-highres_T1w.nii.gz` and `sub-01_acq-lowres_T1w.nii.gz`, however the user is free to choose any other label than `highres` and `lowres` as long as they are consistent across subjects and sessions. In case different sequences are used to record the same modality (for example, RARE and FLASH for T1w) this field can also be used to make that distinction. At what level of detail to make the distinction (for example, just between RARE and FLASH, or between RARE, FLASH, and FLASHsubsampling) remains at the discretion of the researcher.

Similarly the OPTIONAL `ce-<label>` key/value can be used to distinguish sequences using different contrast enhanced images. The label is the name of the contrast agent. The key `ContrastBolusIngredient` MAY be also be added in the JSON file, with the same label.

Some meta information about the acquisition MAY be provided in an additional JSON file. See Common metadata fields for a list of terms and their definitions. There are also some OPTIONAL JSON fields specific to anatomical scans:

Key name	Requirement level	Data type	Description
ContrastBolusIngredient	OPTIONAL	string	Active ingredient of agent. Values MUST be one of: IODINE, GADOLINIUM, CARBON DIOXIDE, BARIUM, XENON Corresponds to DICOM Tag 0018,1048.

Similarly, the OPTIONAL `rec-<label>` key/value can be used to distinguish different reconstruction algorithms (for example ones using motion correction).

## Task (including resting state) imaging data

Currently supported image contrasts include:

Name	contrast_label	Description
BOLD	bold	Blood-Oxygen-Level Dependent contrast (specialized T2* weighting)
CBV	cbv	Cerebral Blood Volume contrast (specialized T2* weighting or difference between T1 weighted images)
Phase	phase	Phase information associated with magnitude information stored in BOLD contrast

Template:

```

1 sub-<label>/[ses-<label>/]
2   func/
3     sub-<label>[_ses-<label>]_task-<label>[_acq-<label>][_ce-<label>][_dir-<label>][_rec-<label>][_run-<index>][_echo-<index>]_<contrast_label
4     >.nii.gz]
5     sub-<label>[_ses-<label>]_task-<label>[_acq-<label>][_ce-<label>][_dir-<label>][_rec-<label>][_run-<index>][_echo-<index>]_sbref.nii.gz]

```

Functional imaging consists of techniques that support rapid temporal repetition. This includes but is not limited to task based fMRI as well as resting state fMRI, which is treated like any other task. For task based fMRI a corresponding task events file (see below) MUST be provided (please note that this file is not necessary for resting state scans). For multiband acquisitions, one MAY also save the single-band reference image as type **sbref** (for example, `sub-control01_task-nback_sbref.nii.gz`).

Each task has a unique label that MUST only consist of letters and/or numbers (other characters, including spaces and underscores, are not allowed) with the **task-<label>** key/value pair. Those labels MUST be consistent across subjects and sessions.

If more than one run of the same task has been acquired the **run-<index>** key/value pair MUST be used: **\_run-1**, **\_run-2**, **\_run-3**, and so on. If only one run was acquired the **run-<index>** can be omitted. In the context of functional imaging a run is defined as the same task, but in some cases it can mean different set of stimuli (for example randomized order) and participant responses.

The OPTIONAL **acq-<label>** key/value pair corresponds to a custom label one may use to distinguish different set of parameters used for acquiring the same task. For example this should be used when a study includes two resting state images - one single band and one multiband. In such case two files could have the following names: `sub-01_task-rest_acq-singleband_bold.nii.gz` and `sub-01_task-rest_acq-multiband_bold.nii.gz`, however the user is MAY choose any other label than **singleband** and **multiband** as long as they are consistent across subjects and sessions and consist only of the legal label characters.

Similarly the OPTIONAL **ce-<label>** key/value can be used to distinguish sequences using different contrast enhanced images. The label is the name of the contrast agent. The key ContrastBolusIngredient MAY be also be added in the JSON file, with the same label.

Similarly the OPTIONAL **rec-<label>** key/value can be used to distinguish different reconstruction algorithms (for example ones using motion correction).

Similarly the OPTIONAL `dir-<label>` and `rec-<label>` key/values can be used to distinguish different phase-encoding directions and reconstruction algorithms (for example ones using motion correction). See `fmap` Case 4 for more information on `dir` field specification.

Multi-echo data MUST be split into one file per echo using the `echo-<index>` key-value pair. For example:

```
1 sub-01/
2   func/
3     sub-01_task-cuedSGT_run-1_echo-1_bold.nii.gz
4     sub-01_task-cuedSGT_run-1_echo-1_bold.json
5     sub-01_task-cuedSGT_run-1_echo-2_bold.nii.gz
6     sub-01_task-cuedSGT_run-1_echo-2_bold.json
7     sub-01_task-cuedSGT_run-1_echo-3_bold.nii.gz
8     sub-01_task-cuedSGT_run-1_echo-3_bold.json
```

Please note that the `<index>` denotes the number/index (in the form of a nonnegative integer) of the echo not the echo time value which needs to be stored in the field `EchoTime` of the separate JSON file.

Some meta information about the acquisition MUST be provided in an additional JSON file.

#### Required fields

Key name	Requirement level	Data type	Description
<code>RepetitionTime</code>	REQUIRED	number	The time in seconds between the beginning of an acquisition of one volume and the beginning of acquisition of the volume following it (TR). Please note that this definition includes time between scans (when no data has been acquired) in case of sparse acquisition schemes. This value needs to be consistent with the <code>pixdim[4]</code> field (after accounting for units stored in <code>xyzt_units</code> field) in the NIfTI header. This field is mutually exclusive with <code>VolumeTiming</code> and is derived from DICOM Tag 0018, 0080 and converted to seconds.

Key name	Requirement level	Data type	Description
VolumeTiming	REQUIRED	array of numbers	The time at which each volume was acquired during the acquisition. It is described using a list of times referring to the onset of each volume in the BOLD series. The list must have the same length as the BOLD series, and the values must be non-negative and monotonically increasing. This field is mutually exclusive with RepetitionTime and DelayTime. If defined, this requires acquisition time (TA) be defined via either SliceTiming or AcquisitionDuration be defined.
TaskName	REQUIRED	string	Name of the task. No two tasks should have the same name. The task label included in the file name is derived from this TaskName field by removing all non-alphanumeric ([a-zA-Z0-9]) characters. For example TaskName faces n-back will correspond to task label facesnback. A RECOMMENDED convention is to name resting state task using labels beginning with rest.

For the fields described above and in the following section, the term "Volume" refers to a reconstruction of the object being imaged (for example, brain or part of a brain). In case of multiple channels in a coil, the term "Volume" refers to a combined image rather than an image from each coil.

#### Other RECOMMENDED metadata

##### Timing Parameters

Key name	Requirement level	Data type	Description
NumberOfVolumesDiscardedByScanner	RECOMMENDED	integer	Number of volumes ("dummy scans") discarded by the scanner (as opposed to those discarded by the user post hoc) before saving the imaging file. For example, a sequence that automatically discards the first 4 volumes before saving would have this field as 4. A sequence that doesn't discard dummy scans would have this set to 0. Please note that the onsets recorded in the _event.tsv file should always refer to the beginning of the acquisition of the first volume in the corresponding imaging file - independent of the value of <code>NumberOfVolumesDiscardedByScanner</code> field.
NumberOfVolumesDiscardedByUser	RECOMMENDED	integer	Number of volumes ("dummy scans") discarded by the user before including the file in the dataset. If possible, including all of the volumes is strongly recommended. Please note that the onsets recorded in the _event.tsv file should always refer to the beginning of the acquisition of the first volume in the corresponding imaging file - independent of the value of <code>NumberOfVolumesDiscardedByUser</code> field.

Key name	Requirement level	Data type	Description
DelayTime	RECOMMENDED	number	User specified time (in seconds) to delay the acquisition of data for the following volume. If the field is not present it is assumed to be set to zero. Corresponds to Siemens CSA header field <code>1DelayTimeInTR</code> . This field is REQUIRED for sparse sequences using the <code>RepetitionTime</code> field that do not have the <code>SliceTiming</code> field set to allowed for accurate calculation of "acquisition time". This field is mutually exclusive with <code>VolumeTiming</code> .
AcquisitionDuration	RECOMMENDED, but REQUIRED for sequences that are described with the <code>VolumeTiming</code> field and that do not have the <code>SliceTiming</code> field set to allow for accurate calculation of "acquisition time"	number	Duration (in seconds) of volume acquisition. Corresponds to DICOM Tag 0018,9073 <code>AcquisitionDuration</code> . This field is mutually exclusive with <code>RepetitionTime</code> .
DelayAfterTrigger	RECOMMENDED	number	Duration (in seconds) from trigger delivery to scan onset. This delay is commonly caused by adjustments and loading times. This specification is entirely independent of <code>NumberOfVolumesDiscardedByScanner</code> or <code>NumberOfVolumesDiscardedByUser</code> , as the delay precedes the acquisition.

The following table recapitulates the different ways that specific fields have to be populated for functional sequences. Note that all these options can be used for non sparse sequences but that only options B, D and E are valid for sparse sequences.

	<code>RepetitionTime</code>	<code>SliceTiming</code>	<code>AcquisitionDuration</code>	<code>DelayTime</code>	<code>VolumeTiming</code>
option A	[ X ]		[ ]		[ ]
option B	[ ]	[ X ]		[ ]	[ X ]
option C	[ ]		[ X ]	[ ]	[ X ]
option D	[ X ]	[ X ]	[ ]		[ ]

	RepetitionTime	SliceTiming	AcquisitionDuration	DelayTime	VolumeTiming
option E	[ X ]		[ ]	[ X ]	[ ]

#### Legend

- [ X ] --> has to be filled
- --> has to be left empty
- empty cell --> can be specified but not required

#### fMRI task information

Key name	Requirement level	Data type	Description
Instructions	RECOMMENDED	string	Text of the instructions given to participants before the scan. This is especially important in context of resting state fMRI and distinguishing between eyes open and eyes closed paradigms.
TaskDescription	RECOMMENDED	string	Longer description of the task.
CogAtlasID	RECOMMENDED	string	URI of the corresponding Cognitive Atlas Task term.
CogPOID	RECOMMENDED	string	URI of the corresponding CogPO term.

See Common metadata fields for a list of additional terms and their definitions.

Example:

```
1 sub-control01/
2   func/
3     sub-control01_task-nback_bold.json
```

```
1 {
2   "TaskName": "N Back",
3   "RepetitionTime": 0.8,
4   "EchoTime": 0.03,
5   "FlipAngle": 78,
6   "SliceTiming": [0.0, 0.2, 0.4, 0.6, 0.0, 0.2, 0.4, 0.6, 0.0, 0.2, 0.4, 0.6, 0.0, 0.2, 0.4, 0.6],
7   "MultibandAccelerationFactor": 4,
```

```

8  "ParallelReductionFactorInPlane": 2,
9  "PhaseEncodingDirection": "j",
10 "InstitutionName": "Stanford University",
11 "InstitutionAddress": "450 Serra Mall, Stanford, CA 94305-2004, USA",
12 "DeviceSerialNumber": "11035"
13 }

```

If this information is the same for all participants, sessions and runs it can be provided in `task-<label>_bold.json` (in the root directory of the dataset). However, if the information differs between subjects/runs it can be specified in the `sub-<label>/func/sub-<label>_task-<label>[_acq-<label>][_run-<index>]_bold.json` file. If both files are specified fields from the file corresponding to a particular participant, task and run takes precedence.

## Diffusion imaging data

Template:

```

1 sub-<label>/[ses-<label>/]
2   dwi/
3     sub-<label>[_ses-<label>][_acq-<label>][_dir-<label>][_run-<index>]_dwi.nii.gz]
4     sub-<label>[_ses-<label>][_acq-<label>][_dir-<label>][_run-<index>]_dwi.bval
5     sub-<label>[_ses-<label>][_acq-<label>][_dir-<label>][_run-<index>]_dwi.bvec
6     sub-<label>[_ses-<label>][_acq-<label>][_dir-<label>][_run-<index>]_dwi.json
7     sub-<label>[_ses-<label>][_acq-<label>][_dir-<label>][_run-<index>]_sbref.nii.gz]
8     sub-<label>[_ses-<label>][_acq-<label>][_dir-<label>][_run-<index>]_sbref.json

```

Diffusion-weighted imaging data acquired for that participant. The OPTIONAL `acq-<label>` key/value pair corresponds to a custom label the user may use to distinguish different set of parameters. For example this should be used when a study includes two diffusion images - one single band and one multiband. In such case two files could have the following names: `sub-01_acq-singleband_dwi.nii.gz` and `sub-01_acq-multiband_dwi.nii.gz`, however the user is free to choose any other label than `singleband` and `multiband` as long as they are consistent across subjects and sessions. For multiband acquisitions, one can also save the single-band reference image as type `sbref` (for example, `dwi/sub-control01_sbref.nii.gz`) The `bvec` and `bval` files are in the FSL format: The `bvec` files contain 3 rows with `n` space-delimited floating-point numbers (corresponding to the `n` volumes in the relevant NIfTI file). The first row contains the `x` elements, the second row contains the `y` elements and third row contains the `z` elements of a unit vector in the direction of the applied diffusion gradient, where the `i`-th elements in each row correspond together to the `i`-th volume with `[0,0,0]` for non-diffusion-weighted volumes. Inherent to the FSL format for `bvec` specification is the fact that the coordinate system of the `bvecs` is with respect to the participant, defined by the axes of the corresponding `dwi.nii` file, and not the magnet's coordinate system. Thus, any rotations applied to `dwi.nii` also need to be applied to the corresponding `bvec` file.

`bvec` example:

```

1 0 0 0.021828 -0.015425 -0.70918 -0.2465
2 0 0 0.80242 0.22098 -0.00063106 0.1043
3 0 0 -0.59636 0.97516 -0.70503 -0.96351

```

The `bval` file contains the `b`-values (in `s/mm2`) corresponding to the volumes in the relevant NIfTI file), with 0 designating non-diffusion-weighted volumes, space-delimited.



bval example:

```
1 0 0 2000 2000 1000 1000
```

.bval and .bvec files can be saved on any level of the directory structure and thus define those values for all sessions and/or subjects in one place (see Inheritance principle).

See Common metadata fields for a list of additional terms that can be included in the corresponding JSON file.

JSON example:

```
1 {
2   "PhaseEncodingDirection": "j-",
3   "TotalReadoutTime": 0.095
4 }
```

## Fieldmap data

Data acquired to correct for B0 inhomogeneities can come in different forms. The current version of this standard considers four different scenarios. Please note that in all cases fieldmap data can be linked to a specific scan(s) it was acquired for by filling the IntendedFor field in the corresponding JSON file. For example:

```
1 {
2   "IntendedFor": "func/sub-01_task-motor_bold.nii.gz"
3 }
```

The IntendedFor field may contain one or more filenames with paths relative to the subject subfolder. The path needs to use forward slashes instead of backward slashes. Here's an example with multiple target scans:

```
1 {
2   "IntendedFor": ["ses-pre/func/sub-01_ses-pre_task-motor_run-1_bold.nii.gz",
3                  "ses-post/func/sub-01_ses-post_task-motor_run-1_bold.nii.gz"]
4 }
```

The IntendedFor field is OPTIONAL and in case the fieldmaps do not correspond to any particular scans it does not have to be filled.

Multiple fieldmaps can be stored. In such case the `run-<index>` key/value pair should be used. The OPTIONAL `acq-<label>` key/value pair corresponds to a custom label the user may use to distinguish different set of parameters.

Case 1: Phase difference image and at least one magnitude image

Template:

```
1 sub-<label>/[ses-<label>/]
2   fmap/
3     sub-<label>[_ses-<label>][_acq-<label>][_run-<index>]_phasediff.nii.gz]
4     sub-<label>[_ses-<label>][_acq-<label>][_run-<index>]_phasediff.json
5     sub-<label>[_ses-<label>][_acq-<label>][_run-<index>]_magnitude1.nii.gz]
```

## OPTIONAL

```
1 sub-<label>/[ses-<label>/]
2   fmap/
3     sub-<label>[_ses-<label>][_acq-<label>][_run-<index>]_magnitude2.nii.gz]
```

This is a common output for build in fieldmap sequence on Siemens scanners. In this particular case the sidecar JSON file has to define the Echo Times of the two phase images used to create the difference image. `EchoTime1` corresponds to the shorter echo time and `EchoTime2` to the longer echo time. Similarly `_magnitude1` image corresponds to the shorter echo time and the OPTIONAL `_magnitude2` image to the longer echo time. For example:

```
1 {
2   "EchoTime1": 0.00600,
3   "EchoTime2": 0.00746,
4   "IntendedFor": "func/sub-01_task-motor_bold.nii.gz"
5 }
```

Case 2: Two phase images and two magnitude images

Template:

```
1 sub-<label>/[ses-<label>/]
2   fmap/
3     sub-<label>[_ses-<label>][_acq-<label>][_run-<index>]_phase1.nii.gz]
4     sub-<label>[_ses-<label>][_acq-<label>][_run-<index>]_phase1.json
5     sub-<label>[_ses-<label>][_acq-<label>][_run-<index>]_phase2.nii.gz]
6     sub-<label>[_ses-<label>][_acq-<label>][_run-<index>]_phase2.json
7     sub-<label>[_ses-<label>][_acq-<label>][_run-<index>]_magnitude1.nii.gz]
8     sub-<label>[_ses-<label>][_acq-<label>][_run-<index>]_magnitude2.nii.gz]
```

Similar to the case above, but instead of a precomputed phase difference map two separate phase images are presented. The two sidecar JSON files need to specify corresponding `EchoTime` values. For example:

```
1 {
2   "EchoTime": 0.00746,
3   "IntendedFor": "func/sub-01_task-motor_bold.nii.gz"
4 }
```

Case 3: A real fieldmap image

Template:

```
1 sub-<label>/[ses-<label>/]
2   fmap/
```

```
3     sub-<label>[_ses-<label>][_acq-<label>][_run-<index>]_magnitude.nii.gz]
4     sub-<label>[_ses-<label>][_acq-<label>][_run-<index>]_fieldmap.nii.gz]
5     sub-<label>[_ses-<label>][_acq-<label>][_run-<index>]_fieldmap.json
```

In some cases (for example GE) the scanner software will output a precomputed fieldmap denoting the B0 inhomogeneities along with a magnitude image used for coregistration. In this case the sidecar JSON file needs to include the units of the fieldmap. The possible options are: Hertz (Hz), Radians per second (**rad/s**), or Tesla (T). For example:

```
1 {
2     "Units": "rad/s",
3     "IntendedFor": "func/sub-01_task-motor_bold.nii.gz"
4 }
```

Case 4: Multiple phase encoded directions ("pepolar")

Template:

```
1 sub-<label>/[ses-<label>/]
2     fmap/
3         sub-<label>[_ses-<label>][_acq-<label>][_ce-<label>]_dir-<label>[_run-<index>]_epi.nii.gz]
4         sub-<label>[_ses-<label>][_acq-<label>][_ce-<label>]_dir-<label>[_run-<index>]_epi.json
```

The phase-encoding polarity (PEpolar) technique combines two or more Spin Echo EPI scans with different phase encoding directions to estimate the underlying inhomogeneity/deformation map. Examples of tools using this kind of images are FSL TOPUP, AFNI 3dqwarp and SPM. In such a case, the phase encoding direction is specified in the corresponding JSON file as one of: i, j, k, i-, j-, k-. For these differentially phase encoded sequences, one also needs to specify the Total Readout Time defined as the time (in seconds) from the center of the first echo to the center of the last echo (aka "FSL definition" - see [here](#) and [here](#) how to calculate it). For example

```
1 {
2     "PhaseEncodingDirection": "j-",
3     "TotalReadoutTime": 0.095,
4     "IntendedFor": "func/sub-01_task-motor_bold.nii.gz"
5 }
```

The `label` value of the `dir-<label>` key/value pair can be set to arbitrary alphanumeric label (`[a-zA-Z0-9]+` for example LR or AP) that can help users to distinguish between different files, but should not be used to infer any scanning parameters (such as phase encoding directions) of the corresponding sequence. Please rely only on the JSON file to obtain scanning parameters. `_epi` files can be a 3D or 4D - in the latter case all timepoints share the same scanning parameters. To indicate which run is intended to be used with which functional or diffusion scan the `IntendedFor` field in the JSON file should be used.

## Magnetoencephalography

Support for Magnetoencephalography (MEG) was developed as a BIDS Extension Proposal. Please see [Citing BIDS](#) on how to appropriately credit this extension when referring to it in the context of the academic literature.

## MEG recording data

Template:

```
1 sub-<label>/
2   [ses-<label>]/
3   meg/
4     sub-<label>[_ses-<label>]_task-<label>[_run-<index>][_proc-<label>]_meg.<manufacturer_specific_extension>
5     [sub-<label>[_ses-<label>]_task-<label>[_run-<index>][_proc-<label>]_meg.json]
```

Unprocessed MEG data MUST be stored in the native file format of the MEG instrument with which the data was collected. With the MEG specification of BIDS, we wish to promote the adoption of good practices in the management of scientific data. Hence, the emphasis is not to impose a new, generic data format for the modality, but rather to standardize the way data is stored in repositories. Further, there is currently no widely accepted standard file format for MEG, but major software applications, including free and open-source solutions for MEG data analysis, provide readers of such raw files.

Some software readers may skip important metadata that is specific to MEG system manufacturers. It is therefore RECOMMENDED that users provide additional meta information extracted from the manufacturer raw data files in a sidecar JSON file. This allows for easy searching and indexing of key metadata elements without the need to parse files in proprietary data format. Other relevant files MAY be included alongside the MEG data; examples are provided below.

This template is for MEG data of any kind, including but not limited to task-based, resting-state, and noise recordings. If multiple Tasks were performed within a single Run, the task description can be set to `task-multitask`. The `_meg.json` SHOULD contain details on the Tasks.

Some manufacturers' data storage conventions use folders which contain data files of various nature: for example, CTF's `.ds` format, or BTi/4D. Yet other manufacturers split their files once they exceed a certain size limit. For example Neuromag/Elekta/Megin, which can produce several files for a single recording. Both `some_file.fif` and `some_file-1.fif` would belong to a single recording. In BIDS, the `split` entity is RECOMMENDED to deal with split files. Please refer to Appendix VI for general information on how to deal with such manufacturer specifics and to see more examples.

The `proc-<label>` entity is analogous to `rec-<label>` for MR and denotes a variant of a file that was a result of particular processing performed on the device. This is useful for files produced in particular by Elekta's MaxFilter (for example, `sss`, `tsss`, `trans`, `quat`, `mc`), which some installations impose to be run on raw data because of active shielding software corrections before the MEG data can actually be exploited.

### Recording EEG simultaneously with MEG

Note that if EEG is recorded with a separate amplifier, it SHOULD be stored separately under a new `/eeg` data type (see the EEG specification).

If however EEG is recorded simultaneously with the same MEG system, it MAY be stored under the `/meg` data type. In that case, it SHOULD have the same sampling frequency as MEG (see `SamplingFrequency` field below). Furthermore, the EEG sensor coordinates SHOULD be specified using MEG-specific coordinate systems (see `coordinates` section).

### Sidecar JSON (`*_meg.json`)

Generic fields MUST be present:

Key name	Requirement level	Data type	Description
TaskName	REQUIRED	string	Name of the task. No two tasks should have the same name. The task label included in the file name is derived from this TaskName field by removing all non-alphanumeric ([a-zA-Z0-9]) characters. For example TaskName <b>faces n-back</b> will correspond to task label <b>facesnback</b> . A RECOMMENDED convention is to name resting state task using labels beginning with <b>rest</b> .

SHOULD be present: For consistency between studies and institutions, we encourage users to extract the values of these fields from the actual raw data. Whenever possible, please avoid using ad-hoc wording.

Key name	Requirement level	Data type	Description
InstitutionName	RECOMMENDED	string	The name of the institution in charge of the equipment that produced the composite instances.
InstitutionAddress	RECOMMENDED	string	The address of the institution in charge of the equipment that produced the composite instances.
Manufacturer	RECOMMENDED	string	Manufacturer of the MEG system (CTF, Elekta/Neuromag, BTi/4D, KIT/Yokogawa, ITAB, KRISS, Other). See Appendix VII with preferred names.
ManufacturersModelName	RECOMMENDED	string	Manufacturer's designation of the MEG scanner model (for example, CTF-275). See Appendix VII with preferred names.
SoftwareVersions	RECOMMENDED	string	Manufacturer's designation of the acquisition software.
TaskDescription	RECOMMENDED	string	Description of the task.

Key name	Requirement level	Data type	Description
Instructions	RECOMMENDED	string	Text of the instructions given to participants before the scan. This is not only important for behavioral or cognitive tasks but also in resting state paradigms (for example, to distinguish between eyes open and eyes closed).
CogAtlasID	RECOMMENDED	string	URI of the corresponding Cognitive Atlas term that describes the task (for example, Resting State with eyes closed "http://www.cognitiveatlas.org/task/id/trm_54e69c642d89b").
CogPOID	RECOMMENDED	string	URI of the corresponding CogPO term that describes the task (for example, Rest "http://wiki.cogpo.org/index.php?title=Rest").
DeviceSerialNumber	RECOMMENDED	string	The serial number of the equipment that produced the composite instances. A pseudonym can also be used to prevent the equipment from being identifiable, as long as each pseudonym is unique within the dataset.

Specific MEG fields MUST be present:

Key name	Requirement level	Data type	Description
SamplingFrequency	REQUIRED	number	Sampling frequency (in Hz) of all the data in the recording, regardless of their type (for example, 2400).
PowerLineFrequency	REQUIRED	number or "n/a"	Frequency (in Hz) of the power grid at the geographical location of the MEG instrument (for example, 50 or 60).

Key name	Requirement level	Data type	Description
DewarPosition	REQUIRED	string	Position of the dewar during the MEG scan: <b>upright</b> , <b>supine</b> or <b>degrees</b> of angle from vertical: for example on CTF systems, upright=15°, supine=90°.
SoftwareFilters	REQUIRED	object of objects or "n/a"	Object of temporal software filters applied, or "n/a" if the data is not available. Each key:value pair in the JSON object is a name of the filter and an object in which its parameters are defined as key:value pairs (for example, {"SSS": {"frame": "head", "badlimit": 7}, "SpatialCompensation": {"GradientOrder": "Order of the gradient compensation"}}).
DigitizedLandmarks	REQUIRED	boolean	<b>true</b> or <b>false</b> value indicating whether anatomical landmark points (fiducials) are contained within this recording.
DigitizedHeadPoints	REQUIRED	boolean	<b>true</b> or <b>false</b> value indicating whether head points outlining the scalp/face surface are contained within this recording.

SHOULD be present:

Key name	Requirement level	Data type	Description
MEGChannelCount	RECOMMENDED	integer	Number of MEG channels (for example, 275).
MEGREFChannelCount	RECOMMENDED	integer	Number of MEG reference channels (for example, 23). For systems without such channels (for example, Neuromag Vectorview), <b>MEGREFChannelCount</b> should be set to 0.
EEGChannelCount	RECOMMENDED	integer	Number of EEG channels recorded simultaneously (for example, 21).

Key name	Requirement level	Data type	Description
ECOGChannelCount	RECOMMENDED	integer	Number of ECoG channels.
SEEGChannelCount	RECOMMENDED	integer	Number of SEEG channels.
EOGChannelCount	RECOMMENDED	integer	Number of EOG channels.
ECGChannelCount	RECOMMENDED	integer	Number of ECG channels.
EMGChannelCount	RECOMMENDED	integer	Number of EMG channels.
MiscChannelCount	RECOMMENDED	integer	Number of miscellaneous analog channels for auxiliary signals.
TriggerChannelCount	RECOMMENDED	integer	Number of channels for digital (TTL bit level) triggers.
RecordingDuration	RECOMMENDED	number	Length of the recording in seconds (for example, 3600).
RecordingType	RECOMMENDED	string	Defines whether the recording is "continuous", "discontinuous" or "epoched", where "epoched" is limited to time windows about events of interest (for example, stimulus presentations or subject responses).
EpochLength	RECOMMENDED	number	Duration of individual epochs in seconds (for example, 1) in case of epoched data.
ContinuousHeadLocalization	RECOMMENDED	boolean	<b>true</b> or <b>false</b> value indicating whether continuous head localisation was performed.
HeadCoilFrequency	RECOMMENDED	number or array of numbers	List of frequencies (in Hz) used by the head localisation coils ('HLC' in CTF systems, 'HPI' in Elekta, 'COH' in BTi/4D) that track the subject's head position in the MEG helmet (for example, [293, 307, 314, 321]).
MaxMovement	RECOMMENDED	number	Maximum head movement (in mm) detected during the recording, as measured by the head localisation coils (for example, 4.8).



Key name	Requirement level	Data type	Description
SubjectArtefactDescription	RECOMMENDED	string	Freeform description of the observed subject artefact and its possible cause (for example, "Vagus Nerve Stimulator", "non-removable implant"). If this field is set to n/a, it will be interpreted as absence of major source of artifacts except cardiac and blinks.
AssociatedEmptyRoom	RECOMMENDED	string	Relative path in BIDS folder structure to empty-room file associated with the subject's MEG recording. The path needs to use forward slashes instead of backward slashes (for example, sub-emptyroom/ses-/meg/sub-emptyroom_ses-_task-noise_run-_meg.ds).
HardwareFilters	RECOMMENDED	object of objects or "n/a"	Object of temporal hardware filters applied, or "n/a" if the data is not available. Each key:value pair in the JSON object is a name of the filter and an object in which its parameters are defined as key:value pairs (for example, {"Highpass RC filter": {"Half amplitude cutoff (Hz)": 0.0159, "Roll-off": "6dB/Octave"}}).

Specific EEG fields (if recorded with MEG, see Recording EEG simultaneously with MEG SHOULD be present:

Key name	Requirement level	Data type	Description
EEGPlacementScheme	OPTIONAL	string	Placement scheme of EEG electrodes. Either the name of a standardised placement system (for example, "10-20") or a list of standardised electrode names (for example, ["Cz", "Pz"]).
CapManufacturer	OPTIONAL	string	Manufacturer of the EEG cap (for example, EasyCap).

Key name	Requirement level	Data type	Description
CapManufacturersModelName	OPTIONAL	string	Manufacturer's designation of the EEG cap model (for example, M10).
EEGReference	OPTIONAL	string	Description of the type of EEG reference used (for example, M1 for left mastoid, average, or longitudinal bipolar).

Example:

```

1 {
2   "InstitutionName": "Stanford University",
3   "InstitutionAddress": "450 Serra Mall, Stanford, CA 94305-2004, USA",
4   "Manufacturer": "CTF",
5   "ManufacturersModelName": "CTF-275",
6   "DeviceSerialNumber": "11035",
7   "SoftwareVersions": "Acq 5.4.2-linux-20070507",
8   "PowerLineFrequency": 60,
9   "SamplingFrequency": 2400,
10  "MEGChannelCount": 270,
11  "MEGREFChannelCount": 26,
12  "EEGChannelCount": 0,
13  "EOGChannelCount": 2,
14  "ECGChannelCount": 1,
15  "EMGChannelCount": 0,
16  "DewarPosition": "upright",
17  "SoftwareFilters": {
18    "SpatialCompensation": {"GradientOrder": "3rd"}
19  },
20  "RecordingDuration": 600,
21  "RecordingType": "continuous",
22  "EpochLength": 0,
23  "TaskName": "rest",
24  "ContinuousHeadLocalization": true,
25  "HeadCoilFrequency": [1470,1530,1590],
26  "DigitizedLandmarks": true,
27  "DigitizedHeadPoints": true
28 }
```

Note that the date and time information SHOULD be stored in the Study key file (`scans.tsv`), see Scans file. Date time information MUST be expressed as indicated in Units

### Channels description (`*_channels.tsv`)

Template:

```
1 sub-<label>/
2   [ses-<label>]/
3   meg/
4   [sub-<label>[_ses-<label>]_task-<label>[_run-<index>] [_proc-<label>]_channels.tsv]
```

This file is RECOMMENDED as it provides easily searchable information across BIDS datasets for for example, general curation, response to queries or batch analysis. To avoid confusion, the channels SHOULD be listed in the order they appear in the MEG data file. Missing values MUST be indicated with `n/a`.

The columns of the Channels description table stored in `*_channels.tsv` are:

MUST be present:

Column name	Requirement level	Description
name	REQUIRED	Channel name (for example, MRT012, MEG023).
type	REQUIRED	Type of channel; MUST use the channel types listed below. Note that the type MUST be in upper-case.
units	REQUIRED	Physical unit of the value represented in this channel, for example, V for Volt, or fT/cm for femto Tesla per centimeter (see Units).

SHOULD be present:

Column name	Requirement level	Description
description	OPTIONAL	Brief free-text description of the channel, or other information of interest. See examples below.
sampling_frequency	OPTIONAL	Sampling rate of the channel in Hz.
low_cutoff	OPTIONAL	Frequencies used for the high-pass filter applied to the channel in Hz. If no high-pass filter applied, use <code>n/a</code> .

Column name	Requirement level	Description
high_cutoff	OPTIONAL	Frequencies used for the low-pass filter applied to the channel in Hz. If no low-pass filter applied, use n/a. Note that hardware anti-aliasing in A/D conversion of all MEG/EEG electronics applies a low-pass filter; specify its frequency here if applicable.
notch	OPTIONAL	Frequencies used for the notch filter applied to the channel, in Hz. If no notch filter applied, use n/a.
software_filters	OPTIONAL	List of temporal and/or spatial software filters applied (for example, "SSS", "SpatialCompensation"). Note that parameters should be defined in the general MEG sidecar .json file. Indicate n/a in the absence of software filters applied.
status	OPTIONAL	Data quality observed on the channel (good/bad). A channel is considered bad if its data quality is compromised by excessive noise. Description of noise type SHOULD be provided in [status_description].
status_description	OPTIONAL	Freeform text description of noise or artifact affecting data quality on the channel. It is meant to explain why the channel was declared bad in [status].

Example:

```

1 name type units description sampling_frequency low_cutoff high_cutoff notch software_filters status
2 UDI0001 TRIG V analogue trigger 1200 0.1 300 0 n/a good
3 MLC11 MEGGRADAXIAL T sensor 1st-order grad 1200 0 n/a 50 SSS bad

```

Restricted keyword list for field type. Note that upper-case is REQUIRED:

Keyword	Description
MEGMAG	MEG magnetometer
MEGGRADAXIAL	MEG axial gradiometer
MEGGRADPLANAR	MEG planargradiometer
MEGREFMAG	MEG reference magnetometer
MEGREFGRADAXIAL	MEG reference axial gradiometer

Keyword	Description
MEGREFGRADPLANAR	MEG reference planar gradiometer
MEGOTHER	Any other type of MEG sensor
EEG	Electrode channel
ECOG	Electrode channel
SEEG	Electrode channel
DBS	Electrode channel
VEOG	Vertical EOG (electrooculogram)
HEOG	Horizontal EOG
EOG	Generic EOG channel
ECG	ElectroCardioGram (heart)
EMG	ElectroMyoGram (muscle)
TRIG	System Triggers
AUDIO	Audio signal
PD	Photodiode
EYEGAZE	Eye Tracker gaze
PUPIL	Eye Tracker pupil diameter
MISC	Miscellaneous
SYSCLOCK	System time showing elapsed time since trial started
ADC	Analog to Digital input
DAC	Digital to Analog output
HLU	Measured position of head and head coils
FTERR	Fit error signal from each head localization coil
OTHER	Any other type of channel

Example of free text for field description:

- stimulus, response, vertical EOG, horizontal EOG, skin conductance, sats, intracranial, eyetracker

Example:

```

1 name type units description
2 VEOG VEOG V vertical EOG
3 FDI EMG V left first dorsal interosseous
4 UDI0001 TRIG V analog trigger signal
5 UADC001 AUDIO V envelope of audio signal presented to participant

```

Coordinate System JSON (`*_coordsystem.json`)

Template:

```

1 sub-<label>/
2   [ses-<label>]/
3   meg/
4   [sub-<label>[_ses-<label>][_acq-<label>]_coordsystem.json]

```

OPTIONAL. A JSON document specifying the coordinate system(s) used for the MEG, EEG, head localization coils, and anatomical landmarks.

MEG and EEG sensors:

Key name	Requirement level	Data type	Description
MEGCoordinateSystem	REQUIRED	string	Defines the coordinate system for the MEG sensors. See Appendix VIII for a list of restricted keywords for coordinate systems. If <b>Other</b> , provide definition of the coordinate system in <b>MEGCoordinateSystemDescription</b> . Units of the coordinates of <b>MEGCoordinateSystem</b> . MUST be m, cm, or mm.
MEGCoordinateUnits	REQUIRED	string	Units of the coordinates of <b>MEGCoordinateSystem</b> . MUST be m, cm, or mm.
MEGCoordinateSystemDescription	OPTIONAL, but REQUIRED if <b>MEGCoordinateSystem</b> is <b>Other</b>	string	Free-form text description of the coordinate system. May also include a link to a documentation page or paper describing the system in greater detail.
EEGCoordinateSystem	OPTIONAL	string	See Recording EEG simultaneously with MEG for a list of restricted keywords for coordinate systems. If <b>Other</b> , provide definition of the coordinate system in <b>EEGCoordinateSystemDescription</b> . Units of the coordinates of <b>EEGCoordinateSystem</b> . MUST be m, cm, or mm.
EEGCoordinateUnits	OPTIONAL	string	Units of the coordinates of <b>EEGCoordinateSystem</b> . MUST be m, cm, or mm.

Key name	Requirement level	Data type	Description
EEGCoordinateSystemDescription	OPTIONAL, but REQUIRED if EEGCoordinateSystem is Other	string	See Recording EEG simultaneously with MEG. Free-form text description of the coordinate system. May also include a link to a documentation page or paper describing the system in greater detail.

## Head localization coils:

Key name	Requirement level	Data type	Description
HeadCoilCoordinates	OPTIONAL	object of arrays	Key:value pairs describing head localization coil labels and their coordinates, interpreted following the HeadCoilCoordinateSystem (for example, {"NAS": [12.7,21.3,13.9], "LPA": [5.2,11.3,9.6], "RPA": [20.2,11.3,9.1]}). Note that coils are not always placed at locations that have a known anatomical name (for example, for Elekta, Yokogawa systems); in that case generic labels can be used (for example, {"coil1": [12.2,21.3,12.3], "coil2": [6.7,12.3,8.6], "coil3": [21.9,11.0,8.1]}). Each array MUST contain three numeric values corresponding to x, y, and z axis of the coordinate system in that exact order.

Key name	Requirement level	Data type	Description
HeadCoilCoordinateSystem	OPTIONAL	string	Defines the coordinate system for the head coils. See Appendix VIII for a list of restricted keywords for coordinate systems. If <b>Other</b> , provide definition of the coordinate system in <code>HeadCoilCoordinateSystemDescription</code> .
HeadCoilCoordinateUnits	OPTIONAL	string	Units of the coordinates of <code>HeadCoilCoordinateSystem</code> . MUST be m, cm, or mm.
HeadCoilCoordinateSystemDescription	OPTIONAL, but REQUIRED if <code>HeadCoilCoordinateSystem</code> is <b>Other</b>	string	Free-form text description of the coordinate system. May also include a link to a documentation page or paper describing the system in greater detail.

Digitized head points:

Key name	Requirement level	Data type	Description
DigitizedHeadPoints	OPTIONAL	string	Relative path to the file containing the locations of digitized head points collected during the session (for example, <code>sub-01_headshape.pos</code> ). RECOMMENDED for all MEG systems, especially for CTF and BTi/4D. For Elekta/Neuromag the head points will be stored in the fif file.
DigitizedHeadPointsCoordinateSystem	OPTIONAL	string	Defines the coordinate system for the digitized head points. See Appendix VIII for a list of restricted keywords for coordinate systems. If <b>Other</b> , provide definition of the coordinate system in <code>DigitizedHeadPointsCoordinateSystemDescription</code> .



Key name	Requirement level	Data type	Description
DigitizedHeadPointsCoordinateUnits	OPTIONAL	string	Units of the coordinates of <b>DigitizedHeadPointsCoordinateSystem</b> . MUST be m, cm, or mm.
DigitizedHeadPointsCoordinateSystemDescription	OPTIONAL, but REQUIRED if <b>DigitizedHeadPointsCoordinateSystem</b> is <b>Other</b>	string	Free-form text description of the coordinate system. May also include a link to a documentation page or paper describing the system in greater detail.

## Anatomical MRI:

Key name	Requirement level	Data type	Description
IntendedFor	OPTIONAL	string or array of strings	Path or list of path relative to the subject subfolder pointing to the structural MRI, possibly of different types if a list is specified, to be used with the MEG recording. The path(s) need(s) to use forward slashes instead of backward slashes (for example, <b>ses-/anat/sub-01_T1w.nii.gz</b> ).

## Anatomical landmarks:

Key name	Requirement level	Data type	Description
AnatomicalLandmarkCoordinates	OPTIONAL	object of arrays	Key:value pairs of the labels and 3-D digitized locations of anatomical landmarks, interpreted following the <code>AnatomicalLandmarkCoordinateSystem</code> (for example, <code>{"NAS": [12.7,21.3,13.9], "LPA": [5.2,11.3,9.6], "RPA": [20.2,11.3,9.1]}</code> ). Each array MUST contain three numeric values corresponding to x, y, and z axis of the coordinate system in that exact order.
AnatomicalLandmarkCoordinateSystem	OPTIONAL	string	Defines the coordinate system for the anatomical landmarks. See Appendix VIII for a list of restricted keywords for coordinate systems. If <code>Other</code> , provide definition of the coordinate system in <code>AnatomicalLandmarkCoordinateSystemDescription</code> .
AnatomicalLandmarkCoordinateUnits	OPTIONAL	string	Units of the coordinates of <code>AnatomicalLandmarkCoordinateSystem</code> . MUST be m, cm, or mm.
AnatomicalLandmarkCoordinateSystemDescription	OPTIONAL, but REQUIRED if <code>AnatomicalLandmarkCoordinateSystem</code> is <code>Other</code>	string	Free-form text description of the coordinate system. May also include a link to a documentation page or paper describing the system in greater detail.

It is also RECOMMENDED that the MRI voxel coordinates of the actual anatomical landmarks for co-registration of MEG with structural MRI are stored in the `AnatomicalLandmarkCoordinates` field in the JSON sidecar of the corresponding T1w MRI anatomical data of the subject seen in the MEG session (see here ) - for example: `sub-01/ses-mri/anat/sub-01_ses-mri_acq-mprage_T1w.json`

In principle, these locations are those of absolute anatomical markers. However, the marking of NAS, LPA and RPA is more ambiguous than that of for example, AC and PC. This may result in some variability in their 3-D digitization from session to session, even for the same participant. The solution would be to use only one T1w file and populate the `AnatomicalLandmarkCoordinates` field with session-specific labels for example, "NAS-session1": [127,213,139], "NAS-session2": [123,220,142].

Fiducials information:

Key name	Requirement level	Data type	Description
FiducialsDescription	OPTIONAL	string	A freeform text field documenting the anatomical landmarks that were used and how the head localization coils were placed relative to these. This field can describe, for instance, whether the true anatomical locations of the left and right pre-auricular points were used and digitized, or rather whether they were defined as the intersection between the tragus and the helix (the entry of the ear canal), or any other anatomical description of selected points in the vicinity of the ears.

For more information on the definition of anatomical landmarks, please visit: [http://www.fieldtriptoolbox.org/faq/how\\_are\\_the\\_lpa\\_and\\_rpa\\_points\\_defined](http://www.fieldtriptoolbox.org/faq/how_are_the_lpa_and_rpa_points_defined)

For more information on typical coordinate systems for MEG-MRI coregistration: [http://www.fieldtriptoolbox.org/faq/how\\_are\\_the\\_different\\_head\\_and\\_mri\\_coordinate\\_systems\\_defined](http://www.fieldtriptoolbox.org/faq/how_are_the_different_head_and_mri_coordinate_systems_defined), or: <http://neuroimage.usc.edu/brainstorm/CoordinateSystems>

### Landmark photos (\*\_photo.jpg)

Photos of the anatomical landmarks and/or head localization coils (\*\_photo.jpg)

Template:


```

1 sub-<label>/
2   [ses-<label>]/
3     meg/
4       [sub-<label>[_ses-<label>] [_acq-<label>]_photo.jpg]
```

Photos of the anatomical landmarks and/or head localization coils on the subject's head are RECOMMENDED. If the coils are not placed at the location of actual anatomical landmarks, these latter may be marked with a piece of felt-tip taped to the skin. Please note that the photos may need to be cropped or blurred to conceal identifying features prior to sharing, depending on the terms of the consent given by the participant.

The `acq-<label>` entity can be used to indicate acquisition of different photos of the same face (or other body part in different angles to show, for example, the location of the nasion (NAS) as opposed to the right periauricular point (RPA)).

Example of the NAS fiducial placed between the eyebrows, rather than at the actual anatomical nasion: `sub-0001_ses-001_acq-NAS_photo.jpg`



### Head shape and electrode description (\*\_headshape.<ext>)

Template:

```
1 sub-<label>/  
2   [ses-<label>]/  
3   meg/  
4   [sub-<label>[_ses-<label>][_acq-<label>]_headshape.<manufacturer_specific_extension>]
```

This file is RECOMMENDED.

The 3-D locations of points that describe the head shape and/or EEG electrode locations can be digitized and stored in separate files. The `acq-<label>` entity can be used when more than one type of digitization is done for a session, for example when the head points are in a separate file from the EEG locations. These files are stored in the specific format of the 3-D digitizer's manufacturer (see Appendix VI).

Example:

```
1 sub-control01  
2   ses-01  
3     sub-control01_ses-01_acq-HEAD_headshape.pos  
4     sub-control01_ses-01_acq-ECG_headshape.pos
```

Note that the \*\_headshape file(s) is shared by all the runs and tasks in a session. If the subject needs to be taken out of the scanner and the head-shape has to be updated, then for MEG it could be considered to be a new session.

## Empty-room MEG recordings

Empty-room MEG recordings capture the environmental and recording system's noise. In the context of BIDS it is RECOMMENDED to perform an empty-room recording for each experimental session. It is RECOMMENDED to store the empty-room recording inside a subject folder named `sub-emptyroom`. The label for the `task-<label>` entity in the empty-room recording SHOULD be set to `noise`. If a `session-<label>` entity is present, its label SHOULD be the date of the empty-room recording in the format `YYYYMMDD`, that is `ses-YYYYMMDD`. The `scans.tsv` file containing the date and time of the acquisition SHOULD also be included. The rationale is that this naming scheme will allow users to easily retrieve the empty-room recording that best matches a particular experimental session, based on date and time of the recording. It should be possible to query empty-room recordings just like usual subject recordings, hence all metadata sidecar files (such as the `channels.tsv`) file SHOULD be present as well.

Example:

```
1 sub-control01/
2 sub-control02/
3 sub-emptyroom/
4   ses-20170801/
5     sub-emptyroom_ses-20170801_scans.tsv
6     meg/
7       sub-emptyroom_ses-20170801_task-noise_meg.ds
8       sub-emptyroom_ses-20170801_task-noise_meg.json
9       sub-emptyroom_ses-20170801_task-noise_channels.tsv
```

## Electroencephalography

Support for Electroencephalography (EEG) was developed as a BIDS Extension Proposal. Please see Citing BIDS on how to appropriately credit this extension when referring to it in the context of the academic literature.

The following example EEG datasets have been formatted using this specification and can be used for practical guidance when curating a new dataset.

- Single session per subject: `eeg_matchingpennies`
- Multiple sessions per subject: `eeg_rishikesh`
- Combined with fMRI: `eeg_rest_fmri`

Further datasets are available from the BIDS examples repository.

## EEG recording data

Template:

```
1 sub-<label>/
2   [ses-<label>]/
3   eeg/
4     sub-<label>[_ses-<label>]_task-<label>[_run-<index>]_eeg.<manufacturer_specific_extension>
5     sub-<label>[_ses-<label>]_task-<label>[_run-<index>]_eeg.json
```

The EEG community uses a variety of formats for storing raw data, and there is no single standard that all researchers agree on. For BIDS, EEG data MUST be stored in one of the following formats:

- European data format (Each recording consisting of a `.edf` file)
- BrainVision Core Data Format (Each recording consisting of a `.vhdr`, `.vmrk`, `.eeg` file triplet)
- The format used by the MATLAB toolbox EEGLAB (Each recording consisting of a `.set` file with an optional `.fdt` file)
- Biosemi data format (Each recording consisting of a `.bdf` file)

It is RECOMMENDED to use the European data format, or the BrainVision data format. It is furthermore discouraged to use the other accepted formats over these RECOMMENDED formats, particularly because there are conversion scripts available in most commonly used programming languages to convert data into the RECOMMENDED formats. The data in their original format, if different from the supported formats, can be stored in the `/sourcedata` directory.

The original data format is especially valuable in case conversion elicits the loss of crucial metadata specific to manufacturers and specific EEG systems. We also encourage users to provide additional meta information extracted from the manufacturer specific data files in the sidecar JSON file. Other relevant files MAY be included alongside the original EEG data in `/sourcedata`.

Note the `RecordingType`, which depends on whether the data stream on disk is interrupted or not. Continuous data is by definition 1 segment without interruption. Epoched data consists of multiple segments that all have the same length (for example, corresponding to trials) and that have gaps in between. Discontinuous data consists of multiple segments of different length, for example due to a pause in the acquisition.

Note that for proper documentation of EEG recording metadata it is important to understand the difference between electrode and channel: An EEG electrode is attached to the skin, whereas a channel is the combination of the analog differential amplifier and analog-to-digital converter that result in a potential (voltage) difference that is stored in the EEG dataset. We employ the following short definitions:

- Electrode = A single point of contact between the acquisition system and the recording site (for example, scalp, neural tissue, ...). Multiple electrodes can be organized as caps (for EEG), arrays, grids, leads, strips, probes, shafts, and so on.
- Channel = A single analog-to-digital converter in the recording system that regularly samples the value of a transducer, which results in the signal being represented as a time series in the digitized data. This can be connected to two electrodes (to measure the potential difference between them), a magnetic field or magnetic gradient sensor, temperature sensor, accelerometer, and so on.

Although the reference and ground electrodes are often referred to as channels, they are in most common EEG systems not recorded by themselves. Therefore they are not represented as channels in the data. The type of referencing for all channels and optionally the location of the reference electrode and the location of the ground electrode MAY be specified.

Sidecar JSON (`*_eeg.json`)

Generic fields MUST be present:

Key name	Requirement level	Data type	Description
TaskName	REQUIRED	string	Name of the task. No two tasks should have the same name. The task label included in the file name is derived from this TaskName field by removing all non-alphanumeric ([a-zA-Z0-9]) characters. For example TaskName <b>faces n-back</b> will correspond to task label <b>facesnback</b> . A RECOMMENDED convention is to name resting state task using labels beginning with <b>rest</b> .

SHOULD be present: For consistency between studies and institutions, we encourage users to extract the values of these fields from the actual raw data. Whenever possible, please avoid using ad hoc wording.

Key name	Requirement level	Data type	Description
InstitutionName	RECOMMENDED	string	The name of the institution in charge of the equipment that produced the composite instances.
InstitutionAddress	RECOMMENDED	string	The address of the institution in charge of the equipment that produced the composite instances.
Manufacturer	RECOMMENDED	string	Manufacturer of the EEG system (for example, Biosemi, Brain Products, Neuroscan).
ManufacturersModelName	RECOMMENDED	string	Manufacturer's designation of the EEG system model (for example, BrainAmp DC).
SoftwareVersions	RECOMMENDED	string	Manufacturer's designation of the acquisition software.
TaskDescription	RECOMMENDED	string	Description of the task.

Key name	Requirement level	Data type	Description
Instructions	RECOMMENDED	string	Text of the instructions given to participants before the scan. This is not only important for behavioral or cognitive tasks but also in resting state paradigms (for example, to distinguish between eyes open and eyes closed).
CogAtlasID	RECOMMENDED	string	URI of the corresponding Cognitive Atlas term that describes the task (for example, Resting State with eyes closed "http://www.cognitiveatlas.org/task/id/trm_54e69c642d89b").
CogPOID	RECOMMENDED	string	URI of the corresponding CogPO term that describes the task (for example, Rest "http://wiki.cogpo.org/index.php?title=Rest") .
DeviceSerialNumber	RECOMMENDED	string	The serial number of the equipment that produced the composite instances. A pseudonym can also be used to prevent the equipment from being identifiable, as long as each pseudonym is unique within the dataset.

Specific EEG fields MUST be present:

Key name	Requirement level	Data type	Description
EEGReference	REQUIRED	string	General description of the reference scheme used and (when applicable) of location of the reference electrode in the raw recordings (for example, "left mastoid", "Cz", "CMS"). If different channels have a different reference, this field should have a general description and the channel specific reference should be defined in the <code>channels.tsv</code> file.



Key name	Requirement level	Data type	Description
SamplingFrequency	REQUIRED	number	Sampling frequency (in Hz) of all the data in the recording, regardless of their type (for example, 2400).
PowerLineFrequency	REQUIRED	number or "n/a"	Frequency (in Hz) of the power grid at the geographical location of the EEG instrument (for example, 50 or 60).
SoftwareFilters	REQUIRED	object of objects or "n/a"	Object of temporal software filters applied, or "n/a" if the data is not available. Each key:value pair in the JSON object is a name of the filter and an object in which its parameters are defined as key:value pairs. For example, {"Anti-aliasing filter": {"half-amplitude cutoff (Hz)": 500, "Roll-off": "6dB/Octave"}}.

Key name	Requirement level	Data type	Description
CapManufacturer	RECOMMENDED	string	Name of the cap manufacturer (for example, "EasyCap").
CapManufacturersModelName	RECOMMENDED	string	Manufacturer's designation of the EEG cap model (for example, "actiCAP 64 Ch Standard-2").
EEGChannelCount	RECOMMENDED	integer	Number of EEG channels included in the recording (for example, 128).
ECGChannelCount	RECOMMENDED	integer	Number of ECG channels.
EMGChannelCount	RECOMMENDED	integer	Number of EMG channels.
EOGChannelCount	RECOMMENDED	integer	Number of EOG channels.
MiscChannelCount	RECOMMENDED	integer	Number of miscellaneous analog channels for auxiliary signals.
TriggerChannelCount	RECOMMENDED	integer	Number of channels for digital (TTL bit level) trigger.
RecordingDuration	RECOMMENDED	number	Length of the recording in seconds (for example, 3600).

Key name	Requirement level	Data type	Description
RecordingType	RECOMMENDED	string	Defines whether the recording is "continuous", "discontinuous" or "epoched", where "epoched" is limited to time windows about events of interest (for example, stimulus presentations, subject responses).
EpochLength	RECOMMENDED	number	Duration of individual epochs in seconds (for example, 1) in case of epoched data.
EEGGround	RECOMMENDED	string	Description of the location of the ground electrode (for example, "placed on right mastoid (M2)").
HeadCircumference	RECOMMENDED	number	Circumference of the participants head, expressed in cm (for example, 58).
EEGPlacementScheme	RECOMMENDED	string	Placement scheme of EEG electrodes. Either the name of a standardized placement system (for example, "10-20") or a list of standardized electrode names (for example, ["Cz", "Pz"]).
HardwareFilters	RECOMMENDED	object of objects or "n/a"	Object of temporal hardware filters applied, or "n/a" if the data is not available. Each key:value pair in the JSON object is a name of the filter and an object in which its parameters are defined as key:value pairs. For example, {"Highpass RC filter": {"Half amplitude cutoff (Hz)": 0.0159, "Roll-off": "6dB/Octave"}}}

Key name	Requirement level	Data type	Description
SubjectArtefactDescription	RECOMMENDED	string	Free-form description of the observed subject artifact and its possible cause (for example, "Vagus Nerve Stimulator", "non-removable implant"). If this field is set to n/a, it will be interpreted as absence of major source of artifacts except cardiac and blinks.

Example:

```

1 {
2   "TaskName": "Seeing stuff",
3   "TaskDescription": "Subjects see various images for which phase, amplitude spectrum, and color vary continuously",
4   "Instructions": "Your task is to detect images when they appear for the 2nd time, only then press the response button with your right/left hand (
   counterbalanced across subjects)",
5   "InstitutionName": "The world best university, 10 Beachfront Avenue, Papeete",
6   "SamplingFrequency": 2400,
7   "Manufacturer": "Brain Products",
8   "ManufacturersModelName": "BrainAmp DC",
9   "CapManufacturer": "EasyCap",
10  "CapManufacturersModelName": "M1-ext",
11  "EEGChannelCount": 87,
12  "EOGChannelCount": 2,
13  "ECGChannelCount": 1,
14  "EMGChannelCount": 0,
15  "MiscChannelCount": 0,
16  "TriggerChannelCount": 1,
17  "PowerLineFrequency": 50,
18  "EEGPlacementScheme": "10 percent system",
19  "EEGReference": "single electrode placed on FCz",
20  "EEGGround": "placed on AFz",
21  "SoftwareFilters": {
22    "Anti-aliasing filter": {
23      "half-amplitude cutoff (Hz)": 500,
24      "Roll-off": "6dB/Octave"
25    }
26  },
27  "HardwareFilters": {

```

```

28     "ADC's decimation filter (hardware bandwidth limit)":{
29         "-3dB cutoff point (Hz)":480,
30         "Filter order sinc response":5
31     }
32 },
33 "RecordingDuration":600,
34 "RecordingType":"continuous"
35 }

```

Note that the date and time information SHOULD be stored in the Study key file (`scans.tsv`). Date time information MUST be expressed as indicated in Units

### Channels description (`*_channels.tsv`)

Template:

```

1 sub-<label>/
2   [ses-<label>]/
3     eeg/
4       [sub-<label>[_ses-<label>]_task-<label>[_run-<index>]]_channels.tsv]

```

This file is RECOMMENDED as it provides easily searchable information across BIDS datasets for for example, general curation, response to queries or batch analysis. The required columns are channel `name`, `type` and `units` in this specific order. To avoid confusion, the channels SHOULD be listed in the order they appear in the EEG data file. Any number of additional columns may be added to provide additional information about the channels. Note that electrode positions SHOULD NOT be added to this file, but to `*_electrodes.tsv`.

The columns of the Channels description table stored in `*_channels.tsv` are:

MUST be present:

Column name	Requirement level	Description
name	REQUIRED	Channel name (for example, FC1, Cz)
type	REQUIRED	Type of channel; MUST use the channel types listed below. Note that the type MUST be in upper-case.
units	REQUIRED	Physical unit of the value represented in this channel, for example, V for Volt, or fT/cm for femto Tesla per centimeter (see Units).

SHOULD be present:

Column name	Requirement level	Description
description	OPTIONAL	Free-form text description of the channel, or other information of interest. See examples below.
sampling_frequency	OPTIONAL	Sampling rate of the channel in Hz.
reference	OPTIONAL	Name of the reference electrode(s) (not needed when it is common to all channels, in that case it can be specified in *_eeg.json as EEGReference).
low_cutoff	OPTIONAL	Frequencies used for the high-pass filter applied to the channel in Hz. If no high-pass filter applied, use n/a.
high_cutoff	OPTIONAL	Frequencies used for the low-pass filter applied to the channel in Hz. If no low-pass filter applied, use n/a. Note that hardware anti-aliasing in A/D conversion of all EEG electronics applies a low-pass filter; specify its frequency here if applicable.
notch	OPTIONAL	Frequencies used for the notch filter applied to the channel, in Hz. If no notch filter applied, use n/a.
status	OPTIONAL	Data quality observed on the channel (good, bad). A channel is considered bad if its data quality is compromised by excessive noise. Description of noise type SHOULD be provided in status_description.
status_description	OPTIONAL	Free-form text description of noise or artifact affecting data quality on the channel. It is meant to explain why the channel was declared bad in status.

Restricted keyword list for field **type** in alphabetic order (shared with the MEG and iEEG modality; however, only the types that are common in EEG data are listed here). Note that upper-case is REQUIRED:

Keyword	Description
AUDIO	Audio signal
EEG	Electroencephalogram channel
EOG	Generic electrooculogram (eye), different from HEOG and VEOG
ECG	Electrocardiogram (heart)
EMG	Electromyogram (muscle)
EYEGAZE	Eye tracker gaze
GSR	Galvanic skin response

Keyword	Description
HEOG	Horizontal EOG (eye)
MISC	Miscellaneous
PPG	Photoplethysmography
PUPIL	Eye tracker pupil diameter
REF	Reference channel
RESP	Respiration
SYSCLOCK	System time showing elapsed time since trial started
TEMP	Temperature
TRIG	System triggers
VEOG	Vertical EOG (eye)

Example of free-form text for field `description`

- n/a, stimulus, response, skin conductance, battery status

Example:

	name	type	units	description	status	status_description
2	VEOG	VEOG	uV	n/a	good	n/a
3	FDI	EMG	uV	left first dorsal interosseous	good	n/a
4	Cz	EEG	uV	n/a	bad	high frequency noise
5	UADC001	MISC	n/a	envelope of audio signal	good	n/a

### Electrodes description (`*_electrodes.tsv`)

Template:

```

1 sub-<label>/
2   [ses-<label>]/
3   eeg/
4   [sub-<label>[_ses-<label>][_acq-<label>][_run-<index>]_electrodes.tsv]
```

File that gives the location of EEG electrodes. Note that coordinates are expected in cartesian coordinates according to the `EEGCoordinateSystem` and `EEGCoordinateUnits` fields in `*_coordsystem.json`. If an `*_electrodes.tsv` file is specified, a `*_coordsystem.json` file **MUST** be specified as well. The order of the required columns in the `*_electrodes.tsv` file **MUST** be as listed below.

**MUST** be present:

Column name	Requirement level	Description
name	REQUIRED	Name of the electrode.
x	REQUIRED	Recorded position along the x-axis.
y	REQUIRED	Recorded position along the y-axis.
z	REQUIRED	Recorded position along the z-axis.

SHOULD be present:

Column name	Requirement level	Description
type	RECOMMENDED	Type of the electrode (for example, cup, ring, clip-on, wire, needle).
material	RECOMMENDED	Material of the electrode (for example, Tin, Ag/AgCl, Gold).
impedance	RECOMMENDED	Impedance of the electrode, units MUST be in kOhm.

Example:

```

1 name  x      y      z      type  material
2 A1    -0.0707 0.0000 -0.0707 clip-on Ag/AgCl
3 F3    -0.0567 0.0677 0.0469 cup    Ag/AgCl
4 Fz    0.0000 0.0714 0.0699 cup    Ag/AgCl
5 REF   -0.0742 -0.0200 -0.0100 cup    Ag/AgCl
6 GND   0.0742 -0.0200 -0.0100 cup    Ag/AgCl

```

The `acq-<label>` key/value pair can be used to indicate acquisition of the same data. For example, this could be the recording of electrode positions with a different electrode position recording device, or repeated digitization before and after the recording.

### Coordinate System JSON (`*_coordsystem.json`)

Template:

```

1 sub-<label>/
2   [ses-<label>]/
3   eeg/
4   [sub-<label>[_ses-<label>][_acq-<label>]]_coordsystem.json]

```

A `*_coordsystem.json` file is used to specify the fiducials, the location of anatomical landmarks, and the coordinate system and units in which the position of electrodes and landmarks is expressed. The `*_coordsystem.json` is REQUIRED if the optional `*_electrodes.tsv` is specified. If a corresponding anatomical MRI is available, the locations of landmarks and fiducials according to that scan should also be stored in the `*_T1w.json` file which goes alongside the MRI data.

For disambiguation, we employ the following definitions for fiducials and anatomical landmarks respectively:

- Fiducials are objects with a well defined location used to facilitate the localization of electrodes and co-registration with other geometric data such as the participant's own T1 weighted magnetic resonance head image, a T1 weighted template head image, or a spherical head model. Commonly used fiducials are vitamin-E pills, which show clearly in an MRI, or reflective spheres that are localized with an infrared optical tracking system.
- Anatomical landmarks are locations on a research subject such as the nasion, which is the intersection of the frontal bone and two nasal bones of the human skull.

Fiducials are typically used in conjunction with anatomical landmarks. An example would be the placement of vitamin-E pills on top of anatomical landmarks, or the placement of LEDs on the nasion and preauricular points to triangulate the position of other LED-lit electrodes on a research subject's head.

- For more information on the definition of anatomical landmarks, please visit: [http://www.fieldtriptoolbox.org/faq/how\\_are\\_the\\_lpa\\_and\\_rpa\\_points\\_defined](http://www.fieldtriptoolbox.org/faq/how_are_the_lpa_and_rpa_points_defined)
- For more information on coordinate systems for coregistration, please visit: [http://www.fieldtriptoolbox.org/faq/how\\_are\\_the\\_different\\_head\\_and\\_mri\\_coordinate\\_systems\\_defined](http://www.fieldtriptoolbox.org/faq/how_are_the_different_head_and_mri_coordinate_systems_defined)

General fields:

Key name	Requirement level	Data type	Description
IntendedFor	OPTIONAL	string	Relative path to associate the electrodes, landmarks and fiducials to an MRI/CT.

Fields relating to the EEG electrode positions:

Key name	Requirement level	Data type	Description
EEGCoordinateSystem	REQUIRED	string	Defines the coordinate system for the EEG sensors. See Appendix VIII for a list of restricted keywords for coordinate systems. If <code>Other</code> , provide definition of the coordinate system in <code>EEGCoordinateSystemDescription</code> .
EEGCoordinateUnits	REQUIRED	string	Units in which the coordinates that are listed in the field <code>EEGCoordinateSystem</code> are represented. MUST be <code>m</code> , <code>cm</code> , or <code>mm</code> .



Key name	Requirement level	Data type	Description
EEGCoordinateSystemDescription	RECOMMENDED, but REQUIRED if EEGCoordinateSystem is Other	string	Free-form text description of the coordinate system. May also include a link to a documentation page or paper describing the system in greater detail.

Fields relating to the position of fiducials measured during an EEG session/run:

Key name	Requirement level	Data type	Description
FiducialsDescription	OPTIONAL	string	Free-form text description of how the fiducials such as vitamin-E capsules were placed relative to anatomical landmarks, and how the position of the fiducials were measured (for example, both with Polhemus and with T1w MRI).
FiducialsCoordinates	RECOMMENDED	object of arrays	Key:value pairs of the labels and 3-D digitized position of anatomical landmarks, interpreted following the FiducialsCoordinateSystem (for example, {"NAS": [12.7,21.3,13.9], "LPA": [5.2,11.3,9.6], "RPA": [20.2,11.3,9.1]}). Each array MUST contain three numeric values corresponding to x, y, and z axis of the coordinate system in that exact order.
FiducialsCoordinateSystem	RECOMMENDED	string	Defines the coordinate system for the fiducials. Preferably the same as the EEGCoordinateSystem. See Appendix VIII for a list of restricted keywords for coordinate systems. If Other, provide definition of the coordinate system in FiducialsCoordinateSystemDescription.

Key name	Requirement level	Data type	Description
FiducialsCoordinateUnits	RECOMMENDED	string	Units in which the coordinates that are listed in the field <b>AnatomicalLandmarkCoordinateSystem</b> are represented. MUST be m, cm, or mm.
FiducialsCoordinateSystemDescription	RECOMMENDED, but REQUIRED if <b>FiducialsCoordinateSystem</b> is <b>Other</b>	string	Free-form text description of the coordinate system. May also include a link to a documentation page or paper describing the system in greater detail.

Fields relating to the position of anatomical landmark measured during an EEG session/run:

Key name	Requirement level	Data type	Description
AnatomicalLandmarkCoordinates	RECOMMENDED	object of arrays	Key:value pairs of the labels and 3-D digitized position of anatomical landmarks, interpreted following the <b>AnatomicalLandmarkCoordinateSystem</b> (for example, {"NAS": [12.7, 21.3, 13.9], "LPA": [5.2, 11.3, 9.6], "RPA": [20.2, 11.3, 9.1]}). Each array MUST contain three numeric values corresponding to x, y, and z axis of the coordinate system in that exact order.
AnatomicalLandmarkCoordinateSystem	RECOMMENDED	string	Defines the coordinate system for the anatomical landmarks. Preferably the same as the <b>EEGCoordinateSystem</b> . See Appendix VIII for a list of restricted keywords for coordinate systems. If <b>Other</b> , provide definition of the coordinate system in <b>AnatomicalLandmarkCoordinateSystemDescription</b> .

Key name	Requirement level	Data type	Description
AnatomicalLandmarkCoordinateUnits	RECOMMENDED	string	Units in which the coordinates that are listed in the field <code>AnatomicalLandmarkCoordinateSystem</code> are represented. MUST be m, cm, or mm.
AnatomicalLandmarkCoordinateSystemDescription	RECOMMENDED, but REQUIRED if <code>AnatomicalLandmarkCoordinateSystem</code> is <code>Other</code>	string	Free-form text description of the coordinate system. May also include a link to a documentation page or paper describing the system in greater detail.

If the position of anatomical landmarks is measured using the same system or device used to measure electrode positions, and if thereby the anatomical landmarks are expressed in the same coordinates, the coordinates of the anatomical landmarks can be specified in `electrodes.tsv`. The same applies to the coordinates of the fiducials.

Anatomical landmarks or fiducials measured on an anatomical MRI that match the landmarks or fiducials during an EEG session/run, must be stored separately in the corresponding `*_T1w.json` or `*_T2w.json` file and should be expressed in voxels (starting from [0, 0, 0]).

Example:

```

1 {
2   "IntendedFor":"/sub-01/ses-01/anat/sub-01_T1w.nii",
3   "EEGCoordinateSystem":"Other",
4   "EEGCoordinateUnits":"mm",
5   "EEGCoordinateSystemDescription":"RAS orientation: Origin halfway between LPA and RPA, positive x-axis towards RPA, positive y-axis orthogonal to
   x-axis through Nasion, z-axis orthogonal to xy-plane, pointing in superior direction.",
6   "FiducialsDescription":"Electrodes and fiducials were digitized with Polhemus, fiducials were recorded as the centre of vitamin E capsules
   sticked on the left/right pre-auricular and on the nasion, these are also visible on the T1w MRI"
7 }
```

### Landmark photos (`*_photo.jpg`)

Photos of the anatomical landmarks and/or fiducials.

Template:

```


1 sub-<label>/
2   [ses-<label>]/
3   eeg/
4     [sub-<label>[_ses-<label>][_acq-<label>]_photo.jpg]
```

Photos of the anatomical landmarks and/or fiducials are OPTIONAL. Please note that the photos may need to be cropped or blurred to conceal identifying features prior to sharing, depending on the terms of the consent given by the participant.

The `acq-<label>` key/value pair can be used to indicate acquisition of different photos of the same face (or other body part in different angles to show, for example, the location of the nasion (NAS) as opposed to the right periauricular point (RPA)).

Example:

Picture of a NAS fiducial placed between the eyebrows, rather than at the actual anatomical nasion: `sub-0001_ses-001_acq-NAS_photo.jpg`



## Intracranial Electroencephalography

Support Intracranial Electroencephalography (iEEG) was developed as a BIDS Extension Proposal. Please see Citing BIDS on how to appropriately credit this extension when referring to it in the context of the academic literature.

### iEEG recording data

Template:

```
1 sub-<label>/
2   [ses-<label>]/
3     ieeg/
4       sub-<label>[_ses-<label>]_task-<label>[_run-<index>]_ieeg.<manufacturer_specific_extension>
5       sub-<label>[_ses-<label>]_task-<label>[_run-<index>]_ieeg.json
```

The iEEG community uses a variety of formats for storing raw data, and there is no single standard that all researchers agree on. For BIDS, iEEG data **MUST** be stored in one of the following formats:

- European Data Format (Each recording consisting of a `.edf` file)
- BrainVision Core Data Format (Each recording consisting of a `.vhdr`, `.vmrk`, `.eeg` file triplet)
- The format used by the MATLAB toolbox EEGLAB (Each recording consisting of a `.set` file with an optional `.fdt` file)
- Neurodata Without Borders (Each recording consisting of a `.nwb` file)
- MEF3 (Each recording consisting of a `.mef` directory)

It is **RECOMMENDED** to use the European data format, or the BrainVision data format. It is furthermore discouraged to use the other accepted formats over these **RECOMMENDED** formats, particularly because there are conversion scripts available in most commonly used programming languages to convert data into the **RECOMMENDED** formats.

Future versions of BIDS may extend this list of supported file formats. File formats for future consideration **MUST** have open access documentation, **MUST** have open source implementation for both reading and writing in at least two programming languages and **SHOULD** be widely supported in multiple software packages. Other formats that may be considered in the future should have a clear added advantage over the existing formats and should have wide adoption in the BIDS community.

The data format in which the data was originally stored is especially valuable in case conversion elicits the loss of crucial metadata specific to manufacturers and specific iEEG systems. We also encourage users to provide additional meta information extracted from the manufacturer-specific data files in the sidecar JSON file. Other relevant files **MAY** be included alongside the original iEEG data in the `/sourcedata` directory.

Note the `RecordingType`, which depends on whether the data stream on disk is interrupted or not. Continuous data is by definition 1 segment without interruption. Epoched data consists of multiple segments that all have the same length (for example, corresponding to trials) and that have gaps in between. Discontinuous data consists of multiple segments of different length, for example due to a pause in the acquisition.

#### Terminology: Electrodes vs. Channels

For proper documentation of iEEG recording metadata it is important to understand the difference between electrode and channel: an iEEG electrode is placed on or in the brain, whereas a channel is the combination of the analog differential amplifier and analog-to-digital converter that result in a potential (voltage) difference that is stored in the iEEG dataset. We employ the following short definitions:

- Electrode = A single point of contact between the acquisition system and the recording site (for example, scalp, neural tissue, ...). Multiple electrodes can be organized as arrays, grids, leads, strips, probes, shafts, caps (for EEG), and so forth.
- Channel = A single analog-to-digital converter in the recording system that regularly samples the value of a transducer, which results in the signal being represented as a time series in the digitized data. This can be connected to two electrodes (to measure the potential difference between them), a magnetic field or magnetic gradient sensor, temperature sensor, accelerometer, and so forth.

Although the reference and ground electrodes are often referred to as channels, they are in most common iEEG systems not recorded by themselves. Therefore they are not represented as channels in the data. The type of referencing for all channels and optionally the location of the reference electrode and the location of the ground electrode **MAY** be specified.

## Sidecar JSON (\*\_ieeg.json)

For consistency between studies and institutions, we encourage users to extract the values of metadata fields from the actual raw data. Whenever possible, please avoid using ad hoc wording.

Generic fields **MUST** be present:

Key name	Requirement level	Data type	Description
TaskName	REQUIRED	string	Name of the task. No two tasks should have the same name. The task label included in the file name is derived from this TaskName field by removing all non-alphanumeric ([a-zA-Z0-9]) characters. For example, TaskName <b>faces n-back</b> will correspond to task label <b>facesnback</b> . A RECOMMENDED convention is to name resting state task using labels beginning with <b>rest</b> .

Note that the **TaskName** field does not have to be a "behavioral task" that subjects perform, but can reflect some information about the conditions present when the data was acquired (for example, "rest", "sleep", or "seizure").

**SHOULD** be present: For consistency between studies and institutions, we encourage users to extract the values of these fields from the actual raw data. Whenever possible, please avoid using ad hoc wording.

Key name	Requirement level	Data type	Description
InstitutionName	RECOMMENDED	string	The name of the institution in charge of the equipment that produced the composite instances.
InstitutionAddress	RECOMMENDED	string	The address of the institution in charge of the equipment that produced the composite instances.
Manufacturer	RECOMMENDED	string	Manufacturer of the amplifier system (for example, "TDT, Blackrock").
ManufacturersModelName	RECOMMENDED	string	Manufacturer's designation of the iEEG amplifier model.

Key name	Requirement level	Data type	Description
SoftwareVersions	RECOMMENDED	string	Manufacturer's designation of the acquisition software.
TaskDescription	RECOMMENDED	string	Longer description of the task.
Instructions	RECOMMENDED	string	Text of the instructions given to participants before the recording. This is especially important in context of resting state and distinguishing between eyes open and eyes closed paradigms.
CogAtlasID	RECOMMENDED	string	URI of the corresponding Cognitive Atlas Task term.
CogPOID	RECOMMENDED	string	URI of the corresponding CogPO term.
DeviceSerialNumber	RECOMMENDED	string	The serial number of the equipment that produced the composite instances. A pseudonym can also be used to prevent the equipment from being identifiable, as long as each pseudonym is unique within the dataset.

Specific iEEG fields MUST be present:

Key name	Requirement level	Data type	Description
iEEGReference	REQUIRED	string	General description of the reference scheme used and (when applicable) of location of the reference electrode in the raw recordings (for example, "left mastoid", "bipolar", "T01" for electrode with name T01, "intracranial electrode on top of a grid, not included with data", "upside down electrode"). If different channels have a different reference, this field should have a general description and the channel specific reference should be defined in the channels.tsv file.
SamplingFrequency	REQUIRED	number	Sampling frequency (in Hz) of all the iEEG channels in the recording (for example, 2400). All other channels should have frequency specified as well in the channels.tsv file.
PowerLineFrequency	REQUIRED	number or "n/a"	Frequency (in Hz) of the power grid where the iEEG recording was done (for example, 50 or 60).
SoftwareFilters	REQUIRED	object of objects or "n/a"	Temporal software filters applied, or "n/a" if the data is not available. Each key:value pair in the JSON object is a name of the filter and an object in which its parameters are defined as key:value pairs. For example, {"HighPass": {"HalfAmplitudeCutOffHz": 1, "RollOff": "6dB/Octave"}}}

Specific iEEG fields SHOULD be present:



Key name	Requirement level	Data type	Description
DCOffsetCorrection	RECOMMENDED	string	A description of the method (if any) used to correct for a DC offset. If the method used was subtracting the mean value for each channel, use "mean".
HardwareFilters	RECOMMENDED	object of objects or "n/a"	Object of temporal hardware filters applied, or "n/a" if the data is not available. Each key:value pair in the JSON object is a name of the filter and an object in which its parameters are defined as key:value pairs. For example, {"Highpass RC filter": {"Half amplitude cutoff (Hz)": 0.0159, "Roll-off": "6dB/Octave"}}}
ElectrodeManufacturer	RECOMMENDED	string	Can be used if all electrodes are of the same manufacturer (for example, AD-TECH, DIXI). If electrodes of different manufacturers are used, please use the corresponding table in the _electrodes.tsv file.
ElectrodeManufacturersModelName	RECOMMENDED	string	If different electrode types are used, please use the corresponding table in the _electrodes.tsv file.
ECOGChannelCount	RECOMMENDED	integer	Number of iEEG surface channels included in the recording (for example, 120).
SEEGChannelCount	RECOMMENDED	integer	Number of iEEG depth channels included in the recording (for example, 8).
EEGChannelCount	RECOMMENDED	integer	Number of scalp EEG channels recorded simultaneously (for example, 21).
EOGChannelCount	RECOMMENDED	integer	Number of EOG channels.
ECGChannelCount	RECOMMENDED	integer	Number of ECG channels.
EMGChannelCount	RECOMMENDED	integer	Number of EMG channels.
MiscChannelCount	RECOMMENDED	integer	Number of miscellaneous analog channels for auxiliary signals.

Key name	Requirement level	Data type	Description
TriggerChannelCount	RECOMMENDED	integer	Number of channels for digital (TTL bit level) triggers.
RecordingDuration	RECOMMENDED	number	Length of the recording in seconds (for example, 3600).
RecordingType	RECOMMENDED	string	Defines whether the recording is "continuous", "discontinuous" or "epoched", where "epoched" is limited to time windows about events of interest (for example, stimulus presentations or subject responses)
EpochLength	RECOMMENDED	number	Duration of individual epochs in seconds (for example, 1) in case of epoched data. If recording was continuous or discontinuous, leave out the field.
iEEGGround	RECOMMENDED	string	Description of the location of the ground electrode ("placed on right mastoid (M2)").
iEEGPlacementScheme	RECOMMENDED	string	Freeform description of the placement of the iEEG electrodes. Left/right/bilateral/depth/surface (for example, "left frontal grid and bilateral hippocampal depth" or "surface strip and STN depth" or "clinical indication bitemporal, bilateral temporal strips and left grid").
iEEGElectrodeGroups	RECOMMENDED	string	Field to describe the way electrodes are grouped into strips, grids or depth probes for example, {'grid1': "10x8 grid on left temporal pole", 'strip2': "1x8 electrode strip on xxx"}.

Key name	Requirement level	Data type	Description
SubjectArtefactDescription	RECOMMENDED	string	Freeform description of the observed subject artefact and its possible cause (for example, "door open", "nurse walked into room at 2 min", "seizure at 10 min"). If this field is left empty, it will be interpreted as absence of artifacts.

Specific iEEG fields MAY be present:

Key name	Requirement level	Data type	Description
ElectricalStimulation	OPTIONAL	boolean	Boolean field to specify if electrical stimulation was done during the recording (options are "true" or "false"). Parameters for event-like stimulation should be specified in the events.tsv file (see example below).
ElectricalStimulationParameters	OPTIONAL	string	Free form description of stimulation parameters, such as frequency or shape. Specific onsets can be specified in the events.tsv file. Specific shapes can be described here in freeform text.

Example:

```

1 {
2   "TaskName": "visual",
3   "InstitutionName": "Stanford Hospital and Clinics",
4   "InstitutionAddress": "300 Pasteur Dr, Stanford, CA 94305",
5   "Manufacturer": "Tucker Davis Technologies",
6   "ManufacturersModelName": "n/a",
7   "TaskDescription": "visual gratings and noise patterns",
8   "Instructions": "look at the dot in the center of the screen and press the button when it changes color",
9   "iEEGReference": "left mastoid",
10  "SamplingFrequency": 1000,
11  "PowerLineFrequency": 60,

```

```
12 "SoftwareFilters":"n/a",
13 "DCOffsetCorrection":0,
14 "HardwareFilters":{"Highpass RC filter": {"Half amplitude cutoff (Hz)": 0.0159, "Roll-off": "6dB0ctave"}}},
15 "ElectrodeManufacturer":"AdTech",
16 "ECOGChannelCount":120,
17 "SEEGChannelCount":0,
18 "EEGChannelCount":0,
19 "EOGChannelCount":0,
20 "ECGChannelCount":0,
21 "EMGChannelCount":0,
22 "MiscChannelCount":0,
23 "TriggerChannelCount":0,
24 "RecordingDuration":233.639,
25 "RecordingType":"continuous",
26 "iEEGGround":"placed on the right mastoid",
27 "iEEGPlacementScheme":"right occipital temporal surface",
28 "ElectricalStimulation":false
29 }
```

Note that the date and time information SHOULD be stored in the Study key file (`scans.tsv`). Date time information MUST be expressed as indicated in Units

### Channels description (`*_channels.tsv`)

Template:

```
1 sub-<label>/
2   [ses-<label>]/
3   ieeg/
4   [sub-<label>[_ses-<label>]_task-<label>[_run-<index>]_channels.tsv]
```

A channel represents one time series recorded with the recording system (for example, there can be a bipolar channel, recorded from two electrodes or contact points on the tissue). Although this information can often be extracted from the iEEG recording, listing it in a simple `.tsv` document makes it easy to browse or search (for example, searching for recordings with a sampling frequency of  $\geq 1000$  Hz). Hence, the `channels.tsv` is RECOMMENDED. The two required columns are channel **name** and **type**. Channels SHOULD appear in the table in the same order they do in the iEEG data file. Any number of additional columns may be provided to provide additional information about the channels. Note that electrode positions SHOULD NOT be added to this file but to `*_electrodes.tsv`.

The columns of the Channels description table stored in `*_channels.tsv` are:

MUST be present:

Column name	Requirement level	Description
name	REQUIRED	Label of the channel. The label must correspond to <code>_electrodes.tsv</code> name and all ieeg type channels are required to have a position. The reference channel name MAY be provided in the reference column.
type	REQUIRED	Type of channel, see below for adequate keywords in this field. Note that the type MUST be in upper case.
units	REQUIRED	Physical unit of the value represented in this channel, for example, V for Volt, or fT/cm for femto Tesla per centimeter (see Units).
low_cutoff	REQUIRED	Frequencies used for the low pass filter applied to the channel in Hz. If no low pass filter was applied, use n/a. Note that anti-alias is a low pass filter, specify its frequencies here if applicable.
high_cutoff	REQUIRED	Frequencies used for the high pass filter applied to the channel in Hz. If no high pass filter applied, use n/a.

SHOULD be present:

Column name	Requirement level	Description
reference	OPTIONAL	Specification of the reference (for example, 'mastoid', 'ElectrodeName01', 'intracranial', 'CAR', 'other', 'n/a'). If the channel is not an electrode channel (for example, a microphone channel) use n/a.
group	OPTIONAL	Which group of channels (grid/strip/seeg/depth) this channel belongs to. This is relevant because one group has one cable-bundle and noise can be shared. This can be a name or number. Note that any groups specified in <code>_electrodes.tsv</code> must match those present here.
sampling_frequency	OPTIONAL	Sampling rate of the channel in Hz.
description	OPTIONAL	Brief free-text description of the channel, or other information of interest (for example, position (for example, "left lateral temporal surface")).
notch	OPTIONAL	Frequencies used for the notch filter applied to the channel, in Hz. If no notch filter applied, use n/a.

Column name	Requirement level	Description
status	OPTIONAL	Data quality observed on the channel (good/bad). A channel is considered bad if its data quality is compromised by excessive noise. Description of noise type SHOULD be provided in [status_description].
status_description	OPTIONAL	Freeform text description of noise or artifact affecting data quality on the channel. It is meant to explain why the channel was declared bad in [status].

Example sub-01\_channels.tsv:

```

1 name  type  units  low_cutoff  high_cutoff  status  status_description
2 LT01  ECG    uV      300         0.11        good    n/a
3 LT02  ECG    uV      300         0.11        bad     broken
4 H01   SEEG   uV      300         0.11        bad     line_noise
5 ECG1  ECG    uV      n/a         0.11        good    n/a
6 TR1   TRIG   n/a     n/a         n/a         good    n/a

```

Restricted keyword list for field type in alphabetic order (shared with the MEG and EEG modality; however, only types that are common in iEEG data are listed here). Note that upper-case is REQUIRED:

Keyword	Description
EEG	Electrode channel from electroencephalogram
ECOG	Electrode channel from electrocorticogram (intracranial)
SEEG	Electrode channel from stereo-electroencephalogram (intracranial)
DBS	Electrode channel from deep brain stimulation electrode (intracranial)
VEOG	Vertical EOG (electrooculogram)
HEOG	Horizontal EOG
EOG	Generic EOG channel if HEOG or VEOG information not available
ECG	ElectroCardioGram (heart)
EMG	ElectroMyoGram (muscle)
TRIG	System Triggers
AUDIO	Audio signal
PD	Photodiode
EYEGAZE	Eye Tracker gaze
PUPIL	Eye Tracker pupil diameter
MISC	Miscellaneous

Keyword	Description
SYSCLOCK	System time showing elapsed time since trial started
ADC	Analog to Digital input
DAC	Digital to Analog output
REF	Reference channel
OTHER	Any other type of channel

Example of free-form text for field **description**:

- intracranial, stimulus, response, vertical EOG, skin conductance

### Electrode description (**\*\_electrodes.tsv**)

Template:

```

1 sub-<label>/
2   [ses-<label>]/
3     ieeg/
4       sub-<label>[_ses-<label>][_space-<label>]_electrodes.tsv

```

File that gives the location, size and other properties of iEEG electrodes. Note that coordinates are expected in cartesian coordinates according to the `iEEGCoordinateSystem` and `iEEGCoordinateUnits` fields in `*_coordsystem.json`. If an `*_electrodes.tsv` file is specified, a `*_coordsystem.json` file **MUST** be specified as well.

The optional `space-<label>` entity (`*[_space-<label>]_electrodes.tsv`) can be used to indicate the way in which electrode positions are interpreted. The space label needs to be taken from the list in Appendix VIII

For examples:

- `_space-MNI152Lin` (electrodes are coregistered and scaled to a specific MNI template)
- `_space-Talairach` (electrodes are coregistered and scaled to Talairach space)

When referring to the `*_electrodes.tsv` file in a certain space as defined above, the `space-<label>` of the accompanying `*_coordsystem.json` **MUST** correspond.

For example:

- `sub-01_space-Talairach_electrodes.tsv`
- `sub-01_space-Talairach_coordsystem.json`

The order of the required columns in the `*_electrodes.tsv` file **MUST** be as listed below.

**MUST** be present:

Column name	Requirement level	Description
name	REQUIRED	Name of the electrode contact point.
x	REQUIRED	X position. The positions of the center of each electrode in xyz space. Units are specified in <code>space-&lt;label&gt;_coordsystem.json</code> .
y	REQUIRED	Y position.
z	REQUIRED	Z position. If electrodes are in 2D space this should be a column of n/a values.
size	REQUIRED	Surface area of the electrode, units MUST be in $\text{mm}^2$ .

SHOULD be present:

Column name	Requirement level	Description
material	RECOMMENDED	Material of the electrodes.
manufacturer	RECOMMENDED	The manufacturer for each electrode. Can be used if electrodes were manufactured by more than one company.
group	RECOMMENDED	The group that the electrode is a part of. Note that any group specified here should match a group specified in <code>_channels.tsv</code> .
hemisphere	RECOMMENDED	The hemisphere in which the electrode is placed, one of ['L' or 'R'] (use capital).

MAY be present:

Column name	Requirement level	Description
type	OPTIONAL	Optional type of the electrode, for example, cup, ring, clip-on, wire, needle, ...
impedance	OPTIONAL	Impedance of the electrode, units MUST be in $\text{k}\Omega$ .
dimension	OPTIONAL	Size of the group (grid/strip/probe) that this electrode belongs to. Must be of form [AxB] with the smallest dimension first (for example, [1x8]).

Example:



```
1 name  x   y   z   size  manufacturer
2 LT01  19 -39 -16  2.3   Integra
3 LT02  23 -40 -19  2.3   Integra
4 H01   27 -42 -21  5     AdTech
```

### Coordinate System JSON (**\*\_coordsystem.json**)

Template:

```
1 sub-<label>/
2   [ses-<label>]/
3     ieeg/
4       sub-<label>[_ses-<label>] [_space-<label>]_coordsystem.json
```

This `_coordsystem.json` file contains the coordinate system in which electrode positions are expressed. The associated MRI, CT, X-Ray, or operative photo can also be specified.

General fields:

Key name	Requirement level	Data type	Description
IntendedFor	RECOMMENDED	string	This can be an MRI/CT or a file containing the operative photo, x-ray or drawing with path relative to the project folder. If only a surface reconstruction is available, this should point to the surface reconstruction file. Note that this file should have the same coordinate system specified in <code>iEEGCoordinateSystem</code> . For example, T1: <code>sub-&lt;label&gt;/ses-&lt;label&gt;/anat/sub-01_T1w.nii.gz</code> Surface: <code>/derivatives/surfaces/sub-&lt;label&gt;/ses-&lt;label&gt;/anat/sub-01_T1w_pial.R.surf.gii</code> Operative photo: <code>/sub-&lt;label&gt;/ses-&lt;label&gt;/ieeg/sub-0001_ses-01_acq-photo1_photo.jpg</code> Talairach: <code>/derivatives/surfaces/sub-Talairach/ses-01/anat/sub-Talairach_T1w_pial.R.surf.gii</code>

Fields relating to the iEEG electrode positions:

Key name	Requirement level	Data type	Description
iEEGCoordinateSystem	REQUIRED	string	Defines the coordinate system for the iEEG sensors. See Appendix VIII for a list of restricted keywords for coordinate systems. If <code>Other</code> , provide definition of the coordinate system in <code>iEEGCoordinateSystemDescription</code> . If positions correspond to pixel indices in a 2D image (of either a volume-rendering, surface-rendering, operative photo, or operative drawing), this must be "Pixels". For more information, see the section on 2D coordinate systems
iEEGCoordinateUnits	REQUIRED	string	Units of the <code>_electrodes.tsv</code> , MUST be "m", "mm", "cm" or "pixels".
iEEGCoordinateSystemDescription	RECOMMENDED, but REQUIRED if iEEGCoordinateSystem is <code>Other</code>	string	Free-form text description of the coordinate system. May also include a link to a documentation page or paper describing the system in greater detail.
iEEGCoordinateProcessingDescription	RECOMMENDED	string	Has any post-processing (such as projection) been done on the electrode positions (for example, "surface_projection", "none").
iEEGCoordinateProcessingReference	RECOMMENDED	string	A reference to a paper that defines in more detail the method used to localize the electrodes and to post-process the electrode positions. .

### Recommended 3D coordinate systems

It is preferred that electrodes are localized in a 3D coordinate system (with respect to a pre- and/or post-operative anatomical MRI or CT scans or in a standard space as specified in BIDS Appendix VIII about preferred names of coordinate systems, such as ACPC).

### Allowed 2D coordinate systems

If electrodes are localized in 2D space (only x and y are specified and z is n/a), then the positions in this file must correspond to the locations expressed in pixels on the photo/drawing/rendering of the electrodes on the brain. In this case, coordinates must be (row,column) pairs, with (0,0) corresponding to the upper left pixel and (N,0)

corresponding to the lower left pixel.

### Multiple coordinate systems

If electrode positions are known in multiple coordinate systems (for example, MRI, CT and MNI), these spaces can be distinguished by the optional `space-<label>` field, see the `*_electrodes.tsv`-section for more information. Note that the `space-<label>` fields must correspond between `*_electrodes.tsv` and `*_coordsystem.json` if they refer to the same data.

Example:

```
1 {
2   "IntendedFor": "/sub-01/ses-01/anat/sub-01_T1w.nii.gz",
3   "iEEGCoordinateSystem": "ACPC",
4   "iEEGCoordinateUnits": "mm",
5   "iEEGCoordinateSystemDescription": "Coordinate system with the origin at anterior commissure (AC), negative y-axis going through the posterior
    commissure (PC), z-axis going to a mid-hemispheric point which lies superior to the AC-PC line, x-axis going to the right",
6   "iEEGCoordinateProcessingDescription": "surface_projection",
7   "iEEGCoordinateProcessingReference": "Hermes et al., 2010 JNeuroMeth"
8 }
```

### Photos of the electrode positions (`*_photo.jpg`)

Template:

```
1 sub-<label>/
2   [ses-<label>]/
3     ieeg/
4       sub-<label>[_ses-<label>][_acq-<label>]_photo.json
```

These can include photos of the electrodes on the brain surface, photos of anatomical features or landmarks (such as sulcal structure), and fiducials. Photos can also include an X-ray picture, a flatbed scan of a schematic drawing made during surgery, or screenshots of a brain rendering with electrode positions. The photos may need to be cropped and/or blurred to conceal identifying features or entirely omitted prior to sharing, depending on obtained consent.


If there are photos of the electrodes, the `acq-<label>` entity should be specified with:

- `*_photo.jpg` in case of an operative photo
- `*_acq-xray#_photo.jpg` in case of an x-ray picture
- `*_acq-drawing#_photo.jpg` in case of a drawing or sketch of electrode placements
- `*_acq-render#_photo.jpg` in case of a rendering

The `ses-<label>` entity may be used to specify when the photo was taken.

Example of the operative photo of ECoG electrodes (here is an annotated example in which electrodes and vasculature are marked, taken from Hermes et al., JNeuroMeth 2010).


- 1 sub-0001\_ses-01\_acq-photo1\_photo.jpg
- 2 sub-0001\_ses-01\_acq-photo2\_photo.jpg



Below is an example of a volume rendering of the cortical surface with a superimposed subdural electrode implantation. This map is often provided by the EEG technician and provided to the epileptologists (for example, see Burneo JG et al.

1. doi:10.1016/j.clineuro.2014.03.020).

- 1 sub-0002\_ses-01\_acq-render\_photo.jpg



## Electrical stimulation

In case of electrical stimulation of brain tissue by passing current through the iEEG electrodes, and the electrical stimulation has an event structure (on-off, onset, duration), the `_events.tsv` file can contain the electrical stimulation parameters in addition to other events. Note that these can be intermixed with other task events. Electrical stimulation parameters can be described in columns called `electrical_stimulation_<label>`, with labels chosen by the researcher and optionally defined in more detail in an accompanying `_events.json` file (as per the main BIDS spec). Functions for complex stimulation patterns can, similar as when a video is presented, be stored in a folder in the `/stimuli/` folder. For example: `/stimuli/electrical_stimulation_functions/biphasic.tsv`

Example:

```
1 onset duration trial_type          electrical_stimulation_type electrical_stimulation_site electrical_stimulation_current
```

2	1.2	0.001	electrical_stimulation	biphasic	LT01-LT02	0.005
3	1.3	0.001	electrical_stimulation	biphasic	LT01-LT02	0.005
4	2.2	0.001	electrical_stimulation	biphasic	LT02-LT03	0.005
5	4.2	1	electrical_stimulation	complex	LT02-LT03	n/a
6	15.2	3	auditory_stimulus	n/a	n/a	n/a

## Task events

Template:

```

1 sub-<label>/[ses-<label>]
2   func/
3     <matches>_events.tsv
4     <matches>_events.json

```

Where `<matches>` corresponds to task file name. For example: `sub-control01_task-nback`. It is also possible to have a single `_events.tsv` file describing events for all participants and runs (see Inheritance Principle). As with all other tabular data, `_events.tsv` files MAY be accompanied by a JSON file describing the columns in detail (see Tabular Files).

The purpose of this file is to describe timing and other properties of events recorded during the scan. Events MAY be either stimuli presented to the participant or participant responses. A single event file MAY include any combination of stimuli and response events. Events MAY overlap in time. Please mind that this does not imply that only so called "event related" study designs are supported (in contrast to "block" designs) - each "block of events" can be represented by an individual row in the `_events.tsv` file (with a long duration). Each task events file **REQUIRES** a corresponding task imaging data file (but a single events file MAY be shared by multiple imaging data files - see Inheritance Principle). The tabular files consists of one row per event and a set of **REQUIRED** and **OPTIONAL** columns:

Column name	Requirement level	Description
onset	REQUIRED	Onset (in seconds) of the event measured from the beginning of the acquisition of the first volume in the corresponding task imaging data file. If any acquired scans have been discarded before forming the imaging data file, ensure that a time of 0 corresponds to the first image stored. In other words negative numbers in "onset" are allowed.
duration	REQUIRED	Duration of the event (measured from onset) in seconds. Must always be either zero or positive. A "duration" value of zero implies that the delta function or event is so short as to be effectively modeled as an impulse.

Column name	Requirement level	Description
sample	OPTIONAL	Onset of the event according to the sampling scheme of the recorded modality (that is, referring to the raw data file that the <code>events.tsv</code> file accompanies).
trial_type	OPTIONAL	Primary categorisation of each trial to identify them as instances of the experimental conditions. For example: for a response inhibition task, it could take on values "go" and "no-go" to refer to response initiation and response inhibition experimental conditions.
response_time	OPTIONAL	Response time measured in seconds. A negative response time can be used to represent preemptive responses and "n/a" denotes a missed response.
stim_file	OPTIONAL	Represents the location of the stimulus file (such as an image, video, or audio file) presented at the given onset time. There are no restrictions on the file formats of the stimuli files, but they should be stored in the /stimuli folder (under the root folder of the dataset; with optional subfolders). The values under the stim_file column correspond to a path relative to "/stimuli". For example "images/cat03.jpg" will be translated to "/stimuli/images/cat03.jpg".
value	OPTIONAL	Marker value associated with the event (for example, the value of a TTL trigger that was recorded at the onset of the event).
HED	OPTIONAL	Hierarchical Event Descriptor (HED) Tag. See Appendix III for details.

5 For example in case there is an in scanner training phase that begins before the scanning sequence has started events from this sequence should have negative onset time counting down to the beginning of the acquisition of the first volume.

An arbitrary number of additional columns can be added. Those allow describing other properties of events that could be later referred in modelling and hypothesis extensions of BIDS. Note that the `trial_type` and any additional columns in a TSV file SHOULD be documented in an accompanying JSON sidecar file.

Example:

```

1 sub-control01/
2   func/
3     sub-control01_task-stopsignal_events.tsv

```



```
4 sub-control01_task-stopsignal_events.json
```

Example of the content of the TSV file:

```
1 onset duration trial_type response_time stim_file
2 1.2 0.6 go 1.435 images/red_square.jpg
3 5.6 0.6 stop 1.739 images/blue_square.jpg
```

In the accompanying JSON sidecar, the `trial_type` column might look as follows:

```
1 {
2   "trial_type": {
3     "LongName": "Event category",
4     "Description": "Indicator of type of action that is expected",
5     "Levels": {
6       "go": "A red square is displayed to indicate starting",
7       "stop": "A blue square is displayed to indicate stopping",
8     }
9   }
10 }
```

Note that all other columns SHOULD also be described but are omitted for the sake of brevity.

For multi-echo files, the `*_events.tsv` file is applicable to all echos of a particular run:

```
1 sub-01_task-cuedSGT_run-1_events.tsv
2 sub-01_task-cuedSGT_run-1_echo-1_bold.nii.gz
3 sub-01_task-cuedSGT_run-1_echo-2_bold.nii.gz
4 sub-01_task-cuedSGT_run-1_echo-3_bold.nii.gz
```

## Stimuli databases

References to existing databases can also be encoded using additional columns. The following example includes references to the Karolinska Directed Emotional Faces (KDEF) database.

Example:

```
1 sub-control01/
2   func/
3     sub-control01_task-emoface_events.tsv
4     sub-control01_task-emoface_events.json
```

Example of the content of the TSV file:

```
1 onset duration trial_type identifier database response_time
2 1.2 0.6 afraid AF01AFAF kdef 1.435
3 5.6 0.6 angry AM01AFAN kdef 1.739
4 5.6 0.6 sad AF01ANSA kdef 1.739
```

The trial\_type and identifier columns from the \*\_events.tsv files might be described in the accompanying JSON sidecar as follows:

```
1 {
2   "trial_type": {
3     "LongName": "Emotion image type",
4     "Description": "Type of emotional face from Karolinska database that is displayed",
5     "Levels": {
6       "afraid": "A face showing fear is displayed",
7       "angry": "A face showing anger is displayed",
8       "sad": "A face showing sadness is displayed"
9     }
10  },
11  "identifier": {
12    "LongName": "Karolinska (KDEF) database identifier",
13    "Description": "ID from KDEF database used to identify the displayed image"
14  }
15 }
```

Note that all other columns SHOULD also be described but are omitted for the sake of brevity.

Stimulus presentation details

It is RECOMMENDED to include details of the stimulus presentation software, when applicable:

Key name	Requirement level	Data type	Description
StimulusPresentation	RECOMMENDED	object of strings	Object containing key value pairs related to the software used to present the stimuli during the experiment, specifically: <code>OperatingSystem</code> , <code>SoftwareName</code> , <code>SoftwareRRID</code> , <code>SoftwareVersion</code> and <code>Code</code> . See table below for more information.

The object supplied for StimulusPresentation SHOULD include the following key-value pairs:

Key name	Requirement level	Data type	Description
OperatingSystem	RECOMMENDED	string	Operating system used to run the stimuli presentation software (for formatting recommendations, see examples below this table).
SoftwareName	RECOMMENDED	string	Name of the software that was used to present the stimuli.
SoftwareRRID	RECOMMENDED	string	Research Resource Identifier of the software that was used to present the stimuli. Examples: The RRID for Psychtoolbox is 'SCR_002881', and that of PsychoPy is 'SCR_006571'.
SoftwareVersion	RECOMMENDED	string	Version of the software that was used to present the stimuli.
Code	RECOMMENDED	string	URI of the code used to present the stimuli. Persistent identifiers such as DOIs are preferred. If multiple versions of code may be hosted at the same location, revision-specific URIs are recommended.

The operating system description SHOULD include the following attributes:

- type (for example, Windows, macOS, Linux)
- distribution (if applicable, for example, Ubuntu, Debian, CentOS)
- the version number (for example, 18.04.5)

Examples:

- Windows 10, Version 2004
- macOS 10.15.6
- Linux Ubuntu 18.04.5

The amount of information supplied for the `OperatingSystem` SHOULD be sufficient to re-run the code under maximally similar conditions.

The information related to stimulus presentation might be described in the accompanying JSON sidecar as follows (based on the example of the previous section):

```

1 {
2   "trial_type": {
3     "LongName": "Emotion image type",
4     "Descripton": "Type of emotional face from Karolinska database that is displayed",
5     "Levels": {

```

```
6         "afraid": "A face showing fear is displayed",
7         "angry":  "A face showing anger is displayed",
8         "sad":    "A face showing sadness is displayed"
9     }
10 },
11 "identifier": {
12     "LongName": "Unique identifier from Karolinska (KDEF) database",
13     "Description": "ID from KDEF database used to identify the displayed image"
14 },
15 "StimulusPresentation": {
16     "OperatingSystem": "Linux Ubuntu 18.04.5",
17     "SoftwareName": "Psychtoolbox",
18     "SoftwareRRID": "SCR_002881",
19     "SoftwareVersion": "3.0.14",
20     "Code": "doi:10.5281/zenodo.3361717"
21 }
22 }
```

Note: Events can also be documented in machine-actionable form using HED (Hierarchical Event Descriptor) tags. This type of documentation is particularly useful for datasets likely to be used in event-related analyses. See [Hierarchical Event Descriptors](#) for additional information and examples.

## Physiological and other continuous recordings

Template:

```
1 sub-<label>/[ses-<label>/]
2   <datatype>/
3     <matches>[_recording-<label>]_physio.tsv.gz
4     <matches>[_recording-<label>]_physio.json
5     <matches>[_recording-<label>]_stim.tsv.gz
6     <matches>[_recording-<label>]_stim.json
```

Optional: Yes

For the template directory name, <datatype> can correspond to any data recording modality, for example `func`, `anat`, `dwi`, `meg`, `eeg`, `ieeg`, or `beh`.

In the template file names, the <matches> part corresponds to task file name before the suffix. For example for the file `sub-control01_task-nback_run-1_bold.nii.gz`, <matches> would correspond to `sub-control01_task-nback_run-1`.

The `recording-<label>` entity can be used to distinguish between several recording files. For example `sub-01_task-bart_recording-eyetracking_physio.tsv.gz` to contain the eyetracking data in a certain sampling frequency, and `sub-01_task-bart_recording-breathing_physio.tsv.gz` to contain respiratory measurements in a different sampling frequency.

Physiological recordings (including eyetracking) SHOULD use the `_physio` suffix, and signals related to the stimulus SHOULD use `_stim` suffix.

Physiological recordings such as cardiac and respiratory signals and other continuous measures (such as parameters of a film or audio stimuli) can be specified using two files: a gzip compressed TSV file with data (without header line) and a JSON for storing the following metadata fields:

Note that when supplying a `*_<physio|stim>.tsv.gz` file, an accompanying `*_<physio|stim>.json` MUST be supplied as well.

Key name	Requirement level	Data type	Description
SamplingFrequency	REQUIRED	number	Sampling frequency in Hz of all columns in the file.
StartTime	REQUIRED	number	Start time in seconds in relation to the start of acquisition of the first data sample in the corresponding neural dataset (negative values are allowed).
Columns	REQUIRED	array of strings	Names of columns in file.

Additional metadata may be included as in any TSV file to specify, for example, the units of the recorded time series. Please note that, in contrast to other TSV files in BIDS, the TSV files specified for physiological and other continuous recordings do not include a header line. Instead the name of columns are specified in the JSON file. This is to improve compatibility with existing software (for example, FSL, PNM) as well as to make support for other file formats possible in the future.

Example `*_physio.tsv.gz`:

```
1 sub-control01/
2   func/
3     sub-control01_task-nback_physio.tsv.gz
```

(after decompression)

```
1 34    110    0
2 44    112    0
3 23    100    1
```

Example `*_physio.json`:

```
1 sub-control01/
2   func/
3     sub-control01_task-nback_physio.json
```

```
1 {
2   "SamplingFrequency": 100.0,
3   "StartTime": -22.345,
```

```

4  "Columns": ["cardiac", "respiratory", "trigger"],
5  "cardiac": {
6      "Units": "mV"
7  }
8 }

```

## Recommendations for specific use cases

To store pulse or breathing measurements, or the scanner trigger signal, the following naming conventions SHOULD be used for the column names:

Column name	Description
cardiac	continuous pulse measurement
respiratory	continuous breathing measurement
trigger	continuous measurement of the scanner trigger signal

For any other data to be specified in columns, the column names can be chosen as deemed appropriate by the researcher.

Recordings with different sampling frequencies and/or starting times should be stored in separate files.

If the same continuous recording has been used for all subjects (for example in the case where they all watched the same movie), one file MAY be used and placed in the root directory. For example, `task-movie_stim.tsv.gz`

For motion parameters acquired from MRI scanner side motion correction, the `_physio` suffix SHOULD be used.

For multi-echo data, a given `physio.tsv` file is applicable to all echos of a particular run. For example:

```

1 sub-01_task-cuedSGT_run-1_physio.tsv.gz
2 sub-01_task-cuedSGT_run-1_echo-1_bold.nii.gz
3 sub-01_task-cuedSGT_run-1_echo-2_bold.nii.gz
4 sub-01_task-cuedSGT_run-1_echo-3_bold.nii.gz

```

## Behavioral experiments (with no neural recordings)

Template:

```

1 sub-<label>/[ses-<label>/]
2   beh/
3     sub-<label>[_ses-<label>]_task-<label>[_acq-<label>][_run-<index>]_events.tsv
4     sub-<label>[_ses-<label>]_task-<label>[_acq-<label>][_run-<index>]_events.json
5     sub-<label>[_ses-<label>]_task-<label>[_acq-<label>][_run-<index>]_beh.tsv

```

```

6      sub-<label>[_ses-<label>]_task-<label>[_acq-<label>][_run-<index>]_beh.json
7      sub-<label>[_ses-<label>]_task-<label>[_acq-<label>][_run-<index>][_recording-<label>]_physio.tsv.gz
8      sub-<label>[_ses-<label>]_task-<label>[_acq-<label>][_run-<index>][_recording-<label>]_physio.json
9      sub-<label>[_ses-<label>]_task-<label>[_acq-<label>][_run-<index>][_recording-<label>]_stim.tsv.gz
10     sub-<label>[_ses-<label>]_task-<label>[_acq-<label>][_run-<index>][_recording-<label>]_stim.json

```

In addition to logs from behavioral experiments performed alongside imaging data acquisitions, one can also include data from experiments performed with no neural recordings. The results of those experiments can be stored in the `beh` folder using the same formats for event timing (`_events.tsv`), metadata (`_events.json`), physiological (`_physio.tsv.gz`, `_physio.json`) and other continuous recordings (`_stim.tsv.gz`, `_stim.json`) as for tasks performed during MRI, electrophysiological or other neural recordings. Additionally, events files that do not include the mandatory `onset` and `duration` columns can still be included, but should be labeled `_beh.tsv` rather than `_events.tsv`.

The OPTIONAL `acq-<label>` key/value pair corresponds to a custom label to distinguish different conditions present during multiple runs of the same task. For example, if a study includes runs of an n-back task, with deep brain stimulation turned on or off, the data files may be labelled `sub-01_task-nback_acq-dbson_beh.tsv` and `sub-01_task-nback_acq-dbsoff_beh.tsv`.

## Genetic Descriptor

Support genetic descriptors was developed as a BIDS Extension Proposal. Please see Citing BIDS on how to appropriately credit this extension when referring to it in the context of the academic literature.

Genetic data are typically stored in dedicated repositories, separate from imaging data. A genetic descriptor links a BIDS dataset to associated genetic data, potentially in a separate repository, with details of where to find the genetic data and the type of data available.

## Dataset Description

Genetic descriptors are encoded as an additional, OPTIONAL entry in the `dataset_description.json` file.

Datasets linked to a genetic database entry include the following REQUIRED or OPTIONAL `dataset_description.json` keys (a dot in the key name denotes a key in a sub-object, see the example further below):

Key name	Requirement level	Data type	Description
Genetics.Dataset	REQUIRED	string	URI where data can be retrieved.
Genetics.Database	OPTIONAL	string	URI of database where the dataset is hosted.
Genetics.Descriptors	OPTIONAL	string or array of strings	List of relevant descriptors (for example, journal articles) for dataset using a valid URI when possible.

Example:

```
1 {
2   "Name": "Human Connectome Project",
3   "BIDSVersion": "1.3.0",
4   "License": "CC0",
5   "Authors": ["1st author", "2nd author"],
6   "Funding": ["P41 EB015894/EB/NIBIB NIH HHS/United States"],
7   "Genetics": {
8     "Dataset": "https://www.ncbi.nlm.nih.gov/projects/gap/cgi-bin/study.cgi?study_id=phs001364.v1.p1",
9     "Database": "https://www.ncbi.nlm.nih.gov/gap/",
10    "Descriptors": ["doi:10.1016/j.neuroimage.2013.05.041"]
11  }
12 }
```

## Subject naming and Participants file

If the same participants have different identifiers in the genetic and imaging datasets, the column `genetic_id` SHOULD be added to the `participants.tsv` file to associate the BIDS participant with a subject in the `Genetics.Dataset` referred to in the `dataset_description.json` file.

Information about the presence/absence of specific genetic markers MAY be duplicated in the `participants.tsv` file by adding optional columns (like `idh_mutation` in the example below). Note that optional columns MUST be further described in an accompanying `participants.json` file as described in Tabular files.

`participants.tsv` example:

1	participant_id	age	sex	group	genetic_id	idh_mutation
2	sub-control01	34	M	control	124587	yes
3	sub-control02	12	F	control	548936	yes
4	sub-patient01	33	F	patient	489634	no

## Genetic Information

Template:

```
1 genetic_info.json
```

The `genetic_info.json` file describes the genetic information available in the `participants.tsv` file and/or the genetic database described in `dataset_description.json`. Datasets containing the `Genetics` field in `dataset_description.json` or the `genetic_id` column in `participants.tsv` MUST include this file with the following fields:



Key name	Requirement level	Data type	Description
GeneticLevel	REQUIRED	string or array of strings	Describes the level of analysis. Values MUST be one of <b>Genetic</b> , <b>Genomic</b> , <b>Epigenomic</b> , <b>Transcriptomic</b> , <b>Metabolomic</b> , or <b>Proteomic</b> .
AnalyticalApproach	OPTIONAL	string or array of strings	Methodology or methodologies used to analyse the GeneticLevel. Values MUST be taken from the database of Genotypes and Phenotypes (dbGaP) under /Study/Molecular Data Type (for example, <b>SNP Genotypes (Array)</b> or <b>Methylation (CpG)</b> .
SampleOrigin	REQUIRED	string	Describes from which tissue the genetic information was extracted. Values MUST be one of <b>blood</b> , <b>saliva</b> , <b>brain</b> , <b>csf</b> , <b>breast milk</b> , <b>bile</b> , <b>amniotic fluid</b> , <b>other biospecimen</b> .
TissueOrigin	OPTIONAL	string	Describes the type of tissue analyzed for SampleOrigin brain. Values MUST be one of <b>gray matter</b> , <b>white matter</b> , <b>csf</b> , <b>meninges</b> , <b>macrovascular</b> or <b>microvascular</b> .
BrainLocation	OPTIONAL	string	Refers to the location in space of the TissueOrigin. Values may be an MNI coordinate, a label taken from the Allen Brain Atlas, or layer to refer to layer-specific gene expression, which can also tie up with laminar fMRI.
CellType	OPTIONAL	string	Describes the type of cell analyzed. Values SHOULD come from the cell ontology.

To ensure dataset description consistency, we recommend following Multi-omics approaches to disease by Hasin et al. 2017 to determine the GeneticLevel:

- **Genetic**: data report on a single genetic location (typically directly in the `participants.tsv` file)
- **Genomic**: data link to participants' genome (multiple genetic locations)

- **Epigenomic:** data link to participants' characterization of reversible modifications of DNA
- **Transcriptomic:** data link to participants RNA levels
- **Metabolomic:** data link to participants' products of cellular metabolic functions
- **Proteomic:** data link to participants peptides and proteins quantification

genetic\_info.json example:

```
1 {  
2   "GeneticLevel": "Genomic",  
3   "AnalyticalApproach": ["Whole Genome Sequencing", "SNP/CNV Genotypes"],  
4   "SampleOrigin": "brain",  
5   "TissueOrigin": "gray matter",  
6   "CellType": "neuron",  
7   "BrainLocation": "[-30 -15 10]"  
8 }
```

## BIDS Derivatives

Derivatives are outputs of common processing pipelines, capturing data and meta-data sufficient for a researcher to understand and (critically) reuse those outputs in subsequent processing. Standardizing derivatives is motivated by use cases where formalized machine-readable access to processed data enables higher level processing.

The following sections cover additions to and divergences from "raw" BIDS. Placement and naming conventions for derived datasets are addressed in Storage of derived datasets, and dataset-level metadata is included in Derived dataset and pipeline description.

### Metadata conventions

- Unless specified otherwise, individual sidecar JSON files and all metadata fields within are **OPTIONAL**. However, the appropriate use of these files and pertinent fields is very valuable and thus encouraged. Moreover, for some types of files, there may be one or more required metadata fields, in which case at least one metadata file containing that field must be located somewhere within the file's hierarchy (per the Inheritance Principle).
- When chaining derivative pipelines, any JSON fields that were specified as mandatory in the input files **SHOULD** be propagated forward in the output file's JSON provided they remain valid. Non-required JSON fields **MAY** be propagated, and are highly useful, but it is the pipeline's responsibility to ensure that the values are still relevant and appropriate to the type of output data.

### File naming conventions

- Filenames that are permissible for a raw BIDS data type have a privileged status. Any modification of raw files must use a modified filename that does not conflict with the raw filename. Further, any files created as part of a derivative dataset must not match a permissible filename of a valid raw dataset. Stated equivalently, if any filename in a derivative dataset has a name permissible for a raw BIDS data, then that file must be an identical copy of that raw file.
- Each Derivatives filename **MUST** be of the form: `<source_entities>[_keyword-<value>]_<suffix>.<ext>` (where `<value>` could either be an `<index>` or a `<label>` depending on the keyword; see Definitions)

- When the derivatives chain involves outputs derived from a single raw input, `source_entities` MUST be the entire source filename, with the omission of the source suffix and extension. One exception to this rule is filename entities that are no longer relevant. Depending on the nature of the derivative file, the suffix can either be the same as the source file if that suffix is still appropriate, or a new appropriate value selected from the controlled list.
- There is no prohibition against identical filenames in different derived datasets, although users should be aware of the potential ambiguity this can create and use the sidecar JSON files to detail the specifics of individual files.
- When necessary to distinguish two files that do not otherwise have a distinguishing entity, the `_desc-<label>` keyword-value SHOULD be used. This includes the cases of needing to distinguish both differing inputs and differing outputs (for example, `_desc-T1w` and `_desc-T2w` to distinguish brain mask files derived from T1w and T2w images; or `_desc-sm4` and `_desc-sm8` to distinguish between outputs generated with two different levels of smoothing).
- When naming files that are not yet standardized, it is RECOMMENDED to use names consistent with BIDS conventions where those conventions apply. For example, if a summary statistic is derived from a given task, the file name SHOULD contain `_task-<label>`.

## Common data types and metadata

### Common file level metadata fields

Each derivative data file SHOULD be described by a JSON file provided as a sidecar or higher up in the hierarchy of the derived dataset (according to the Inheritance Principle) unless a particular derivative includes REQUIRED metadata fields, in which case a JSON file is also REQUIRED. Each derivative type defines their own set of fields, but all of them share the following (non-required) ones:

Key name	Requirement level	Data type	Description
Description	RECOMMENDED	string	Free-form natural language description of the nature of the file.
Sources	OPTIONAL	array of strings	A list of files with the paths specified relative to dataset root; these files were directly used in the creation of this derivative data file. For example, if a derivative A is used in the creation of another derivative B, which is in turn used to generate C in a chain of A->B->C, C should only list B in <code>Sources</code> , and B should only list A in <code>Sources</code> . However, in case both X and Y are directly used in the creation of Z, then Z should list X and Y in <code>Sources</code> , regardless of whether X was used to generate Y.

Key name	Requirement level	Data type	Description
RawSources	OPTIONAL	array of strings	A list of paths relative to dataset root pointing to the BIDS-Raw file(s) that were used in the creation of this derivative.

### Examples

Preprocessed bold NIfTI file in the original coordinate space of the original run. The location of the file in the original datasets is encoded in the `RawSources` metadata, and `desc-<label>` is used to prevent clashing with the original file name.

```
1 sub-01/func/sub-01_task-rest_desc-preproc_bold.nii.gz
2 sub-01/func/sub-01_task-rest_desc-preproc_bold.json
```

```
1 {
2   "RawSources": ["sub-01/func/sub-01_task-rest_bold.nii.gz"]
3 }
```

If this file was generated with prior knowledge from additional sources, such as the same subject's T1w, then both files MAY be included in `RawSources`.

```
1 {
2   "RawSources": [
3     "sub-01/func/sub-01_task-rest_bold.nii.gz",
4     "sub-01/anat/sub-01_T1w.nii.gz"
5   ]
6 }
```

On the other hand, if a preprocessed version of the T1w image was used, and it also occurs in the derivatives, `Sources` and `RawSources` can both be specified.

```
1 {
2   "Sources": [
3     "sub-01/anat/sub-01_desc-preproc_T1w.nii.gz"
4   ],
5   "RawSources": [
6     "sub-01/func/sub-01_task-rest_bold.nii.gz"
7   ]
8 }
```

### Spatial references

Derivatives are often aligned to a common spatial reference to allow for the comparison of acquired data across runs, sessions, subjects or datasets. A file may indicate the spatial reference to which it has been aligned using the `space` entity and/or the `SpatialReference` metadata.

The **space** entity may take any value in Image-Based Coordinate Systems.

If the **space** entity is omitted, or the space is not in the Standard template identifiers table, then the **SpatialReference** metadata is REQUIRED.

Key name	Requirement level	Data type	Description
SpatialReference	RECOMMENDED if the derivative is aligned to a standard template listed in Standard template identifiers. REQUIRED otherwise.	string or object	For images with a single reference, the value MUST be a single string. For images with multiple references, such as surface and volume references, a JSON object MUST be used. See examples below.

SpatialReference key allowed values

Value	Description
orig	A (potentially unique) per-image space. Useful for describing the source of transforms from an input image to a target space.
URI or path	This can be used to point to a specific file. Paths are written relative to the root of the derivative dataset.

In the case of images with multiple references, an object must link the relevant structures to reference files. If a single volumetric reference is used for multiple structures, the **VolumeReference** key MAY be used to reduce duplication. For CIFTI-2 images, the relevant structures are BrainStructure values defined in the BrainModel elements found in the CIFTI-2 header.

### Examples

Preprocessed bold NIfTI file in individual coordinate space. Please mind that in this case **SpatialReference** key is REQUIRED.

```
1 sub-01/func/sub-01_task-rest_space-individual_bold.nii.gz
2 sub-01/func/sub-01_task-rest_space-individual_bold.json
```

```
1 {
2   "SpatialReference": "sub-01/anat/sub-01_desc-combined_T1w.nii.gz"
3 }
```

Preprocessed bold CIFTI-2 files that have been sampled to the fsLR surface meshes defined in the Conte69 atlas along with the MNI152NLin6Asym template. In this example, because all volumetric structures are sampled to the same reference, the **VolumeReference** key is used as a default, and only the surface references need to be specified by BrainStructure names.

```
1 sub-01/func/sub-01_task-rest_space-fsLR_den-91k_bold.dtseries.nii
2 sub-01/func/sub-01_task-rest_space-fsLR_den-91k_bold.json
```

```
1 {
2   "SpatialReference": {
3     "VolumeReference": "https://templateflow.s3.amazonaws.com/tpl-MNI152NLin6Asym_res-02_T1w.nii.gz",
4     "CIFTI_STRUCTURE_CORTEX_LEFT": "https://github.com/mgxd/brainplot/raw/master/brainplot/Conte69_Atlas/Conte69.L.midthickness.32k_fs_LR.surf.gii",
5     "CIFTI_STRUCTURE_CORTEX_RIGHT": "https://github.com/mgxd/brainplot/raw/master/brainplot/Conte69_Atlas/Conte69.R.midthickness.32k_fs_LR.surf.gii"
6   }
7 }
```

## Preprocessed or cleaned data

Template:

```
1 <pipeline_name>/
2   sub-<participant_label>/
3     <datatype>/
4       <source_entities>[_space-<space>][_desc-<label>][_suffix>].<ext>
```

Data is considered to be preprocessed or cleaned if the data type of the input, as expressed by the BIDS **suffix**, is unchanged. By contrast, processing steps that change the number of dimensions are likely to disrupt the propagation of the input's **suffix** and generally, the outcomes of such transformation cannot be considered preprocessed or cleaned data.

Examples of preprocessing:

- Motion-corrected, temporally denoised, and transformed to MNI space BOLD series
- Inhomogeneity corrected and skull stripped T1w files
- Motion-corrected DWI files
- Time-domain filtered EEG data
- MaxFilter (for example, SSS) cleaned MEG data

The **space** keyword is recommended to distinguish files with different underlying coordinate systems or registered to different reference maps. See Spatial references for details. The **desc** (description) keyword is a general purpose field with freeform values, which **SHOULD** be used to distinguish between multiple different versions of processing for the same input data.

Examples of preprocessed data:

```
1 pipeline1/
2   sub-001/
3     anat/
```

```
4         sub-001_space-MNI305_T1w.nii.gz
5         sub-001_space-MNI305_T1w.json
6     func/
7         sub-001_task-rest_run-1_space-MNI305_desc-preproc_bold.nii.gz
8         sub-001_task-rest_run-1_space-MNI305_desc-preproc_bold.json

1 pipeline2/
2     sub-001/
3         eeg/
4             sub-001_task-listening_run-1_desc-autoannotation_events.tsv
5             sub-001_task-listening_run-1_desc-autoannotation_events.json
6             sub-001_task-listening_run-1_desc-filtered_eeg.edf
7             sub-001_task-listening_run-1_desc-filtered_eeg.json
```

All REQUIRED metadata fields coming from a derivative file's source file(s) MUST be propagated to the JSON description of the derivative unless the processing makes them invalid (for example, if a source 4D image is averaged to create a single static volume, a `RepetitionTime` property would no longer be relevant).

## Imaging data types

This section pertains to imaging data, which characteristically have spatial extent and resolution.

### Preprocessed, coregistered and/or resampled volumes

Template:

```
1 <pipeline_name>/
2     sub-<participant_label>/
3         <datatype>/
4             <source_entities>[_space-<space>][_res-<label>][_den-<label>][_desc-<label>]_<suffix>.<ext>
```

Volumetric preprocessing does not modify the number of dimensions, and so the specifications in Preprocessed or cleaned data apply. The use of surface meshes and volumetric measures sampled to those meshes is sufficiently similar in practice to treat them equivalently.

When two or more instances of a given derivative are provided with resolution or surface sampling density being the only difference between them, then the `res` (for resolution of regularly sampled N-D data) and/or `den` (for density of non-parametric surfaces) SHOULD be used to avoid name conflicts. Note that only files combining both regularly sampled (for example, gridded) and surface sampled data (and their downstream derivatives) are allowed to present both `res` and `den` entities simultaneously.

Examples:

```
1 pipeline1/
2     sub-001/
3         func/
```

```

4      sub-001_task-rest_run-1_space-MNI305_res-lo_bold.nii.gz
5      sub-001_task-rest_run-1_space-MNI305_res-hi_bold.nii.gz
6      sub-001_task-rest_run-1_space-MNI305_bold.json

```

The following metadata JSON fields are defined for preprocessed images:

Key name	Requirement level	Data type	Description
SkullStripped	REQUIRED	boolean	Whether the volume was skull stripped (non-brain voxels set to zero) or not.
Resolution	REQUIRED if <b>res</b> is present.	string or object mapping labels to strings	Specifies the interpretation of the resolution keyword.
Density	REQUIRED if <b>den</b> is present.	string or object mapping labels to strings	Specifies the interpretation of the density keyword.

Example JSON file corresponding to pipeline1/sub-001/func/sub-001\_task-rest\_run-1\_space-MNI305\_bold.json above:

```

1 {
2   "SkullStripped": true,
3   "Resolution": {
4     "hi": "Matched with high-resolution T1w (0.7mm, isotropic)",
5     "lo": "Matched with original BOLD resolution (2x2x3 mm^3)"
6   }
7 }

```

This would be equivalent to having two JSON metadata files, one corresponding to res-lo (pipeline1/sub-001/func/sub-001\_task-rest\_run-1\_space-MNI305\_res-lo\_bold.json):

```

1 {
2   "SkullStripped": true,
3   "Resolution": "Matched with original BOLD resolution (2x2x3 mm^3)"
4 }

```

And one corresponding to res-hi (pipeline1/sub-001/func/sub-001\_task-rest\_run-1\_space-MNI305\_res-hi\_bold.json):

```

1 {
2   "SkullStripped": true,
3   "Resolution": "Matched with high-resolution T1w (0.7mm, isotropic)"
4 }

```

Example of CIFTI-2 files (a format that combines regularly sampled data and non-parametric surfaces) having both **res** and **den** entities:



```
1 pipeline1/
2   sub-001/
3     func/
4       sub-001_task-rest_run-1_space-fsLR_res-1_den-10k_bold.dtseries.nii
5       sub-001_task-rest_run-1_space-fsLR_res-1_den-41k_bold.dtseries.nii
6       sub-001_task-rest_run-1_space-fsLR_res-2_den-10k_bold.dtseries.nii
7       sub-001_task-rest_run-1_space-fsLR_res-2_den-41k_bold.dtseries.nii
8       sub-001_task-rest_run-1_space-fsLR_bold.json
```

And the corresponding sub-001\_task-rest\_run-1\_space-fsLR\_bold.json file:

```
1 {
2   "SkullStripped": true,
3   "Resolution": {
4     "1": "Matched with MNI152NLin6Asym 1.6mm isotropic",
5     "2": "Matched with MNI152NLin6Asym 2.0mm isotropic"
6   },
7   "Density": {
8     "10k": "10242 vertices per hemisphere (5th order icosahedron)",
9     "41k": "40962 vertices per hemisphere (6th order icosahedron)"
10  }
11 }
```

## Masks

Template:

```
1 <pipeline_name>/
2   sub-<participant_label>/
3     anat|func|dwi/
4       <source_entities>[_space-<space>][_res-<label>][_den-<label>][_label-<label>][_desc-<label>]_mask.nii.gz
```

A binary (1 - inside, 0 - outside) mask in the space defined by <space>. If no transformation has taken place, the value of `space` SHOULD be set to `orig`. If the mask is an ROI mask derived from an atlas, then the `label` entity SHOULD be used to specify the masked structure (see Common image-derived labels), and the `Atlas` metadata SHOULD be defined.

JSON metadata fields:

Key name	Requirement level	Data type	Description
RawSources	REQUIRED	array of strings	Same as defined in Common data types, but elevated from OPTIONAL to REQUIRED.
Type	RECOMMENDED	string	Short identifier of the mask. Reserved values: <b>Brain</b> - brain mask, <b>Lesion</b> - lesion mask, <b>Face</b> - face mask, <b>ROI</b> - ROI mask
Atlas	RECOMMENDED if <b>label</b> entity is defined	string	Which atlas (if any) was used to generate the mask.
Resolution	REQUIRED if <b>res</b> is present	string or object mapping labels to strings	Specifies the interpretation of the resolution keyword.
Density	REQUIRED if <b>den</b> is present	string or object mapping labels to strings	Specifies the interpretation of the density keyword.

Examples:

```

1 func_loc/
2   sub-001/
3     func/
4       sub-001_task-rest_run-1_space-MNI305_desc-PFC_mask.nii.gz
5       sub-001_task-rest_run-1_space-MNI305_desc-PFC_mask.json

```

```

1 manual_masks/
2   sub-001/
3     anat/
4       sub-001_desc-tumor_mask.nii.gz
5       sub-001_desc-tumor_mask.json

```

## Segmentations

A segmentation is a labeling of regions of an image such that each location (for example, a voxel or a surface vertex) is identified with a label or a combination of labels. Labeled regions may include anatomical structures (such as tissue class, Brodmann area or white matter tract), discontinuous, functionally-defined networks, tumors or lesions.

A discrete segmentation represents each region with a unique integer label. A probabilistic segmentation represents each region as values between 0 and 1 (inclusive) at each location in the image, and one volume/frame per structure may be concatenated in a single file.

Segmentations may be defined in a volume (labeled voxels), a surface (labeled vertices) or a combined volume/surface space.

The following section describes discrete and probabilistic segmentations of volumes, followed by discrete segmentations of surface/combined spaces. Probabilistic segmentations of surfaces are currently unspecified.

The following metadata fields apply to all segmentation files:

Key name	Requirement level	Data type	Description
Manual	OPTIONAL	boolean	Indicates if the segmentation was performed manually or via an automated process.
Atlas	OPTIONAL	string	Which atlas (if any) was used to derive the segmentation.
Resolution	REQUIRED if <b>res</b> is present	string or object mapping labels to strings	Specifies the interpretation of the resolution keyword.
Density	REQUIRED if <b>den</b> is present	string or object mapping labels to strings	Specifies the interpretation of the density keyword.

### Discrete Segmentations

Discrete segmentations of brain tissue represent multiple anatomical structures (such as tissue class or Brodmann area) with a unique integer label in a 3D volume. See Common image-derived labels for a description of how integer values map to anatomical structures.

Template:

```
1 <pipeline_name>/
2   sub-<participant_label>/
3     anat|func|dwi/
4       <source_entities>[_space-<space>][_res-<label>][_den-<label>]_dseg.nii.gz
```

Example:

```
1 pipeline/
2   sub-001/
3     anat/
4       sub-001_space-orig_dseg.nii.gz
5       sub-001_space-orig_dseg.json
```

A segmentation can be used to generate a binary mask that functions as a discrete "label" for a single structure. In this case, the mask suffix **MUST** be used, the **label** entity **SHOULD** be used to specify the masked structure (see Common image-derived labels), and the **Atlas** metadata **SHOULD** be defined. For example:

```
1 pipeline/
2   sub-001/
3     anat/
4       sub-001_space-orig_label-GM_mask.nii.gz
```

### Probabilistic Segmentations

Probabilistic segmentations of brain tissue represent a single anatomical structure with values ranging from 0 to 1 in individual 3D volumes or across multiple frames. If a single structure is included, the `label` entity SHOULD be used to specify the structure.

Template:

```
1 <pipeline_name>/
2   sub-<participant_label>/
3     func|anat|dwi/
4       <source_entities>[_space-<space>][_res-<label>][_den-<label>][_label-<label>]_probseg.nii.gz
```

Example:

```
1 pipeline/
2   sub-001/
3     anat/
4       sub-001_space-orig_label-BG_probseg.nii.gz
5       sub-001_space-orig_label-WM_probseg.nii.gz
```

See Common image-derived labels for reserved key values for `label`.

A 4D probabilistic segmentation, in which each frame corresponds to a different tissue class, must provide a label mapping in its JSON sidecar. For example:

```
1 pipeline/
2   sub-001/
3     anat/
4       sub-001_space-orig_probseg.nii.gz
5       sub-001_space-orig_probseg.json
```

The JSON sidecar MUST include the `label-map` key that specifies a tissue label for each volume:

```
1 {
2   "LabelMap": [
3     "BG",
4     "WM",
5     "GM"
6   ]
7 }
```

Values of `label` SHOULD correspond to abbreviations defined in Common image-derived labels.

## Discrete surface segmentations

Discrete surface segmentations (sometimes called parcellations) of cortical structures MUST be stored as GIFTI label files, with the extension `.label.gii`. For combined volume/surface spaces, discrete segmentations MUST be stored as CIFTI-2 dense label files, with the extension `.dlabel.nii`.

Template:

```
1 <pipeline_name>/
2   sub-<participant_label>/
3     anat/
4       <source_entities>[_hemi-{L|R}] [_space-<space>] [_res-<label>] [_den-<label>]_dseg.{label.gii|dlabel.nii}
```

The `hemi` tag is REQUIRED for GIFTI files storing information about a structure that is restricted to a hemibrain. For example:

```
1 pipeline/
2   sub-001/
3     anat/
4       sub-001_hemi-L_dseg.label.gii
5       sub-001_hemi-R_dseg.label.gii
```

The REQUIRED extension for CIFTI parcellations is `.dlabel.nii`. For example:

```
1 pipeline/
2   sub-001/
3     anat/
4       sub-001_dseg.dlabel.nii
5       sub-001_dseg.dlabel.nii
```

## Common image-derived labels

BIDS supplies a standard, generic label-index mapping, defined in the table below, that contains common image-derived segmentations and can be used to map segmentations (and parcellations) between lookup tables.

Integer value	Description	Abbreviation (label)
0	Background	BG
1	Gray Matter	GM
2	White Matter	WM
3	Cerebrospinal Fluid	CSF
4	Bone	B
5	Soft Tissue	ST
6	Non-brain	NB
7	Lesion	L

Integer value	Description	Abbreviation (label)
8	Cortical Gray Matter	CGM
9	Subcortical Gray Matter	SGM
10	Brainstem	BS
11	Cerebellum	CBM

These definitions can be overridden (or added to) by providing custom labels in a sidecar `<matches>.tsv` file, in which `<matches>` corresponds to segmentation filename.

Example:

```
1 pipeline/
2   sub-001/
3     anat/
4       sub-001_space-orig_dseg.nii.gz
5       sub-001_space-orig_dseg.tsv
```

Definitions can also be specified with a top-level `dseg.tsv`, which propagates to segmentations in relative subdirectories.

Example:

```
1 pipeline/
2   dseg.tsv
3   sub-001/
4     anat/
5       sub-001_space-orig_dseg.nii.gz
```

These TSV lookup tables contain the following columns:

Column name	Description
index	REQUIRED. The label integer index
name	REQUIRED. The unique label name
abbreviation	OPTIONAL. The unique label abbreviation
color	OPTIONAL. Hexadecimal. Label color for visualization
mapping	OPTIONAL. Corresponding integer label in the standard BIDS label lookup

An example, custom `dseg.tsv` that defines three labels:

```
1 index  name      abbreviation  color    mapping
2 100    Gray Matter  GM          #ff53bb  1
3 101    White Matter  WM          #2f8bbe  2
```

```
4 102    Brainstem      BS          #36de72    11
```

The following example `dseg.tsv` defines regions that are not part of the standard BIDS labels:

```
1 index  name            abbreviation
2 137    pars opercularis  IFGop
3 138    pars triangularis IFGtr
4 139    pars orbitalis   IFGor
```

## Longitudinal and multi-site studies

Multiple sessions (visits) are encoded by adding an extra layer of directories and file names in the form of `ses-<label>`. Session label can consist only of alphanumeric characters `[a-zA-Z0-9]` and should be consistent across subjects. If numbers are used in session labels we recommend using zero padding (for example `ses-01`, `ses-11` instead of `ses-1`, `ses-11`). This makes results of alphabetical sorting more intuitive. Acquisition time of session can be defined in the sessions file (see below for details).

The extra session layer (at least one `/ses-<label>` subfolder) should be added for all subjects if at least one subject in the dataset has more than one session. Skipping the session layer for only some subjects in the dataset is not allowed. If a `/ses-<label>` subfolder is included as part of the directory hierarchy, then the same `ses-<label>` tag must also be included as part of the file names themselves.

```
1 sub-control01/
2   ses-predrug/
3     anat/
4       sub-control01_ses-predrug_T1w.nii.gz
5       sub-control01_ses-predrug_T1w.json
6       sub-control01_ses-predrug_T2w.nii.gz
7       sub-control01_ses-predrug_T2w.json
8     func/
9       sub-control01_ses-predrug_task-nback_bold.nii.gz
10      sub-control01_ses-predrug_task-nback_bold.json
11      sub-control01_ses-predrug_task-nback_events.tsv
12      sub-control01_ses-predrug_task-nback_cont-physio.tsv.gz
13      sub-control01_ses-predrug_task-nback_cont-physio.json
14      sub-control01_ses-predrug_task-nback_sbref.nii.gz
15     dwi/
16       sub-control01_ses-predrug_dwi.nii.gz
17       sub-control01_ses-predrug_dwi.bval
18       sub-control01_ses-predrug_dwi.bvec
19     fmap/
20       sub-control01_ses-predrug_phasediff.nii.gz
21       sub-control01_ses-predrug_phasediff.json
22       sub-control01_ses-predrug_magnitude1.nii.gz
```

```
23     sub-control01_ses-predrug_scans.tsv
24     ses-postdrug/
25     func/
26         sub-control01_ses-postdrug_task-nback_bold.nii.gz
27         sub-control01_ses-postdrug_task-nback_bold.json
28         sub-control01_ses-postdrug_task-nback_events.tsv
29         sub-control01_ses-postdrug_task-nback_cont-physio.tsv.gz
30         sub-control01_ses-postdrug_task-nback_cont-physio.json
31         sub-control01_ses-postdrug_task-nback_sbref.nii.gz
32     fmap/
33         sub-control01_ses-postdrug_phasediff.nii.gz
34         sub-control01_ses-postdrug_phasediff.json
35         sub-control01_ses-postdrug_magnitude1.nii.gz
36     sub-control01_ses-postdrug_scans.tsv
37     sub-control01_sessions.tsv
38 participants.tsv
39 dataset_description.json
40 README
41 CHANGES
```

## Sessions file

Template:

```
1 sub-<label>/
2     sub-<label>_sessions.tsv
```

Optional: Yes

In case of multiple sessions there is an option of adding additional participant key files describing variables changing between sessions. In such case one file per participant should be added. These files need to include compulsory `session_id` column and describe each session by one and only one row. Column names in per participant key files have to be different from group level participant key column names.

`_sessions.tsv` example:

```
1 session_id  acq_time  systolic_blood_pressure
2 ses-predrug 2009-06-15T13:45:30 120
3 ses-postdrug 2009-06-16T13:45:30 100
4 ses-followup 2009-06-17T13:45:30 110
```



## Multi-site or multi-center studies

This version of the BIDS specification does not explicitly cover studies with data coming from multiple sites or multiple centers (such extension is planned in BIDS 2.0). There are however ways to model your data without any loss in terms of metadata.

Treat each site/center as a separate dataset

The simplest way of dealing with multiple sites is to treat data from each site as a separate and independent BIDS dataset with a separate `participants.tsv` and other metadata files. This way you can feed each dataset individually to BIDS Apps and everything should just work.

Option 2: Combining sites/centers into one dataset

Alternatively you can combine data from all sites into one dataset. To identify which site each subjects comes from you can add a `site` column in the `participants.tsv` file indicating the source site. This solution allows you to analyze all of the subjects together in one dataset. One caveat is that subjects from all sites will have to have unique labels. To enforce that and improve readability you can use a subject label prefix identifying the site. For example `sub-NUY001`, `sub-MIT002`, `sub-MPG002` and so on. Remember that hyphens and underscores are not allowed in subject labels.

## BIDS Extension Proposals











The BIDS specification can be extended in a backwards compatible way and will evolve over time. This is accomplished with BIDS Extension Proposals (BEPs), which are community-driven processes (see BEP guidelines [Google Doc](#)).

On the BIDS homepage you can find a list of extension proposals that are currently being worked on.

All changes that are not backwards compatible with the current BIDS specification will be implemented in BIDS 2.0. See the corresponding [GitHub repository](#).

## Appendix I: Contributors



Legend (source: <https://allcontributors.org/docs/en/emoji-key>)




































































































































































































































































































Emoji	Represents
	Answering Questions (on the mailing list, NeuroStars, GitHub, or in person, etc.)
	Bug reports
	Blogposts
	Code
	Content (separate from Blogposts, for example Website news)
	Documentation and specification
	Data (example datasets)
	Design
	Examples (for example datasets, use <b>Data</b> )
	Event Organizers

Emoji	Represents
💰	Financial Support
🔍	Funding/Grant Finders
💡	Ideas & Planning
🏠	Infrastructure (hosting, build-tools, etc.)
🔧	Maintenance of the BIDS standard
👨🏫	Mentoring new contributors
🔌	Plugin/utility libraries
📅	Project management
🗳️	Reviewed Pull Requests
🔧	Tools
🌐	Translation
⚠️	Tests
✔️	Tutorials
📢	Talks
📄	User testing (of new features, tools, etc.)
📺	Videos

The following individuals have contributed to the Brain Imaging Data Structure ecosystem (in alphabetical order). If you contributed to the BIDS ecosystem and your name is not listed, please add it.

- Fidel Alfaró Almagro 🇪🇸🇺🇾🔧🔌
- Stefan Appelhoff 🇩🇪🇺🇸🇨🇦💡🔍🗳️⚠️📢🔧📄🏠🔌
- Tibor Auer 🇪🇸🇺🇾🔧🔌📢
- Sylvain Baillet 🇫🇷🔍
- Arshitha Basavaraj 🇮🇳🏠📄
- Stephan Bickel 🇩🇪
- Elizabeth Bock 🇺🇸🔧
- Kristofer Bouchard 🇨🇦
- Eric Bridgeford 🇺🇸🔧
- Teon L. Brooks 🇺🇸📅⚠️🇺🇸🇨🇦💡🔍🔧📢
- Suyash Bhogawar 🇮🇳🔧⚠️🔌🇺🇸
- Vince D. Calhoun 🇺🇸
- Alexander L. Cohen 🇺🇸📄🇺🇸🇺🇸
- R. Cameron Craddock 🇺🇸📢
- Sasha D'Ambrosio 🇺🇸
- Samir Das 🇮🇳
- Olivier David 🇫🇷
- Orrin Devinsky 🇺🇸
- Alejandro de la Vega 🇪🇸📄⚠️

- Arnaud Delorme 
- Benjamin Dichter 
- Erin W. Dickie   
- Eugene P. Duff 
- Elizabeth DuPre   
- Eric A. Earl 
- Anders Eklund   
- Oscar Esteban   
- Franklin W. Feingold                                
- Guillaume Flandin   
- Adeen Flinker 
- Brett L. Foster 
- Remi Gau   
- Satrajit S. Ghosh   
- Tristan Glatard   
- Mathias Goncalves   
- Krzysztof J. Gorgolewski                               
- Alexandre Gramfort 
- Jeffrey S. Grethe                                 
- Iris Groen 
- David Groppe 
- Aysegul Gunduz 
- Yaroslav O. Halchenko                                
- Liberty Hamilton 
- Daniel A. Handwerker 
- Michael Hanke                                 
- Michael P. Harms   
- Richard N. Henson 
- Peer Herholz                                  
- Dora Hermes                                  
- Katja Heuer 
- Richard Höchenberger 
- Chris Holdgraf 
- Christopher J. Honey 
- Jean-Christophe Houde 
- International Neuroinformatics Coordinating Facility   
- Andrew Janke   
- Mainak Jas   
- Alexander Jones                                 
- David Keator 

- James Kent 
- Gregory Kiar  
- Robert Knight 
- Jean-Philippe Lachaux 
- Marc Lalancette 
- Pamela LaMontagne  
- Kevin Larcher 
- Jonathan C. Lau 
- Laura and John Arnold Foundation 
- Christopher Lee-Messer 
- Jon Haitz Legarreta  
- Adam Li  
- Xiangrui Li  
- Vladimir Litvak 
- Brian N. Lundstrom 
- Dan Lurie     
- Camille Maumet 
- Christopher J. Markiewicz                                
- Kai J. Miller 
- Jeremy Moreau  
- Zachary Michael 
- Ezequiel Mikulan  
- Michael P. Milham  
- Henk Mutsaerts 
- National Institute of Mental Health 
- Mikael Naveau 
- B. Nolan Nichols 
- Thomas E. Nichols                                 
- Dylan Nielson   
- Guiomar Niso      
- Michael P. Notter                                 
- Jeffrey G. Ojemann 
- Robert Oostenveld                                 
- Dimitri Papadopoulos Orfanos                                 
- Patrick Park      
- Dianne Patterson 
- John Pellman 
- Cyril Pernet                                   
- Franco Pestilli                                   
- Natalia Petridou 

- Dmitry Petrov 
- Christophe Phillips 
- Gio Piantoni 
- Andrea Pigorini 
- Russell A. Poldrack   
- Jean-Baptiste Poline    
- Wouter V. Potters 
- Nader Pouratian 
- Pradeep Reddy Raamana  
- Vasudev Raguram    
- Nick F. Ramsey 
- Kay Robbins   
- Alex Rockhill  
- Ariel Rokem 
- Taylor Salo    
- Matt Sanderson   
- Gunnar Schaefer 
- Jan-Mathijs Schoffelen 
- Robert E. Smith  
- Vanessa Sochat 
- Arjen Stolk 
- Nicole C. Swann 
- François Tadel    
- Roberto Toro 
- Sébastien Tourbier       
- William Triplett 
- Jessica A. Turner 
- Max A. van den Boom   
- Bradley Voytek 
- Brian A. Wandell 
- Joseph Wexler  
- Kirstie Whitaker      
- Jonathan Winawer 
- Gaël Varoquaux 
- Tal Yarkoni        
- Lyuba Zehl 
- Melanie Ganz-Benaminsen      
- Martin Noergaard     

## Appendix II: Licenses

This section lists a number of common licenses for datasets and defines suggested abbreviations for use in the dataset metadata specifications.

Please note that this list only serves to provide some examples for possible licenses. The terms of any license should be consistent with the informed consent obtained from participants and any institutional limitations on distribution.

Identifier	License name	Description
PD	Public Domain	No license required for any purpose; the work is not subject to copyright in any jurisdiction.
PDDL	Open Data Commons Public Domain Dedication and License	License to assign public domain like permissions without giving up the copyright: <a href="http://opendatacommons.org/licenses/pddl/">http://opendatacommons.org/licenses/pddl/</a>
CC0	Creative Commons Zero 1.0 Universal.	Use this if you are a holder of copyright or database rights, and you wish to waive all your interests in your work worldwide: <a href="http://opendatacommons.org/licenses/cc0/">http://opendatacommons.org/licenses/cc0/</a>

## Appendix III: Hierarchical Event Descriptors

Hierarchical Event Descriptors (HED) are a controlled vocabulary of terms describing events in a machine-actionable form so that algorithms can use the information without manual recoding. HED was originally developed with EEG in mind, but is applicable to all behavioral experiments.

Each level of a hierarchical tag is delimited with a forward slash (/). A HED string contains one or more HED tags separated by commas (,). Parentheses (brackets, ()) group tags and enable specification of multiple items and their attributes in a single HED string (see section 2.4 in HED Tagging Strategy Guide). For more information about HED and tools available to validate and match HED strings, please visit [www.hedtags.org](http://www.hedtags.org). Since dedicated fields already exist for the overall task classification in the sidecar JSON files (CogAtlasID and CogPOID), HED tags from the Paradigm HED subcategory should not be used to annotate events.

### Annotating each event

There are several ways to associate HED annotations with events within the BIDS framework. The most direct way is to use the HED column of the `*_events.tsv` file to annotate events.

Example: An `*_events.tsv` annotated using HED tags for individual events.

```

1 onset  duration  HED
2 1.1    n/a      Event/Category/Experimental stimulus, Event/Label/CrossFix, Sensory presentation/Visual, Item/Object/2D Shape/Cross
3 1.3    n/a      Event/Category/Participant response, Event/Label/ButtonPress, Action/Button press
4 ...
```

The direct approach requires that each line in the events file be annotated. Since there are typically thousands of events in each experiment, this method of annotation is not convenient unless the annotations are automatically generated. Usually annotations that appear in the HED column are specific to each individual event. Information that is common to groups of events can be annotated by category. Numerical values associated with each event can be annotated by value type. Annotating by category and by value greatly reduces the effort required to HED tag data and improves the clarity for data users.

### Annotating events by categories

In many experiments, the event instances fall into a much smaller number of categories, and often these categories are labeled with numerical codes or short names. This categorical information usually corresponds to one or more columns in `*_events.tsv` representing categorical values. Instead of tagging this information for each individual event, you can assign HED tags for each distinct categorical value in an accompanying `*_events.json` sidecar and allow the analysis tools to make the association with individual event instances during analysis. The column name in the `*_events.tsv` identifies the type of categorical variable. The following `*_events.tsv` file has one categorical variable called `mycodes` that takes on three possible values: `Fixation`, `Button`, and `Target`.

Example: An `*_events.tsv` containing the `mycodes` categorical column.

```
1 onset  duration  mycodes
2 1.1    n/a      Fixation
3 1.3    n/a      Button
4 1.8    n/a      Target
5 ...
```

Example: An accompanying `*_events.json` sidecar describing the `mycodes` categorical variable.

```
1 {
2   "mycodes": {
3     "LongName": "Local event type names",
4     "Description": "Main types of events that comprise a trial",
5     "Levels": {
6       "Fixation": "Fixation cross is displayed",
7       "Target": "Target image appears",
8       "Button": "Subject presses a button"
9     },
10    "HED": {
11      "Fixation": "Event/Category/Experimental stimulus, Event/Label/CrossFix,
12                  Event/Description/A cross appears at screen center to serve as a fixation point,
13                  Sensory presentation/Visual, Item/Object/2D Shape/Cross,
14                  Attribute/Visual/Fixation point, Attribute/Visual/Rendering type/Screen,
15                  Attribute/Location/Screen/Center",
16      "Target": "Event/Label/TargetImage, Event/Category/Experimental stimulus,
17                Event/Description/A white airplane as the RSVP target superimposed on a satellite image is displayed.,
18                Item/Object/Vehicle/Aircraft/Airplane, Participant/Effect/Cognitive/Target,
19                Sensory presentation/Visual/Rendering type/Screen/2D),
```

```

20         (Item/Natural scene/Aerial/Satellite,
21         Sensory presentation/Visual/Rendering type/Screen/2D)",
22     "Button": "Event/Category/Participant response, Event/Label/PressButton,
23         Event/Description/The participant presses the button as soon as the target is visible,
24         Action/Button press"
25     }
26 }
27 }

```

## Annotating events by value type

Each column of `*_events.tsv` containing non-categorical values usually represents a particular type of data, for example the **speed** of a stimulus object across the screen or the file name of the stimulus image. These variables could be annotated in the HED column of `*_events.tsv`. However, that approach requires repeating the values appearing in the individual columns in the HED column. A better approach is to annotate the type of value contained in each of these columns in the `*_events.json` sidecar. Value variables are annotated in a manner similar to categorical values, except that the HED string must contain exactly one `#` specifying a placeholder for the actual column values. Tools are responsible for substituting the actual column values for the `#` during analysis.

Example: An `*_events.tsv` containing a categorical column (`trial_type`) and two value columns (`response_time` and `stim_file`).

```

1 onset duration trial_type response_time stim_file
2 1.2      0.6      go         1.435      images/red_square.jpg
3 5.6      0.6      stop        1.739      images/blue_square.jpg

```

Example: An accompanying `*_events.json` sidecar describing both categorical and value columns.

```

1 {
2   "trial_type": {
3     "LongName": "Event category",
4     "Description": "Indicator of type of action that is expected",
5     "Levels": {
6       "go": "A red square is displayed to indicate starting",
7       "stop": "A blue square is displayed to indicate stopping",
8     },
9     "HED": {
10      "go": "Event/Category/Experimental stimulus, Event/Label/RedSquare,
11      Event/Description/A red square is displayed to indicate starting,
12      Sensory presentation/Visual, Item/Object/2D Shape/Square,
13      Attribute/Visual/Color/Red, Attribute/Visual/Rendering type/Screen,
14      Attribute/Location/Screen/Center",
15      "stop": "Event/Category/Experimental stimulus, Event/Label/BlueSquare,
16      Event/Description/A blue square is displayed to indicate stopping,
17      Sensory presentation/Visual, Item/Object/2D Shape/Square,

```



```
18     Attribute/Visual/Color/Blue, Attribute/Visual/Rendering type/Screen,
19     Attribute/Location/Screen/Center",
20   }
21 },
22 "response_time": {
23   "LongName": "Response time after stimulus",
24   "Description": "Time from stimulus presentation until subject presses button",
25   "Units": "ms",
26   "HED": "Attribute/Response start delay/# ms, Action/Button press"
27 },
28 "stim_file": {
29   "LongName": "Stimulus file name",
30   "Description": "Relative path of the stimulus image file",
31   "HED": "Attribute/File/#"
32 }
33 }
```

## Best practices

Most studies will have event categorical variables and value variables that are common across many of the datasets in the study. You should try to annotate these columns in a `*_events.json` sidecar as high in the study hierarchy as possible to avoid duplicate annotations. Annotations that can be placed in sidecars are preferred to those placed directly in the HED column, because they are simpler, more compact, and less prone to inconsistent annotation. Downstream tools should not distinguish between tags specified using the explicit HED column and the categorical specifications, but should form the union before analysis. Further, the inheritance principle applies, so the data dictionaries can appear higher in the BIDS hierarchy.

You should try to annotate in as much detail as possible. The HED path structure makes it easy for analysis tools to extract tags at different levels of detail: For example a user can consider extracting events associated with 2D shapes for stimuli, ignoring the particular color or shape details for the stimuli.

## HED schema and HED versions

The HED vocabulary is specified by a HED schema, which delineates the allowed HED path strings. By default, BIDS uses the latest HED schema available in the hed-specification repository maintained by the hed-standard group.

You can override the default by providing a specific HED version number in the `dataset_description.json` file using the `HEDVersion` field. The preferred approach is to validate with the latest version (the default), but to use the `HEDVersion` field to specify which version was used for later reference.

Example: The following `dataset_description.json` file specifies that HED7.1.1.xml from the hed-specification repository should be used to validate the study event annotations.

```
1 {
2   "Name": "The mother of all experiments",
3   "BIDSVersion": "1.4.0",
```

```
4 "HEDVersion": "7.1.1"
5 }
```

Appendix IV: Entity table

This section compiles the entities (key-value pairs) described throughout this specification, and establishes a common order within a filename. For example, if a file has an acquisition and reconstruction label, the acquisition entity must precede the reconstruction entity. REQUIRED and OPTIONAL entities for a given file type are denoted. Entity formats indicate whether the value is alphanumeric (<label>) or numeric (<index>).

A general introduction to entities is given in the section on file name structure, while entity definitions are in Appendix IX.

Magnetic Resonance Imaging

Entity	Subject	Session	Task	Acquisition	Contrast Enhanc- ing Agent	Reconstruction	Phase- Encoding Direction	Run	Corresponding Modality	Echo	Recording
Format	sub-<label>	ses-<label>	task-<label>	acq-<label>	ce-<label>	rec-<label>	dir-<label>	run-<index>	mod-<label>	echo-<index>	recording-<label>
anat(T1w T2w T1rho T1map T2map T2star FLAIR FLASH PD PDmap PDT2 in- planeT1 in- planeT2 angio)	REQUIRED	OPTIONAL		OPTIONAL	OPTIONAL	OPTIONAL		OPTIONAL			
anat(defacedmask)	REQUIRED	OPTIONAL		OPTIONAL	OPTIONAL	OPTIONAL		OPTIONAL	OPTIONAL		
dwi(dwi sbref)	REQUIRED	OPTIONAL		OPTIONAL			OPTIONAL	OPTIONAL			

Entity	Subject	Session	Task	Acquisition	Contrast Enhanc- ing Agent	Reconstruction	Phase- Encoding Direction	Run	Corresponding Modality	Echo	Recording
fmap(phase1)	REQUIRED	OPTIONAL		OPTIONAL				OPTIONAL			
phase1											
phase2											
magni- tude1											
magni- tude2											
magni- tude											
fieldmap)											
fmap(epi)	REQUIRED	OPTIONAL		OPTIONAL	OPTIONAL		REQUIRED	OPTIONAL			
func(bold)	REQUIRED	OPTIONAL	REQUIRED	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL		OPTIONAL	
cbv phase											
sbref											
events)											
func(physio stim)	REQUIRED	OPTIONAL	REQUIRED	OPTIONAL		OPTIONAL		OPTIONAL			OPTIONAL

### Encephalography (EEG, iEEG, and MEG)

Entity	Subject	Session	Task	Acquisition	Run	Processed (on device)	Space	Split
Format	sub-<label>	ses-<label>	task-<label> >	acq-<label>	run-<index>	proc-<label> >	space-< label>	split-< index>
eeg(eeg)	REQUIRED	OPTIONAL	REQUIRED	OPTIONAL	OPTIONAL			
iieg(iieg)	REQUIRED	OPTIONAL	REQUIRED	OPTIONAL	OPTIONAL			
meg(meg)	REQUIRED	OPTIONAL	REQUIRED	OPTIONAL	OPTIONAL	OPTIONAL		OPTIONAL
meg(headshape)	REQUIRED	OPTIONAL		OPTIONAL			OPTIONAL	
meg(markers)	REQUIRED	OPTIONAL	OPTIONAL	OPTIONAL			OPTIONAL	
channels(meg eeg iieg)	REQUIRED	OPTIONAL	REQUIRED		OPTIONAL			
electrodes(eeg iieg)	REQUIRED	OPTIONAL		OPTIONAL			OPTIONAL	
events(meg eeg iieg)	REQUIRED	OPTIONAL	REQUIRED		OPTIONAL			

Entity	Subject	Session	Task	Acquisition	Run	Processed (on device)	Space	Split
photo(meg eeg ieeg)	REQUIRED	OPTIONAL		OPTIONAL				

## Behavioral Data

Entity	Subject	Session	Task	Acquisition	Run	Recording
Format	sub-<label>	ses-<label>	task-<label>	acq-<label>	run-<index>	recording-<label>
beh(stim physio)	REQUIRED	OPTIONAL	REQUIRED	OPTIONAL	OPTIONAL	OPTIONAL
beh(events beh)	REQUIRED	OPTIONAL	REQUIRED	OPTIONAL	OPTIONAL	OPTIONAL

## Appendix V: Units

As described in the Units, the specification of units SHOULD follow the International System of Units (SI, abbreviated from the French *Système international* (d'unités)).

The CMIXF-12 convention for encoding units is RECOMMENDED to achieve maximum portability and limited variability of representation. If a CMIXF-12 representation of a unit is not possible, the unit can be declared as custom units and defined in an accompanying JSON file, as described in the units section. Earlier versions of the BIDS standard listed the following Unicode symbols, and these are still included for backwards compatibility:

1. U+03BC ( $\mu$ ) or U+00B5 ( $\mu$ )
2. U+03A9 ( $\Omega$ ) or U+2126 ( $\Omega$ )
3. U+00B0 ( $^{\circ}$ )

Note that for the first two entries in this list, two characters are permissible for each, but the first character in each entry is preferred, per Unicode rules (see the section on "Duplicated Characters" on page 11 in the unicode report).

It is RECOMMENDED that units be CMIXF-12 compliant or among these five Unicode characters. Please note the appropriate upper- or lower- casing when using CMIXF-12.

For cases that are unspecified by this appendix or the units section, the CMIXF-12 convention applies.

You can use the cmixf Python package to check whether your formatting is compliant.

Examples for CMIXF-12 (including the five unicode symbols mentioned above):

1. Different formatting of "micro Volts":
  - (a) RECOMMENDED: uV or  $\mu$ V
  - (b) NOT RECOMMENDED: microV,  $\mu$ volt or 1e-6V
2. Combinations of units:

- (a) RECOMMENDED: V/us for the Slew rate  
 (b) NOT RECOMMENDED: volts per microsecond

## Unit table

Unit name	Unit symbol	Quantity name
metre	m	length
kilogram	kg	mass
litre (liter)	L	volume
second	s	time
ampere	A	electric current
kelvin	K	thermodynamic temperature
mole	mol	amount of substance
candela	cd	luminous intensity
radian	rad	angle
steradian	sr	solid angle
hertz	Hz	frequency
newton	N	force, weight
pascal	Pa	pressure, stress
joule	J	energy, work, heat
watt	W	power, radiant flux
coulomb	C	electric charge or quantity of electricity
volt	V	voltage (electrical potential), emf
farad	F	capacitance
ohm	Ohm	resistance, impedance, reactance
siemens	S	electrical conductance
weber	Wb	magnetic flux
tesla	T	magnetic flux density
henry	H	inductance
degree Celsius	oC	temperature relative to 273.15 K
lumen	lm	luminous flux
lux	lx	illuminance
becquerel	Bq	radioactivity (decays per unit time)
gray	Gy	absorbed dose (of ionizing radiation)
sievert	Sv	equivalent dose (of ionizing radiation)
katal	kat	catalytic activity

Prefixes

Multiples

Prefix name	Prefix symbol	Factor
deca	da	10 <sup>1</sup>
hecto	h	10 <sup>2</sup>
kilo	k	10 <sup>3</sup>
mega	M	10 <sup>6</sup>
giga	G	10 <sup>9</sup>
tera	T	10 <sup>12</sup>
peta	P	10 <sup>15</sup>
exa	E	10 <sup>18</sup>
zetta	Z	10 <sup>21</sup>
yotta	Y	10 <sup>24</sup>

Submultiples

Prefix name	Prefix symbol	Factor
deci	d	10 <sup>-1</sup>
centi	c	10 <sup>-2</sup>
milli	m	10 <sup>-3</sup>
micro	u	10 <sup>-6</sup>
nano	n	10 <sup>-9</sup>
pico	p	10 <sup>-12</sup>
femto	f	10 <sup>-15</sup>
atto	a	10 <sup>-18</sup>
zepto	z	10 <sup>-21</sup>
yocto	y	10 <sup>-24</sup>

Appendix VI: MEG file formats

Each MEG system brand has specific file organization and data formats. RECOMMENDED values for `manufacturer_specific_extensions`:

Value	Description
<code>ctf</code>	CTF (folder with <code>.ds</code> extension)
<code>fif</code>	Neuromag / Elekta / MEGIN and BabyMEG (file with extension <code>.fif</code> )

Value	Description
4d	BTi / 4D Neuroimaging (folder containing multiple files without extensions)
kit	KIT / Yokogawa / Ricoh (file with extension <code>.sqd</code> , <code>.con</code> , <code>.raw</code> , <code>.ave</code> or <code>.mrk</code> )
kdf	KRISS (file with extension <code>.kdf</code> )
itab	Chieti system (file with extension <code>.raw</code> and <code>.mhd</code> )

Below are specifications for each system brand.

## CTF

Each experimental run with a CTF system yields a folder with a `.ds` extension, containing several files. The OPTIONAL digitized positions of the head points are usually stored in a separate `.pos` file, not necessarily within the `.ds` folder.

```
1 [sub-<label>[_ses-<label>]_headshape.pos]
2 sub-<label>[_ses-<label>]_task-<label>[_run-<index>]_meg.ds>
```

CTF's data storage is therefore via directories containing multiple files. The files contained within a `.ds` directory are named such that they match the parent directory, but preserve the original file extension (for example, `.meg4`, `.res4`). The renaming of CTF datasets SHOULD be done with a specialized software such as the CTF newDs command-line application or MNE-BIDS.

Example:

```
1 sub-control01/
2   ses-001/
3     sub-control01_ses-001_scans.tsv
4     meg/
5       sub-control01_ses-001_coordsystem.json
6       sub-control01_ses-001_headshape.pos
7       sub-control01_ses-001_task-rest_run-01_meg.ds
8       sub-control01_ses-001_task-rest_run-01_meg.json
9       sub-control01_ses-001_task-rest_run-01_channels.tsv
```

To learn more about CTF's data organization: [http://www.fieldtriptoolbox.org/getting\\_started/ctf](http://www.fieldtriptoolbox.org/getting_started/ctf)

## Neuromag/Elekta/MEGIN

Neuromag/Elekta/MEGIN and Tristan Technologies BabyMEG data is stored as FIFF files with the extension `.fif`. The digitized positions of the head points are saved inside the FIFF file along with the MEG data, with typically no `_headshape` file.

```
1 sub-<label>[_ses-<label>]_task-<label>[_run-<index>]_meg.fif
```

### Cross-talk and fine-calibration files

In case internal active shielding (IAS) was used during acquisition, raw FIFF files need to be processed using Maxwell filtering (signal-space separation, SSS) to make the data usable. To this end, two specific files are needed: The cross-talk file, and the fine-calibration file, both of which are produced by the MaxFilter software and the work of the Neuromag/Elekta/MEGIN engineers during maintenance of the MEG acquisition system. Both files are thus specific to the site of recording and may change in the process of regular system maintenance.

In BIDS, the cross-talk and fine-calibration files are shared unmodified, including their original extensions (.fif for cross-talk and .dat for fine-calibration), but with BIDS file naming convention and by using the `acq` entity.

- cross-talk file template: `sub-<label>[_ses-<label>]_acq-crosstalk_meg.fif`
- fine-calibration file template: `sub-<label>[_ses-<label>]_acq-calibration_meg.dat`

Note that cross-talk files **MUST** be denoted using `acq-crosstalk` and fine-calibration files **MUST** be denoted using `acq-calibration`.

The cross-talk and fine-calibration data **MUST** be stored in the subject-level `meg` folder, which may be nested inside a `ses-<label>` folder, as shown in the following examples.

```
1 sub-01/
2   meg/
3     sub-01_coordsystem.json
4     sub-01_task-rest_meg.fif
5     sub-01_task-rest_meg.json
6     sub-01_task-rest_channels.tsv
7     sub-01_acq-crosstalk_meg.fif
8     sub-01_acq-calibration_meg.dat
9 sub-02/
10  meg/
11    sub-02_coordsystem.json
12    sub-02_task-rest_meg.fif
13    sub-02_task-rest_meg.json
14    sub-02_task-rest_channels.tsv
15    sub-02_acq-crosstalk_meg.fif
16    sub-02_acq-calibration_meg.dat
```

```
1 sub-01/
2   ses-01/
3     sub-01_ses-01_scans.tsv
4     meg/
5       sub-01_ses-01_coordsystem.json
6       sub-01_ses-01_task-rest_run-01_meg.fif
```



```
7         sub-01_ses-01_task-rest_run-01_meg.json
8         sub-01_ses-01_task-rest_run-01_channels.tsv
9         sub-01_ses-01_acq-crosstalk_meg.fif
10        sub-01_ses-01_acq-calibration_meg.dat
11    ses-02/
12        sub-01_ses-02_scans.tsv
13    meg/
14        sub-01_ses-02_coordsystem.json
15        sub-01_ses-02_task-rest_run-01_meg.fif
16        sub-01_ses-02_task-rest_run-01_meg.json
17        sub-01_ses-02_task-rest_run-01_channels.tsv
18        sub-01_ses-02_acq-crosstalk_meg.fif
19        sub-01_ses-02_acq-calibration_meg.dat
```

#### Sharing FIFF data after signal-space separation (SSS)

After applying SSS (for example, by using the MaxFilter software), files SHOULD be renamed with the corresponding label (for example, `proc-sss`) and placed in a `derivatives` subfolder.

Example:

```
1 sub-control01_ses-001_task-rest_run-01_proc-sss_meg.fif
2 sub-control01_ses-001_task-rest_run-01_proc-sss_meg.json
```

#### Split files

In the case of long data recordings that exceed a file size of 2Gb, the `.fif` files are conventionally split into multiple parts. For example:

```
1 some_file.fif
2 some_file-1.fif
```

Each of these files has an internal pointer to the next file. This is important when renaming these split recordings to the BIDS convention. Instead of a simple renaming, files should be read in and saved under their new names with dedicated tools like MNE, which will ensure that not only the file names, but also the internal file pointers will be updated.

It is RECOMMENDED that FIFF files with multiple parts use the `split-<index>` entity to indicate each part.

Example:

```
1 sub-control01_ses-001_task-rest_run-01_split-01_meg.fif
2 sub-control01_ses-001_task-rest_run-01_split-02_meg.fif
```

More information can be found under the following links:

- Neuromag/Elekta/MEGIN data organization
- BabyMEG

Recording dates in `.fif` files

It is important to note that recording dates in `.fif` files are represented as `int32` format seconds since (or before) the Epoch (1970-01-01T00:00:00.000000 UTC). Integers in `int32` format can encode values from -2,147,483,647 to +2,147,483,647. Due to this representation, the Neuromag/Elekta/MEGIN file format for MEG (`.fif`) does not support recording dates earlier than 1901-12-13T08:45:53.000000 UTC or later than 2038-01-19T03:14:07.000000 UTC.

## BTi/4D neuroimaging

Each experimental run on a 4D neuroimaging/BTi system results in a folder containing multiple files without extensions.

```
1 [sub-<label>[_ses-<label>]_headshape.pos]
2 sub-<label>[_ses-<label>]_task-<label>[_run-<index>]_meg>
```

One SHOULD rename/create a father run specific directory and keep the original files for each run inside (for example, `c`, `rfhp0.1Hz`, `config` and `hs_file`).

Example:

```
1 sub-control01/
2   ses-001/
3     sub-control01_ses-001_scans.tsv
4     meg/
5       sub-control01_ses-001_coordsystem.json
6       sub-control01_ses-001_headshape.pos
7       sub-control01_ses-001_task-rest_run-01_meg
8       sub-control01_ses-001_task-rest_run-01_meg.json
9       sub-control01_ses-001_task-rest_run-01_channels.tsv
```

Where:

```
1 sub-control01_ses-001_task-rest_run-01_meg/
2   config
3   hs_file
4   e,rfhp1.0Hz.COH
5   c,rfDC
```

More about the 4D neuroimaging/BTi data organization at: [http://www.fieldtriptoolbox.org/getting\\_started/bti](http://www.fieldtriptoolbox.org/getting_started/bti)

## KIT/Yokogawa/Ricoh

Each experimental run on a KIT/Yokogawa/Ricoh system yields a raw (.sqd, .con) file with its associated marker coil file(s) (.sqd, .mrk), which contains coil positions in the acquisition system's native space. Head points and marker points in head space are acquired using third-party hardware.

Example:

```
1 sub-control01/  
2   ses-001/  
3     sub-control01_ses-001_scans.tsv  
4     meg/  
5       sub-control01_ses-001_coordsystem.json  
6       sub-control01_ses-001_headshape.txt  
7       sub-control01_ses-001_task-rest_run-01_meg  
8       sub-control01_ses-001_task-rest_run-01_meg.json  
9       sub-control01_ses-001_task-rest_run-01_channels.tsv  
10      sub-control01_ses-001_task-rest[_acq-<label>]_run-01_markers.<mrk,sqd>  
11      sub-control01_ses-001_task-rest_run-01_meg.<con,sqd>
```

If there are files with multiple marker coils, the marker files must have the `acq-<label>` parameter and no more than two marker files may be associated with one raw data file. While the acquisition parameter can take any value, it is RECOMMENDED that if the two marker measurements occur before and after the raw data acquisition, `pre` and `post` are used to differentiate the two situations.

More about the KIT/Yokogawa/Ricoh data organization at: [http://www.fieldtriptoolbox.org/getting\\_started/yokogawa](http://www.fieldtriptoolbox.org/getting_started/yokogawa)

## KRISS

Each experimental run on the KRISS system produces a file with extension .kdf. Additional files can be available in the same folder: the digitized positions of the head points (\\_digitizer.txt), the position of the center of the MEG coils (.chn) and the event markers (.trg).

```
1 [sub-<label>[_ses-<label>]_headshape.txt]  
2 sub-<label>[_ses-<label>]_task-<label>[_run-<index>]_meg.kdf  
3 sub-<label>[_ses-<label>]_task-<label>[_run-<index>]_meg.chn  
4 sub-<label>[_ses-<label>]_task-<label>[_run-<index>]_meg.trg  
5 sub-<label>[_ses-<label>]_task-<label>[_acq-<label>]_digitizer.txt
```

Example:

```
1 sub-control01/
2   ses-001/
3     sub-control01_ses-001_scans.tsv
4     meg/
5       sub-control01_ses-001_coordsystem.json
6       sub-control01_ses-001_headshape.txt
7       sub-control01_ses-001_task-rest_run-01_meg
8       sub-control01_ses-001_task-rest_run-01_meg.json
9       sub-control01_ses-001_task-rest_run-01_channels.tsv
10      sub-control01_ses-001_task-rest_run-01_meg.chn
11      sub-control01_ses-001_task-rest_run-01_meg.kdf
12      sub-control01_ses-001_task-rest_run-01_meg.trg
13      sub-control01_ses-001_task-rest_digitizer.txt
```

## ITAB

Each experimental run on a ITAB-ARGOS153 system yields a raw (.raw) data file plus an associated binary header file (.mhd). The raw data file has an ASCII header that contains detailed information about the data acquisition system, followed by binary data. The associated binary header file contains part of the information from the ASCII header, specifically the one needed to process data, plus other information on offline preprocessing performed after data acquisition (for example, sensor position relative to subject's head, head markers, stimulus information).

Example:

```
1 sub-control01/
2   ses-001/
3     sub-control01_ses-001_coordsystem.json
4     sub-control01_ses-001_headshape.txt
5     sub-control01_ses-001_task-rest_run-01_meg
6     sub-control01_ses-001_task-rest_run-01_meg.json
7     sub-control01_ses-001_task-rest_run-01_channels.tsv
8     sub-control01_ses-001_task-rest_run-01_meg.raw
9     sub-control01_ses-001_task-rest_run-01_meg.raw.mhd
```

## Aalto MEG-MRI

For stand-alone MEG data, the Aalto hybrid device uses the standard .fif data format and follows the conventions of Elekta/Neuromag as described above. The .fif files may contain unreconstructed MRI data. The inclusion of MRI data and information for accurate reconstruction will be fully standardized at a later stage.

## Appendix VII: MEG systems

Perferred names of MEG systems comprise restricted keywords for Manufacturer field in the \*\_meg.json file:

- CTF
- Neuromag/Elekta/Megin
- BTi/4D
- KIT/Yokogawa/Ricoh
- KRISS
- ITAB
- Aalto/MEG-MRI
- Other

Restricted keywords for ManufacturersModelName field in the \*\_meg.json file:

System Model Name	Manufacturer	Details
CTF-64	CTF	
CTF-151	CTF	<a href="https://www.ctf.com/products">https://www.ctf.com/products</a>
CTF-275	CTF	CTF-275: OMEGA 2000
Neuromag-122	Neuromag/Elekta/Megin	
ElektaVectorview	Neuromag/Elekta/Megin	102 magnetometers + 204 planar gradiometers
ElektaTRIUX	Neuromag/Elekta/Megin	<a href="https://www.elekta.com/diagnostic-solutions/">https://www.elekta.com/diagnostic-solutions/</a>
4D-Magnes-WH2500	BTi/4D	
4D-Magnes-WH3600	BTi/4D	
KIT-157	KIT/Yokogawa	
KIT-160	KIT/Yokogawa	
KIT-208	KIT/Yokogawa	
ITAB-ARGOS153	ITAB	
Aalto-MEG-MRI-YYYY/MM	Aalto/MEG-MRI	YYYY-MM (year, month; or major version)

## Appendix VIII: Coordinate systems

## Introduction

To interpret a coordinate (x, y, z), it is required that you know (1) relative to which origin the coordinate is expressed, (2) the interpretation of the three axes, and (3) the units in which the numbers are expressed. This information is sometimes called the coordinate system.

These letters help describe the coordinate system definition:

- A/P means anterior/posterior
- L/R means left/right
- S/I means superior/inferior

For example: RAS means that the first dimension (X) points towards the right hand side of the head, the second dimension (Y) points towards the Anterior aspect of the head, and the third dimension (Z) points towards the top of the head. The directions are considered to be from the subject's perspective. For example, in the RAS coordinate system, a point to the subject's left will have a negative x value.

Besides coordinate systems, defined by their origin and direction of the axes, BIDS defines "spaces" as an artificial frame of reference, created to describe different anatomies in a unifying manner (see for example, doi:10.1016/j.neuroimage.2012.01.024).

The "space" and all coordinates expressed in this space are by design a transformation of the real world geometry, and nearly always different from the individual subject space that it stems from. An example is the Talairach-Tournoux space, which is constructed by piecewise linear scaling of an individual's brain to that of the Talairach-Tournoux 1988 atlas. In the Talairach-Tournoux space, the origin of the coordinate system is at the AC and units are expressed in mm.

The coordinate systems below all relate to neuroscience and therefore to the head or brain coordinates. Please be aware that all data acquisition starts with "device coordinates" (scanner), which does not have to be identical to the initial "file format coordinates" (DICOM), which are again different from the "head" coordinates (for example, NIFTI). Not only do device coordinate vary between hardware manufacturers, but also the head coordinates differ, mostly due to different conventions used in specific software packages developed by different (commercial or academic) groups.

## Coordinate Systems applicable to MEG, EEG, and iEEG

Generally, across the MEG, EEG, and iEEG modalities, the first two pieces of information for a coordinate system (origin and orientation) are specified in `<datatype>CoordinateSystem`. The third piece of information for a coordinate system (units) are specified in `<datatype>CoordinateUnits`. Here, `<datatype>` can be one of MEG, EEG, or iEEG, depending on the modality that is being used.

Allowed values for the `<datatype>CoordinateSystem` field come from a list of restricted keywords, as listed in the sections below. If no value from the list of restricted keywords fits, there is always the option to specify the value as follows:

- **Other:** Use this for other coordinate systems and specify further details in the `<datatype>CoordinateSystemDescription` field

If you believe a specific coordinate system should be added to the list of restricted keywords for MEG, EEG, or iEEG, please open a new issue on the bids-standard/bids-specification GitHub repository.

## MEG Specific Coordinate Systems

Restricted keywords for the `<datatype>CoordinateSystem` field in the `coordinatesystem.json` file for MEG datasets:

- **CTF**: ALS orientation and the origin between the ears
- **ElektaNeuromag**: RAS orientation and the origin between the ears
- **4DBti**: ALS orientation and the origin between the ears
- **KitYokogawa**: ALS orientation and the origin between the ears
- **ChietiItab**: RAS orientation and the origin between the ears

Note that the short descriptions above do not capture all details, There are detailed extensive descriptions of these EEG coordinate systems on the FieldTrip toolbox web page

## EEG Specific Coordinate Systems

Restricted keywords for the `<datatype>CoordinateSystem` field in the `coordsystem.json` file for EEG datasets:

- **CapTrak**: RAS orientation and the origin between the ears

Note that the short descriptions above do not capture all details, There are detailed extensive descriptions of these EEG coordinate systems on the FieldTrip toolbox web page.

## iEEG Specific Coordinate Systems

Restricted keywords for the `<datatype>CoordinateSystem` field in the `coordsystem.json` file for iEEG datasets:

- **Pixels**: If electrodes are localized in 2D space (only x and y are specified and z is n/a), then the positions in this file must correspond to the locations expressed in pixels on the photo/drawing/rendering of the electrodes on the brain. In this case, coordinates must be (row,column) pairs, with (0,0) corresponding to the upper left pixel and (N,0) corresponding to the lower left pixel.

- **ACPC:** The origin of the coordinate system is at the Anterior Commissure and the negative y-axis is passing through the Posterior Commissure. The positive z-axis is passing through a mid-hemispheric point in the superior direction. The anatomical landmarks are determined in the individual's anatomical scan and no scaling or deformations have been applied to the individual's anatomical scan. For more information, see the ACPC site on the FieldTrip toolbox wiki.

## Image-based Coordinate Systems

The transformation of the real world geometry to an artificial frame of reference is described in `<datatype>CoordinateSystem`. Unless otherwise specified below, the origin is at the AC and the orientation of the axes is RAS. Unless specified explicitly in the sidecar file in the `<datatype>CoordinateUnits` field, the units are assumed to be mm.

### Standard template identifiers

Coordinate System	Description
ICBM452AirSpace	Reference space defined by the "average of 452 T1-weighted MRIs of normal young adult brains" with "linear transforms of the subjects into the atlas space using a 12-parameter affine transformation" <a href="https://www.loni.usc.edu/research/atlas">https://www.loni.usc.edu/research/atlas</a>
ICBM452Warp5Space	Reference space defined by the "average of 452 T1-weighted MRIs of normal young adult brains" "based on a 5th order polynomial transformation into the atlas space" <a href="https://www.loni.usc.edu/research/atlas">https://www.loni.usc.edu/research/atlas</a>
IXI549Space	Reference space defined by the average of the "549 (...) subjects from the IXI dataset" linearly transformed to ICBM MNI 452. Used by SPM12. <a href="http://www.brain-development.org/">http://www.brain-development.org/</a>
fsaverage[3 4 5 6 sym]	NOT RECOMMENDED, please use <b>fsaverage</b> without modifiers. Images were sampled to the FreeSurfer surface reconstructed from the subject's T1w image, and registered to an fsaverage template
fsaverage	The <b>fsaverage</b> is a dual template providing both volumetric and surface coordinates references. The volumetric template corresponds to a FreeSurfer variant of MNI305 space. The <b>fsaverage</b> atlas also defines a surface reference system (formerly described as fsaverage[3 4 5 6 sym]).
fsaverageSym	The <b>fsaverage</b> is a dual template providing both volumetric and surface coordinates references. The volumetric template corresponds to a FreeSurfer variant of MNI305 space. The <b>fsaverageSym</b> atlas also defines a symmetric surface reference system (formerly described as <b>fsaveragesym</b> ).



Coordinate System	Description
fsLR	The <b>fsLR</b> is a dual template providing both volumetric and surface coordinates references. The volumetric template corresponds to MNI152NLin6Asym. Surface templates are given at several sampling densities: 164k (used by HCP pipelines for 3T and 7T anatomical analysis), 59k (used by HCP pipelines for 7T MRI bold and DWI analysis), 32k (used by HCP pipelines for 3T MRI bold and DWI analysis), or 4k (used by HCP pipelines for MEG analysis) fsaverage_LR surface reconstructed from the T1w image.
MNIColin27	Average of 27 T1 scans of a single subject <a href="http://www.bic.mni.mcgill.ca/ServicesAtlases/Colin27Highres">http://www.bic.mni.mcgill.ca/ServicesAtlases/Colin27Highres</a>
MNI152Lin	Also known as ICBM (version with linear coregistration) <a href="http://www.bic.mni.mcgill.ca/ServicesAtlases/ICBM152Lin">http://www.bic.mni.mcgill.ca/ServicesAtlases/ICBM152Lin</a>
MNI152NLin2009[a-c][Sym Asym]	Also known as ICBM (non-linear coregistration with 40 iterations, released in 2009). It comes in either three different flavours each in symmetric or asymmetric version. <a href="http://www.bic.mni.mcgill.ca/ServicesAtlases/ICBM152NLin2009">http://www.bic.mni.mcgill.ca/ServicesAtlases/ICBM152NLin2009</a>
MNI152NLin6Sym	Also known as symmetric ICBM 6th generation (non-linear coregistration). Used by SPM99 - SPM8. <a href="http://www.bic.mni.mcgill.ca/ServicesAtlases/ICBM152NLin6">http://www.bic.mni.mcgill.ca/ServicesAtlases/ICBM152NLin6</a>
MNI152NLin6ASym	A variation of MNI152NLin6Sym built by A. Janke that is released as the MNI template of FSL. Volumetric templates included with HCP-Pipelines correspond to this template too. See doi:10.1016/j.neuroimage.2012.01.024.
MNI305	Also known as avg305.
NIHPD	Pediatric templates generated from the NIHPD sample. Available for different age groups (4.5–18.5 y.o., 4.5–8.5 y.o., 7–11 y.o., 7.5–13.5 y.o., 10–14 y.o., 13–18.5 y.o. This template also comes in either -symmetric or -asymmetric flavor. <a href="http://www.bic.mni.mcgill.ca/ServicesAtlases/NIHPD-obj1">http://www.bic.mni.mcgill.ca/ServicesAtlases/NIHPD-obj1</a>
OASIS30AntsOASISAnts	<a href="https://figshare.com/articles/ANTs_ANTsR_Brain_Templates/915436">https://figshare.com/articles/ANTs_ANTsR_Brain_Templates/915436</a>
OASIS30Atropos	<a href="https://mindboggle.info/data.html">https://mindboggle.info/data.html</a>
Talairach	Piecewise linear scaling of the brain is implemented as described in TT88. <a href="http://www.talairach.org/">http://www.talairach.org/</a>
UNCInfant	Infant Brain Atlases from Neonates to 1- and 2-year-olds. <a href="https://www.nitrc.org/projects/pediatricatlas">https://www.nitrc.org/projects/pediatricatlas</a>
UNCInfant[0 1 2]V[21 22 23]	NOT RECOMMENDED, please use <b>UNCInfant</b> without modifiers. Infant Brain Atlases from Neonates to 1- and 2-year-olds. <a href="https://www.nitrc.org/projects/pediatricatlas">https://www.nitrc.org/projects/pediatricatlas</a>

The following template identifiers are retained for backwards compatibility of BIDS implementations. Their use is NOT RECOMMENDED for new BIDS datasets and tooling, but their presence MUST NOT produce a validation error.

Coordinate System	Recommended identifier
fsaverage[3 4 5 6 sym]	fsaverage[Sym]
UNCInfant[0 1 2]V[21 22 23]	UNCInfant

### Nonstandard coordinate system identifiers

The following template identifiers are RECOMMENDED for individual- and study-specific reference spaces. In order for these spaces to be interpretable, **SpatialReference** metadata MUST be provided, as described in Common file level metadata fields.

In the case of multiple study templates, additional names may need to be defined.

Coordinate System	Description
individual	Participant specific anatomical space (for example derived from T1w and/or T2w images). This coordinate system requires specifying an additional, participant-specific file to be fully defined. In context of surfaces this space has been referred to as <b>fsnative</b> .
study	Custom space defined using a group/study-specific template. This coordinate system requires specifying an additional file to be fully defined.

### Non-template coordinate system identifiers

The **scanner** coordinate system is implicit and assumed by default if the derivative filename does not define any **space-<label>**. Please note that **space-scanner** SHOULD NOT be used, it is mentioned in this specification to make its existence explicit.

Coordinate System	Description
scanner	The intrinsic coordinate system of the original image (the first entry of <b>RawSources</b> ) after reconstruction and conversion to NIfTI or equivalent for the case of surfaces and dual volume/surface files.

## Appendix IX: Entities

This section compiles the entities (key-value pairs) described throughout this specification, and describes each.

A general introduction to entities is given in the section on file name structure.

The ordering of entities and whether it is allowed, OPTIONAL, or REQUIRED for each is given in the Entity Table.

### sub

Full name: Subject

Format: **sub**-<label>

Definition: A person or animal participating in the study.

### ses

Full name: Session

Format: **ses**-<label>

Definition: A logical grouping of neuroimaging and behavioral data consistent across subjects. Session can (but doesn't have to) be synonymous to a visit in a longitudinal study. In general, subjects will stay in the scanner during one session. However, for example, if a subject has to leave the scanner room and then be re-positioned on the scanner bed, the set of MRI acquisitions will still be considered as a session and match sessions acquired in other subjects. Similarly, in situations where different data types are obtained over several visits (for example fMRI on one day followed by DWI the day after) those can be grouped in one session. Defining multiple sessions is appropriate when several identical or similar data acquisitions are planned and performed on all -or most- subjects, often in the case of some intervention between sessions (for example, training).

### task

Full name: Task

Format: **task**-<label>

Definition: Each task has a unique label that MUST only consist of letters and/or numbers (other characters, including spaces and underscores, are not allowed). Those labels MUST be consistent across subjects and sessions.

## acq

Full name: Acquisition

Format: `acq-<label>`

Definition: The `acq-<label>` key/value pair corresponds to a custom label the user MAY use to distinguish a different set of parameters used for acquiring the same modality. For example this should be used when a study includes two T1w images - one full brain low resolution and one restricted field of view but high resolution. In such case two files could have the following names: `sub-01_acq-highres_T1w.nii.gz` and `sub-01_acq-lowres_T1w.nii.gz`, however the user is free to choose any other label than `highres` and `lowres` as long as they are consistent across subjects and sessions. In case different sequences are used to record the same modality (for example, RARE and FLASH for T1w) this field can also be used to make that distinction. At what level of detail to make the distinction (for example, just between RARE and FLASH, or between RARE, FLASH, and FLASHsubsampling) remains at the discretion of the researcher.

## ce

Full name: Contrast Enhancing Agent

Format: `ce-<label>`

Definition: The `ce-<label>` key/value can be used to distinguish sequences using different contrast enhanced images. The label is the name of the contrast agent. The key `ContrastBolusIngredient` MAY be also be added in the JSON file, with the same label.

## rec

Full name: Reconstruction

Format: `rec-<label>`

Definition: The `rec-<label>` key/value can be used to distinguish different reconstruction algorithms (for example ones using motion correction).

## dir

Full name: Phase-Encoding Direction

Format: `dir-<label>`

Definition: The `dir-<label>` key/value can be used to distinguish different phase-encoding directions.

## run

Full name: Run

Format: `run-<index>`

Definition: If several scans of the same modality are acquired they MUST be indexed with a key-value pair: `_run-1`, `_run-2`, ..., `_run-<index>` (only nonnegative integers are allowed for the `<index>`). When there is only one scan of a given type the run key MAY be omitted.

## mod

Full name: Corresponding Modality

Format: `mod-<label>`

Definition: The `mod-<label>` key/value pair corresponds to modality label for defacing masks, for example, `T1w`, `inplaneT1`, referenced by a `defacemask` image. For example, `sub-01_mod-T1w_defacemask.nii.gz`.

## echo

Full name: Echo

Format: `echo-<index>`

Definition: Multi-echo data MUST be split into one file per echo. Each file shares the same name with the exception of the `_echo-<index>` key/value. Please note that the `<index>` denotes the number/index (in the form of a nonnegative integer) of the echo not the echo time value which needs to be stored in the field `EchoTime` of the separate JSON file.

## recording

Full name: Recording

Format: `recording-<label>`

Definition: More than one continuous recording file can be included (with different sampling frequencies). In such case use different labels. For example: `_recording-contrast`, `_recording-saturation`.

## proc

Full name: Processed (on device)

Format: `proc-<label>`

Definition: The `proc` label is analogous to `rec` for MR and denotes a variant of a file that was a result of particular processing performed on the device. This is useful for files produced in particular by Elekta's MaxFilter (for example, `sss`, `tsss`, `trans`, `quat` or `mc`), which some installations impose to be run on raw data because of active shielding software corrections before the MEG data can actually be exploited.

## space

Full name: Space

Format: `space-<label>`

Definition: The `space` label (`*[_space-<label>]_electrodes.tsv`) can be used to indicate the way in which electrode positions are interpreted. The `space` label needs to be taken from the list in Appendix VIII.

## split

Full name: Split

Format: `split-<index>`

Definition: In the case of long data recordings that exceed a file size of 2Gb, the `.fif` files are conventionally split into multiple parts. Each of these files has an internal pointer to the next file. This is important when renaming these split recordings to the BIDS convention.

Instead of a simple renaming, files should be read in and saved under their new names with dedicated tools like MNE, which will ensure that not only the file names, but also the internal file pointers will be updated. It is RECOMMENDED that `.fif` files with multiple parts use the `split-<index>` entity to indicate each part.

## Changelog

## v1.4.1 (2020-10-13)

- [INFRA] minor robustness enhancements to pdf build shell script #642 (yarikoptic)
- [FIX] consistent CoordinateSystem fields for ephys #641 (sappelhoff)
- [INFRA] set up github action to detect latin phrases #636 (Remi-Gau)
- [ENH] Add a definition for "deprecation" #634 (sappelhoff)
- [MISC] consolidate BIDS citations in introduction #630 (sappelhoff)
- [FIX] URI "definition" and recommendation #629 (Remi-Gau)
- [FIX] change remaining latin expressions (etc and i.e.) #628 (Remi-Gau)
- [FIX] replace "e.g.," by "for example" #626 (Remi-Gau)
- [FIX] arrays of 3D coordinates MUST supply numeric values in x, y, z order #623 (sappelhoff)
- [FIX] Accidentally swapped Neuromag/Elekta/MEGIN cross-talk & fine-calibration filename extensions #621 (hoechenberger)
- [FIX] improve HED documentation #619 (VisLab)
- [INFRA] Move MRI section headings up a level #618 (tsalo)
- [INFRA] SCHEMA: Declare entities by concept names, add entity field for filename components #616 (effigies)
- [FIX] Change wrong text references from \*CoordinateSystemUnits to \*CoordinateUnits #614 (sappelhoff)
- [ENH] Describe arbitrary units in Common Principles #606 (tsalo)
- [FIX] Clarify data types and requirement levels for all JSON files #605 (sappelhoff)
- [INFRA] downgrade github-changelog-generator to 1.14.3 due to issue with 1.15.2 #600 (sappelhoff)
- [FIX] tighter rules for sharing MEG cross-talk and fine-calibration .fif files #598 (sappelhoff)
- [MISC] Add tsalo as a BIDS maintainer #597 (tsalo)
- [FIX] clarify definition of events in common principles #595 (sappelhoff)
- [INFRA] use --release-branch option in github-changelog-generator #594 (sappelhoff)
- [ENH] Define "modality" and clarify "data type" #592 (effigies)
- [FIX] Adjust index definition to be nonnegative integer #590 (nicholst)
- [MISC] fix links, make json object links consistent, fix pandoc rendering #587 (sappelhoff)
- [FIX] Fix link in Common principles #583 (tsalo)
- [ENH] Specify how to share cross-talk and fine-calibration for Neuromag/Elekta/MEGIN data #581 (sappelhoff)
- [ENH] Specify echo and run indices are nonnegative integers in schema #578 (tsalo)
- [ENH] add optional presentation software name, version, OS, and code to events.json #573 (Remi-Gau)
- [ENH] added PPG as an accepted channel type for EEG, MEG and iEEG #570 (robertoostenveld)
- [INFRA] Move entity definitions to a separate page #568 (tsalo)
- [INFRA] enable pandoc emojis for the pdf build #562 (sappelhoff)
- [INFRA] Auto adjust table fences before PDF conversion #560 (sebastientourbier)
- [ENH] Support run and acq entities in behavior-only data #556 (tsalo)
- [FIX] Clarify requirement levels for TSV metadata fields #555 (sappelhoff)
- [FIX] Reorganize rec, ce entities, \_defacemask #550 (emdubre)
- [FIX] Clarify Upper-casing of Channels.tsv Channel Type #548 (adam2392)
- [ENH] Extend date time information to include optional UTC syntax, warn about FIF requirements #546 (sappelhoff)
- [FIX] clarify that \<physio|stim>.json is REQUIRED #542 (sappelhoff)
- [FIX] Replace all non-breaking spaces with vanilla spaces #536 (nicholst)

- [FIX] Clarify indices are nonnegative integers. #535 (nicholst)
- [FIX] Clarify use of session entity in file names #532 (Moo-Marc)
- [ENH] Add the ability of users to specify an explicit HED.xml schema for validation. #527 (VisLab)
- [FIX] clarify that scans.json is allowed and recommended #523 (sappelhoff)
- [INFRA] add copyright holder to license. #521 (sappelhoff)
- [FIX] clarify XXXCoord\* in the coordinate systems appendix #520 (sappelhoff)
- [ENH] Update beh/ specification to contrast with any neural recordings #515 (effigies)
- [Fix] 'segmentation' spelling in 05-derivatives/03-imaging.md #514 (rwblair)
- [FIX] restructure and clarify \*\_physio/\*\_stim section #513 (sappelhoff)
- [FIX] clarify file formats in EEG, iEEG #511 (sappelhoff)
- [Fix] Add links and release dates to pre GH changelog, fix formatting #509 (sappelhoff)
- [FIX] Clarify that acq\\_time in scans.json refers to first data point acquired #506 (tsalo)
- [INFRA] make circle artifact link a GH action, point to pdf #505 (sappelhoff)
- [FIX] Typos in DECISION-MAKING file #504 (tsalo)
- [ENH] Add Commenting on a PR to CONTRIBUTING.md #490 (franklin-feingold)
- [FIX] clarify MEG empty-room recording naming conventions #480 (sappelhoff)
- [INFRA] Convert entity table to yaml #475 (tsalo)
- [FIX] Recommend SI units formatting to adhere to CMIXF-12 #411 (sappelhoff)

#### v1.4.0 (2020-06-11)

- [FIX] Clarify language on unsetting a key/value pair #495 (nicholst)
- [ENH] optionally allow LICENSE file #483 (sappelhoff)
- [INFRA] linkchecker - ignore github pull and tree URLs #477 (yarikoptic)
- [ENH] Allow fractional seconds in scans file datetimes #470 (tsalo)
- [MISC] Maintainers - Scope responsibility #467 (franklin-feingold)
- [FIX] Align tables in MRI section #465 (sappelhoff)
- [FIX] Drop \\_part- reference from example, introduce \\_split- entity #460 (sappelhoff)
- [FIX] clarify participants tsv+json with examples and recommendations #459 (sappelhoff)
- [FIX] Remove BESA from list of restricted keywords of EEG coordsystems #457 (sappelhoff)
- [INFRA] add steps for release protocol (PDF upload) #455 (sappelhoff)
- [FIX] Add reference to PDF on front page of specification #452 (nicholst)
- [INFRA] Add conditional for link-checking releases #451 (franklin-feingold)
- [FIX] unordered list formatting in BEP018 #449 (sappelhoff)
- [FIX] fix inconsistencies for task label between sections #446 (Remi-Gau)
- [FIX] update DECISION-MAKING.md document with new governance #441 (sappelhoff)
- [ENH] BEP 003: Common Derivatives #265 (effigies)
- [ENH] Add Glossary of terms/abbreviations used in the specification #152 (yarikoptic)



### v1.3.0 (2020-04-14)

- [INFRA] add zenodo badge to README #447 (sappelhoff)
- [MISC] Added contributors from VisLab #444 (VisLab)
- [FIX] Clarify snake\_case+CamelCase in TSV+JSON #442 (sappelhoff)
- [FIX] Eliminate web/online-specific language #437 (nicholst)
- [INFRA] ensure build\_docs\_pdf CircleCI job runs last #436 (sappelhoff)
- [INFRA] Add issue templates for GitHub #434 (sappelhoff)
- [INFRA] Get latest PDF build from CircleCI artifacts #433 (sappelhoff)
- [INFRA] Update release protocol #432 (franklin-feingold)
- [INFRA] add support for building PDF versions of the spec #431 (Arshitha)
- [ENH] Explicitly mention bids-validator and update link #428 (sappelhoff)
- [INFRA] use new bids-maintenance GitHub account to take over automatic work #426 (sappelhoff)
- [FIX] Unify section titles and table-of-contents entries #422 (nicholst)
- [INFRA] add # before heading in CHANGES #419 (sappelhoff)
- [INFRA] fix heading of auto changelog to be a markdown header #417 (sappelhoff)
- [ENH] Add OPTIONAL EthicsApprovals field to dataset description #412 (effigies)
- [ENH] BEP 018 - Genetic Information #395 (effigies)

### v1.2.2 (2020-02-12)

- [FIX] improve wording on data dictionaries #410 (sappelhoff)
- [MISC] update contributions by CPernet #409 (CPernet)
- [MISC] Add Sébastien Tourbier to contributors #394 (sebastientourbier)
- [FIX] consistent units description between EEG/MEG/iEEG. Clarify (derived) SI units + prefixes #391 (sappelhoff)
- [MISC] moved list of extension proposals to the main BIDS website #389 (robertoostenveld)
- [FIX] Typos and clarifications #386 (apjanke)
- [INFRA] Add watermark to drafts #383 (effigies)
- [MISC] Teon Brooks retiring moderator duties for BEP021 #381 (teonbrooks)
- [FIX] clarify that string is expected for HowToAcknowledge field in dataset\_description.json #380 (sappelhoff)
- [MISC] Typo and style #378 (TheChymera)
- [FIX] divide readme into 3 parts #374 (sappelhoff)
- [FIX] Refer to BIDS consistently, instead of "<Modality>-BIDS" #366 (sappelhoff)
- [FIX] Change recommended anonymization date from 1900 to 1925 #363 (alexrockhill)
- [FIX] Minor fixups of inconsistencies while going through a PDF version #362 (yarikoptic)
- [FIX] clarify that filters should be specified as object of objects #348 (sappelhoff)
- [FIX] Clarify channels.tsv is RECOMMENDED consistently across ephys #347 (sappelhoff)
- [FIX] Typo fix (contract -> contrast) in events documentation #346 (snastase)
- [MISC] rm TOC.md - seems no longer pertinent/used #341 (yarikoptic)

- [MISC] Move the PR template to a separate folder and improve contents #338 (jhlegarreta)
- [INFRA] Find npm requirements file in Circle #336 (franklin-feingold)
- [ENH] Clarify phenotypic and assessment data in new section #331 (sappelhoff)
- [MISC] add information about continuous integration checks to PR template #330 (sappelhoff)
- [FIX] Fix Common principles Key/value files section level #328 (jhlegarreta)
- [INFRA] Set the maximum heading length lint check to `false` #325 (jhlegarreta)
- [FIX] Number explicitly all cases in MRI field map section headers #323 (jhlegarreta)
- [FIX] Add SoftwareFilters to EEG sidecar example #322 (Remi-Gau)
- [MISC] Fixing Travis errors with Remark #320 (franklin-feingold)
- [INFRA] Link to doc builds in CI checks #315 (jasmainak)
- [MISC] Add BEP027 - BIDS Execution to BEP list #314 (effigies)
- [FIX] Add CBV and phase to Entity table #312 (tsalo)
- [FIX] Normalization of template-generated standard spaces #306 (oesteban)
- [ENH] Release protocol notes #304 (franklin-feingold)
- [INFRA] Adding contributor appendix sentence to PR template #299 (franklin-feingold)
- [ENH] Added discontinuous datatype for EEG and iEEG #286 (wouterpotters)
- [FIX] Clarify paragraph about custom data types #264 (effigies)

#### v1.2.1 (2019-08-14)

- FIX: repair link in anatomical MRI table #297 (sappelhoff)
- [ENH] Clarify requirements in Release Protocol #294 (franklin-feingold)
- [INFRA+FIX] Use linkchecker (from a dedicated docker image) to check all URLs #293 (yarikoptic)
- [ENH] Adding Contributors and updating contributions #284 (franklin-feingold)
- [MISC] update Code of Conduct contact #281 (franklin-feingold)
- [ENH] Update contributing guide and README to make discussion forums easy to find #279 (emdupre)
- [ENH] Starter Kit dropdown menu #278 (franklin-feingold)
- [ENH] BEP Update #277 (franklin-feingold)
- [INFRA] Update pipenv #274 (sappelhoff)
- [INFRA] Transpose the entity table and link to text anchors describing each entity #272 (sappelhoff)
- [ENH] Add Twitter badge to README and link to website to landing page #268 (franklin-feingold)
- [ENH] adding release guidelines #267 (franklin-feingold)
- [FIX] Common principles: Fix filename in inheritance principle #261 (Lestropie)
- [MISC] update modality references #258 (sappelhoff)
- [INFRA] adding logo to RTD #256 (franklin-feingold)
- [INFRA] add footer, replacing mkdocs/material advert with Github link #250 (sappelhoff)
- [MISC] rename logo files, add a README of where they come from, fix favicon #249 (sappelhoff)
- [MISC] updating MEG doc links, manufacturer names, and adding a missing MEG example #248 (sappelhoff)
- [ENH] Add favicon to RTD #246 (franklin-feingold)

- [MISC] Update Authors in BEP025 #241 (josator2)
- [MISC] Document BEPs that are not active anymore, but have not been merged #240 (sappelhoff)
- [FIX] remove ManufacturersAmplifierModelName (again) #236 (robertoostenveld)
- [INFRA] Update release protocol #235 (effigies)
- [INFRA] Enable version panel for quickly finding previous versions #232 (effigies)
- [FIX] Clarify Appendix II: The list of licenses only lists examples #222 (sappelhoff)
- [FIX] Trivial column header fix #220 (nicholst)
- [INFRA] Add clarification on merge methods to DECISION\_MAKING #217 (sappelhoff)
- [INFRA] Enable permalink urls to appear at (sub)section headings #214 (yarikoptic)
- [INFRA] bump up mkdocs-materials version #211 (sappelhoff)
- [MISC] Fix github username for @chrisgorgo #204 (chrisgorgo)
- [FIX] clarify example 3 in common principles (inheritance) #202 (sappelhoff)
- [MISC] Expand entity table for MEG/EEG/iEEG specific files #198 (sappelhoff)
- [FIX] make iEEG ToC more consistent with MEG and EEG #191 (robertoostenveld)
- [FIX] Clarify use of acq and task parameters in EEG, MEG, and iEEG #188 (sappelhoff)
- [FIX] clarify use of tools for CTF data renaming #187 (sappelhoff)
- [MISC] Add bep006 and bep010 to completed beps and fix links #186 (sappelhoff)
- [FIX] change file for definition of electrical stimulation labels from \_electrodes.json to \_events.json #185 (ezemikulan)
- [ENH] relax ieeg channel name requirements of letters and numbers only #182 (sappelhoff)
- [FIX] make MEG section headings and ToC consistent to the EEG and iEEG specs #181 (robertoostenveld)
- [FIX] make section headings and ToC consistent between meg and eeg specs #180 (robertoostenveld)
- [MISC] Spelling fixes #179 (DimitriPapadopoulos)
- [ENH] Alternative folder organization for raw, derived, and source data #178 (chrisgorgo)
- [INFRA] Adding instructions for naming PRs #177 (chrisgorgo)
- [MISC] Introducing Stefan Appelhoff as the first Maintainer #176 (chrisgorgo)
- [FIX] Clarify name of "BrainVision" format #175 (JegouA)
- [FIX] Fixes spelling of continuous #171 (emdupre)
- [FIX] Clarify continuous recording metadata fields #167 (effigies)
- [FIX] changed reference of dcm2nii to dcm2niix #166 (DimitriPapadopoulos)
- [FIX] Removing a leftover file #162 (chrisgorgo)
- [FIX] Specify marker file names for KIT data (MEG) #62 (monkeyman192)
- [FIX] Remove father-level for meg filetypes other than BTi/4D data #19 (teonbrooks)

## v1.2.0 (2019-03-04)

- [MISC] Adding Dimitri Papadopoulos Orfanos to the list of contributors #157 (DimitriPapadopoulos)
- [FIX] use "specification" not "protocol" to refer to BIDS #156 (yarikoptic)
- [FIX] Fix example misalignment #155 (DimitriPapadopoulos)
- [INFRA] Update Pipfile.lock #144 (franklin-feingold)

- [ENH] clarify decimal sep and numerical notation convention #143 (sappelhoff)
- [ENH] clarify encoding of README, CHANGES, TSV, and JSON files #140 (sappelhoff)
- [MISC] Update site\_name and release protocol #137 (franklin-feingold)
- [FIX] Example for IntendedFor was missing session indicator in the filename #129 (yarikoptic)
- [ENH] Add "\_phase" suffix to func datatype for functional phase data #128 (tsalo)
- [MISC] Update to Release\_Protocol.md #126 (franklin-feingold)
- [MISC] Update tag naming convention #123 (chrisgorgo)
- [ENH] Merge bep006 and bep010 #108 (sappelhoff)
- [MISC] Adding formal decision-making rules #104 (chrisgorgo)
- [FIX] number of small corrections to the specification #98 (robertoostenveld)

### v1.1.2 (2019-01-10)

- [MISC] Update 01-contributors.md #120 (oesteban)
- [ENH] Global fields in data dictionaries #117 (chrisgorgo)
- [MISC] Propose BEP026 MER #116 (greydongilmore)
- [FIX] Remove duplicate entries in MEG table #113 (franklin-feingold)
- [MISC] Propose BEP025 MIDS #110 (josator2)
- [FIX] repair links #106 (sappelhoff)
- [INFRA] Autogenerate CHANGES.md #103 (franklin-feingold)
- [MISC] Added contributor information #100 (jgrethe)
- [ENH] First(?) good practice recommendation. No excessive overrides in Inheritance principle #99 (yarikoptic)
- [MISC] adding extensions page #97 (choldgraf)
- [FIX] fix some urls (as detected to be broken/inconsistent) #95 (yarikoptic)
- [MISC] Change BEP numbers to include MRS #94 (Hboni)
- [FIX] harmonize and thus shorten templates etc #93 (yarikoptic)
- [MISC] put links and some text into README #91 (sappelhoff)
- [MISC] Add extension proposal in 01-introduction.md #88 (Hboni)
- [FIX] additional table to recap 'volume acquisition timing' #87 (Remi-Gau)
- [FIX] Small typo in "scanning sequence" DICOM tag #84 (Remi-Gau)
- [MISC] Update 01-contributors.md #83 (teonbrooks)
- [ENH] Added CBV contrast #82 (TheChymera)
- [MISC] Add CC-BY 4.0 license #81 (KirstieJane)
- [INFRA] Fix Travis break #80 (franklin-feingold)
- [ENH] allow \_dir for other EPI (func, dwi) sequences #78 (yarikoptic)
- [MISC] Added appendix to mkdocs and added some internal links #77 (franklin-feingold)
- [MISC] added JC Houde as contributor. #76 (jchoude)
- [MISC] Updated my contributions #75 (nicholst)
- [FIX] update HED appendix #74 (sappelhoff)

- [FIX] unicode: replace greek mu and omega by micro and ohm signs #73 (sappelhoff)
- [MISC] Update 01-contributors.md #72 (francopestilli)
- [ENH] add ce-\<label> for fmri data #70 (dasturge)
- [INFRA] pin pip version #68 (chrisgorgo)
- [MISC] Fix link in index #46 (chrisgorgo)
- [MISC] edit contributing guide #44 (Park-Patrick)
- [INFRA] Mkdocs configuration and RTD setup #42 (choldgraf)
- [MISC] Move definitions, compulsory, and raw/derivatives sections to principles #40 (chrisgorgo)
- [MISC] Remove duplicate section #39 (chrisgorgo)
- [INFRA] mkdocs rendering #36 (chrisgorgo)
- [MISC] Style consistency #35 (chrisgorgo)
- [MISC] Renaming files to conform with style guide #34 (chrisgorgo)
- [INFRA] enable travis cache #32 (chrisgorgo)
- [MISC] corrected link that is shown for CC0 #31 (robertoostenveld)
- [INFRA] added linter integration via travis #30 (chrisgorgo)
- [MISC] Cleanup #29 (chrisgorgo)
- [MISC] split intro, commons, mr, and meg into folder from specification.md #28 (teonbrooks)
- [MISC] Add some bids starter kit contributors #27 (KirstieJane)
- [MISC] Embedded footnotes into text #25 (franklin-feingold)
- [MISC] Making HED Strategy Guide link prettier #24 (fake-filo)
- [MISC] more cleanup #21 (chrisgorgo)
- [MISC] formatted MEG (8.4) #17 (franklin-feingold)
- [MISC] small fixes #16 (chrisgorgo)
- [MISC] Add meg img #14 (sappelhoff)
- [WIP] Cleaning up the specification #13 (chrisgorgo)
- [MISC] Adding code of conduct #6 (chrisgorgo)
- [INFRA] Renaming the main document #1 (chrisgorgo)

### 1.1.1 (2018-06-06)

- Improved the MEG landmark coordinates description.
- Replaced ManufacturersCapModelName in meg.json with CapManufacturer and CapManufacturersModelName.
- Remove EEGSamplingFrequency and ManufacturersAmplifierModelName from the meg.json.
- Improved the behavioral data description.

### 1.1.0 (2018-04-19)

- Added support for MEG data (merged BEP008)

- Added `SequenceName` field.
- Added support for describing events with Hierarchical Event Descriptors [4.3 Task events].
- Added `VolumeTiming` and `AcquisitionDuration` fields [4.1 Task (including resting state) imaging data].
- Added `DwellTime` field.

### 1.0.2 (2017-07-18)

- Added support for high resolution (anatomical) T2star images [4.1 Anatomy imaging data].
- Added support for multiple defacing masks [4.1 Anatomy imaging data].
- Added optional key and metadata field for contrast enhanced structural scans [4.1 Anatomy imaging data].
- Added `DelayTime` field [4.1 Task (including resting state) imaging data].
- Added support for multi echo BOLD data [4.1 Task (including resting state) imaging data].

### 1.0.1 (2017-03-13)

- Added `InstitutionName` field [4.1 Task (including resting state) imaging data].
- Added `InstitutionAddress` field [4.1 Task (including resting state) imaging data].
- Added `DeviceSerialNumber` field [4.1 Task (including resting state) imaging data].
- Added `NumberOfVolumesDiscardedByUser` and `NumberOfVolumesDiscardedByScanner` field [4.1 Task (including resting state) imaging data].
- Added `TotalReadoutTime` to functional images metadata list [4.1 Task (including resting state) imaging data].

### 1.0.1-rc1

- Added T1 Rho maps [4.1 Anatomy imaging data].
- Added support for phenotypic information split into multiple files [3.2 Participant key file].
- Added recommendations for multi site datasets
- Added `SoftwareVersions`
- Added `run-<run_index>` to the phase encoding maps. Improved the description.
- Added `InversionTime` metadata key.
- Clarification on the source vs raw language.
- Added `trial_type` column to the event files.
- Added missing `sub-<participant_label>` in behavioral data file names
- Added ability to store stimuli files.
- Clarified the language describing allowed subject labels.
- Added quantitative proton density maps.

## 1.0.0 (2016-06-23)

- Added ability to specify fieldmaps acquired with multiple parameter sets.
- Added ability to have multiple runs of the same fieldmap.
- Added FLASH anatomical images.

## 1.0.0-rc4

- Replaced links to neurolex with explicit DICOM Tags.
- Added sourcedata.
- Added data dictionaries.
- Be more explicit about contents of JSON files for structural (anatomical) scans.

## 1.0.0-rc3

- Renamed `PhaseEncodingDirection` values from "x", "y", "z" to "i", "j", "k" to avoid confusion with FSL parameters
- Renamed `SliceEncodingDirection` values from "x", "y", "z" to "i", "j", "k"

## 1.0.0-rc2

- Removed the requirement that TSV files cannot include more than two consecutive spaces.
- Refactor of the definitions sections (copied from the manuscript)
- Make support for uncompressed `.nii` files more explicit.
- Added `BIDSVersion` to `dataset.json`
- Remove the statement that `SliceEncodingDirection` is necessary for slice time correction
- Change dicom converter recommendation from `dcmstack` to `dcm2nii` and `dicm2nii` following interactions with the community (see <https://github.com/moloney/dcmstack/issues/39> and <https://github.com/neurolabusc/dcm2nii/issues/4>).
- Added section on behavioral experiments with no accompanying MRI acquisition
- Add `_magnitude.nii.gz` image for GE type fieldmaps.
- Replaced `EchoTimeDifference` with `EchoTime1` and `EchoTime2` (SPM toolbox requires this input).
- Added support for single band reference image for DWI.
- Added `DatasetDOI` field in the dataset description.
- Added description of more metadata fields relevant to DWI fieldmap correction.
- `PhaseEncodingDirection` is now expressed in "x", "y" etc. instead of "PA" "RL" for DWI scans (so it's the same as BOLD scans)
- Added `rec-<label>` flag to BOLD files to distinguish between different reconstruction algorithms (analogous to anatomical scans).
- Added recommendation to use `_physio` suffix for continuous recordings of motion parameters obtained by the scanner side reconstruction algorithms.

## 1.0.0-rc1

- Initial release

\* This Change Log was automatically generated by `github_changelog_generator`

## 1.1.1 (2018-06-06)

- Improved the MEG landmark coordinates description.
- Replaced `ManufacturersCapModelName` in `meg.json` with `CapManufacturer` and `CapManufacturersModelName`.
- Remove `EEGSamplingFrequency` and `ManufacturersAmplifierModelName` from the `meg.json`.
- Improved the behavioral data description.

## 1.1.0 (2018-04-19)

- Added support for MEG data (merged BEP008)
- Added `SequenceName` field.
- Added support for describing events with Hierarchical Event Descriptors [4.3 Task events].
- Added `VolumeTiming` and `AcquisitionDuration` fields [4.1 Task (including resting state) imaging data].
- Added `DwellTime` field.

## 1.0.2 (2017-07-18)

- Added support for high resolution (anatomical) T2star images [4.1 Anatomy imaging data].
- Added support for multiple defacing masks [4.1 Anatomy imaging data].
- Added optional key and metadata field for contrast enhanced structural scans [4.1 Anatomy imaging data]
- Added `DelayTime` field [4.1 Task (including resting state) imaging data].
- Added support for multi echo BOLD data [4.1 Task (including resting state) imaging data].

## 1.0.1 (2017-03-13)

- Added `InstitutionName` field [4.1 Task (including resting state) imaging data].
- Added `InstitutionAddress` field [4.1 Task (including resting state) imaging data].



- Added `DeviceSerialNumber` field [4.1 Task (including resting state) imaging data].
- Added `NumberOfVolumesDiscardedByUser` and `NumberOfVolumesDiscardedByScanner` field [4.1 Task (including resting state) imaging data].
- Added `TotalReadoutTime` to functional images metadata list [4.1 Task (including resting state) imaging data].

### 1.0.1-rc1

- Added T1 Rho maps [4.1 Anatomy imaging data].
- Added support for phenotypic information split into multiple files [3.2 Participant key file].
- Added recommendations for multi site datasets
- Added `SoftwareVersions`
- Added `run-<run_index>` to the phase encoding maps. Improved the description.
- Added `InversionTime` metadata key.
- Clarification on the source vs raw language.
- Added `trial_type` column to the event files.
- Added missing `sub-<participant_label>` in behavioral data file names
- Added ability to store stimuli files.
- Clarified the language describing allowed subject labels.
- Added quantitative proton density maps.

### 1.0.0 (2016-06-23)

- Added ability to specify fieldmaps acquired with multiple parameter sets.
- Added ability to have multiple runs of the same fieldmap.
- Added FLASH anatomical images.

### 1.0.0-rc4

- Replaced links to neurolex with explicit DICOM Tags.
- Added sourcedata.
- Added data dictionaries.
- Be more explicit about contents of JSON files for structural (anatomical) scans.

### 1.0.0-rc3

- Renamed `PhaseEncodingDirection` values from "x", "y", "z" to "i", "j", "k" to avoid confusion with FSL parameters

- Renamed `SliceEncodingDirection` values from "x", "y", "z" to "i", "j", "k"

## 1.0.0-rc2

- Removed the requirement that TSV files cannot include more than two consecutive spaces.
- Refactor of the definitions sections (copied from the manuscript)
- Make support for uncompressed `.nii` files more explicit.
- Added `BIDSVersion` to `dataset.json`
- Remove the statement that `SliceEncodingDirection` is necessary for slice time correction
- Change dicom converter recommendation from `dcmstack` to `dcm2nii` and `dicm2nii` following interactions with the community (see <https://github.com/moloney/dcmstack/issues/39> and <https://github.com/neurolabusc/dcm2niix/issues/4>).
- Added section on behavioral experiments with no accompanying MRI acquisition
- Add `_magnitude.nii.gz` image for GE type fieldmaps.
- Replaced `EchoTimeDifference` with `EchoTime1` and `EchoTime2` (SPM toolbox requires this input).
- Added support for single band reference image for DWI.
- Added `DatasetDOI` field in the dataset description.
- Added description of more metadata fields relevant to DWI fieldmap correction.
- `PhaseEncodingDirection` is now expressed in "x", "y" etc. instead of "PA" "RL" for DWI scans (so it's the same as BOLD scans)
- Added `rec-<label>` flag to BOLD files to distinguish between different reconstruction algorithms (analogous to anatomical scans).
- Added recommendation to use `_physio` suffix for continuous recordings of motion parameters obtained by the scanner side reconstruction algorithms.

## 1.0.0-rc1

- Initial release