

```
% AmirHosein Sadeghimanesh
% 2020 February, modified 2021 August
%
% This script contains the computations for finding the PSS representation
% of the multistationarity region of the LacI-TetR network introduced
% in Section 4.2 of the paper, which is depicted in Figure 6 parts b, c and
% d for degrees 2, 4 and 8 respectively. For different degrees, simply vary
% the value of 'd' below in PART 1.
%
% This file use the rectangular representation found by the script
% "Matlab_LacI_TetR_rectangular.m".
%
% PART 1
%
% Computing the target function for the optimization problem in PART 2.
%
n = 2;
syms x [1, n]
B = [0, 0.1; 0, 0.1];
d = 2;
[p, c] = multPoly(n, x, d);
f = intOverB(p, n, x, B);
%
% PART 2
%
% Computing the coefficients of the polynomial p of the PSS
% representation using SOS optimization by YALMIP and SEDUMI.
%
K = [0,0,1,1;
     0,1,1,2;
     0,2,1,3;
     1,1,2,2;
     1,2,2,3;
     1,3,2,4;
     1,4,2,5;
     1,5,2,6;
     2,2,3,3;
     2,3,3,4;
     2,4,3,5;
     2,5,3,6;
     2,6,3,7;
     2,7,3,8;
     3,4,4,5;
     3,5,4,6;
     3,6,4,7;
     3,7,4,8;
     3,8,4,9;
     4,5,5,6;
     4,6,5,7;
     4,7,5,8;
     4,8,5,9;
     4,9,5,10;
     5,7,6,8;
     5,8,6,9;
     5,9,6,10;
```

```

        6,9,7,10]*0.01;
a = SOSFitting(n, x, p, c, f, B, K);
disp(a)
% Saving the coefficient vector of the PSS polynomial in a txt file.
folder = 'C:\Home\PSS\Codes\LacI_TetR'; % replace this directory to the directory of
the folder you are using.
baseFileName = "PSS_degree_" + d + "_output_vector_a.txt";
fullFileName = fullfile(folder, baseFileName);
a_vec_file = fopen(fullFileName, 'w');
fprintf(a_vec_file, 'The coefficient vector of the polynomial p of the PSS
representation.\n\n');
fprintf(a_vec_file, 'a: ');
for i = 1:length(a)
    fprintf(a_vec_file, '%f,', a(i));
end
fclose(a_vec_file);
%
% PART 3
%
% Plotting the PSS approximation of the multistationarity region.
%
if n == 2
    fig = figure;
    fig.Units = 'pixels';
    fig.Position(1:2) = [100, 100];
    fig.Position(3:4) = [540, 460];
    % The main plot.
    fcontour(subs(p, c, a), [B(1, 1), B(1, 2), B(2, 1), B(2, 2)], 'LevelList', [0, 1],
'Fill', 'on')
    axis([B(1, 1) B(1, 2) B(2, 1) B(2, 2)])
    xticks(B(1, 1):(B(1, 2)-B(1, 1))/5:B(1, 2))
    yticks(B(2, 1):(B(2, 2)-B(2, 1))/5:B(2, 2))
    xlabel('$k_7$', 'interpreter', 'latex', 'FontName', 'Times New Roman', 'FontSize',
18)
    ylabel('$k_8$', 'interpreter', 'latex', 'FontName', 'Times New Roman', 'FontSize',
18)
    set(get(gca, 'ylabel'), 'rotation', 0)
    ax = gca;
    ax.XRuler.Exponent = 0;
    % colormap to only have three colors, below 0, between 0 and 1, and
    % above 1.
    cMap=[
        0.57, 0.88, 1;
        1, 1, 0];
    colormap(cMap); % generating the colormap for the colorbar.
    for idx = 1:size(K, 1)
        hold on
        fill([K(idx, 1), K(idx, 3), K(idx, 3), K(idx, 1), K(idx, 1)], [K(idx, 2), K
(idx, 2), K(idx, 4), K(idx, 4), K(idx, 2)], [1, 0.5, 0]);
        end
        hold off
    else
        disp("The dimension is higher than 2.")
    end
end
%
```

```

%%%%%%%%%%%%%%
% Functions %
%%%%%%%%%%%%%%
%
% Generating a matrix that each of its rows is an exponent vector of a
% monomial of degree at most d in n variables.
% The monomials are ordered with respect to the graded lexicographic
% monomial order.
%
function vMtx = allMonomials(n, d)
    % if isinteger(n)==0 || isinteger(d)==0 || n<=0 || d<0
    %     error("The input arguments are not valid. The first argument must be a
positive integer and the second argument must be a nonnegative integer.");
    % end
    vMtx = zeros(nchoosek(d+n, n), n);
    for idx = 1:nchoosek(d+n, n)-1
        vMtx(idx+1, :) = nxtMonomial(vMtx(idx, :));
    end
end
%
% Generating the next exponent vector of the next monomial in the graded
% lexicographic order.
%
function v = nxtMonomial(v, n)
    % if nargin>1
    %     if isinteger(n)==0 || n<1 || n~=length(v)
    %         error("The second input argument must be a positive integer equal to the
length of the first input argument.");
    %     end
    % else
    %     n=length(v);
    % end
    if nargin == 1
        n = length(v);
    end
    if n == 1
        v(1) = v(1)+1;
        return
    end
    idx1 = 0;
    for idx2 = n:-1:1
        if v(idx2) ~= 0
            idx1 = idx2;
            break;
        end
    end
    if idx1 == 0
        v(1) = 1;
        return
    end % so there is a first nonzero index.
    if idx1 ~= n
        v(idx1) = v(idx1)-1;
        v(idx1+1) = v(idx1+1)+1;
        return
    end % here we know idx1=n, so no point in keeping idx1 for saving a fixed known

```

number which is already saved at some variable.

```

    idx1 = 0;
    for idx2 = n-1:-1:1
        if v(idx2) ~= 0
            idx1 = idx2;
            break;
        end
    end
    if idx1 == 0
        v(1) = v(n)+1;
        v(n) = 0;
        return
    end % so there is a second nonzero index.
    tmpMem = v(n);
    v(n) = 0;
    v(idx1) = v(idx1)-1;
    v(idx1+1) = v(idx1+1)+tmpMem+1;
end
%
% The following function receives an integer, a symbol and another integer,
% respectively n, x and d. Then returns a polynomial in n variables of
% total degree d with all monomials. It also returns a second output which
% is a vector of coefficients of this polynomial.
%
function [p, c] = multPoly(n, x, d)
    %syms x [1,n] % remove x from the input arguments and ncomment this
    %line if you want the function generate the variables as x1 ... xn
    %itself.
    Mtx = allMonomials(n, d);
    c = str2sym(arrayfun(@(idx) "c" + join("_" + Mtx(idx,:), ""), 1:size(Mtx, 1)));
    p = sum(arrayfun(@(idx) c(idx).*prod(x.^Mtx(idx,:)), 1:size(Mtx, 1)));
end
%
% The following function receives a polynomial, an integer, a symbol and a
% hyperrectangle, respectively called p, n, x and B. Then it returns the
% n-dimensional integral of p in x over B.
%
function f = intOverB(p, n, x, B)
    f = p;
    for idx = n:-1:1
        f = int(f, x(idx), B(idx, :));
    end
end
%
% The following function is the SOS optimization formulating the
% PSS polynomial with the help of YALMIP and SeDuMi.
%
function PSSCoeffs = SOSFitting(n, x, p, c, f, B, K) %#ok<STOUT>
    for idx = 1:n
        eval("sdpvar " + string(x(idx)));
    end
    for idx = 1:length(c)
        eval("sdpvar " + string(c(idx)));
    end
    eval("p=" + string(p));

```

```

eval("F=" + string(f));
for idx1 = 1:n
    eval("[s" + idx1 + "B,c" + idx1 + "B]=polynomial([" + join(arrayfun(@(idx2) ✓
string(x(idx2)), 1:n)) + "],0)");
end
for idx1 = 1:size(K, 1)
    for idx2 = 1:n
        eval("[s" + idx2 + "K" + idx1 + ",c" + idx2 + "K" + idx1 + "]=polynomial✓
([" + join(arrayfun(@(idx3) string(x(idx3)), 1:n)) + "],0)");
    end
end
tmpStr = "Goal=[sos(p";
tmpStr = tmpStr + join(arrayfun(@(idx) "-s" + idx + "B*(" + string(x(idx)) + "-("✓
+ B(idx, 1) + "))*((" + B(idx, 2) + ")-" + string(x(idx)) + ")", 1:n), "") + ")\n";
tmpStr = tmpStr + join(arrayfun(@(idx) "sos(s" + idx + "B)", 1:n), ",\n") + ",\n";
tmpStr = tmpStr + join(arrayfun(@(idx1) ...
    "sos(p-1" + join(arrayfun(@(idx2) ...
        "-s" + idx2 + "K" + idx1 + "*(" + string(x(idx2)) + "-(" + K(idx1, idx2) + "))✓
*("(" + K(idx1, n+idx2) + ")-" + string(x(idx2)) + ")", 1:n), "") + ")\n" + ...
    join(arrayfun(@(idx2) "sos(s" + idx2 + "K" + idx1 + ")", 1:n), ",\n"), 1:size✓
(K, 1)), ",\n") + "];
eval(sprintf(tmpStr));
eval("solvesos(Goal, F, [], [" + ...
    join(arrayfun(@(idx1) "c" + idx1 + "B;", 1:n), "") + ...
    join(arrayfun(@(idx1) ...
        join(arrayfun(@(idx2) "c" + idx2 + "K" + idx1 + ";", 1:n), ""), 1:size(K, 1)),✓
"")) + ...
    join(arrayfun(@(idx1) string(c(idx1)), 1:length(c)), ";") + "]);
eval("PSSCoeffs=[" + join(arrayfun(@(idx) "value(" + string(c(idx)) + ")", 1:✓
length(c)), ",") + "]);
end
%
% End of the file.

```