

Medical Informatics

Lecture 11: SPARQL Querying

Dr Areti Manataki



Nanjing Medical University

In the previous lecture

- Turtle serialisation

```
@prefix dbpedia: <http://dbpedia.org/resource/> .
@prefix rdf: <http://www.w3.org/1999/02/22-rdf-syntax-ns#> .
@prefix : <http://usher.ed.ac.uk/medinf/vocab/> .

dbpedia:Leonardo_DiCaprio rdf:type :Actor ;
                           :playedIn dbpedia:The_Wolf_of_Wall_Street ,
                                       dbpedia:Inception .
```

- A short introduction to RDFS

```
@prefix terms: <http://usher.ed.ac.uk/medinf/vocab/> .
@prefix rdf: <http://www.w3.org/1999/02/22-rdf-syntax-ns#> .
@prefix rdfs: <http://www.w3.org/2000/01/rdf-schema#> .

terms:Giraffe rdf:type rdfs:Class .
terms:Herbivore rdf:type rdfs:Class .
terms:Giraffe rdfs:subClassOf terms:Herbivore .
```

In this lecture

- Triple & graph patterns
- SPARQL query structure
- Using OPTIONAL & solution modifiers
- Querying multiple sources

SPARQL

- **SPARQL** (SPARQL Protocol And RDF Query Language) is the standard way to access RDF data.
- The SPARQL query language works closely with the structure of RDF, making use of its graph model.
- It shares many features with SQL.
- It is an official W3C Recommendation
 - SPARQL 1.0 in 2008
 - SPARQL 1.1 in 2013
- Further info at <https://www.w3.org/TR/sparql11-query/>

Triple pattern

- Triple pattern: `subject predicate object .`
- Variables included for any of the subject, predicate or object.
 - `?actor uv:playedIn :Giant .`
- Triple patterns help us select triples from a given RDF graph.

Triple pattern

```
:JamesDean uv:bornIn ?city .
```

Data

```
:JamesDean uv:bornIn :MarionIndiana .
```

```
:JamesDean uv:playedIn :Giant .
```

```
:JamesDean uv:playedIn :EastOfEden .
```

```
:JamesDean uv:playedIn :RebelWithoutaCause .
```

Triple pattern

- Triple pattern: `subject predicate object .`
- Variables included for any of the subject, predicate or object.
 - `?actor uv:playedIn :Giant .`
- Triple patterns help us select triples from a given RDF graph.

Triple pattern

```
:JamesDean uv:playedIn ?film .
```

Data

```
:JamesDean uv:bornIn :MarionIndiana .
```

```
:JamesDean uv:playedIn :Giant .
```

```
:JamesDean uv:playedIn :EastOfEden .
```

```
:JamesDean uv:playedIn :RebelWithoutaCause .
```

Graph patterns

- Graph pattern: a collection of triple patterns, enclosed in { }

Graph pattern

```
{ :JamesDean uv:playedIn ?film .  
  ?film uv:directedBy ?director . }
```

Data

```
:JamesDean uv:playedIn :Giant .  
:JamesDean uv:playedIn :EastOfEden .  
:JamesDean uv:playedIn :RebelWithoutaCause .  
:Giant uv:directedBy :GeorgeStevens .  
:EastOfEden uv:directedBy :EliaKazan .
```

SPARQL Query Structure

list of prefixes

PREFIX pref: <URI>

...

result description

SELECT...

graph to search

FROM ...

query pattern

WHERE { ... }

query modifiers

ORDER BY...

A simple example

SPARQL query

```
PREFIX : <http://usher.ed.ac.uk/medinf/resource>
PREFIX uv: <http://usher.ed.ac.uk/medinf/vocab/>
SELECT ?film
WHERE { :JamesDean    uv:playedIn    ?film . }
```

Data

```
:JamesDean uv:bornIn    :MarionIndiana .
:JamesDean uv:playedIn  :Giant .
:JamesDean uv:playedIn  :EastOfEden .
:JamesDean uv:playedIn  :RebelWithoutaCause .
:ElizabethTaylor uv:playedIn :Giant .
:Giant uv:directedBy   :GeorgeStevens .
:EastOfEden uv:directedBy :EliaKazan .
```

Results

?film
:Giant
:EastOfEden
:RebelWithoutaCause

Another example

SPARQL query

```

PREFIX : <http://usher.ed.ac.uk/medinf/resource>
PREFIX uv: <http://usher.ed.ac.uk/medinf/vocab/>
SELECT ?film ?director
WHERE { :JamesDean uv:playedIn ?film .
        ?film uv:directedBy ?director . }

```

Results

Data

```

:JamesDean uv:bornIn :MarionIndiana .
:JamesDean uv:playedIn :Giant .
:JamesDean uv:playedIn :EastOfEden .
:JamesDean uv:playedIn :RebelWithoutaCause .
:ElizabethTaylor uv:playedIn :Giant .
:Giant uv:directedBy :GeorgeStevens .
:EastOfEden uv:directedBy :EliaKazan .

```

?film	?director
:Giant	:GeorgeStevens
:EastOfEden	:EliaKazan

Using OPTIONAL

SPARQL query

```

PREFIX : <http://usher.ed.ac.uk/medinf/resource>
PREFIX uv: <http://usher.ed.ac.uk/medinf/vocab/>
SELECT ?film ?director
WHERE { :JamesDean uv:playedIn ?film .
        OPTIONAL { ?film uv:directedBy ?director . }
      }

```

Data

```

:JamesDean uv:bornIn :MarionIndiana .
:JamesDean uv:playedIn :Giant .
:JamesDean uv:playedIn :EastOfEden .
:JamesDean uv:playedIn :RebelWithoutaCause .
:ElizabethTaylor uv:playedIn :Giant .
:Giant uv:directedBy :GeorgeStevens .
:EastOfEden uv:directedBy :EliaKazan .

```

Results

?film	?director
:Giant	:GeorgeStevens
:EastOfEden	:EliaKazan
:RebelWithoutaCause	

Using solution modifiers

- Query patterns generate an unordered collection of solutions.
- In order to reorganise the solutions, we use solution sequence modifiers.
- Commonly used solution sequence modifiers:
 - **DISTINCT**: ensures solutions in the sequence are unique
 - **ORDER BY**: puts the solutions in order
 - **LIMIT**: restricts the number of solutions
 - **OFFSET**: controls where the solutions start from in the overall sequence of solutions

Using solution modifiers: DINSTINCT

SPARQL query

```
PREFIX : <http://usher.ed.ac.uk/medinf/resource>
PREFIX uv: <http://usher.ed.ac.uk/medinf/vocab/>
SELECT ?actor
WHERE {?actor uv:playedIn ?film . }
```

Data

```
:JamesDean uv:bornIn :MarionIndiana .
:JamesDean uv:playedIn :Giant .
:JamesDean uv:playedIn :EastOfEden .
:JamesDean uv:playedIn :RebelWithoutaCause .
:ElizabethTaylor uv:playedIn :Giant .
:Giant uv:directedBy :GeorgeStevens .
:EastOfEden uv:directedBy :EliaKazan .
```

Results

?actor
:JamesDean
:ElizabethTaylor

Using solution modifiers: DINSTINCT

SPARQL query

```
PREFIX : <http://usher.ed.ac.uk/medinf/resource>
PREFIX uv: <http://usher.ed.ac.uk/medinf/vocab/>
SELECT DISTINCT ?actor
WHERE { ?actor uv:playedIn ?film . }
```

Data

```
:JamesDean uv:bornIn :MarionIndiana .
:JamesDean uv:playedIn :Giant .
:JamesDean uv:playedIn :EastOfEden .
:JamesDean uv:playedIn :RebelWithoutaCause .
:ElizabethTaylor uv:playedIn :Giant .
:Giant uv:directedBy :GeorgeStevens .
:EastOfEden uv:directedBy :EliaKazan .
```

Results

?actor
:JamesDean
:ElizabethTaylor

FROM-part

- By using the FROM clause you can specify against which RDF dataset(s) your SPARQL query will be run.
- This is typically a URI that is addressable via HTTP when the query is executed.

```
PREFIX foaf: <http://xmlns.com/foaf/0.1/>  
SELECT ?s ?o  
FROM <https://www.w3.org/People/Berners-Lee/card.rdf>  
WHERE { ?s foaf:family_name ?o }
```

FROM-part

- By using the FROM clause you can specify against which RDF dataset(s) your SPARQL query will be run.
- This is typically a URI that is addressable via HTTP when the query is executed.
- Multiple data sources can be used.

```
PREFIX foaf: <http://xmlns.com/foaf/0.1/>
SELECT ?s ?o
FROM <https://www.w3.org/People/Berners-Lee/card.rdf>
FROM <https://aic.ai.wu.ac.at/~polleres/foaf.rdf>
WHERE { ?s foaf:family_name ?o }
```

Conclusions

- Query structure
- Simple SPARQL queries

SPARQL query

```
PREFIX : <http://usher.ed.ac.uk/medinf/resource>  
PREFIX uv: <http://usher.ed.ac.uk/medinf/vocab/>  
SELECT ?film  
WHERE { :JamesDean    uv:playedIn    ?film . }
```

- Using OPTIONAL & solution modifiers
- Querying multiple sources
- In the next lecture we'll discuss the principles of Linked Data.

Acknowledgements

The content of these slides was originally created for the Medical Informatics course from The University of Edinburgh, which is licensed under a Creative Commons Attribution-ShareAlike 4.0 International (CC BY-SA 4.0) license.

These lecture slides are also licensed under a CC BY-SA 4.0 license.

