

Medical Informatics

Lecture 5: Translating an ER model into the Relational Model


Dr Areti Manataki



Nanjing Medical University

The story so far: ER model

- ER diagram basics



The story so far: ER model

- ER diagram basics:
 - Entity sets: rectangles
 - Relationship sets: diamonds connected to the entity sets
 - Attributes: ovals (with primary keys underlined)
 - Key constraints: arrows
 - Total participation: thick line
 - Weak entity sets: thick or double border
 - Entity hierarchies: ISA

The story so far: relational model

- Relational model basics

The diagram illustrates a relational table with the following structure:

mn	name	email	age
s0785212	Andrew	andrew@maths	19
s1253477	Jenny	jenny@inf	23
s1456381	Rhona	rhona@inf	18
s1489673	Stuart	stuart@law	34
s1473612	Alan	alan@law	20


Annotations:

- schema*: A red arrow points to the header row of the table.
- fields*: Four yellow arrows point from the word "fields" to the columns: **mn**, **name**, **email**, and **age**.
- tuples*: A purple bracket on the left side of the table encompasses the five data rows.

The story so far: relational model

- Relational model basics:
 - Relation schema: the format of a table, consisting of its name and the names and domains of each column
 - Relation instance: set of tuples matching the schema
 - Primary key: minimal set of fields uniquely identifying a tuple
 - Foreign key: values must be drawn from key values in the referenced table


The story so far: relational model



```
CREATE TABLE Takes (
  mn CHAR(8),
  cid CHAR(20),
  mark INTEGER,
  PRIMARY KEY (mn, cid),
  FOREIGN KEY (mn) REFERENCES Student,
  FOREIGN KEY (cid) REFERENCES Course
)
```

In this lecture

- Systematically transform an ER model (conceptual model) into a relational one (implementation in RDBMS)



```
CREATE TABLE Employee (
  nin CHAR(9),
  name VARCHAR(20),
  email VARCHAR(35),
  PRIMARY KEY (nin) )
```

```
CREATE TABLE Works_In (
  nin CHAR(9),
  did INTEGER,
  since INTEGER,
  PRIMARY KEY (nin, did),
  FOREIGN KEY (nin) REFERENCES Employee,
  FOREIGN KEY (did) REFERENCES Department
)
```

```
CREATE TABLE .....
```


In this lecture

- Systematically transform an ER model (conceptual model) into a relational one (implementation in RDBMS)
- Transforming:
 - entity and relationship sets
 - key and participation constraints
 - weak entity sets and hierarchies

Entity sets to tables

- Create a table for the entity set.
- Each attribute becomes a field, with the corresponding domain.
- The primary key is declared.

```
CREATE TABLE Employee (  
  nin CHAR(9),  
  name VARCHAR(20),  
  email VARCHAR(35),  
  PRIMARY KEY (nin) )
```




Relationship sets to tables

In the case where there are no constraints:

- Create a table for the relationship set.
- Specify a field (with the corresponding domain) for each of the following:
 - attributes of the relationship set
 - primary key attributes of each participating entity set.
- Declare primary key using all key attributes from participating entity sets.
- Declare foreign key constraints for all key attributes from participating entity sets.

Relationship sets to tables




```
CREATE TABLE Works_In (  
  nin CHAR(9),  
  did INTEGER,  
  since INTEGER,  
  PRIMARY KEY (nin, did),  
  FOREIGN KEY (nin) REFERENCES Employee,  
  FOREIGN KEY (did) REFERENCES Department  
)
```

Mapping relationship sets with key constraints – 1st approach

- Create a table for the relationship set.
- Specify a field (with the corresponding domain) for each of the following:
 - attributes of the relationship set
 - primary key attributes of each participating entity set.
- Declare primary key using only key attributes of the source entity set.
- Declare foreign key constraints for all key attributes from participating entity sets.

Mapping relationship sets with key constraints – 1st approach




```
CREATE TABLE Manages (  
  nin CHAR(9),  
  did INTEGER,  
  since INTEGER,  
  PRIMARY KEY (did),  
  FOREIGN KEY (nin) REFERENCES Employee,  
  FOREIGN KEY (did) REFERENCES Department  
)
```

Mapping relationship sets with key constraints – 2nd approach

- Main idea: no separate table, just include the information about the relationship set in the table for the entity set with the key (source entity set).
- In the table for the source entity set:
 - Specify a field (with the corresponding domain) for each of the following:
 - attributes of the relationship set
 - primary key attributes of the target entity set.
 - Declare foreign key constraints for the primary key attributes of the source entity set.

Mapping relationship sets with key constraints – 2nd approach




```
CREATE TABLE Department (  
  did INTEGER,  
  dname VARCHAR(20),  
  budget INTEGER,  
  nin CHAR(9),  
  since INTEGER,  
  PRIMARY KEY (did),  
  FOREIGN KEY (nin) REFERENCES Employee )
```

Mapping key and participation constraints

- In the table for the source entity set:
 - Specify a field (with the corresponding domain) for each of the following:
 - attributes of the relationship set
 - primary key attributes of the target entity set.
 - Declare foreign key constraints for the primary key attributes of the source entity set.
 - Declare those fields as NOT NULL.

Mapping key and participation constraints



```
CREATE TABLE Department (  
  did INTEGER,  
  dname VARCHAR(20),  
  budget INTEGER,  
  nin CHAR(9) NOT NULL,  
  since INTEGER,  
  PRIMARY KEY (did),  
  FOREIGN KEY (nin) REFERENCES Employee )
```


Mapping participation constraints

When not combined with a key constraint, a participation constraint cannot be captured in SQL, unless we use more advanced SQL.

Translating weak entity sets

- Create a table for the weak entity set.
- Specify a field (with the corresponding domain) for each of the following:
 - attributes of the weak entity set
 - attributes of the identifying relationship set
 - primary key attributes of the identifying owner.
- Declare a primary key that consists of the partial key of the weak entity set and the key attributes of the identifying owner.
- Declare foreign key constraints for the primary key attributes of the identifying owner, and set them **ON DELETE CASCADE**.

Translating weak entity sets




```
CREATE TABLE Dependent (
  pname VARCHAR(20),
  age INTEGER,
  cost INTEGER,
  nin CHAR(9),
  PRIMARY KEY (pname, nin),
  FOREIGN KEY (nin) REFERENCES Employee
  ON DELETE CASCADE )
```

Translating entity hierarchies

- Create a table for the superclass, as usual.
- For each subclass:
 - Create a table.
 - Specify a field (with the corresponding domain) for each of the following:
 - attributes of the subclass
 - primary key attributes of the superclass.
 - Declare the primary key to be the primary key of the superclass.
 - Declare foreign key constraints for the primary key attributes of the superclass.

Translating entity hierarchies

```
CREATE TABLE Hourly_Employee (  
  nin CHAR(9),  
  hourly_wage INTEGER,  
  PRIMARY KEY (nin),  
  FOREIGN KEY (nin) REFERENCES Employee  
)  
CREATE TABLE Contract_Employee (  
  nin CHAR(9),  
  contract_id INTEGER,  
  PRIMARY KEY (nin),  
  FOREIGN KEY (nin) REFERENCES Employee  
)
```



Conclusions

- We've seen how to systematically transform an ER model into a relational one.
- Some constraints expressed in the ER model might not be that easy to capture in the relational model.
- In some cases, there might be more than one possible transformations.
- In the next lecture we'll learn how to populate tables. We'll also get to write some simple queries in SQL.

Acknowledgements

The content of these slides was originally created for the Medical Informatics course from The University of Edinburgh, which is licensed under a Creative Commons Attribution-ShareAlike 4.0 International (CC BY-SA 4.0) license.

These lecture slides are also licensed under a CC BY-SA 4.0 license.

