

(7)

Thermal Conductivity Core Track Sheets

EXP	SITE	HOLE	CORE	SEC	OFFSET	NEEDLE or PUCK #	THERMCON VALUES	NOTES
392	U1580	A	1	4	73	V10702	No good measurements	
392	U1580	A	1R	4	67	"	No data	
			1R	5	65	"	No data	
392	U1580	A	2R	4	72	"	1.339 1.342	
392	U1580	A	1R	5	103	H11038	1.279 1.277 1.23	Good!
392	U1580	A	2R	5	48	"	1.367 1.397 1.389	
"	U1580	A	4R	3	71	"	1.481 1.512 1.503	
"	"	A	6R	3	43	"	1.510 1.555 1.566	
"	4	A	8R	3	72	"	1.612 1.575 1.611	
392	U1580	A	9R	3	137	"	1.544 1.564 1.559	
"	"	A	10R	3	122	"	1.671 1.625 1.622	

Thermal Conductivity Core Track Sheets

EXP	SITE	HOLE	CORE	SEC	OFFSET	NEEDLE or PUCK #	THERMCON VALUES	NOTES
392	U1580	A	12R	2	62cm	H11038	1.644 1.629 1.666	
392	U1580	A	13R	3	80cm	"	1.583 1.698 1.629	
"	"	"	14R	3	38cm	"	1.619 1.628 1.618	
392	1580	A	17R	2	115	"	1.667 1.585 1.550	
G	"	"	18R	6	70	"	1.790 1.782 1.785	
G	"	"	20R	2	93	"	1.710 1.662 1.663	
392	U1580	A	24R	3	43	"	1.968 1.927 1.959	Noticably higher
392	U1580	A	23R	2	80	"	2.192 2.178 2.180	
A	"	A	26R	1	39	"	1.853 1.848 1.862	
"	"	A	28R	4	87	"	2.146 2.127 2.135	
		"	29R	3	69	"	2.056 2.073 2.082	

28-2-22

(9)

Thermal Conductivity Core Track Sheets

EXP	SITE	HOLE	CORE	SEC	OFFSET	NEEDLE or PUCK #	THERMCON VALUES	NOTES
392	U 1580	A	30R	4	25	Puck H11038	1.974	
							1.958	
							1.994	
"	1580	A	31R	5	99	"	1.041	
							1.052	
							1.028	
"	U 1580	A	32R	3	80	"	1.077	
							1.070	
							1.072	
392	U 1580	A	33R	3	80	"	1.086	
							1.098	
							1.115	
392	U 1580	A	34R	4	90	"	1.123	
							1.166	
							1.160	
"	"	"	35R	3	61	"	1.102	
							1.122	
							1.128	
"	"	"	36R	3	96	"	1.473	
							1.336	
							1.372	
"	"	"	37R	5	37	"	1.152	
							1.174	
							1.185	
"	"	"	38R	6	60	"	1.418	
							1.421	
							1.427	
"	"	"	39R	5	95	"	1.423	
							1.335	
							1.319	
"	"	"	39R	5	108	"		

Thermal Conductivity Core Track Sheets

EXP	SITE	HOLE	CORE	SEC	OFFSET	NEEDLE or PUCK #	THERMCON VALUES	NOTES
392	u 1580	A	40R	3	93cm	H11038	1.529 1.515 1.536	short chunk (< 10 cm)
"	"	"	42R	2	52	"	1.855 1.841 1.854	
			45R	1	105	"	1.388 1.412 1.396	Salt water bath
"	"	"	48R	6	111	"	1.520 1.545 1.520	
"	"	"	49R	5	5	"	1.566 1.575 1.569	
"	"	"	50R	8	87	"	1.546 1.579 1.580	
"	"	"	51R	2	40	"	1.486 1.517 1.498	
"	"	"	52R	3	20	"	1.682 1.651 1.657	
"	"	"	53R	5	132	"	1.679 1.661 1.698	
"	"	"	54R	2	41	H51027	1.751 1.759 1.729	
"	"	"	55R	4	62	H11038	1.811 1.738 1.715	

Thermal Conductivity Core Track Sheets

EXP	SITE	HOLE	CORE	SEC	OFFSET	NEEDLE or PUCK #	THERMCON VALUES	NOTES
392	1580	A	56R	3	124cm	H11038	1.709 1.698 1.710	
392	1580	A	59R	1	62cm	"	1.462 1.483 1.504	
9	"	A	62R	1	84	"	1.544 1.542 1.574	
—	"	—	63R	4	12	"	1.748 1.749 1.714	
—	"	—	64R	3	66	"	1.743 1.736 1.774	
"	"	"	65R	1	24	"	1.721 1.796 1.790	
"	"	"	66R	5	40cm	"	1.613 1.668 1.701	
"	"	"	67R	4	140cm	"	1.613 1.591 1.599	
—	"	—	68R	4	23	"	1.825 1.825 1.799	
EOS								