CAD-based shape optimisation of the NASA CRM wing-body and nacelle-pylon intersections

Orest Mykhaskiv,^{*}Pavanakumar Mohanamuraly,[†] and Shenren Xu^{‡§}

Queen Mary University of London, London E1 4NS, UK

Mladen Banovic,[¶]Andrea Walther,^{||}

University of Paderborn, Warburger Str. 100, 33098 Paderborn, Germany

Jens-Dominik Müller^{**}

Queen Mary University of London, London E1 4NS, United Kingdom

Numerical shape optimisation is becoming an essential tool in aeronautic design. High-fidelity optimisation with many design variables will require gradient-based optimisation, adjoint methods can compute gradients very efficiently. CAD models are used on every stage of engineering product development from design to manufacturing. Ideally, the CAD system is kept inside the optimisation loop to maintain a consistent CAD model during the optimisation, as often practised in gradient-free optimisation. However, typical commercial CAD systems do not offer derivative computation, and standard CAD parametrisations may not define a suitable design space for the optimisation.

In this work, we use the automatically differentiated (AD) version of Open Cascade Technology (OCCT) CAD-kernel, which robustly provides accurate derivatives with respect to CAD parameters. The kernel is used to handle implicit CAD parametrisations, e.g. move control points of NURBS surfaces, automatically re-parametrise these surfaces, compute intersections between them and perform corresponding mesh morphing. We apply the differentiated CAD tool and parametrisation to high-fidelity aerodynamic shape optimisation of the NASA CRM wing-body intersection and exercise the CAD method for the pylon-nacelle modification.

I. Introduction

The common approach to describe and manipulate geometry is the CAD model which expresses a hierarchy of interacting elements (the feature tree) in a typically opaque, proprietary data-structure, and makes the skin of the shape available in an interchangeable Boundary Representation (BRep) such as NURBS patches in a STEP file. Consistency of geometry between the various disciplines in the analysis and design process is essential, and most gradient-free optimisation approaches would work with CAD ‘inside the loop’, i.e. use a parametrisation defined in CAD that defines the design space, allow the optimiser to modify this parameter set, and pass the geometry on through a BRep to mesh generators and ultimately analysis tools.

High-fidelity shape optimisation that seeks innovative, ‘out-of-the-box’ designs needs to employ very rich design spaces that allow detailed shape modifications, hence have a large number of design variables. Gradient-based optimisation is the only viable approach, and adjoint solvers are essential to compute the derivative of the objective function with respect to these design variables. A number of CAD-free parametrisation approaches are widely used, such as node-based methods, Free-Form Deformation, Radial Basis Functions or Hicks Henne bumps. While it is straightforward to compute the derivatives of the objective w.r.t. to

^{*}PhD student, School of Engineering and Materials Science, Queen Mary University of London, London E1 4NS, UK.

[†]PhD student, School of Engineering and Materials Science, Queen Mary University of London, London E1 4NS, UK.

[‡]Research Associate, School of Engineering and Materials Science, Queen Mary University of London, London E1 4NS, UK.

[§]Reader, School of Engineering and Materials Science, Queen Mary University of London, London E1 4NS, UK.

[¶]PhD Student, Institute of Mathematics, University of Paderborn, Warburger Str. 100, 33098 Paderborn, Germany

^{||}Professor, Institute of Mathematics, University of Paderborn, Warburger Str. 100, 33098 Paderborn, Germany

^{**}Senior Lecturer, School of Engineering and Materials Science, Queen Mary University of London, London E1 4NS, UK.

these design variables, the optimal shape only exists as a deformed mesh. Except for FFD, it also becomes complex to impose geometric or manufacturing constraints and to define a consistent surface between multiple disciplines such as fluid and structure. The most severe drawback is that the deformed shape needs to be manually transcribed back into CAD, not just a severe process bottleneck, but also a step where relevant design features may be lost.

To keep a valid CAD model in the gradient-based design loop requires the computation of CAD sensitivities, the derivative of surface mesh nodes w.r.t. design variables defined in the CAD model. This is currently not available from either commercial or open-source CAD kernels. We are hence developing a CAD framework which is based on Open Cascade (OCCT) CAD-kernel and is suitable for aerodynamic shape optimisation. The OCCT kernel was algorithmically differentiated and now can robustly provide derivatives of CAD models with respect to its design parameters,^{1,2} These gradients, also referred here as CAD sensitivities, are then coupled with adjoint CFD and provided to a gradient-based optimiser. The direct access to the source code of the kernel supports two separate approaches to parametrisation. Firstly, following an approach similar to common parametric CAD design with ‘user at the mouse’, we can construct an explicit parametric CAD models within OCCT using engineering design parameters (e.g. leading edge radius of the wing profile, thickness of the wing, span, etc.). This approach constructs a conventional and intuitive design space, but typically has only a limited number of parameters and may not contain important shape modes. Alternatively, we can derive an ‘implicit’ parametrisation automatically from the Boundary Representation (BRep) of an existing model. The BRep is expressed as a collection of NURBS patches, such as in the STEP or IGES files, the NURBS surfaces are controlled by the positions of their control points. Starting with the design space of freely displacing all control points, and imposing geometric constraints such as continuity between patches or thickness, radius, non-intersection, an effective basis for the restricted space can be constructed.²⁻⁴ This approach allows to refine design space by standard OCCT knot insertion algorithms, or coarsen it using OCCT derivatives as in Sec. III.B. In many cases, the NURBS surfaces are trimmed as a result of surface-surface intersections in the CAD software. This paper addresses these type of geometries.

This work is based and extends the previous authors publication.⁵ In this abstract we recall main results reported in the initial work and describe several new on-going developments. This abstract is organised as follows: Section II describes the main features of CAD-based method introduced in the previous work: use of adjoint CFD for aerodynamic shape optimisation, differentiation of CAD-kernel OCCT, treatment of geometries with intersections and optimisation results. In the Sec. III we describe upgrades to our optimisation design chain: recent advances of our CFD solver, improvement in calculation of CAD derivatives and finally implications for wing-faring optimisation and application of the method for nacelle-pylon geometry.

II. Existing Optimisation Design chain

II.A. Discrete adjoint equation

In a shape optimisation problem one seeks to minimise an objective function J such as the aerodynamic force like lift, drag, etc. with respect to design variables α . In CAD-based optimisation α will be parameters of the CAD model,

$$\min_{\alpha} J(U(X(\alpha)), X(\alpha), \alpha) \quad (1)$$

For immersed bodies, the optimisation is subject to the constraint of satisfying the flow equations,

$$R(U(X(\alpha)), X(\alpha)) = 0, \quad (2)$$

where R is the residual of the discretised conservation equations of the flow over the shape, in the following termed the ‘primal’. In this work we consider the system of Reynolds-Averaged Navier-Stokes equations with the state variable U and a computational mesh coordinates X , which in turn depend on the design parameters α . For these problems the number of design parameters is typically large which suggests to use the computationally efficient adjoint technique which could be derived by application of the chain rule of calculus to the system (1)-(2):

$$\frac{dJ}{d\alpha} = \left[\frac{dJ}{dX} + \nu^T f \right] \frac{\partial X}{\partial \alpha}, \quad (3)$$

where

$$f = -\frac{\partial R}{\partial X} \quad (4)$$

Figure 1. Left: B-spline surfaces forming the NASA CRM wing-body model; right: fairing subject to design changes (in orange).

and ν represents the solution of adjoint equations,

$$\left(\frac{\partial R}{\partial U}\right)^T \nu = \frac{\partial J}{\partial U}. \quad (5)$$

After computing the solution of primal and adjoint equations (2),(5), one can rewrite cost function gradient in terms of surface grid points derivatives:

$$\frac{dJ}{d\alpha} = \frac{dJ}{dX} \frac{dX}{dX_S} \frac{dX_S}{d\alpha}. \quad (6)$$

The first term in (6), usually called *CFD sensitivity*, represents the sensitivity of the objective function w.r.t the volume grid points X . These derivatives can be evaluated efficiently using (3) if the adjoint solution is available. In this work we use our in-house discrete adjoint solver STAMPS.⁶ The second term is the sensitivity of the surface to volume mesh deformation. The relation $X = X(X_S)$, describes the mesh morphing method employed to translate the surface mesh displacement into the volume. In the present work we use the inverse-distance weighted interpolation (IDW)⁷ to interpolate the surface displacements into the volume. We exactly differentiate the IDW mesh morpher to obtain the projected surface sensitivity from the volume sensitivity (also CFD sensitivity). The third term, the (*CAD sensitivity*), represents the derivative of the surface grid point positions X_S with respect to changes in the CAD model design parameters α . This term is calculated using the algorithmically differentiated version of OCCT.^{1,8}

The total sensitivity of (3) is then used in an optimisation loop.

$$\alpha^{(n+1)} = A\left(\alpha^{(n)}, \frac{dJ}{d\alpha}(\alpha^{(n)})\right), \quad (7)$$

where A is a suitable gradient-based optimisation algorithm. In the next sections, we describe the parametrisation and the influence of design parameters α on the intersection lines.

II.B. Parametrisation using NURBS

The geometry for the NASA CRM used in this work could be found on-line^a. We consider the implicit NURBS-based parametrisation to redesign the wing root fairing (the orange patch in Fig. 1). The other patches (in blue) i.e., the complete fuselage and the entire wing, remain fixed and are not changed during the design process. Therefore the control points positions of the fairing surface compose our CAD space.

In the reference description of the geometry this patch has an O-mesh type topology with 306 by 567 control points. It can be assumed that the fine control net is not a design intent, but results from a surface patch fitting process with default tolerances. To obtain a suitable design space, a first step is hence to re-parametrise it. We can use standard tools available in OCCT to replace the original intersection patch with a rectangular patch with 22 by 22 control points in the u and v parametric directions.

We maintain continuity between the design patch and the rest of the fuselage by restricting control points movement at the outer perimeter of the surrogate patch. This ensures the fairing and the fuselage remain G0 continuous. Therefore, only control points inside the green polygon in Fig. 2 are allowed to move and compose our final design space.

II.C. Dealing with intersection lines and corresponding surface mesh movement

Variation of the design parameters modifies the fairing surface, and hence the intersection with the fixed wing (Fig. 3). Therefore, we require a technique to propagate and sync these geometrical changes with the computational mesh.

^acommonresearchmodel.larc.nasa.gov

Figure 2. Original trimmed fairing from the inside (left); Untrimmed re-approximated fairing with 22x22 Control Points (middle); 169 design control points inside green polygon (right).

Using OCCT, we parse the STEP file of the entire NASA CRM and extract the BRep data for the design surfaces. Although we allow only the fairing surface to deform, we do consider the three adjacent wing patches (Fig. 2) as design patches, since the mesh on these surfaces will be modified due to intersection. We perform point inversions (projections) to determine positions of the surface mesh points on the CAD faces. As a result, each Cartesian (3d) mesh point acquires a pair of 2d parametric coordinates (u, v) on the corresponding design patch.

We use OCCT to determine the closed topological bounds of each CAD face: a combination of edges and intersection lines that encircle the face (Fig. 3). On these boundaries, we generate artificial mesh points (boundary mesh points also have 2d coordinates (u_b, v_b) belonging to the face) and use them to control the inner points mesh movement. Afterwards, any movement of the fairing triggers the following sequence of operations for each design face:

- (i) Using OCCT we recalculate all intersections and use them to reconstruct the topological boundaries of the face
- (ii) On each topological boundary (whether it is the intersection or the edge) we update the artificial boundary mesh points (u_b^{upd}, v_b^{upd}) . We maintain the constant arc-length ratio between each boundary point, based on 1d parametrisation of the corresponding boundary, ensuring uniform distribution in 2d parametric space (Fig. 3 (right))
- (iii) We apply the inverse distance weighting⁷(IDW) in 2d space of each face to morph the surface mesh points (u, v) . We use (u_b, v_b) and (u_b^{upd}, v_b^{upd}) as the boundary conditions for the method
- (iv) Finally, we use the updated parametric coordinates to calculate 3d Cartesian surface mesh displacements, and propagate them into the volume mesh also using IDW

Figure 3. Fairing movement (left); Initial position of the boundary mesh points in 2D parametric space (middle) and the updated positions used then for IDW (right).

The algorithm described above has a hierarchical structure when one starts with mesh displacement in 1d space, then these displacements are propagated within 2d parametric space of each surface and only then it is available as an updated 3d Cartesian mesh. Alternatively, the step (iii - smoothing in the parametric space of the face) could be substituted by application of IDW to the inner surface mesh directly in the 3d space. Here an additional step is required, namely the re-projection of updated 3D points back to the CAD surfaces. The method has advantages for multi-patch intersection cases, as mesh movement is no longer restricted within each patch. This would allow the surface mesh to "slide" between adjacent patches, avoiding undesirable mesh stretches appearing for the large deformations.

Figure 4. The fairing perturbation (left); The original and perturbed surface meshes (right).

Figure 5. The original (left) and perturbed (right) surface meshes in 2d parametric space of the fuselage.

In the Fig. 4 (left), we deliberately perturb several control points in the vicinity of the wing junction, such that the fairing creates a bump on the wing. The results of steps (ii)-(iii) (2d mesh smoothing) are shown for the parametric spaces of the fuselage and one of the wing faces in the Fig. 5 and Fig. 6 respectively. As a consequence of this 2d mesh movement, the corresponding 3d mesh 'follows' the CAD geometry as shown in Fig. 4 (right).

II.D. CAD Sensitivities including Intersections

As we build our framework for the intersections and the corresponding mesh movement algorithm on top of the differentiated OCCT, the complete process (i)-(iv) is also algorithmically differentiated. Therefore, the code is capable of providing exact gradients of the above mentioned algorithm with respect to the fairing control point movements. On the Fig. 7, the magnitudes of the CAD sensitivities with respect to the movement of three different control points in the direction towards the wing are shown. The variation of the first control point (red) corresponds to the finite step deformation showcased in the previous subsection. As a result, the CAD sensitivity resembles the mesh changes on both the fairing and the wing surface (Fig. 4). The second control point (blue) is located further from the junction, and due to the locality of NURBS, does

Figure 6. The original (left) and perturbed (right) surface meshes in 2d parametric space of the bottom wing's surface.

Figure 7. Magnitude of CAD Sensitivities w.r.t. three different control points.

not influence the surface at the wing junction. Therefore, the obtained sensitivity does not differ from the one, which would be obtained in the case without intersections. Finally, the last control point influence the intersection between all three wing surfaces (top, bottom and the trailing edge), hence the non-zero CAD derivatives are present on all of them.

The sensitivity results were compared against the finite differences and showed mutual agreement, thus providing confidence in the differentiated OCCT and algorithms used in this work. Note that finding a proper step size for finite differences is a challenging task therefore making differentiated codes a desirable feature for CAD-based methods. We divide our final 507 design variables into three blocks and apply vector differentiation consequently. The time spent on this is lower than for the corresponding low-fidelity CFD calculation.

III. Extension of the Optimisation Design chain

III.A. CFD solver and sensitivity

The flow and discrete-adjoint solver STAMPS, its numerical algorithms and application of automatic differentiation by source-transformation using Tapenade⁹ is described in the paper.^{5,6} Recently, hybrid distributed parallelisation of STAMPS primal and discrete adjoint solver using MPI and OpenMP was carried out using a zero-halo partitioning scheme.¹⁰ This allowed to consider finer mesh than in the initial work. The new NASA CRM mesh (previously used by SU2 solver¹¹) consists of 12M cells with 7.5M prismatic elements near wall, 4M tetrahedral cells outside the near wall region and 0.5M pyramids in between. In the Fig. 8 STAMPS parallel primal flow solver was used to calculate pressure contours for the NASA CRM configuration (run on 32 processor cores).

Figure 8. C_p contours for CRM wing-body configuration

III.B. NURBS reparametrisation using derivatives

Often the BRep of certain CAD models is not suitable for direct aerodynamic shape optimisation (Sec. II.B, Sec. III.E). It is ineffective to use control points to manipulate geometries that contain multiple tiny patches, or have very dense control nets. To alleviate this, we have devised generic re-parametrisation technique based on differentiated OCCT. To re-approximate the CRM fairing, we uniformly distribute points $T_i, i = \{1, \dots, m\}$ on the original patch (Fig. 9). As in the previous work, by means of OCCT we create a new face that contains much lower amount of control points. Second, particular to this work, we use these control points P of this new patch as design variables to minimise the following function:

$$\min_P I(P) = \sum_{i=1}^m \|X_i(P) - T_i\|^2, \quad P^{n+1} = P^n - t \cdot \frac{dI}{dP}.$$

Here, X_i is a projection of T_i on the new patch. This least-square distance minimisation allows to match original geometry to a high precision, but more importantly allows to use NURBS spaces suitable for optimisation. Same procedure could be used to fit CAD model to existing mesh or point cloud. This technique is used in this work to re-parametrise the fairing and the pylon as described later.

Figure 9. Points on the original fairing (green) and updated topology (grey).

III.C. Reverse mode for differentiated OCCT

Usually on each design iteration, the following matrix is calculated with differentiated OCCT:

$$\frac{dX_S}{d\alpha} = \frac{dX_S}{dP} = \underset{\downarrow}{\overset{3 \times N}{\overset{3 \times M}{\left(\begin{array}{cccc} \frac{\partial X_{S1}}{\partial P_1} & \frac{\partial X_{S1}}{\partial P_2} & \dots & \frac{\partial X_{S1}}{\partial P_N} \\ \vdots & \vdots & \ddots & \vdots \\ \frac{\partial X_{SM}}{\partial P_1} & \frac{\partial X_{SM}}{\partial P_2} & \dots & \frac{\partial X_{SM}}{\partial P_N} \end{array} \right)}}} \cdot \quad (8)$$

Here M and N correspond to a number of design mesh points and control points respectively. In the initial work,⁵ these CAD sensitivities were evaluated using the *traceless* forward vector mode of ADOL-C. Using the *traceless* forward vector mode, the derivatives w.r.t. an arbitrary number of design parameters (directions) are calculated directly together with the primal evaluation. Increasing the number of directions requires more computational time and memory. To avoid an issue of heavy memory usage, we took the advantage of ADOL-C vectorisation mechanism and subdivided our 169 design control points into 3 chunks. Each chunk was used to compute corresponding rows of the above mentioned matrix. Once the corresponding CAD sensitivity matrix is computed, it is multiplied with the CFD sensitivity to get the total gradient (6).

To further improve this process, in this study we investigate the *trace-based* reverse mode of ADOL-C. As opposed to the *traceless* functionality, here ADOL-C first generates an internal representation of the function to be differentiated. This internal representation is later evaluated using ADOL-C drivers to compute the desired gradient. Here the procedure is that the CFD sensitivity is evaluated first and then propagated as a derivative seed vector to reverse differentiated OCCT. Such an approach represents a full reverse mode differentiation of the complete design chain and has a potential to dramatically reduce the temporal complexity of the derivative computation.

III.D. Gradient-based optimiser

In the initial paper a steepest descent optimiser was driven by inviscid flow gradients to change the fairing-wing intersection and reduce the drag. In this work, we are using SLSQP optimiser (available in SciPy¹²) to include lift and moment constraints into optimisation. Recent advances in the CFD solver enable us to use high-fidelity viscous flow calculations during optimisation, which consequently will have an impact on the final shape of the fairing and will exercise our CAD-based method further.

III.E. Nacelle-Pylon intersections

Nacelle-Pylon junction is another component that can utilise the CAD-based intersection algorithm described above. As reported in,¹³ the re-engine of an aircraft is a common procedure, which involves substitution of an engine, for instance by more efficient model. In comparison to the original one, it could be of a different size and weight which poses a multidisciplinary problem. The new aero-structural design of the pylon and its mounting location with the engine have to be determined in order to improve the overall aircraft performance. To mimic this process, we consider the geometry of NASA-CRM high-lift configuration from

3rd drag prediction workshop ^b. Several other versions of nacelle-pylon geometries exist with different CAD topology, but the algorithm is generic and can be applied to any of them. In the Fig. 10 both complete aircraft

Figure 10. Nacelle-Pylon of the high-lift CRM configuration (left); design surfaces of the pylon in yellow (right).

and nacelle-pylon geometry is presented. Similarly to the fairing-wing case, we will consider movement of pylon control points (patches in yellow) when nacelle geometry is fixed (in blue). OCCT will be used to recompute occurring intersections with the engine casing, resemble this in the gradient calculation and perform corresponding mesh movement.

Figure 11. NURBS Control point net of the nacelle-pylon

Similarly to the fairing case, the geometry of the pylon obtained from the STEP file is not ideal for direct optimisation. As seen in Fig. 11, it consists of multiple patches with density of control points surpassing the density of the mesh. Hence, the re-parametrisation, as described in Sec. III.B will be also performed for several pylon patches.

IV. Summary and future work

We have shown the extension of CAD-based method for the optimisation of wing-body and nacelle-pylon intersections. The modification of surfaces control points allows to maintain CAD-models throughout the optimisation loop which is an enabling factor for a multi-disciplinary design process. NURBS design space could be tuned to be effective for the purposes of optimisation with proposed re-parametrisation technique. The OCCT CAD kernel that is algorithmically differentiated will be extended to use reverse mode of differentiation, which accelerates geometrical derivatives computations.

^b<https://hiliftpw.larc.nasa.gov/>

In this work we consider fairing-wing intersection optimisation under turbulent flow condition. Here the fairing intersection will play more significant role in the overall aerodynamic efficiency in comparison to the previously reported inviscid flow case.

Acknowledgements

The research leading to these results was co-funded by:

- IODA project - Industrial Optimal Design using Adjoint CFD. IODA is *Marie Skłodowska-Curie Innovative Training Network* funded by European Commission under Grant Agreement No. 642959.

References

- ¹M. Banovic, O. Mykhaskiv, S. Auriemma, A. Walther, H. Legrand, and J. D. Müller. Automatic differentiation of the Open CASCADE Technology CAD system and its coupling with an adjoint cfd solver. In *Optimization Methods and Software*, 2017.
- ²O. Mykhaskiv, M. Banovic, S. Auriemma, A. Walther, and J.-D. Mueller. NURBS-based and Parametric-based shape optimisation with differentiated CAD kernel. *Submitted to Computer-Aided Design & Applications*, 2017.
- ³Shenren Xu, Wolfram Jahn, and Jens-Dominik Müller. Cad-based shape optimisation with CFD using a discrete adjoint. *International Journal for Numerical Methods in Fluids*, 74(3):153–168, 2014.
- ⁴S. Xu, D. Radford, M. Meyer, and J.-D. Müller. CAD-based adjoint shape optimisation of a one-stage turbine with geometric constraints. ASME Turbo Expo 2015, June 2015. GT2015-42237.
- ⁵O. Mykhaskiv, P. Mohanamuraly, J.-D. Müller, S. Xu, and S. Timme. Cad-based shape optimisation of the nasa crm wing-body intersection using differentiated cad-kernel. In *35th AIAA Applied Aerodynamics Conference*, 2017.
- ⁶J.-D. Müller, P. Mohanamuraly, S. Xu, J. Hückelheim, and M. Gugala. STAMPS: a finite-volume solver framework for adjoint codes derived with source transformation AD. *AIAA-CP XX-2018*, 2018. submitted.
- ⁷J. A. Witteveen. Explicit and robust inverse distance weighting mesh deformation for CFD. In *48th AIAA Aerospace Sciences Meeting*, volume 165, 2010.
- ⁸S. Auriemma, M. Banovic, O. Mykhaskiv, H. Legrand, J.-D. Müller, and A. Walther. Optimisation of a U-bend using CAD-based adjoint method with differentiated CAD kernel. In *ECCOMAS Congress*, 2016.
- ⁹L. Hascoët and V. Pascual. The Tapenade Automatic Differentiation tool: Principles, Model, and Specification. *ACM Transactions On Mathematical Software*, 39(3), 2013.
- ¹⁰P. Mohanamuraly, Jan Hückelheim, and Müller Jens-Dominik. Hybrid parallelisation of an algorithmically differentiated adjoint solver. In *ECCOMAS Congress*, 2016.
- ¹¹F. Palacios, T. D. Economon, and J. J. Alonso. Large-scale aircraft design using su2. In *53rd AIAA Aerospace Sciences Meeting*, page 1946, 2015.
- ¹²Eric Jones, Travis Oliphant, and Pearu Peterson. Scipy: open source scientific tools for python. 2014.
- ¹³Anne Gazaix, Francois Gallard, Vincent Gachelin, Thierry Druot, Stephane Grihon, Vincent Ambert, Damien Guenot, Remi Lafage, Charlie Vanaret, Benoit Pauwels, et al. Towards the industrialization of new mdo methodologies and tools for aircraft design. In *18th AIAA/ISSMO Multidisciplinary Analysis and Optimization Conference*, 2017.