diminish, the difference in lift of the two planes occurs in an opposite manner, and the greater lift of the front one brings the machine up to an even keel once more.

This principle was tried out in the Eiffel laboratory on a model one tenth the size of a full-sized machine. The model was suspended at different angles of incidence and the experiments proved that it is possible to obtain longitudinal automatic stability by the arrangement of the planes shown in the diagram, whereby the rear plane is set at an angle of 3 degrees less than the front one. Moreover, it has been proved by experiment that when the planes both have the same angle, the lift of the second one is practically nothing. If the second plane is given 5 degrees less angle than the front one, there is no lift at all, but rather a downward force. If the second plane has less angle at $2\frac{1}{2}$ degrees than the front one, however, the lift produced is practically the same as that of the front one, so that in addition to obtaining automatic stability, a lift as great or greater than that obtained with an ordinary biplane is to be had. These results were obtained experimentally by Eiffel, and M. Drzewiecki constructed his machine in accordance with them. The forward wings can be turned about their axes in order to correct the lateral balance, and also to increase or decrease their angle of incidence when it is desired to rise or descend. Each wing is built about a central spar that turns in a ball bearing, and they can be operated separately or together by means of two levels. The twin vertical rudders on the ends of the rear wings can be turned inward across the machine at right angles with its axis, in order to form a brake when the machine makes a sudden descent. The motor used is a 70 horse-power Labor, and the machine is provided with oleo-pneumatic shock absorbers so arranged that the moment the wheels strike the ground a skid is thrown downward in contact with the soil, acting as a brake.

In the pages of the current SCIENTIFIC AMERICAN SUPPLEMENT will be found a discussion of the design from the aerodynamic standpoint.

New Types for the Japanese Navy

By Oscar Parkes

THE sister ships, "Kawachi," which was commissioned last year, and "Setsu," due for completion this year, are Japan's first all-big-gun ships to be built. Their predecessors, the "Aki" and "Satsuma," although often classed as dreadnoughts, were "intermediates" like the French "Danton" and the British "Lord Nelson" types, as they carried a main armament of four 12-inch and twelve 10-inch guns. The "Kawachi" is the normal development of these ships, and in general design seems an enlarged "Katori" with 12-inch guns replacing the 10-inch ones at the four corners of the superstructures, her twelve big guns being distributed after the earlier German fashion, now discarded in that and other navies in favor of the center-line arrangement. The "Kawachi" displaces some 20,750 tons, her dimensions being: Length over all, 481 feet; beam, 86 feet; and maximum draught, $28\frac{1}{4}$ feet. As originally designed she was to have carried fourteen 12-inch guns, with triple turret fore-and-aft and four twin positions amidships, but this was modified in the earlier stages of construction to twelve guns, twin turrets replacing the triple.

Her secondary battery of ten 6-inch pieces is disposed along the main deck, the end guns being recessed to secure axial fire. The 4.7 guns are mounted at the extreme bow and stern and in the superstructures. Five submerged torpedo tubes are carried, two bearing on each broadside, and one astern. These fire the 18-inch Whitehead weapon.

Her protection consists of the usual complete Japanese belt 12-inch amidships, tapering to 5-inch at the bow and stern, which reaches to the lower deck. Above this is a 9-inch strake amidships, reaching to the battery deck, and here the guns are behind 6-inch armor. A 3-inch armor deck incloses the engines and vitals. All the big-gun turrets are 9 inches thick and are reported to have 12-inch bases.

Both ships are turbine driven, the "Kawachi" having Curtis engines and the "Setsu" Parsons. Steam is generated in Miyabara boilers of standard Japanese pattern, and the designed horse-power of 25,500 is expected to produce a speed of over 20 knots. The coal supply is 900 tons normal and 2,500 maximum.

From our illustrations it will be seen that the ships present a somewhat unique appearance owing to the peculiar funnel spacing, and the two tripod masts of British pattern. The "Kawachi" was laid down at Kure in January, 1909, and the "Setsu" at Yokosuka in April, of the same year, but owing to financial reasons the last-named will not be completed until some time in 1913.

The battle-cruiser "Kongo" is one of a class of four ships of 27,500 tons displacement, and is under construction at the Vickers yard, England. Her dimensions are: Length, 704 feet; beam, 92 feet; and draught, $27\frac{1}{2}$ feet; and she carries an armament of eight 14-inch and sixteen 6-inch guns.

The big guns weigh 80 tons and are 45 calibers long. They are mounted four forward and four aft, the second and third turrets being raised "Michigan" fashion to allow an axial fire of four, and a broadside of eight guns. Along the upper deck are the 6-inch guns, and on the turret tops and upper works are distributed sixteen smaller quick-fire pieces.

Official details of the armor and protection are lacking, but reliable information gives the belt as 10-inch amidships, tapering fore and aft and terminating some distance short of the extremities.

Beneath this is an auxiliary belt which is very deep, protecting the ship against under-water attack. Above is a 7-inch strake extending from the first to the fourth turret bases, and the battery is behind 6-inch armor. The protective deck is 2 inches thick.

Her 14-inch guns are in $9\frac{3}{4}$ -inch turrets with armored bases of unknown, but probably similar, thickness. Driven by Parsons turbines of 60,000 nominal horse-power the "Kongo" has a designed speed of 25 knots, but 27 knots is expected of her. She carries 4,000 tons of coal and 1,000 tons of oil fuel.

Of the four ships, the "Kongo" was laid down in January, 1911, and is to be completed early in 1913. The "Haruna" (Curtis turbines), "Kirishima" and "Hiyei" are all building in Japan, and are due for completion between 1914 and 1916.

Dussaud's "Cold Light"

REPORTS of the experiments that M. Dussaud, a French savant, has been carrying on since 1909 at his "Cold Light Laboratory," have occasionally filtered into the newspaper columns. These reports, although as a rule exaggerated and perverted, have created considerable curiosity about Dussaud and his work. While the discoveries he has made will not "revolutionize electric lighting," as one recent press story predicted, the truth remains that he has applied some old principles to newly and ingeniously devised lighting apparatus, and has conceived some really startling applications for the latter. On three occasions communications by Dussaud have been presented to that august body, the French Academy of Sciences, by Prof. Branly of wireless telegraph fame.

Dussaud's apparatus, in its most typical form, consists essentially of the following parts.

1. A disk or wheel, with suitable mechanism for revolving it.
2. A number of tungsten filament lamps (usually 16 of them) spaced uniformly around the rim of the wheel. The lamps have small, closely coiled filaments, the whole filament structure in a single lamp occupying only 10 cubic millimeters, whereas the filament of an ordinary tungsten lamp encompasses a space some 2,000 times as great. The bulbs are small and round, similar to those commonly used in automobile headlights. A battery or low-voltage dynamo or transformer supplies the current.
3. A commutator, keyed to the shaft of the wheel, which causes each lamp successively to be lighted, for about $1/20$ of a second only, as it passes a certain fixed point near the periphery of the wheel.
4. A projecting lens so designed and placed as to receive the light-rays from the lamps, as each in turn passes by the fixed point where it is lighted.

For most purposes (moving-picture machine work for example) the wheel is revolved at a speed of 16 or more revolutions per second, so that the optical effect, due to persistence of vision, is that of a single steady, continuous light emanating from a point. For other purposes, as for example, in light-house beacons, the wheel is revolved more slowly, so that the light is seen to be a succession of flashes.

M. Dussaud finds it possible, by making the apparatus of little inertia and using special mechanism, to stop the wheel during the twentieth-of-a-second or so that each lamp is alight, so that the filament, while lighted, remains stationary at the exact focus of the lens. In the case of lamps with fairly large bulbs, when necessary, he mounts the filament off center, thus bringing it near enough to the inclosing glass of the bulb for the little incandescent coil to be in focus.

There may seem to be nothing startling in all this, but now comes the spectacular part of the performance. Using the apparatus above described. Dussaud finds that *more than twice* their normal voltage can be impressed on the lamps, yet they will last for several hours, while the light is obtained at an economy of electrical energy absolutely unknown with any other illuminating device using incandescent lamps. Thus, by doubling the impressed voltage, a lamp normally requiring 1 watt per candle-power is made to deliver light at an efficiency of 0.2 W. P. C.! He actually impresses $2\frac{1}{2}$ times the normal voltage in certain applications of the apparatus, such as medical examinations of interior parts of the body, and thereby raises the efficiency to 0.1 watt per candle, making a light twice as efficient as that of the yellow flaming arc.

While the efficiency is increased by "overvolting," the candle-power obtainable from a given bulb is in-

creased in still greater proportion. Thus a 200 per cent of normal voltage, a ten candle-power lamp, with a bulb less than two inches in diameter, emits a light of over 140 candles.

There are two advantages in Dussaud's scheme of using several lamps in rapid rotation, rather than a single lamp continuously. In the first place, the life of each filament is increased about twenty-fold, since it is in commission only one twentieth of the time. Secondly, the bulbs do not have a chance to get hot, a fact of great importance when they are used close up to moving-picture films or expensive lenses. Thus the light is a "cold light" in a double sense; very little heat is evolved in proportion to the light delivered, and even that little is so thoroughly dissipated that the apparatus remains cool.

The light intensity in a given direction may, of course, be increased by the use of a reflector in addition to the concentrating lens. Dussaud has two forms of apparatus employing reflectors; in one form the reflectors are rigidly attached to the lamps on the wheel, and revolve with it; in the other form there is a single fixed reflector mounted coaxially with the concentrating lens.

The distinguishing principle of Dussaud's "cold light" may best be stated in his own words:

"This method dissipates the objectionable *heating effect* of the electric current over a *maximum surface* where it offers no inconvenience, and concentrates the useful *luminous effect* on the minimum surface where it is needed."

With a consumption of only 160 watts of electrical energy—which will not produce even the smallest commercial arc light—Dussaud's apparatus produces results in projection work that would be impracticable with even the largest arcs manufactured.

The *applications* that Dussaud has discovered for his invention have done more to bring it into public notice than has the mere fact that the light is surpassingly efficient and intense. And the man is no dreamer. Already he has induced the French Minister of Instruction to give the "cold light" a thorough try-out in the public schools in connection with educational moving pictures exhibitions, while the Minister of War is considering its applicability to military search-lights.

Owing to the comparatively high expense of bulb renewals with the Dussaud system, as well as the necessity of moving parts, one is inclined to view with incredulity any claims that it will ever find much favor as a general illuminant, although the inventor rather naively suggests that it may be used with hollow inverted reflectors to produce beautiful indirect-lighting effects in drawing-rooms, conservatories, etc. Its province seems rather to embrace several specialized applications of electric lighting, to the development of which he is wisely confining his attention.

Among these special applications is that of endoscopy, or examinations of the internal organs of the body. So intense is the light that, when it is placed under the hand, the finger-bones and principal blood-vessels are clearly seen. In many cases it is believed that this powerful, cold light will enable bullets and other foreign substances to be located without the necessity of an X-ray examination. Letters can be read, it is said, even when wrapped in a dozen thicknesses of note paper and inclosed in an envelope.

A second application, already mentioned, is that of cinematography. Dussaud claims that his apparatus will do away with the cumbrous moving-picture machines and asbestos-lined cabinets now in use. No shutter will be necessary to cover the lens during the interval of $1/64$ of a second between two successive pictures, for that can be taken care of by the commutator, which causes the incandescent lamp to be extinguished during that interval. Moreover, the present commercial dimensions of the positives, $8\frac{1}{2} \times 10$ centimeters, can be reduced to 19×24 millimeters, owing to the possibility of using lenses of shorter focus; in fact, the "pocket moving-picture machine" is seen as an imminent possibility. The cost of the lamp bulbs with the Dussaud machine is about equal to the cost of current with an arc, but a considerable saving is said to result on account of the smaller investment with the former.

Paradoxically, the Dussaud "cold light" is produced at an unusually high filament temperature; indeed it is that very fact that makes the "cold light" possible. As high-temperature radiation is rich in the shorter wave lengths (blue, green, violet, ultra-violet) which are chemically the most active, it follows that the new light is a good one for photographic purposes, such as the making of silver prints. For flash-light photography it can be used on many occasions when magnesium powder would be considered a nuisance.

M. Dussaud is experimenting with a "cold light" machine in which the lamps and optical system are of quartz instead of glass, in order that the chemical and pathological effects of the ultra-violet rays may be studied.

Recent reports indicate that Dussaud's "concentrated cold light" has another field of practical usefulness in light-house beacons.