ception of the fact that flying under scientific guidance will be the future's safest form of rapid transit.

The Blériot machines are extremely graceful, and have changed little in form from year to year. Blériot has put his attention mainly on the constructive detail of the apparatus.

Plate III, Fig. 6, shows how the cables are attached to the main planes which they support, anchoring them to the elongated mast. The construction of the wings is charted in Figs. 1 to 12, Plate I. The main planes have been greatly strengthened in comparison with those of former years, and the convexity decreased.

(Fig. 2 shows the normal convexity of this apparatus.)

The attachment of the ribs to the body is very strong (A, B, Figs. 1, 3, 5), and the forward rib A is firmly set in a steel cylinder. Strong eye-plates (F) of steel serve for the attachment of the bracing cables (Fig. 6, Plate III; Fig. 12, Plate I).

Plate II.—Schematic representation of Pégoud's inverted and vertical loops.

1.—INVERTED FLIGHT:

- A—Start.
- B—Slightly downward direction taken by machine.
- C—"Rearing" by means of elevator; motor working.
- D—Gliding of inverted machine.
- E—Oblique position acquired by warping.
- F—Vertical position—acceleration of the head.
- G—Righting through use of elevator.

2.—THE CLOSED VERTICAL LOOP:

- H—Flight directed slightly downward.
- J—"Rearing" as in C, overturning.
- K, L—Righting by means of elevator. Gliding landing.

3.—PLAY OF FORCES INVOLVED IN TURNING:

- (a) Forces maintaining direction:
 - S—Gravity, 334 kilogrammes.
 - Z—Pull of propeller and kinetic energy, about 130 kilogrammes.
 - W—Resistance of wings and body.
- (b) Forces tending to change of direction:
 - D—Rudder pressure.
 - F—Centrifugal force.
 - R—Resultant force of P and Z.

Fig. 1.

Fig. 2.

Fig. 3.

Fig. 4.

Fig. 5.

Fig. 6.

Plate III.—Pégoud's safe Blériot monoplane.

FIG. 1.—Graphic determination of the center of gravity and of the amounts of inertia by means of the string polygon. FIG. 2.—Tail steering gear (enlarged dimensions). FIG. 3.—Detail of body with runner. FIG. 4.—Axle of carriage. FIG. 5.—Attachment of bracing cable to the back of wings. FIG. 6.—Waist of rudder.

Stellar Photometry*

By the Use of the Photo-Electric Cell

By W. F. Schulz

THE great sensitiveness of the photo-electric cell has been shown experimentally by Elster and Geitel,¹ by Nichols and Merritt,² and J. G. Kemp.³ From the results of these investigations it seemed that such a cell might be used to measure the light from fixed stars,

and its variation. The following is an account of some successful preliminary experiments in an attempt to make such measurements.

Several cells of the form shown in the accompanying diagram were prepared in the following way. The anode was a platinum wire about 0.5 millimetre in diameter, bent into a rectangular loop about $1 \times 1\frac{1}{2}$ centimeters on the side, the terminal passing through a glass sleeve 3 or 4 centimeters long. On the wall of the

tube facing the plane of this loop was a layer of potassium which formed the cathode. In order to have good contact at the cathode a layer of silver was deposited on and around the platinum terminal on the inside of the bulb. The bulb proper was about 5 centimeters in diameter. Potassium was distilled from a similar bulb into a second one, then poured into a tube just outside the bulb of the photo-electric cell and finally distilled upon the silver surface surrounding the cathode terminal.

* Reproduced from the *Astrophysical Journal*.

¹ *Physikalische Zeitschrift*, 13, 468, 1912.

² *Physical Review*, 34, 476, 1912.

³ *Ibid.* (2), 1, 274, 1913.

A little hydrogen gas was then introduced by heating a strip of palladium contained in a side tube. A potential-difference of 560 volts D. C. was applied to the electrodes P_1 and P_2 , P_1 being negative, with a lamp resistance of 3,000 ohms in series with the cell. When the circuit was closed for a few seconds the bright metallic colors of the hydrogen compound appeared at once on the potassium. There was a uniform soft glow over the entire surface of the metal, the rest of the bulb being non-luminous. It was found necessary to use a rather high potential-difference with a resistance. When a potential-difference of 300 volts with little or no resistance was applied, the discharge took the form of an arc rather than that of a glow, and the current rose rapidly, in one case even melting the electrode.

The circuit was broken when the surface of the potassium had assumed a brilliant violet-blue color and the hydrogen was carefully pumped out and was replaced by a small quantity of helium. All traces of oxygen were removed from the helium by passing it through a tube in which potassium was evaporated, before introducing it into the cell. The photo-electric cell was next connected in series with a sensitive galvanometer and the lamp resistance, and a potential-difference of 300 volts was applied. The light from a small gas flame was allowed to fall on the metal of the cell, and the pressure in the latter was varied by small steps until the galvanometer deflection was a maximum. The tube was then sealed off and proved to be constant for a period of several months.

For measuring very small intensities of light two different methods were used. In the colder winter months, especially in the open observatory, the temperature of the cell was so low that the natural leak through the dark cell was negligible, and the photo-electric current was measured directly by the rate of deflection of a quadrant electrometer. Toward the spring, however, when the temperature rose, the natural leak through the cell increased rapidly with the temperature, and it was found necessary to compensate this current by means of an independent circuit as shown in the diagram. The anode of the cell was connected to a storage battery of 160 cells, the negative terminal of which was earthed. The cathode was earthed through a high resistance R_1 and connected through a discharge key to one pair of quadrants of a Dolezalek electrometer. In the compensating circuit a battery of 3 cells sent current through a variable resistance R_2R_3 of 20,000 ohms, and the

negative terminal was earthed. The other pair of quadrants was connected to R_2R_3 by means of a traveling plug. By this arrangement the "dark current" could be completely neutralized. V_1 was varied from 150 to 320 volts. This was not quite the upper limit at which the cell could be used, but 350 volts was too large, and the photo-electric current reached a value beyond that of saturation. R_1 was a very high resistance of xylol with just a trace of pure alcohol. The sensitiveness of the electrometer was such that a potential difference of 20 volts on the needle and 1.4 volts between the quadrants produced a deflection of 120 millimeters at a scale distance of 2 meters. The deflections were very steady. The cell was tested by the light from a

Diagram of apparatus.

small incandescent lamp, which was cut down by passing it through two large crossed Nicol prisms. The cell was mounted in a light-tight box, carefully blackened inside, and closed by means of a shutter. A long closed tube was screwed into the opening of the box, and the lamp placed in this at 1.5 meters distance from the cell. The Nicols were inserted between lamp and cell, with a device for measuring and varying the angle between them. The candle-power of the lamp measured on a two-meter photometer with Lummer-Brodhup screen was approximately 0.003 at 6 volts. The deflections of the electrometer were easily read even when the planes of polarization made an angle of 85 deg. with each other. The intensity of the light which passed through an opening of 1 square centimeter area at the cell was therefore $0.003 \times \cos^2 85/1.5^2 = 0.000010$ candle meters.

It has been shown by Angström that the energy flowing from an amyl acetate lamp is approximately 10^{-8} gram calories per square centimeter at a distance of

1 meter. Assuming the Hefner unit and the candle-power to be equal and the distribution of energy to be the same in both lamps, we find that the quantity of energy incident on the cell is approximately 0.000010×10^{-8} gram calories or 4.19×10^{-6} ergs. This produces a deflection of the electrometer which is easily read. So far the light from two stars has been measured by means of this cell; in December 1912, that of *Capella* and in April 1913, that of *Arcturus*. The cell in its light-tight box was mounted on the 12-inch equatories at the observatory of the University of Illinois, and placed in such a position beyond the focal plane of the objective that the circle of illumination on the sensitive surface of the cell had an area of about 1 square centimeter.

On the cold December nights the natural leak through the cell was almost zero, and the photo-electric current was measured by the rate of the electrometer deflection. With 40 volts on the needle and 160 volts on the cell, the rate of deflection at a scale-distance of 2 meters was 20 millimeters in 30 seconds. With 200 volts on the cell, the rate was 18 millimeters in 20 seconds. These deflections were repeated without difficulty.

In April 1913, another set of readings was taken with the light from *Arcturus*. This time the dark current had to be compensated. With 60 volts on the needle and 250 on the cell, the deflection due to the photo-electric current alone was 22 millimeters. This was reduced to zero each time by varying the resistance R_3 . With 60 volts on the needle and 300 on the cell, the deflection when the cell was exposed to the light of *Arcturus* was 48 millimeters; with 60 volts on the needle and 325 on the cell the deflection was 190 millimeters; and with 80 volts on the needle and 325 on the cell the deflection was 248 millimeters. The sensitiveness of both cell and electrometer can be increased.

These measurements seem to show that it is possible to use the photo-electric cell for astrophysical investigations. The present research is being continued along various lines. It is planned to compare the sensitiveness of the photo-electric cell with that of the selenium cell, and to study the influence of temperature upon the "dark current," the effect of the wave-length of the incident light upon the lower limit of sensitiveness, and the use of various alkali metals for the sensitive layer.

These measurements were made at the suggestion of my friend Dr. Jakob Kunz, to whom I am deeply indebted for the benefit of his invaluable experience in making the cells and for assistance in conducting the experiments.

Flexible Metallic Tubing*

THE amount of attention recently attracted to oil fuel and to devices for storing and handling it may justify a brief account of an important manufacture which has rendered great services in regard to the transport of oil, and especially its transference into the tanks of ships. For many years tubes or hose made of rubber held the field for all purposes where great flexibility was essential. In cases where the employment of rubber was out of the question short lengths of rigid tube, with somewhat ungainly flexible leather joints, were substituted, and for certain requirements woven canvas hose did good service; but there were many purposes, especially those entailing the conveyance of oil, for which neither rubber nor any of the above substitutes could be used with advantage, and for which a tube of metal possessed of considerable flexibility was desirable.

When the new metal tubing was first brought into public notice the late Sir Frederick Bramwell said that the idea of a tube with a continuous joint from end to end was quite subversive of all preconceived theories of sound construction, and he admired the ingenuity of an invention which caused the joint to become tighter as the internal pressure increased. In the formation of the tubing a plain strip of steel or other metal is passed between a graduated set of mollets which bend it into external curves and at the same time cause the curved links to interlock while passing round the mandrel on which the tube is coiled. For certain purposes a thin thread of asbestos is at the same time tightly wound between each strand, so that the tube becomes a continuous interlocked ribbon of metal with a suitable packing along the joint. Flexibility is insured by the piston-like motion of a small corrugation within a larger one.

PREPARATION OF THE STRIP.

The metal strips, either of steel or of copper, are received from the manufacturers in the form of coils, hot-rolled, and are of various thickness and weights, ranging from $1\frac{1}{2}$ hundredweight to $3\frac{3}{4}$ hundredweight in steel, and from 2 hundredweight to $4\frac{1}{2}$ hundredweight in bronze. These coils when finished may be 1,000 feet or even in some cases 3,000 feet in length. The first step is to clean the strip thoroughly from any adherent scale or foreign matter, and for this purpose it has to be unwound and made up into a fresh coil in

such a way that the strands of metal no longer touch one another. The coil thus opened out is immersed in a tank or bath of dilute acid, in which it may remain for five or six hours, so as to dissolve away all the impurities and leave the metal surface bright and clean. From the acid bath the strip goes into an alkaline bath to neutralize the residual acid, being afterward well washed in clean water to remove all traces of the chemicals. It is then cold rolled to the exact thickness required, and bright annealed.

In the next operation the strip, which may be in some cases from three to five times the width needed for the tube-making, is passed through a machine that slits it up into any required number of narrow bands, each of which, as it leaves the cutters, is wound into fresh coils. It is possible to construct the tube of any tough metal in the form of strip, and copper, brass, nickel, and aluminium can all be employed for the purpose.

GALVANIZING AND SHAPING.

For the great majority of uses the steel strip has to be galvanized, to protect it from the action of the weather, and for this purpose it is washed in hot water and conveyed into a long, stoneware-lined bath in which it traverses the electrolyte, the speed at which it moves through the bath being regulated in such a way that the time elapsing between its entrance and exit just suffices to coat the metal with the requisite amount of zinc. From the galvanizing department it passes at once to the shaping machine, when the entire process of bending it and coiling it to form the tube is effected in one operation.

As the diameter of the finished tube may vary from 1-16 inch up to 12 inches, it will readily be understood that the machines fitted for this part of the work differ considerably in size and speed of drive. A very small tube like a quill will need but little power for its production, while a heavy machine will have to be employed for making a 12-inch tube from a plain strip 50 millimeters wide by 2 millimeters thick. Whatever the size of the finished tube may be, the mode of forming it is precisely the same, and involves the use of numerous sets of steel mollets which produce the necessary amount of corrugation and finally coil the strip round a mandrel of the requisite size. As it quits the machine the tube is received in a wooden trough, which must be sufficiently long to contain the entire length of the section. In certain sizes the completed tube may run to as much as 100 feet in length, and even the very large tubes, 10

inches and 12 inches in diameter, are occasionally made in lengths of 30 feet to 35 feet.

USES OF THE TUBING.

In many industries the adoption of metallic tubing which will not char and which is sufficiently rigid to withstand the application of heavy weights, has found a useful place. Thus for laundry purposes, in which rubber tubing was at one time employed to carry the gas or steam to hot irons, rubber has been superseded by metallic tubing. An advantage claimed for this form of tubing is that it will not kink, and thus cut off the supply of gas. Where rubber tube is in use to convey gas to a burner, as is often the case in chemical laboratories, the extinction of the gas at the burner, owing to kinks in the tube, is a frequent cause of serious leakages. For superheated steam flexible metallic tubing will resist pressures and temperatures quite beyond the range of possibility with rubber hoses, however carefully they may be armored with an external sheath of wire or metal. When manufactured in a special way the metallic tubing can be made to withstand extremely high pressure, and tubing has been supplied to the British Admiralty guaranteed to take a pressure of 5,000 pounds per square inch.

Mineral oil has a very destructive action on India-rubber, and partly in consequence of this fact, and partly owing to the possibilities of making the metal tubing of very large diameters up to 12 inches, the use of rubber for conveying oil has been almost wholly discontinued since the introduction of metallic tubing, which is in general use for pumping oil into the reservoirs from tank-steamers, and for the purpose of taking up oil at sea.

Mercury and Musts

THE influence of mercury on alcoholic fermentation has just been studied by M. P. Nottin. The presence of mercury in a liquid in a state of fermentation produces two distinct phenomena. The mercury feebly attacked by the natural acid must produce toxic salts, which, according to their dose, keep back or hinder entirely the development of the yeast. Secondly, the mercury as a metal increases the production of the yeast, because it continually removes from the must its carbonic acid by a phenomenon of a purely physical order, and thus allows the yeast to breathe and vegetate more easily. Platinum and porous substances produce the same effect.—*Chemical News*.

* Reproduced from the Engineering Supplement of the *London Times*.