Absorption of Gases in the Electric Discharge Tube

This content has been downloaded from IOPscience. Please scroll down to see the full text.

1920 Proc. Phys. Soc. London 33 73

(<http://iopscience.iop.org/1478-7814/33/1/309>)

View [the table of contents for this issue](#), or go to the [journal homepage](#) for more

Download details:

IP Address: 132.203.227.61

This content was downloaded on 03/10/2015 at 02:57

Please note that [terms and conditions apply](#).

VIII. *Absorption of Gases in the Electric Discharge Tube.*

By F. H. NEWMAN, M.Sc., A.R.C.Sc., University College, Exeter.

RECEIVED JULY 20, 1920.

ABSTRACT.

Various elements were deposited in a pure condition on the cathode in an electric discharge tube. To obtain a clean surface of the element, the latter was distilled in vacuum. An electric discharge was passed through nitrogen gas contained in the tube. Measurements were made to compare the amount of gas absorbed by the element in the tube with the quantity of electricity passing in the circuit. Potassium, sodium, mercury, cadmium, antimony, magnesium, calcium, zinc, tin, phosphorus, sulphur and iodine were tested in this way. The rates of absorption were very great with the last three elements. Hydrogen gas was also used in the tube, and absorption occurred with phosphorus, sulphur and iodine. The absorption of the gases is due principally to chemical action, and is attributed to the nitrogen and hydrogen assuming active modifications on the passage of an electric discharge, the gases being at low pressure.

1. INTRODUCTION.

THE present investigation is a development of the experiments described in "Proc." Roy. Soc., A., Vol. XC. (1914), and Proc. Phys. Soc., Vol. XXXII. (1920). In these Papers it has been shown that sodium, potassium and the liquid alloy of sodium and potassium absorb nitrogen when these metals are used as electrodes in the electric discharge tube. The gas is absorbed at a greater rate if the metal is used as the cathode. The quantity of gas absorbed, per unit quantity of electricity passing through the discharge tube, was measured at various pressures of the gas. No absorption occurred unless the surfaces of the metals were quite clean. Sodium and potassium were distilled in vacuum in order to obtain surfaces which were not contaminated. Other elements, in the molten condition, had been tested without success; this was traced to the contamination of the surfaces, and these elements are re-examined in the present work. The same apparatus, as described in the above Papers, was used, but the form of the discharge tube was changed, and is shown in Fig. 1. The electrodes *A* and *B* were of aluminium. To the end of the cathode *B* was attached a small disc of platinum foil. The

element under examination was placed at the bottom of the tube, and by distilling it in vacuum, a thin layer of the element was formed on the foil.

2. EXPERIMENTS.

A clean surface of the element having been formed on the cathode, a known quantity of nitrogen was admitted into the discharge tube. The method of measuring this amount of gas has been described in the previous Papers. The electric discharge was then passed through the gas, and the amount

FIG. 1

of hydrogen liberated in the voltameter gave a measure of the quantity of electricity passing in the circuit. The absorption of gas during the passage of the discharge was noted. In some cases it was necessary to maintain the discharge tube at a low temperature, by placing it in an enclosure surrounded with a freezing mixture. The nitrogen used in the experiments was prepared by allowing air to stand over phosphorus for two or three days. The hydrogen was obtained by electrolysis. Both gases were examined at various pressures, and the results obtained are shown in Tables I. and II.

3. ABSORPTION OF NITROGEN.

Lead, thallium and arsenic did not absorb nitrogen. The elements were tested with the gas at different pressures and temperatures.

TABLE I.—*Absorption of Nitrogen.*

Element.	Pressure in mms. Hg.	Temper- ature.	Volume of N ₂ absorbed in c.c. (A)	Volume of H ₂ liberated in Volta- meter in c.c. (B)	Ratio $\frac{A}{B}$	Pressures at which absorption takes place in mms. Hg.
Mercury	1.3 0.9 0.6	−13°C.	0.40 0.36 0.33	2.21 0.92 0.51	0.2 0.4 0.6	0.5–1.5
Cadmium	1.1 1.8	30°C.	0.18 0.29	0.13 0.21	1.4 1.4	1.1–1.8
Arsenic Lead Thallium	} No absorption					
Antimony	1.8 1.5	−15°C.	0.65 0.31	0.45 0.22	1.4 1.4	1.2–1.9
Magnesium	3.4 2.0 1.9 1.3	50°C.	0.07 0.17 0.31 9.68	0.11 0.19 0.16 0.24	0.6 0.9 1.9 2.8	1.0–4.3
Calcium	1.8 1.2	−12°C.	0.14 0.19	0.12 0.14	1.2 1.3	1.1–1.9
Zinc	1.7 1.5	−12°C.	0.13 0.20	0.10 0.14	1.3 1.4	1.2–1.8
Tin	1.7 1.2 0.9	0°C.	0.28 0.14 0.17	0.57 0.23 0.17	0.5 0.6 1.0	0.1–2.0
Phosphorus.....	13.3 10.1 7.3 4.0 2.5 1.0	−12°C.	0.37 0.27 0.29 0.14 0.15 0.27	0.03 0.03 0.04 0.05 0.07 0.13	12.3 9.0 7.2 2.8 2.1 2.1	X-Ray stage to 20 mms.
Sulphur	11.6 7.9 3.2 1.6	−12°C.	0.23 0.15 0.13 0.08	0.04 0.04 0.04 0.03	5.8 3.8 3.2 2.7	0.1–12.0
Iodine	16.4 12.2 8.3 4.1 1.9	−20°C.	0.44 0.29 0.27 0.31 0.23	0.08 0.07 0.08 0.11 0.11	5.5 4.1 3.4 2.8 2.1	1.0–18.0
Bismuth	1.7 1.4	−14°C.	0.43 0.22	0.36 0.17	1.2 1.3	1.1–1.8

TABLE II.—*Absorption of Hydrogen.*

Element.	Pressure in mm.s Hg.	Tempera- ture.	Volume of H, absorbed in c.c. (A)	Volume of H, liberated in volta- meter in c.c. (B)	Ratio $\frac{A}{B}$	Pressures at which absorption takes place in mm.s Hg.
Phosphorus ...	12.8	-12°C.	0.28	0.03	9.4	X-ray stage to 18.0 mm.s
	11.2		0.25	0.03	8.3	
	8.1		0.29	0.05	5.8	
	3.7		0.26	0.09	2.9	
	2.4		0.23	0.11	2.1	
Sulphur	12.1	-12°C.	0.37	0.05	7.4	0.5—12.0
	8.3		0.13	0.03	4.3	
	3.1		0.37	0.11	3.4	
	1.4		0.29	0.12	2.4	
Iodine	14.6	-20°C.	0.39	0.09	4.3	1.0—15.0
	11.8		0.40	0.12	3.3	
	7.3		0.23	0.07	3.3	
	3.1		0.25	0.09	2.8	
	2.3		0.27	0.11	2.5	

Mercury absorbed nitrogen when the pressure of the gas was between 0.5 mm. and 1.5 mm. of mercury, if the tube was kept at -13°C. The amount of gas which could be absorbed at a time was very small. When the discharge was stopped, and the tube heated to about 20°C., all the gas which had disappeared was re-liberated. After the surface of the mercury had been exposed to the atmosphere, no absorption occurred, which showed the importance of having a clean surface of the element. Stark* has noted that mercury, used as an electrode in the discharge tube, absorbs nitrogen and oxygen.

Cadmium absorbed the gas at ordinary temperatures, providing the pressure was between 1.1 mm. and 1.8 mm. of mercury. Most of it was re-liberated on heating the tube. The effect in this case may be due to occlusion of the gas within the metal. On the other hand, there may be a chemical compound of cadmium and nitrogen produced, which compound dissociates easily on the application of heat. The total amount of gas which was absorbed at a time was very small.

Antimony absorbed the gas at low temperatures if the pressure varied from 1.2 mm. to 1.9 mm. of mercury. The amount of gas which disappeared before it was necessary to

* "Phys. Zeit.," Vol. XIV., p. 417 (1913).

prepare a fresh surface was only 0.2 c.c., and the gas absorbed was evolved when the tube was heated to 50°C. Antimony resembles cadmium in this respect.

When magnesium is heated to a red heat it combines with nitrogen, forming a nitride of magnesium. This fact was utilised by Rayleigh* in the separation of nitrogen and argon. At ordinary temperatures there is no such combination. When magnesium was used as the electrode in the discharge tube, nitrogen was absorbed if the pressure of the gas was between 1.0 mm. and 4.3 mm. of mercury. At low pressures the rate of absorption was very high. This absorbed gas was not re-liberated when the tube was heated to 300°C. After about 4 c.c.s of the gas had disappeared, the contents of the tube were mixed with caustic soda, and boiled. Ammonia gas was evolved, showing that magnesium nitride had been formed in the tube. The absorption in this case is due to chemical action. It was possible to absorb about 4 c.c.s of gas at atmospheric pressure before the action ceased.

Soddy† has shown that when calcium is first heated in vacuo, gaseous compounds of carbon, hydrogen and oxygen are given off; if the heating be continued, absorption of the gases begins, accompanied by volatilisation of the calcium. Experiments were made by him on the power of calcium, to absorb different gases, and he found that all gases, except the argon group, were rapidly absorbed. In the discharge tube I found that nitrogen was absorbed at 12°C. if the pressure of the gas was between 1.1 mm. and 1.9 mm. of mercury. It was possible to absorb only 0.1 c.c. of gas at a time, but this small amount was due to the very thin layer of calcium deposited on the cathode. On heating the tube to 300°C. none of the gas was evolved. This suggests that chemical action accounts for the absorption in this case.

Zinc absorbed nitrogen at -12°C., providing the pressure of the gas varied from 1.2 mm. to 1.8 mm. of mercury. The total amount of gas which disappeared was very small, and most of it was re-liberated when the tube was heated.

Tin does not combine with nitrogen when it is heated in that gas, but the gas was freely absorbed by the metal in the discharge tube if the pressure was within the range 2.0 mm. — 0.1 mm. of mercury. The rate of absorption was uniform, and was large compared with that obtained with other metals.

* "Phil. Trans.," 186 (1895).

† "Proc." Roy. Soc., Ser. A., 78, p. 429 (1907).

It was possible to absorb 0.3 c.c. of gas at a time. When the tube was heated to 300°C. no gas was evolved from the metal, and the presence of a nitride of tin was found by the method described in the case of magnesium. This absorption of nitrogen by tin has not been observed previously.

Strutt* has shown that phosphorous absorbs nitrogen and hydrogen when an electric discharge is passed through a bulb containing this element. The gases were not re-liberated on heating, and he attributed the absorption to the formation of chemical compounds. The rate of absorption of these gases, compared with the quantity of electricity passing through the tube, is very great; and if phosphorus is placed in a discharge bulb the vacuum is kept very high. In the present experiments the discharge tube was maintained at -12°C., in order to minimise the production of phosphorus vapour. The actual rate of absorption was about 4 c.c.s (at atmospheric pressure) in 15 minutes; this rate decreased as the discharge continued, and the amount of gas which could be absorbed depended on the thickness of the phosphorus layer used in the experiment. As shown by Strutt, the gas was not re-liberated from the phosphorus when the tube was heated, and it appears that a chemical compound of nitrogen and phosphorus is formed.

With sulphur, a large rate of absorption was observed, and the absorption occurred over a range of pressures 12.0 mm.—0.1 mm. of mercury. By means of the discharge the pressure of the gas in the tube was lowered rapidly, and reached the X-Ray stage, provided a clean surface of sulphur was used on the cathode. When the sulphur was exposed to the atmosphere, the rate of absorption of the gas was less, and it was not possible to obtain such a final low-pressure in the tube. No re-liberation of the gas occurred when the contents of the tube were heated to 100°C. Of course the sulphur vaporised, but on allowing the contents to cool, the original volume was attained. This showed that chemical combination had occurred between the gas and sulphur. The absorption of the gas was greater if the film of sulphur on the cathode was formed by condensation of the vapour, than if the layer was produced by allowing melted sulphur to flow over the cathode.

The results obtained with iodine resembled those noted in the case of phosphorus. No absorption occurred if the

* "Proc." Roy. Soc., Ser. A., 87 (1912).

pressure of the gas was below 1 mm. of mercury. On account of the sublimation of iodine, the tube was maintained at -20°C . After the surface of the substance had been exposed to the atmosphere, the rate of absorption decreased. There was no re-liberation of the gas when the contents of the tube were heated to 100°C ., which indicated that the phenomenon was due to chemical action, and not to mere occlusion of the gas within the iodine.

The results obtained with bismuth were similar to those found with antimony. The discharge tube was maintained at -14°C ., and absorption occurred when the pressure was between 1.8 mm. and 1.1 mm. of mercury. Only 0.18 c.c. of gas was absorbed by any one surface, and all of the gas absorbed was evolved when the tube and its contents were heated to 40°C . The effect in this case appears to be due to occlusion.

4. ABSORPTION OF HYDROGEN.

As shown in Table II. the only elements which absorbed hydrogen were phosphorus, sulphur and iodine. The amount of hydrogen which could be absorbed at a time by phosphorus, and the rate of absorption, both increased when the tube was warmed. In this case it seems that the chemical action between the solid and the gas is increased as the temperature rises. It is known that phosphoretted hydrogen is produced when phosphorus is heated in a stream of hydrogen. If the discharge was stopped, and the tube warmed, some of the gas absorbed was re-liberated. In this case, therefore, the absorption is due partly to occlusion, and partly to chemical action.

Sulphur absorbed well, providing the pressure of the gas was not below 0.5 mm. of mercury. Below this pressure the effect disappeared. When the contents of the tube were heated above the temperature of melting sulphur, and then allowed to cool, about one-sixth of the gas that had been absorbed was re-liberated. In this case, therefore, chemical action and occlusion account for the absorption.

The amounts of gas absorbed by iodine were similar to those found with phosphorus. There was no absorption when the pressure of the gas was below 1 mm. of mercury. About one-fifth of the gas which had been absorbed in an experiment was evolved when the contents of the tube were heated to 100°C .

5. CONCLUSIONS.

When considering the absorption of gases in the electric discharge tube, the part which the glass of the tube plays must be taken into account. Willows* has shown that in a Crooke's tube there is absorption of the gas, and that it is due probably to chemical action between the gases and the glass. He found that, with a volume of 108 c.c., and a pressure of 1 mm. of mercury, a current of 10.8×10^{-4} ampere passing for 30 minutes reduced the pressure nearly one-eleventh. This is a very small absorption compared with that found in the present work. The effect of absorption by the glass can thus be neglected in the present experiments. Willows and George† found that large quantities of hydrogen were absorbed by a quartz bulb, if the discharges were alternated with those in air. They supposed that chemical actions occur with the air, giving oxidation products; these are reduced by hydrogen. This would account for the large quantity of gas which can be absorbed. In the present work, as no oxygen was used, this effect is negligible. Thus practically all the absorption of gases shown in Tables I. and II. is attributed to the elements on the cathode.

The absorption of nitrogen is not an occlusion effect, but is due to chemical action. In several cases, the amount of gas absorbed is many times greater than the quantity of hydrogen liberated in the voltameter. This indicates that the phenomenon is not due to the positive ions within the tube, unless these ions are attached to neutral molecules of the gas. The nitrogen must assume an active modification when the discharge passes, and since the rate of absorption increases as the temperature falls, this modification must be intensified by cooling. Strutt‡ showed that pure nitrogen, subjected to the jar discharge, produces an active modification of nitrogen, and that it is not due to the ions in the discharge tube. He found that the modification was weakened by heating, and intensified by cooling. It acted on ordinary phosphorus and other elements.

Table I. shows that phosphorus, sulphur and iodine absorb nitrogen at a greater rate than other elements. In addition to the absorption by the cathode, there is chemical action occurring between the vapour of the elements and the gas.

* "Phil. Mag.," 1 (1901).

† Proc. Phys. Soc., Vol. XXVIII. (1916).

‡ "Proc." Roy. Soc., Ser. A., 85 (1911).

This view is strengthened when we consider that the three substances have low boiling points. Some elements do not absorb nitrogen, and this is due, probably, to the absence of suitable conditions (as regards pressure and temperature) in the discharge tube.

Hydrogen is absorbed by sulphur, phosphorus and iodine. With this gas the effect appears to be due to two causes—occlusion of the gas within the substance, and chemical action. As the amount of gas occluded is very small, the more important factor in the absorption is chemical action. The results suggest that hydrogen assumes an active modification in the discharge tube, and that this modification is not due to gaseous ions. Recently, and while the present work was in progress, Wendt and Landauer* have shown that an active modification of hydrogen may be obtained by various methods, all dependent on gaseous ionisation; by α -rays from radium emanation, by electrical discharge under reduced pressure, and by the high-potential corona at atmospheric pressure. They state that this active hydrogen reduces sulphur, arsenic, phosphorus, mercury, nitrogen and both acid and neutral permanganates. It is unstable, and reverts to the ordinary form in about a minute. The activity is not due to gaseous ions, and they suppose that the stable hydrogen molecules undergo dissociation into free atoms, when an electron is removed during the process of ionisation; these atoms then attach themselves to neighbouring neutral molecules to form triatomic systems.

The disintegration of the cathode in a vacuum tube causes a film of metal to form on the adjacent glass. In this way a clean surface of metal is produced. When an electric discharge is passed, the conditions are favourable for the absorption of the gas by the metal. Considering the disappearance of the gas in a vacuum tube it is necessary to take into account the absorption of gas by the film of metal, and also the absorption by the glass walls of the tube. It is probable that the film of metal accounts for the greater part of the effect. Brodetsky and Hodgson showed that the disappearance of gases in vacuum tubes is a problem of some complexity, and that with metallic electrodes the effect is due principally to absorption of gas by disintegrated metal; it may also depend partly on the liberation of the alkali metals by electrolysis of the glass, and chemical combination of these metals with the gas.

* "Am. Chem. Soc. Journ.," 42, May (1920).

DISCUSSION.

Dr. GOUCHER said that work bearing closely upon Mr. Newman's experiments on the disappearance of gas in the electric discharge had been carried on lately in the Research Laboratory of the General Electric Company. Some of it had already been published ("Phil. Mag.," XL, 585, Nov., 1920). It had led to conclusions precisely opposite to those of Mr. Newman. It did not appear to him that Mr. Newman had brought any direct evidence in favour of absorption being due to chemical action; the only direct evidence of that view would be the establishment of the "law of constant proportions," and of a constant ratio between the amount of gas disappearing and that of something else disappearing at the same time. The absorption of gas in the presence of phosphorus had been studied with especial care, and it had been found that there was no simple relation between the amount of gas disappearing and the amount of phosphorus used. Undoubtedly chemical action plays some part in the disappearance. For instance, the discharge through CO converts the gas into CO_2 , and the relation between the current and the amount of gas transformed obeys accurately Faraday's law in suitable conditions. If, as in the discharge tubes which Mr. Newman used, ionisation is accompanied by recombination, it is not to be expected that Faraday's law should be obeyed. But even in such a case where a chemical action takes place, that action is not usually directly responsible for the disappearance of the gas. Chemical action will not cause complete absorption unless the products of the reactions are solid. Such compounds might be formed between nitrogen and the metal of the electrodes, but there is no evidence whatever that they can be formed between nitrogen and phosphorus or sulphur. The main cause of absorption of gas is, in the great majority of cases, adhesion to the walls of the vessel. This adhesion is greatly favoured by the deposition over the adhering gas of a solid layer of some other substance. The solid may be metal spluttered from the cathode or it may be, in the case of phosphorus, red phosphorus produced by the discharge from phosphorus vapour. All the work to which he referred indicated that actions of this kind were the main cause of the disappearance of gas in the electric discharge, except, possibly, when very active metals were used as cathodes.

Dr. H. BORNS inquired whether formation of hydrides had been observed. If the alkali metals absorbed hydrogen also, as he understood the author to say, alkali hydrides might be formed, which were crystalline compounds like common salt, not in the least resembling metals. Quite recently Nernst and K. Moers ("Zeits. f. Elektrochem.," Aug. 1, 1920) had electrolysed fused lithium hydride to see whether the hydrogen would really go to the anode in this case, as the metallic lithium would go to the cathode. Quantitatively the difficult experiments had not been conclusive, but there was evidence of hydrogen at the anode and hence experimental evidence confirming the possibility of the existence of both positive and negative hydrogen ions.

The AUTHOR, in reply to Dr. Goucher, said he did not think the results he mentioned were conclusive against chemical action. Lord Rayleigh had also attributed the effect to chemical action.

In reply to Dr. Borns, he could not say whether hydrides were formed or not.