to vaporize, the pressure exerted by the vapor being determined from a manometer attached to the apparatus. Knowing the atmospheric pressure, the per cent by volume of benzene vapor is computed. A modification of the apparatus employed by Burrell and Robertson has been suggested by Whiton¹ as being more desirable for use in determining the efficiency of the benzol scrubbers used on coke-oven gas.

FUMING SULFURIC ACID METHOD

The determination of the combined benzene and ethylene content of an illuminating gas by fuming sulfuric acid may be utilized for the indirect determination of benzene when the amount of ethylene is determined by some other method. Haber and Oechelhäuser² have employed this procedure, determining the ethylene content of the gas mixture by treatment with standardized bromine water, and subsequent determination of the excess of bromine. Since benzene is also absorbed by bromine water, the combined benzene and ethylene content can be determined approximately by bromine water, as well as by fuming sulfuric acid. Haber and Lunge³ have described a method for determining ethylene in the presence of benzene by causing the ethylene to combine with hydrogen in the presence of platinum black. The amount of benzene is then arrived at indirectly by taking the difference between the combined benzene and olefine content, as determined by fuming sulfuric acid, and the ethylene content.

PARAFFIN OIL METHOD

Müller⁴ has proposed that benzene vapor in illuminating gas be determined by passing the gas through cooled paraffin oil. The greater part of the benzene vapor can be absorbed by this method. Nowicki⁵ had described a special absorbing device for carrying out this determination. The method has been elaborated by Krieger.⁶ Neubeck⁷ has modified the procedure by distilling off the benzene taken up by the oil, but does not recommend the method on account of the difficulty in maintaining air-tight joints during the distillation. Copp⁸ has described the procedure adopted by him in obtaining more efficient absorption of the benzene vapor.

SPECIFIC GRAVITY METHOD

In Lunge's "Chemisch-technische Untersuchungsmethoden," Vol. 2 (1900), p. 586, there is described a method for determining the benzene content of an illuminating gas from the specific gravity of the gas and the amount of olefines in it. This method is open to the objection that possible variations in the amounts of the other constituents of the gas are not considered.

AMMONIACAL NICKEL CYANIDE METHOD

Dennis and O'Neill⁹ developed a gas-volumetric method for the determination of benzene, employing

as a reagent an ammoniacal solution of nickel nitrate. Later Dennis and McCarthy¹ suggested the use of an ammoniacal solution of nickel cyanide instead of nickel nitrate, having found that more uniformly reliable results could be obtained with the former reagent.

SULFURIC ACID METHOD

Morton² has suggested the use of concentrated sulfuric acid for the absorption of benzene vapor in the presence of ethylene. Dennis and McCarthy³ found that this reagent does not give satisfactory results both on account of the fact that some ethylene is absorbed by it, and also because the absorption of benzene is not complete.

SATURATION METHOD

The Société Roubaissienne d' Eclairage par le Gaz and R.R. L. H. Forrieres⁴ have developed a method for benzene based upon the determination of the amount of benzene that is required to saturate a known volume of gas. After computing the amount that would be required, under the conditions of the experiment, for gas containing no benzene vapor, the benzene content of the gas is gotten by difference.

THE NEW METHOD

During the summer of 1915, in attempting to develop a method for determining benzene vapor in gas simply, quickly, and accurately, the author did considerable preliminary work upon a method which appears more nearly to satisfy these requirements than any of the methods that have been mentioned. In the proposed method, a measured quantity of gas containing an unknown amount of benzene vapor is placed in contact with benzene in a special apparatus and the increase in volume read. By determining what the increase in volume would have been, had the gas contained no benzene vapor, the amount of benzene vapor actually present is easily computed. That this idea is not entirely new was learned when a search of the literature was made and reference to the German Patent described under the previous heading was found. The procedure that has been employed is, however, much simpler and quicker than that described in the patent.

Owing to the failure of attempts to obtain, under present conditions, apparatus considered essential for the proper standardization of the method, its further development has been temporarily postponed.

CORNELL UNIVERSITY
ITHACA, NEW YORK

RESEARCH ON THE DETECTION OF ADDED WATER IN MILK

By HALSEY DURAND AND RESTON STEVENSON
Received September 13, 1917

At the annual meeting of the American Chemical Society, held in New York City, September 27, 1916, one of the authors read a paper on "The Detection of Added Water in Milk,"¹ in which the importance of devising a rapid and accurate method was brought

¹ THIS JOURNAL, 8 (1916), 733.

² Ber., 29 (1896), 2700; J. Gasbel., 39 (1896), 804.

³ Z. anorg. Chem., 16 (1898), 26.

⁴ J. Gasbel., 41 (1898), 433.

⁵ Ibid., 48 (1905), 292.

⁶ Ibid., 58 (1915), 61.

⁷ Ibid., 58 (1915), 815.

⁸ Gas World, 66 (1917), 222.

⁹ J. Am. Chem. Soc., 25 (1903), 503.

¹ J. Am. Chem. Soc., 30 (1908), 233.

² Ibid., 28 (1906), 1732.

³ Ibid., 30 (1908), 233.

⁴ German Patent No. 267,491, May, 1913.

⁵ THIS JOURNAL, 9 (1917), 44.

out and a review of the existing methods was presented.

The *first* was the determination of the refractive index of the milk serum, which, while having the advantage of speed, proved unreliable for the detection of less than 10 per cent of added water, vastly too great a margin. The *second* was the determination of the freezing point,¹ the elevation above that of normal milk indicating the percentage of added water; this is an excellent method, but one requiring too much time for a routine laboratory. A *third* method, the determination of the specific gravity of the whole milk and of the serum, was also mentioned as having been in use for many years, but never having given satisfactory results.

TABLE I—PRELIMINARY EXPERIMENTS

Cell No.	SAMPLE	No.	Temp. ° C.	Conductivity
1	Whole Milk <i>a</i>	1	25.2	0.00527
	<i>b</i>	2	25.17	0.00520
	<i>c</i>	3	25.15	0.00520
	<i>b</i> + 10% Distilled Water.....	4	25.10	0.00479
	<i>a</i> + 10% Croton Water.....	5	25.17	0.00478
	<i>c</i> + 10% Distilled Water.....	6	25.07	0.00466
	Whole Milk <i>a</i>	7	24.95	0.00513
2	Milk from Individual Cow	1	25.0	0.00522
	Suspicious Sample	2	25.0	0.00523
	Sealect, Grade A.....	3	25.0	0.00522
		4	25.0	0.00549
		5	25.0	0.00517
		6	25.0	0.00503
		7	25.0	0.00585
		8	25.0	0.00530
	After Standing in Ice-box for 2 days	9	25.0	0.00521
		10	25.0	0.00571
		11	25.0	0.00624
		12	25.0	0.00755
		13	25.0	0.00360
		14	25.0	0.00315
		15	25.0	0.00369

TABLE II—TESTS USING TEST-TUBES AS CELLS

SAMPLE	No.	Temp. 25° C.	Conductivity
Authentic Sample	1	0.00543	
Authentic Sample	2	0.00504	
Same as 2.....	3	0.00504	
Same as 1.....	4	0.00518	
Same as 2.....	5	0.00475	
Authentic Sample	6	0.00504	
Authentic Sample	7	0.00495	
Authentic Sample	8	0.00460	
Authentic Sample	9	0.00563	
Same as 1.....	10	0.00559	
Same as 2.....	11	0.00605	
Same as 3.....	12	0.00712	
Same as 4.....	13	0.00727	

TABLE III—TESTS USING CELL NO. 2, ACCURATELY FILLED TO MARK

SAMPLE	No.	Temp. 25° C.	Conductivity
Borden's Grade B, pasteurized.....	1	0.00519	
Borden's Grade B, pasteurized.....	2	0.00519	
Locust Farm Grade B, pasteurized...	3	0.00516	
Milk from Individual Holstein Cow (Morning Milking, unpasteurized)	4	0.00519	
	5	0.00516	
	6	0.00519	
	7	0.00513	
	8	0.00519	
No. 4 + 10% Distilled Water.....	9	0.00478	
+ 10% Distilled Water.....	10	0.00478	
+ 20% Distilled Water.....	11	0.00430	
+ 50% Distilled Water.....	12	0.00307	
+ 1.3% Distilled Water.....	13	0.00513	
+ 3% Distilled Water.....	14	0.00503	
+ 5% Distilled Water.....	15	0.00491	
+ 7% Distilled Water.....	16	0.00482	
+ 10% Distilled Water.....	17	0.00477	
Grade A Milk from 1/2 bottle (2 days old)	18	0.00503	
Cream from No. 8.....	19	0.00439	
Milk from 1 after Removal of Cream	20	0.00532	

A brief outline was given, in which methods for further research were proposed and the results obtained are the subject of this contribution.

I—The first of these methods to be investigated was based on the theory that added water would increase the solubility of inorganic salts in the serum. A series of determinations was made using a weighed amount of anhydrous lead subacetate. The reagent was that used in Horne's methods for sugar analysis. Experiment showed that 3 g. were required for the coagulation of 100 cc. of milk. After the addition of the subacetate, the contents of the flask were vigorously shaken to coagulate the milk thoroughly. The contents of the flask were poured on a dry folded filter and 50 cc. of the serum collected for the determination. The lead was precipitated with 25 per cent of sulfuric acid, and alcohol added to facilitate the precipitation. The lead sulfate was collected in an alundum crucible, washed with water and finally with alcohol, ignited and weighed. Several determinations were made by the above method.

The results proved unreliable, in that a variable amount of the subacetate in solution is adsorbed by the coagulum, and that, owing to the slowness of the filtration, it proved impractical to wash out all of the organic matter not coagulated, this latter causing a reduction of a portion of the lead sulfate when ignited.

¹ Chem. News, 110, No. 2870, p. 259; No. 2871, p. 275; No. 2872, p. 283.

II—A second series of determinations was made, in which weighed amounts of finely divided silver nitrate was used for the coagulation. The procedure was the same as described under I. The silver in 50 cc. of the serum was determined by titration with *N*/10 ammonium sulfocyanate, after addition of nitric acid and using ferric ammonium sulfate as indicator. This method is much more accurate and rapid than Method I, but the results show that the differences in the number of cc. used, in milks of known purity, are sometimes greater than those between whole milk and samples watered in the laboratory. The method was, therefore, abandoned as useless.

III—The third method, the determination of the electrical conductivity by method of Kohlrausch

of the whole milk, and of the serum after coagulation with electrolytes and non-electrolytes, has been tried out in an exhaustive manner during the past year by the authors.

Through the courtesy of Dr. Charles Baskerville, director of the Department of Chemistry, of the College of the City of New York, permission was obtained to carry on these experiments in the laboratories of that institution.

The first series of experiments (Table I) was performed in a cell used for conductivity experiments in the laboratory, in which the electrodes were kept at a uniform distance, but were placed in the cell after filling without regard to their proximity to the sides. This cell was designated as No. 1. A constant temperature was maintained during all of the following determinations, by warming the water by a coil of resistance wire, and stirring by bubbling compressed air, the current in the coil being regulated by a rheostat. It will be observed from these results that there is a decided similarity in the results on whole milk, and also following the theory, the milks to which water has been added give a lower conductivity.

In the second series of experiments, Table I, Cell 2, a cell similar in construction to Cell 1 but of greater capacity and with larger electrodes than the above, was used.

Here as with Cell 1, the samples of known purity gave excellent results. The results on the samples

marked, "in ice-box 2 days," are not to be relied on, as change in composition has probably taken place.

In Table II, test-tubes, of the same commercial size, were used to facilitate the work, as a number of tubes could be placed in the bath at the same time, to bring them to the required temperature. The same methods were used as in Table I. In this series a wide deviation was observed on different tubes containing the same milk, amounting at most to 37.0 per cent in the conductance. This was found to be due to the difference in size of the tubes and to the amount of sample contained. To avoid a continuance of these errors a file mark was made on Cell 2 and in the subsequent determinations the cell was carefully filled to this mark.

The results in Table III for the whole milk are much more uniform than in the previous determinations, but a variation still persists. The samples to which

water has been added show a regular decrease in conductivity as the amount of water added increases. A search of the literature on electrical conductivity, while discussing the size and distance of the electrodes and the form of the cell, fails to make mention of the error introduced by using varying amounts of solution. This phenomenon is being made the subject of a separate investigation.

As a final effort to determine the cause of the above variations in the whole milk a special cell was constructed as shown in the accompanying drawing. This cell has the advantage that the electrodes are sealed in a permanent position, a constant distance apart, and with the same amount of liquid above and below them.

The results in Table IV are most unsatisfactory,

TABLE IV—TESTS USING SPECIAL CELL (No. 3)

SAMPLE OF MILK	Temperature, 28° C.	No.	Conductivity
Grade A (Sealect), 1 day after pasteurization.....		1	0.00546
Raw Herd Milk from Fresh Cows.....		2	0.00540
No. 2 Pasteurized at 67 to 72° C. (½ hr.) 4 hrs. after pasteurization.....		3	0.00541
Grade B pasteurized (Borden's).....		4	0.00563
Same, another sample.....		5	0.00559
Same, another sample.....		6	0.00559
Grade B pasteurized (Sheffield).....		7	0.00544
Grade B pasteurized (Clover Farm).....		8	0.00569
Same, another sample.....		9	0.00566
Grade B pasteurized (Mutual-McDermott).....		10	0.00563
No. 4 + 2 per cent distilled water.....		11	0.00546
No. 4 + 5 per cent distilled water.....		12	0.00537
No. 4 + 10 per cent distilled water.....		13	0.00512
No. 7 + 2 per cent distilled water.....		14	0.00536
No. 7 + 5 per cent distilled water.....		15	0.00523
No. 8 + 5 per cent distilled water.....		16	0.00541
Grade B collected from shop.....		17	0.00539
		18	0.00541
		19	0.00550
		20	0.00560
		21	0.00561
		22	0.00555
No. 22 repeated after 5 minutes.....		23	0.00554
Grade B collected from shop.....		24	0.00558
		25	0.00577
		26	0.00579
		27	0.00535
		28	0.00558
No. 27 repeated.....		29	0.00536
Grade B collected from shop.....		30	0.00560
		31	0.00575
		32	0.00554
		33	0.00567
		34	0.00566
		35	0.00563
		36	0.00564
		37	0.00563
		38	0.00577
		39	0.00554
		40	0.00537
		41	0.00546
Grade A collected from shop.....		42	0.00555
		43	0.00552
		44	0.00532
		45	0.00534
		46	0.00535
		47	0.00530
		48	0.00548
Grade A, mixed samples, 1st bottle.....		49	0.00652
2nd bottle.....		50	0.00633
Authentic sample.....		51	0.00678
No. 51 second reading.....		52	0.00682
Authentic sample.....		53	0.00450
		54	0.00643
		55	0.00843
No. 53 + 7 per cent water.....		56	0.00435
Authentic sample, unpasteurized.....		57	0.00555
Milk from 3 or 4 mixed breed cows.....		58	0.00552
Same as above after 10 minutes.....		59	0.00565
No. 59 after 40 minutes.....		60	0.00569
Same as No. 57.....		61	0.00575
		62	0.00551
No. 62 second reading.....		63	0.00545

in that a wide discrepancy in conductivity exists even in authentic samples. It was then decided to separate the milk and cream and to determine the conductivity of the skimmed milk. Through the courtesy of Messrs. Paul and Terhune of the DeLaval Separator Company, a cream separator was obtained and the samples separated. Determinations were made on whole milk, skimmed milk and cream.

The determinations in Table V were made under ideal conditions. The cell was accurately filled to the mark, the temperature kept at 28.0° C. ± 0.05 and correction made for each deviation. A large number of the samples were collected under the personal supervision of department inspectors so that there could be no doubt as to their authenticity. The method of measurement was sufficiently sensitive to detect 0.5 per cent of added water, and the fact that the cell constant did not vary was confirmed by frequent determinations, using $N/50$ potassium chloride solution. To preclude the possibility of error through improper running of the separator, a representative of the

TABLE V—DETERMINATION ON WHOLE AND SKIMMED MILK AND CREAM
Authentic Samples. From 5 Cows. Milk from 4 Cows in Each Can. Morning Milkings (1-13)
Temperature, 28° C.

SAMPLE	No.	Conductivity	SAMPLE	No.	Conductivity
Whole Milk, Can No. 1.....	1	0.00561	No. 47 after separation.....	52	0.00574
No. 1 after separation.....	2	0.00590	No. 48 after separation.....	53	0.00589
Whole Milk, Can No. 2.....	3	0.00592	No. 49 after separation.....	54	0.00616
No. 2 after separation.....	4	0.00629	No. 50 after separation.....	55	0.00593
Whole Milk, Can No. 3.....	5	0.00567	No. 51 after separation.....	56	0.00632
No. 3 after separation.....	6	0.00605	Separated cream from all samples mixed.....	57	0.00395
Whole Milk, Can No. 4.....	7	0.00595	Separated milk from all samples mixed.....	58	0.00601
No. 4 after separation.....	8	0.00621			
Whole Milk, Can No. 5.....	9	0.00555	Separator run by representative of DeLaval Co.	59	0.00576
No. 5 after separation.....	10	0.00594	Milk from single Holstein unpasteurized.....	60	0.00555
No. 5 after separation and filtering to remove air bubbles.....	11	0.00595		61	0.00536
No. 4 after separation, coagulated with rennin and filtered.....	12	0.00672		62	0.00606
No. 3 after separation, coagulated with pancreatin and filtered.....	13	0.00643		63	0.00569
One Holstein cow producing 16 qts. per day.....	14	0.00539	No. 59 after separation.....	64	0.00606
One Jersey cow producing 14 qts. per day.....	15	0.00601	No. 60 after separation.....	65	0.00586
Mixed Jersey and Holstein herd.....	16	0.00555	No. 61 after separation.....	66	0.00569
	17	0.00547	No. 62 after separation.....	67	0.00614
Holstein herd.....	18	0.00554	No. 63 after separation.....	68	0.00610
No. 14 after separation.....	19	0.00576	Mixed separated milk + 5 per cent separated cream.....	69	0.00593
No. 15 after separation.....	20	0.00627	+ 10 per cent separated cream.....	70	0.00589
No. 16 after separation.....	21	0.00596	Mixed separated milk, all samples.....	71	0.00602
No. 17 after separation.....	22	0.00581	Mixed separated cream, all samples.....	72	0.00445
No. 18 after separation.....	23	0.00586	Grade A, certified unpasteurized (Sheffield).....	73	0.00554
No. 18 after separation and filtration.....	24	0.00586	Grade A, pasteurized (Locust Farms).....	74	0.00581
Grade B, pasteurized (Borden's).....	25	0.00565	Grade A, pasteurized (Sheffield, Sealect).....	75	0.00573
Grade B, pasteurized (Sheffield).....	26	0.00543	Grade A, pasteurized (Sheffield, Sealect).....	76	0.00552
Grade B, pasteurized (Clover Farms).....	27	0.00580	Grade A, pasteurized (Mutual-McDermott).....	77	0.00547
Grade A, pasteurized (Locust Farms).....	28	0.00573	No. 73 after separation.....	78	0.00591
Grade A, pasteurized (Sealect Sheffield).....	29	0.00560	No. 74 after separation.....	79	0.00619
No. 25 after separation.....	30	0.00596	No. 75 after separation.....	80	0.00595
No. 26 after separation.....	31	0.00381	No. 76 after separation.....	81	0.00575
No. 27 after separation.....	32	0.00605	No. 77 after separation.....	82	0.00570
No. 28 after separation.....	33	0.00399	Separated cream from No. 73.....	83	0.00448
No. 29 after separation.....	34	0.00386	Separated cream from No. 74.....	84	0.00431
No. 29 coagulated with rennin and filtered.....	35	0.00611	Separated cream from No. 75.....	85	0.00435
No. 28 coagulated with rennin and filtered.....	36	0.00645	Separated cream from No. 76.....	86	0.00414
One Holstein cow.....	37	0.00590	Separated cream from No. 77.....	87	0.00417
One Durham cow.....	38	0.00538	Grade B raw taken from cans.....	88	0.00585
Mixed Holstein and Durham herd.....	39	0.00560	Nos. 88 and 89 mixed.....	89	0.00592
	40	0.00559		90	0.00589
	41	0.00560	Grade B raw taken from cans.....	91	0.00545
No. 37 after separation.....	42	0.00607		92	0.00537
No. 38 after separation.....	43	0.00574	Nos. 91 and 92 mixed.....	93	0.00540
No. 39 after separation.....	44	0.00587	Nos. 88, 89, 91, 92 mixed.....	94	0.00563
No. 40 after separation.....	45	0.00599	No. 89 second reading.....	95	0.00555
No. 41 after separation.....	46	0.00599	Nos. 88, 89, 91, 92 mixed, after separation.....	96	0.00589
1 qt. morning milk 4 or 5 cows.....	47	0.00538		97	0.00596
Mixed common herd unpasteurized.....	48	0.00562		98	0.00592
	49	0.00561		99	0.00594
	50	0.00561	No. 95 after separation.....	100	0.00597
	51	0.00603	No. 88 after separation and standing 24 hours.....	101	0.00590

DeLaval Company, separated the samples in Determinations 59 to 72.

As the milk after separation contains air bubbles, the milk was filtered to remove them. It was found that the readings before and after filtration did not vary (Nos. 10 and 11).

As the samples were run through the separator one after another, it was deemed advisable to determine if the samples were affected by the ones preceding. Four samples were mixed thoroughly, then divided again into 4 samples and run through the separator successively (Nos. 96 to 99). Three of these results were fairly uniform.

It will also be observed that the average of the readings on individual milks corresponds very closely with the reading after mixing Nos. 88 to 94.

With all known sources of error eliminated the readings on authentic samples still showed so wide a difference as to render the method useless.

In the freezing-point determination the fat and protein of the milk play no part and the constant depends entirely on the concentration of the substances in solution.

In the conductivity measurements, however, the fat and protein of the milk decrease the specific con-

ductance by decreasing the number of ions between the electrodes in just the same manner as would glass beads placed in the cell between the electrodes.

A final series of determinations (Table VI) was made on samples of milk coagulated with basic lead acetate

TABLE VI—TESTS USING MILK SERA
Temperature, 28° C.

CHEMICAL ANALYSIS		No.	Conductivity
SAMPLE	Total Solids		
AA-223.....	11.82	1	0.00653
AA-226.....	12.01	2	0.00645
AA-227.....	13.18	3	0.00647
AA-228.....	11.94	4	0.00647
AA-230.....	12.06	5	0.00649
AA-232.....	11.90	6	0.00645
AA-233.....	11.78	7	0.00645
AA-234.....	11.94	8	0.00649
AA-235.....	12.13	9	0.00643
B-456.....	11.94	10	0.00651
B-457.....	12.13	11	0.00649
B-460.....	11.70	12	0.00649
B-461.....	12.38	13	0.00653
B-463.....	12.28	14	0.00647
2A-501.....	12.36	15	0.00647
2B-505.....	11.87	16	0.00643
2A-505.....			
Serum + 5 per cent water.....		17	0.00653
Serum from authentic milk Grade A raw.....		18	0.00682
		19	0.00659
		20	0.00667
		21	0.00682
		22	0.00657
		23	0.00667
As above + 5 per cent water.....		24	0.00639
+ 5 per cent water.....		25	0.00663
+ 10 per cent water.....		26	0.00628
+ 10 per cent water.....		27	0.00616
+ 20 per cent water.....		28	0.00573
+ 20 per cent water.....		29	0.00591

(Horne's). One hundred cubic centimeters of the milk were taken and 3 g. of the acetate accurately weighed and added, thoroughly shaken and filtered to 50 cc. Readings were then made on the clear sera.

The determinations made on laboratory samples 1 to 16 show a fair degree of uniformity. It will be observed from a comparison of the conductivity and the chemical analysis, that the differences in fat and total solids content bear no relation to the differences in conductivity. The sera from authentic samples 18 to 23 show a far greater variation than has been observed in any of the foregoing determinations and the results are entirely unreliable.

In the authentic samples adulterated in the laboratory (24 to 29) the water was first added to the samples and 100 cc. of the adulterated milk were then taken and coagulated as described above.

These results show great differences, even at the same adulteration and these differences are greater than those between the authentic and adulterated samples. This is probably due to an irregular adsorption of the lead salt by the coagulum, which would account for the lack of uniformity in the results, as was the case in experiments mentioned under Method I at the beginning of this paper.

Having tried out the method and investigated all of the modifications at hand in a most exhaustive manner and being unable to obtain any uniformity in results it was decided to abandon the method as impractical.

It is to be regretted that this method proved ineffective, as a rapid and accurate method of this sort would be of great value to the food analyst.

One of the authors, Durand, proposes at an early date to continue this research, making use of the osmotic pressure of milk, in a cell specially constructed to measure the differential osmotic pressure between milks and a standard saline solution.

CHEMICAL LABORATORY, DEPARTMENT OF HEALTH
AND
COLLEGE OF THE CITY OF NEW YORK
NEW YORK CITY

THE LOGANBERRY AND THE ACID CONTENT OF ITS JUICE

By MILO REASON DAUGHTERS
Received September 24, 1917

Attention has been called to the composition of loganberry pulp and juice and to the drying properties of loganberry oil.¹ This paper gives the composition of the fresh, ripe, whole berry and some data on the juice, with special reference to its acid content.

TABLE I—COMPOSITION OF THE LOGANBERRY²

	Per cent
Total Solids.....	20.74
Moisture.....	79.26
Citric Acid (anhydrous).....	1.52
Invert Sugar.....	7.15
Sucrose.....	Absent
Proteins (N $\times$ 6.25).....	4.55
Fat (ether extract).....	0.613
Crude Fiber.....	1.38
Ash.....	0.571

¹ THIS JOURNAL, 9 (1917), 1043.

² Colby reported the analysis of a sample of California loganberries. California Experiment Station Report, 1895, 177.

The sample (Table I) was taken from 14 lbs. of berries gathered at the close of a uniformly dry season. Total moisture was obtained by heating *in vacuo* at 70° C. to constant weight. An electric muffle furnace heated to dull redness was used for the ash determinations. Citric acid was estimated by the method given in the *Journal of the Association of Official Agricultural Chemists*, Vol. 2 (1916), 183.

TABLE II—COMPOSITION OF THE JUICE

SAMPLE NO.	I	II	III	IV
Date of Collection (1917).....	July 18	July 25	July 28	August 7
Specific Gravity (25° C.).....	1.0526	1.0548	1.0565	1.0599
Acidity (as anhydrous citric).....	1.904	1.60	1.515	1.54
Citric Acid (anhydrous).....	1.82	1.521	1.511	1.54
Volatile Acids (acetic).....		0.048	0.025	
Total Solids.....		12.84	12.49	14.74
Invert Sugar.....	8.35	8.80	9.06	8.74
Protein (N $\times$ 6.25).....		0.871	0.497	0.37
Ash.....		0.499	0.45	0.39

The first three samples of juice were pressed from 4 to 5 lbs. of berries purchased in the open market. The berries were ground in a food chopper and then pressed in a small fruit press lined with doubled bird's-eye cotton cloth. Sample IV was obtained in a similar manner in a larger press from 14 lbs. of berries after removing the sample for the analysis given in Table I. The specific gravity readings were made by the pycnometer method on the juice which was kept in a constant temperature bath at 25° C.

Dunbar and Lepper¹ have made a study of the Kunz² modification of Stahre's method³ for the quantitative estimation of citric acid and have announced its applicability to fruit products. This method was applied directly to the juice without preliminary precipitation of the citric acid as the barium salt in the last three samples. Twenty-five grams of juice were placed in a volumetric flask of 100 cc. capacity, and 2 cc. of dilute sulfuric acid and 5 cc. of freshly prepared bromine water added, and then made up to the mark with distilled water. Aliquots of 25 cc. each were used in the analysis. Approximately 40 cc. of 5 per cent potassium permanganate were required to complete the oxidation of the citric acid, pectins, sugars, etc. Pentabromacetone separated in a very satisfactory manner as a white semicrystalline solid, leaving a clear supernatant liquid after the addition of ferrous sulfate.

Samples II and III were examined for volatile acids, which were found to be present in traces. Tartaric acid was found in traces by Jorgensen's method.⁴ Dunbar and Bacon's⁵ uranyl acetate method for malic acid was tried on Sample I, but with negative results.

In conclusion, it may be stated that citric is the chief acid of the loganberry. Traces of tartaric and volatile acids are also present. Malic acid is absent.

DEPARTMENT OF CHEMISTRY
OREGON STATE AGRICULTURAL COLLEGE
CORVALLIS

¹ *Jr. A. O. A. C.*, 3 (1916), 182; No. 4 (1917), 175.

² *Arch. Chem. Mikros.*, 7 (1914), 285; *Chem. Abs.*, 9 (1915), 687.

³ *Nordisk Tidsskrift*, 2 (1895), 141; *Z. anal. Chem.*, 36 (1897), 195.

⁴ *Z. Nahr. Genussm.*, 17 (1909), 397; Abderhalden, "Handbuch Biochem. Arbeitsmeth.," 2 (1910), 35; *Chem. Abs.*, 3 (1909), 1781.

⁵ U. S. Dept. of Agr., Bureau of Chemistry, *Circular* 76; *Jr. A. O. A. C.*, 2 (1917), 179; THIS JOURNAL, 3 (1911), 826.