Besides these borax deposits, there are deposits of double borate of lime at Rhodes and Columbus, in Nevada, and Death Valley, in California. And also mines of sesquiborate of lime at Dagget, in San Bernardino County, at Death Valley, in Inyo County, California, and at Chetco, in Oregon.

The general view of a borax marsh is perhaps best illustrated by a photograph, and, for this purpose, we will throw on the screen a photograph of the Saline Valley borax marsh.

This marsh, which is one of the richest in the State of California, is situated on the eastern slope of the Sierra Nevada mountains, 11 miles from the line of the Carson and Colorado Railroad, and 220 miles east of San Francisco; the valley is 18 miles long by 12 miles wide. The crude borax covers the plain to the extent of over a thousand acres, with a depth of from 6 inches to 18 inches.

The borax is mixed with sand, sulphate of soda, carbonate of soda and salt. The color of the crude material, as it lies upon the plain, is of a peculiar grayish yellow, giving the surface the appearance of snow, somewhat tinged by age. The material varies in richness from 10 to 90 per cent. of pure borax.

The next photograph will show the crude method adopted in refining the borax. The plant consists of long semicircular iron pans, into which the material is thrown, the pans are boiled by fires underneath, and when the solution is of the required strength, after settling for a few hours to allow the solid matters to subside, the clear liquor is run off into vats to crystallize, which takes about a week; and the crystallization being complete, the mother liquors are decanted, and the borax removed and packed.

The process is so simple that Indians are employed in borax refining. The next two photographs will show groups of these natives; they belong to the Pah Ute tribe, and very good fellows they are; they are paid a dollar a day.*

The cost of obtaining a ton of borax at the marsh amounts to £3 10s., in addition to which there is hauling and railroad, and freight to the market.

The Death Valley borax marsh lies a little to the southeast of Saline Valley, and more remote from the railroad. Death Valley takes its name from the circumstance of a company of emigrants entering it, on their way from Salt Lake to California, in the year 1850. Very little was known then of the passes through the mountains, and this party made the fatal mistake of attempting a more direct pass than that by the well known emigrant road. The valley was to them a *cul de sac*. While seeking an outlet, they experienced dangers and difficulties altogether unexpected and almost insurmountable. Finding it impossible to take their wagons over the mountains, they abandoned them, and while some of the party climbed the rugged and roadless passes, others, seeking water, miserably perished.

In this valley, and also at Calico in San Bernardino, there exist mines of sesquiborate of lime, or borate spar. This borate lies in ledges varying in thickness from 6 inches to 6 or 7 feet, and crops out at the surface at different angles.

The photographs now exhibited on the screen will best explain the manner in which this borate occurs.

The borate is mined in the ordinary manner by sinking shafts and running levels.

The material is carefully picked and freed from the limestone, gypsum, and steatite with which it is associated, when it yields a product containing from 35 per cent. to 40 per cent. boracic acid, and can be converted into its own weight of borax.

There are three kinds of sesquiborate of lime that correspond to the three varieties of carbonate of lime, viz., calc spar, marble and chalk. In many instances it is extremely difficult to distinguish by the eye the difference between the borate and the carbonate.

Prospectors for borax and borates frequently use a little sulphuric acid and alcohol to detect their presence; the boracic acid liberated by the acid gives with alcohol, upon ignition, a beautiful green flame. If you have no means of obtaining these, a little vinegar and whisky will give the same result.

These three varieties of sesquiborate of lime are worked in Oregon, California and Asia Minor.

At Chetco, Oregon, the borate of lime occurs in large, beautifully white nodules, embedded in a soft serpentine formation. This variety is similar to chalk.

The borate spar of California is similar to calc spar, and the borate of Asia Minor may be likened to marble.

At the present time, the production of borax on the Pacific coast amounts to 6,000 tons per annum, most, if not all, of which is consumed within the limits of the United States.

The next and last source is that from Asia Minor. Boracite, as it is called, was discovered in 1869 at Sultan Chaiir, near Suzurlu, in Asia Minor, forty-five miles from Panderma, a port on the Sea of Marmora, 100 miles from Constantinople, with which city there is a regular service of steamboats.

The principal deposits, as far as yet known, exist near the Tschatalja mountain, in longitude 28° 2' east, and latitude 40° north. It is mined by means of both shafts and tunnels. The boraciferous stratum varies in depth, the nodules or borate being disseminated through the gypsum and other earthy impurities with which it is associated, and from which it has to be selected and picked. The material is hauled to Panderma in "arabas," or native ox carts, or else packed on the back of camels. It tests from 40 to 44 per cent. of boracic acid. The present annual yield is from 8,000 to 9,000 tons.

There are other minerals existing in different parts of the globe that contain boracic acid, but either the quantity, the quality, or other difficulties exist that prevent their being dealt with commercially. They are interesting mineralogically.

The manufacture of borax, as far as the English are concerned, divides itself into two classes—the manufacture of borax from boracic acid and that from sesquiborate of lime and double borate of lime and soda.

The mere refining or recrystallizing of crude borax requires no skill at all. The manufacture of borax from

boracic acid imported from Italy involves several processes. The sulphates of ammonia and magnesia have first to be washed out of the crystallized acid, and this is effected by reason of their superior solubility. The boracic acid is then boiled in large iron pans, with the requisite amount of carbonate of soda, the impurities allowed to subside, and the clear liquor run to large iron vats to crystallize. This first borax is not pure enough for commerce, and requires a second crystallization.

The impure borax liquors are boiled down, and upon reaching a strength of 60° Twad., or 1,300 specific gravity, are allowed to recrystallize and throw down a further crop of borax. Before the mixture reaches a temperature of 80° Fahr. it is drawn off into other vats to allow the sulphate of soda to crystallize out, and, finally, the liquor is raised to the boiling point, and concentrated, in order to get rid of the common salt.

Borax manufactured from boracic acid is liable to be tinged with various colors, such as black, green or yellow, on account of impurities contained in the acid or the soda ash, and are due to the presence of sulphides or oxides of iron. In order to overcome this difficulty the borax is bleached when in a state of solution.

The manufacture of borax from boracite, colmanite, or ulexite presents a new feature that does not appear in the manufacture from boracic acid, and that is, that when any of these minerals are reduced to a state of the finest powder, and boiled with carbonate of soda, what is known as borate of soda, as well as biphosphate of soda, is formed.

The biphosphate of soda or borax crystallizes out in the ordinary way, but the borate of soda remains as a thick sirupy liquor, which has to be decomposed either with carbonic acid, boracic acid, or bicarbonate of soda. If this is not done, loss is apt to occur, and the full strength of the mineral is not obtained.

With such abundant and redundant supplies of borate of lime throughout the world, it becomes a question of transporting the boracic acid it contains in as concentrated a form as possible, especially in those regions where the quality is but poor, and, therefore, many plans have been devised. One of the simplest is what is known as the sulphurous acid process, and this is to be preferred to others on account of the small quantity of sulphur required to extract the boracic acid.

The process consists in burning sulphur, and injecting the sulphurous vapors into the decomposing vessel, where the borate of lime is kept in a state of agitation and suspension in water.

Only one ton of sulphur is required to produce five tons of acid, and the saving effected in cost of transportation, where it takes two or even three tons of borate of lime to produce a ton of boracic acid, requires no recommendation.

The price or value of borax has probably interfered to a great extent with its more general use. The fluctuations can be better described by a diagram on the wall, and shows the value in London and New York for the last twenty years.

In 1872, owing to a combination, the price was forced up to over £100 a ton, since which time, owing to the American and Asia Minor supply becoming developed, the price has declined, increased and declined again. And at the present time the curious circumstance exists that the price of borax in America is higher than it is in England. America, of all places in the world! The way it came about was this. Prior to 1883 Italian boracic acid was admitted into the United States duty free; so some of the borax manufacturers applied to Congress to put on a duty, as it was ruining the borax industry. This Congress obligingly consented to do, and put on a duty of 4 cents a pound. There has been a duty on borax of foreign manufacture all along; but American borax, shipped from San Francisco to New York, via Panama or round the Horn, is admitted duty free. Even if American borax is shipped from San Francisco to Liverpool, it can be reshipped to America and admitted duty free. Still the price of borax in the United States went down until, in 1885, it was sold at £21 per ton in San Francisco. It then occurred to the borax producers to combine and put up prices, which in 1887 they did, limiting the production to the requirements of the United States, and selling to actual consumers in a few other countries. The price was put up to the full extent of the tariff on borate of lime and boracic acid. And so the consumers of borax in the United States, where there is probably more borax than any other section of the globe, have to pay more for it. You will notice that twenty-eight industries, owing to the action of the protection policy of the United States, thus suffer to benefit one.

But in order to maintain that price the Americans are restricted to the consumption in their own country, for fear of their borax being bought at the current price in England, and shipped across to New York to compete with the higher prices there.

Various estimates have been made of the consumption of borax throughout the world, and one of the methods of ascertaining this is by referring to the productions of different countries and converting the different materials into their equivalent of borax. We thus find the production to be as follows:

	Tons.
Asia Minor.....	8,000
Thibet	2,000
Italy	3,000
United States.....	6,000
Chili and Bolivia	3,000
Total.....	22,000

As the American and Asia Minor supply has been developed within the last 20 years, it will be seen that the uses of borax, to the extent of 14,000 tons per annum, have increased during that period, or nearly 300 per cent., and it may be taken for certain that its uses will still further extend.

In the discussion which followed Mr. Arthur Robertson said he was neither a chemist nor a geologist, but he had traveled much in search of borax, feeling sure that its general use would be a great value to the world. He was the first to bring it from California, and having a large stock of course he tried how he could dispose of it, and to what uses it could be put. He, therefore, induced the butcher in the village where he resided to let him have some cowhides,

which he treated with borax. He then had them tanned and sent the leather to Northampton, where it was pronounced to be as fine as any in the world; in fact one man was so pleased with it that he had kept a specimen in his window ever since. When he first went to America borax was little known there except to druggists, but he spoke about it, and got its uses noticed in the papers. Rambling in the Death Valley he saw a dead horse lying on the ground, and pulling out some of the hair and finding it perfectly firm he cut a piece of flesh with his knife and found it perfectly sweet, although, as he ascertained afterward, the carcass had been lying there a long time. He got this noticed in the California papers, from which it was copied into others, and that was the beginning of the use of borax as a preserving agent in America, a use which had now become so general. Near the Death Valley there was a deposit of crude borax, which he discovered about a foot under the blue mud. When this was removed the borax was accessible; and when the sulphate of soda was dissolved out, it was tolerably pure. He sent a cargo of it home round Cape Horn, and felt very proud when it arrived. It was a very toilsome journey to get there, for there was no railway then; and he had 212 miles to walk, through a very difficult country; but he felt amply repaid, when he found the borax, knowing it would have the effect of bringing the price down, and putting it within the reach of all.

With regard to its effects on the human system, he believed Sir Henry Thompson had spoken of it as deleterious, but he took it constantly, and was never out of health, and he had cured many sore throats with it, for he always kept a supply of it about him. Sir Joseph Lister was the first to use it as an antiseptic in medicine, and if people could only be taught to use it in their socks it would be an immense boon to soldiers, policemen, postmen and others who had a great deal of walking to do. The great difficulty was to get shopkeepers to sell it, but he did his best to make its virtues known. He had been in communication with hundreds of chemists on the subject, and he always endeavored to find out what their customers said of it. The antiquity of tinctal as an import from Thibet was considerable. He had reason to believe that it was brought by caravan from beyond Shata to China, and hence by way of Babylon and Palmyra, to the Mediterranean ports before the Christian era. In 1707 the price of tinctal in London was £9 5s. a cwt., or £185 a ton; and in July, 1756, from a price current, he found it was £14 a cwt., or £280 a ton. Of course at such a price it could not be used for washing. The great thing to be desired was that it should be low in price, so that washerwomen might use it instead of soda; they would not get sore arms, and if they had such it would cure them.

ON THE MAGNETIZATION OF METALS.

By THOMAS T. P. BRUCE WARREN.

It is well known that if a bar of iron or steel be magnetized, there is a linear increase in the magnetic "line of direction," but I am not aware of any previously published experimental data showing whether the increment is cubical, or whether the extension in length, or "line of direction," is accompanied with a diminution in the other linear directions of the mass. My experiments, which have been frequently repeated, show that there must be a diminution in the transverse section of a rod, for the same rod, when magnetized, occupies the same bulk as before being magnetized; in fact, there seems to be a slight diminution. I hope to deal more fully with this portion of the subject in a future communication.

I cannot find that any experiments have been made showing the effects of cubical compression. If, for instance, a bar of iron or steel be rigidly prevented from altering its dimensions, would it be possible for the same to acquire a high degree of magnetization relatively, when under no restraint? The solution of this problem might throw much light on the behavior of the dipping needle when traversing a country where magnetic rocks are supposed to exist.

Bearing upon this, we must not omit to take into account the screening effect due to the magnetic permeability of the various geological deposits overlying a stratum of high magnetic susceptibility.

An arrangement which I designed some time ago, and which I termed a "torpedo finder," is based upon these facts. The position of a submerged torpedo, anchor, or any piece of iron may be indicated by means of the magnet, but, unfortunately, the low permeability of water involves the lowering of the magnet to within a short depth of the plane containing the submerged mass.

An electromagnet, or solenoid, may be made magnetically stronger than an ordinary magnet. The electromagnet is lowered to within a few feet of the bottom, the depth of which has been previously ascertained by careful sounding. The electromagnet is excited by a primary or secondary battery. By means of a delicate dynamometer, the strain due to the electromagnet and its leading wires is noted, the battery power is increased, when any increased pull will indicate the existence of some disturbing cause in the neighborhood; by keeping the magnet clear of the bottom and gently steering, we avoid uncertainty in the dynamometer indication, as is experienced in dragging over a rough or uneven bottom.—*Chem. News.*

THE TELEPHONE AS AN OPTICAL CURRENT MEASURER.

By MAX WIEN.

THE author arranges his "optical telephone" as follows: A thin corrugated German silver membrane, such as is used for aneroid barometers, is provided at the middle of that side which is toward the electro-magnet with a piece of soft iron and on the other side with a pin. The latter presses against a piece of very fine watch spring steel, one end of which is fixed, while the other carries a very light mirror. A telescope is used to throw the image of an illuminated slit on the mirror.

If a constant current is allowed to pass through the apparatus, the membrane changes its position of equilibrium; the beam of light is displaced, and remains so as long as the current does not alter. This displacement is proportional to the current intensity, and can

* For illustrations of Borax Lake, California, and works, see SCIENTIFIC AMERICAN SUPPLEMENT, No. 731. For illustration of Chilean deposits, see SUPPLEMENT, No. 581. For early history of the California deposits, see SUPPLEMENT, No. 573.

be experimentally regulated. Since the telescope allows 100 divisions of the scale by tenths to be observed, and one division may be made to correspond to about 5×10^{-5} amperes, a conclusion as to the sensitiveness attainable can be arrived at.

Although the "optical telephone" is thus highly suited for constant currents, it is still better adapted for those which alternate. If a simple sine current passes through the apparatus, the membrane vibrates and with it the mirror. Instead of an ordinary displacement a band of light is then produced, the breadth of which is a measure of the amplitude of the sine current.

FIG. 1.—PORTELECTRIC TRACK AT DORCHESTER, MASS.

It is, however, necessary that the natural tones of the membrane and the spring and the number of alternations of the sine current should be in correspondence with one another. This may be easily effected so far as the membrane and the spring are concerned, and also for the current, if the latter is derived from an induction coil, the contact breaker spring of which is brought to the right tone.

By comparing the results with those given by a dynamometer, the proportionality between the displacement and amplitude of the current was experimentally established. The author shows how with his apparatus he has measured self-induction and fluid resistance with alternating currents. Finally, he gives a table showing the conductivity of dilute sulphuric acid of specific gravities between 1.200 and 1.250. The maximum value 691.9×10^{-7} is reached at a temperature of 17.3°C . at a specific gravity of 1.224.—*Wied. Ann.*

THE NEW ENGLAND PORTELECTRIC COMPANY'S SYSTEM OF TRANSPORTATION.

SINCE the close of the exhibition of the model of the portelectric in the "Old South Church," Boston, over a year ago, persistent and unremitting efforts have been made to determine all the conditions neces-

sary for the construction of a commercial line for practical business purposes. Much delay has been caused in the progress of the work by the severe and uncalled for test to which the invention was put by the contracted course which the company was compelled to adopt, and which gave little opportunity for straight runs, so essential to the development of high speed.

The present experimental track is situated at Dorchester, Mass., and the tests have been carried on under the supervision of Mr. J. T. Williams, the inventor of the system, assisted by Prof. A. E. Dolbear, the electrician of the company. In a report recently made by Franklin L. Pope, we gather some interesting details as to the methods employed and the possibilities of the system.

The experimental plant at Dorchester comprises an endless track, Figs. 1 and 2, elevated upon a wooden trestle a few feet above the ground, 2,794 feet in circuit, consisting of one tangent of 492 feet and another of 430 feet long, united at their ends by two curves, one of which is 1,092 feet long and 282.5 feet radius and the other 780 feet long and 234.4 feet radius. The track in the first tangent of 588 feet is level, while in other portions of the circuit are grades rising to a maximum of $4\frac{1}{2}$ per cent., or 227 feet per mile.

The track consists of an upper and a lower rail,

all of which, being fitted with ball bearings, revolve with very slight friction.

The propelling power is derived from a series of hollow helices of insulated copper wire, each of which encircles the track and carrier. These are fixed along the permanent way at intervals measuring 6 feet from center to center. Each helix is composed of 630 turns of No. 14 copper wire, in five layers, weighing about 20 pounds, and having a resistance of about 5 ohms. A contact wheel, mounted upon the carrier, and running in contact with the upper track rail (which is divided into sections, and utilized as an electric conductor), connects the several helices in succession with the source of electricity as the carrier moves forward upon the track.

The electric current is supplied by a dynamo having a maximum capacity of about 8,000 watts, or a little over ten horse power, driven by a steam engine rated at ten horse power.

Experiments were first made to determine the maximum speed of carrier which could be obtained from the appliances in use at the time of inspection. This was found to be 2,784 feet in 56.5 seconds, or 49.3 feet per second, equal to 33.5 miles per hour.

The consumption of electric current, or rate of electric work while the carrier was in motion, was between

nine and ten electric horse power. The maximum tractive effort with a current of ten amperes was found to be 80 pounds. The electrical force producing this magnetic attraction was 6,300 ampere turns.

The rate of acceleration was found to be as high as 4.5 feet per second. The force of traction required to produce this acceleration, with the carrier of 500 pounds weight, is about 70 pounds.

A tractive effort of 70 pounds, exerted upon the carrier moving at the rate of 50 feet per second, requires the expenditure of 6.3 horse power, or 4,712 watts. As the average electrical energy supplied appeared to represent something like 8,000 watts, the efficiency of the helices and carrier, considered as an electric motor, may be estimated at about 60 per cent., which figure agrees very well with other determinations of solenoid magnets.

There are eight hundred and eighty helices, and seventeen thousand six hundred pounds of insulated wire per mile in the helices, in addition to that in the main conductors.

As each coil is ordinarily in circuit for only a fraction of a second at a time, it is evident that a volume of current per unit of sectional area may be used with impunity in this case which would be wholly inadmissible under ordinary conditions.

As each coil is ordinarily in circuit for only a fraction of a second at a time, it is evident that a volume of current per unit of sectional area may be used with impunity in this case which would be wholly inadmissible under ordinary conditions.

As each coil is ordinarily in circuit for only a fraction of a second at a time, it is evident that a volume of current per unit of sectional area may be used with impunity in this case which would be wholly inadmissible under ordinary conditions.

As each coil is ordinarily in circuit for only a fraction of a second at a time, it is evident that a volume of current per unit of sectional area may be used with impunity in this case which would be wholly inadmissible under ordinary conditions.

As each coil is ordinarily in circuit for only a fraction of a second at a time, it is evident that a volume of current per unit of sectional area may be used with impunity in this case which would be wholly inadmissible under ordinary conditions.

As each coil is ordinarily in circuit for only a fraction of a second at a time, it is evident that a volume of current per unit of sectional area may be used with impunity in this case which would be wholly inadmissible under ordinary conditions.

As each coil is ordinarily in circuit for only a fraction of a second at a time, it is evident that a volume of current per unit of sectional area may be used with impunity in this case which would be wholly inadmissible under ordinary conditions.

As each coil is ordinarily in circuit for only a fraction of a second at a time, it is evident that a volume of current per unit of sectional area may be used with impunity in this case which would be wholly inadmissible under ordinary conditions.

As each coil is ordinarily in circuit for only a fraction of a second at a time, it is evident that a volume of current per unit of sectional area may be used with impunity in this case which would be wholly inadmissible under ordinary conditions.

As each coil is ordinarily in circuit for only a fraction of a second at a time, it is evident that a volume of current per unit of sectional area may be used with impunity in this case which would be wholly inadmissible under ordinary conditions.

As each coil is ordinarily in circuit for only a fraction of a second at a time, it is evident that a volume of current per unit of sectional area may be used with impunity in this case which would be wholly inadmissible under ordinary conditions.

As each coil is ordinarily in circuit for only a fraction of a second at a time, it is evident that a volume of current per unit of sectional area may be used with impunity in this case which would be wholly inadmissible under ordinary conditions.

As each coil is ordinarily in circuit for only a fraction of a second at a time, it is evident that a volume of current per unit of sectional area may be used with impunity in this case which would be wholly inadmissible under ordinary conditions.

As each coil is ordinarily in circuit for only a fraction of a second at a time, it is evident that a volume of current per unit of sectional area may be used with impunity in this case which would be wholly inadmissible under ordinary conditions.

The provision for power required to propel the carrier at the assumed rate of 150 miles per hour may be taken at fifteen hundred volts and seven amperes per forty miles of single track, or about 0.33 horse power of generating capacity per mile. This may be estimated, including steam plant and buildings, at \$125 per horse power, or say \$45 per mile.

The actual cost of the electric power required to propel the carrier at this rate may fairly be taken at five cents per horse power hour, including cost of attendance at stations. The mere cost of power for propelling a carrier from Boston to New York would, therefore, not exceed seventy-five cents per trip.

Excessive estimates of the cost of a double track line, making liberal allowances in all directions, do not exceed \$35,000 per mile, or about \$7,000,000 for a line between Boston and New York.—*Elec. Engineer.*

THE ELECTRIC TRAMWAY AT BUDAPEST.*

By F. UPPENBORN.

THE use of overhead conductors for tramway purposes introduces in many plants almost insuperable difficulties. In many large towns especially it will not be possible to obtain the permission for this kind of working, and the choice will therefore mostly have to be made between accumulators and underground conductors. Traction by means of accumulators has many points preferable over the other arrangement. Independence of a central station, which was formerly considered as a chief consideration, has gradually lost its importance in the course of successful endeavors to raise the safety of central station working on the one hand and the security of the connection of the electric car to the central station on the other. The most important advantage arises from the fact that accumulator cars can at once use the existing tramway lines. Against this advantage there are, however, many considerable disadvantages, among which we may point merely to a striking one—namely, the absence of an accumulator thoroughly suitable for tramway purposes and tested by lengthy work. This reason was at the time of choice of the system for the electric tramway at Budapest even more preponderating than it is at present, when we are, at any rate, in possession of satisfactory accumulators for stationary purposes. The decision was therefore made for underground conductors.

The electric tramway as it has been carried out and is already working in three streets of Budapest is a slotted conduit system, and in exterior appearance hardly differs at all from ordinary tramways. As shown in the cut, the rails, corresponding in some de-

SECTION OF BUDAPEST ELECTRIC TRAMWAY.

gree to the rails of the Haarmann system, are separated by a gap of 33 mm. (1.3 in.). One rail of the track is screwed by means of wrought iron angular fish plates on 18 cm. (7.1 in.) wide cast iron frames corresponding to the profile of the conduit running beneath this rail, and designed to receive the conductors. The conduit has an oval, egg-shaped profile, 28 cm. (11 in.) wide and 33 cm. (13 in.) high; at its upper side it has a 33 mm. (1.3 in.) wide gap corresponding to that of the rail, so that, as in other conduit systems, the slot in the rail leaves the conduit open at the top along its whole length. The iron frames, on which the double rail is screwed, occur at intervals of 1.2 m. (4 ft.). Besides supporting and fastening the rail they serve also as skeleton to the conduit, and, further, they carry the insulators supporting the electric conductors. The conduit, the whole of which runs at a constant depth of 57 cm. (22.44 in.) beneath the upper border of the pavement and rail, is built in concrete between the iron frames, the frames being used as guides. The rails have the requisite strength to bear with safety any street loads occurring between the two supporting frames. The lateral pressure of the pavement, tending to straighten the gaps between the two single rails, is sufficiently provided for by the angular fish plates.

The second rail of the track has only a subordinate importance, as no conduit extends beneath it. It can be, therefore, carried out on any system, such as the Phoenix rail, as Vignoles rail without furrow, eventually even as a simple flat rail. In Budapest, for this second rail, the double tram rail of Haarmann has been used. Its two single rails are held together by bolts, and the two double rails of the line are connected together at intervals by track rods, as shown.

In the inner flanges of the iron frames, box-shaped insulators are inserted, carrying the electric conductors inside the conduit. The conductors consist of angular iron bars, which have, at a sufficient conductivity, the requisite strength to resist the wearing away caused by the friction of sliding contacts. The two conductors, one of which serves as lead and the other as return, lie perfectly protected beneath the rails, so that from without they can be neither seen nor touched. The conductors are situated so high above the bottom of the conduit that the surface water collecting in the conduit can flow away beneath the conductors without coming into contact with them. Shaft drains, to admit the surface water, are arranged at intervals close to the conduit. The water, after being separated from any possible slime, flows out of these

*Translated from *Elektrotechnische Zeitschrift*.—*Electrical Engineer*.

FIG. 3.—CARRIER OF THE PORTELECTRIC SYSTEM.