Associate Members—continued.

WILLIAM WATTS RATCLIFF.	FRANCIS LONGSTRETH THOMPSON, B.Sc.
WILLIAM HENRY REAN.	(Engineering) (<i> Lond.</i>), Stud. Inst.
WILLIAM BRUCE ALMON RITCHIE, B.Sc.	C.E.
(<i>Birmingham</i>).	JOHN BELL LANGHORN THOMPSON, Stud.
RONALD MELVILLE SCOTT, B.E. (<i>Adelaide</i>).	Inst. C.E.
LESLIE AINSWORTH SELICK, B.Sc.	ROBERT FRANCIS STAFFORD THOMPSON,
(Engineering) (<i> Lond.</i>), Stud. Inst.	Stud. Inst. C.E.
C.E.	CYRUS ELLERTON TILDESLEY.
JAMES MAXWELL SMITH SHAND.	GEORGE GORDON TAYLOR TOLLER.
FERGUS WILLIAM SLANE.	NORMAN HOWARD BESTALL TRIMMER.
ALAN THOMAS COCKBURN SMITH, B.Sc.	RANDLE HENRY NEVILLE VAUDREY,
(<i>Edin.</i>).	B.Sc. (<i>Birmingham</i>).
ERIC ROSKILLY SMITH.	STANLEY CECIL HAYTER WARREN, Stud.
CHARLES NORMAN STUART, Stud. Inst.	Inst. C.E.
C.E.	GEORGE FREDERICK WHITE.
JOSEPH SUTCLIFFE, B.Sc. Tech. (<i>Manchester</i>).	FREDERICK JAMES WILLSON, B.A.
	(<i>Cantab.</i>).
	ERNEST HAZELL WILSON, B.A. (<i>Cape</i>),
	B.Sc. (<i>Glas.</i>).

THE "JAMES FORREST" LECTURE, 1915.

The PRESIDENT said the members were assembled to hear the Twenty-third "James Forrest" Lecture, the delivery of which had been delayed, owing to unavoidable circumstances, beyond the end of Session 1914-15. Unfortunately, the lecturer, Mr. H. M. Hobart, had found it impossible to leave America to deliver the Lecture personally, and in these circumstances he had asked his friend Mr. Aspinall to deliver it for him. Mr. Aspinall's consent to this request had been greatly appreciated by Mr. Hobart, as the President was sure it would be also by the members. It was quite unnecessary to introduce Mr. Aspinall.

Mr. James Forrest, in whose honour the Lectures were founded, had now entered upon his ninety-first year. In doing so he sent a message of respect to the Council and of continuing affection for and interest in The Institution, in reply to which the Council had had the pleasure of expressing their compliments and best wishes on the occasion. Mr. Forrest's association with The Institution had extended over a period of nearly 73 years, and the members sincerely hoped that he might live to read many more Lectures delivered in his honour.

“Electrical Railways.”

By HENRY METCALF HOBART, M. Inst. C.E.

Delivered on his behalf by JOHN A. F. ASPINALL, M. Inst. C.E.

RETROSPECTIVE.

DURING the last 25 years electricity has been employed to a rapidly-increasing extent as a motive power for trains. At the beginning of this period the art of manufacturing electricity was in its incipient stages, the supply was limited, and the cost was high. The growth of the electricity-supply business has been very rapid, and thousands of miles of railways are so situated as to be able to purchase at a very low price all the electricity they would require were they to undertake to adopt electric propulsion for their entire traffic.

Although trains hauled by electric locomotives were in regular operation in 1890 on the City and South London Railway, the first application of electricity to train haulage in America was in May, 1895, when electric locomotives were employed by the Baltimore and Ohio Railroad to haul trains through its Belt Line Tunnels in Baltimore. The rate at which the electrification of sections of American steam railways has grown since that date may be seen from the following Table :—

Year.	A.—Electrically-Equipped Single-Track Mileage of Steam Railways in the United States and Canada.	B.—Total Single-Track Mileage of Steam Railways in the United States and Canada.	$\frac{100 A}{B}$
	Miles.	Miles.	
1895	8	233,000	..
1900	51	259,000	..
1905	215	307,000	..
1910	1,580	352,000	0·45
1915 ¹	3,460	380,000	0·91

The above figures, however, do not indicate the growth of the electric railway industry in America. The greatest activity has heretofore related chiefly to independent electric railway undertakings not necessarily involving the operation of trains. The

¹ The figures for 1915 include mileage now being electrified.

rapid growth of this business is indicated by the statistics in the following Table:—

Year.	Total Single-Track Mileage of Electric Railways in the United States and Canada.	Total Number of Motor Cars.
	Miles.	
1890	1,260	5,600
1895	12,100	26,000
1900	19,300	43,600
1905	32,500	64,000
1910	40,000	89,600
1915	45,000	100,000

Thus we see that in 1915, while the electric railways in the United States and Canada comprise an aggregate of 45,000 miles of single track, the electrically-equipped single-track mileage of steam railways is only 3,460 miles, and still constitutes less than 1 per cent. of the total single-track mileage of steam railways.

RAPID DECREASE IN COST OF ELECTRICITY.

The accelerated growth of the electric railway industry has been in no small measure a consequence of, and has also been a contributory cause of, the continual decrease in the cost of manufacturing electricity. It would have been impossible 20 years ago to manufacture electricity at a cost of much less than 2*d.* per kilowatt-hour. Ten years ago a price of 1*d.* per kilowatt-hour would usually have been the minimum permitting of any profit. At present there are electricity-supply undertakings which could make a profit in supplying electricity to railways in their district at but little over $\frac{1}{2}$ *d.* per kilowatt-hour. Indeed, many millions of kilowatt-hours have during the last couple of years been delivered on the premises of the Butte, Anaconda and Pacific Railway at a price of 0·265*d.* per kilowatt-hour, and employed by the railway in the movement of millions of tons of ore and other freight. In the electric operation of 440 miles of its main line over the Rocky Mountains, the Chicago, Milwaukee and St. Paul Railway will pay 0·260*d.* per kilowatt-hour for electricity delivered to its high-pressure tie-in line. In both these cases the electricity is generated from water-power, and the conditions are exceptionally favourable.

Fifteen years ago the best available electricity-generating sets consisted of low-speed reciprocating engines direct-connected to

electric generators. A 3,000-kilowatt set was considered to be about as large as could be used to advantage. Such an engine and generator cost some £30,000 (or £10 per kilowatt). At present 30,000-kilowatt steam-turbine-driven sets are available at a price considerably below £60,000—that is to say, the set with ten times the output costs less than twice as much.

Furthermore, while the 3,000-kilowatt generating set of 15 years ago consumed some 18 lbs. of steam per kilowatt-hour, the present-day 30,000-kilowatt set only consumes some 12 lbs. of steam per kilowatt-hour, i.e., two-thirds as much. The corresponding progress in steam-raising plant and condensing plant has also been by no means inconsiderable, and in conjunction with the requirement of only two-thirds as much steam and fuel, may be roughly taken as at least halving the initial outlay per rated kilowatt installed, for these components of an electricity manufacturing plant.¹

RELATIVE MERITS OF HYDRO-ELECTRIC AND STEAM STATIONS.

Developments in hydro-electric installations for manufacturing electricity have been also very satisfactory, but in districts where coal is obtainable at a low price it is rarely possible for a hydro-electric plant to supply electricity at a competitive price except for applications with a fairly high load-factor. The influence of the load-factor on the relative appropriateness of steam and hydro-electric means of manufacturing electricity is very appreciable, and it is important that it should be understood. For a hydro-electric undertaking which is not dependent (or but slightly dependent) upon storage water or steam reserve, the annual cost of supplying any consumer is closely proportional to the kilowatts of his maximum demand, and is nearly independent of the quantity of electricity which he consumes per annum. For example, if a railway's maximum demand from a typical hydro-electric station is 30,000 kilowatts, it costs almost as much to supply the demand irrespective of whether the 30,000 kilowatts is required for 24 hours a day during the entire 365 days in the year, which would amount to 262 million kilowatt-hours per annum, or whether it is only required for, say, one-tenth of the time. In the latter case the cost per kilowatt-hour would be nearly ten times as great as in the former case. But in a coal-burning generating-station the annual outlay for fuel is fairly proportional to the total number of kilowatt-

¹ In this connection reference should be made to a Paper by Messrs. Stott, Pigott and Gorsuch, entitled "Present Status of Prime Movers": *Proc. Am. Inst. Elec. Eng.*, vol. xxxiii (1914), p. 953.

hours consumed per annum, and with coal at anything more than an exceedingly low price, the outlay for the coal will be quite a substantial percentage of the total cost of manufacturing the electricity. The very low initial cost per kilowatt, of large modern electricity-supply stations employing steam turbines, contributes largely to bringing this about. The price for electricity manufactured in a coal-burning station is consequently much less controlled by the maximum demand and much more controlled by the quantity of electricity consumed in a given time than in the case of a hydro-electric undertaking. While all outlays for water-storage or steam reserves for a hydro-electric undertaking tend to increase the

Fig. 1.

INTERDEPENDENCE OF COST OF ELECTRICITY AND LOAD-FACTOR
FOR STEAM AND HYDRAULIC STATIONS.

influence of the total kilowatt-hour consumption on the cost, there can be very liberal provisions of this kind without materially impairing the correctness of the proposition that a high load-factor will permit of effecting a greater reduction in the cost of manufacturing electricity (as compared with the cost of the same quantity of electricity but of low load-factor) in the case of a hydro-electric station than in the case of a coal-burning generating-station.

On various occasions engineers have drawn attention to this distinctive difference between hydro-electric and steam-electric generating-stations. The arrangement of the curves in *Figs. 1* and *2* was suggested by data given by Mr. Henry Flood, jun., in a

Paper¹ entitled "Hydro-Electric Development." The curves are based on appropriate assumptions as to the first cost of a hydro-electric station and a transmission-line to the desired district in the one case, and of a steam station located in that district (and hence not requiring a transmission-line) in the other case. It will be seen that while the fixed charges are much lower than the operating costs for the steam undertaking, the reverse is the case for the hydro-electric undertaking. This is in accordance with the well-known attributes of such undertakings, and requires no comment. The two curves of the Total Cost of Electricity in *Fig. 1* are brought together in *Fig. 2*, from which it is seen that while, for

Fig. 2.

COMPARATIVE COST OF ELECTRICITY, FOR STEAM-ELECTRIC AND HYDRO-ELECTRIC STATIONS.

very low load-factors, the steam undertaking can supply electricity at the lowest cost, when we come to load-factors above 0.20 the hydro-electric undertaking has the advantage, and that for unity load-factor the hydro-electric undertaking can supply electricity at practically half the price attainable with the steam undertaking. While every case requires a separate analysis, it may be said that

¹ Read at Schenectady on the 7th May, 1915, at a joint meeting of the Eastern New York Section of the National Electric Light Association and the Empire State Gas and Electric Association. Mr. F. G. Baum also elaborates the distinction in a Paper entitled "Class Rates for Electric Light and Power Systems or Territories": *Proc. Am. Inst. Elec. Eng.*, vol. xxxiv (1915), p. 485.

the curves in *Figs. 1* and *2* are thoroughly typical. Since an extensive electrically-operated railway will have a fairly good load-factor, the curves indicate one reason for the remarkable progress which has already been made with railway electrification in countries which are rich in water-power.

INFLUENCE OF THE FUEL COST ON THE COST OF MANUFACTURING ELECTRICITY IN STEAM-ELECTRIC GENERATING-STATION.

The total cost of manufacturing electricity may conveniently be considered as made up as follows¹ :—

Total Cost of Electricity at Outgoing Cables from Generating-Station.	Production Costs.	<ul style="list-style-type: none"> Fuel. Oil and Stores. Wages and Salaries. Repairs. Interest.
	Investment Costs.	<ul style="list-style-type: none"> Rates and Taxes. Insurance. Amortization.
	Administration Costs.	

It is desired to set forth the effect exerted on the Total Cost by variations in the Fuel Cost, all the other component costs remaining unchanged. Consequently, for the above scheme of segregation of costs we shall substitute the following :—

Total Cost of Electricity at Outgoing Cables from Generating-Station.	<ul style="list-style-type: none"> Fuel Component of Production Costs. Remaining Components of Production Costs, plus Investment Costs, plus Administration Costs.
---	--

This has been worked out for a 150,000-kilowatt generating-station equipped with five 11,000-volt, 50-cycle, 1,500-revolutions per minute, three-phase, steam-turbine-driven generating sets, each with a continuous rating of 30,000 kilowatts at unity power-factor. The station has a favourable location as regards an ample supply of circulating water, and as regards low cost for land and buildings. The fuel has a calorific value of 14,000 B.Th.U. per pound. The load-factor at the generating-station is 0.50.

For such conditions representative figures for the costs per kilowatt-hour of output from a modern generating-station for various fuel costs are shown in the Table on p. 139.

It is interesting to note that increasing the price of fuel three-fold, namely, from 4s. per ton to 12s. per ton, increases the

¹ See Paper entitled "Standardization of Method for Determining and Comparing Power Costs," by H. G. Stott and W. S. Gorsuch: Proc. Am. Inst. Elec. Eng., vol. xxxii (1913), p. 1619.

Cost of Fuel per Ton.	Fuel Cost per Kilowatt-Hour	All Remaining Costs per Kilowatt-Hour.	Total cost per Kilowatt-Hour of Electricity as Delivered from the Generating-Station.
<i>s.</i>	<i>d.</i>	<i>d.</i>	<i>d.</i>
4	0·038	0·190	0·228
6	0·056	0·190	0·246
8	0·075	0·190	0·265
10	0·094	0·190	0·284
12	0·112	0·190	0·302

cost of the electricity, under these conditions, by 33 per cent., since $\frac{0\cdot302}{0\cdot228} = 1\cdot33$. The percentage influence of the cost of fuel

will obviously be less, the greater the aggregate of the remaining cost. For a generating-station located in or near a large city the greater cost for land and buildings alone might occasion a 100-per-cent. increase in the sum of all costs other than fuel, so that while with fuel at 4*s.* per ton the electricity would cost—

$$0\cdot038 + 0\cdot380 = 0\cdot418d. \text{ per kilowatt-hour,}$$

the cost with fuel at 12*s.* per ton would be

$$0\cdot112 + 0\cdot380 = 0\cdot492d. \text{ per kilowatt-hour,}$$

or an increase of only 18 per cent. in the cost of electricity with a three-fold increase in the price of fuel. For 8*s.* per ton the cost would be

$$0\cdot075 + 0\cdot380 = 0\cdot455d. \text{ per kilowatt-hour.}$$

The limitations of this lecture will only permit of touching briefly on the additional costs associated with the transmission of electricity over considerable distances, although this is a very important factor in the application of electricity to the working of main-line railways.

If the output of the 150,000-kilowatt generating-station above considered is transmitted by overhead conductors to an average distance of 100 miles, the additional investment costs associated with the step-up and step-down transformers and the transmission-line, together with the operating costs for these links in the system, will add about 0·18*d.* to the cost per kilowatt-hour, delivered at the 100-miles-distant, low-pressure terminals of the step-down transformers, if the load is transmitted over ten different routes, and

consequently subdivided amongst ten separate transmission-lines from the generating-station, each transmission-line comprising six conductors carried on steel towers. But if the entire quantity of electricity were to be transmitted 100 miles *en bloc* over six conductors carried by a single line of steel towers, the increase in cost would only be of the order of 0·08*d.* per kilowatt-hour.

Reverting to the costs of electricity at the generating-station with fuel at 8*s.* per ton, which have already been set forth as ranging from 0·265*d.* to 0·455*d.* per kilowatt-hour, and adding these transmission costs, we have :—

Cost per Kilowatt-Hour of 0·5-Load-Factor, Unity-Power-Factor Electricity at the 150,000-Kilowatt Generating-Station, with Fuel at 8 <i>s.</i> per Ton.	Cost per Kilowatt-Hour Delivered from the Low-Pressure Terminals of the 100-Miles-Distant Step-Down Transformers.	
	Transmission <i>en bloc.</i>	Transmission over Ten Independent Lines of Towers.
<i>d.</i> 0·265	<i>d.</i> 0·345	<i>d.</i> 0·445
0·455	0·535	0·635

It should be evident that in other than an involved analysis, which would be quite beyond the scope of this Lecture, it would be out of the question to give more than the above broad indications of the order of magnitude of the costs under the various conditions which occur in dealing with railway-electrification undertakings.

Higher load-factors reduce the investment costs and consequently also the total cost. The transmission of smaller quantities of electricity is associated with higher costs. Loads with a lagging power-factor, unless compensated by loads with a leading power-factor, can only be supplied at an increased cost. Every additional transformation of pressure, periodicity, or kind, of electricity increases the cost.

LOAD-FACTOR AND DIVERSITY FACTOR WITH ELECTRIC LOCOMOTIVES.

To obtain a high load-factor with electrically-propelled trains, it becomes necessary either to have a dense service or else to extend over a large mileage of track. By either expedient the object is accomplished of averaging the widely-varying individual consumptions of many electric locomotives. Even if the average consumption of an individual electric locomotive may, during several hours in service, only amount to, say, 15 per cent. of its maximum consumption during those hours—that is to say, even if its individual load-

factor is only 0.15—the combined average consumption of, say, thirty such locomotives will have a load-factor more of the order of, say, 0.60. If the thirty locomotives are all supplied with electricity from one source, the cost of the electricity will be that corresponding to the combined load-factor, which in the above example has been assumed to be 0.60. The ratio of the combined load-factor of the thirty locomotives to the average of their individual load-factors is termed the “diversity factor.” In our example the diversity factor is $\left(\frac{0.60}{0.15}\right) 4.0$.¹

Representing by 15 the average consumption of the single locomotive, then its maximum consumption is 100. The average consumption of the thirty locomotives is $(30 \times 15 =) 450$, and their maximum consumption is $\left(\frac{450}{0.6} =\right) 750$, or only 7.5 times the maximum consumption of a single locomotive. The sum of the maximum consumptions of the thirty locomotives is $(30 \times 100 =) 3,000$. The diversity factor of the system is $\left(\frac{3,000}{750} =\right) 4.0$.

One of the most important attributes of the electric-locomotive system of propelling trains relates to the ability to take scientific advantage of the diversity factor of a system comprising many locomotives in providing a high resultant load-factor and to secure economies incident thereto. In fact, the resultant load-factor of the railway's load will combine with the resultant load-factor of the loads of other consumers to yield an ultimate resultant load-factor at the generating-station which will usually be appreciably better than the railway's own load-factor. Consequently, a railway rarely manufactures its own electricity, for its own exclusively-railway

¹ The following are approved definitions of the terms “load-factor” and “diversity factor” :—

“The *Load Factor* of a machine, plant or system. The ratio of the average power to the maximum power during a certain period of time. The average power is taken over a certain period of time, such as a day, a month, or a year, and the maximum is taken as the average over a short interval of the maximum load within that period.

“In each case the interval of maximum load and the period over which the average is taken should be definitely specified, such as a ‘half-hour monthly’ load-factor. The proper interval and period are usually dependent upon local conditions and upon the purpose for which the load-factor is to be used.” (Standardization Rules of Am. Inst. Elec. Eng. Edition of 1 July, 1915, p. 12.)

“The *Diversity Factor* is the ratio of the sum of the maximum power demands of the subdivisions of any system or parts of a system to the maximum demand of the whole system or of the part of the system under consideration, measured at the point of supply.” (Standardization Rules of Am. Inst. Elec. Eng. Edition of 1 July, 1915, p. 13.)

load, at so low a cost as that at which it can be manufactured by an electricity-supply company whose system comprises the loads of other large consumers.

ELECTRIC-LOCOMOTIVE OPERATION OF MOUNTAIN-GRADE RAILWAYS.

It is only recently that the electrical industry has grown to the stage which permits of putting these principles into practice on so large a scale as to conclusively demonstrate their correctness. The first extensive application of electric propulsion to a mountain-grade system employing a considerable number of freight locomotives is that of the Butte, Anaconda and Pacific Railway, which will now be described.

THE BUTTE, ANACONDA AND PACIFIC 2,400-VOLT RAILWAY.¹

Prior to the summer of 1913 the trains on the Butte, Anaconda and Pacific Railway were hauled exclusively by steam locomotives. The railway comprises 114 miles of single track, of which some 70 miles is in yards and sidings. There is very little tangent track in the course of the entire 114 miles. For the 12 months preceding June, 1913, the traffic aggregated about 760,000 locomotive-miles. This traffic was handled with twenty-seven steam locomotives, giving an average of 28,000 miles per steam locomotive per year. The steam locomotives were of the following types:—

Number.	Type.	Average Weight with Loaded Tender.	Weight on Drivers.
15	Consolidation and Miscellaneous . .	British Tons. ² 138	British Tons. 74
10	Mastodon	145	74
2	Passenger	118	54
27	= Total number of steam locomotives.		

¹ The Author wishes to acknowledge the cordial assistance which has been given to him by Mr. J. B. Cox in those sections of the Lecture which relate to the electrification of the Butte, Anaconda and Pacific Railway. Mr. Cox was responsible for the installation of the electric locomotives on this railway and is the Author of two Papers in which the railway is described, namely: "The Electrical Operation of the Butte, Anaconda and Pacific Railway," Proc. Am. Inst. Elec. Eng., 1914, p. 1729, and "Contact System of the Butte, Anaconda and Pacific Railway," Proc. Am. Inst. Elec. Eng. 1915, p. 1447.

² Throughout this Lecture the ton of 2,240 lbs. has been used, and in most instances this has been expressly termed the British ton to avoid any confusion with the 2,000-lb. ton usually employed in America.

The 760,000 locomotive-miles per annum were distributed as follows:—

Service.	Locomotive-Miles per Annum.	Percentage of Total Annual Locomotive-Miles.
		Per Cent.
Switching	310,000	41
Freight	300,000	39
Passenger	84,000	11
Non-revenue and special	66,000	9
Total	760,000	100

The annual coal-consumption for these twenty-seven locomotives amounted to 67,000 British tons. This reduces to 197 lbs. of coal per locomotive-mile. The price of the coal, delivered at the bins of the railway company, was 19s. per British ton. This works out at a fuel cost of 19·9*d*. per locomotive-mile. The fuel is lignite, and has a calorific value of 12,250 B.Th.U. per pound (3·60 kilowatt-hours per pound).¹

Ninety-one miles of single-track of this system have now been equipped for electric operation, and all but four of the twenty-seven steam locomotives have been withdrawn from service. The remaining 23 miles of single track will soon be ready for electric operation, and the four steam locomotives will then be withdrawn. They are at present employed chiefly on various duties on a system of non-electrified tracks and sidings at the copper mines on Butte Hill.

At present the annual traffic is slightly greater than during the last year of "all-steam-locomotive" operation. This traffic is handled with seventeen electric locomotives and the four steam locomotives above mentioned. These four steam locomotives now account for 130,000 locomotive-miles per annum, or an average of 32,500 miles for each locomotive. They are burning 11,200 British tons of coal per annum, or 193 lbs. per locomotive-mile. This, at 19s. per ton, amounts to 19·5*d*. per locomotive-mile, substantially the same figure per locomotive-mile as during the time of "all-steam-locomotive" operation.

¹ One kilowatt-hour = 3,411 B.Th.U. Consequently, for coal of this quality, the calorific value of a British ton is $\left(\frac{2,240 \times 12,250}{3,411} = \right)$ 8,100 kilowatt-hours.

The seventeen electric locomotives are at present accounting for 700,000 locomotive-miles per annum. This is an average of 41,000 miles per electric locomotive per annum. The energy consumed by the seventeen electric locomotives requires the supply to the sub-stations of 18,500,000 kilowatt-hours of electricity per annum, or 26·3 kilowatt-hours per locomotive-mile. The electricity is delivered to the sub-stations at a price of 0·265*d.* per kilowatt-hour. Consequently the expenditure for electricity per locomotive-mile amounts to $(26·3 \times 0·265 =) 7d.$

Tabulating these results we have—

		Outlay for Fuel and Power per Locomotive-Mile. <i>d.</i>
Prior to the summer of 1913, when employing twenty-seven steam locomotives		19·9
At present, with four steam loco- motives and seventeen electric locomotives	<div> <div>Per steam locomotive- mile</div> <div>Per electric locomotive- mile</div> </div>	<div> 19·5 </div> <div>7·0</div>

Thus the outlay for electricity per locomotive-mile is only 7*d.* as against an outlay of 19·9*d.* for coal per steam locomotive-mile. Too much significance, however, should not be attached to this ratio, since it is largely dependent upon local conditions. For the same price (0·265*d.* per kilowatt-hour) for electricity, but with coal of the same quality—at, say, 8*s.* per ton—the outlay for fuel per locomotive-mile would only have been $(8/19 \times 19·5 =) 8·2d.$ per steam locomotive-mile. Furthermore, notwithstanding the gradual decrease in the cost of manufacturing electricity, conditions will usually make it quite out of the question to obtain electricity at so low a price as 0·265*d.* per kilowatt-hour. Had it been necessary to pay a 50-per-cent.-higher price for the electricity—namely, 0·40*d.* per kilowatt-hour—the outlay for electricity per locomotive-mile would have been 10·5*d.*, which would correspond to an outlay for fuel per steam locomotive-mile on the basis of coal at $\left(\frac{10·5}{19·5} \times 19 =\right) 10·2s.$ per ton.

Each of the seventeen electric locomotives weighs 72 British tons, and the entire weight is on drivers. The weight per axle is 18 tons. Fifteen are employed in freight service and two in passenger service. A type of motor, known as the G.E. 229-A, is employed both on the freight- and passenger-locomotives, the only difference relating to the gear ratio, which for the freight-locomotives is $(87 : 18 =) 4·83$, and for the passenger-locomotives is $(80 : 25 =) 3·20$, the passenger-locomotives thus having a 51-per-cent.-higher speed for a given speed of the armature. The locomotives receive 2,400-volt

direct current¹ (d.c.) electricity from overhead conductors by means of roller pantograph trollies. Each of the four motors constituting the equipment of a locomotive is wound for a working pressure of 1,200 volts, and the winding is insulated for a pressure to ground of 2,400 volts. The motors are permanently connected in pairs of two in series. By series-parallel control the two pairs can be operated in series or in parallel with one another. The maximum free running speed of the freight-locomotives is about 35 miles per hour. Each freight-locomotive is capable of developing continuously a tractive effort of 25,000 lbs. at 16·2 miles per hour, the corresponding output at the drivers being—

$$\frac{25,000 \times 16 \cdot 2 \times 5,280}{60 \times 33,000} = 1,080 \text{ HP.}$$

At starting, the locomotive provides a tractive effort of 40,000 lbs. for a coefficient of adhesion of 0·25, and 48,000 lbs. for a coefficient of adhesion of 0·30. The thermal characteristics are such as to permit of the development of a tractive effort of 48,000 lbs. for 5 minutes, starting cold. This 5-minute rating provides a valuable margin for the slow acceleration from rest of long freight-trains on heavy grades; in other words, it provides liberal emergency capacity. Another occasion when this 5-minute rating is utilized is when a very long freight-train is headed by one locomotive and pushed by another. The inability to maintain prompt communication between the ends of a long train may occasion the pusher to consume electricity for some time in the vain attempt to start the train without the co-operation of the locomotive at the head of the train. A properly-designed freight-locomotive serving as pusher under these conditions can, for some 5 minutes, absorb without any injury enough electricity to slip the driving wheels. The electrical equipment of the locomotive weighs 60,000 lbs., or 55·5 lbs. per HP. of continuous output at the rims of the drivers. Conversely expressed, the locomotive is capable of delivering continuously at the drivers an output of 40·5 HP. per British ton of weight of electrical equip-

¹ The term "direct current" (or d.c.) is used throughout instead of "continuous current" in order to avoid confusion with the use of the word "continuous" as a kind of rating. The British Engineering Standards Committee and the American Institute of Electrical Engineers both subdivide ratings into two sorts; the one sort is termed the "Continuous Rating" and the other sort is termed the "Short-Time Rating." This use of the word "continuous" has recently become of such frequent occurrence in electrical engineering publications as to render it desirable to avoid its use for designating a "kind" of electrical current.—H. M. H.

ment. The motors are cooled by the circulation through them of air supplied from a motor-driven blower.

The traffic of the Butte, Anaconda and Pacific Railway has up to the present consisted chiefly in the transportation of some five million tons of ore annually from the copper mines on Butte Hill to the Washoe Smelter on Smelter Hill, a distance of about 31·5 miles by rail. This section has grades up to 2·5 per cent. at some portions. Owing to the success of the electrical service, it was, in 1914, decided to treat at the Washoe Smelter a further one million tons of ore per year which had previously been treated at the Great Falls Smelter. The total quantity of ore transported annually will consequently henceforth be more of the order of at least six million tons. To provide for this increase, additional sub-station machinery has been installed and also four more electric freight-locomotives.

Four tractor trucks have also been added to the rolling-stock equipment. Each tractor truck is equipped with two motors and can be used with any one of the nineteen freight-locomotives which are equipped with the necessary switch and cable connections. A locomotive with its tractor truck carries six motors, and the combination has a weight of 108 British tons. The control is so arranged that the six motors can be operated either all in series or in two parallels of three in series. A locomotive with one of these tractors is thus capable of exerting continuously a tractive effort of 37,500 lbs. at 10·8 miles per hour.

For a road of the character of the Butte, Anaconda and Pacific Railway it is difficult to arrive at a satisfactory basis on which to establish comparisons. The locomotive-mile is an unsatisfactory common denominator, since widely-different abilities pertain to different types of electric locomotives. The difficulty is accentuated by the large percentage which the "switching" mileage and the "non-revenue and special" mileage bear to the total annual mileage of the locomotives. These percentages are as follows:—

Kind of Locomotive-Mileage.	Percentage of Total Annual Locomotive-Mileage.	
	With Twenty-Seven Steam Locomotives.	With Four Steam and Seventeen Electric Locomotives.
	Per Cent.	Per Cent.
Switching	40·5	32·9
Non-revenue and special	9·3	4·3
"Switching" plus "Non-revenue and special"	49·8	37·2

The data in the above Table afford evidence of the superiority of the electric locomotive for switching work and of the relatively small amount of non-revenue mileage associated with its use.

The net ton-mileage of freight carried annually by the railway is at present some 170 million ton-miles. No data are available to show the total ton-mileage, but, exclusive of the locomotives, it is probably about 340 millions. Exclusive of the passenger service, the locomotive-mileage is about 775,000 per annum, making a further $(72 \times 775,000 =)$ 56 million ton-miles, or a total, including locomotives, of some 400 million ton-miles per annum.

Increased Weight of Trains Hauled by Electric Locomotives.—Whereas in the days of “all-steam-locomotive” operation the average weight of the ore trains for the main-line portion of the journey from the mines to the smelter (i.e., for the 20-mile run from Rocker to East Anaconda shown in *Fig. 3*) was about 1,600 British tons, the average weight with electric traction has been increased 35 per cent. to about 2,100 British tons. Trains composed of sixty-five loaded ore cars, with an average weight of about sixty-three British tons per car, headed by two 72-ton electric locomotives and weighing (complete with locomotives) 4,300 tons, are drawn up gradients of 0·3 per cent., the drawbar-pull under these conditions amounting to about 48,000 lbs. The empty cars each weigh about 18 tons, the load of ore averaging 45 tons per car.

In the “all-steam-locomotive” days a Mastodon locomotive, weighing, with loaded tender, 141 tons, was accustomed to haul up this 0·3-per-cent. grade fifty to fifty-five loaded ore cars at a speed of about 7 miles per hour. With fifty-five loaded ore cars the total train weight was about 3,600 tons.

The speed of two 72-ton electric locomotives when hauling these 4,300-ton trains up the 0·3-per-cent. grade is about 16 miles per hour, or over twice as great as the speed of the lighter trains formerly hauled by steam locomotives.

“Drivers-to-drawbar” Efficiency of Locomotives.—The term “drivers-to-drawbar” efficiency of a locomotive may be defined as the percentage which the work delivered from the drawbar of a locomotive constitutes of the work delivered from the rims of the drivers. Otherwise expressed—

$$\text{“Drivers-to-drawbar” efficiency} = \frac{100 \times \text{drawbar pull}}{\text{tractive effort}}.$$

There should be no need to discuss the obvious modifications of this definition which are required when more than one locomotive is employed for hauling a train, or when an additional locomotive is employed at the rear of the train as a pusher.

Let us examine the "drivers-to-drawbar" efficiencies of the electric and steam trains described above. On the basis of 6 lbs. per ton for train resistance, the tractive effort required for the 4,300-ton train, comprising two 72-ton electric locomotives and 4,156 tons behind the drawbar, is, on a 0·3-per-cent. grade—

$$(0\cdot3 \times 22\cdot4 + 6) \times 4,300 = 55,000 \text{ lbs.}$$

Assuming that the frictional resistance of the locomotives, expressed in pounds per ton, is the same as that of the loaded ore cars, i.e., assuming that it is 6 lbs. per ton both for locomotives and cars, then the "drivers-to-drawbar" efficiency for these conditions is—

$$\frac{4,300 - 2 \times 72}{4,300} \times 100 = 96\cdot9 \text{ per cent.}$$

For the steam train representative of the practice on this road prior to electrification the total weight of the train was—

$$55 \times 63 + 141 = 3,470 + 141 = 3,611 \text{ tons.}$$

Again assuming the same pound-per-ton friction for the locomotives as for the ore cars, we have—

$$\text{"Drivers-to-drawbar" efficiency} = \frac{3,470}{3,611} \times 100 = 96\cdot2 \text{ per cent.}$$

Available data regarding the frictional resistance of locomotives are very meagre. In the absence of adequate data of the resistance of locomotives of various types, and at given speeds, statements of the "drivers-to-drawbar" efficiency should be qualified with careful statements of the corresponding assumptions.

While for the case of heavy-freight trains on easy grades the "drivers-to-drawbar" efficiency is so high as not to constitute a factor of much importance, this is not the case for freight-trains on heavy grades, or for high-speed passenger-trains, as will appear from examples which will be given in the course of this lecture.

In *Fig. 3* is shown the profile of the 20 miles of main line between East Anaconda and Rocker. Below are given the results of two tests which have been carried out to determine the power-consumption at the locomotives when running over this 20-mile section:—

	Rocker to East Anaconda.	East Anaconda to Rocker.
Direction	Westbound	Eastbound
Distance	20 miles	20 miles
Number of cars in train	57 loaded cars	64 empty cars
Number of locomotives	2	2
Weight of each locomotive	72 tons	72 tons
Gross weight (including locomotives)	3,700 "	1,190 "
Gross ton-miles	74,000	23,800
Schedule speed	20 miles per hour	20 miles per hour
Total consumption	654 kilowatt-hours	852 kilowatt-hours
Consumption per ton-mile	8·8 watt-hours	35·8 watt-hours

It is interesting to attempt to segregate the energy-consumption measured on these tests. Let us first deal with the westbound run. The schedule speed was 20 miles per hour, and the maximum speed was about 32 miles per hour. Practically the entire consumption of electricity occurs on the last 8 miles from Gregson to East Anaconda, during which the train ascends 85 feet. Indeed, when the train enters upon this ascent the momentum-energy due to its speed is about 100 kilowatt-hours. We may assume that 30 kilowatt-hours of this momentum-energy offsets the electrical consumption from Rocker to Gregson, and that the remaining 70 kilowatt-

Fig. 3.

PROFILE OF THE BUTTE, ANACONDA AND PACIFIC RAILWAY BETWEEN EAST ANACONDA AND ROCKER.

hours relieves the motors (during the balance of the journey) by this amount. Since 1 kilowatt-hour = 2,659,000 foot-lbs., there will, for overcoming gravity through 85 feet, be required for the 3,700-ton train—

$$\frac{85 \times 3,700 \times 2,240}{2,659,000} = 265 \text{ kilowatt-hours.}$$

The friction of trains of heavily-loaded ore cars, expressed in pounds per ton, is very low, but in consideration of the frequent curves, it may for this journey be taken as 6 lbs. per ton. Then the energy

delivered from the motors to overcome friction during the journey amounted to—

$$\frac{6 \times 3,700 \times 8 \times 5,280}{2,659,000} = 355 \text{ kilowatt-hours.}$$

We now have—

For overcoming gravity	265 kilowatt-hours.	
„ „ friction	355	„
Available from momentum acquired prior to commencement of ascent	70	„

The output from the motors during the 20-mile journey amounts to—

$$265 + 355 - 70 = 550 \text{ kilowatt-hours.}$$

The input to the locomotives was 654 kilowatt-hours. Of this amount ($654 - 550 =$) 104 kilowatt-hours represents the losses in the electrical equipment. The efficiency of the electrical equipment for the westbound journey was $\left(\frac{550 \times 100}{654} =\right)$ 84·0 per cent.

The Frictional Resistance of Electric Locomotives.—For those portions of the journey during which the motors are propelling the train, the losses in friction of gearing and of commutator brushes, the bearing friction of the armature, and the windage friction of the armature and commutator are taken into account in the value of the efficiency of the electrical equipment. But during the times when the train is impelled exclusively by its own momentum or by gravity, these constitute components of the frictional resistance of the locomotive. In careful analyses of train movements it is sometimes of importance to have a full realization of the extent to which these components may affect the frictional resistance of the locomotive. The losses mentioned will, according to the particular design, usually amount to from 3 to 5 per cent. of the continuous rating of the electrical equipment. Taking 4·0 per cent. for the Butte locomotive, then when two locomotives are employed, as in the runs we have analysed, we have—

$$2 \times 1,080 \times 0\cdot040 = 86 \text{ HP.}$$

If we denote the corresponding resistance, in pounds per ton, by P, we have for the locomotives' rated speed of 16·2 miles per hour—

$$P = \frac{86 \times 60 \times 33,000}{16\cdot2 \times 5,280 \times 2 \times 72} = 14 \text{ lbs. per ton.}$$

In analysing the run from Rocker to East Anaconda, the resistance for the entire train was taken as 6 lbs. per ton. Since for coasting the frictional resistances associated with armatures, commutators and gears alone amount to 14 lbs. per ton, our assumption is only tenable on the basis of a frictional resistance of less than 6 lbs. per ton for the loaded ore cars, and materially more than 6 lbs. per ton for the resistance of the locomotives. Let us take the total resistance of the locomotives, when coasting, as 18 lbs. per ton. This leaves for the friction of the ore cars—

$$\frac{6 \times 3,700 - 18 \times 144}{3,700 - 144} = 5.5 \text{ lbs. per ton.}$$

On this assumption the portion of the resistance of the locomotives which is not included in the losses in the electrical equipment is $(18 - 14 =) 4$ lbs. per ton.

“Drivers-to-drawbar” Efficiency during the Westbound Run.—Taking into account these differences between the frictional resistance of locomotives and loaded ore cars, we have, for the “drivers-to-drawbar” efficiency—

$$\frac{5.5 \times 3,556 \times 100}{5.5 \times 3,556 + 4 \times 144} = 97.0 \text{ per cent.}$$

If the difference between the frictional resistance of the locomotives and loaded ore cars, in pounds per ton, had not been taken into account, the “drivers-to-drawbar” efficiency would have been $\left(\frac{3,556 \times 100}{3,700} =\right) 96.0$ per cent., the 1 per cent. difference in this case being of negligible consequence. Any distinction of this sort should, of course, be based upon quantitative measurements, and the example is merely given as suggesting the nature of the required data.

The total efficiency of the locomotive, “from pantograph to drawbar,” is equal to the “efficiency of the electrical equipment” multiplied by the “drivers-to-drawbar” efficiency. In this case we have—

$$\text{“Pantograph-drawbar” efficiency} = 84.0 \times 0.97 = 81.5 \text{ per cent.}$$

On the eastbound journey the locomotives hauled empty ore cars, whose friction is high. Let us take the friction of the complete train at 10 lbs. per ton. The first 8 miles consists of an average 0.20 per cent. down grade. This contributes $(0.2 \times 22.4 =) 4.5$ lbs. per ton towards overcoming train friction. The remaining 5.5 lbs.

per ton must be supplied from the motors. There is consequently required for this 8 miles—

$$\frac{5.5 \times 1,190 \times 8 \times 5,280}{2,659,000} = 105 \text{ kilowatt-hours.}$$

For the remaining 12 miles of the journey (i.e., from Gregson to Rocker) the train rises 260 feet, and requires—

For overcoming friction :

$$\frac{10 \times 1,190 \times 12 \times 5,280}{2,659,000} = 285 \text{ kilowatt-hours.}$$

For overcoming gravity :

$$\frac{260 \times 1,190 \times 2,240}{2,659,000} = 260 \text{ kilowatt-hours.}$$

The schedule speed was 20 miles per hour, and the maximum speed was 29 miles per hour. The momentum of the 1,170-ton train at 29 miles per hour is 28 kilowatt-hours. Let us assume that in originally acquiring speed and in accelerating after slow-downs, 60 kilowatt-hours was absorbed by the train in momentum-energy in the course of the 20-mile journey.

We now have—

	Kilowatt-hours.
Output from motors from East Anaconda to Gregson	105
" " " for overcoming friction for remaining 12 miles	285
" " " " " gravity " " " "	260
" " " " providing momentum	60
Total output from motors for 20-mile journey	710

Since the input was 852 kilowatt-hours, the losses in the electrical equipment were $(852 - 710 =)$ 142 kilowatt-hours. The efficiency of the electrical equipment for the eastbound journey was thus $\left(\frac{710 \times 100}{852} =\right)$ 83.3 per cent.

The "Drivers-to-drawbar" Efficiency during the Eastbound Run.—Again, taking the friction of the locomotives at 4 lbs. per ton, we have—

"Drivers-to-drawbar" efficiency

$$= \frac{10 \times 1,190 - 4 \times 144}{10 \times 1,190} \times 100 = 95.0 \text{ per cent.}$$

Had no distinction been drawn between the different frictional resistances of locomotives and empty ore cars, the result would have been—

“Drivers-to-drawbar” efficiency

$$= \frac{1,190 - 144}{1,190} \times 100 = 88.0 \text{ per cent.}$$

Here is a difference of 7 per cent. as against the difference of only 1 per cent. for the conditions of the westbound journey with

Fig. 4.

PROFILE OF THE BUTTE, ANACONDA AND
PACIFIC RAILWAY BETWEEN EAST
ANACONDA AND THE WASHOE SMELTER.

loaded ore cars. While in the one case the distinction is of importance, in the other case it is practically negligible.

The “pantograph-drawbar” efficiency for the eastbound trip is—

$$83.3 \times 0.95 = 79.2 \text{ per cent.}$$

The assumptions made in these calculations are, of course, of so rough a character as simply to indicate the approximate results.

In Figs. 4 and 5 are shown the profiles of the two portions of the

system connecting the main line with the Washoe Smelter and the Butte Hill mines respectively. The former has a ruling grade of 1·1 per cent. and an average grade of 1·02 per cent. The Washoe Smelter is located at an altitude of 380 feet above East Anaconda, and the distance by rail is 7 miles. The Butte Hill yards are 4·5 miles by rail from Rocker and 520 feet above it. This 4·5-mile section has a ruling gradient of 2·5 per cent. and an average gradient of 2·2 per cent. The ore cars are loaded whilst on spur tracks on

Fig. 5.

PROFILE OF THE BUTTE, ANACONDA AND PACIFIC
RAILWAY BETWEEN ROCKER AND BUTTE HILL
YARDS.

Butte Hill. After they are loaded, the cars are drawn to the Butte Hill yards and made up into trains of some thirty-five to forty-five cars each.

On the arrival of these trains at Rocker they are usually rearranged into longer trains, which then travel over the main line to East Anaconda. At East Anaconda the long trains were formerly, when steam locomotives were used, broken up into trains

of only sixteen cars each, and each of these short trains was hauled up to the Washoe Smelter behind a steam locomotive which required about 45 minutes for the 7-mile journey. When electric operation was first inaugurated, two 72-ton electric locomotives were employed in hauling these same sixteen-car trains. They made the trip in only 22 minutes, i.e., in half the time required by the steam locomotives. At present, however, greater advantage is taken of the larger capacity of the electric locomotives, and they haul twenty-five cars from East Anaconda to the Washoe Smelter. The running time is 26 minutes as against the 45 minutes required by the steam locomotive in making the same journey with only sixteen cars. No time is, however, saved in returning with the empty cars, since the curves on this section limit the safe maximum speed to 25 miles per hour.

Tests runs have been made on this Smelter Hill service of hauling loaded ore trains from East Anaconda to the concentrator. The following is a record of three runs and their average:—

From	East Anaconda			
To	Concentrator on Smelter Hill			
Distance	7·0 miles			
Vertical lift	380 feet			
Friction (assumed)	6 lbs. per British ton			
Motive power	Two 72-ton locomotives			
Designation of Run.	1	2	3	Average.
Number of cars in train	18	21	25	21·3
Gross weight of train in British tons	1,270	1,410	1,710	1,460
Gross ton-miles	8,900	9,900	12,000	10,300
Schedule speed in miles per hour	16·1	16·2	14·2	15·5
Total consumption in kilowatt-hours	580	560	746	629
Watt-hours per ton-mile	65·1	56·5	62·2	61·5
Kilowatt-hours per train-mile	..	..	..	90·0

Let us endeavour to check the average results in the last column. The train is hauled up this heavy grade at a fairly steady speed, and, corresponding to the schedule speed of 15·5 miles per hour, we may take the maximum speed as being 22 miles per hour. The momentum of a 1,460-ton train at 22 miles per hour is

$\left[\frac{1}{2} \times \frac{1,460 \times 2,240}{32 \cdot 2} \times \left(\frac{22 \times 5,280}{3,600} \right)^2 = \right] 52,400,000$ foot-lbs., or $\left(\frac{52 \cdot 4}{2 \cdot 659} = \right) 19 \cdot 8$ kilowatt-hours. The allowance for acceleration from rest and after slow-downs will, in this instance, be assumed to be 40 kilowatt-hours. The energy to overcome friction amounts to—

$$\left(\frac{6 \times 1,460 \times 7 \cdot 0 \times 5,280}{2,659,000} = \right) 12 \cdot 2 \text{ kilowatt-hours.}$$

The energy to overcome gravity amounts to—

$$\left(\frac{380 \times 1,460 \times 2,240}{2,659,000} = \right) 470 \text{ kilowatt-hours.}$$

The output from the motors is—

$$(40 + 12 + 470 =) 522 \text{ kilowatt-hours.}$$

Since the input is 629 kilowatt-hours, the losses in the electrical equipments are $(629 - 522 =)$ 107 kilowatt-hours, and the efficiency of the electrical equipments is $\left(\frac{522}{629} \times 100 = \right) 83 \cdot 0$ per cent.

On the assumption of frictional resistances (except when coasting) of 4 lbs. per ton for locomotives and 5·5 lbs. per ton for loaded ore cars, we have—

“Drivers-to-drawbar” efficiency

$$= \frac{5 \cdot 5 \times 1,316 \times 100}{5 \cdot 5 \times 1,316 + 4 \times 144} = 92 \cdot 8 \text{ per cent.}$$

The “pantograph-drawbar” efficiency is—

$$83 \cdot 0 \times 0 \cdot 928 = 77 \cdot 0 \text{ per cent.}$$

In the estimation of the efficiencies of the electrical equipments for the two runs between Rocker and East Anaconda, and for this run from East Anaconda to the concentrator, rough assumptions of an average frictional resistance for the entire train have been deemed sufficient, the allocation of different values to ore cars and locomotives merely having been introduced for the “drivers-to-drawbar” efficiency in order to explain the importance of the

distinction, and with a view to suggesting the desirability of measurements permitting of its correct estimation.

In the following Table are brought together the three sets of efficiency results :—

	Efficiency of Electrical Equipments.	" Drivers-to- Drawbar " Efficiency.	" Pantograph- Drawbar " Efficiency of Locomotives.
	Per Cent.	Per Cent.	Per Cent.
Westbound trip of 3,700-ton train of loaded ore cars from Rocker to East Anaconda at a schedule speed of 20 miles per hour	84·0	97·0	81·5
Eastbound trip of 1,190-ton train of empty ore cars from East Anaconda to Rocker at a speed of 20 miles per hour	83·3	95·0	79·2
7-mile trip up Smelter Hill with two 72-ton locomotives hauling 1,316 tons of loaded ore cars, the total train weight being 1,460 tons	83·0	92·8	77·0

If a locomotive is loaded up to the limit of the coefficient of adhesion on the ruling grade, i.e., if, on the ruling grade, it is exerting a tractive effort of some 18 per cent. of the weight on drivers, the " drivers-to-drawbar " efficiency will be less the steeper the grade. It will also be less the lower the ratio of the weight on drivers to the total weight of the locomotive.

During the journeys up Smelter Hill, the data of which are tabulated above, the average output per motor was—

$$\frac{522 \times 15\cdot5}{8 \times 7\cdot0} = 144 \text{ kilowatts} = 192 \text{ HP.}$$

Since the continuous rating of each motor is $\left(\frac{1,080}{4} = \right) 270 \text{ HP.}$, the average load was 71·3 per cent. of the motor's continuous rating.

THE EQUIVALENT RUN WITH STEAM LOCOMOTIVES.

If this 7-mile run up Smelter Hill were required to be made by means of steam locomotives at the schedule speed of 15·5 miles per hour, attained when employing electric locomotives, it would be necessary to employ two steam locomotives, and each, with loaded tender, would weigh, say, 142 tons, thus increasing the total train

weight from 1,460 to 1,600 tons. This would require an average development in the cylinders of about 2,200 I.H.P. Making no allowance for any stop, the total energy for the 7-mile climb would be—

$$\left(\frac{7}{15.5} \times 2,200 =\right) 990 \text{ I.H.P.-hours.}$$

At 3.7¹ lbs. of coal per I.H.P.-hour the consumption for the journey would amount to 3,660 lbs. The coal-consumption per train-mile would be 520 lbs. At 19s. per ton the fuel cost per steam train-mile would be 52*d*. At an outlay of 0.265*d*. per kilowatt-hour for electricity, and assuming an overall efficiency of 75 per cent. from the point of purchase to the pantograph, the power cost per electric train-mile works out at—

$$\frac{90}{0.75} \times 0.265 = 32.0*d*.,$$

or 62 per cent. of the outlay for fuel for the steam train.

The fact that the outlay for fuel and power per locomotive-mile has, for the average of all the traffic on the road, decreased to only 39 per cent. as much with electric as with steam locomotives, as shown by the results in the Table on p. 144, indicates that the coal-consumption per I.H.P.-hour is much in excess of the 3.7 lbs. assumed in the above estimate. It is probably more of the order of at least 5 lbs. per I.H.P.-hour (61,000 B.Th.U. per I.H.P.-hour).

SEGREGATION OF LOCOMOTIVES' ACTIVITIES.

Let us now review the familiar studies of the segregation of the total hours in the life of a locomotive. Mr. L. R. Pomeroy, in a Paper entitled "The Electrification of Trunk Lines,"² states that from an actual three months' test on a trunk line, a committee on time service of locomotives gave the following as the

¹ 3.7 lbs. of coal (of a calorific value of 12,250 B.Th.U. per pound) per I.H.P.-hour is 45,500 B.Th.U. per I.H.P.-hour, or $\left(\frac{45,500}{3,411} =\right)$ 13.3 kilowatt-hours per I.H.P.-hour. The corresponding efficiency from the fuel to the cylinder is $\left(\frac{0.746}{13.3} =\right)$ 5.6 per cent.

² Proc. Inst. Mech. Engineers, 1910, p. 1195.

representative division of a "locomotive working day" for freight-locomotives:—

	Average per Day.	Per Cent. of the 24 Hours.
A. Time for which mechanical department is responsible .	Hours. 5·3	22
B. The average time the locomotive is performing useful work, i.e., actually pulling trains (taken at 3,000 miles per month and 100 miles per day)	6·7	28
C. Time that the locomotive is under steam, with crew, and ready to go, i.e., time at terminal yards, side tracks, and awaiting orders	12·0	50
Total	24·0	100

In the Paper in question Mr. Pomeroy cites this data in seeking to make the point that the only extent to which this state of affairs can be improved by substituting electric locomotives is in reducing A to about one-half, and in, "perhaps owing to greater speed," increasing B, but that C, which he calls "the lost motion period due to traffic and operating causes," is inevitable. The results already obtained on the Butte, Anaconda and Pacific Railway, however, are to the effect that the "lost motion" conditions are decidedly improved with electric locomotives. Mr. Pomeroy, in the same Paper, quotes Mallets as burning from 600 to 800 lbs. of coal per hour while lying on sidings, and states that under these circumstances "a 2-8-0 locomotive with 50 square feet of grate surface burns 300 lbs. of coal per hour."

Mr. C. P. Kahler, electrical engineer of the Oregon Short Line Railway, in a Paper entitled "Trunk Line Electrification,"¹ publishes Tables (from which the Table at the top of p. 160 has been compiled) showing the allocation of time of the twenty-eight passenger- and ninety-six freight-locomotives employed on a section of a railroad between 500 and 600 miles in length.

In this connection Mr. Kahler makes the further statement that "the records of two western steam roads show that their passenger-locomotives spent respectively 21 per cent. and 17 per cent. of their time in the shops, and that the freight-locomotives of the same roads were in the shop 30 per cent. and 24 per cent. of their time."

¹ Trans. Am. Inst. Elec. Eng., vol. xxxii (1913), p. 1205.

	Passenger-Locomotives.			Freight-Locomotives.		
	Per Cent. of Total Time.	Days per Year.	Number of Loco- motives.	Per Cent. of Total Time.	Days per Year.	Number of Loco- motives.
In shops	22·4	82	6·2	28·2	103	27·1
Spare	1·4	5	0·4	2·7	10	2·6
In engine-house (having running repairs done, boilers washed, fire- boxes cleaned)	53·2	194	14·9	35·9	131	31·4
Running to and from trains	1·6	6	0·5	1·1	4	1·0
In helper service	1·1	4	0·3	4·3	16	4·2
On road { Actually running	20·3	74	5·7	17·1	62	16·4
{ Standing on sidings, taking water, etc.				10·7	39	10·3
Totals	100·0	365	28·0	100·0	365	96·0

STEAM-LOCOMOTIVE EFFICIENCIES.

The following efficiencies have been estimated by the Author (in a Paper entitled "2,400-Volt Railway Electrification," published at p. 1149 of vol. xxxii (1913) of Trans. Am. Inst. Elec. Eng.), as not likely to be exceeded by steam locomotives in regular service :—

	Efficiencies.	
	Express Passenger Service.	Heavy Freight Service.
From coal to cylinders whilst train is running on its useful journey	5·2	4·6
From coal to rims of drivers	4·4	3·9
From coal to drawbar	3·5	3·2
Do. corrected for coal burned at other times than on the useful journey	2·7	2·3

In a contribution to the discussion of the Paper in question, Mr. Roger T. Smith gave figures for the "coal-to-drawbar," and for the "journey" efficiency based upon the Great Western Railway's express passenger service, burning Welsh coal of a calorific value of 15,400 B.Th.U. per pound. The fuel-consumption for that service

was 2·75 lbs. per I.H.P.-hour (42,500 B.Th.U. per I.H.P.-hour), and the ratio of drawbar HP. to I.H.P. was taken as 0·70. Mr. Roger Smith's figures and the Author's are brought together in the following Table:—

	Overall Efficiencies for Express Passenger Service with Steam Locomotives.	
	Author's Estimate.	Great Western Railway.
	Per Cent.	Per Cent.
From coal to drawbar	3·5	4·1
Do. corrected for coal burned at other times than on the useful journey	2·7	3·2

In the same Paper the Author contrasts these efficiencies of the order of 3 per cent. with the actual working efficiencies of over 6 per cent. from the coal in the electricity-supply station to the rims of the drivers on the locomotives, which, with electric propulsion, are obtained not only with dense services of frequently-stopping trains, but also with quite sparse services of trains running considerable distances between stops. By thus more than doubling the overall efficiency from the fuel to the rims of the drivers, the fuel-consumption is, for a given service, decreased to less than half that corresponding to the use of steam locomotives. Furthermore, a much cheaper fuel can be burned in generating-stations than is practicable on locomotives, and it is conservative to set the outlay for fuel for a given traffic at one-third as much in the former case as in the latter.

Steam-Locomotive Coal-Consumption per Indicated Horse-Power-Hour.

—It is of little use to make statements of the coal-consumption of locomotives per I.H.P.-hour without associating with such statements data of the calorific value of the coal in B.Th.U. per pound (or kilowatt-hour per pound or per ton). While laboratory tests of locomotives may show consumptions as low as 30,000 B.Th.U. per I.H.P.-hour, it is rare that, taking into account its entire traffic of all kinds, a railway operates with less than 80,000 B.Th.U. per I.H.P.-hour, and figures decidedly in excess of this are common.¹ When consideration

¹ At p. 1034 of vol. xvii (1914) of the *General Electric Review*, Mr. A. H. Armstrong writes: "Carefully compiled statistics indicate that certain western railroads purchase in the neighbourhood of 12 lbs. of coal for each HP.-hour of actual work expended at the driver rims in hauling trains of all classes." The fuel was of 11,000 B.Th.U. quality; consequently, the gross consumption amounted to 132,000 B.Th.U. per HP.-hour at the rims of the drivers.

is given to such figures as those set forth on pp. 160 and 161, showing the large amount of time that locomotives are burning fuel whilst not pulling trains, it becomes clear that this must be the case. For specific runs discussed in this Paper consumptions of 45,000 B.Th.U. per I.H.P.-hour are debited against steam locomotives. When compared with the results of laboratory tests at the locomotive's most economical load, such a figure as 45,000 B.Th.U. per I.H.P.-hour looks high at first glance, but although reliable data of the coal-consumption of locomotives in actual service is very meagre, there is no doubt that such values favour the steam locomotive in comparisons of the kind undertaken in this Paper.

COAL-CONSUMPTION IN ELECTRICITY GENERATING-STATIONS.

Recent years have witnessed marked improvement in the overall efficiency of electricity generating-stations. Thirteen per cent. from coal-pile to outgoing cables represents a typical value for the annual overall efficiency for large modern stations with a good load-factor—say a load-factor of 0·5. This means that, taken over the entire year, 13 per cent. of the calorific value of the coal burned is sent out of the station as electricity. On the basis of coal of a calorific value of 14,000 B.Th.U. per pound (or $\frac{14,000}{3,411} = 7\cdot10$ kilowatt-hours per pound), an overall efficiency of 13 per cent. is obtained when the coal-consumption for the entire year works out at $\left(\frac{3,411}{14,000 \times 0\cdot13} = \right)$ 1·9 lb. per kilowatt-hour of output from the generating-station.

INFLUENCE OF GREATER SPEED AND HEAVIER TRAINS ON OUTLAY FOR ENGINE CREWS AND TRAIN CREWS.

Whereas in the days of “all-steam-locomotive” operation of the Butte, Anaconda and Pacific Railroad the average weight of the ore trains was 1,600 British tons, the average weight with electric locomotives has been increased 34 per cent. to 2,100 British tons. For hauling a given quantity of ore, this has permitted of decreasing the number of trains per day by 25 per cent. Furthermore, the running time on the various sections has been greatly decreased, and delays have been largely eliminated as compared with the conditions formerly obtaining with steam locomotives.

The consequences of the improvements in these respects are very marked as regards decreased outlay for wages of engine-men and

train crews. As regards the engine crews the improvement is strikingly shown in the following Table:—

	Number of hours engine crews were employed in various services.		
	Regular hours.	Overtime hours.	Total hours.
Month of June, 1913, when operation was with 27 steam locomotives	4,280	1,010	5,290
Month of June, 1914, when operation was with 4 steam locomotives and 17 electric locomotives	3,300	440	3,740
Decrease in June, 1914, as compared with June, 1913	980	570	1,550
Do. in per cent.	23 per cent.	56 per cent.	29 per cent.
Inferred percentage decrease with "all-electric" service	25 per cent.	65 per cent.	33 per cent.

Only a single engine crew is employed even when a train is headed by two 72-ton electric locomotives, since the control is effected entirely in the leading locomotive. Although the scale of wages paid by the Butte, Anaconda and Pacific Railway is the same as formerly with "all-steam-locomotive" operation, the total expenditure for wages of engine-men has decreased from £21,000 per annum with "all-steam-locomotive" operation (or £780 per locomotive) to £14,000 per annum at present with four steam and seventeen electric locomotives. Of this latter figure of £14,000 per annum, £5,000 per annum is due to the four steam locomotives (or £1,250 per locomotive), and £9,000 to the seventeen electric locomotives (or £530 per locomotive), although the average mileage per electric locomotive is 41,000 miles per annum against an average of only 32,500 miles per annum for each of the four steam locomotives. The outlay for engine crews per locomotive-mile is shown in the following Table:—

	Expenditure for Wages of Engine Crews per Locomotive-Mile.
Prior to the summer of 1913 when employing 27 steam locomotives	6·6 pence
At present with 4 steam locomotives and 17 electric locomotives	<div> <div>Per steam locomotive-mile</div> <div>7·2 pence</div> <div>Per electric locomotive-mile</div> <div>3·2 pence</div> </div>

A related saving which should be credited to electric operation is that of £6,200 per annum in trainmen's wages, a decrease of 21 per cent. This decrease is mainly accomplished by the greater speed, less delays and consequent great reduction in overtime. Although this decrease in outlay for trainmen's wages is not a component of locomotive expenditures, it has been effected through improvement in locomotive performance, and from this viewpoint it is interesting to note that it works out at a saving of 1·7*d.* per locomotive-mile.

THE PASSENGER SERVICE ON THE BUTTE, ANACONDA AND PACIFIC RAILWAY.

The passenger service consists of main-line trains between Butte and Anaconda, a distance of 26 miles.¹ Although with a 72-ton electric locomotive the schedule speed could have been increased 25 per cent. to 32·5 miles per hour, the speed of the passenger trains is maintained at only 26 miles per hour as formerly with steam locomotives. The 72-ton electric locomotives with their entire weight on drivers have replaced steam locomotives which weighed, with loaded tender, 118 tons, of which only 54 tons was on drivers. The usual composition of the train now comprises a 72-ton electric locomotive hauling a mail and baggage coach weighing 36 tons and two passenger coaches each weighing 40 tons. This makes a total train weight of $(72 + 36 + 2 \times 40 =)$ 188 tons. The equivalent train hauled by a steam locomotive weighed 234 tons, or 25 per cent. more than the electric train, the increase of 46 tons in weight being due to the greater weight of steam locomotive and tender.

"Drivers-to-drawbar" Efficiencies of Passenger Trains.—Neglecting any differences in the frictional resistances, in pounds per ton, in the locomotive and the load behind the drawbar, the "drivers-to-drawbar" efficiencies are:—

$$\text{For electric train: } \frac{116}{188} \times 100 = 61\cdot5 \text{ per cent.}$$

$$\text{For steam train: } \frac{116}{234} \times 100 = 49\cdot5 \text{ per cent.}$$

Whereas during June, 1913, with steam locomotives, the total passenger-train delays amounted to 1,250 minutes, the delays for June, 1914, with electric locomotives, amounted to only 310 minutes, or only one-fourth as much as with steam.

¹ Referring to *Fig. 3*, it should be stated that Butte lies 4 miles east of Rocker and that Anaconda lies 2 miles west of East Anaconda.

LOCOMOTIVE EXPENDITURE PER LOCOMOTIVE-MILE.

It will be seen that for so miscellaneous a traffic as that on the Butte, Anaconda and Pacific Railway analyses of the component sorts of traffic are practically out of the question. The locomotive expenditures per locomotive-mile during the last 6 months of "all-steam-locomotive" operation are compared with those during the corresponding 6 months of the following year, when four steam locomotives and seventeen electric locomotives were used, in the following Table:—

		Locomotive Expenditure per Locomotive-Mile.		
		"All-Steam- Locomotives" Operation.	Operation with 4 Steam Locomotives and 17 Electric Locomotives.	
		Pence per Steam Locomotive- Mile.	Pence per Steam Locomotive- Mile.	Pence per Electric Locomotive- Mile.
I. Maintenance of equipment expenses.	Repairs	6.5	8.6	2.2
	Depreciation ¹	1.0	2.1	1.2
	Supervision	0.4	0.8	0.2
	Total	7.9	11.5	3.6
II. Transportation expenses.	Wages of engine-men .	6.6	7.2	3.2
	Engine-house expenses	1.9	1.8	0.9
	Fuel and power . . .	19.9	18.1 ²	7.0
	Water	0.8	0.3	—
	Lubrication	0.6	0.7	0.2
	Other supplies	0.3	0.6	0.2
	Total	29.6	28.7	11.5
Total (I) plus Total (II)		37.5	40.2	15.1

With the traffic of some 800,000 locomotive-miles per annum, which may be taken as roughly representative of the usual con-

¹ The amount to be set against depreciation is more or less arbitrarily fixed by the Interstate Commerce Commission, and does not necessarily reflect the physical condition of the locomotive.

² The discrepancy between this figure and the 19.5*d.* given on p. 144 is due to fluctuations in the average price of coal. On p. 144 the same price (19*s.* per ton) was taken for both periods.

ditions on the Butte, Anaconda and Pacific Railway, the two items of expenditure, of which the locomotive-mile costs are given in the preceding Table, would make up annual outlays of

$$\left(\frac{37.5 \times 800,000}{240} = \right) \text{£}125,000 \text{ for "all-steam-locomotive" operation,}$$

and

$$\left(\frac{15.1 \times 800,000}{240} = \right) \text{£}51,000 \text{ for "all-electric" operation.}$$

The annual saving under the heading of "Locomotive Expenditure" would thus be

$$(\text{£}125,000 - \text{£}51,000 =) \text{£}74,000.$$

There is involved a further annual saving of some £6,000 in outlays for wages of train crews.

As debit items we have repairs and maintenance of sub-stations and distribution system, and the associated wages and supervision items. No statement of these outlays is available. They may fairly be taken as not exceeding £6,000 per annum.

Thus the net annual credit available for liquidating the capital expenditure associated with the electrification of the road is

$$\text{£}74,000 + \text{£}6,000 - \text{£}6,000 = \text{£}74,000.$$

The original costs of the electrification of the Butte, Anaconda and Pacific Railway, set forth as required of the railway company by the Interstate Commerce Commission, are shown in the following Table:—

Designating Number of Account.	Description of Account.	Amount of Account.
1	{Engineering and superintendence (including general preliminary report)}	£2,190
12	Roadway tools (used for construction 19 and 22) . .	770
16	Crossings, fences, guards and signs	50
17	{Interlocking and signal apparatus. (The introduction of electric operation required the installation of a new system)}	4,450
19	Poles and fixtures (approximately 91 miles of track) .	27,100
22	Distribution (approximately 91 miles of track were wired)	71,500
25	Sub-station building (existing buildings were used) . .	40
31 and 36	{Electrical equipment (five 1,000-kilowatt motor-generator sets and seventeen 72-ton locomotives)}	134,200
41	Interest	2,000
	Total	£242,300

The completion of the electrification of the entire 114 miles of single track and the outlay for the four additional locomotives may be roughly taken as increasing this capital expenditure to £300,000. The credit of £74,000 per year, arrived at above, is 24·7 per cent. of this total capital expenditure. Furthermore, the additional equipment is being provided to enable the railway to transport 20 per cent. more ore to the Washoe Smelter. Consequently, the traffic will henceforth amount to nearly one million locomotive-miles per annum, and the revenue will be proportionately greater. It is thus undoubtedly conservative to state that the savings, as compared with steam-locomotive operation, will within 7 years of the inauguration of electric operation, i.e., by the year 1920, have liquidated the capital expenditure of £300,000 incurred in the years 1913, 1914, and 1915.

RELATIVE INVESTMENT COSTS OF ELECTRIC AND STEAM LOCOMOTIVES.

The largest item in the capital expenditure for electrifying a railway of this character is that for electric locomotives. In considering the relative status of steam and electric locomotives, sight must not be lost of the circumstance that for every electric locomotive in existence the number of steam locomotives runs into the hundreds. In the manufacture of steam locomotives the experience of many years is available. Standardized parts are employed throughout. The market price of steam locomotives is of the order of only £30 per British ton, while the corresponding figure for electric locomotives of types in which the axles are driven through gears is usually of the order of from £80 to £90 per British ton. While the price of the Butte locomotives has not been published, it would appear from the above assumption that $(72 \times 80 =)$ £5,760, or, say, £6,000 per locomotive, should be a representative figure. The capital expenditure for the seventeen original electric locomotives would thus amount to $(17 \times 6,000 =)$ £102,000. If we assume for the four additional electric locomotives (including tractor trucks) a price of £8,000 each, we arrive, for the twenty-one electric locomotives, at a total outlay of £134,000. These twenty-one electric locomotives will handle a 20 per cent. greater traffic than the displaced twenty-seven steam locomotives. We may conservatively consider the twenty-one electric locomotives as equivalent (with respect to their capacity to handle the traffic) to thirty-two steam locomotives with an average weight, including tender, of 140 tons and an average cost of $(30 \times 140 =)$ £4,200 apiece. Thus the outlay for these thirty-two steam loco-

motives would be $(32 \times 4,200 =)$ £134,000. With the particular price basis selected, this gives us the same total outlay for locomotives, whether steam or electric, and it may in general be said that the greater weight usually required per locomotive and the greater number of locomotives necessary to handle a given amount of traffic will necessitate as great a total outlay for steam locomotives, notwithstanding their much lower cost per ton, as is required for their equivalent in electric locomotives. With the gradual increase in the number of electric locomotives built and used annually, greater standardization can be introduced into their manufacture, and their cost per ton will less exceed the corresponding value for steam locomotives. However, their construction inherently involves a considerably greater cost per ton than is involved in steam locomotives, but the ratio of costs is, with greater standardization and the building of thousands annually, in place of dozens, certain to decrease.

The item of "repairs"¹ of steam locomotives is inherently much greater per mile than that for electric locomotives of approved types. The sixteen "1913" type New York Central electric locomotives of 2,600 HP. continuous capacity (a tractive effort of 13,800 lbs. at 54.5 miles per hour) and weighing 119 British tons, require only 1.7*d.* per locomotive-mile for "repairs," as against 2.9*d.* for all the steam locomotives on the New York Central Railroad. The electric locomotives on that road average about 26,500 miles per year, as against 38,400 miles for the steam passenger-locomotives and 21,000 miles for the steam freight-locomotives. The reason for the lower annual mileage of the electric locomotives on this road is that they are only employed on the short runs from the Grand Central Station to the 34 miles-distant limit (Croton) of the electrified zone,² whereas the steam passenger-locomotives operate over divisions of not less than 100 miles each. The electric locomotives of the Butte, Anaconda and Pacific Railway require 2.2*d.* for "repairs" (see the Table on p. 165) per locomotive-mile as against 6.5*d.* for the displaced steam locomotives.

The 140-British-ton direct-current locomotives, with a continuous rating of 1,800 HP. (tractive effort, 12,300 lbs. at 54.3 miles per

¹ "Repairs" should not be confused with maintenance, of which it is only one component, the other components consisting of "depreciation" and "supervision." The last item, namely, "supervision," is usually of the order of one-tenth, or less, of the outlay for "repairs" (see the Table on p. 165).

² The total electrified mileage of single track on the New York Central Railroad is 251 miles,

hour), of which thirty-three have been in operation on the Pennsylvania Railroad since 1910 (and which have averaged 28,000 miles per locomotive per year), require for repairs 2·8*d.* per locomotive-mile, as against 4·2*d.* for the steam locomotives on the New Jersey Division of the Pennsylvania Railroad, and 5·7*d.* for the average of all the steam locomotives on the entire Pennsylvania Railroad, the average miles per year for the steam locomotives being about the same figure as that given above for the electric locomotives on this railway.

SUB-STATION MACHINERY OF THE BUTTE, ANACONDA AND PACIFIC RAILWAY.

Electrification requires expenditure for sub-station machinery. In the case of the Butte, Anaconda and Pacific Railway it sufficed to locate the sub-station machinery at two points. These locations were respectively on Butte Hill and Smelter Hill, in buildings already serving to house electrical machinery employed at the mines and the smelter. The distance between the two sub-stations is about 26 miles. This relatively great distance apart is rendered practicable by the use of the 2,400-volt system for supplying the locomotives. Had it been necessary to keep the pressure down to 600 volts, at least half a dozen sub-stations would have been necessary, and then not only would their aggregate initial cost have been at least twice as great as for the two 2,400-volt installations, but they would have had a much lower load-factor and a lower "energy" efficiency. Furthermore, a greater outlay would have been required for the wages of sub-station attendants. The sub-station machinery comprises five 720-revolutions-per-minute motor-generator sets, each having a continuous rating of 1,000 kilowatts at 2,400 volts when supplied with three-phase, 60-cycle, 2,300-volt electricity. Their 2-hour rating is 1,500 kilowatts, and their 5-minute rating 3,000 kilowatts. The design comprises a ten-pole synchronous motor direct connected to two four-pole commutating generators. Each of these generators supplies a pressure of 1,200 volts at its commutator. The two commutators are connected in series, thus providing the required terminal pressure of 2,400 volts. The commutating generators are compound wound, and their pole shoes are fitted with distributed compensating windings, which, in conjunction with the interpole windings, provide for excellent commutation. The main field windings are separately excited from a 125-volt supply. There are three of these sets at the Smelter Hill sub-station and two at the Butte Hill

sub-station. The entire outlay for sub-station machinery has been only a matter of some £30,000. The precise figure is not published. Each motor-generator set weighs about 36 British tons.

In *Fig. 6* are given curves showing for the first 10 days in December, 1913, the peak loads and the average loads from the two

Fig. 6.

BUTTE, ANACONDA AND PACIFIC RAILWAY: PEAK AND AVERAGE LOADS FROM SUB-STATIONS.

sub-stations, and the sum of the average loads from the two sub-stations. An examination of this data shows the average load-factor for this period to have been 0.34. The average load for the 10 days was 2,050 kilowatts, and the peaks for the 10 days averaged $\left(\frac{2,050}{0.34} = \right)$ 6,000 kilowatts.

The motors of the motor-generator sets are proportioned to absorb 1,450 kilovolt-amperes when the sets are delivering 1,000 kilowatts. This is in order that they may be worked with such over-excitation of the motor fields as to have a leading power-factor. This leading power-factor offsets the lagging power-factor of other customers of the Great Falls Power Company, which supplies the electricity to the railway company. If the sets were worked with a leading power-factor of 0.7, every 1,000 kilowatts consumed would be accompanied by a wattless leading component of 1,000 kilovolt-amperes. This should be of advantage to the supply company, and ought to be worth to them a matter of, say, 0.040*d.* for every leading kilovolt-ampere-hour. In other words, were the load of unity power-factor, it would, on this assumption, have been consistent to charge the railway company some $(0.265 + 0.040 =) 0.305*d.*$ per kilowatt-hour, a 15 per cent. higher price. Conversely, another customer using annually an equal amount of electricity at the same load-factor, but with a lagging power-factor of 0.7, would, if the economics of the business were appreciated, have to pay some $(0.305 + 0.040 =) 0.345*d.*$ ¹ per kilowatt-hour, a 30 per cent. higher price than that paid for 0.7 leading power-factor electricity. As a matter of fact the sub-stations are not operated with a leading power-factor much below unity.

The distribution from the sub-stations has involved the installation of about 250 British tons of copper for feeders. The feeder cables are carried on the trolley-line poles. About 190 tons out of the total feeder copper consists in two cables, each having a cross section of 0.390 square inch. These two cables are operated in multiple and extend 26 miles from the Smelter Hill sub-station to the Butte Hill sub-station. They are tapped to the trolley wire about every 1,000 feet. There are further feeders to provide the necessary reinforcement at other portions of the system. In addition to the positive feeder system, which accounts for about 200 tons of copper, the track return circuits are reinforced with about 50 tons of negative feeders. These comprise over 30 miles of 4/0 (0.166 square inch) cable. These negative feeders are also carried on the trolley-line poles. The positive and negative feeder

¹ Arno, as the result of an analysis of the influence of lagging power-factors on the cost, arrived at the conclusion that the equitable cost for any power-factor could be estimated by adding one-third of the output in kilovolt-ampere-hours to two-thirds of the output in kilowatt-hours. Applying Arno's rule to the above case, then if 0.305*d.* is an equitable price per kilowatt-hour for unity-power-factor electricity, the corresponding price for lagging 0.7-power-factor electricity would be $(0.33 \times 1.41 + 0.67) \times 0.305 = 0.347*d.*$

copper, on the basis of £80 per British ton, has involved an outlay of about £20,000, or an average of $\left(\frac{20,000}{114} =\right)$ £175 per mile of single track. The trolley conductor has a cross section of 0.166 square inch (4/0 B and S). A conductor of this cross section weighs 3,400 lbs. per mile. There has thus been required for the 114 miles of single track 182 tons. At £80 per ton this represents an expenditure of £14,500, or £127 per mile. The track rail is chiefly 85 lbs. per yard, and about 40,000 bonds have been employed in fitting the 114 miles of single track for electric operation. At 3.3d. per bond the outlay for bonds amounts to £550, or £48 per mile of single track.

The various items in the cost of the distribution system are brought together in the following Table :—

Feeder copper	£200 per mile.
Trolley wire	130 „
Line material	65 „
Poles	60 „
Steel strands	60 „
Bonds	45 „
Cost of erection	550 „
<hr/>	
Total cost	£1,110 „

The complete cost of the distribution system, including feeders and bonding, has amounted to £1,110 per mile of single track. The maintenance of the entire distribution system, including track bonding, is running at about £22 per mile of single track.

ROLLER PANTOGRAPH COLLECTORS.

Each of the 72-ton freight-locomotives is fitted with a roller pantograph trolley. The additional four freight-locomotives are each fitted with two pantographs, but only one is in use at a time. All the heavier freight-trains are headed by two 72-ton locomotives, and consequently the current for the heavier freight-trains is collected at two contact points. The eight motors on two locomotives have an aggregate continuous capacity of 2,160 HP. At an efficiency of 0.85 per cent. for the electrical equipment on the locomotive, the corresponding current to be collected is

$$\frac{2,160 \times 746}{0.85 \times 2,400} = 790 \text{ amperes.}$$

The general practice during starting and accelerating is to keep the current at not more than 500 amperes per 72-ton locomotive.

Thus currents as great as about 800 amperes will be collected from the 4/0 trolley wire, and on the reasonable assumption that the current will not divide equally between the two pantographs, it is incumbent upon each pantograph to be capable of dealing with current up to 500 amperes, in the service on the Butte, Anaconda and Pacific Railway. The 4/0 trolley wire will have a rise of about 180° C. when carrying 1,000 amperes continuously in the open air. For this temperature rise it can carry a considerably greater current for a few minutes. It is to be noted that the current will flow to the points above the locomotives from both directions from the nearest feeding points behind and ahead of the locomotives. Taking these data into consideration, it will be seen that the system could deal with four 72-ton locomotives simultaneously located between two-adjacent feeding points and requiring an aggregate of some 2,000 amperes. The three Smelter Hill sub-station sets deliver, when all in service, 1,250 amperes at their continuous rated load, but they are capable of providing ($3 \times 1,250 =$) 3,750 amperes for five minutes.

The limiting currents which have been mentioned rarely obtain. Under usual service conditions the average current collected per pantograph is only some 400 to 500 amperes when starting and when ascending grades. When, as is usual, a freight-train is headed by two 72-ton locomotives, the two pantographs are connected in multiple by a bus line run on the top of the locomotives, with a jumper for effecting the connection between them. Each passenger-locomotive is equipped with two pantographs, but only one is in use at a time.

THE CHICAGO, MILWAUKEE AND ST. PAUL 3,000-VOLT ELECTRIFICATION.¹

In the map in *Fig. 7* will be seen, represented by light lines, the main line of the Butte, Anaconda and Pacific Railway, the electrification of which has been described in the preceding pages. The heavy lines represent a 440-mile section of the Chicago, Milwaukee and St. Paul Railway. This 440-mile section comprises

¹ The Author wishes to take this opportunity to express his thanks to Messrs. A. H. Armstrong and E. S. Johnson, who are closely associated with the electrification of the Chicago, Milwaukee and St. Paul Railway, for the assistance which they have given him in supplying the information embodied in his description of this undertaking. Reference should also be made to an article entitled "Electrification of 440.5 miles of the St. Paul," *Railway Age Gazette*, 1915, p. 683.

MAP SHOWING THE 440-MILE SECTION OF THE CHICAGO, MILWAUKEE AND ST. PAUL RAILWAY (AVERY TO HARLOWTON) IN COURSE OF ELECTRIFICATION; ALSO THE BUTTE, ANACONDA AND PACIFIC RAILWAY.

(including yards and sidings) 650 miles of single track, and runs from east to west, extending from Harlowton in the State of Montana to Avery in the State of Idaho. The line from Harlowton to Avery comprises four divisions, the average length of each division amounting to 110 miles. Avery is only some 400 miles from the Pacific Coast, and in the event of satisfactory experience with electric operation of the 440 miles between Harlowton and Avery, the railway contemplates continuing the electrification to Seattle on the coast, which will make a total distance of 850 miles from Harlowton. The railway commenced in the latter part of 1914 to put its electrification plans into effect, and forty-two electric locomotives, each weighing 250 British tons, together with machinery for fourteen sub-stations and material for the transmission and distribution of the electricity, are now being supplied. In the spring and summer of 1915 the 113 miles between Three Forks and Deer Lodge were equipped for electrical operation, and it is intended that by the beginning of 1916 all trains passing over this division shall be propelled exclusively by electric locomotives. The electricity will be supplied under a contract with the Montana Power Company, which has ten hydro-electric plants in this region.

These ten electricity-supply stations will, when completed, have an aggregate installed capacity of over 200,000 kilowatts. The Montana Power Company supplies electricity to consumers distributed over many parts of the States of Montana and Idaho. The total water-storage capacity provided in this system is over 400,000 acre-feet, which, with the other arrangements provided by the Power Company, affords ample assurance of an uninterrupted supply of electricity at all seasons.¹ The railway company is providing a 100,000-volt tie-in transmission-line. The Power Company will deliver the electricity into this tie-in transmission-line at several feeding-in points. The price of the 100,000-volt 60-cycle three-phase electricity delivered to the railway company at these feeding-in points is 0.26*d.* per kilowatt-hour. The railway sub-stations are supplied from the 100,000-volt tie-in line,

¹ For every foot of elevation, the potential energy in a British ton is 0.840 watt-hour. One acre-foot of water weighs 1,220 British tons. Consequently, for every foot of elevation, an acre-foot of water represents 1.025 kilowatt-hour of potential energy. Assuming that the 400,000 acre-feet of water-storage in question has an average utilizable head of 70 feet, and that 50 per cent. of it can be delivered as electricity to consumers, then the total amount of electricity which thus can be made available is

$$(400,000 \times 1.025 \times 70 \times 0.50 =) 14.4 \text{ million kilowatt-hours.}$$

PROFILE OF ELECTRIFIED DIVISIONS OF CHICAGO, MILWAUKEE AND ST. PAUL RAILWAY.

which is located partly on the railway company's right-of-way and runs partly over public domain to cut out detours.

A profile of the 440-mile section of railway from Harlowton to Avery is shown in *Fig. 8*. There are fourteen sub-stations for the 440 miles from Harlowton to Avery, and these are shown in the Figure. The distance between sub-stations ranges from 18 to 43 miles, the average distance being 32.5 miles. (We have seen that the distance between the sub-stations on the Butte 2,400-volt railway was 26 miles.) The section between Three Forks and Deer Lodge includes the crest of the line over the main range of the Rocky Mountains. West-bound trains have a 21-mile climb up a 2-per-cent. grade, while east-bound trains must ascend 10 miles of 1.66-per-cent. grade.

The sub-station equipment comprises oil-immersed three-phase transformers (for stepping down the pressure from 100,000 volts to 2,300 volts) and motor-generator sets which convert the 2,300-volt three-phase electricity into 3,000-volt direct current. Each motor-generator set comprises a 60-cycle synchronous motor, direct connected to two 1,500-volt direct-current generators. These two generators are connected in series to provide 3,000 volts. The excitation for each set is supplied from two exciters, one at each end of the shaft. The motor-generator sets are of two sizes, the continuous ratings being respectively 1,500 and 2,000 kilowatts. Their 2-hour ratings are respectively 2,250 and 3,000 kilowatts, and the generators are compound-wound to maintain constant terminal pressure for all loads up to their 2-hour rating. They also have 5-minute ratings of three times their continuous rating. Thus we have for the two sizes—

Continuous rating. . . .	1,500 kilowatts	2,000 kilowatts
Two-hour ,, 	2,250 ,,	3,000 ,,
Five-minute ,, 	4,500 ,,	6,000 ,,

The location and equipment of the fourteen sub-stations are given in the Table on p. 178.

It is seen from this Table that there is a total capacity of 74,600 kilovolt-amperes of transformers to supply the synchronous motors, as against 59,500 kilowatts in direct-current generators. Taking the overall efficiency of the sets as 91 per cent., the input to the synchronous motors for a rated output of 59,500 kilowatts from the generators is 65,500 kilowatts, and since the corresponding input is 74,600 kilovolt-amperes, the machines may be operated with a power-factor of 0.88; that is to say, if the fields of the synchronous motors are sufficiently over-excited, the

Name of Sub-Station.	Distance from Avery in Miles.	No. of Step-Down Transformers.	Size of each Transformer in KVA.	Total Capacity of Transformers in KVA.	No. of Motor-Generator Sets.	Size of each Motor-Generator Set in KW.	Total Capacity of Motor-Generator Sets in KW.
Two Dot .	426	2	2,500	5,000	2	2,000	4,000
Summit. .	392	2	2,500	5,000	2	2,000	4,000
Josephine .	362	2	2,500	5,000	2	2,000	4,000
Eustis . .	332	2	2,500	5,000	2	2,000	4,000
Piedmont .	289	3	1,900	5,700	3	1,500	4,500
Janney . .	262	3	1,900	5,700	3	1,500	4,500
Morel . .	228	2	2,500	5,000	2	2,000	4,000
Gold Creek.	193	2	2,500	5,000	2	2,000	4,000
Ravena . .	160	2	2,500	5,000	2	2,000	4,000
Primrose .	122	2	2,500	5,000	2	2,000	4,000
Tarkio . .	86	2	2,500	5,000	2	2,000	4,000
Drexel . .	47	2	2,500	5,000	2	2,000	4,000
East Portal.	24	3	2,500	7,500	3	2,000	6,000
Avery . .	0	3	1,900	5,700	3	1,500	4,500

TOTAL FOR FOURTEEN SUB-STATIONS.

74,600 kilovolt-amperes of transformers.

59,500 kilowatt of motor generators.

transformers will provide an incoming current which will lead with a power-factor of 0.88.

The forty-two locomotives each have a continuous rating of 3,020 HP. and weigh 250 British tons. A 250-ton St. Paul locomotive is thus 40 per cent. more powerful than two 72-ton Butte locomotives operated as a single machine. In addition to this, the St. Paul locomotives are equipped for regenerative braking for long periods on down-grades. The electrical equipment is consequently very liberally designed and weighs 73 lbs. per HP. of continuous rating.

Of the forty-two locomotives, thirty are for freight service. Each motor's armature shaft is fitted with an 18-tooth pinion at each end. These pinions engage with 82-tooth gears on the locomotive axle, the ratio of speed reduction thus being 4.56. The remaining twelve locomotives are for passenger service. These have 29-tooth pinions and 71-tooth gears, the ratio being 2.45. Except for this difference, and an additional weight of 18 British tons for steam-heating equipment, the passenger-locomotives are

identical with the freight-locomotives. Six of the thirty freight-locomotives also have the steam-heating equipment, and are thus available for hauling passenger-trains.

The trolley is of the "double-wire catenary" construction, and consists of two 4/0 wires suspended from the same catenary, but by independent hangers. This interesting and very effective construction is difficult to illustrate. Above tangent track, the two wires lie close together, and are not readily distinguished from one another. But on curves there is a little distance between the two wires at the points of suspension. The points of suspension of the one wire, by means of its hangers, are midway between the points of suspension of the other wire. This alternation continues right along the structure.

The locomotive's pantographs each carry a double-pan collector. By means of such a double-pan collector making sliding contact with two 4/0 trolley wires supported as above described, 2,000 amperes can be satisfactorily collected at any speed up to 60 miles per hour. There will be no occasion to collect so great a current as 2,000 amperes in the contemplated service. Each locomotive is fitted with two pantographs. The method of alternate suspension of the two trolley wires has been found to provide an exceedingly smooth operation with complete elimination of any tendency to flash at the points of suspension at any speed.

The leading dimensions and performance characteristics of the freight-locomotive are as follows:—

Total weight	250 British tons
Weight, mechanical equipment	340,000 lbs.
" electrical "	220,000 "
" on drivers	200 British tons
" on each guiding truck	25 " "
No. of driving-axles	8
Weight per driving-axle	25 British tons
No. of motors	8
" " guiding trucks	2
" " axles per guiding truck	2
Weight on guiding axle	12·5 British tons
Overall length of locomotive	112 feet
Rigid wheel-base	10 feet 6 inches
Diameter of driving-wheel	52 inches
" " guiding " "	36 "
Total output of motors (continuous rating)	3,020 HP.
Tractive effort (continuous rating)	71,000 lbs.
Speed at this tractive effort at 3,000 volts	15·9 miles per hour
Per cent. which above tractive effort consti- tutes of weight on drivers	15·8 per cent.

If we assume a train friction of 6 lbs. per ton, then, when developing its rated tractive effort of 71,000 lbs., the following are the complete train weights and the trailing loads which one of these 250-ton locomotives can draw up various grades. The speed will, in each case, be 15.9 miles per hour, and the load on the motors will be 3,020 HP.

Grade.	Total Train Weight.	Trailing Load.
Per Cent.	British Tons.	British Tons.
0.5	4,120	3,870
1.0	2,500	2,250
2.0	1,400	1,150
3.0	970	720
4.0	740	490

On the assumption of equal frictional resistance of locomotive and load hauled, in pounds per ton, the efficiencies for these five cases are as follows:—

Grade.	Efficiency of Electrical Equipment.	"Drivers-to-Drawbar" Efficiency.	"Pantograph-Drawbar" Efficiency.
0.5	0.89	0.94	0.83
1.0	0.89	0.90	0.80
2.0	0.89	0.82	0.73
3.0	0.89	0.74	0.66
4.0	0.89	0.66	0.59

The locomotive's characteristic curves at 3,000 volts are drawn in *Figs. 9, 10, 11 and 12*. The eight motors are geared to the locomotive's driving wheels and each has a continuous rating of 378 HP. at 1,500 volts. They are permanently connected in series pairs, each pair using a pressure of 3,000 volts for the parallel running position. Each motor is cooled by the forced circulation of air through it from an external blower outfit.

The passenger-locomotive weighs 268 tons and will haul a 700-ton trailing passenger-train at a speed of 60 miles per hour on level track, and it will carry this train up all gradients of not over 1.5 per cent. For 2-per-cent. grades the assistance of a pusher will be required. A 550-ton train can be hauled up a 2-per-cent.

Fig. 9.

SPEED-CURRENT CURVE OF CHICAGO, MILWAUKEE AND ST. PAUL 3,000-VOLT GOODS-LOCOMOTIVE. (Diameter of Driving-Wheels, 52 Inches ; Gear-Ratio, 4.56.)

Fig. 10.

TRACTION-EFFORT-CURRENT CURVE OF CHICAGO, MILWAUKEE AND ST. PAUL 3,000-VOLT GOODS-LOCOMOTIVE.

grade by one of these 268-ton passenger-locomotives without assistance.

The heaviest duty of the freight-locomotives consists in drawing a trailing load of 2,230 British tons from Lombard (see *Fig. 8*) to Summit over the Belt Mountains. The distance is 49 miles, the ruling grade is 1 per cent., and the average grade for the 49 miles is 0·7 per cent. The tractive effort for the average grade is

$$(22\cdot4 \times 0\cdot7 + 6) \times (2,230 + 250) = 54,000 \text{ lbs.}$$

Fig. 11.

TRACTION-EFFORT-SPEED CURVE OF CHICAGO,
MILWAUKEE AND ST. PAUL 3,000-VOLT
GOODS-LOCOMOTIVE.

From the characteristic curve in *Fig. 11* we find the corresponding speed to be 16·5 miles per hour. The average output from the motors is

$$\frac{16\cdot5 \times 5,280 \times 54,000}{60 \times 33,000} = 2,380 \text{ HP.}$$

The average current is 670 amperes. When this run is made without stops, it will take 3·0 hours to cover the 49 miles between Lombard and Summit. On the ruling grade of 1 per cent., the tractive effort required is 71,000 lbs., and the corresponding speed

and the output are 15.9 miles per hour and 3,020 HP. The average consumption for this 49-mile run is

$$\left(\frac{670 \times 3,000 \times 3.0}{2,480 \times 49} = \right) 49.5 \text{ watt-hours per ton-mile.}$$

Assuming 75 per cent. efficiency from the points where the electricity is delivered to the railway, the amount of electricity purchased is $\left(\frac{49.5}{0.75} = \right) 66.0$ watt-hours per ton-mile. Since the price is 0.26*d.* per kilowatt-hour, the outlay for power is $(0.26 \times 0.066 =) 0.0172d.$ per ton-mile, or

$$(2,230 + 250) \times 0.0172 = 43d. \text{ per train-mile.}$$

Fig. 12.

EFFICIENCY-CURRENT CURVE OF CHICAGO, MILWAUKEE AND ST. PAUL 3,000-VOLT GOODS-LOCOMOTIVE.

The best steam-locomotive alternative consists in hauling such a train by a locomotive with 200 tons on drivers. Such a locomotive with loaded tender would weigh 330 tons. When hauling a 2,230-ton trailing load on the average grade of 0.7 per cent. the speed will not exceed 8.3 miles per hour, or about half the speed of the electric locomotive. Exclusive of stops, the time required for the 49 miles would be 6.0 hours. The tractive effort on the 0.7-per-cent. average grade is

$$(2,230 + 330) \times (22.4 \times 0.7 + 6) = 55,500 \text{ lbs.}$$

The output at the drivers is

$$\frac{55,500 \times 8.3 \times 5,280}{60 \times 33,000} = 1,230 \text{ HP.}$$

This corresponds to $\left(\frac{1,230}{0.75} = \right)$ 1,640 I.H.P. If the locomotive burns lignite with a calorific value of 11,000 B.Th.U. per pound, the consumption will be 4.0 lbs. per I.H.P.-hour. The 49-mile run requires $(1,640 \times 6.0 =)$ 9,850 I.H.P.-hour. Consequently (exclusively of the consumption during stops) $\left(\frac{9,850 \times 4.0}{2,240} = \right)$ 17.5 tons of coal will be burned during the journey, or 2.92 tons (6,550 lbs.) per hour.

This rate is beyond the capacity of hand-firing, and requires a locomotive equipped with mechanical stokers. The fuel consumption will be

$$\left(\frac{17.5 \times 2,240}{49} = \right) 800 \text{ lbs. per locomotive-mile.}$$

The stops inherent to steam-locomotive operation will not be accompanied (as in the electric locomotive) with a complete cessation of fuel-consumption. On the contrary, the fuel burned during stops will bring the consumption per locomotive-mile up to at least 900 lbs. At 12s. per ton, the fuel-cost will be

$$\frac{900 \times 12 \times 12}{2,240} = 58d. \text{ per train-mile,}$$

as against 43d. per train-mile for the electric locomotive. The 49-mile run forming the subject of this estimate represents the heaviest duty, and it will, for the purposes of a rough survey, be assumed that the average consumption of electricity and coal per locomotive-mile will, taken over the year, be only one-third of the amounts estimated for the 49-mile run.

While large Mallets can be bought for a matter of £24¹ per

¹ At p. 1242 of vol. xxxii (1913) of the Trans. Am. Inst. Elec. Eng., Messrs. Hall and Welsh state: "Also, the cost of 250-ton Mallets is given as \$45,000. The 300-ton Mallet mentioned above costs new approximately \$33,500, and the heaviest Mallet locomotives ever built (weighing 425 tons) cost slightly less than \$44,000. It is evident that the figure of \$45,000 is much too high." Translating these figures we have :—

$$\text{Cost of 268-British-ton Mallet} = \frac{33,500}{5 \times 268} = £25 \text{ per ton.}$$

$$\text{Cost of 380-British-ton Mallet} = \frac{44,000}{5 \times 380} = £23 \text{ per ton.}$$

British ton, electric locomotives of the type under discussion cost fully three times as much, say at least £80 per ton. On the other hand, the repairs of a 330-ton Mallet amount to a matter of at least 12*d.* per mile, as against not over 5·5*d.* per mile for the 250-ton electric locomotive. If we credit both locomotives with a 15-year life, crediting the electric locomotive with 35,000 miles per annum and the steam locomotive with 25,000 miles per annum, and debiting both locomotives with 7*d.* per mile for wages of crew, the account stands :—

	Annual Outlay in Pounds Sterling.	
	Per 250-Ton Electric Locomotive.	Per 330-Ton Mallet Locomotive.
I. Fuel and power	£ 2,080	£ 2,020
II. Wages of locomotive crews	1,020	730
III. Repairs of locomotive	810	1,250
IV. Interest (5 per cent.), taxes and insurance (3 per cent.) and amortization (4·6 per cent.) }	2,400	950
Total of I + II + III + IV	£6,310	£4,950
Do. per locomotive-mile	43·3 <i>d.</i>	47·5 <i>d.</i>

For the above study, which is based on equal weights of train hauled, the saving in favour of the electric locomotive is of inconsiderable amount. In practice, however, advantage is taken of the inherent ability of hauling heavier trains with electric locomotives and at higher speeds. In both of these respects electric operation increases the capacity of a railroad and incidentally decreases the outlay for wages of engine-crews and train-crews. This has already been brought out in the analyses of the results actually obtained on the Butte, Anaconda and Pacific Railway.

Indeed, the Mallets actually employed on the Chicago, Milwaukee and St. Paul Railway are much smaller than that on which the above illustration is based, and cannot, even at their lower speed, handle the service for which the electric locomotives are adequate.

A comparison between the St. Paul Mallets and the 250-ton electric freight-locomotives is given in the Table on p. 186, from which we see that, although the weight of the electric locomotive is practically equal to the combined weight of steam locomotive and tender, it has a 38 per cent. greater weight on drivers, and consequently can, for a given limiting coefficient of

	C., M. & St. P. Mallet Locomotive.	C., M. & St. P. Electric Locomotive.
Total weight (in British tons) . . . { 218 (including) tender }		250
Weight on drivers (in British tons) .	145	200
Tractive effort which electric locomotive can develop for 1 hour, starting cold }	..	84,400 lbs.
Tractive effort which electric locomotive can develop continuously . . }	..	71,000 lbs.
Wheels per guiding truck	2	4
Weight per driving axle (in British tons) }	24·0	25·0
Total weight on one rigid-wheel-base truck }	72·5	50·0

adhesion, develop a 38 per cent. greater tractive effort. This gives it, for a 1-per-cent. grade and for a coefficient of adhesion of 0·18 in both cases, and allowing 6 lbs. per ton for friction, capacity to haul a train of $(2,850 - 250 =)$ 2,600 British tons behind the drawbar, as against a train of only $(2,050 - 250 =)$ 1,800 British tons for the Mallet under the same conditions. The result is in favour of the electric locomotive to the extent of 44 per cent.

(since $\frac{2,600}{1,800} = 1·44$) for these particular conditions. Even in these

estimates the Mallet has not been debited with any greater friction than the electric locomotive, although some investigators have arrived at values of the order of over 30 lbs. per ton for the resistance of Mallet locomotives.¹ Since the electric locomotive has guiding-trucks at both ends, there is no need for turn-tables, and the outlay for these, as also for stations for replenishing supplies of coal and water, is dispensed with.

Opinions of Relative Ruggedness of Steam and Electric Locomotives.

—At p. 294 of *The Electric Journal* for July, 1915, in the course of some comments on the Norfolk and Western electric locomotives (which are discussed at p. 195 of this Lecture), Mr. G. M. Eaton writes :—

The impression given by the locomotives as they pass, hauling their loads, is one of rugged simplicity and of fitness for handling the service. This picture is intensified and is indelibly fixed on the minds of those fortunate enough to see the steam and the electrically-hauled trains in direct comparison, as has been

¹ See p. 1308 of Mr. Cary T. Hutchinson's Paper entitled "The Electric System of the Great Northern Railroad Company at Cascade Tunnel": *Trans. Am. Inst. Elec. Eng.*, vol. xxviii (1909), p. 1281.

possible during the period of changing over from steam to electric service. Three great Mallet steam locomotives, of most modern construction, labour past hauling their train up the grade at about 7 miles per hour. A little later come two electric locomotives hauling a train of identical make up over the same grades and curves at twice the speed, and without apparent effort.

At p. 830 of *The General Electric Review* for August, 1915, Mr. A. H. Armstrong, in alluding to the electric locomotives for the Chicago, Milwaukee and St. Paul Railway, writes:—

For example, it has a capacity of 3,600 HP. for 1 hour, and even greater than this for short periods. The sustained tractive effort is 72,000 lbs. at a speed of $15\frac{3}{4}$ miles per hour at full sub-station line potential. Compare this with the Mallet engine of approximately the same weight now in operation on the St. Paul road, and we find that the Mallet has 76,200 lbs. tractive effort, corresponding to 23.5 per cent. coefficient of adhesion, but those of you familiar with the performance of this beast of burden know that it toils painfully at speeds seldom exceeding 7 to 10 miles per hour when operating at its full hauling capacity. It is in this matter of higher speed for the same tractive effort that the electric locomotive excels.

At p. 1889 of the *Proc. Am. Inst. Elec. Eng.* for August, 1915, Mr. W. S. Murray writes:—

The steam locomotive has lived a useful life of 80 years. This is not a prediction that it will not live many more! Even in the clothes of its mechanical ruggedness it is not difficult to conceive of its having once been a pretty delicate machine, deserving of a very great deal of care and attention. The electric locomotive was born of even a more delicate nature, and while its ruggedness is increasing, it can never possibly be the great mechanical brute that our high-powered steam locomotives may be typified as being to-day.

It is impossible to reconcile Mr. Murray's conception of the electric locomotive as a "delicate" machine and of the steam locomotive as a machine characterized by "mechanical ruggedness" with the established fact that "repairs" per locomotive-mile are less than half as much for an electric locomotive as for a steam locomotive for the same service.

The Pusher Service for Heavy Grades.—On those sections of the line where the grade is much in excess of 1 per cent. for any considerable distance, a second 250-ton electric locomotive will be employed as a pusher. On the 440 miles between Harlowton and Avery there are only two points where, with electric operation, a pusher locomotive will be required, whereas with steam-locomotive operation many such points were required. At the ends of the pusher divisions sidings are provided permitting the pusher locomotive to be transferred to the head of the train where it supplements

the other locomotive in providing regenerative braking on the down grade.

Although the control permits of operating two 250-ton locomotives together under the control of one engineer by means of the multiple-unit-control system, this can only be done when the two locomotives are either pushing at the rear end of the train or else being pushed by the train on down grades, for the two locomotives are capable (with a coefficient of adhesion of 0.25) of exerting a tractive effort of 100 tons, an amount decidedly in excess of the strength of the draft rigging.

Regenerative Braking.—The electric service on the Chicago, Milwaukee and St. Paul Railway will include the feature of regenerative braking.

In a Paper by the Author, entitled "2,400-Volt Railway Electrification," and published at p. 1149 of vol. xxxii (1913) of the Trans. Am. Inst. Elec. Eng., estimates were made relating to the electrification of a hypothetical 96-mile single-track mountain-grade division of a main-line railway. The trains ascended to an altitude of 3,800 feet in 48 miles and returned to the original level in the remaining 48 miles, the average gradient thus being 1.5 per cent. It was assumed that the ruling gradient was 2.2 per cent. Trains of weights up to 1,600 British tons were to be hauled by electric locomotives over this division, the average speed between stops being 12 miles per hour. For standard equipments with series motors and with no provision for regenerative braking the costs per locomotive-mile as compared with steam-locomotive haulage were worked out.

Were regenerative control to be employed during the 48-mile descent, the estimates would be as follows:—

The altitude attained by the train is 3,800 feet. In descending there is given up by a train with a weight of 1,600 British tons behind the drawbar of two 143-ton locomotives—

$3,800 \times (1,600 + 2 \times 143) \times 2,240 = 16,100,000,000$ foot-lbs. of energy.

There is required for friction—

$(1,600 + 2 \times 143) \times 8 \times 5,280 \times 48 = 4,300,000,000$ foot-lbs.

After deducting the amount required for friction, there remains 11,800,000,000 foot-lbs., or 4,450 kilowatt-hours (since 1 kilowatt-hour = 2,659,000 foot-lbs.).

This energy can be applied to drive the motors as dynamos and

return most of it, in the form of electricity, to the distribution system.

The Author was associated with successful tests of this kind (although on a city tramcar) made at Newcastle in 1901. Careful measurements were made in the Newcastle tests, and for regeneration on long descents high efficiency was obtained.

Mechanical brakes will still be provided in the case we are considering, in order to have duplicate means of controlling the train, but these will be regarded as a reserve, and will not be employed except at the very lowest speeds and to hold the train at rest on grades. Let us take the efficiency of regeneration at 68 per cent. Then

$$0.68 \times 4,450 = 3,000 \text{ kilowatt-hours}$$

of electricity will be sent back into the line during the 48-mile descent.

It had been estimated in the Author's Paper that without regenerative control the consumption of the 1,600-ton train in making the 96-mile journey would be 11,700 kilowatt-hours.

With regenerative braking, and employing the conservative estimate above set forth, the consumption is reduced to

$$11,700 - 3,000 = 8,700 \text{ kilowatt-hours.}$$

By similar estimates of the consumption of electricity for the entire traffic occurring on this 96-mile division in 1 year, a total annual input to the sub-stations of 107 million kilowatt-hours is estimated as against 144 million kilowatt-hours per annum without regeneration. The price paid for the electricity is 0.336*d.* per kilowatt-hour in both cases. Forty-eight locomotives, each averaging 27,200 miles per annum, are estimated to be required to handle the traffic. The total annual outlay for electricity, and also the annual outlay per locomotive and per locomotive-mile, without and with regenerative control, work out as follows:—

Annual Outlays for Electricity.	Without Regenerative Control.	With Regenerative Control.
Total	£200,000	£149,000
Per locomotive . . .	£4,160	£3,100
” ” -mile . .	36.8 <i>d.</i>	27.4 <i>d.</i>

The relative operating costs for the steam locomotive and for the two cases of the electric locomotive, i.e., without and with the

allowance for regeneration, arrived at in the preceding calculation, are shown in the following Table, which is based on electricity at 0·336*d.* per kilowatt-hour, and lignite with a calorific value of 11,000 B.Th.U. per pound at 11*s.* per British ton.

	Operating Expenses in Pence per Locomotive-Mile.		
	Steam Locomotive.	Electric Locomotive.	
		Without Regen- erative Control.	With Regen- erative Control.
Fuel	30·7	—	—
Electricity	—	36·8	27·6
Repairs	9·6	2·7	2·7
Wages	9·0	9·1	9·1
Engine-house expenses. . .	1·7	—	—
Lubricants	0·4	0·2	0·2
Stores	0·3	0·2	0·2
Total	51·7 <i>d.</i>	49·0 <i>d.</i>	39·8 <i>d.</i>

It was shown in the Paper that for 1,600 British tons behind the drawbar there would be required three 220-British-ton steam locomotives or two 143-British-ton electric locomotives. Consequently the operating expenses (for locomotives) per train-mile work out as follows:—

	Operating Expenses in Pence per Train-Mile.		
	With Three 220-Ton Steam Locomotives.	With Two 143-Ton Electric Locomotives.	
		Without Regen- erative Control.	With Regen- erative Control.
Fuel	92·1	—	—
Electricity	—	73·6	55·2
Repairs	28·8	5·4	5·4
Wages	27·0	18·2	18·2
Engine-house expenses. . .	5·1	—	—
Lubricants	1·2	0·4	0·4
Stores	0·9	0·4	0·4
Total	155·1 <i>d.</i>	98·0 <i>d.</i>	79·6 <i>d.</i>

For mountain-grade applications such as that employed in the above example and for sparse traffic in general, certain important advantages attending the application of regenerative control to a dense traffic are not obtained, and although the saving in the amount of electricity consumed may often be notable, as shown by the above results, a main consideration in adopting regenerative control relates to the lesser wear of the wheels, the brake shoes, and the brake rigging. With mechanical braking, the speed at which a heavy freight-train may be taken down mountain grades is often limited by the permissible heating of the brake shoes. With regenerative braking, the limit is raised to that imposed by other factors such as the safe speed imposed by curves or by the construction of the rolling stock or permanent way.

With a dense traffic the employment of regenerative braking introduces savings of another character as the result of the interchange of current between neighbouring trains. Ascending or accelerating trains draw a part of their power directly from neighbouring descending or stopping trains. It is analogous to the installation of many additional sub-stations distributed along the route. With electricity thus interchanged between neighbouring ascending and descending trains, there is associated a lower loss in the distributing system than is the case when the electricity is sent over a considerable distance from the sub-stations to the train. Furthermore, the sub-stations are relieved of a part of the burden, and the load-factor of the remaining part is increased. Thus the sub-stations are shielded from the peaks of load and need not be equipped with motor-generators of so great a short-time rating. Indeed their continuous rating may also be less, since the average output is decreased when supplying trains with regenerative equipment, except in so far as such equipment will be heavier and will increase the total weight moved. The energy-efficiency of these motor-generators will be higher with the more uniform load. These conclusions only hold good for a dense traffic. For a traffic of so sparse a character that on some occasions the load comprises only one train, there can be no equalizing-out between trains, and this will also be the case with several trains per sub-station if all the trains are simultaneously absorbing power from the sub-station. Consequently the maximum of advantage from the employment of regeneration so far as regards decreased outlay for power will be obtained with a dense, well-distributed traffic and with the use of so high a working pressure as to permit of locating the sub-stations long distances from one another. While on the Chicago, Milwaukee and St. Paul Railway the trains will be relatively infrequent, it is nevertheless considered that

the advantages obtainable by incorporating the regenerative feature in the locomotive equipment are amply sufficient. These advantages relate chiefly to emancipation from the limitations of mechanical brakes.

The modern motor for locomotive equipments is provided with forced ventilation and is much lighter for a given continuous output than were the earlier self-cooled motors. An important feature affecting its appropriateness for regenerative braking is that its continuous output is well up towards the output of which it is capable for 1 or 2 hours for a given temperature rise. Consequently it is not necessary to greatly increase its weight in order that it shall be able to perform as a generator on down grades and when decelerating the train. This was not the case with the railway motor of a dozen years ago. At that time the continuous output for a given temperature rise was rarely as much as half of the output of which it was capable for 1 hour for the same temperature rise. Under those conditions it was essential to successful regeneration to employ very much heavier equipment. The increased weight and cost of such an equipment, had it been provided, would have gone far towards offsetting the decreased energy-consumption per ton-mile obtained in virtue of regeneration. Moreover, it would have been necessary to take into account, not only the increased first cost of these heavy equipments, but also the increased depreciation associated with this larger outlay.

If the subject had been thoroughly analysed in those days it would have been found that in most cases the increased weight of the electric equipment would have occasioned a 10-per-cent. or, in some cases, even a 15-per-cent. increase in the total weight of the car or train. Consequently a 20-per-cent. decrease in the energy-consumption expressed in watt-hours per ton-mile obtained in virtue of regeneration would have left an insignificant margin for net decrease in energy-consumption per car-mile or per train-mile. But with modern methods of intensive ventilation regenerative-control equipments can be built with but moderate increase in weight, and still operate within approved temperature limits, notwithstanding the performance of the double function of motoring and generating.

From the considerations which have been set forth, the appropriateness of regenerative control for a dense traffic such as systems of urban and suburban trains should be evident when reconsidered in the light of the characteristics of modern railway equipments. The capital cost for generating-station, for transmission-line, and for sub-stations should be notably less when the rolling stock is

equipped with regenerative-control apparatus than would otherwise be the case. We thus have not only the decreased consumption at the train per ton-mile, but we also have the decreased interest and depreciation outlays for sub-stations, transmission-line and generating-station. For instance, if there were required for the operation of an electric railway with a dense traffic an output from the generating-station of, say, 100,000,000 kilowatt-hours per annum, then while for an ordinary system without regenerative control it would be necessary to install fully 25,000 kilowatts rated capacity of generating sets, this aggregate capacity would, with regenerative control, be materially reduced, say, to 22,500 kilowatts rated capacity. The percentage decrease in the rated capacity required in the sub-stations would be of at least equal amount, and savings would also be effected in the transmission-cables and in the distributing system between the sub-stations and the contact conductors. Added to these capital savings, there is the further operating saving resulting from the reduced consumption at the train.

It will be recognized from a consideration of the various factors entering into the problem that it requires very careful estimating to arrive in any particular case at a fair quantitative comparison of two systems, the one with and the other without the regenerative feature. Different results will be obtained in different cases. For a level service the shorter the distance between stops and the higher the schedule speed the more appropriate does the regenerative system become. For other than a level service, obviously, the more irregular the profile of the route the more appropriate is regenerative control.¹

THE NORFOLK AND WESTERN 11,000-VOLT RAILWAY.

The Bluefield Division of the Norfolk and Western Railway comprises the 29 miles of main line from Vivian to Bluefield in the State of West Virginia. *Figs. 13 and 14* show the plan and profile

¹ On the 9th December Mr. Aspinall received the following cable from Mr. Hobart.—SEC. INST. C.E.

“On occasion my ‘James Forrest’ Lecture please announce that on Saint Paul electrification 2,500 British ton trailing load twelve per cent. more than guarantee has been hauled up the twenty-mile grade Piedmont to Donald containing two per cent. grades by two 250-ton 3,000-volt electric locomotives descent successfully controlled regeneratively returning electricity into 100,000-volt transmission system. Official tests now taking place to be followed immediately by regular electrical services on 113-mile division between Three-forks and Deerlodge.”

[THE INST. C.E. VOL. CCL.]

of the road, which is double track for the entire distance with the

ELECTRIFIED DIVISION OF THE NORFOLK AND WESTERN RAILWAY.

exception of the Elk Horn Tunnel, which is single track. Sidings, branches into the coal workings, and yard trackage bring the aggregate electrified length of single track up to 97 miles. It will be seen from the profile in *Fig. 14* that the line has long grades, sometimes amounting to over 2 per cent. In the Elk Horn Tunnel the eastbound trains ascend a 1.5-per-cent. grade. In addressing the New York Railroad Club on March 20th, 1914, Mr. George Gibbs made the following interesting allusions to this undertaking:—

I will take the case of the Norfolk and Western first. It is perhaps the heaviest electric traction scheme proposed anywhere in the world as yet. The coal traffic of this railway is the important one, and originates in the Flat Top and Pocahontas fields, which lie on the west slope of the Allegheny Mountains. It is this section of the road we are electrifying—that is, the section between Bluefield on the east and Eckman on the west end, a distance of about 30 route miles, or about 90 track miles. Within this distance, and practically at the summit of the Alleghenies, is the Elkhorn tunnel, about 4,000 feet long; it is a single-track tunnel, and constitutes “the neck of the bottle,” limiting the capacity of the entire road. The alternatives to electrification to relieve congestion were either to double-track the tunnel or to build a relief line, both of which would cost a great deal of money and require years of time.

It is found that electrification of the existing tracks would not only give the

desired increase in capacity of the line, but would give it promptly, and would afford savings in operating costs which would carry the interest and depreciation charges on its cost and leave a handsome surplus besides. The maximum east-bound tonnage at present is about 65,000 tons per day up the gradient, of which about 48,000 tons is revenue traffic; this tonnage, by the way, is exclusive of the ordinary tonnage of the road—it is simply coal tonnage that I am talking about. This tonnage is loaded in about twenty train units of 3,250 tons each, trailing load. This train is hauled up a 2 per cent. grade over the mountain to Flat Top Yard by three Mallet compound engines, thence to Bluefield, 15 miles further, over an undulating grade with $1\frac{1}{4}$ per cent. maximum by two Mallets. At this point trains are made up for the road run to tide water. The entire 30 miles that we are electrifying is what we might call a "gathering division," the tonnage being filled out in the section from the various coal workings; it is, therefore, treated as a separate engine division, and this makes the substitution of electric for steam power unusually advantageous and economical. For these Mallet engines we will substitute electric locomotives.

Fig. 14.

PROFILE OF ELECTRIFIED DIVISION OF THE NORFOLK AND WESTERN RAILWAY.

Electric operation of the Bluefield Division of the Norfolk and Western Railway was inaugurated in May, 1915, with twelve 240-British-ton locomotives of the split-phase type. This type of locomotive operates from a 'single-phase overhead conductor. In the case of the Norfolk and Western system, a pressure of 11,000 volts and a periodicity of 25 cycles per second are supplied from the overhead conductor.

Each 240-ton locomotive is made up of two 120-ton halves, and each half may be operated as an independent locomotive. The trains are, however, very heavy, and for grades of 1.5 per cent. or more, two 240-ton locomotives are necessary, the one at the head of the train and the other pushing at the rear. Trains of this composition and comprising forty-five cars loaded with coal, weigh

2,900 British tons, or, including the two 240-ton locomotives, 3,380 tons. They are known as "tonnage" trains. Such a train is made up at or near the west end of the Division. The up-grade trip from Vivian to Ruth at the eastern end of the Elk Horn Tunnel is made at a speed of 14 miles per hour. Formerly it required three 240-ton Mallet engines, two at the head and one at the rear end of the train, to make the same trip at about 7 miles per hour, exclusive of stoppages for coal and water. Such a steam-locomotive train weighed complete $(2,900 + 3 \times 240 =)$ 3,620 tons, or 7.0 per cent. more than the electric train. The total elevation from Vivian to Ruth is about 900 feet. The distance is 15 miles, the average grade thus being about 1.13 per cent.

On the assumption of the same pounds per ton of frictional resistance, the "drivers-to-drawbar" efficiencies for these trains are:—

$$\text{Electric train } \frac{2,900}{3,380} \times 100 = 86.0 \text{ per cent.}$$

$$\text{Steam train } \frac{2,900}{3,620} \times 100 = 80.0 \text{ per cent.}$$

The Norfolk and Western Electrification provides the following important features:—

1. Decreased outlay for wages of locomotive crews and train crews due to the greater speed and longer trains.
2. Decreased outlay for maintenance of electric locomotives as compared with that of Mallets.
3. Greater annual train- (and ton-) mileage per locomotive.
4. Greatly increased capacity of the division.
5. Superiority of electric traction for lines with frequent and long tunnels.
6. Decreased outlay for track maintenance with electric locomotives as compared with Mallets.
7. Savings in brake-shoe renewals, and freedom from speed restrictions on down grades due to the heating of brake shoes in virtue of employment of regenerative control.
8. Elimination of congestion at tunnels, especially at the single-track Elk Horn Tunnel.

It is desired to dwell for a moment on this last feature. The 3,000-foot single-tracked Elk Horn Tunnel is the bottle-neck of the system. Even the inherently slow Mallets were driven through the tunnel at reduced speed to reduce the quantity of smoke and gases. It was necessary to delay sending in a train until sufficient time had elapsed partly to free the tunnel from the smoke and gases

emitted by the preceding train. Such considerations occasion a bunching up of trains at both ends of a tunnel. Obviously, with steam trains, a serious congestion of this sort can only be slowly relieved, owing to the time which must be allowed to elapse between the passage of successive trains. They cannot be "bunched" in the tunnel. With electric locomotives, very long trains can be taken through, headed by one 240-ton locomotive and with two more 240-ton pusher locomotives. A train of this formation may considerably exceed in useful weight any steam-hauled train, since each steam locomotive employed increases the amount of smoke and gases and the time required to put the tunnel in condition for another train. Electric trains maintaining a speed of 14 miles per hour can be dispatched through the Elk Horn Tunnel at the rate of a train every 3 minutes, as against 6 miles per hour steam trains, of less useful weight, every 7 minutes. Taking into account the greater useful tonnage per train which can be carried electrically through the tunnel, and the greater speed, it may be fairly stated that any bunching up of tonnage on the division can be relieved by electric operation in about one-third the time which would be required with steam locomotives.

It has sometimes been claimed¹ that electric operation is inferior to steam-locomotive methods with respect to the ability with the latter to dispatch trains in fleets in emergencies. It has been stated that in this respect electric operation takes away track capacity "just at the time when the operating official most needs it." While the Author admits that such occasions may arise, he

¹ Mr. A. H. Babcock, at p. 1851 of vol. xxxii (1913) of the Trans. Am. Inst. Elec. Eng., in a Paper entitled "Mountain Railway Electrification," states: "A slight derangement of schedules, or an extra freight movement, citrus fruits or oil, or a blockade, for example, will cause congestion beyond any possibility of estimating. This traffic must be handled as circumstances require. It cannot be spaced conveniently for power demands, as many engineers and power men have suggested, but the terminal yards must be cleared as the cars accumulate."

At p. 927 of vol. x (1913) of *The Electric Journal*, in an article entitled "Heavy Electrification Tendencies," Mr. W. S. Murray writes: "Suppose a bunching-up of trains and tonnage to take place at some point on the system, due to a wreck, a broken wire, a short-circuit or trouble with signals. When conditions ahead have been adjusted and traffic may be resumed, the operating official in charge wishes to let his trains through, one behind the other, just as fast as his block sections will permit, and so make up time lost due to the breakdown. With steam service there is nothing to prevent this."

It has been shown that in such cases as that at the Elk Horn Tunnel there is, contrary to Mr. Murray's suggestion, much more to prevent the resumption of normal conditions with steam service than with electric service, and equivalent conditions are constantly met.

considers that for every such occasion there can be cited others where the electric operation of heavy freight-trains will permit of relieving, or (which is more important) preventing congestion by the increased capacity with which it endows a system with a given trackage.

Generating-Station at Bluestone.—For the case of the Norfolk and Western Railway, the single-phase electricity is provided from a special 25-cycle generating-station located at Bluestone, as shown in *Fig. 13*. This generating-station is equipped with three 10,000-kilovolt-ampere steam-turbine-driven, 11,000-volt, single-phase generators. The pressure is stepped up from 11,000 volts to 44,000 volts, and transmitted at this pressure to five sub-stations, where are installed an aggregate of 28,000 kilovolt-amperes of transformers for stepping down to 11,000 volts, the pressure required at the locomotives.

The Norfolk and Western Electric Locomotives.—The twelve 240-ton electric locomotives operating on the Norfolk and Western Railway are equipped with the split-phase system; 25-cycle, 11,000-volt, single-phase electricity is collected from the overhead conductor by a pantograph trolley with a sliding collector. This high-pressure electricity is received by a stepdown transformer carried on the locomotive, and indicated at A in the diagram in *Fig. 15*. The pressure at the secondary terminals of this transformer is 750 volts. Part of the electricity goes direct from the secondary of the transformer to the polyphase motors (indicated diagrammatically as B in *Fig. 15*) which drive the locomotive. The remainder of the electricity passes through the phase-splitter C on its way to the polyphase motors B. By this means the single-phase electricity supplied to the locomotive is converted into polyphase electricity, and is thus made suitable for driving the polyphase motors B. Each 240-ton locomotive is equipped with eight of these polyphase driving motors. The power from the motors is delivered to the driving-wheels through geared side-rods, the gear ratio being 4.72.

The rotors of the polyphase motors are provided with definite windings and slip rings, so that water-rheostats may be inserted in the rotor circuits during the starting and also for purposes of speed control.

The 240 British tons of weight of the Norfolk and Western locomotive is made up of 227,000 lbs. of electrical equipment and 310,000 lbs. of mechanical equipment. The motors can be operated with either eight or four poles. With the former connection the speed is 14 miles per hour, and the continuous rating is 2,600 HP., corresponding to a tractive effort of 68,600 lbs. With the four-pole

connection the speed is 28 miles per hour, and the continuous rating is 3,000 HP., corresponding to a tractive effort of 40,000 lbs. For these two connections the weight of the electrical equipment per horse-power of continuous rating works out respectively at 86.0 lbs. and 75 lbs.

When addressing the New York Railroad Club on the 19th

Fig. 15.

CONNECTIONS OF TRANSFORMER PHASE-SPLITTER AND MOTOR OF NORFOLK AND WESTERN LOCOMOTIVE.

March, 1915, Mr. George Gibbs gave the following data of these electric locomotives :—

Length overall	105 feet 8 inches
Rigid wheel-base	11 feet
Truck wheel-base	16 feet 6 inches
Diameter of driving-wheels	62 inches
Diameter of pony-wheels	30 inches
Weight on drivers	197 British tons
Total weight of locomotive	240 British tons

The Mallet locomotives which were employed on the Bluefield Division prior to its electrification were described by Mr. Gibbs as "of the latest compound type, fitted with mechanical stokers and superheaters." He gave their weight as "about 370,000 lbs. on drivers, and 540,000 lbs. total, including tender," and said they were "estimated to have a tractive power of about 85,000 lbs." He stated that tonnage-trains were handled normally at a speed of from 7 to 8 miles per hour on the grades, except in the Elk Horn Tunnel.

RATIO OF TON-MILEAGE TO TRAIN-MILEAGE OF FREIGHT TRAFFIC.

Mr. James J. Hill has stated that "the place for the railroads to save is in their train-miles." *The Annalist* for the 6th September, 1915, gives statistics which bring out very clearly the extent of the practical application of this maxim to American railroads during recent years. The statistics quoted by *The Annalist* are plotted in *Figs. 16 to 20*. From *Figs. 16 and 17* we see that for two specific

Fig. 16.

cases, the Chicago, Burlington and Quincy Railroad, and the Wabash Railway, while the total annual train-mileage of goods traffic during the last 14 years shows no marked change, decreasing 11.1 per cent. for the first-mentioned railway, and increasing 17.5 per cent. for the last-mentioned railway, the total annual ton-mileage has in these 14 years increased respectively in the two cases by no less than 127 per cent. and 75 per cent. *Figs. 18 and 19*

relate to the results for the entire railway system of the United States, and show that corresponding to an increase of only 22 per cent. in the annual train-mileage of goods traffic during the 14 years there has been an increase of 104 per cent. in the annual ton-mileage of goods traffic. Finally, in *Fig. 20* are plotted, for the

Fig. 17.

ANNUAL GOODS TON-MILEAGE ON TWO AMERICAN RAILWAYS.

three cases, the ratio of the ton-mileage to the train-mileage for the annual goods traffic during the last 14 years, and the following results are given :—

PERCENTAGE INCREASE IN THE LAST 14 YEARS IN THE RATIO OF TON-MILES TO TRAIN-MILES FOR THE GOODS TRAFFIC PER ANNUM.

All United States railways	68 per cent.
Chicago, Burlington and Quincy Railroad	156 „
Wabash Railway	48 „

The Analyst's article is entitled "A Triumph of Intensification." It is stated that although allowance must be made for certain factors which cannot be easily calculated, the percentage increases in the ratio of ton-miles to train-miles is a measure of the extent to which the railroads have been able to intensify their goods traffic. The article goes on to state that: "A number of factors have contributed to this result. Increasing wages and other operating costs have

Fig. 18.

ANNUAL GOODS TON-MILEAGE FOR ALL RAILWAYS IN THE UNITED STATES.

Fig. 19.

ANNUAL GOODS TRAIN-MILEAGE OF ALL RAILWAYS IN THE UNITED STATES.

compelled the railroads, as a matter of self-preservation, to effect economies in operation which were unknown at the beginning of the period. They have learned, first—and it is perhaps the most important knowledge of all—that the most profitable train to run is the one which does not move until it has been filled to engine capacity. Therefore they strive continually not only to accomplish that, but to increase the capacity of the locomotive as well, so that

the load in turn may be further increased. In the 12 years ending with June 30, 1914, the average tractive power of American locomotives increased by approximately 50 per cent. This has also

Fig. 20.

RATIO OF TON-MILEAGE TO TRAIN-MILEAGE FOR GOODS-TRAFFIC FOR ALL RAILWAYS IN THE UNITED STATES AND FOR TWO INDIVIDUAL CASES.

resulted in increasing the size of other equipment. The average capacity of a freight car is now about 40 per cent. greater than it was 15 years ago."

The points brought out in the present Lecture render it almost superfluous to call attention to the inevitability of the rapid introduction of the electric locomotive in the further pursuance of the policy discussed by *The Annalist*. While the steam locomotive, as stated in *The Annalist's* article, has increased in 12 years by 50 per cent., in the feature of the average tractive effort of which it is capable, there has been no notable increase in the speed of goods-locomotives. The electric goods-locomotive provides any tractive effort permitted by the draw-gear, and also provides any increase in speed permitted by curves, and strength of goods-wagons and permanent way. It has been shown in the Paper that the heaviest goods-trains may, with electric locomotives, be propelled over heavy grades at twice the speed possible with steam locomotives.

PASSENGER-LOCOMOTIVES ON THE NEW YORK CENTRAL RAILROAD.

The 600-volt electrification of the New York Central Railroad, which at present comprises 52 route miles (or 251 miles of single track), and extends on one division 34 miles from the Grand Central Station in New York City, is now an old story, and no general description is necessary. It is briefly touched upon in this Paper with the object of describing the "1913" type of electric locomotive, of which sixteen are now in service in addition to the forty-seven original locomotives which date from 1906.

This "1913" locomotive, which weighs 115 British tons, is designed for high-speed passenger service. Its continuous rating is 2,000 HP., and corresponds to a tractive effort of 13,840 lbs. at 54.5 miles per hour. Its 1-hour rating is 2,600 HP., and corresponds to a tractive effort of 20,400 lbs. at 48 miles per hour. The locomotive operates from a 600-volt conductor rail. The two-axle guiding trucks at each end are each fitted with two motors. These, with the four motors carried by the articulated middle truck, make a total of eight motors for the locomotive. The entire weight is on drivers, the weight per axle being 14.4 tons. Each motor has a continuous rating of 250 HP. For this rating a volume of 3,000 cubic feet of air per minute is blown through it. The motors are bipolar, and their armatures are mounted directly on the axles, gearing losses thus being eliminated. The locomotive is suitable for all speeds up to 75 miles per hour.

These locomotives haul, at 60 miles per hour, trains with a total weight of 1,100 British tons. The tractive effort of 20,400 lbs. corresponding to the 1-hour rating only amounts to 8 per cent. of the weight on drivers, the locomotive's capacity being controlled by that of its electrical equipment and not by any limiting

coefficient of adhesion. The locomotive could haul the heaviest passenger-trains over steeper grades than any on the New York Central Railroad. A 1,100-ton train on a 0.4-per-cent. grade requires a tractive effort of about 20,400 lbs., and the speed corresponding to this tractive effort is 48 miles per hour. For these conditions the "drivers-to-drawbar" efficiency, on the assumption

Fig. 21.

CHARACTERISTIC CURVES OF MOTOR FOR "1913" TYPE OF NEW YORK CENTRAL PASSENGER-LOCOMOTIVE.

of equal resistance, in pounds per ton, for both locomotive and passenger coaches, is—

$$\frac{1,100 - 115}{1,100} = 89.5 \text{ per cent.}$$

Owing to the absence of gearing, the efficiency of the electrical equipment is exceptionally high. The characteristic curves for the motor employed are given in *Fig. 21*, and the efficiency of the motors, for a speed of 48 miles per hour, is seen to be 91 per cent. Allowing

an additional 2·5 per cent. to cover the energy consumed by the blower and other auxiliaries, we have—

	Per Cent.
Efficiency of electrical equipment	88·5
“Drivers-to-drawbar” efficiency	89·5
Efficiency from collecting shoe to drawbar	79·2

The total locomotive weight of 112 British tons is made up of 167,000 lbs. of mechanical equipment and 83,000 lbs. of electrical equipment.¹

RELATIVE EXTENT, IN 1915, OF SINGLE-PHASE AND HIGH-PRESSURE DIRECT-CURRENT ELECTRIFICATION.

In the following Table are given data of the growth, in the United States, of single-phase and high-pressure direct-current electric railways during the last 9 years.

TOTAL MILEAGE OF SINGLE-TRACK OPERATING AND UNDER CONSTRUCTION.

Year.	Single-Phase.	High-Pressure Direct Current.		
		1,200 and 1,500 Volts.	2,400 and 3,000 Volts.	Total for High-Pressure Direct Current.
	Miles.	Miles.	Miles.	Miles.
1906	650	..	..	..
1907	1,040	..	..	..
1908	1,130	..	..	..
1909	960 ²	..	..	..
1910	990 ²	600	..	600
1911	1,040 ²	1,100	..	1,100
1912	1,040 ²	1,600	100	1,700
1913	940 ²	2,200	200	2,400
1914	1,340	2,750	450	3,200
1915	1,490	2,810	910	3,720

It should not be concluded from the data in the above Table that there is no longer any activity in America in applying the single-phase system to railways. For tramways and light railways single-

¹ This is the weight of the locomotive as delivered. The subsequent addition by the railway company of heating equipment and certain other accessories has increased the weight to about 119 British tons.

² The falling off in increase in single-phase mileage during 1909 to 1913 was partly due to changing over eight roads (aggregating over 300 miles of single track) from single phase to direct current.

phase apparatus is generally admitted to be inferior, and no new undertakings have adopted the single-phase system for several years. But extensive single-phase applications have been made in the electrification of sections of main-line railways. Notable amongst these are the Norfolk and Western Railway, the New York, New Haven and Hartford Railroad, and the Pennsylvania Railroad.

The Author is satisfied that the high-pressure direct-current system is so distinctly superior in essential respects as ultimately to ensure its general use on main-line railways, in preference to the single-phase system or any of its modifications.

The serious disabilities of the single-phase system were well understood long ago by a small number of engineers, including the Author of the present Paper. At p. 31 of vol. xxvi (1907) of the *Trans. Am. Inst. Elec. Eng.* appears a Paper by Messrs. Stillwell and Putman, entitled "The Substitution of the Electric Motor for the Steam Locomotive." In that Paper the Authors take the standpoint that the single-phase system is the only system worthy of consideration for railway electrification. "Where, 10 years from to-day," they ask, "will be the 1,200- or the 1,500-volt direct-current systems which have been suggested as substitutes for high-potential alternating-current systems in heavy electric traction?" In *The Times Engineering Supplement* for the 10th April, 1907, I expressed the opinion that the Authors of that Paper had "allowed a desire, shared by all engineers, to secure the best system for long-distance work, to supplant sufficient study of adverse details in the single-phase system." I went on to state my opinion "that within 10 years direct-current systems, as applied to railway electrification, will employ line pressures more of the nature of 2,000 or 3,000 volts, and these systems will in all probability have come into extended use. The single-phase delusion will meanwhile have been exposed." Only 8 of the 10 years have yet elapsed, and we can record very satisfactory progress toward the fulfilment of this expectation.

It should, however, be clearly understood that some of the original advocates of the single-phase system continue to suggest that it is the most appropriate. Mr. B. G. Lamme, in the *Electric Journal* for October, 1913, closes an article as follows:—

It would appear, therefore, that the single-phase system, taken in its broad sense, presents possibilities not found with any other general system yet proposed. At present the system allows the use of two radically different types of equipment, namely the straight single-phase and the split-phase, while certain other types present very great possibilities. Thus the system appears to be

broadening out in its application, instead of narrowing, which is a most promising feature. With this one general system, terminal and yard work, main-line service, tunnel operation, mountain grade work, branch line and feeders, etc., can all be handled.

In the August, 1915, issue of the *Proceedings of the Am. Inst. Elec. Eng.* is a Paper by Mr. W. S. Murray, Consulting Electrical Engineer to the New York, New Haven and Hartford Railroad, entitled "Conditions Affecting the Success of Main-Line Electrification." At p. 1885 of this Paper Mr. Murray says:—

At this juncture it is of interest to point to the fact that under the single-phase high-potential contact-wire three types of electric motive-power—the single-phase, the three-phase, and the direct-current (through the medium of a rectifier)—can operate; thus each class of equipment is permitted a supply of power unchanging in form.

The principle of cardinal importance to the writer's mind, and one of the conditions affecting the success of main-line electrification, may, therefore, be said to be the establishment of a standard system of power distribution, from the contact wires of which shall be delivered power in standard and unchanging form; and while all electric locomotives or multiple-unit equipment will primarily receive this power in identical form, it may thereafter be modified or transformed to conform to any type of alternating-current or direct-current equipment, which is in turn prescribed by the local conditions. Such a standardization would provide a single high-voltage contact-wire running throughout an entire electrification zone upon which are impressed 11,000 volts of 25-cycle single-phase electricity.

Again at p. 1882 of Mr. Murray's Paper we find:—

The recent decision as to choice of system on the part of the Pennsylvania Railroad in favour of single phase for the proposed electrification on the main line between Philadelphia and Paoli, this action being a forecast of the system to be employed in the event of the future financial situation permitting electrification between New York and Washington, was one of no small consequence and pleasure to those who had been toiling to establish a correct application of electrification to trunk line territory.

To those who every day had been in close association with the practical workings of this system initially installed on the New Haven, failures were too closely associated with cause and effect to suggest even disappointment, to say nothing of discouragement, but let me refer to an admirable and fine distinction as evidenced in the decision of Gibbs and Hill, which discounted apparent for real results, and settled that the body of their electrification should be upon a single-phase basis, notwithstanding that the largest terminal upon the same railroad was operated upon a direct-current basis.

It is not proposed in this Paper to deal quantitatively with the relative merits of single-phase and direct-current locomotives further than to state the Author's conclusion that, owing to the lower "drivers-to-drawbar" efficiency and the lower efficiency of the electrical equipment of single-phase locomotives, a given output from the drawbar will (taking into consideration all the

varieties of traffic on a railway) require so much greater consumption of electricity by the locomotives as to fully offset any economies in sub-stations and distribution system. This conclusion concerning the relative consumption of the two types simply refers to one of the items entering into a comprehensive comparison. Amongst other matters requiring consideration are the relative initial costs of locomotives of equal capabilities of the two types, the relative outlays for repairs, and the relative reliability.

An interesting sidelight is thrown on the superiority of the direct-current motor by the following statement by Mr. Murray at a meeting of the New York Railroad Club on March 19th, 1915, in commenting on the "rectifier" locomotive :—

In the alternating current supplied to our passenger engines now operating between New York and New Haven by the use of the rectifier there is permitted an increase of about 50 per cent. in traction, with all of the speed characteristics that these engines now possess retained. This characteristic will doubtless permit us to avoid the necessity of the purchase of a large number of passenger engines in the future as our passenger traffic increases, as our alternating-current direct-current engines can be converted into rectifier engines in proportion to the increased traffic requirements, the cost of this change-over being only a small percentage of the cost of new engines.

Here we have a record of Mr. Murray's experience that the commutator motors on his single-phase locomotives have only two-thirds as great an output when supplied with single-phase as when supplied with direct-current electricity, and that single-phase equipment is much heavier for a given output than direct-current equipment.

In view of the increasingly frequent allusions in the technical press to the use of rectifiers on "single-phase" locomotives, it should be pointed out that a rectifier supplied with single-phase current differs from a polyphase rectifier in that it does not inherently supply the practically non-pulsating current required for obtaining the best operating results from direct-current motors. Also the supply of single-phase electricity to such locomotives leaves the system on the same unsatisfactory basis as regards its constituting a source of inductive disturbance to telephone and telegraph systems. At p. 136 of vol. xxxi (1912) of the Trans. Am. Inst. Elec. Eng., in a Paper entitled "The Relative Costs and Operating Efficiencies of Polyphase and Single-Phase Generating and Transmitting Systems," the author commented on this subject as follows :—

At this point I am tempted to include mention of the consequences which would result from the development of large static-rectifier sets. It would appear that those of the mercury-arc type will be at least equally small and efficient at

high periodicities as at low periodicities. If further developments bear out this indication, then the use of mercury-arc rectifiers in substations as an alternative to synchronous converters will permit (when the periodicity is not fixed by other conditions) of employing periodicities of 60 cycles per second with the associated advantages as regards lower price and higher efficiency of the step-down transformers. On this plan, the transmission would continue to be polyphase. But if (as some single-phase advocates propose) static rectifiers are placed on the train and employed to supply direct-current motors, the difficulties relating to the impedance of steel rails would continue to necessitate the use of low periodicities such as 25 or even 15 cycles per second, or else it will be necessary to supply liberal copper feeders tapped off to the rails at frequent intervals.

The indications are that the commercial development of static rectifiers of large capacity will increase the range of appropriate application of the three-phase system with substations and employing direct-current motors on the trains, or, conversely, and contrary to the usual prediction, will greatly narrow the range where the single-phase system is economically more appropriate. But the chief cause for satisfaction, and one which will be shared by all electrical engineers, is that any such development of static rectifiers will increase the range or work where electrical methods of operating trains will be economically more appropriate than steam-locomotive methods. Judging from the properties of mercury-arc rectifiers, large polyphase static rectifiers will be not only more efficient than, but also considerably cheaper than, the equivalent synchronous converters, and this, together with the probable practicability of employing a periodicity of 60 cycles per second, will materially decrease the cost of the electricity required for given train operations.

When consideration is given to the characteristics of single-phase and direct-current locomotives, we find ourselves faced with the purchase at the point of delivery to the sub-stations, either of a given quantity of single-phase lagging-power-factor electricity, or an appreciably-less quantity of three-phase unity power-factor or even leading-power-factor electricity. It will rarely be practicable to supply the former kind of electricity to the sub-stations at a price per kilowatt-hour less than 30 per cent. in excess (see p. 215) of that at which the latter kind of electricity can be profitably supplied to the sub-stations.

In America by far the most usual periodicity is 60 cycles per second. Most of the great transmission systems employ 60 cycles. If the single-phase system were to be employed by a railway purchasing 60-cycle electricity, it would be necessary to equip the sub-stations with motor-generator sets. Such motor-generator sets would consume 60-cycle three-phase electricity and deliver single-phase 25-cycle electricity. On this plan the sub-stations with the single-phase system would be on the same basis, as regards the greater first cost and the lower efficiency of rotating machinery, as the direct-current system, leaving the single-phase system at a disadvantage as regards both total first cost and annual overall

efficiency from generating-station to drawbar of locomotive. The same considerations apply in Great Britain and other countries in which by far the most usual periodicity is now 50 cycles per second. It would either be necessary to employ separate generating-stations to provide the 25-cycle single-phase electricity, and forgo the advantages of high load-factor and diversity-factor, or else interpose motor-generator sub-stations of the same order of cost and efficiency as the motor-generator sub-stations required for the high-pressure direct-current system.

COST OF ELECTRICITY AT THE LOCOMOTIVE.

At this point it is of interest to investigate the cost of electricity as delivered at the locomotive with direct-current and single-phase systems. Let us compare the three following systems:—

A. Polyphase, 60-cycle generation and high-pressure transmission to sub-stations where the pressure is stepped down, the electricity then being delivered into polyphase synchronous motors operated at unity power-factor, and afterwards being delivered from direct-connected, high-pressure direct-current generators, and thence distributed to high-pressure direct-current locomotives.

B. Polyphase, 60-cycle generation and high-pressure transmission to sub-stations where the pressure is stepped down, the electricity then being delivered into polyphase synchronous motors operated at unity power-factor, and afterwards being delivered from direct-connected, 25-cycle, single-phase generators, and thence distributed at an average lagging power-factor of 0.75 to single-phase locomotives.

C. Single-phase, 25-cycle generation (in large stations for supplying many locomotives), and high-pressure transmission to sub-stations where the pressure is stepped down, and the electricity distributed direct from the step-down transformers, and at an average lagging power-factor of 0.75, to single-phase locomotives.

We may assume that the electrification in question requires at the locomotives some 70 million to 90 million kilowatt-hours per annum, or a matter of about 100 million kilowatt-hours from the generating-station. The comparisons are so arranged that the results are independent of the precise annual consumption; it is only desired to indicate that the amount of electricity required is of the order of 100 million kilowatt-hours per annum.

System A.—Let us assume that for System A 100 million kilowatt-hours of electricity is delivered per annum, for the railway's requirements, from the generating-station to the step-up transformers, at

a cost of 0·290*d.* per kilowatt-hour. Let this low cost be in part due to the circumstance that the supply station has other large consumers and that, were it not for the diversity-factor of the railway load with relation to the loads taken by these other consumers, the cost of the 100 million kilowatt-hours required by the railway would have been 6 per cent. greater, i.e., 0·307*d.* per kilowatt-hour. Furthermore, let the cost of 0·290*d.* per kilowatt-hour be based on a load-factor at the generating-station of 0·50 for the 100 million kilowatt-hours of railway load. While at the present state of the art these various assumptions are all reasonable under favourable conditions, and with thoroughly modern design, it would not be right to infer without investigation that in any particular case it would be practicable to supply electricity at prices based on so low a cost. The assumptions are employed because they are attainable under favourable circumstances, and are consistent with one another. The employment of a higher basic cost, while it would be without much influence on the final conclusions, would have relegated the values to times and conditions from which we are emerging instead of adjusting them into consonance with the conditions upon which the art is now entering.

The investment and operating costs (the latter being chiefly represented by the losses) in the 60-cycle, polyphase, step-up transformers will increase the cost of the electricity (expressed in terms of the output from the transformers) by 0·013*d.* per kilowatt-hour, making it $(0\cdot290 + 0\cdot013 =) 0\cdot303*d.*$ This is based upon the market value of such transformers, on appropriate values for interest, depreciation, taxes and insurance, and on an annual overall efficiency (of the transformers) of 97·5 per cent.

Let the average distance of transmission be 100 miles, and let the conductors be proportioned for an annual overall efficiency of transmission of 95·0 per cent. The investment and operating costs associated with the transmission-line (exclusive of step-up and step-down transformers) will increase by 0·083*d.* per kilowatt-hour, the cost of the electricity delivered from its distant end, making the cost at that point 0·386*d.* per kilowatt-hour.

The polyphase, 60-cycle, step-down transformers will have an annual overall efficiency of about 97·0 per cent. Their investment and operating costs will increase the cost of the electricity by 0·017*d.* to 0·403*d.* per kilowatt-hour of electricity delivered from them.

The annual overall efficiency of the motor-generator sets in the sub-stations may conservatively be taken at 0·87 per cent. The investment and operating costs of the sub-stations (exclusive of the

step-down transformers, which have already been considered) will increase the cost of the electricity delivered from them by 0·175*d.* to 0·578*d.* per kilowatt-hour.

Taking the distribution system (i.e., the system intermediate between the sub-stations and the locomotives) as having an annual overall efficiency of 92·0 per cent., we may assess the increase in the cost of the electricity due to the investment and operating costs of the distribution system at 0·160*d.* per kilowatt-hour, bringing up the cost of the electricity at the locomotives to 0·738*d.*

The annual overall efficiency of the system from the outgoing cables at the generating-station to the pantographs on the locomotives is :—

$$0\cdot975 \times 0\cdot950 \times 0\cdot970 \times 0\cdot870 \times 0\cdot920 \times 100 = 71\cdot8 \text{ per cent.}$$

System B.—In this case we have, up to the motor-generator sets in the sub-stations, the same results as for System A. But the generators of the motor-generator sets are now single-phase machines instead of direct-current machines. Notwithstanding the absence of commutators, the single-phase generators do not represent any lower cost or better efficiency, even although, owing to the use of 11,000 volts as against 3,000 volts, there may be employed less sub-stations, each sub-station having sets of larger capacity and having a better load-factor. It does not seem to be generally recognized that a single-phase generator of a given output in kilowatts, but supplying a lagging load of 0·75 power-factor, costs fully twice as much, and has considerably lower efficiency than a three-phase unity-power-factor generator for the same rated output, equal temperature rises being assumed in the two cases. Taking into account these disabilities of single-phase generators, even the lesser number of sub-stations and the better load-factor does not decrease the addition to the cost debited to the sub-stations in System A, but we will credit the motor-generators with the same annual overall efficiency of 87·0 per cent. Thus at the point of delivery from the sub-stations the cost of the electricity is the same as in System A, namely, 0·578*d.* per kilowatt-hour. For the distribution system, however, the investment cost will be less than for System A, even for a higher annual overall efficiency, which we will take at 0·96 per cent. (as against 0·92 per cent. for System A). The investment and operating costs associated with the distribution system will increase the cost of the electricity by 0·100*d.* to 0·678*d.* per kilowatt-hour at the points of delivery to the locomotives of the 0·75-power-factor lagging electricity.

The annual overall efficiency of System B from the outgoing

cables from the generating-station to the pantographs on the locomotive is—

$$0.975 \times 0.950 \times 0.970 \times 0.870 \times 0.960 \times 100 = 75.0 \text{ per cent.}$$

System C.—The investment and operating costs of a generating-station for the exclusive supply of the 25-cycle railway load, per kilowatt-hour of output from the station, would be 0.315*d.* (as against 0.290*d.*) on account, firstly, of the sacrifice of the savings which may be effected with the high diversity factor of the railway load associated with the load of other consumers, and secondly, on account of the smaller annual output from the generating-station.

But in addition to these considerations, it costs more to provide a given amount of electricity of 0.75 power-factor than of unity power-factor. From the considerations set forth on p. 171, it will be seen that on this account the cost will be increased from 0.315*d.* to 0.345*d.* per kilowatt-hour.

There is the still further additional cost due to the inherently higher cost and lower efficiency of single-phase as compared with polyphase generators. These differences are much greater than are generally conceded, and will increase the cost of the 25-cycle, 0.75-power-factor, single-phase electricity delivered from the generating-station in System C, by a further 0.015*d.* per kilowatt-hour, bringing it up to 0.360*d.* at the point of delivery to the step-up transformers.

The annual overall efficiency of the 0.75-power-factor, single-phase, 25-cycle step-up transformers will be 96.5 per cent. Their investment and operating costs will increase the cost of the electricity by 0.023*d.*, making it 0.383*d.* at the point of delivery to the transmission-line.

Letting the pressure between the conductors of the single-phase transmission-line be 15 per cent. higher¹ than in the three-phase transmission-line employed in Systems A and B, and employing the same total cross section of copper as in those cases, then for the transmission of the same total number of kilowatt-hours, but at 0.75 power-factor and single-phase, the annual overall efficiency of the transmission-line will be only 91.0 per cent. (as against 95.0 per cent. for the three-phase unity-power-factor transmission-line of Systems A and B). The investment and operating costs (the latter being chiefly the cost of the energy dissipated in the transmission-line) of the transmission-line will add 0.105*d.* per

¹ This 15 per cent. higher pressure between conductors corresponds to the same pressure between conductors and ground for both systems.

kilowatt-hour, making the cost at the distant end 0.488*d.* per kilowatt-hour. The investment and operating costs of the sub-stations and their contents (the step-down transformers, whose annual overall efficiency is 96.0 per cent., and the switch-gear) increase the cost by 0.040*d.*, bringing it up to 0.528*d.* per kilowatt-hour as delivered from the sub-stations. The investment and operating costs of the distribution system are 0.097*d.*, a trifle less than for System B (since the cost of the electricity dissipated in the distribution system is slightly lower), making the cost of the 0.75-power-factor, single-phase electricity delivered to the locomotives 0.625*d.* per kilowatt-hour.

The annual overall efficiency of System C from the generating-station to the pantographs on the locomotives is—

$$0.965 \times 0.910 \times 0.960 \times 0.960 \times 100 = 80.9 \text{ per cent.}$$

In the following Table are brought together the costs of the electricity at the locomotives for the three systems.

Regeneration is not taken into consideration in the Table, but it should be pointed out that, while considerable gains are available with regeneration in System A, the split-phase type of single-phase equipment is the only one permitting of the commercial utilization of regeneration, and that even then the range of speeds permitting of its use is relatively limited.

It should be obvious from the nature of the method of comparison that the efficiencies of the different systems do not constitute criteria of their relative economy, since costs are assessed to each loss when it first comes up for consideration.

Cost of the Electricity in Pence per Kilowatt-Hour.	System A.	System B.	System C.
As delivered from generating-station . . .	0.290	0.290	0.360
As delivered from step-up transformers . .	0.303	0.303	0.383
As delivered from transmission-line	0.386	0.386	0.488
As delivered from step-down transformer . .	0.403	0.403	0.528
As delivered from sub-stations	0.578	0.578	0.528
As delivered to locomotives	0.738	0.678	0.625

Although various kinds of service, such as hauling local and express passenger-trains, freight-train service of various classes,

and switching¹ service, affect the extent to which single-phase locomotives are handicapped as regards current consumption, they will, even under the most favourable conditions, not be likely to consume less than 15 per cent. more electricity than direct-current locomotives for the same output at the drawbar averaged over the entire traffic of a railway. Taking this percentage, relative figures for the outlay for electricity are derived in the following Table:—

	System A.	System B.	System C.
Cost of electricity as delivered at the loco- motives per kilowatt-hour)	0·738 <i>d.</i>	0·678 <i>d.</i>	0·625 <i>d.</i>
Relative consumption of electricity at loco- motive pantographs)	1·00	1·15	1·15
Product of I. and II.	0·738	0·780	0·719
Ditto in terms of total cost of electricity for System A taken as 100)	100	106	97·5

The 6-per-cent. and 2·5-per-cent. differences are too small to be considered in this rough comparative study. Consequently we may, on the basis of our assumptions, which have certainly not favoured the direct-current system, take the outlay for electricity as about the same for the three systems, leaving the single-phase systems handicapped by the greater inherent cost of single-phase locomotives.

If, up to the locomotive, any material savings could have been demonstrated for the single-phase system, then the correct choice would be influenced by the density of traffic; the greater outlay per single-phase locomotive with a sparse traffic being more than offset by the savings up to the locomotive, while with a dense traffic the greater outlay per single-phase locomotive would more than offset any savings up to the locomotive. Since, however, up to the locomotive, the costs are a stand-off, it would appear that even with a sparse traffic the direct-current system is the most economical, and that the percentage by which it is more economical increases with the percentage which the locomotive investment bears to the total investment.

The conclusions of this Paper are to the effect that: 1st, we are

¹ The greater the proportion of switching service, the greater will be the ratio of single-phase consumption to direct-current consumption for a given total output at the drawbars of all the locomotives in all services, partly owing to the inferiority of the single-phase system with respect to the "drivers-to-drawbar" efficiency.

on the eve of the extensive employment of electric locomotives on railroads at present operated with steam locomotives; 2nd, that the direct-current system is the most appropriate; and 3rd, that direct-current locomotives for use from high-pressure contact conductors are now a thoroughly demonstrated success.

The Author wishes to acknowledge his indebtedness to Messrs. W. B. Potter, G. H. Hill, A. H. Armstrong, J. B. Cox, C. J. Hixson, E. S. Johnson, John Liston and W. D. Bearce for much cordially rendered co-operation in the preparation of this Lecture.

The PRESIDENT remarked that the "James Forrest" Lecture was not submitted to the criticism of the members, but he thought their opinion of the Lecture just delivered would only be in its favour. The deductions were drawn from facts, and were of a most interesting character. He moved a cordial vote of thanks to the Lecturer, Mr. Hobart, and to Mr. Aspinall.

The resolution having been carried by acclamation,

Mr. ASPINALL thanked the members on behalf of Mr. Hobart and himself.