Scientific American Supplement, Vol. XX., No. 503.
Scientific American, established 1845.

NEW YORK, AUGUST 22, 1885.

Scientific American Supplement, \$5 a year.
Scientific American and Supplement, \$7 a year.

THE INAUGURATION OF THE STATUE OF NIEPCE.

On June 21, 1885, the statue of Nicéphore Niepce, the inventor of photography, was inaugurated in the pretty town of Châlon on the Saône, whose quays with their life and bustle were formerly the admiration of travelers, but are now silent and unused, the weeds growing in the cracks of the pavement.

This recognition of the inventor's work was due to Niepce, who during his lifetime was poor and unknown, although photography is, unquestionably, one of the greatest inventions of modern times. Justice has finally been rendered him, and this bronze statue, the work of Mr. Guillaume, stands to-day on the bank of the Saône. It represents the inventor with his head raised, looking at the sun, while the movement of his right hand seems to indicate that it is by the rays of the sun which entered the camera that he obtained such great results. In his left hand, which rests on the camera, he holds the first heliographic proof made, a portrait of Cardinal d'Amboise. This plate is preserved in the museum of Châlon. The pedestal was made from the plans of Mr. Narjoux, an architect of Paris, and Mr. Poinet, an architect of Châlon.

The sun was obscured until noon, but appeared at the right moment to assist at the fête, which was partly its own. Addresses were delivered by the mayor of Châlon and others, and a poem was read by Mr. Lucien Pate.—*L'Illustration*.

A SKETCH OF ROMAN BUILDING CONSTRUCTION.*

By W. T. OLDRIEVE.

To disentangle the architectural conceptions of a people from that which is borrowed or inherited by tradition, leaving that which can justly be called their own, is a task by no means easy. Architectural writers have, in attempting it, entered upon an arena of strife which, to the amateur and the professional student, is not a little perplexing. It is only necessary in this "sketch" to assume that we may legitimately call that Roman which the Romans first made a principle of construction or design, although the primary forms adopted may have been previously used by other

* Being the Cousin Prize Essay in the Class of Fine Art, Edinburgh University, Session 1884-85.—*Building News*.

nations. It is proposed to consider the subject under— I. Principles and forms of Roman construction. II. Processes and methods. III. Materials and workmanship.

I. PRINCIPLES AND FORMS.

Although the Romans used the three "orders," it was in some important respects in a different manner to that in which the Greeks made use of them. The Romans did not rest satisfied with them, nor did they enter wholly into the spirit of an epistyle construction as the Greeks, whose purity of form and delicacy of line were never appreciated by the Roman architects. While the architecture of the Greeks is expressive of an artistic and refined simplicity, that of the Romans is expressive of vast resources, indomitable energy, and great constructive skill. The Greeks so designed their buildings that no decoration or adornment was needed as a necessity to make them artistic, for the artistic spirit is in the construction. Not so is it, as a principle, with the architecture of the Romans; the form which covers the construction is often independent of it. This may be stated as a first principle in Roman construction. Undoubtedly the most characteristic feature in the buildings of the Roman period is the arch. The Romans first used it in a true sense architecturally and consistently, although its use can be traced back, in a more or less perfect form, to almost all the ancient nations. In adopting the arch as an architectural feature, the column and the entablature were not discarded by the Romans, though they show by their great vaults and domes that they could constructively have been dispensed with. It is generally assumed that in the combination of arch and epistyle in a Roman facade, the arch and wall are Roman, and the column, etc., are borrowed from the Greeks. Semper has entered a protest against this assumption, and asks why the column should be borrowed by the Romans from the Greeks, when both nations belonged to the same family and started with the same traditions, and when the column is found as early in Italy as in Greece. It is probable that the column and entablature were used as the natural construction, and the wall and arch introduced in the buildings of several orders in height, as the Colosseum, to support the upper stories as well as to form an outer screen. A feature was thus added which gave increase of strength while preserving the columnar principle. Viewed in this way, the Roman combination of column and arch

INAUGURATION OF THE STATUE OF NICEPHORE NIEPCE, AT CHALON-SUR-SAONE.

is not an architectural scandal, though this is frequently taught. It is considered not improbable that this combination was introduced from some of the Hellenistic cities, though its introduction does not seem to have been clearly traced. The first Roman example is believed to be the Tabularium at Rome, B. C. 78. Another combination of the same nature, though less defensible, is the use of piers or mullions in an arch-headed aperture. This can only be mentioned here. The Pantheon at Rome exhibits, in its front external elevation, the curious effect produced by the pedimented portico placed in front of a domed circular structure. Ferguson and others have held that the portico is a later addition, but authorities are pretty generally agreed that this is not so. It is in the use of the arch principle as a vault that the Romans have gained pre-eminence. Vaulting was no doubt used earlier in underground tunnels, etc., and the Hellenistic city of Mitylene in Asia Minor is supposed to have furnished the model for the first Roman stone-constructed theater on flat ground, B. C. 50, where arches supported the rows of seats; while a writer of about B. C. 40, referring to the city of Alexandria, says that the buildings were without boarding or timber of any kind, so that vaulting seems to have been in common use there. In no part of the architecture of the Romans can we get a better knowledge of the principles which guided them in their treatment of the arch. Although the vast extent of their undertakings seems at first sight to indicate that they were lavish in their expenditure of labor and materials, a more careful examination shows that there was really a feeling of economy, and that there is a correspondence between the extent of the building and the means adopted. By their scientific and constructive skill in the use of the vault, the Romans produced in their structures perfect solidity and incomparable grandeur with a minimum of expenditure. In following out our next division of the subject under consideration, we shall be able to trace in detail the carefully considered economy of parts and labor which was practiced in Roman buildings, as, for instance, the brick rib and concrete filling principle of vaulting, and the hidden buttresses in the thickness of the walls of the Pantheon, whereby greater resistance to the pressure of the vaulting was obtained than if the walls, 20 ft. thick, had been solid, though only half the quantity of materials was used.

II. PROCESSES AND METHODS.

It will be necessary, in order to keep within the limit of a short class essay, to confine our inquiry to Roman building construction in its most limited sense, not giving much attention to the great engineering works of the Romans in the shape of viaducts, bridges, etc., which they have left in so many parts of the world. Again, of the processes and methods of building construction adopted by the Roman, only those which are peculiarly characteristic need be referred to. The arch and vault were constructed both of stone and of brick and concrete; the round arch, the barrel and the domed vault being almost the only forms used. When of stone work, the arch stones, or "voussoirs," were carefully hewn to the proper form and built in alternate bands, thus economizing the centering. The old Roman baths at Nîmes (now called the Temple of Diana) offer a good example of this construction. Another form of stone barrel vaulting was constructed with stone ribs and slabs between, and is interesting as bearing a resemblance to what is found in some early Christian churches in Syria. It seems a little astonishing that the Romans with all their constructive skill avoided groining in their stone cross-vaults. Wherever squared stone vaulting met, the stone construction would be stopped, and the vault worked in brick and concrete. In sloping vaults, as the entrance passages to the amphitheatres, the arching was sometimes executed in stepped rings, each separate arch standing vertically and exerting no pressure upon the lower part of vault. The inside of the stones would in this construction be dressed off to the slope, probably after the stones were set in position. In the passages with converging sides the voussoirs were sometimes arranged with the line of keystone and the lines of springing stones of parallel widths, the filling-in stones being wedge-shaped on plan. At other times the side and key stones were wedge-shaped on plan, and the filling-in stones parallel. In the construction of the oblique arch, the abutments of the stone rings were at right angles to the faces of the rings, the stones being cut to the required obliquity. The brick and concrete vault is most characteristic of Roman construction, although it does not date further back than the time of Augustus. It is thought probable that this too came from the Hellenistic cities. Had the great Roman vaults been "cast" entirely of concrete, the timber centering would have shrunk during the execution of so extensive a work, and caused cracks in the concrete which might have led to an entire collapse. Viollet le Duc calculated that the centering for the dome over the Pantheon would have sunk about 20 inches in from three to six months if constructed over the whole area at once like an inverted basin. To avoid this, and to give elasticity to the whole covering, the Romans constructed light ribs of brick, and filled in between them with concrete. The brick ribs, unlike those in the Gothic periods, were not intended to be decorative features, and so were not permanently exposed. The concrete filling was economical, only easy, straightforward labor being necessary. I may also mention a building on the Palatine at Rome. Here the ribs are made up of cells formed by large flat bricks, 2 ft. square, and smaller bricks, 2 ft. by 6 in., their thickness being 2 in. The cellular construction was sometimes applied to the whole vault, as at the Palatine, and as here illustrated. The cells gave support to the concrete, both by adhesion and by their wedge shape. The concrete filling between the brick ribs appears to have been sometimes arched on the upper surface, but it is not easy to see how this could have added much to the strength of the vault. The great example of Roman barrel vaulting is that over the Basilica of Constantine, near the Colosseum at Rome, the span being no less than 80 ft. The cassettes here, as in the Pantheon and other examples, greatly reduced the weight of concrete while not causing any decrease of strength, for where the cassette is most deeply sunk an approximation to the form of an arch is formed, as shown by dotted lines on sketch. The wood moulds fastened to the centering before the concrete was filled in would greatly assist in securing the ribs in their position laterally. Exception

might perhaps be taken to the smaller sinkings in the face of the ribs, as in the Pantheon.

If the ribs were intended to be displayed, these sinkings would certainly be most objectionable, but the objection is at least answerable when we recognize that the principle of the Roman architects was not to display the parts of construction, but to construct a framework and apply a covering, thus following the principle of overlaying, which is observed to govern many styles of architecture. There is still another method of constructing the vault which was used by the Romans, namely, that by which the vault was formed by layers of tiles or flat bricks over the centering. The arching was reduced, as much as possible, by carrying up the wall considerably above the line of springing. This system has the advantage that skeleton centering would serve the purpose of supporting the tiles at their joints. This construction is still in use in Italy. In dealing with cross vaults the Romans preferred to have two barrel vaults of the same span, but they sometimes stilted one vault to have both crowns on a level. Ob-long vaults were occasionally used, but the square were preferred. The groins in cross vaulting of the brick and concrete construction were formed in a similar manner to the ribs already described; the lower edges of the bricks, however, had to be either specially moulded to the proper angle before the bricks were burnt, or cut to the exact line after being set in position. Where the groin ribs meet at the crown of vault, no attempt was made to make a finished junction or miter, one rib was carried over unbroken, and the other simply butted up against it on either side. The cross vaulting over the Theatre of Diocletian illustrates this. Domical vaulting was executed by the Romans in a very similar manner to the brick rib and concrete barrel vaulting. At the Pantheon the ribs are probably of brick, and carried up of the same width to the top, where they abut against the curb of the hypæthral opening. Viollet le Duc thus vividly describes this masterpiece of spherical vaulting: "What, in the Pantheon at Rome, is it that produces the most lively impression? It is that immense vault which derives all its decoration from its very structure; it is that single opening for light, 26 ft. in diameter, perforated in its summit, through which the zenith is seen, and which throws upon the pavement of porphyry and granite a large circle of light. It is there that the genius of the Roman appears in full strength. So great is the elevation of this orifice above the floor, that its enormous opening scarcely affects the internal temperature. The most violent storms scarcely send down a breath of air on the head of a person standing beneath its orbit; and when it rains, the drops are seen falling perpendicularly down upon the pavement of the Rotunda, on which they describe a circle of wet. The cylinder of rain drops, falling from that height through the space of the building, renders sensible the immensity of that space. It is in conceptions like this that the Roman is really grand, because they are the outcome of his own genius, and because for their execution he borrows from no one, nor asks the aid of any artist whose nature is foreign to his." The diameter of this building is 143 ft., the height from floor to top of dome is the same, and the springing of the vault is exactly half way up. The spaces between the ribs are filled in with concrete and cassetted or coffered, with four sinkings so arranged that a spectator in the center of floor sees all the margins of sinkings of equal width. A rosette of gilded bronze was originally placed in the center of each coffer, and bronze ornaments decorated the borders. An old writer states that he saw the manner of the construction of the dome during some repairs, and that there are series of arches. If this is the case, this outer system of arched reticulation must be regarded as an additional means of bracing the cupola. Nothing need be said of the portico, except that its roof was originally supported by bronze girders of the section of an inverted rectangular trough, which fact is interesting as pointing to the existence of so early an example of tubular metal girders. Professor Adler has described the scientific construction of this building, and points out that the cupola is really supported by eight pillars and strengthened by the upper buttresses, the remainder of wall being merely filling in between the constructive parts. Professor Adler's restoration of the upper story of the Pantheon is now generally acknowledged by authorities. Roman domes and vaults were not protected by outer roofs as in more modern examples, the interior only being considered by the architects.

III. MATERIALS AND WORKMANSHIP.

The ordinary mason's work of the Romans was not executed in large blocks of stone, as the smaller were more economically worked. It is true that large blocks of stone are found of Roman work in the temple at Jerusalem ("Opus Quadratum"), but they are evidently in imitation of the older work of Solomon's temple. Foundations and first courses are often of stone when the other parts of walls are of brick strengthened by timber. Two kinds of exterior facing to stone walls are mentioned by Vitruvius as commonly used by the Romans, "Reticulatum" (net-like) and "Incertum" (irregular). Vitruvius says that the former was the method in general use in his day, and the latter the ancient method. A limestone called travertine was much used in Rome; the Colosseum and other buildings being built of it. Travertine, Saxum Tiburtinum, is calcareous deposit found along the course of the Anio and Aqua Albula, by whose waters it is deposited, but most plentifully in the neighborhood of Tivoli, the ancient Tibur, whence its name is derived. When first taken from the rock it is soft and easily cut, but the longer it is exposed to the air the harder it becomes. This may be ascertained by comparing its state in the native rocks near Tivoli with the exterior walls of the Colosseum. For less exposed work, as the interior of walls, and where covered by plaster, soft tufa was used, and a hard volcanic substance called peperine, which could be exposed to the air with more freedom. Very many buildings in Rome are composed of it. Basalt was principally used in paving roads and streets; but it is also to be found employed in consolidating and packing other stones, as in the interior of the wall of Servius Tullius, etc. Pumice was only used to lighten a building, as in the vault of the Pantheon and in the Colosseum. Marble was imported for monolithic columns, and was much used in slabs for lining interiors of walls, etc. It was the boast of Augustus that he had found Rome brick and left it marble. The chief

supply of white marble was derived from Luna, called Marmor Lunense, and the same quarries are still worked, the marble being well known by its modern name of Carrara. The white marbles of Greece were also occasionally employed. Of colored marbles the most esteemed are the Rosso, Verde, and Giallo Antico, and Cipollino, Africano, and Pavonazetto. Roman bricks were of different forms and sizes; flat tile-like bricks were generally used, some found 2 ft. square and 2 in. thick, others 1½ ft. by 1 ft. and 1½ in. thick. A triangular form, for Opus latinum, was also used in facing. Vitruvius devotes a chapter to a description of bricks. About the time of Constantine a practice was introduced of using large jars of baked clay (testæ) to diminish the weight of a dome or the upper part of a wall. The Romans are famous for their mortar and cement, the excellence being due to the use of puzzolana earth, which was used along with the lime. The puzzolana is a volcanic substance, and very abundant in every part of the Campagna di Roma, and the extent to which it was used is shown by the vast caverns which form the Catacombs. The name puzzolana is said to be derived from the Pulvis Puteolana, which was a similar substance found near Puteoli, now Pozzuoli. Concrete was much used, as we have already seen in considering the processes and methods of construction. It was always covered with a facing of finer material. The method of laying concrete was by an even bed of mortar 6 in. to 8 in. thick first put down, and then the stones pressed into it while soft, until the desired solidity was attained. This process was, of course, only applicable where there was resistance to lateral pressure. Plaster work (intonacum) was brought to great perfection, particularly for coating the specus of aqueducts, the interior of piscine, and those walls of houses which were adorned by fresco painting. Metals were not much used. The bronze beams of the portico of the Pantheon have already been alluded to. The doors of this building were of the same material. Iron was used for clamps in stonework. Lead pipes for water service are supposed to have been used. Glass was sparingly used for lighting, and as early as the time of Agrippa was employed in mosaic work. Mosaic pavement was introduced into Rome in the time of Sylla, and was largely used. Tiles appear to have been the only covering made and used for roofs. Roman works were carried out by either, 1, paid labor; 2, forced labor; or, 3, soldier labor. The materials were obtained either, 1, bought; 2, taxed; or, 3, procured from the quarries, etc., by forced labor. The regular workman had considerable political power. Trade guilds were formed and recognized by most emperors, after it was found impossible to put them down. Immunities and privileges were granted on certain conditions, as that government works should be carried out at fixed rates, etc. Time will not now permit of further notice of workmanship, and so this paper must close with a word of admiration for the constructive and organizing genius of Roman architects.

THE CASINO AT SCHEVENINGEN, HOLLAND.

In the cut opposite, taken from the *Illustrirte Zeitung*, the new "Curhaus" or Casino at Scheveningen, on the North Sea, is shown. It was designed by Messrs. Hinkenhoff, Ebert, and M. A. Reis, the latter being the director and superintendent of the watering place at Scheveningen.

The building is constructed in the shape of an extended U, between the wings of which a platform about six feet above the dike and 426 feet wide is formed. The higher central part of the building is surmounted by a large dome, flanked at the corners by towers. On the land side a covered veranda is erected, which leads to the adjacent galleries containing the shops, etc. The facade facing the sea is also provided with verandas in which panes of glass are held movably, so that the openings in the veranda can be closed in stormy, rainy weather. The style of the building is Italian Renaissance combined with some of the elements of the Dutch Renaissance. The facades are erected in tufaceous limestone, and for the remaining parts yellowish-red bricks are used. A rich frieze of sgraffito is arranged under the cornice, and gives an elegant finish to the upper part of the building. The center and side wings are connected by a two story loggia, as is shown in the cut. The main hall, which is in the center of the building, is of sufficient size to hold 3,000 people. It has a rich ceiling of cathedral glass, and a mosaic floor. The dining room, reading rooms, card rooms, etc., are all richly decorated. The theater is in that part of the building facing inland. The building is also to be used as a hotel.

NEW WEST FRONT, ST. ALBAN'S ABBEY.

OUR sketch, taken on the spot, shows the design, line for line, as it has been executed. Sir Edmund Beckett has paid the cost, and he has been his own architect. Messrs. Longmire and Burge are the builders, and Mr. John Chapple is the clerk of the works. We give the drawing without comment, and each reader will judge for himself as to whether the design merits the confidence with which its author seems to view it, or deserves the sweeping strictures passed upon the composition by certain professional critics and some leading architects. The work, anyway, has been very well done, and the carving throughout is excellent. The following may be taken briefly as the concise history of this west front. The Norman buildings at this end of the church, by Abbot de Paul, were pulled down by Abbot John de Cella between 1195 and 1214. The rebuilding was completed by Abbot Wm. de Trumpington, from 1214 to 1235. The generally received idea is that there was a rose window in this west front then with tall lancet windows; but Neale, in his "Monograph," says that this supposition is not well supported. The three porches, we know, had high-pitched roofs, and above these porches were three tiers of arcading. Before the present works were commenced, the lowest sill of these arcadings remained in confirmation of this statement. Above the arcades were six lancet windows arranged in pairs, and inclosed by outer moulded arches, with shafts as on the north side of the nave arcade. The arcade, level with the clerestory, had windows alternating with these recessed arches corresponding with those on the exterior of the western bays of the north and south aisles of nave. Passages were continued around the west end of the nave, both at the triforia and clerestory levels. The west front