It is extremely easy to use a machine like this in the car of a balloon. When everything has been properly prepared before starting, there is nothing more to do but to plunge a small copper fork into the mercurial cups of the commutator in order to set the helix in motion. There is no fire to be feared, there is no change in weight that might cause the altitude of the aerial ship to vary, there is no manual labor for the operator. Nothing but electricity could have so well fulfilled these fundamental conditions of the aerostatic motor.—*G. Tissandier, in La Nature.*

EXPLORATION OF CAVES BY ELECTRICITY.

Among the numerous applications of electricity there is certainly none more curious than the one which we are now about to describe. Almost all grand spectacles of nature have, up to the present time, disappeared from view when night came on to cover them with her dark mantle; and the brightest moonshine has scarcely given sufficient light to allow such things to be admired. So, for some time back, it has been proposed to employ recent processes for giving

very beautiful effects, are too ephemeral, and the combustion of the chemicals composing the Bengal fire so vitiates a mass of air that is not often renewed as to render a long stay underground impossible. So, for making a prolonged excursion into the different parts of a cave, for examining its galleries and chambers, and for getting an exact plan of it, or for studying the constituent elements of its walls, none of the means employed in modern times has been found practical, or at least sufficient.

The installation shown in the annexed cut constitutes a progress of the most remarkable character. Thanks to electricity, the light penetrates everywhere, and the remotest depths, which were apparently destined to remain in an eternal night, suddenly become resplendent with light and unveil to the astonished visitor marvels that had scarcely been expected, and that were in some cases completely unknown.

Under a dome hung with curiously entangled stalactites, the rays from the regulators are so arranged as to pierce the darkness of the galleries and variously formed arches and give the fantastic place a strange brightness, the crystalliza-

A GROTTO LIGHTED BY ELECTRICITY.

certain picturesque places much frequented by travelers a new view by night, and certain effects that a view by day would scarcely have led them to expect.

After the numerous experiments that have been made nearly everywhere with a view to rendering certain sites accessible to visitors at night, it was but natural to think of illuminating by the electric light such of the more important grottoes as could not, even in broad day light, be entered without the use of an artificial light. Whoever has traversed the Pyrenees, Auvergne, and the volcanic regions of Italy, not to speak of more remote countries, where gigantic caves are met with, has certainly observed in his visits to these latter how defective are the processes used for illuminating them.

The primitive torch is the light that is most usually used, and the smoky glimmerings of this, as well as its asphyxiating exhalations, not only discommodate tourists, but also permit of but a very imperfect examination of the galleries or domes into which the excursion is made. In cases where more serious preparations have been made, Bengal or magnesium lights have, indeed, been employed; but such processes of lighting, although evidently capable of producing

tions on the walls taking on a surprising iridescent luster, and the damp stratum that covers the whole being transferred into a marvelous varnish. In the experiment shown in our engraving, the motive power necessary to actuate the dynamo machines that supply the regulators is derived from a water fall in the vicinity, and is transported electrically.—*La Lumière Electrique.*

At the British Association meeting a paper by Prof. J. A. Ewing was read, on the magnetic susceptibility and retentiveness of iron and steel. This paper was a preliminary notice of some results of an extended investigation which the author had been conducting for three years in Japan. Experiments with annealed rods and rings of soft iron wire showed that that material possesses the property of retentiveness in a very high degree. As much as 90 and even 93 per cent. of the induced magnetism survived the removal of the magnetizing force. The extraordinary spectacle was presented of pieces of soft iron entirely free from magnetic influence, nevertheless holding an amount of magnetism, per unit of volume, greatly exceeding what is ever held by permanent magnets of the best tempered steel.

ON SECONDARY BATTERIES AND THE ELECTRICAL STORAGE OF ENERGY.*

By Professor OLIVER LODGE, M.A., D.Sc.

LECTURE I.

THE ordinary methods of storing energy at present in use may be divided roughly into mechanical, chemical, and electrical. As an example of the first kind, we may take the raising of weights, which is accomplished on a large scale hydraulically, and is applied to the working of cranes and dock gates; another example is the coiling of springs, as in clocks and musical boxes. An example of a chemical storage of energy is gunpowder; another is zinc or other smelted metal; and a third example is vegetation, whence arises all the energy of coal and gas engines. The charging of a Leyden jar, and the decomposition of dilute acid, furnish examples of electrical storage, and the explosive gases derived from the last mentioned operation could doubtless be used to drive some form of gas-engine.

All these methods of storing energy involve some loss, and many of them are accompanied with a great deal of loss. The advantage of being able to store energy frequently outweighs the disadvantage of a considerable amount of loss of energy in the process; and there are three main cases in which this occurs.

One is when regularity and continuity of supply of energy is needed, and when the source of energy to be utilized is irregular and fitful. For instance, it would be convenient to be able to store wind or wave power, and utilize it in an equable and dependable manner.

Another case is when occasional power is needed at times when the source of energy is not acting, or when a very great power is required for a short time, whereas the source of energy at your command has a steady but insufficient power. This would be exemplified in the utilization of a small engine for lighting purposes.

The third case is when the power at your disposal is so great and so unutilized that the saving of even a fraction of it is a clear gain, no matter what becomes of the rest. This case frequently occurs when natural water-power is utilized. Processes of vegetation also utilize but a meager proportion of the solar radiation, but the small proportion saved and stored up in the coal fields represents so much clear gain.

The mode of electric storage which has recently excited so much interest involves the use of a secondary battery, which may be defined as an instrument for receiving the energy of an electric current, and for giving it out again in the same form. This is a case of storage without transmutation, such as is also accomplished in the simple operation of winding a clock, where mechanical energy is taken in, to be subsequently given out in the same form. But in the electro-chemical decomposition of acid, the energy of an electric current is stored in such a way as to give sound, and heat, and light, and motion, but not an electric current under ordinary circumstances. There is one arrangement for making the evolved gases directly furnish an electric current, and that is a true secondary battery, viz., Grove's gas battery, or a voltameter.

A primary battery means one in which the plates have been made, or prepared and rendered active, by chemical means; a secondary battery means one in which the activity of the plates depends upon electrical energy having been first expended upon them. Any two conducting bodies, immersed in a conducting liquid able to chemically attack one of them more than the other, constitutes a battery; and the difference in the attackability of the two bodies, or "plates," may be caused either by making them originally of different materials, or else by modifying their surfaces in some way, permitting the main bulk of them to remain identical.

Most run down batteries can be re-excited by forcing a reverse current through them, and they then become true secondary batteries.

The polarization of voltameter plates was studied by Gautherot, Ritter, and Grove in the earlier years of the century; and more recently and exhaustively by Plante, who found that plates of lead acted extremely well, and retained their energy for a long time.

The gas battery consists of two similar platinum plates, one soaked, or coated, or alloyed, with hydrogen, the other with oxygen. But the quantity of oxygen which platinum can store up is very minute; the advantage of using a metal actually oxidizable is manifest. Platinum, and still more palladium, have considerable holding power for hydrogen, but by the use of a salt or an oxide as a recipient of the hydrogen a far greater amount of reversible action can be stored up than by attempting to store up the hydrogen itself by any power of occlusion.

A Plante cell, from the beginning, furnishes an oxidizable plate on the positive side, but its negative plate has at first no practical occluding power for hydrogen.

Reversing a once charged Plante cell, however, we get metallic lead for the oxidizable plate, and an already oxidized, and therefore reducible, plate to receive the hydrogen; the oxide gradually being reduced to metallic lead, of a porous or spongy consistency. By many reversals of this kind, Plante "formed" his cells, until the lead plates were deeply acted on, and a considerable storage capacity obtained.

The modification of Faure consisted in providing both an oxidizable and reducible porous material from the very first by coating the plates with minium or litharge. The plates could then be peroxidized, and reduced respectively to a considerable depth, without any tedious process of "formation." A considerable storage capacity was thus obtained, but difficulties presented themselves connected with the adhesion of the coatings to the plates, and these were not got over until perforated plates were employed to hold the applied substances. Perforated plates, by rendering unnecessary any jacket of cloth or felt to keep the coating on, and by thus permitting a free circulation of the liquid, no doubt are a considerable improvement; and cells, as now made, often work extremely well; at the same time a layer of uniform thickness spread all over the plate, and not locally distributed in a non-homogeneous manner, would seem theoretically to be preferable, if the practical difficulties connected with such a uniformly spread layer had not seemed too great. Plates made in the old manner did not safely bear transport and rough usage, and a film of insulating sulphate of lead was apt sometimes to creep between the metallic lead and the peroxide coating, and to destroy all electrical connection between them over large patches.

The process of manufacture, as now carried on, is here illustrated by a number of specimens of plates in different stages, kindly lent for the purpose by the Electrical Power Company, of Millwall.

The first operation is the casting of the lead grid, the holes in the plate being from $\frac{1}{4}$ in. to $\frac{3}{8}$ in. square. The

* Two lectures delivered before the Society of Arts, London, May, 1883.

positive grid is made a little thicker than that which is to be the negative, for reasons which will shortly appear. The thickness of the grids at present most employed are, positive $\frac{1}{8}$ in. to $\frac{1}{4}$ in.; negative $\frac{1}{8}$ in. to $\frac{1}{4}$ in.; and they are made in two sizes, one $7\frac{1}{2}$ in. by $5\frac{1}{4}$ in., the other 9 in. by 10 in.; the former being used in the small or "half horse-power" boxes, the larger plate being used in all other sizes, it being found more convenient to vary the number of plates in a cell than to have in stock a number of different sized plates. The weights of the formed plates are, small size negative, 15 oz.; small size positive, 21 oz.; large size negative, 50 oz.; large size positive, 70 oz., about.

The next operation is the filling of the grids with a paste of oxide of lead mixed with dilute sulphuric acid. The negative plates are filled with litharge, PbO , the positive with minium, Pb_3O_4 , since there is an evident economy in having to reduce only the lower oxide, and to peroxidize only the higher one.

The plates are then taken to be "formed" by the electric current, for which purpose they are packed alternately in square stoneware jars filled up with dilute sulphuric acid, and a current of about two or three amperes per pair of plates supplied. At the first instant of immersion in acid, a darkening of the minium occurred, owing to a partial formation of peroxide in it by the action of the acid; and this darkening continues, under the influence of the nascent oxygen liberated by the current, until the whole of the composition is converted into peroxide. The litharge is, on the other hand, gradually reduced to metallic lead by the action of the nascent hydrogen produced by the current, the reduced lead having a slightly porous or spongy consistency.

No gas is evolved from the cells for some time; it is all consumed in effecting these chemical changes. A few minute oxygen bubbles do, however, make their appearance on the positive plate, much of it being in the form of ozone. Ultimately, as the surface of the positive plate gets peroxidized over, a good deal of oxygen escapes, and it is only after a long-continued current that the portions of minium in the interior get acted upon. In time, all the minium is attacked, however deeply buried; the reason being that less E.M.F. is needed to send the current to an oxidizable substance than to saturated peroxide.

The reduction of the litharge is a somewhat slower process, but, the plates being thinner, it is accomplished in approximately the same time, which may be taken as between three days and a week. When the process is approaching completion, torrents of both kinds of gas rise from their respective plates. The plates are then removed from the forming pot, rinsed plentifully with water to remove the excess of acid, and then stacked till wanted. Unless the rinsing operation is carried out, the spongy lead plates are found to heat considerably, by reason of the acid in their pores combining with the lead.

In order to keep the plates from touching each other when subsequently used in battery cells, various devices have been tried. The one now most in favor is to punch out the composition from a tolerable number of the holes of each negative plate, and to insert instead a block of vulcanized India-rubber in each. These plugs project nearly a quarter of an inch on either side the face of the plate, and effectually prevent the adjacent positive from coming into contact with it.

Another matter which has given some trouble to determine is the best method of connecting the plates together. All the positive and all the negative plates in a cell have to be electrically connected in the most complete and permanent manner. Clips and clamps of various kinds have been tried; but, to guard against all possibility of corroded surfaces and imperfect connection, it is now thought wise always to use solder, whether in combination with screw clamps, or otherwise, and to protect the joint from the action of acid spray by a varnish, or by a mass of paraffin. It is curious to notice how persistently the junctions of the + plates tend to corrode, showing how the oxidizing action creeps up liquid films on the lugs.

When the plates are to be used, they are packed alternately in glass or ebonite boxes, the India rubber plugs keeping them apart, and wooden supports keeping them off the bottom of the cell. Their lugs are connected together, and the box is filled with dilute sulphuric acid, say, of specific gravity 1.100 or 1.150. A charging current is then supplied, so as to freshen up the plates, and they are then discharged, and charged up again once or twice, to bring them into good condition. It is not a good plan to discharge them too completely, nor to let them remain idle for very long together; neither should they be charged or discharged too rapidly, so as to heat them above a gentle warmth. The more regularly they are worked—as, for instance, when they receive a charge every day and discharge every evening—the better they behave. Regularly and carefully worked cells will keep in good order for a very long time; but if they remain idle for weeks together, some of the plates are apt to warp, and otherwise give trouble and require attention. They must not be over-charged very excessively either. When full, they indicate the fact by evolving a good deal of gas, and it is best not to continue the charging power much longer when this stage is fully reached, partly because nearly all the charge then put in is wasted, but principally because a little of the oxygen is absorbed by the lead of the grid, and it therefore gets slowly peroxidized, so that, after a sufficient lapse of time, it may get actually eaten through, and the plate become friable. When a plate has got into this state, the only plan seems to be to melt it down with a flux, and recover the lead. But the complete peroxidation of a plate by overcharging is a work of time, by far the greater quantity of gas being harmlessly, though wastefully, set free; and it is not necessary to be alarmed at a slight evolution of gas which usually goes on from the positive plate when being charged, more especially as the cell is getting full. Alarm at the appearance of bubbles may lead to the cell never being properly filled up, in which case the battery will fail to work satisfactorily.

The number of plates which are packed into each box depends entirely upon the size of the box, and it is in this way that the different sized cells are constructed, not by varying the size of the plates; except that the smallest cells are made with half-sized plates.

Taking the full-sized plates, we may reckon that each pair is able easily to receive and give out electricity at the rate of 4 amperes per pair. This of course reckons both faces of each plate as active. This process may be continued for, say, 8 hours on the average, consequently the storage capacity of a cell is 32 ampere hours per pair of plates. The E.M.F. of discharge is as nearly as possible 2 volts; consequently the power of a cell is 8 watts per pair of plates; and the total available energy per pair of plates, when full, is 8 watts for 8 hours, or 170,000 foot-pounds; which may be also, though clumsily, expressed as one-twelfth of a horse-power-

hour per pair of plates. Consequently, a box which is to give 1 horse-power-hour should contain 12 pair of plates; a 2 horse-power box 24 pair, and so on. But each box will not really give a horse-power for an hour, it will rather give an eighth of a horse-power for 8 hours. If a horse-power is wanted, all you need do is to take 8 cells, and then they will give you a horse-power and will last 8 hours; 16 cells will give 2 horse-power for the same time, and so on. By drawing off the power more slowly, the discharge will last longer, and it is more economical thus to work, except as regards first cost of batteries. This latter item it is which usually causes them to be called upon to exert power up to their maximum reasonable capacity. It is true that a cell will give a much higher power for a short time if called upon—thus a single cell might possibly be made to give a horse-power, but then it would not last out its proportionate time. I have found some cells, which I discharged at a very moderate rate, continue discharging an extraordinary time, and give out sometimes even more than was put in, which of course means that the effect of previous charges was being drawn upon.

When a cell which is being rapidly discharged has apparently run completely down a few minutes' rest will suffice to recover it a little; and after an hour or two's rest a cell will commonly have recovered sufficiently to enable it to discharge with something of its old vigor for a period comparable with that of the rest. This recuperative power of the cells is in some respects advantageous, but, on the whole, it would be better if they gave out the whole of their energy continuously without needing intervals for refreshment. The more slowly a cell is discharged, the less noticeable is this temporary falling off and subsequent recovery.

When a cell has run down, it is interesting to examine which of its three constituents is the one that has failed; the positive plate, the negative plate, or the acid. Sometimes, especially in cells too crowded with plates, there is not enough acid present; the free acid is absorbed by the lead, and only water is left. The specific gravity of the acid may however be easily watched by floating a little hydrometer in the cell. More frequently the negative plate is the first to fall off; as may be shown by removing it and inserting a fresh one, when the cell will go on again. The cause of this, and of several other peculiarities observed in batteries, may be readily made out by experiments on a small scale, on two little plain lead strips, held in a convenient clamp, and immersed in dilute acid.

To a pair of such strips of sheet lead supply a current, from a couple of Groves, say, for half an hour or so. The positive plate is seen to become coated with a puce layer which gradually darkens to black. The other plate seems unchanged. Gas is evolved from both plates. On now connecting them with an electric bell, it will ring for a minute or more. Now recharge, but this time, instead of discharging the cell, remove the negative plate, and insert instead a bit of clean lead, the same in appearance as the one against which hydrogen has been so long liberated, and then discharge the cell; it will only ring the bell for about two seconds. Depress the plain lead plate further into the acid, so as to expose a fresh surface, and the bell will give a few more strokes. Remove this plate altogether, and reinsert the hydrogenized plate which had been used for charging the cell, and the bell rings vigorously for as long a time as it did in the first experiment, showing that the peroxide plate is perfectly vigorous, and showing also that the nascent hydrogen has modified the lead in some way or other.

The natural supposition is that the lead has occluded hydrogen, but Dr. Frankland has shown that, if such hydrogenized lead be melted down, it gives off no hydrogen worth mentioning. It is not easy to see wherein the change consists. Under the microscope, the hydrogenized plate looks a little darker than the plain plate, but no real porosity is noticeable. The fact, however, is certain, that it behaves in a very different manner to plain lead, and that it retains this singular power long after it has been removed from the liquid and rinsed.

To avoid misunderstanding, it might have been well to state earlier that I use the term "positive plate" to signify that at which the charging current enters, and from which the discharge current leaves. It is that one whose terminal is colored red in the cells of commerce. It is that which must be joined to the + pole of a magneto-machine, whether the latter is to act as a generator or a motor. I make no distinction between positive plate and positive pole, because all such distinctions end in confusion.

The plain lead plate, which refused to give a current when opposed to peroxide, did not fail because of its high position in the electro-chemical series, as may be proved by opposing it to the hydrogenized plate, when it is equally inert; it fails simply and solely on account of a film of some non-conducting substance which spreads over its surface the instant it is used as one electrode of a battery, the substance appearing to be sulphate of lead. The internal resistance of the cell thus becomes enormous, and the current ceases. On standing idle for a time, the film has a chance of clearing off—though from a plain lead plate I do not notice much tendency to clear—or it may be wiped off with a cloth at once; but a fresh film speedily forms. If amalgamated lead be used, the white scum can be seen, and it sometimes drops off in a filmy sheet. One remarkable way of instantly clearing off the scum is to touch the lead under the liquid with a scrap of amalgamated zinc. The effect is magical; the scum vanishes, and the bell again rings for several seconds after the zinc has been removed. So long as the zinc is present the current will continue, until indeed the positive plate becomes exhausted.

To examine whether the positive plate also exhibits the temporary falling off, and to eliminate the concurrent action of the negative, the best plan is to use a piece of amalgamated zinc for the latter; for since sulphate of zinc is soluble, it remains perfectly clear, and all variation is traceable at once to the behavior of the positive. Under these circumstances, the cell, if rapidly discharged, does show a slight recuperative power, recovering somewhat on standing. So far as I can make out, this appears to be mainly due to a temporary exhaustion of the acid close to the surface and in the pores of the peroxide, so that the power falls until, by rapid diffusion, the absorbed acid has been replenished. The insulating scum of sulphate on the negative plate is, however, by far the most powerful cause of the ordinary running down of a cell.

When we come to try the hydrogenized plate employed in charging the cell, instead of the plain plate, we find that it also ceases to act before the positive is exhausted, though it is able to go on for a considerable time; it ultimately acquires a scum. On standing, the scum clears off partially, and the cell recovers. A piece of zinc made to touch the plate under the liquid clears it, and in a short time restores it to its original power, having precisely the same effect as a reapplication of the charging current. The fact is not sur-

prising, since the zinc naturally causes nascent hydrogen to be liberated on the plate, just the same as a current would; but the quick and prompt action of the merest scrap of zinc is somewhat striking, and some practical application of the fact would seem to be possible.

Instead of a plain lead plate, lead sponge may be employed for the negative plate, such as is made by Watt, of Liverpool, by blowing high pressure steam through a jet of molten lead; or such as Mr. Desmond Fitzgerald has brought me here, made in some other way. The enormous surface of this spongy lead enables it to go on acting for a much longer time than plain lead, without being stopped appreciably by a scum. This effect is due to the extent of surface, and it appears to be owing to a sort of potential hydrogenation caused by the ability of acid to attack spongy lead, or any metal in a fine state of division, more easily than when massive; and the sulphate of lead formed, though it certainly clogs up the pores, is not readily able to form a continuous protecting film.

A thin coat of peroxide formed on a lead plate rapidly becomes lighter in color when the current is stopped, being evidently reduced to a lower oxide by local action with the lead underneath. When the coat is very thin, the changes go on so rapidly that, by quickly pressing the charging battery key down and up, flashes of peroxide appear and disappear on the surface. It is by this local action effect, no doubt, that peroxidation eats deeper and deeper into metallic lead, for otherwise, as soon as a complete layer of peroxide was once formed, all subsequent gas would be given off from its surface (it being a conductor), and the lead beneath would be protected.

The local action proclivity between lead and peroxide has two unpleasant consequences, however; one is that the peroxide gradually disappears on long standing, and the cell thus loses its charge; the other is that the metallic lead of the plate gets gradually eaten into and corroded away. These two results are modified in practice by the fact that, whereas local action destroys the peroxidation of thin films in an instant, in the deeper layers of thick films it goes on very slowly, partly because fresh acid cannot so easily penetrate, but principally because the sulphate and lower oxides formed, being non-conductors, exert a clogging and protective action.

Instead of using a lead negative plate, a copper plate may be used and will give a strong and lasting current. It lasts, of course, because copper sulphate is soluble, and no insulating scum is formed; but that this Sutton cell has a fairly high E.M.F. is a striking proof of the value of peroxide of lead as the electro-negative element of a battery.

Even platinum gives a current when opposed to peroxide of lead, though of course it is a feeble one. But if zinc is used, we have the strongest practicable battery I know, each cell having an E.M.F. of $2\frac{1}{2}$ volts.

LECTURE II.

I must now say a few words about the methods and instruments for practically measuring the various quantities involved in the storage of energy by secondary batteries. We need current or ampere-meters, potential or volt-meters, quantity or coulomb-meters, and energy or erg-meters. The well-known dead-beat am-meters and volt-meters of Professors Ayrton and Perry are exceedingly convenient instruments, especially the former; the only objection to them is the frequent calibration they require, because their permanent magnet changes in strength. Where portability is not essential, I find a high resistance galvanometer, of the form known on the Continent as the "Wiedemann," a most accurate and convenient volt-meter. The needle has a thick copper damper, which makes it almost dead beat, and a resistance of 30,000 ohms or so has to be added to the circuit in order to bring the deflection given by one cell within moderate range. It thus taps off an absolutely infinitesimal fraction of the current.

The deflections are immediately interpreted by observing, at the same time, the reading produced by a couple of common Daniell cells in series, each of these being assumed to be 1.12 volts. There is a trifle of uncertainty about the absolute E.M.F. of even a freshly set up Daniell, and this uncertainty will continue until an authoritative standard of E.M.F. is issued by the British Association Standards Committee; but in variations in E.M.F., one-thousandth part of the whole can be readily detected; and a sensitive volta-meter is somewhat important, if fouling cells are to be detected in their early stages, and before the cell is seriously injured.

As a meter for the quantity of electricity supplied or withdrawn to the cells, I use a large copper drum, suspended in sulphate of copper on the end of a balance arm, in such a way that it can be weighed at any moment without withdrawing it from the solution. Contact is easily made with it by means of mercury, and it is surrounded with a larger cylinder of copper, to act as the other pole. Allowing for the buoyancy of the solution in which it is weighed, every gramme increase or diminution of the drum means 1.04 ampere-hours put into or taken out of the cells. Frequent weighings of the drum enable one to get a very good idea of the cells as regards charge, and they keep an accurate record of the loss, or discrepancy between the charge and discharge quantity.

A copper drum coulomb-meter may also be made floating, so as to indicate by its height the quantity of electricity which has passed through. If such a vertical-moving quantity indicator carries a sheet of sensitized paper, on which the horizontal moving spot of light from a volt-meter records a trace, the arrangement will give an indicator diagram of the charge and discharge precisely analogous to the indicator diagram for the steam engine, except that the area enclosed by the curve represents the loss of work instead of the balance of useful work. The useful work is indicated by the area between the discharge curve and the two straight lines of reference.

Many plans can be devised for combining the two traces, the quantity and the E.M.F., at right angles to one another and the continued use of some such instrument would, I believe, assist in detecting the peculiarities of cells, and in improving their manufacture and system of treatment, almost to the same extent as the indicator throws light on the peculiarities of different steam-engines. But even without such an instrument for automatically constructing the diagrams, a curve plotted in this way (with quantity for abscissa and E.M.F. for ordinate) is the readiest mode of exhibiting the results of measurement taken with ordinary meters, and making the value of the cell manifest at a glance.

A highly ingenious quantity-meter has been devised by Dr. Hopkinson, and since it indicates precisely like a gas-meter, it is easily intelligible, and may come into general use. But at the present, I believe, it only works one way, hence it is not so directly applicable to secondary batteries; it would add up both charge and discharge in one continuous record, drawing no distinction between them. The sim-

plest power or watt-meter is the Siemens dynamometer, arranged with one series and one shunt-coil; and it indicates at any instant the power which is being supplied or withdrawn from the cells.

An erg-meter, or energy-integrator, can be made in various forms. The one I have here to show is Ayrton and Perry's modification of an eight-day clock. They substitute a fine coil of wire for the bob of the pendulum, and surround this with another larger and thick coil. A current sent in the same direction round two nearly concentric coils, causes the smaller one to move to the center of the large one. Thus, if the pendulum is oscillating, and the clock keeping good time, a current sent round the two coils will cause the clock either to gain or lose, according as the currents are opposed or agree in direction. If the two coils are both in series in the circuit, the gain or loss of the clock will indicate the coulombs passed through. But if the small fine coil is a shunt, while the other is a series, the force acting on the bob will be a function of the power, and the gain or loss of the clock will indicate the energy in some more or less arbitrary way, which can be made simple proportion by empirically adjusting the relations among the parts.

To determine the internal resistance of a battery cell, or of a whole battery, the plan is to measure its electromotive force when driving two different strengths of current, as different as possible and both known. One strength of current is most conveniently zero; the other must be measured, say, by an am-meter in the circuit. A volt-meter, such as the high resistance Wiedemann, is connected to the terminals of the battery, and read. Its indication will be a scrap higher if the current was being supplied by the cells, but lower if the current was being supplied to them. The difference of the indication of the volt-meter, when a current is passing, and when no current is passing, is proportioned to the resistance of the battery, and for a secondary battery cell in good order, the difference is surprisingly small, so much so that an ordinary volt-meter will often fail to detect it. To get the resistance of the battery in ohms, you must divide the difference in the readings of the volt-meter (interpreted into volts) by the strength of the current passing in the main circuit, reckoned in amperes. A moment's interruption is sufficient with a good dead-beat volt-meter, and the current may be immediately switched on again before the disturbance in the circuit has had time to show itself, except indeed where the current is being used for lighting purposes, in which case no tricks may be played unless there are several batteries in multiple arc, and one of them can be disconnected without detriment. This, indeed, is a good plan of connecting batteries, as it allows measurements, examinations, and repairs to go on while the current is being used. The resistance of one of the small sized (half horse-power-hour) cells with nine pair of plates averages 0.002 ohm. Large cells have a still lower resistance, of course, and it is to this extremely low internal resistance that the secondary battery owes much of its great practical value. The current from an ordinary Grove's battery is by no means proportionate to the external resistance of the circuit unless this is high; in other words, the driving power of a cell, or the difference of potential between its terminals, falls off greatly when strong currents are demanded. But a secondary battery, from its enormous area of surface, not only gives a higher E.M.F. than a Grove ever does, but it keeps this two volts difference of potential between its terminals for pretty nearly any reasonable strength of current. Hence the current does within wide limits vary with the external resistance, and the current which such a cell will drive through a piece of thick copper wire is simply tremendous.

I must now say a few words about the uses to which secondary batteries can be applied; and, first of all, for general laboratory purposes they are invaluable. A small gas-engine and shunt-dynamo are necessary to charge them up occasionally, but they then retain their charge for days or weeks, according to the demand made upon them, and they are ready at any moment to produce a current, strong or weak, according to wish. They thus save a deal of trouble in setting up Grove batteries, and, moreover, the current they give is much steadier, for unless they are run to near their falling-off point, their E.M.F. continues very constant, and no compunction is felt at leaving them connected up to the circuit for a long time together—for such a time as would make Grove-cells heat violently and boil over. When they are run down, a few days' charging replenishes them again.

As regards durability, the cells repay cleanliness and attention. I mount them in front of a window, on a slab of thick glass raised above the bench; one can then see all over and through them, the light being reflected from below the glass slab by an inclined bit of looking-glass which can be moved about. It ought also to be possible to get on both sides of the bench, so as to be able to detect and remove any attempt at contact between the plates of a cell.

If a lump of composition tumble out and bridge across from one plate to the next, it can be removed with a paper-knife. Plenty of light, easy access, and clear vision through between the plates of each cell are highly desirable. The glass cells and the slab should also be kept clean, and free from acid splashes and spray, for all this moisture promotes leakage, and causes the cells to lose their charge more rapidly than they would by ordinary and unavoidable local action.

When cells are stowed away in dirty dark cellars, on wooden shelves, like wine bottles, the leakage must often be considerable, and the cells may get into any state of dilapidation without detection, or attempt at remedy. A light attic, or glass house, with crockery slabs at a convenient height, is a much more suitable place for secondary batteries than a wine cellar.

It is important to be able to detect an incipient flaw in a cell before it has had time to damage the cell perceptibly. A sensitive volt-meter may do this, but an ordinary one will not show any difference for a long time, and if the cell is in series with others, as soon as it begins to run down in E.M.F. the others rush it down to, and past zero, and begin to charge it up wrong way. This reversal is very bad for a cell, besides its very weakening effect upon the main current. It is very important to keep all the cells of a series as exactly alike as possible. A bad short circuit often causes a hissing noise which can be heard with a stethoscope applied to the cell, even when it is not loud enough to call your attention, as it sometimes is. But the most delicate detector of an incipient short circuit is the thermometer. All the cells heat by their proper current, but any abnormal action going on in a cell, whether it be short current or local action, or any other dissipation of energy, must result in heat, and the thermometer is the natural detector of this. Any cell warmer than the others should be examined, and set right, or else replaced.

The lugs and contacts should be wiped clean occasionally

from the acid spray which collects on them, and they may also be recoated with paraffin and shellac. This acid spray is thrown up by the bubbles of gas which rise when the cell is getting full. The hydrogen bubbles throw up largish globules, which bound two or three inches into the air, and fall all over the slab and terminals; but when hydrogen comes off freely, the cell is commonly quite full. The oxygen, which comes off slightly during the greater part of the charging, throws up much more minute globules, which float about as an acid spray, very irritating to the nostrils and very provocative of leakage. The spray may be greatly diminished by a layer of oil spread over the surface, in which the bubbles collect and break in a different way, and it also checks evaporation; but the oil introduces difficulties of its own when the plates have to be lifted out of the cell, though indeed it may be first flooded off. The contacts of the positive plates are very apt to be corroded by the spray and creeping film, together with the peroxidizing action of the current crawling up wet lugs, and they require occasional attention. Unless absolute uniformity of contact is secured, some of the plates will take nearly all the current and get peroxidized to pieces, while the others are nearly idle.

I use pans of very dilute ammonia, or perforated boxes of carbonate, to neutralize the acid spray. The atmosphere is then much improved, and instead of acid films, white crusts of ammonia sulphate collect, which are less harmful, and may be cleared off. Another precaution is always to keep the cells filled with acid above the level of the plates, so that they are completely immersed, else the part above the liquid will be exposed to the influence of non-concentrated acid, from the evaporation of the water out of the acid film covering it. It is important to remember that all these exposed layers of acid are likely to become pretty concentrated, and hence that they may be expected to corrode more rapidly than the mass of the solution.

Another advisable precaution is to stir or agitate the liquid occasionally, more particularly during charging. The bubbles of gas, fortunately, do this to some extent, if the cells are well filled up electrically; but if no such agitation is excited the acid at the bottom of the cell is apt to become very much more concentrated than that at the top. Not that gravity is able to pull down strong acid out of once thoroughly mixed dilute acid. Gravity cannot undo diffusion like this. But it is the acid freshly formed during recharging, by decomposition of the sulphate of lead on both plates—it is this acid which falls to the bottom and accumulates there, frequently corroding the bottoms of the plates.

One great advantage of the present cells over the old flannel-swathed Faure, is that they permit free circulation of the liquid. To make the cells answer various laboratory requirements, I have a sort of resistance-box, made with uncovered spirals of German silver wire, in a stoneware water trough, so that the wires do not melt, and I can then throw in any resistance from a quarter ohm upward, otherwise the current would be frequently too strong. For working a Serrin lamp no extra resistance is necessary, and from eighteen to twenty-two cells work it admirably. Even when one drives the lamp direct from the dynamo, the battery is still connected as a shunt circuit, to act as a regulator and steady the current. Moreover, it has the great advantage of preventing the engine from racing away when one puts out the lamp. A well governed engine, of course, ought not to do this in any case, but I have not found a gas engine behave well when work is thrown on and off it in such an irregular and fitful manner as a lamp is commonly used in a lecture. It is much better for it to be pumping into the cells whenever the lamp is put out. Moreover, one can get a far more powerful current through the lamp in this way than from a small dynamo direct. Another advantage of having the battery connected is, that it will not permit the locking of the carbons, and thus the short circuiting of the field magnets of the shunt dynamo, which is a not infrequent occurrence when a shunt dynamo alone is used to feed an arc lamp.

If, however, only a regulator is wanted, and not a store of energy, a set of zinc and lead plates can be easily arranged which will do all that is wanted in the way of regulation; and as the lead gets gradually more and more "formed," the battery will gradually acquire more and more actual storage capacity. The cells were very useful once when the gas-engine was being repaired. I took the dynamo over to a neighboring steam engine, and laid its comparatively full current with spans of common wire to the battery. From the battery thus charged, the powerful occasional currents needed for some magnetic researches then going on were readily obtained. To bring such currents from the distant dynamo would have necessitated the use of very thick and expensive cable, and would in fact have seriously damaged its armature.

The battery thus acted as a transmuter of weak currents into strong ones, and this illustrates on a small scale one of its very important future functions, viz., a receiver of energy transmitted from a distance, as Sir Wm. Thomson has pointed out. Currents generated at a distant station, to be conveyed to a distance, ought not to be strong; they ought to be feeble currents at a high potential. They can be received by a great number of batteries in series, and the batteries so charged can be used for any local purposes, and made to give any reasonable desired current by altering their connections. Moreover, they can be coupled up to a number of independent circuits, so that irregularities in one shall not interfere with the others. The great advantage of a set of batteries as a receiver, over a set of dynamos in series, is that the latter would need such a high internal resistance to give the necessary back E.M.F., whereas a battery, even of small cells, can give 1,000 volts E.M.F. with an internal resistance of only 2 ohms. Hence the waste in heating the receiver is next to nothing. There is another kind of waste, no doubt, for the work got out of a battery can never be anything like that put in. The E.M.F. of charge is about 2.3 or even 2.4 volts, while that of discharge is scarcely above 2; besides this, there is a slight loss or discrepancy between the quantity supplied and that afterward withdrawn. Notwithstanding this waste, they must come into use when made in a satisfactory and quite dependable manner, for their great convenience and steadiness. And when the power at the distant station is water or wind-power, as I doubt not it often will be, waste becomes of secondary importance, and a convenient method of storing is the first consideration.

So plainly is high E.M.F. pointed at as the requisite for the economical transmission of energy, that I cannot help thinking that, in some cases, a use will be found for electrostatic machines as generators instead of dynamos. Not exactly a Holtz machine—which has a high internal resistance, and must dissipate energy, from its use of non-conductors and sparking intervals—but some gigantic form of Thompson's replenisher with metallic contacts. A large

machine is needed to give a current of one ampere, but not outrageously large, and a clear separation of the parts by a millimeter will enable 4,000 volts E.M.F. to be obtained. No great horse-powers are here represented, but it would be transmitted by a well insulated wire with very small loss.

In using a waterfall running continuously to light a town for, say, eight hours, batteries are evidently desirable. Three sets might be used, each charging for eight hours—one or other of them always charging, and two of them discharging during the eight hours the light is required. Or two sets would be sufficient if the water-power itself could be used for lighting direct. But the use of three sets of batteries would enable a reasonably distant waterfall to be used, and would, for the eight hours the light is needed, give an actually greater horse-power than the fall itself possesses.

For locomotion in cases where the current cannot easily be supplied to the moving carriage by metallic conduction, as in tram-cars on common streets, batteries carried by the tram-car afford an obvious, and, moreover, an economical form of motive power. It is sincerely to be hoped that electric tram-cars may speedily come to perfection, and that the excessive wear and tear of horseflesh in this monotonous and severe labor may be checked.

A number of motors were exhibited, some lent by the Electrical Power Storage Company, and some by Professors Ayrton and Perry. A De Meritens motor, driven by 18 storage cells, was used to drive a small Siemens dynamo by a strap, the current from this being used to drive another motor, which worked a lathe, or was used to light four small Swan lamps. A Pilsen arc-lamp was shown, working very steadily with the current from the battery, and a number of Swan lamps were also excited, so as to show how entirely any one was unaffected by the turning out of the others, a battery behaving in this respect like a very good compound wound dynamo. Diagrams of the mode of connecting up cells and dynamos for transmission or power and curves representing the charge and discharge of cells, as tested by Dr. Hopkinson and Messrs. Ayrton and Perry, were also exhibited, but it is thought unnecessary to reproduce them here.]

For driving boats electrically, secondary batteries are obviously necessary, because the laying on of a current by a wire is not only inconvenient but impossible. The storage cells will act as ballast, and can be charged while the boat is moored. For swift short voyages, and for pleasure vessels, nothing better than electrical propulsion is likely to be devised. For long voyages and big ships, the weight of secondary batteries would need all the floating power the ship possesses, and perhaps more. The energy consumed in propelling the present Atlantic liners is something almost incredible.

When motors are driven by secondary batteries with very short connecting wire, the question arises, Is high E.M.F. still desirable, as it is when transmission across great distances is concerned, or may powerful currents be now used with advantage? The answer is that, neglecting the resistance of battery and connecting wires, there is neither gain nor loss in using powerful currents, provided the dynamo is properly wound, and has brushes that will not burn up.

But if we do not neglect the resistance of the batteries—a thing we have no right whatever to do—the answer is, that high E.M.F. is of very great advantage. A large number of cells in series, driving a high E.M.F. dynamo at its highest possible speed, and with as small a current as is needed for the power, is by far the most economical arrangement. Now, a screw for a ship has always needed a high speed for economy, and in the old days gearing used to be employed between the steam-engine and the screw, because no high speed engine was sufficiently economical. I understand that slow engines are still the best, but the disadvantages of gearing are so great that high-speed direct-acting engines are always used. But a high speed is absolutely essential to economy in an electric motor, and no screw, as ordinarily made, would work at such a speed; consequently there is a temptation to use gearing the other way, and to gear down the dynamo to suit the screw. I hope the attempt will be resisted, and high-speed screws made of small size, smooth surfaces, and low pitch, so that the electric motor axle may be coupled direct to the screw shaft. The direct rotatory action of a dynamo used as a motor, as opposed to the oscillating action of a steam-engine, is a great simplifier of mechanism, and will be found extremely convenient.

For all kinds of short transit locomotion, electric power will, probably, prove to be the most suitable, and the improvement in the atmosphere of the Underground Railway, which would result from the adoption of such a means of propulsion, would be far more remarkable than anything which ventilators, whether ornamental or the contrary, are able to effect. In fact, there can be little doubt that the practical development of electrical appliances in the near future will be something extraordinary, and the consequence of this, and of the extensive use of gaseous fuel, will be, I most sincerely hope, and not unreasonably believe, not only the abatement, but the compulsory abolition, of smoke and all other artificial pollution of the atmosphere, and such an improvement in the air of towns as will change them from stifling purgatories into wholesome and refreshing centers of life and work.

THE MOST SENSITIVE GALVANOSCOPE.

By Prof. ERNST VON FLEISCHL.

THE most sensitive galvanoscope is the nerve of a frog. Its superiority over other galvanoscopes depends not so much upon its power of indicating traces of electricity as such, but rather upon its power of showing fluctuations in the strength of currents even of the feeblest intensity, if only they take place with sufficient rapidity.

As the readers of this memoir cannot be supposed to be possessed of a knowledge of anatomical and physiological details, we must first give a description of the position, of the appearance, and the general properties of the nerves and muscles of the frog. The reason why frogs are selected for these experiments is that they are easily procured in our districts; that their tissues, after the death of the frog, retain for some hours their vital properties in a degree not sensibly diminished, and lastly, that a nerve has its course in the hinder extremities of these animals, which possesses suitable dimensions for the experiment, and which is easy to prepare.

Near the lower end of the backbone of these animals the roots of the nerves for the lower extremities issue from two series of apertures in the form of fine white threads. These, after forming a plexus, unite to a thicker cylindrical stem of 1 millimeter in diameter, from which branches are given off in the shape of fine threads. These, under the microscope, appear formed of a number of extremely fine parallel fibers, each from 0.03 to 0.001 millimeter in diameter.