sum measured on the wings, so that the algebraic sum of all the horizontal components acting upon the entire bird (body and wings) should be zero. It follows from this condition that the sum of the horizontal components affecting the wings alone must act in the opposite direction to the horizontal component of the wind velocity.

I have shown that, in order to explain soaring flight, the absolute necessity of admitting that the motionless wings of the bird are acted upon by a horizontal force contrary to the direction of the wind (reckoned horizontally) proves that the direction of the wind cannot be horizontal, but that it must have an ascending tendency.

I further stated that the curve in the wing surfaces of the bird greatly facilitated the production of the

negative horizontal component of the wind pressure, and that the approximate calculation of this component (and of the vertical component, for that matter) was relatively much simpler than seemed likely from the rudimentary state of our knowledge concerning the laws governing the action of a fluid in motion on a surface which is not normal to the direction of the stream lines, even when it is a simple plane.

Moreover, apart from the formulæ I have established, which are not applicable in the case of a curved surface save when the wind is almost tangential in effect, I have devised a graphic method for showing immediately in a striking way how easily one may obtain, with a curved surface, the negative horizontal force necessary to support the bird motionless, and this independently of the direction and speed of the air

current on the various points of the wing surface.

I will state some of the consequences of my theory:

1. The velocity of the wind has no influence whatever on the horizontal equilibrium of the bird; in other words, the horizontal equilibrium which has been established for a given velocity of the wind remains if the wings retain their position when the velocity of the wind changes. But not so with the vertical equilibrium.

2. The shape of the rear portion of the bird's body and of its tail helps to create a negative horizontal force which is added to that of the wings.

3. The ascending inclination of the wind necessary for soaring flight diminishes in proportion as the surface of the wings increases relatively to the master diameter of the bird's body.

RATING AN AUTOMOBILE ENGINE.

DETERMINING HORSE-POWER FROM THE CYLINDER DIMENSIONS.

BY THOMAS L. WHITE.

THE problem of rating a car is one which is of equal interest to the manufacturer who makes it, the engineer who designs it, and the layman who buys it; but it is especially to the last that this article is addressed, the aim being to explain the broad principles by aid of which the horse-power of a motor can be determined from the cylinder dimensions, rather than to add still another to the numerous rating formulæ already in existence.

The power of an automobile motor, or in fact of any engine, is measured by the amount of work that it can render in a certain time. It is a *rate*, and as such cannot be dissociated from the conception of a definite period of time during which a certain task is performed. It must not be confused with the idea of pressure or torque or thrust, nor with the degree of magnitude of any of these.

Since power implies so much work per minute, to use the unit of time which custom has decreed as most convenient, the mathematical determination of power involves the determination of work, and in the exact engineering sense of the term work means motion against resistance. It is measured by the product of the resistance and the distance through which it is overcome, or what is the same thing, by the product of the acting force and the distance through which it acts. The engineering unit of work is the work done in lifting a mass of one pound through a vertical distance of one foot against the resistance exerted by the attraction of the earth. It is called a foot pound, and it will be noticed that there is no element of time involved in its conception. Work is not a rate, and the energy expended in overcoming a certain resistance through a certain distance is independent of the elapsed time necessary for the operation.

In measuring the work done by engines, the foot pound is inconveniently small, and engineers have adopted the estimate made by Watt of the power of a horse, viz., 33,000 foot pounds per minute, as a more suitable standard. This is known as a horse-power, and the power of engines is expressed in terms of this unit.

The internal combustion engine may be defined to be an instrument by which the energy or capacity of doing work stored up in fuels is transformed into the heat energy of expanding gases, and finally into useful mechanical work done against resistances. In this transformation, or rather series of transformations, there are three coefficients or multipliers, by which the total number of heat units liberated during the combustion of the fuel must be multiplied in order to arrive at the number of foot pounds in the useful output of the motor.

The first is the mechanical equivalent of heat, and if we denote its value by the symbol x , then x times the number of British thermal units liberated by the combustion of a stated weight of fuel is the number of foot pounds of work that the motor would be capable of turning out if the energy of the fuel were completely reproduced in useful effect at the crankshaft.

The second is the thermal efficiency of the engine. If we denote it by y , then y times the last product is equal to the number of foot pounds actually delivered by the expanding gases on the piston against the friction and inertia of the engine and against the resistance of the load. For most gasoline engines y lies between 10 per cent and 20 per cent, and the last product is the one which enters into the determination of the nominal horse-power of the motor.

The third multiplier may be called the mechanical coefficient, and it corresponds to the *pro rata* loss

between the piston and the crankshaft. If we denote this quantity by z , we have for the whole process, taking the number of heat units in a pound of gasoline as 19,000, a final output at crankshaft of $19,000xyz$ foot pounds per pound of gasoline consumed. This, the third quantity derived from the original calorific value of the fuel, bears the same relation to the brake horse-power that the second bore to the nominal horse-power.

Neither of the last two results, which represent actual transformations of energy, affords any indication whether the effect is obtained in a thousand strokes or in ten thousand, or whether those strokes, whatever be their number, are quick or slow. In other words, the results afford no information of a direct character as to the power of the motor, that is to say, the rate at which it is working; and in order to proceed, it is now necessary to consider the unit effort of the engine, of which its total effect is merely a multiple, viz., the expansion stroke.

When the explosion takes place in the cylinder of a motor, the energy liberated is associated with a rise in pressure, and the force exerted by this increased pressure impels the piston forward. In order to understand what follows, it should be carefully noted in this connection that a pressure is not a force any more than a velocity is a length. A pressure is so many units of force acting per unit of area, say ten pounds per square foot, just as a velocity is so many feet passed over per second; and in exactly the same way as by multiplying the time and the velocity together we get the distance traversed, so by multiplying a pressure by the area on which it is exerted, we get the total force which is its effect. Bearing this in mind, if we suppose that the pressure of the explosion in the combustion chamber is p pounds per square foot, then the piston at the beginning of its motion has impressed on it by the expanding gases a force of pA pounds, where A is the area of the piston head expressed in square feet. Now, in order to be able to analyze the exact manner in which this force acting on the piston is doing work, we will make the supposition that the whole distance through which the piston travels is divided into n equal parts, n being very great, so that each of the subdivisions into which the total piston travel is divided is small enough for the pressure exerted by the expanding gases while the piston is passing over a given subdivision to be regarded as appreciably constant, though less than the pressure in passing over the previous subdivision and greater than the pressure in passing over the next succeeding subdivision. If the total piston travel be S feet, it is clear that the length of each of the subdivisions is S/n .

If we further suppose that the pressure while the piston is passing over the first subdivision is equal to p pounds, over the second to p' pounds, over the third to p'' pounds, and so forth, then it is clear that the work done while the piston is passing over the first subdivision is pAS/n , this being the product of the force pA and S/n , the distance through which it is exerted. Similarly, the work done while the piston is passing over the second subdivision is $p'AS/n$, over the third subdivision is $p''AS/n$, and so on, the total work done during the expansion being equal to the sum of these instalments into which we have considered it to be divided up, that is, to—

$$pAS/n + p'AS/n + p''AS/n + \text{etc.},$$

which equals

$$AS/n (p + p' + p'' + \text{etc.}),$$

which can be written

$$AS \cdot \frac{(p + p' + p'' + \text{etc.})}{n}$$

Now the last factor in the last form of the expression for the total work is the sum of the successive pressures exerted during the expansion divided by their number, that is to say, that it is the *mean* or *average* pressure, and we have as our final result as the whole work done on the piston during the expansion stroke,

$$ASp_m \text{ foot pounds,} \quad (1)$$

where p_m is used to denote the mean pressure exerted by the expanding gases. It should be noticed that this expression is independent of n , the number of parts into which the length of the stroke was supposed to be divided. It follows that result (1) would have been the same had n been infinitely great, in which case our assumption of the pressure descending by a series of small differences would, instead of being an approximation, have been an exact representation of the continuous fall of pressure which in reality occurs in the cylinder during the stroke.

Result (1) is fundamental, and enters into all determinations of nominal horse-power. It can be written in several ways, or rather it is susceptible of several interpretations. Thus AS is the piston clearance or cylindrical volume of the motor, the portion of the whole volume of the cylinder which is swept out by the piston during the stroke, and we accordingly have as another form of the total work of the expansion,

$$V p_m \quad (2)$$

where V is the volume in question in cubic feet.

Or, again, the same result may be expressed so as to bring in the diameter of the cylinder. If this latter quantity be equal to D feet, then for A in formula (1) we can substitute $\pi D^2/4$, which is the area of the face of the piston calculated from the diameter, and we obtain the alternative formula,

$$\frac{\pi D^2 p_m S}{4} \quad (3)$$

Having established expressions for the work done during one working stroke in terms of the cylinder measurements and the mean pressure, the next thing is to consider the work done during one minute. It will be remarked that this manner of considering the output evades any difficulty which may arise from the fact that the work of an internal combustion engine is intermittently rendered, there being in the case of the usual four-cycle motor one working stroke to every two revolutions of the crankshaft. If we denote the number of revolutions by w , then the number of working strokes per minute is $w/2$, and the total work done on the piston in the same time is,

$$\frac{V p_m w}{2} \quad (4)$$

$$\frac{A S p_m w}{2} \quad (5)$$

$$\frac{\pi D^2 S p_m w}{8} \quad (6)$$

according to the form for the work during one expansion which it is most desirable to use. It should be noticed that the results (4), (5), and (6), in that they are each equal to a certain amount of work done during the unit of time, express the nominal power of the motor in foot pounds per minute, and any one of these expressions divided by 33,000 will give a quotient which is equal to the nominal horse-power of the

motor for the particular value of w at which the motor is running.

We have already seen that the work done by the explosive force on the piston of a motor is equal when multiplied by z , the mechanical coefficient, to the net work rendered at the crankshaft. This last quantity may be directly measured by applying to the rim of the flywheel a frictional resistance sufficiently great to hold the engine down to a constant number of revolutions per minute. Let F be the magnitude in pounds of this force, and let L be the flywheel radius. Then it is clear that the distance through which the force F acts during one revolution is equal to $2\pi L$ feet, this being the circumference of the flywheel, and that consequently the work done by the engine against the frictional resistance is $2\pi LF$ foot pounds during one revolution, or $2\pi wLF$ foot pounds per minute. We thus have two expressions for the power of the motor at the crankshaft, both expressed in foot pounds per minute, and equating them we get

$$2\pi wLF = \frac{zw p_m V}{2}$$

or dividing out by $2\pi w$,

$$LF = \frac{zV}{4\pi} \cdot p_m \quad (7)$$

The product LF is known as the motor moment or torque, and the last equation is an expression of the fact that in a given motor the mean pressure on the piston is directly proportional to the torque exerted on the crankshaft. Also, since it is evident, other things being equal, that the explosive force is proportional to the density of the mixture, that is to the weight of mixture per cubic foot of cylinder volume, equation (7) also proves that for the same motor the density of the mixture bears a constant ratio to the motor moment.

In coming now to apply the formulæ which have been established to the problem of comparing the horse-powers of different motors, it will be necessary to change our view of the constancy of the quantities which enter into them. So far our assumption has been that V , D , A , and S are constants and w and p_m variables. For instance, we have virtually regarded expression (4) as a statement that the volume cleared by the piston being constant, the nominal power is proportional to the mean pressure multiplied by the number of revolutions per minute. The formulæ are, however, susceptible of being interpreted in another way. Let us consider the case of two motors of different volumetric capacity, which are running at the same number of revolutions and in which the mean pressures developed by the explosions are the same. Then we have,

$$\text{Power of the first motor} : \text{Power of the second motor} \\ :: w p_m V : w' p'_m V'$$

$$:: \frac{2}{V} : \frac{2}{V'}$$

since $w p_m$ is equal to $w' p'_m$, the dashes indicating that the quantities to which they are affixed have the same significance for the second motor that the plain symbols have for the first. But this is the same thing as saying that if we denote the nominal horse-power by P , so that

$$P = \frac{w p_m V}{2} \quad (8)$$

then, p_m and w being constant, the power P is in constant proportion to the volume. This hypothetical case is typical of similar comparisons, and we shall now cease to consider the dimensional quantities as fixed and the mean pressure and speed as varying, taking the opposite view that the mean pressure and speed or their product or some simple relation between them are constant and that the dimensional measurements have the nature of variables. The values of p_m and w which will be considered will be those corresponding to the maximum power of the motor in question, and our connecting link, so to speak, in passing from one motor to another will be the experimental fact that the mean pressures and velocities of different motors are for maximum powers simply related in a way which is independent of volumetric measurements.

When a motor is accelerated, the amount of frictional resistance that it is necessary to apply to the flywheel in order to take up the load becomes less and less as the angular velocity increases, and a point is at length reached when a further increase in the number of revolutions no longer produces a net increase in the power. In other words, it is an experimental fact that the expression $2\pi wFL$ has a maximum value which divided by 33,000 is the maximum brake horse-power of the motor. It is the derivation

$$\text{from the corresponding expression } \frac{wVp_m}{2} \text{ of a corre-}$$

sponding maximum value, which shall only involve dimensional quantities and which shall be independent of the mean pressure and of the speed, which consti-

tutes the problem of rating. Of course, if every engine could be put on the testing stand, and a table of values of the left-hand member of equation (7) computed corresponding to the various values of w , any other determinations would be unnecessary; but there are many contingencies where it is important to know the maximum power of a motor and where a practical test is out of question, and it is to meet the requirements of such cases that a rating is designed.

By writing equation (8) in the form

$$\frac{P}{V} = \frac{w p_m}{2}$$

it is clear that if the value of $p_m w$ is the same for all motors when they are developing their maximum power, then that maximum power will be in the proportion of the piston clearance, that is to say, the maximum number of foot pounds of which the engine is capable per cubic foot of piston clearance will be constant and independent of the motor dimensions. Let us see how this hypothesis squares with the facts, interpreted in a liberal spirit, for it is never possible to say of two engines that they are equally well designed or that they can be tested under exactly the same conditions.

The subjoined table gives the stroke, bore, piston clearance volume, maximum brake horse-power, and the number of revolutions at which it was delivered, of ten representative motors. In volumetric capacity they cover a range from one to fifteen liters, and they were selected from a much longer list compiled by Arnoux, a French engineer, the principle of the selection being to retain only those motors which for their size were the most powerful. The motors were all of the four-cylinder type, and the values of V given in the table are the total capacities of all four cylinders. The metrical measurements have been retained as being more convenient for manipulation.

Motor.	D mm.	S mm.	w	H.P.	V	P/V	p_m
1.....	65	70	1,600	12.5	928	13.5	8.4
2.....	85	90	1,600	22.5	2,042	11.0	6.9
3.....	100	105	1,500	33.5	3,300	10.1	6.7
4.....	120	122	1,350	52.0	5,522	9.4	7.0
5.....	130	128	1,350	60.0	6,798	8.8	6.5
6.....	140	138	1,400	76.0	8,501	8.9	6.4
7.....	150	148	1,400	90.0	10,466	8.6	6.1
8.....	165	155	1,200	110.5	13,262	8.3	6.9
9.....	170	165	1,200	120.0	14,986	8.0	6.7
10.....	180	160	1,300	135.0	16,293	8.3	6.4

The column headed P/V gives the maximum horse-power per liter of piston clearance. The numbers in the last column are proportional to the mean pressure in whatever unit this latter may be expressed. They are derived from equation (8) by substituting the known values of P , V , and w .

The immediate inquiry is whether it is admissible to consider $p_m w$ as constant, and a glance at the P/V values, which are proportional to this product, will show that instead of being independent of the dimensional measurements $p_m w$ decreases as the motor grows bigger. If we assign to it a value which will give a correct volumetric power for motors of moderate capacity, then for large motors we shall derive a horse-power which is much too high and *vice versa*. Without trying to evade the conclusion that the volumetric power of motors decreases with their size, let us take a mean value of 9 horse-power per liter of piston clearance, this being the average of the last nine motors in our table, and test whether the ratings obtained on this supposition depart very far from their experimental values. We have, then:

Motor.	Calculated Rating.	Error. Per cent.
2.....	18.4	18
3.....	29.7	11
4.....	49.7	9
5.....	61.2	2
6.....	76.5	1
7.....	94.0	4
8.....	119.5	8
9.....	135.0	12
10.....	146.7	9

And it appears that except for the fact that the first two motors are considerably underrated, the results derived by taking P/V as equal to 9 are fairly accurate. The equivalent American rating would be 1 H.P. per 7 cubic inches of piston clearance.

The column of mean pressures in our table shows that although there is a slight uniform decline in the value of p_m , yet the average value for the last nine motors, which is 6.6, is very close to the actual value in any particular case. If we assume that p_m is constant for all motors when they are delivering their maximum power, then the power of any given motor would be as the product of the R.P.M. rate and the piston clearance volume. The average value of w for over one hundred tests made by Arnoux was 1,300, and if we take this figure as a mean, we obtain an average value of P/V for all motors of $1,300 \times 6.6$ or 8.6 which does not differ materially from the value

9 which we derived from our table of ten selected motors.

Much labor has been devoted by various investigators to the derivation of rating formulæ of the form $k D^n$, where k is constant, and n lies between 2 and 3. Whatever be their merit from a technical point of view, such formulæ, necessitating the use of logarithms for their application, lack the element of simplicity, which, at any rate from the point of view of a layman, is, next to accuracy, the first desideratum in a rating rule. Moreover, such formulæ have no special claim to mathematical exactitude. They are derived by plotting the data from tests in the form of curves, the objects being to construct a mean or average curve, whose equation will serve as a relation between P and D .

The fact of the matter is that no great variety of hypotheses about the relations of w and p_m is possible. We can assume the constancy of p_m , or of w , or of $p_m w$ or we can assume that the piston velocity is constant, which necessitates the constancy of wS and gives from formula (5) a rating depending on D^2 . We shall not, however, consider these departures, as they involve nothing new in principle which has not been analyzed when we were deducing a relation between the power and the volume, and the aim of this article being not to criticise rating formulæ, but to outline the reasoning on which they are based.

THE SYNCHRONOUS CONDENSER.

PROBABLY of all of the characteristic performances of the synchronous motor, none is more interesting than its operation as a "condenser"; that is, its tendency to draw leading wattless current from the supply system when its field current is increased above that value giving minimum armature current. Although the machine possesses this tendency to a marked extent, it exhibits few of the characteristics of the apparatus known as a stationary condenser. For example, when the machine is operating as a synchronous condenser, an increase in the supply E. M. F. results in a decrease in the leading wattless current in its armature, while a stationary condenser takes a leading wattless current which continues to increase in value as the supply E. M. F. is increased. The condenser action of a synchronous motor can conveniently be investigated by neglecting momentarily certain minor modifying influences. With a degree of accuracy amply satisfactory for practical purposes, it may be said that throughout its working range the wattless component of current in the armature of a synchronous motor varies directly with the change in the field current from that value which causes the counter E. M. F. of the armature to equal the E. M. F. impressed upon the armature leads. This action is attributable to the demand for a counter E. M. F. equal to the impressed and therefore for a relatively constant field magnetism independent of the value of the field current. The excess or deficiency in magnetomotive force supplied by the field circuit ampere-turns above or below that necessary to maintain the required field magnetism is supplied by a wattless leading or lagging component of the armature current. The latter component may be considered as a "condenser" current having either a positive or a negative value according to whether the field current is above or below that value which causes the condenser current to reduce to zero.

It is worthy of note that the exact amount of change in power factor is not always a true measure of the advantage of eliminating wattless currents from a transmission system. For example, it might seem that a change that would result in increasing the power factor from 78 per cent to 95 per cent is far preferable to a change that would increase the power factor from 95 per cent to 100 per cent. However, the former change indicates the neutralization of the same value of wattless current as does the latter change, and in many cases the detrimental effect of operating a low power factor varies directly with the value of the wattless currents present in the system rather than with the difference between the actual power factor and 100 per cent.—Electrical World.

On May 15 there was held in Cracow, at the Academy of Sciences, a celebration of the twenty-fifth anniversary of Prof. Ilszewski's work on the liquefaction of gases, his first researches in that direction having been commenced during the spring of 1883 with the late Prof. Wróblewski. The celebration was an unofficial one, and only the members of the mathematical and natural history class of the academy took part in it. The president of the academy, Prof. Count Tarnowski, congratulated Prof. Ilszewski in an address, after which an album containing photographs of the members of the mathematical and natural history class was presented to him. As the intention of the academy to celebrate the work of its distinguished member was not publicly made known, only a few letters and telegrams reached him, including those of several societies in Warsaw and of the professors of chemistry and of physics in the University of Fribourg.