CREUSOT AND THE ORDNANCE MADE THERE.*

By L. RAMAKERS.

ONE of the largest establishments for the manufacture of war material is that of Messrs. Schneider & Co. at Creusot, France. It was the Schneider guns which enabled Boers to offer such a sturdy resistance to the English in the last war in the Transvaal. As a proof of this, we have only to cite some passages from the London Times of the 26th and 28th of December, 1899: "The Boers have obtained the latest type of ordnance, compared with which the English guns are antique. . . . It is absolutely evident that if the English gunners had occupied the same position as the Boers, and been provided with the same weapons possessed by the Boers, viz., guns constructed by Messrs. Schneider & Co., the loss in men and property at Ladysmith would have been ten times as great."

The foundries of Creusot have furnished also the greater part of the ordnance both for Russia and Japan, and for this reason this establishment possesses great interest at the present time.

The Creusot works turn out all sorts of large metal work, but more particularly do they devote their energies to the making of ordnance and armor plating, a branch which has become a specialty since the war of 1870. The establishment carries upon its rolls about 18,000 employees. The foundries and machine shops devoted to ordnance alone cover a superficial area of 30,000 square meters, and extend to a length of four kilometers without interruption.

Modern cannon are divided as follows:

1. According to their type; guns of standard length, medium howitzers or shell guns, and short guns or mortars.
2. According to their caliber; in great guns of 10 to 50 centimeters bore, or medium guns of 6 to 10 centimeters, or small guns of from 25 to 50 millimeters bore.
3. According to their rapidity of fire; into ordinary guns, rapid-fire guns, and automatic guns and mitrailleuses or multiple cannon.

PROVING GROUNDS AT HARFLEUR.

CREUSOT AND THE ORDNANCE MADE THERE.

4. According to their purpose; for ships, for fortresses, for the field or mountain guns.

Among the cannon made at Creusot we shall glance at the principal types, and among them particularly those called rapid-fire guns. Since the advent of smokeless powder, all the manufacturers have striven to increase the rapidity of fire, which is now no longer restricted by the clouds of smoke issuing from the mouths of the pieces, and which had to become dissipated before the gun could be trained again.

The naval rapid-fire gun of 15 centimeters (about 6 inches), mounted upon a front pintle carriage or upon a center pintle carriage, has a recoil that is scarcely sensible. These pieces may be loaded very quickly, the charge and projectile forming one piece, as in the ordinary infantry weapon, the shell being in general automatically ejected. These guns are usually placed behind a metallic shield.

Another type of rapid-fire gun is a cannon of 47 millimeters bore and 60 calibers length, built for automatic loading. Its recoil is entirely overcome, the gunner holding his shoulder to the butt, and sighting as with a rifle. This gun is capable of rapid manipulation, and is much employed by armored ships against the torpedo craft; it is in fact the only defense it has against these small but terrible adversaries.

The Creusot works recently furnished the Servian government with a series of very remarkable guns. These guns have been built for transportation over all sorts of road or country, and at any marching speed.

Before delivery, all pieces of ordnance built at the Creusot works are tested for every requirement. For this purpose Schneider & Co. control a proving ground at La Villedieu near Creusot and a field for long-range target practice at Harfleur near Havre. The proving grounds at La Villedieu afford facilities for testing military material of any power whatever, and in all possible manners; be it for its ballistic properties, its resistance, or its action in the most varied cases and conditions. In the interest of such tests a number of heavy timber platforms have been erected, upon which are placed the pieces to be tested. This is of course to prevent the cannon from gradually embedding them-

selves in the ground from the force of the recoils, as well as to facilitate bringing the gun again into the same position for firing. From these bases it is possible to shoot into beds of sand 22 to 32 feet thick, from any desired angle of elevation. With the aid of telescopes or strong field glasses, it is possible to note from the observatory the result of each discharge upon the butts, and observe just how the material behaves under conditions similar to those in actual conflict. Shooting into the sand bed is done with a view to ascertaining the muzzle velocity of the projectile. For this purpose, two velocity frames are interposed between the piece and the sand bed in the path of the projectile. As the latter passes through them, it breaks some of the wires and interrupts the electric current with which they are charged, and which is in turn connected with the apparatus for measuring and registering the instant of passage of the projectile. The time required for the projectile to cover the distance between the two is called the initial or muzzle velocity of the projectile.

The proving grounds are provided with the most approved instruments for obtaining all desirable data, such as electric chronographs, crushers for measuring the pressures in the piece, registering gages for showing the pressures in the check cylinders, speedometers for measuring the movement of the recoil from the carriage, etc. Thus it is possible to obtain exact information concerning the functioning details of the carriage, whether the projectile be shot into the sand bank or into the sea.

The proving ground is laid out in such a manner that all these tests may be carried out with the greatest safety possible. A system of mirrors affords complete observation of all the effects of the shot. The gun is fired from a distance, either with an electric primer, or with the ordinary lanyard and primer.

The long-range testing grounds at Harfleur form a natural complement to the ordnance establishment of Messrs. Schneider & Co.

The field is situated upon a terrain which extends over a distance of 13½ miles in length, and is laid

out in such a manner as to allow of carrying out, under the best conditions, all the experiments in ballistics necessary for a range of from 3¼ to 5 miles.

It serves especially:

1. For the establishing of range tables for different materials.
2. For experiments in precision at great distances, notably for field, siege, or fortress guns.
3. For discharges with powerful explosives.
4. And for the study of experimental fuses.

This proving ground, which is situated upon a remarkably uniform territory, possesses three principal ranges, of which one is especially adapted to the use of powerful explosives, since its limits on the south are bounded by the sea shore itself, which at low tide exposes considerable extent of dry land, that lends all the more securely, and under the best possible conditions, to this sort of gun practice.

Within the proving grounds annexed to the Creusot establishment are tested the Schneider armor plates for turrets and the sheathing of ships. Here they are forced to withstand the energies of the different engines of war they are likely to meet in actual service. This is a fitting place to make a few remarks upon the Schneider plate. We recall that after the war of secession, in which the first armored ship, the "Merrimac," made its appearance, the attention of metallurgists was seriously attracted toward the manufacture of armor plates. Messrs. Schneider were among the first to appreciate the importance of this branch of the founder's business, and immediately devoted a part of their activity to it, soon acquiring considerable repute in this specialty.

Thanks to the powerful machines at the disposal of Schneider & Co., among which we have only to cite the great press for compressing liquid steel under a force of 10,000 tons, the Creusot works are able to make armor plate 23.62 inches thick and weighing 65 tons. They have already delivered to the various naval departments about 80,000 tons of these plates. France alone has ordered about 36,000 tons of them, and the difference has been parceled out to almost every naval establishment of the world.

The plates are alloyed with different metals, such as nickel, cobalt, etc., which confer upon them enormous

resisting powers. Armor plates made twenty-five years ago are pierced without the slightest difficulty by the projectiles of the present day.

To-day, thanks to a specially tempered steel which is one of the secrets of manufacture, the works at Creusot are turning out plates upon which the modern shells fired from the large guns of the day have but small effect.

SUPERHEATED STEAM.*

By F. J. ROWAN.

SUPERHEATED steam offers a most interesting subject for study, whether it is considered from the abstract and theoretic side or from the concrete and practical side.

With the former are connected the thermo-dynamic propositions and calculations which assume a perfectly gaseous condition for superheated steam, and deduce its efficiency accordingly. This view of the subject is fully dealt with in Rankine's "Steam Engine and Other Prime Movers," in Prof. R. H. Thurston's "Superheated Steam" (Amer. Soc. Mech. Eng., vol. xvii.), and in Peabody's "Thermo-dynamics of the Steam Engine." The literature devoted to the practical side of the subject is voluminous, and contains the history of the various attempts to introduce the use of superheated steam, with the failures of the early and the successes of the later forms of apparatus.

HISTORICAL.

Although the "flash" boilers, which date from that of John Payne, in 1736, undoubtedly produced steam which was more or less superheated, necessarily on account of the method of steam production adopted in these boilers, yet the design of Sir William Congreve, in 1821, was perhaps the earliest attempt to treat steam after its formation in a boiler, his object having been "to increase its volume." It is not likely that the importance of increasing its temperature would be recognized at so early a date.

The system invented by Jacob Perkins, in 1822, was also, in one aspect of it, a method of producing superheated steam, although the degree of superheat was probably small. In this case the water in the boiler was heated to 400 deg. or 500 deg. F. without allowing steam to form, the boiler being quite full of water. When a small additional quantity of water was then forced into the boiler by a pump, a corresponding quantity of the superheated water escaped by a valve into a steam pipe, where it instantly flashed into steam.

French writers (such as M. Maurice Miet, in *Le Génie Civil*) mention that the superheating apparatus was designed by Becker (in 1827), Trevithick (in 1828 or 1832)†, Raffard‡ (in 1848), de Quillac (in 1849), Moncheul (in 1850), and by Hirn (in 1855); but, except in the case of the last of these, no permanent benefits seem to have been secured. Trevithick reported, in 1828, on the engines of the Brinner Downs Mine in Cornwall, where the steam pipes and cylinders had been inclosed in brick-built flues, with a fire-grate conveniently attached, in order by heating them up to prevent condensation. The idea was merely to make a better non-conducting covering than that of the sawdust used at a neighboring mine, but unexpected economy was realized, the duty of the engine having been increased from 41 to 63 million foot-pounds per bushel (84 pounds) of coal. When the superheating flues consumed 5 bushels of coal per 24 hours, the steam boiler required 67 bushels, which quantity became 108 bushels when the superheating was not employed, this showing a saving of 33.4 per cent.

The boiler, which Trevithick patented in 1832, was composed of vertical water tubes set in a circle, and joined to an annular chamber at top and bottom; the superheater pipes were U-shaped, dependent over the fire, with all joints in the upper part of the boiler and clear of the fire gases, which were led off into the cylinder jacket on their way to the funnel or chimney.

The investigations of Hirn, most of which were published in the Bulletin of the Industrial Society of Mulhouse, or in that of the Alsatian Society of Steam Users, have been the means of encouraging the engineers of Alsace and the adjoining country, so that at the present day Germany holds the lead in the successful application of numerous forms of superheaters, and in the use of superheated steam. Hirn patented, in 1855, a form of superheater which he called a "hyper-thermo-generator," formed principally of cast iron.

The late Mr. John Penn (Proceedings Inst. Mech. Eng., 1859) ascribed his knowledge of the subject to Mr. Thomas Howard, of Rotherhithe, who had tried superheated steam about 1831 or 1832, and to Dr. Haycraft, of Greenwich, who had taken up the subject after Mr. Howard. It is, however, stated elsewhere that as early as 1831 Dr. Henry Haycraft himself obtained a patent for superheated steam, and believed that he had discovered a power ten times greater than ordinary steam.

In 1849 Mr. James Frost, of Brooklyn, N. Y.; communicated a paper to the Rumford Committee of Cambridge University, in which he claimed that he had increased the power of steam four to six times, and that at 650 deg. F. a change took place, a new vapor, which he called "stame," being formed. This was subsequently proved to be merely perfectly dry steam or "steam gas," but the term "stame" was used for some years in controversies which arose in technical

* Read before Institution of Engineers and Shipbuilders.

† Spence (in 1840) [see Engineering, 14th Feb. 1890, p. 174].

‡ See also Prof. R. H. Thurston on Superheated Steam, Trans. Am. Soc. Mech. Eng., vol. xvii., p. 490.

* Specially prepared for the SCIENTIFIC AMERICAN SUPPLEMENT.

journals. The Committee of the University reported unfavorably on Mr. Frost's claims, but several experimenters corroborated his statements by results obtained at a subsequent date.

The subject was investigated by Mr. B. F. Isherwood in 1854, 1860, and in 1862-64, and his results were published in the Journal of the Franklin Institute (vol. xxvii., third series) in his "Experimental Researches" (vols. i. and ii.), and in the official reports of the United States government. The first experiments were made with the Wethered system of using a mixture of saturated and "surcharged" steam; the second with Waterman's apparatus, which consisted of a steam jacket around a steam supply valve, connected with a superheating arrangement when desired, and also a peculiar throttle valve. This plan was arranged for "the steam to heat itself by means of the differences of temperature due to differences of pressure produced by the use of a simple throttle valve." This was evidently a plan to produce the small amount of superheating derived from wire-drawing the steam, and it proved abortive in these experiments, even with the steam jacket, because "so great were the refrigerating influences in the cylinder that an adheating of 31.7 degrees possessed by the steam on entering the valve chest, obtained by the Waterman system of throttling, was inadequate to the production of any net gain in the cost of power." The experiments undertaken for the United States government were more varied and were carried out principally in steamers or marine engines and to much higher temperatures than had formerly been used.

Messrs. C., J., and S. Wethered, who were large woolen manufacturers in Baltimore, U. S. A., had been experimenting for some time before they applied for a patent, in May, 1853, for the employment of a mixture of superheated with saturated steam in the cylinders of steam engines. Their superheater consisted of a pipe led from the steam space of the boiler at the upper part and near the rear end, and continued in a coil in the combustion space directly over the fire and in the heating flues. This superheater had about three square feet of surface per nominal horse-power. Mr. Wethered laid great stress upon his employing two steam pipes, and reckoned that the admixture of saturated with superheated steam preserved the cylinder and valve surfaces, while giving the benefit of superheat. (See Min. Proc. Inst. C. E., 1860, vol. xix., p. 462*; and Trans. Inst. Mech. Eng., January, 1860, p. 85.) This apparatus was in different forms tried in the P. and O. Company's steamers, in H. M. S. "Dee," and in the Admiralty yacht "Black Eagle," with good results. An apparatus on similar lines was said to have been supplied by Messrs. Boulton & Watt to the steamer "Great Eastern" about the year 1862 ("Bourne on the Steam Engine," p. 242), but this does not clearly appear from the illustrations given by Bourne. Although excellent results were obtained in several instances of the use of Messrs. Wethered's plan, it was proved that a mixture of ordinary with superheated steam was unnecessary, because the mean temperature arrived at was precisely that of moderately superheated steam alone. The effects of the Wethereds' mixture could be obtained when a temperature of not over 369 deg. F. was employed in the superheated steam. Experiments made by Mr. Isherwood with the Wethereds' plan in New York, in 1853, were, however, the means of spreading the belief that the presence of the saturated steam provided a lubricating quality, which was absent from unmixed superheated steam. (Journal of the Franklin Inst., vol. xxvii., third series, pp. 257-261.) Consequently several patents were taken out in America for modifications of the Wethered plan by Cornell (1867), Stone (1859-1860), Brown & Gregg (1865), and Carvalho (1860). Carvalho's patent aimed at preventing the action on certain qualities of iron which had been noticed in steam engines, and had been ascribed to the decomposition of the superheated steam at high temperature. Such action was, however, more likely to occur in the pipes or tubes employed as superheaters, and subjected to the high temperatures of the flame or hot gases in the combustion chamber or flues in which the superheaters were placed, and the deterioration of the metal surfaces of cylinders and slide valves and faces must be ascribed to other causes.

Bourne, in his "Treatise on the Steam Engine," describes the superheaters constructed by R. Napier & Sons, Lamb & Summers, W. Beardmore, and Thos. Richardson & Sons, the last having been designed by G. W. Jaffrey; and in a paper by Mr. John N. Ryder to the Institution of Mechanical Engineers (Proceedings, January, 1860), there are descriptions of the superheaters of Parson & Pilgrim and of D. Patridge, with some account of their action.

The papers by Mr. William Patchell (in Proc. Inst. Mech. Engineers, April, 1896), and by Prof. William Ripper (in Min. Proc. Inst. C. E., vol. cxxviii., May, 1897, p. 60) are among the earliest of those which deal with the more recent practice in the use of superheated steam, and may be said to mark the period of the revival of any great degree of interest in it as far as this country is concerned. Prof. R. H. Thurston's able treatise on the same subject ("Superheated Steam: Facts, Data, and Principles Relating to the Problem") in Transactions of the American Society of Mechanical Engineers (vol. xvii., p. 488), which was read in May, 1896, is another prominent landmark in connection with it. From that time onward the Minutes of Proceedings of the Institute of Civil Engineers are seldom without records of investigations made on the continent of Europe with different forms of steam

superheaters, and many papers have appeared elsewhere.

DESIGNS OF SUPERHEATERS.

The early forms of superheaters used in this country were placed above the boiler at the base of the funnel in the case of marine boilers, with which they were almost exclusively used. One of the earliest was that introduced by John Penn & Son, in the P. and O. Company's steamer "Valetta" (see Trans. Inst. Mech. Eng., 1859, p. 195). The engines were of 260 nominal horse-power, and the boilers were of Lamb & Summers's design, the superheaters being placed in the uptake outside the ends of the vertical flues, which in Lamb's arrangement took the place of horizontal flue tubes. Two horizontal faggots of wrought-iron tubes, 2 inches diameter inside and 6 feet 3 inches long, formed the superheater, each bundle consisting of 44 tubes. They were placed in vertical rows, with clear spaces between the rows horizontally for allowing access in cleaning the boiler flues. The tubes were fixed into three flat chambers made of wrought iron welded up at the corners, and closed each with a single flange joint. The steam from the boiler entered the center chamber through a stop valve, and was taken off from the end chambers by other stop valves communicating with the steam pipes to the engine. The total area of superheating surface, including the wrought-iron chambers, was 374 square feet in each of the two boilers. The pressure of steam then used was 20 pounds per square inch, and the steam was superheated 100 degs., or from 260 degs. up to 360 or 370 degs. F.

Patridge's superheater consisted of a cylinder filled with vertical tubes, placed vertically over the uptake, and resting on the steam chest at the base of the chimney (see Trans. Inst. Mech. Eng., 1860, p. 25). The furnace gases passed up through the tubes and through an annular space surrounding the cylinder between it and the chimney, and the steam was passed across the cylinder and over a vertical baffle plate in the center by means of steam pipes arranged on each side at its base. This apparatus was fitted in H. M. S. "Dee," and afterward in the R. M. S. "Tyne," in the Cunard Company's steamer "Persia," and in an oblong form in the "Great Eastern."

In the case of the "Great Eastern," the superheating apparatus was constructed by Messrs. Boulton & Watt, and the oblong chambers containing the vertical tubes were placed in a casing of similar form which constituted the base of the chimney. A more simple construction was introduced by the same firm in the Holyhead steam packets. In these examples the lower part of the chimney was surrounded by a steam casing, which was divided radially by six partitions, the steam alternately ascending and descending in these until it passed over all the surface exposed to the heat from the chimney.

Messrs. R. Napier & Sons introduced into the steamer "Oleg" superheaters, consisting of horizontal steam tubes placed in an oblong casing forming the roof of the funnel. The tubes were 2 inches outside diameter, 5 feet 6 inches long, and were fastened in flat stayed boxes or headers.

Messrs. Lamb & Summers employed flat-sided flues similar to those used in their marine boiler, in place of tubes, the steam being passed inside the flue passages in the superheater instead of the reverse arrangement, which was adopted in their boiler. The alternate spaces were used for passages for the chimney gases. These were 2½ inches wide, the free spaces in the steam passages being ½ inch wide. An improved form was made in 1865.

In Beardmore's superheater, horizontal steam tubes with flat headers were used, but this arrangement differed from the others, in that it formed an integral portion of the boiler, and no stop valves were employed. It was placed, like the others, in the uptake just below the chimney.

Still another arrangement similarly placed, but differing widely in design from those mentioned, was that of Jaffrey. This was made of cast iron in two different designs, one being a radial and the other a parallel arrangement of tubes and chambers.

Parson & Pilgrim's superheater, although contemporaneous with these other forms, differed from them all in having been placed in the furnaces of the marine boilers. A steam pipe common to two furnaces descended from the steam space of the boiler between the furnace doors, and branched into horizontal pipes, one of which entered each furnace below the fire bars, and passed along to near the back of the grate. Two saddle-shaped pipes then rose from horizontal pipe into the combustion space, and the steam passed through them and returned to an outgoing horizontal pipe laid at the opposite side of the ashpit from the ingoing pipe.

The arched pipes were frequently made red-hot, and it is said (Trans. Inst. Mech. Eng., 1860, p. 23) that steam of 20 pounds pressure, or 264 degs. F. temperature, was found to have attained a temperature of from 484 degs. to 540 degs. F., the pressure remaining unchanged. This apparatus was first applied to a stationary boiler at Woolwich Arsenal, and afterward to marine boilers in vessels of the Waterman's Steam Packet Company on the Thames, and in H. M. steam tug "Bustler."

Of more recent superheaters that of Schwoerer, which was derived directly from that of Hirn, has had a wide application on the Continent. It consists of cast-iron pipes, joined by semi-circular bends, so that the pipes are zig-zagged, and form flattened spirals. The pipes have longitudinal projections from the surface inside, similar to those of the Serve tube, but not so large, and have transverse ribs outside like those

of radiator tubes. These pipes are placed vertically in independently-fired arrangements, and horizontally in combination with boilers of various design. This superheater has been applied to a water-tube boiler at the Grand Junction Water Works, Kew Bridge (see Engineering, 20th March, 1895, p. 403), and it is also in use at the works of Messrs. Fraser & Chalmers, Ltd., at Erith.

A former design of the Uhler superheater, recently revived in Germany, has given rise to various modifications of multi-tubular superheaters, of which one has been described by Messrs. Grouville & Arquebourg in the Genié Civil, xxiv., No. 12, p. 181.

In the Uhler, as now made, steel is used for the header, which has two divisions, from which tubes of the "Perkins" or "Field" pattern extend. It is claimed that this method of construction prevents the tubes being overheated, as the saturated steam meets the tubes at their hottest parts, and that higher temperatures and pressures can be used with this superheater; while the tubes remain more free from solid deposit.

The Hering superheater is made of tubes of small diameter of Swedish steel without welds, zig-zagged in parallel folds, the several coils passing the steam "in parallel." It has been applied to Elephant boilers and to water-tube boilers. As so arranged, the hot gases can be shut off by dampers entirely from the superheater, and made to pass over the boiler surfaces in the ordinary way. Ordinarily steam temperatures of 450 degs. to 550 degs. are attained, but temperatures as high as 800 degs. can be used.

The Gehre superheater, when fitted in a boiler flue, or as separately fired, consists of horizontal cylindrical chambers of small diameter, through which small tubes for the conduct of the hot gases pass, the steam being in the space surrounding these tubes. In the case of the Gehre arrangement adapted to a water-tube boiler, one or two rows of water-tubes are omitted, and, by means of sleeves carried through the headers, these tubes are transformed into superheating tubes, the saturated steam entering at the front and the superheated steam escaping at the back. Two tiers of these tubes are employed when a high degree of superheat is wanted.

Musgrave & Dixon's superheater consists of a row or nest of U tubes suspended from a tube plate forming the bottom of a box, and placed in the flue of a Lancashire or other boiler at the back of the furnace tubes. The box or header is divided by a vertical diaphragm so as to direct the course of the steam. By-pass and other valves are arranged, as it is not intended to pass all the steam from the boiler through the superheater. The superheater had 120 square feet heating surface, with a boiler having 1,195 square feet.

McPhail & Simpson's superheater was generally combined with an internal radiator or generator of radiating tubes placed in the interior of a boiler, the idea being to control the amount of superheat in the steam passing to the engines. This arrangement consists of two nests of vertical steel tubes expanded into cast steel headers. One of the top headers is connected to the anti-priming pipe in the boiler, and the corresponding bottom box is in connection with a copper pipe laid inside the boiler below the furnace flue. The other end of the radiator pipe connects to the second bottom box or header, and the top header of this nest to another horizontal pipe laid in the top of the boiler over the internal flue just under the water line, and ending at the main steam stop valve.

Another form of this superheater, as applied to water-tube boilers, and applications of this form of superheating tubes seem also to have been made without the radiating tubes in the water space of the drum.

Sinclair's superheater was installed by Prof. Kennedy at Edinburgh Electric Lighting Station, and various results of its working have been published. The superheater tubes are flanged and bolted to cross inlet and outlet tubes, the joints being kept away from the action of the hot gases.

Holt's superheater is of the U-tube design, and is said to have been fitted to boilers at Saltaire in 1866.

The Davey-Paxman superheater, as shown at the Glasgow Exhibition, was composed of seven elements, each consisting of one divided header, the compartments of which were connected by a series of single loop or U-shaped tubes extending horizontally into the combustion chamber. The headers were connected together by elbows in the rear, and the steam flowed seven times through the superheating chamber, commencing in the lowest rows of tubes, which are exposed to the greatest heat, and then rose to the topmost element and working downward to the second lowest and hottest element, from which it passed to the engine. It was independently fired, the hot gas from its furnace being under control so that it could be delivered under an adjacent boiler before passing to the economizer, or sent direct to the economizer and chimney, or passed into a main flue without rising through the superheater.

The Sugden superheater is another modification of the U-tube form. It is illustrated in The Engineer of January 23, 1903 (page 100). Other British superheaters include that of Prof. Watkinson, about which we may hope to learn some particulars from him; that of Chatwood, illustrated in Min. Proc. Inst. C. E., vol. cxxviii., pp. 110-111; those of Cruse, the Stirling Co., the Babcock Wilcox Co., and some others. Among those in use on the Continent are the Walther, the Steinmuller, the Reisert, the Meyer, the Buttner, the Durr, the Simonis & Lanz, the Göhrig, the Gohring, the Bohmer, and the Hildebrandt forms. Some of these are composed of straight tubes, some of zig-zagged tubes, but a large number of some form of

* See also vol. xviii., p. 277.

U tube. The last three named have various forms of coiled tube. All are illustrated in The Mechanical Engineer of June 8 and 22, and July 13, 20, and 27, 1901.

One form of superheater has been proposed by R.

words must be devoted to the Schmidt arrangement before concluding this section.

In one form it consists of spirally-coiled tubes, and in the independently-fired variety the tubes are horizontally coiled. They are arranged so that the satu-

eight tiers of 2 $\frac{3}{4}$ -inch pipe directly above forming the superheater. The wet steam enters below and passes through the first four tiers, then to the eighth, and flows downward to the fifth, from which it is withdrawn. A somewhat similar arrangement is observed in the other form.

FIGS. 1 AND 2.—HORIZONTAL AND VERTICAL SECTIONS OF A BUTLER ROTARY VALVE FOR A SINGLE-CYLINDER GAS ENGINE.

FIG. 6.—HORIZONTAL CROSS-SECTION THROUGH ROTARY VALVE OF THREE-CYLINDER ENGINE.

Mr. Rowan concluded his paper by referring at some length and in an interesting manner to the use of superheated steam.

A ROTARY INDUCTION AND EXHAUST VALVE FOR EXPLOSION ENGINES.

INTERNAL combustion engines do not admit of the ap-

FIGS. 3 AND 4.—CROSS-SECTIONS THROUGH ROTARY VALVE FOR 700 HORSE-POWER DOUBLE ACTING GAS ENGINE.

FIG. 7.—DIAGRAMS SHOWING POSITIONS OF THE VALVE AND THE CRANKS WHILE CRANKSHAFT IS MAKING ONE REVOLUTION.

FIG. 5.—CROSS-SECTION THROUGH CYLINDER AND VALVES OF 700 HORSE-POWER DOUBLE-ACTING GAS ENGINE.

GAS ENGINES FOR ELECTRIC LIGHTING, FITTED WITH A NOVEL ROTARY VALVE.

Wolf for locomotive type boilers. Another arrangement more suitable for locomotives proper has been proposed by Mr. J. Riekie. Space is not available for a description in detail of all these forms, but a few

rated steam from the boiler meets the hottest gases. In the spirally-coiled form the lowest coils, composed of eight tiers containing five coils each of spirally-wound 2-inch pipe, constitute the economizer, the

plication of slide valves of the kind used in the ordinary steam engine, owing to the difficulty of keeping a slide valve gas tight on its seat against the pressure of explosive action in the cylinder, which is opposed only by the pressure of the atmosphere for keeping the valve against its seat. The explosion engine is in this respect entirely different from all engines actuated by compressed air, steam, or other fluids under pressure; and the gas and oil engines in which slide valves have been used have consequently required a cover at the back of the valve for holding it in place. In these cases the face of the cylinder, as well as the cover and both sides of the valve, have been of necessity very accurately faced.

The valves in most general use in all classes and sizes of explosion engines are of the lift or poppet order. These disk valves—whether with flat or conical seats—when used for the exhaust, always require a cam or other operating mechanism to open them against the pressure of the gases in the cylinder at about the termination of the power stroke. This pressure may be as high as 40 pounds per square inch, and, consequently, the cams, levers, and gearing used require to be of substantial proportion. It is also quite general practice now to provide cams or other operating mechanism for the induction valves used for the admission of the explosive mixture. Each cylinder thus requires two separate valves with lifting or opening mechanism.

The balanced rotary valve introduced by Mr. Edward Butler, of Gleneldon Road, Streatham, London, England, controls both the functions of induction and exhaust of the gases to and from the motor; and further, as may be seen in the illustrations, can be used for two or three cylinders, thus dispensing with two or three sets of valves and gearing as ordinarily used