any material changes in the mode of carrying on the telegraph service, numerous minor improvements have been effected, which have enabled the department to afford increased facilities to the public, and in many cases materially to lessen the cost of working. Of these the principal have been the further application of the system of 'duplex' telegraphy, and the more general use of the so-called 'sounder' instrument—a form of apparatus greatly in favor in the United States."

There has again been a large increase in the rental from private wires, the sum having risen from about £47,000 to about £53,000, or about 12 per cent.

IMPROVED SCREW-PROPELLER.

By J. E. WILSON, Brazoria, Texas.

Figure 1, side view of a vessel and the new propeller. Fig. 2, plan of the under side thereof.

Consists in the combination of a screw-propeller having a graduated pitch of its thread or blades from the front toward the rear of the vessel, with a recess, box, or chamber having a graduated or enlarged area from its front toward its rear.

A hull of vessel having a V-shaped even keel, B. In the after part or stern of the hull, and between the forks or

IMPROVED SCREW-PROPELLER.

branches of the keel, is a chamber, *a*, which inclines upward from the junction of the branches with the stem of the keel, so as to enlarge the area or water-way of said chamber from its front toward its rear end, which is open, as is also its under side. C is a screw-propeller, hung and revolving in the chamber *a*.

The propeller is as follows: Upon a central shaft, *b*, are constructed the threads *c*, the pitch of which is gradually spread from front to rear, so as to correspondingly enlarge the water-way between them from front to rear.

The object of the spreading of the screw from front to rear is that the succeeding threads or coils shall not work in the broken water of the preceding thread, coil, or turn of the screw.

The author states that the graduated spread of the screw should be from twenty-five to thirty per cent increase; or, say in a propeller of two and one half feet in diameter, the space between the first two turns of the thread or screw may be four and three quarter feet, the next space five and one quarter feet, the next six and one half feet, and so on.

The chamber, *a*, is enlarged in area from front to rear, so that as the vessel settles by the stern, by the raising of the bow, which occurs in loading the vessel, the rear of the screw will have abundant clearance or water-way, so as not to impede the action of the screw.

The object attained by the combination of a continuously-expanding screw-thread with a continuously-expanding chamber is twofold: first, that the succeeding turn of the thread may not turn in the whirl created by the preceding turn; or, in other words, that every portion of the thread may work in differently-moving water, or water not broken up by the preceding thread into a whirl corresponding with the next thread, and that the chamber or water-way may furnish the requisite volume of water to the propeller, which receives and throws it off at a continuously varying angle in relation to the shaft.

Two rudders, *d e*, may be used, one at each termination of the forks or branches of the keel.

The screw may be constructed with a single or double thread.

IMPROVED WATER-METER.

IMPROVED WATER-METER.

By B. HUBER, Brooklyn, N. Y.

FIGURE 1 is a section of the meter taken on line *xx* of Fig. 2. Fig. 2 is a plan view, and Fig. 3 is a section of Fig. 2 on line *yy*.

A circular tube, of flat, flexible material, arranged on level bed B, with the inlet at C, and outlet D, so that the roller E will be carried beyond the inlet before it escapes from the influence of the discharging fluid, the inlet being so constructed, by being made narrower or being fastened down to the bed-plate under the discharge, and for a little distance beyond, that it does not rise as high by the fluid as the discharge does, so that the roller passes smoothly and surely over the inlet and discharge. The tube is made of three layers of flexible material, *a*, *b*, and *d*, the two upper ones, *a* and *b*, being cemented together at the outer and inner edges *f*, and *b* being cemented at the middle of the under side to the bottom layer, *d*, to secure it in position, and at the same time allow of the inflation of the tube by the fluid. The bottom layer forms a portion of the tube at the inlet *e*, and the rest of it forms an elastic rest for the layers *a b* above, and it affords a simple means of attaching the tube to the bed, be held down by the cover which is to inclose the tube and receive the fluid, and form the packing for the cover.

The roller is pivoted to a centre stud, G, by a stem, H, with an eye in it, and this stem serves for driving the recording mechanism by turning a wheel above by means of a crank-pin, J, extending down from the side of the wheel in front of the stems.

Two rollers may be used on one stem, the latter being extended on the opposite side of the pivot.

NEW GAS-MACHINE RETORT.

By T. VAN KANNEL and TOWSLEY, Cincinnati.

FIGURE 1 is a vertical section. Fig. 2, plan. Fig. 3, adjustable damper-sleeve.

Relates to that class of gas-machines wherein a light hydrocarbon is brought to a vapor of high pressure by heat, which vapor forces up and fills the gasometer by emerging

NEW GAS-MACHINE RETORT.

from a small jet which draws in and mixes therewith a given quantity of air.

A is the main housing or shell, inclosing a double coil of spiral pipe, B, which has within it another double coil of spiral pipe, C, the two being of such relative size as to allow a space between them, which space is occupied by water. These pipes have one end protruding below, and the other above, the shell, A. The pipe B is closed by caps, D D', which are to allow pipe C to pass through.

The inner pipe, C, thus has a through-passage, while the outer one has not.

The pipe B, or its lower cap, D, is tapped at *d*, to receive a pipe which communicates with a regulating and indicating valve, whereby the increased pressure of water in the coil will shut off the gas which heats said water, and *vice versa*. The upper cap, D', is tapped to receive a steam-gauge, and this opening also serves to replenish the coil with water when necessary. The inner pipe, C, leads below to the oil-tank, kept under pressure by water or otherwise, and is supplied with a valve or stop-cock for shutting off this communication when it is so desired. The upper end of pipe C leads first to the mixing-valve, and then to the gas-holder. In the centre, vertically, is seen a section of pipe, E, which is firmly screwed within shell, A, and within pipe E is seen sleeve F, which may be raised or lowered, and is kept in position by its elasticity and pressure against the interior of pipe E. This constitutes a chimney for the escape of the heated air, smoke, etc., and just below the shell, A, receives another pipe, G, through an opening, which conducts pure air to the burners, H H. An inverted convex and concave disk, I, is placed between the sleeve, F, and the pipe G, having two large openings surrounding the burner-tips. At J is seen an opening closed by a plug, through which a taper may be applied to burners H.

The operation is as follows: The space between the two coils having been filled with water (except a small space left for steam), this compartment is put in communication with the pressure-gauge and heat-regulator valve. This valve is to be so adjusted that when the water or steam has attained a pressure of ten pounds, or other given degree, to the square inch, the gas which gives the heat is partly shut off, so that the water-pressure never rises above a given degree. The amount of heat is sufficient to change the gasoline in pipe C into a vapor of sufficient pressure to elevate the gas-holder as above mentioned.

The arrows show the air-currents as they supply the burners. As the air enters below, it can only move to the burners through two large openings surrounding them. As the heat passes up it touches every side of the coil, and descends near and around the damper-sleeve, F, which it enters and passes out of. Thus the pure air, on entering, has no chance to mix with the carbonic-acid gas which descends around the damper, F, while the hot air is given a complete circulation, thus heating every part of the coil.

When the escape of heat is too free, the damper can be lowered; when the reverse, then it is to be raised, giving freer escape to the heated air.

IMPROVEMENT IN CAR-WHEELS.

By W. H. PAIGE, Springfield, Mass.

THE object is to form a railway-car wheel of wrought metal, or having the side plates and tire of wrought metal, and secured together by spinning or turning the parts one over the other, and dispensing with much of the heavy and expensive forging or casting.

Figure I. is a plan view of the inside of one of the plates attached to the tire, and prepared to receive the hub. Fig. II. is a plan view of the inside of the other plate separate from the tire, and Fig. III. is a central vertical section of the wheel as finished.

IMPROVED CAR-WHEEL.

A represents one of the side-plates of a car-wheel, the centre of which is punched through at the dotted lines radiating from the centre, as shown in Fig. I., and the parts inclosed between these dotted lines are then turned back, when heated, firmly against the inner face of the plate, forming the triangular parts *e*. This renders that portion of the plate at the centre, for one third its area, of double thickness, and forms a polygonal hole in the centre, as shown clearly in Fig. I. A hub, *f*, having a hole therein in which to insert the axle *h*, and of a form to fit the central hole in the plate, and having an annular flange, *g*, is then inserted from the outside, and the plate and hub being heated to the desired degree, a washer, *c*, is placed over the inner end of the hub, *f* (the washer being also heated, if desirable), and swaged down firmly against the parts *e*, as shown clearly in section in Fig. III. This swaging of the washer, *c*, into its proper place may be done by hammering, while the hub, plate, and washer are heated; but I should prefer, as a cheaper and more expeditious process, to place the outer end of the hub in a die or bed of the proper form to receive it, with its inner end uppermost, the hub having been previously inserted into its place in the plate, and swage the washer, *c*, down firmly against the parts *e*, and the washer and hub will then be held firmly in place, and the hub, if it should require it, may be given its proper interior form afterward, by boring or otherwise. Each side plate is treated in like manner, and, when secured in the plates, the hubs nearly or quite touch at their inner ends, when the plates are secured to the tire, as shown in Fig. III. An annular channel, *i*, is made in the tire—one on each side for each plate—with an annular projection, *a*, formed just outside of it, and the plates A and C are made of a diameter to just fit into their respective channels, and when the plate is inserted therein the projecting metal at *a* is turned in over the edge of the plate all around. This may be done by a hammer, or the wheel may be placed upon a rotating disk or platform, and a rotating movement being given to the platform and wheel, the metal at the ridge *a* may be pressed upon by a roller with sufficient power to force the metal of the ridge *a* over and upon the edge of the plate firmly enough to hold the plate perfectly tight and secure. If the channel *i* were made scalloped, as shown at *i'*, or even in a more serrated form, and the plate made of a corresponding form, the latter might be less liable to work loose; and to make the plate stronger at the periphery, it may be reinforced with an additional strip welded on near the edge, or the edge turned over and back against the plate if desirable. The tire may have a steel tread, secured either by welding or by any other desirable and convenient means which will prevent the tire from wearing as fast as it might otherwise do.

APPARATUS FOR THAWING FROZEN WATER-PIPES.

By T. J. SLOAN, New-York.

IN northern latitudes, where buildings are supplied with water from street-mains, much trouble, inconvenience, and expense is caused by the freezing of the water-pipes, the ordinary remedy being to dig up the street and thaw out the pipes by heat externally applied. This device is intended to save all such trouble. It consists of a flexible pipe, constructed with a suitable outlet-nozzle, and having a spiral or screw thread formed upon its outer surface by means of a wire appropriately coiled on the said pipe, so that when the nozzle is inserted in the water-pipe to be thawed, and an axial or rotary motion given to the aforesaid flexible pipe, the latter will screw itself along to bring the nozzle in due contact or relation with the ice. Hot water is then introduced within the flexible pipe, and the ice is quickly melted.