RAILWAY TRAIN LIGHTING.

INTRODUCTION BY PRESIDENT SCOTT.

A gentleman whose whitened hair indicated that he has passed his three-score years and ten, recently gave me a most interesting account of his wedding journey some fifty years ago from Western Pennsylvania to Philadelphia. It was a story of travel on stage coaches and canal boats for nearly a week. The particularly impressive point was the change which has taken place in the mode of travel, not only in speed but in comfort and convenience. We take it as a matter of course that our trains are not only to be comfortable and convenient in their various appointments, but that they are to be replete with the luxuries of the drawing-room and the parlor, the dining room and the sleeping apartment. Those of us who are in early or middle life may know nothing of the stage coach, but we can easily recall some of the earlier conditions of train equipment, for it has been only a few years since three or four oil lamps which did little more than make visible the outlines of the interior of a car, were replaced by systems of gas lighting.

The electric light is in many respects the ideal light for train illumination. The light is brilliant, it may be generously distributed in small units, it contributes little to the heating and nothing to the vitiation of the air, it is under easy control and in emergency or accident there is not the liability to cause fires that is possessed by oil or gas.

The electric problem is in one sense a very simple one—a small number of lamps such as are found in an ordinary residence or office is to be supplied by current. On the other hand, the problem of supplying the necessary current to these lamps is a pecu-

liarily intricate and difficult one. The only practical source of current is a generator from which the current must come either directly or through a storage battery. The simplest equipment is probably the storage battery located upon each car, which is charged or replaced at stations or lay-over points. The arrangement is comparable to the electric automobile except that the demands upon the train battery are not subject to the severe and irregular service which falls to the lot of the automobile battery. The arrangements for the charging of the batteries are apt to be, to say the least, somewhat inconvenient and expensive and the battery itself may be of a considerable weight, if it is to be in service for long periods without recharging.

If an engine-driven generator be placed upon the train, it may receive steam from the locomotive, or the engine may have its own fuel supply. Dependence upon steam supply from a locomotive is not easily practicable if a continuous supply of current is to be obtained, nor does a generating plant upon a single car of a train, even if it have its own fuel supply, allow the ready shifting of cars and making up of trains, unless there be a storage battery auxiliary. A generating unit upon each car is apt to be expensive and add to the general complication of the equipment.

A generator driven from the car axle by the motion of the train involves the operation of an essentially constant voltage machine from a variable speed drive having wide and irregular variations, as well as periods of rest. The problem, therefore, is a most difficult one as the supplying of a small amount of energy to a few lamps cannot by our present methods of converting energy be conveniently effected from any available source.

The fact that current for train lighting is obtained by one means or another demonstrates the facility which inventors and engineers possess for overcoming difficult problems, and it also emphasizes the value attached to electric light. The fundamental difficulty lies in the fact that the available methods of transforming energy and of storing electrical energy are so cumbersome and inadequate. The very difficulties are an appeal for new methods, for simple and efficient methods of transforming energy from its abundant and convenient sources into the desired form of electrical current. The motion energy of the train is almost infinite compared with the meagre amount of energy required for a few glow lamps, but apparatus for transforming, regulating and storing that energy is complicated and costly. The chemical energy contained in a few pounds of coal would be

ample for the evening lighting of a whole train, could it be efficiently transformed into electrical energy. An ice machine by which the heat in a pail of water could be abstracted in the form of electrical energy, would illuminate a car during a long journey as a lump of ice was being frozen.

The problem of train lighting is of general interest, aside from the specific interest which there is in following the details of systems by which the illumination may now be accomplished. It indicates the admirable adaptation of electricity through the incandescent lamp for contributing to the safety, the convenience and the luxury of travel. It presents most peculiar and exacting conditions with respect to the supplying of current which do not render our present sources of current readily applicable. And it further shows the inadequacy and the limitations of our present methods of transforming energy and the possibilities which await scientific investigation, discovery and invention in unexplored fields.