theory, had stood for centuries, without exhibiting any symptoms of failing.

Mr. SCOTT RUSSELL had always found a difficulty in applying, practically, Professor Moseley's theory, and he did not see clearly, from the diagrams before him, what determined the relative proportions of the distance of the line of resistance, from the intrados and from the extrados, in any given case. It must be evident, that if the stones were incompressible and of infinite strength, then the distance would not exist: in fact, the masses would turn upon each other at their edges, or points of contact: but in practice, and taking into consideration the strength of materials, it was of importance to ascertain the point to which the line of resistance could approach towards the intrados, in order to know how much of the intrados would split off, on the opening of the joint at the extrados. He thought these points could only be ascertained by careful experiments, on a large scale, to which also might be applied the formulæ given by Mr. Snell, in order to test their accuracy.

Mr. SNELL observed, that the published results of experiments, already made on various building materials, would, he supposed, suffice for the determination of most questions, with as much accuracy as was required by the engineer, who would of course be careful not to consider the material to be of too great strength; but would make sure that it was twice, or three times, as strong as was shown by theory to be requisite.

APPENDIX I.

ART. I. On the determination of the centres of gravity of surfaces, required in the application of the problems, in the preceding articles.

This subject is treated in a simple elementary manner in Professor Moseley's '*Illustrations of Mechanics*,' Articles 140 and following, and is fully discussed in his '*Mechanical Principles of Engineering and Architecture*,' Articles 20 and following, and formulæ for calculating the centres of gravity of different figures, are given in the latter and other works.

The author of this paper used a very simple apparatus, by the aid of which, the centre of gravity of any shaped surface, representing the section of a material of uniform specific gravity, may be found with great accuracy. The principle upon which the method is founded, is treated of in '*Moseley's Illustrations of Mechanics*,' Art. 141, and this is merely a more accurate method of applying that principle, than any there proposed.

The apparatus consists of an upright rod, with a centre line drawn down it; this rod is fixed to a stand, on three screw legs, so that the centre line can be adjusted to a vertical position, as indicated by a plummet; a few holes are drilled in this centre line, and a peg, with a needle at its end, is turned to fit these holes. A piece of cardboard must be cut to the shape of the surface, whose centre of

gravity is required, and the centre line of the rod being adjusted, and the peg with the needle being placed through one of the holes, the card mould must be pushed on to the needle, so as to be suspended from it, care being taken, that the hole made by the needle is sufficiently large, to allow the card mould to hang freely upon it; the peg must then be drawn back, until the mould touches the rod, and marks must be made at the points, where the centre line of the rod meets the card, at the upper and lower edges. Then a line drawn through the point of suspension, parallel to a line drawn through these two points, will pass through the centre of gravity.

Then suspend the card in a similar manner, from another point in it, when it will take up another position; the vertical line drawn through the point of suspension will also pass through the centre of gravity, but the only point through which each of the lines passes is their point of intersection; therefore this is the centre of gravity.

If the mould is suspended from a third point and the vertical line is drawn through the point of suspension, this line will also pass through the point of intersection of the other two lines, if the former operations have been correctly performed: this third, or checking, line should always be drawn.

ART. 2. The tediousness of a separate calculation, or experiment, for every separate portion of the arch under consideration, may generally be avoided by a method that the author has used in the figures illustrating this paper.

The example, Plate 31, will best illustrate this method: it will there be seen, that a scale has been drawn, by which the position of the centre of gravity of any portion of the arch, from 1 to 90 degrees, may be found; that scale is thus obtained:—

Find by calculation, or by experiment, the centre of gravity of one portion of the arch, or, for instance, of 10° of the arch.

Mark this centre of gravity: then; to find the centre of gravity of 20° —mark the centre of gravity M, of the portion of the arch 10 degrees in length, between joint 10° and joint 20° from the crown; then a vertical line from the centre of gravity of 10 degrees to A, will represent the direction of the resultant of the weight of the first 10 degrees; and a vertical line MB, from the centre of gravity of the next 10 degrees to B, will represent the resultant of the weights of the second 10 degrees. Draw the horizontal line connecting these two lines; then the resultant of these two forces will act vertically through a point C, whose position in the horizontal line is such, that the length CB, is to the length CA, as the pressure at A, is to the pressure at B; but the pressure at A, equals the weight of 10° , and the pressure at B, equals the weight of 10° , therefore the length CB, equals the length CA, and the centre of gravity is somewhere in the vertical line through C; but it is also in the radius 10° from the crown, for if the portion of the arch was so turned, that the radial line 10° was vertical, it is evident, that the portion 20° of the arch would balance on a joint, in that radial line; the point of intersection of these two lines is therefore the centre of gravity required.

To check the accuracy of the work, draw the horizontal lines, $(CG\ 10^\circ) E$, and ML; draw a vertical line DF, joining these two lines, and find in it some point, E, such that the length ED, is to the length EF, as the weight of the portion from 10 degrees to 20 degrees is to the weight of the first 10° . In this case the weights of these two portions are equal, and therefore ED, is equal to

EF; then a horizontal line through E, will pass through the centre of gravity of 20°; for if the arch be turned round so that the lines (CG 10°) E, and ML, are vertical, these lines will represent the direction of the resultant of the weights of each 10 degrees of the arch, and the horizontal line through E, will then be vertical and represent the resultant of the weight of the whole portion 20°.

In like manner, to find the centre of gravity of 30°, the line CG 20 A2, represents the resultant of the weight of this 20 degrees of the arch; R 10 B2, represents the resultant of the weight of the portion of the arch between 20 and 30 degrees. Divide the horizontal line A2 B2, into 3 parts; make A2 C2, equal to 1 part, and C2 B2, equal to 2 parts; the centre of gravity will be in the vertical line drawn from C2, and also in the radial line 15 degrees, and the point of intersection is the centre of gravity of 30 degrees of the arch. The horizontal lines being drawn as above described, will check the accuracy of the work, the centres of gravity are thus determined for 10, 20, 30, 40, 50, 60, 70, 80, and 90 degrees of the arch; from which a scale may be constructed to determine the centres of gravity of any number of degrees of the arch. Such a scale is constructed in Figure 1.

APPENDIX II.

THE CONDITIONS OF THE STABILITY OF THE ARCH OF THE PONT-Y-TU-PRYDD.

The memoir of this structure by Mr. T. M. Smith, M. Inst. C.E., read before a meeting of the Institution, in the year 1838, and the plates accompanying that paper, are the authorities for the sections and dimensions used in the following analysis.

Plate 38 represents a transverse section through the crown of the arch, and a longitudinal section through the centre of the roadway. The three circles in the haunches, represent cylindrical openings through the whole width of the bridge. From the plates accompanying the memoir, it appears, that the soffit of the arch is formed of stones about 1 foot 6 inches deep, rough hewn, and set in mortar composed of Aberthaw lime; the arch-stones on the faces are 2 feet 6 inches deep, and are apparently roughly dressed.

Whether the construction of the arch is such, that the soffit will not fail unless the facings, or quoin-stones, yield, or whether the soffit will crack, or bulge, and so fail, even if the quoin-stones remain stable, are questions of practical experience, which the author will not discuss, but will proceed to show the application of the problems of the preceding paper, upon the former hypothesis.

The plate represents the application of the problem, in Sections 2 and 3, on the supposition that the soffit and quoin-stones will yield together; the effect of the parapet walls, on the stability of the structure, will then be the same, as if the materials composing them were laid equally over the whole width of the bridge, as represented by the dotted line A a. The bridge widens at the haunches, and this will cause the positions of the centres of gravity, of the different portions of the structure, to differ from those of the surface of the section; however, if the stones were taken from the extra width and were piled on the roadway, as shown by the dotted line A D, then, although the positions