12 February, 1889,

SIR GEORGE B. BRUCE, President,
in the Chair.

(Paper No. 2363.)

“Some Canal, River, and other Works, in France, Belgium,
and Germany.”

By LEVESON FRANCIS VERNON-HARCOURT, M.A., M. Inst. C.E.

ON the way to the International Inland-Navigation Congress, held at Frankfort-on-the-Main, in August 1888, the Author had an opportunity of inspecting some works in France and Belgium, as well as various others in the neighbourhood of Frankfort visited by the Congress. These works are almost all of quite recent date; and the Author thinks that brief references to them, besides possessing the interest of novelty, will serve to illustrate the progress being achieved by neighbouring nations, and to indicate the variety of works that may be easily visited during a brief tour abroad, which also comprised regular attendance at all the sittings of the Congress.

HYDRAULIC CANAL-LIFTS.

Plate 6, Fig. 1.

Fontinettes Lift.—This lift is situated about two or three miles from the St. Omer station, on the railway between Calais and Lille. It was designed to supplement a flight of five locks on the Neuffossé Canal, which connects the North Sea ports with Paris, as the trade along this canal has so much increased that the chain of locks is incapable of accommodating the traffic.

The lift, designed by Messrs. Clark, Standfield and Clark, for surmounting a difference of level of 43 feet, consists of two counterbalancing troughs, each resting on a central hydraulic ram, thus resembling in principle the Anderton lift designed by Mr. Edwin Clark.¹ The Fontinettes lift, however, is considerably larger than its prototype, as it accommodates barges of 300 tons, instead of only 100 tons: its troughs are 129 feet 7 inches long, 18 feet 4½ inches broad, and contain 6 feet 6¾ inches depth of water; and

¹ Minutes of Proceedings Inst. C.E., vol. xlv. p. 107.

its cast-iron rams have a diameter of 6 feet 6 $\frac{3}{4}$ inches, in place of the 3-foot rams at Anderton. The addition of a layer of 16 inches of water in the upper trough supplies an ample surcharge for overcoming the resistances, and effects the descent of this trough and the ascent of the other; and since the trough descends into a dry pit, from which the water in the lower reach is shut off by a lifting-gate, as at the entrance to the upper reach, the trough does not lose weight by immersion at the end of its descent, which is an important improvement on the Anderton arrangement. Accordingly, in theory, the surcharge introduced into the top trough would suffice to complete the whole operation; but a turbine has been provided, turned by a flow of water from the upper reach, which works a pair of hydraulic engines with accumulators. The first raising of a trough was thereby effected; and the accumulators serve to compensate for leakages in the presses, work the pump for keeping the pits dry, lift the counterbalanced gates at the extremities of the troughs and reaches, and turn the capstans placed on the quays at the entrances to the lift. The machinery is situated in a building erected in the space between the two trough pits. The upper part of the building provides a dwelling for the men working the lift; whilst at the summit, a look-out cabin contains the levers of the valve-machinery for controlling the motion of the lift. The troughs are maintained in position by central guides, sliding in grooves in the main building and side-towers adjoining the middle of the troughs. In order to prevent any swinging round of the troughs, guides have been placed at each side of the up-stream ends of the troughs, sliding against cast-iron plates let into the masonry pier supporting an aqueduct which, spanning a railway, connects the lift with the upper reach of the canal. Dimensions and other figures relating to this lift, furnished to the Author by Mr. Lyonel Clark, the Resident Engineer, are given in Appendix I.

The adjoining pair of gates, at each end of a trough and at the extremities of the canal-reaches, are locked together previous to being lifted, so that they may be raised simultaneously by chains from the frames erected at the extremities of the lower reach and the aqueduct, and thus dispense with frames over the ends of the troughs. This arrangement had led to a curious accident at the time of the Author's visit. Owing to the failure of the cast-iron presses at Anderton in 1882, the Fontinettes presses were made of weldless steel coils, with internal copper lining;¹ and the packing

¹ Minutes of Proceedings Inst. C.E., vol. lxxx. p. 401; and *Le Génie Civil*, vol. iii. p. 176, and vol. vi. p. 101.

was made of caoutchouc, with copper to protect it on the side next the ram. A portion of the copper packing having been torn away, a considerable leakage occurred from the southern press when the trough was at the top, and its gate locked to the adjoining gate of the aqueduct. The trough consequently descended, leaving its upper gate suspended above; and, the water flowing out, the southern trough no longer counterbalanced the other. New packing had been inserted at the time of the inspection; but it leaked so much at first that, though the full trough was raised up to the top by two hours' direct pumping into its press from the hydraulic machinery, it was unable, in descending, to raise the empty trough near enough to the top to regain its gate. On a second attempt, however, just before the Author's departure, when the packing had been made tighter by the water-pressure, the empty trough was raised sufficiently high that, by the aid of props built up inside, it was enabled to recover its gate.

During this stoppage of the lift, the traffic had to be passed through the chain of locks, and was consequently delayed. The lift was constructed by the Société des Anciens Établissements Cail; it was opened for traffic in 1887, and has passed a large number of boats, the time of passage being about twenty minutes.

Louvière Lift.—This lift is situated in Belgium, close to the Louvière station on the railway between Mons and Namur, near the centre of the coal and iron industries of that flourishing little country. It is the first of a series of four lifts to be placed on a length of 5 miles of the new Canal du Centre, in course of construction, for connecting the waterways near Mons with the waterways of Brussels, Charleroi, and Liège. The difficulties, hitherto, in the way of connecting the Condé Canal at Mons with the Charleroi and Brussels Canal, have been a difference of level of about 293 feet in the 13 miles to be traversed by the new canal, 217 feet of which have to be surmounted in the last 5 miles, and a great scarcity of water; but these difficulties are being overcome by the construction of four lifts on the steep section of the canal, with rises of from $50\frac{1}{2}$ to $55\frac{1}{2}$ feet, which can be worked with a very small expenditure of water. The lift at Louvière has been constructed as a test of the system: it is situated at the upper extremity of the canal furthest from Mons, so that, though connected with the adjacent Charleroi and Brussels Canal, it at present leads merely into a cul-de-sac below. As, however, the working of the Louvière lift has proved perfectly satisfactory, the other three lifts, each rising $55\frac{1}{2}$ feet, are to be undertaken at once, as well as the completion of the canal, some of the works of which

with the locks and side-ponds, in the section between Mons and Thieu, skirt the railway on the left-hand side from Mons towards Louvière. On the completion of this canal, Mons will be placed in direct communication by water with Brussels, as well as with Charleroi and Liège; and these towns will obtain direct access by water, through the Condé, and other canals, to the north of France and Paris.

The Louvière lift resembles in its main features the Fontinettes lift, for its troughs have nearly the same area (141 feet by 19 feet), and the rams the same diameter (6 feet 6 $\frac{3}{4}$ inches) (Plate 6, Fig. 1).¹ The difference of level, however, surmounted is 50 $\frac{1}{2}$ feet, as compared with 43 feet at Fontinettes; and the depth of water in the troughs is 7 feet 10 $\frac{1}{2}$ inches, in place of 6 $\frac{1}{2}$ feet, as they were designed to receive vessels of about 400 tons, making the total weight lifted 1,037 tons, instead of 785 tons. The lift was designed by Messrs. Clark, Standfield and Clark, and Mr. Lyonel Clark is the Resident Engineer, as at Fontinettes; but the Contractors were the Société Cockerill of Seraing.

The figures in Appendix II, furnished by Mr. Lyonel Clark, give additional particulars relating to this lift; and a comparison of Appendixes I and II indicate the main differences between this lift and its predecessor in France. The guides at Louvière slide against light wrought-iron lattice towers at the centre and each end of the troughs. These towers support a footway round the top of the lift; and spiral staircases inside the towers give access to the footway from the quay, and to the central cabin at the top, from which the working of the lift is controlled. A system of interlocking prevents the working of the lift till the gates are in place and everything ready, an arrangement which is also in operation at Fontinettes. A wrought-iron aqueduct, crossing over an adjacent high road, connects the upper reach of the canal with the lift. The hydraulic machinery and quarters for the attendants are contained in a building at the side; and the machinery is worked by two turbines with horizontal axes, on the Girard system, turned by the fall of water from the upper reach. The presses are constructed of cast-iron enclosed in continuous coils of weldless steel: their packing is simpler and more efficient than at the Fontinettes lift; and the dryness of the lift-pits indicates the watertightness at the presses and the lifting-gates. The actual time occupied in raising a trough, as timed by the Author, was two

¹ The illustration is drawn from one of a series of photographic views of the lift taken by Mr. Lyonel Clark.

and a half minutes. A barge can be conveyed from a point on the canal about 100 feet from the lift, placed in the trough, lifted, taken out, and conveyed a similar distance away in nineteen minutes; so that six barges of 360 tons (the size proposed to be accommodated) could be passed through the lift, three each way, in an hour. The lift appeared to work satisfactorily in every respect; and the Author, having stood on one of the troughs while it was being raised, can testify to the regularity and ease of the motion. Altogether, the Louvière lift exhibits a decided improvement on the Fontinettes lift; and the Belgian Government may be congratulated on the boldness with which it has entrusted the working of this important link in the canal system of Belgium to a series of four lifts, which, to judge from the results achieved at La Louvière, appears likely to be fully justified.¹

WEIRS ON THE MEUSE AND THE SAMBRE.

A short stay at Namur enabled the Author to visit the weirs on the Meuse above and below that town.

Weirs between Namur and Liège.—All the weirs below Namur are needle weirs, on the Poirée system,² furnished with an arrangement, invented by Mr. Kummer, a Belgian engineer, for releasing the needles. The bars along the top of the frames on the upstream side, for supporting the needles, have one extremity hinged to a frame, whilst the other end is held in place by a vertical spindle on the adjacent frame, so formed that by giving it a quarter of a turn the end of the bar is released, and, revolving on its other extremity, sets free the set of needles resting against it,³ which are subsequently recovered by a rope passing through iron eyes attached to each needle. A long, solid overfall weir, with its masonry sill parallel to the stream, is placed between two bays of the needle weir, situated consequently at two different points of the river, one adjoining the lock, and the other further down stream to the extent of the length of the overfall weir. This overfall is a necessary adjunct to the needle weirs, in order to

¹ Further particulars and illustrations of these lifts are given in *Le Génie Civil*, vol. vi. p. 101; "Engineering," vol. xl. pp. 29, 101, and 103, and vol. xlv. p. 201; "Mittheilungen über die Hydraulischen Schiffselevatoren," von Carl Fréron, Frankfurt a. M., 1888; and "The Engineer," vol. lxi. 1888, p. 514, and vol. lxxvii. 1889, pp. 28, 76 and 82.

² Minutes of Proceedings Inst. C.E., vol. ix. p. 30.

³ *Ibid.*, vol. lxii. p. 375; and *Annales de l'Association des Ingénieurs sortis des Ecoles spéciales de Gand*, vol. ii. p. 119.

provide for changes in the discharge of the river, and to prevent a sudden flood from submerging the foot-bridge on the frames of the needle weir before the weir-keeper is able to release the needles. The river is being enlarged for a little distance below Namur to facilitate the passage of floods, which are liable to inundate parts of the town. A new lock, of large dimensions, has accordingly been constructed, on the right bank, at the first weir below Namur; and the site of the old lock is being converted into an extension of the weir. All the weirs on the river between Namur and Liège have been constructed on the above system; and at the weir at Liège two locks have been provided for the navigation, and also a basin at the side, in which vessels can take shelter from floods or floating ice.

Weirs above Namur.—Above Namur, the weirs consist of a combination of the Poirée and Chanoine systems; for whilst needles are used for closing the navigable pass, shutters are placed across the shallower passes.¹ In the earlier weirs on this part of the river, shutters were placed across the whole weir; but the raising of the last shutters proved difficult, and the closing of the weir caused abrupt variations in the water-level. Accordingly, in the later weirs, and in deepening the navigable passes of the existing weirs, needle weirs have been substituted for shutters across the navigable passes. The shutter weirs in these cases, with their large butterfly-valves, serve for regulating the discharge of the river, and for preventing the submergence of the needle weir, and enable a solid overfall to be dispensed with; but, on the other hand, the shutter weirs are more subject to injury than the needle weirs, and are also more costly, when provided with the requisite adjunct of a footbridge on movable frames.

Weir on the Sambre.—The lowest weir on the Sambre, at Namur, just above its confluence with the Meuse, consists of three bays separated by masonry piers; and it is closed by the primitive arrangement of letting down long timber balks horizontally, kept in place at each end by grooves in the piers, which are raised again, for opening the weir, with chains by aid of winches on the piers. The adjacent lock is of very small width, and appears quite inadequate to accommodate properly the traffic on the river.

THE GILEPPE RESERVOIR DAM.

Plate 6, Figs. 2 and 3.

Dolhain Station, near the Belgian frontier, is only a short journey from Liège; and the Gileppe dam is only about half an

¹ Minutes of Proceedings Inst. C.E., vol. ix. p. 33.

hour's drive from the station. This masonry dam was constructed in 1867-75 across the deep, narrow, rocky valley of the River Gileppe, to form a reservoir for supplying the cloth manufactories at Verviers with water (Plate 6, Fig. 2). The dam is one of the highest in existence, for it retains a head of water of $147\frac{3}{4}$ feet, being only a few feet lower than the Furens and Villar dams,¹ and somewhat higher than the Vyrnwy dam,² the first masonry dam in England, where, though the head of water retained will not exceed 86 feet, the maximum height of the dam exposed to water-pressure amounts to about 132 feet, owing to the depth of the surface of the rock below the upper porous stratum. The dam is a fine piece of masonry work, well executed; but the roadway and footpaths along the top, with a total width of $49\frac{1}{2}$ feet, exhibit a superabundant strength, which is continued all the way down, imposing an unnecessary pressure on the base (Plate 6, Fig. 3). It compares unfavourably in this respect with the Furens dam across the valley d'Enfer in France, which approximates very closely to the theoretical section, having been given a width of $18\frac{3}{4}$ feet at the surface of the reservoir, and a width of 164 feet at the bottom level of the reservoir, in place of the 216 feet width at the base of the Gileppe dam, although the maximum head of water retained at Furens exceeds the head at the Gileppe by $16\frac{1}{2}$ feet. The possibility, however, of raising the Gileppe dam 33 feet higher at some future time was contemplated, in which case its base would approximate to the theoretical width. The dam has been given a convex form towards the reservoir, which adds to its strength; and the masonry has been carried into the solid rock both at the base and sides. A certain amount of infiltration has occurred along the lower portion of the central part of the dam, accompanied with the oozing out of a little of the lime, which has formed a sort of scale on the down-stream face of the dam; but, though this face is wet, its solidity does not appear to have been affected. The dam, as viewed from the valley below, is somewhat dwarfed in appearance by the colossal lion at the top, which affords a deceptive comparison of size.

The reservoir was full of water up to the sills of the by-washes when the Author saw it; and at this level it has an area of $197\frac{2}{3}$ acres, and contains about 16,000,000 cubic yards of water.

¹ Minutes of Proceedings Inst. C.E., vol. lxxi. p. 379.

² Sections of the four dams here referred to, drawn to the same scale, are given in the article "Water-Supply" of the *Encyclopædia Britannica*, 9th Edition, vol. xxiv. p. 407.

Two by-washes, 82 feet wide, formed in the rock beyond each end of the dam, provide for the discharge of the floods of the River Gileppe; and the road is carried over these by-washes on low bridges, as the road is $6\frac{1}{2}$ feet above the sills of the by-washes. The cast-iron conduits for conveying the water-supply have been carried through the solid rock, on each side of the valley, about 250 feet beyond the ends of the dam.¹

THE RIVER MAIN BETWEEN FRANKFORT AND MAINZ.

Plate 6, Figs. 4 and 5.

Canalization of the River Main.—Till quite recently, the traffic up to Frankfort by water was comparatively inconsiderable, and had to be carried on by small barges; for the longitudinal training works on the left bank, and the cross jetties along the right bank had only secured a depth of 3 feet of water at the low stage of the river. The canalization, however, of the Main from its junction with the Rhine at Mainz up to Frankfort, a distance of about 22 miles, commenced in 1883 and completed in 1886, has given a minimum depth throughout of $6\frac{1}{2}$ feet, enabling vessels to get up to Frankfort, and has thus entirely transformed the navigation of the river. This has been effected by the erection of five locks and weirs, the lowest of which is situated a little above Kostheim, about 2 miles from the mouth of the Main, and the one furthest up stream at Niederrad, 2 miles below Frankfort. These two locks have a lift of 8 feet 10 inches each, and the three intermediate locks have each a lift of 5 feet 11 inches, making the total average rise from the Rhine to Frankfort, at the low stages of the rivers, 35 feet 5 inches (Plate 6, Figs. 4 and 5). The river has also been dredged in several places where deficient in depth; and a rocky reef has been removed from its bed at Frankfort.

The works at the junction of each of the reaches into which the Main has been divided below Frankfort, comprise: (1) a lock on the left bank, constructed in a side cut; (2) a fish-ladder in masonry between the river embankment of the lock and the weir; (3) a needle weir across the main portion of the river, divided into two or more bays by masonry piers; and (4) a pass for rafts of timber, adjoining the right bank, closed by a drum weir.

¹ A full description, with illustrations, of the Gileppe dam is given in the *Annuaire de l'Association des Ingénieurs sortis de l'École de Liège*, 2nd series, vol. v. p. 281, and vol. vi. pp. 268 and 421; and an abstract of these articles will be found in *Minutes of Proceedings Inst. C.E.*, vol. xlviii. p. 312.

Locks on the River Main.—The locks have been provided with a long approach channel, separated from the main river by an embankment; they are 279 feet long between the gates, affording an available length of 246 feet for vessels; and they are $34\frac{1}{2}$ feet wide. The sills of the locks have been placed 8 feet $2\frac{1}{2}$ inches below the water-level retained by the weirs, although the minimum depth of the river is only 6 feet 7 inches, in order to allow of a further deepening of the bed of the river, in the event of the minimum navigable depth of the Rhine being increased to $8\frac{1}{4}$ feet, by the erection of a lock and weir between Bingen and St. Goar, where, occasionally, in times of drought, the depth falls to 5 feet. The locks on the Main have been designed to accommodate the steamboats navigating the Rhine, which are 246 feet long, $32\frac{1}{2}$ feet broad, and can carry up to 1,300 tons of cargo when the state of the river admits of their maximum draught of 7 feet 10 inches. Vessels of from 700 to 1,000 tons can now go up to Frankfort. Provision has been made, in forming the side channel, to allow for elongating the locks at a future time, by placing a third pair of gates 920 feet lower down, to enable a train of barges with a tug to be locked in one operation. The upper pair of gates of the locks, together with their adjoining side walls and quays, have been raised above flood-level at all the locks except Flörsheim, so as to be always under control, and to prevent a rush of water through the lock in flood-time; and the lock-keeper's house, which is placed at the same level, is connected with them by a high embankment, so that he has always access to the upper gates with their machinery.

Needle Weirs on the River Main.—These weirs, which stretch right across the river, from the lock on the left bank to the timber pass on the right bank, are divided into bays by masonry piers; and one of these openings in each weir (from $154\frac{1}{2}$ feet to $193\frac{1}{2}$ feet in width) serves as the navigable pass for vessels in flood-time, when the lock is submerged and the weir open; and its sill is 10 feet 2 inches below the water-level retained by the weir. The remainder of the weir has its sill 2 feet higher, as it only serves, when open, for the discharge of the flood-waters. The weir at Niederrad, near Frankfort, has four openings,¹ with a total width of $526\frac{1}{4}$ feet; the weirs at Höchst and at Kostheim have each two equal openings of $193\frac{1}{2}$ feet, giving a total width of 387 feet; the weir at Okriftel consists of two openings of $177\frac{3}{4}$ feet, making a total width of $355\frac{3}{4}$ feet; and the weir at Flörsheim, in addition to two similar

¹ The openings at the Niederrad weir consist of two bays of $142\frac{3}{4}$ feet, one of $154\frac{1}{2}$ feet, and one of $87\frac{1}{4}$ feet in width.

openings, has a third opening of $181\frac{1}{4}$ feet, affording a total width of about $537\frac{1}{2}$ feet.

These weirs have been constructed on the Poirée system,¹ with iron frames hinged at the bottom, and wooden needles in which the Kummer modifications have been introduced; and, therefore, they are precisely similar to the needle weirs on the Meuse described above. The long overfall weirs, however, which adjoin the needle weirs on the Meuse, have been dispensed with, as the drum weir across the timber pass can be used to regulate a sudden flood till the needles can be released, and also acts as an

FIG. 1.

DRUM WEIR ON THE MAIN.

Scale $\frac{1}{80}$.

overfall for adjusting small variations of level. The leakage also between the needles, aided here and there by their accidental or intended displacement, provides an outflow for the summer discharge of the river.

Timber Passes with Drum Weirs.—The timber passes consist of a channel, from 656 feet to 1,312 feet long, and $39\frac{1}{2}$ feet wide at the bottom, formed between the right bank and an embankment in the river, and closed at the upper end by a drum weir (Fig. 1). The sill of this weir is 5 feet 7 inches below the water-level maintained by the weir; and the bed of the channel has been formed to a slope

¹ Minutes of Proceedings Inst. C.E., vol. lx. p. 30.

of 1 in 200 down-stream. Timber rafts can at any time be floated through these passes by opening the drum weir, which is about in a line with the needle weir, but separated from it by the embankment.

The drum weir consists of an upper and an under paddle, capable of making a quarter of a revolution on a horizontal axis between the paddles at the level of the sill of the weir. The

FIG. 2.

DRUM WEIR ON THE SPREE AT CHARLOTTENBURG.

Scale $\frac{1}{80}$.

upper paddle closes the weir, when vertical; and the pressure of the water on the under paddle regulates the working of the weir, by a see-saw arrangement of sluice-gates opening or closing; the communication between the drum, in which the under paddle revolves, and the upper and lower reach respectively. The weir is, in fact, precisely similar in principle and action to the drum weirs established by Mr. Desfontaines on the River Marne many years ago, described in the Author's Paper on "Fixed and Movable

Weirs;"¹ but it differs from them in having only a single paddle for closing the weir, 39½ feet wide, stretching right across the opening for the timber pass, instead of consisting of a series of paddles only 4 feet 11 inches wide each. The height, also, of the upper paddle of the drum weirs on the Main has been made 5 feet 7 inches; whereas the upper paddles on the Marne weirs are only 3 feet 7½ inches in height. The drum weirs on the Main, accordingly, mark a distinct extension of the system to larger dimensions; and these weirs had previously been exclusively confined to the Marne.²

A still larger drum weir, however, has been erected recently on the River Spree at Charlottenburg (Fig. 2); for the upper paddle, closing the navigable pass, is 32 feet 9½ inches wide, and 9 feet 8½ inches high; the sill of the weir is only 2¼ feet above the bed of the river, and the head of water retained is 9 feet 2¼ inches.³

Cost and results of Canalization of the Main.—The works were carried out by the State at a cost of £275,000, on the understanding that the town of Frankfort would carry out important works for improving the commercial capabilities of the port. Some details of the cost are given in Appendix III. The navigation of the river is free; and no tolls are charged for passing through the locks.

The increased depth of the river, aided by the improvement of the port, has produced a very remarkable development in the trade going up the river to Frankfort; for, whereas the traffic coming up to the port, in the last two years before the carrying out of the works, amounted to only from 10,000 to 11,000 tons, it rose in 1887, the first year after the completion of the works, to 250,000 tons; and it has been estimated that it would reach between 400,000 and 500,000 tons in 1888, having attained 200,000 tons in the first half of the year. The traffic between Frankfort and places above it has not shared in this increase, being unaffected by the improvement of the river, and appears, indeed, to have somewhat

¹ Minutes of Proceedings Inst. C.E., vol. ix. pp. 36 and 58, and Plate 3, Figs. 3 and 4.

² Additional details of these works will be found in "Zeitschrift für Bauwesen," Berlin, 1888. Text, p. 19, and Atlas, Plates 14 to 17; "Die Canalisirung des Mains von Frankfurt a. M. bis zum Rhein;" and Annales des Ponts et Chaussées, 6th series, vol. xv. 1888, p. 931. The works have also been briefly referred to in Minutes of Proceedings Inst. C.E., vol. lxxxviii. p. 501, and vol. xcii. p. 444.

³ "Zeitschrift für Bauwesen," Berlin, 1886. Text, p. 338, and Atlas, Plates 31 and 32.

decreased; but the exports from Frankfort, both up and down the river, though much smaller than the imports, have also experienced a remarkable increase since the completion of the works, for they rose from 1,900 tons in 1885 to 7,100 tons in 1886, and to 46,600 tons in 1887. This wonderful rise in the river traffic is the more satisfactory as it is not due to a diversion of trade from the railways to the river, brought about by the expenditure of public money for which no charges are levied, for the railways have also shared in the increase of traffic. Thus the increase of traffic on the river has been accompanied by an augmentation of 36 per cent. in the railway traffic, showing that, under certain conditions, the improvement of inland waterways, even when in a position to enter into competition with railways, may so develop the trade of a district that the railways largely benefit by the increase of prosperity effected by their apparent rivals.

PORT OF FRANKFORT.

Plate 6, Fig. 6.

The port of Frankfort consists of quays along both banks of the river through the town, and of a haven for vessels to take refuge in from floods and floating ice, which is also used for commercial purposes. The formation of the haven, and an extension of the quays have been carried out by the town of Frankfort, in fulfilment of an agreement entered into when the State undertook the improvement of the Main (Plate 6, Fig. 6).

Quays.—The quays extend through the town, almost continuously, along each bank of the Main, above the disused Main-Neckar railway bridge crossing the river beyond the lower end of the town, and have a total length of nearly 3 miles. The recent extensions consist of 492 lineal yards of the Obermain quay and 547 yards of the Untermain quay on the right bank, and 558 yards of the Deutschherrn quay on the left bank, at a total cost of £27,590. The quays on the right bank adjoining the town are provided with railway accommodation throughout, with additional sidings in some places; but the quays on the left bank are not in communication with the railways, with the exception of the new quay for heavy goods below the Main-Neckar bridge. This new quay, extending along the left bank of the Main between the Main-Neckar and Staats railway bridges, 1,160 yards long, is mainly used for a coal depôt: it is provided with sidings alongside the river, with travelling hydraulic cranes, with overhead tram-roads

on which small trollies run for distributing the coal, and with sidings on the land side of the pens, in which the coal is stored, communicating with the railways.

Haven at Frankfort.—The haven has been formed on the right bank of the Main, just below the Main-Neckar bridge, by an embankment, about 580 yards long, in the river, parallel to the shore, and raised above flood-level, thus enclosing a basin, 1,740 feet long and 246 feet wide, permanently open only at its lower end for the entrance of vessels, which are sheltered in it during high floods, and against floating ice in the winter (Plate 6, Fig. 6). It has been excavated to a depth of 9 feet 2 inches below the lowest water-level, so that vessels may remain afloat in it when the Niederrad weir is open; and it has a depth of $16\frac{3}{4}$ feet below the ordinary water-level retained by the river. An entrance has been formed at the upper end for facilitating traffic in ordinary times, furnished with a pair of gates which can be closed when required. Quays have been formed round the haven, 580 yards in length along the embankment, and 908 yards along the shore, which have been provided with sidings; and one large warehouse has been erected, together with some sheds, space being left for the erection of four more warehouses when required. The quay along the shore has been furnished with hydraulic travelling cranes, capstans, and traversers for shifting the wagons. A telescopic grain-elevator, for lifting the grain from the hold of a vessel and discharging it into sacks, has been placed on the quay, and can be moved along rails the whole length of the quay between the warehouses and the haven. The warehouse, having six floors and a basement, is separated into three blocks: it has a total length of 328 feet, and a width of 87 feet. It is provided with lifts; and a large grain elevator projects over the quay, from the centre of the front of the building, by which grain can be raised direct from the vessel, and can then be distributed to various parts of the warehouse by aid of travelling bands and shoots. These machines are all worked by hydraulic power; and provision has been made for using the same power for working the gates closing the upper entrance to the basin, and the swing-bridge across the entrance connecting the lines of way on the embankment with the mainland. Sidings on the far side of the warehouse communicate both with the lines along the quays of the right bank, and also with the main lines, and are connected with the sidings in front of the warehouses by traversers.

The cost of these works, together with the quays, sidings, and depôts on the opposite bank, amounted to £315,800; so that, with

the extension of the quays above, the town has spent nearly £350,000 in the improvement of the port. The works of the haven and quays had, since 1878, been carried out by Mr. W. H. Lindley, M. Inst. C.E., Engineer to the town of Frankfort.¹ The works on the right bank were completed in 1887, and those on the left bank in 1888.

The success which has attended the works of improvement of the Main, and of the port of Frankfort, must be in a great measure attributed to the position occupied by Frankfort, which is now the eastern terminus of the river traffic along the Rhine. The River Main above Frankfort, from which the town formerly derived the greater portion of its traffic, is in communication with the Danube through the River Regnitz, a tributary of the Main, and the Main-Danube canal which joins the River Altmühl, a tributary of the Danube; but the depth is inadequate between Frankfort and Bamberg, on the Regnitz; and the remainder of the route is impeded by numerous small locks and a deficiency of water in the canal, and by a low water-level or a rapid current in the rivers as far as Ratisbon on the Danube. The traffic, accordingly, along this route is very small; but these impediments, though stopping the extension of inland navigation in this direction, have the advantage for Frankfort of leaving it at the head of the river trade towards the east.

New Passenger Station at Frankfort.—Whilst the river and port have been improved, the railway companies have not remained idle; for the Author, on his arrival at Frankfort, in August, 1888, entered the new station there on the day of its opening. This central station has replaced the three small terminal stations of the Main-Weser, the Taunus, and the Main-Neckar lines (Plate 6, Fig. 6), and has also been placed in communication with the lines to the east of the town. The covered portion is 610 feet long and 551 feet broad, with a glazed arched roof in three spans, resembling three Cannon Street stations side by side, with iron columns for the intermediate supports. The station receives eighteen lines of way, and has a grand central entrance-hall containing the various booking-offices, handsome large side passages leading from the hall to the various waiting-rooms, refreshment-rooms, &c.; and a wide space beyond, between the offices and the ends of the lines, leads to the several platforms. The whole building is very tastefully designed and decorated; and the main station and its approach lines are illuminated at night by electric arc-lights; whilst the offices,

¹ Full details of these works, with illustrations, are given in "Beschreibung der Frankfurter Hafenanlage," by W. H. Lindley, 1888.

rooms, and passages are lighted with glow-lamps. Lifts have been erected at suitable places on the platforms; so that the luggage, which is conveyed along underground passages, can be raised to the vans, or lowered and removed, without interfering with the passengers or blocking up the platforms. The electric lighting and the working of the lifts are effected by the aid of hydraulic machinery, situated in a handsome building, surmounted by a dome, on the right bank of the Main near the Niederrad weir. Steam-engines in an adjacent building generate the hydraulic pressure, which is stored by two large square accumulators, from whence it is transmitted to the dynamos, for producing the electricity, which are placed nearer the station. The station and accessory works cost altogether £1,750,000; but a considerable portion of this expenditure will be repaid by the sale of the lands previously occupied by the stations and railways, which penetrated further into the town. The Author considers that the station, both in its design, general arrangements, and details, is an excellent model of what a station ought to be, with the exception of the platforms, which being, according to the usual continental plan, nearly on the level of the rails, render the getting into and out of the high carriages so inconvenient. Also vehicles are not admitted into the station; but this inconvenience is to a great extent obviated by the arrangements for the luggage.

Sewage Disposal Works at Frankfort.—The town of Frankfort no longer pollutes its river with its sewage; for works have been constructed by Mr. W. H. Lindley, on the left bank of the Main, about a mile below Niederrad weir, for separating the solids and purifying the effluent. The sewage on its arrival is mixed with alum and lime; and, being passed through a series of underground tanks, the solids are precipitated and settle down, and the liquid portion is clarified. The purified effluent is then restored to the river; and the sludge is pumped up into two open tanks above ground, and is either used upon the adjacent land, or prepared for manure. The sewerage of the town was commenced in 1867; the greatest progress was made between 1872 and 1878; and the works were completed in 1886, when a detailed account was published by Mr. Lindley.¹ The works have had a remarkable effect on the health of the town; for whereas, up to 1874, typhus was very prevalent in most years, the number of cases diminished rapidly in the next three years; and the maximum percentage since 1875 has never reached the minimum of the previous twenty-five years.

¹ "Beschreibung der Enterwässerungs-Anlagen der Stadt Frankfurt-am-Main" von Stadtbaurath, W. H. Lindley, 1886.

PORT OF GUSTAVSBURG.

Plate 6, Fig. 7.

The Hessische Ludwigs Railway Company, owning the line between Mainz and Frankfort, has not quietly awaited the possible diversion of its traffic by the canalization of the Main, but has hastened to improve the port of Gustavsburg on the right bank of the Rhine, opposite Mainz, just above the confluence of the Main (Plate 6, Fig. 7). New basins have been constructed, with railway sidings alongside the quays which have been amply provided with cranes, sheds, and other appliances for facilitating trade. The quays have been formed of timber platforms resting upon piles driven into the pitched slopes surrounding the basins, and have been so laid out as to provide a considerable length of quays in proportion to the water area. The fan-like form of the sidings, also, is very advantageous for the traffic. The railway company is endeavouring, by these increased facilities, to forestall some of the traffic which might otherwise go up to Frankfort by water; and there appears to be a good amount of trade in the port.

PORT OF MAINZ.

Plate 6, Fig. 8.

Another port has been established at Mainz, a little lower down the Rhine than Gustavsburg, on the left bank just below the town, with a basin surrounded by quay walls, and a haven of refuge for vessels (Plate 6, Fig. 8). A large warehouse, in the form of a square, with a courtyard in the centre, has been built on a quay projecting into one end of the basin, so that it is surrounded by water on three sides. This warehouse has wine vaults in the basement, and several floors above; and side passages along each floor enable any division to be reached without passing through the others. Turrets, at each of the internal corners, contain winding staircases of communication to the several floors. The warehouse is furnished with lifts, cranes, and movable jiggers, worked by hydraulic machinery. It is a handsome building, though without undue ornamentation; and two smaller warehouses face it on either side of the basin. The extension of the river bank with quay walls in front, the construction of the basin, and the formation of the haven, cost altogether £380,000; and the warehouses, with the railway sidings on the quays, cost £65,000.

The depth of the Rhine has been improved along a shallow portion between Mainz and Bingen, by training works between Eltville and Oestrich, regulating and restricting the channel along each side of an island, and for some distance below, with longitudinal training works commenced in 1886.¹ The direction, as well as the depth, of the navigation channel has been thereby improved; and this reach is no longer an impediment to vessels.

PORT OF MANNHEIM.

Plate 6, Figs. 9 and 10.

Mannheim possesses the special importance of being at the southern limit of the large navigation up the Rhine, and therefore holds the position as regards the southern districts which Frankfort has endeavoured to secure towards the east. It is, moreover, well situated at the junction of the Rhine and the Neckar, affording it a long line of easily accessible water frontage along both rivers; and it possesses excellent railway communication with the interior. The course of the Rhine has been altered, at its junction with the Neckar, by cutting off a sharp bend, and training the prolonged channel of the Neckar to join the new channel of the Rhine, thus improving the course of the Rhine and the lines of confluence of the two rivers, and providing a large space between the old and new channel of the Rhine for the formation of basins and quays (Plate 6, Fig. 9). The accommodation for vessels provided by the port is indicated on the plan (Plate 6, Fig. 10), from which it will be seen that some basins between the two rivers supplement the river frontages for the purposes of trade, and, together with the old channel of the Rhine, afford a refuge for vessels from floods and ice. Railway accommodation is provided along all the quays; and ample sidings have been laid along the quays surrounding the Mühlau basin, and on the left bank of the Neckar. Numerous warehouses and sheds have been erected on the quays; and some of the warehouses are provided with grain elevators and travelling bands, as well as with other machinery for transporting and storing goods. The total length of wharfs and quays in the port, and along the Rhine and the Neckar, amounts to $4\frac{1}{2}$ miles.²

¹ Minutes of Proceedings Inst. C.E., vol. xcii. p. 445.

² Additional details about the port will be found in "Die Mannheimer Hafenanlagen, 1886," and statistics relating to its trade in "Jahresbericht der Handelskammer für den Kreis Mannheim für das Jahr 1887."

The training of the Neckar was commenced in 1864, and completed in 1873; the Mühlau basin and the central goods depôt alongside were commenced in 1870; and the Junction Canal, connecting the Mühlau basin with the Neckar, was constructed in 1875-78. Access to the upper end of the Mühlau basin is afforded by a lock, whose chamber is 315 feet long, and $34\frac{1}{2}$ feet wide; and the iron lock-gates close this entrance against floods and ice. A sum of about £965,000 has been spent in the last twenty-four years upon the works of the port. The training of the Neckar cost £88,700; the Mühlau basin and central goods depôt, £420,000; the Junction Canal, £52,100; the works along the river bank, £86,900; the sorting sidings, £108,100; and the extension of quays, new basins, and bridge, £120,000.

The traffic of the port of Mannheim has increased more rapidly than that of any of the other ports on the Rhine in recent years, having risen from 252,000 tons in 1856 to 583,000 tons in 1876, and to 1,796,000 tons in 1886. It is only exceeded by Ruhrort, below Düsseldorf, which, though having a much smaller import trade, has a much larger export trade than Mannheim. The joint trade, however, of Mannheim and Ludwigshafen, on the opposite bank, of 2,443,000 tons in 1886, very nearly equalled the 2,472,000 tons of Ruhrort; and as the trade of Mannheim has been increasing still more rapidly than the trade of Ruhrort in recent years, it is probable that Mannheim and Ludwigshafen together will soon be decidedly in advance of all the other ports on the Rhine. The prosperity of the port of Mannheim exemplifies, in a remarkable manner, the advantages of extending deep-water communication as far into the interior of a country as practicable; and the rapid growth of the river traffic, both at Mannheim and Frankfort, indicates the important position held by those ports which are situated at the extreme limits of large navigations.

Concluding Remarks.—In visiting the works above described, the Author was struck with the great industrial activity of Belgium, and the rapid development of inland navigation in Germany; the solicitude which the Belgian and German governments have exhibited for improving and extending the water-ways of their countries, and the eagerness with which the local authorities second these improvements, by enlarging their ports, and providing them with the most modern mechanical appliances for facilitating trade.

More attention appears to be paid on the Continent to the architectural features of buildings devoted to trade purposes, so that warehouses, and even engine-houses and buildings for hydraulic machinery, exhibit some pretensions to adornment. These advan-

tages, moreover, appear to be attained without undue expenditure by authorities whose whole object is the promotion of trade.

The Author considers that visits abroad indicate that English engineers cannot afford to relax their exertions in the way of progress, if they are to keep in advance of their professional brethren on the Continent; and that the extension of water-communication gives facilities for economical traffic, which English merchants must not neglect if they desire to retain the ascendancy of English trade.

The Paper is accompanied by several small scale drawings, from which Plate 6 and the Figs. in the text have been engraved.

APPENDIXES.

APPENDIX I.—FONTINETTES LIFT, NEUFFOSSÉ CANAL, FRANCE.

Trough:—			Metres.	Feet.	Ins.
Length			39·50	=	129 7
Breadth			5·60	=	18 4½
Depth of water			2·00	=	6 6¼
Press; copper internal cylinder, with exterior weldless steel coils:—					
Thickness of copper cylinder		Millimetres.	3	=	0·118
„ external steel coils			55	=	2·165
Length of press		Metres.	14·987	=	49 2
„ stroke (height of lift)			13·13	=	43 1
Pressure on press		Atmos.	25	=	442·5
Ram:—					
Thickness of cast-iron		Millimetres.	60	=	2·362
External diameter		Metres.	2·00	=	6 6¼
Total weight lifted, including trough, water, and ram			785 tons		
equivalent to a pressure of		Atmos.	25	=	442·5
The contents of one stroke in water			41¼ tons.		
equivalent to a surcharge on the trough of		Centimetres.	20	=	8
Actual surcharge used			88 tons.		
equivalent to a depth of water of		Millimetres.	400	=	16
Size of boats lifted			250 tons.		
Actual time of lift			5 to 7 minutes.		
Total time of passing one boat up and one boat down			20 minutes.		

APPENDIX II.—LOUVIÈRE LIFT, CANAL DU CENTRE, BELGIUM.

Trough:—			Metres.	Feet.	Ins.
Length			43·000	=	141 1
Breadth			5·800	=	19 0¼
Depth			3·250	=	10 8
Draught of water			2·400	=	7 10½
Breadth of free passage			5·200	=	17 0¾
Headroom under gates			4·250	=	13 11¾
Length of centre guides			7·768	=	25 5¾
„ end „			3·450	=	11 3¾
Ram; cast-iron:—					
Diameter			2·000	=	6 6¾
Thickness			0·075	=	0 3
Length			19·440	=	63 9½

Press; cast-iron, hooped with continuous steel weldless coils:—

	Metres.	Feet.	Ins.
Internal diameter	2·060 =	6	9
Thickness of cast-iron core	0·100 =	0	4
„ steel coils	0·050 =	0	2
Length of press	19·590 =	64	3½
Stroke	15·397 =	50	6½
Working pressure	32 =	469	

Two turbines and four pumps to furnish collectively 24 cubic metres (5,275 gallons) of water per hour under a pressure of 40 atmospheres = 569 lbs. per square inch.

Accumulator:—

	Metres.	Feet.	Ins.
Ram, diameter	0·500 =	1	7¾
Stroke	7·700 =	25	3

equivalent to 40 centimetres stroke of great rams.

Weight of trough, water, and ram 1,037 tons.

	Atmos.	Lbs. per sq. in.
equivalent to a pressure of	32 =	469

Weight of water in trough (depth 2·40 metres) 598 tons.

Normal working surcharge, 0·25 metre 10 inches = 62 „

Stroke of press equivalent to 48½ tons of water.

Size of vessels lifted 400 tons.

Actual time of lift 2½ minutes.

Total time, including entering and departure of barge 15 „

this comprises the lifting of one boat and lowering of another = 800 tons passed.

APPENDIX III.—CANALIZATION of the RIVER MAIN.

Cost of Weirs and Locks.

Name.	Land.	Needle Weir, Timber Pass, and Fish Pass (exclusive of Ironwork).	Lock.	Approach Channel to Lock.	Buildings for Attendants.	Ironwork for Needle and Drum Weirs.	Total Cost.
	£.	£.	£.	£.	£.	£.	£.
Frankfort .	9,350	22,715	14,455	14,995	2,150	1,615	65,280
Höchst . .	1,450	16,165	16,323	9,050	905	1,199	45,092
Okriftel . .	1,040	13,715	15,141	7,300	1,000	1,106	39,302
Flörsheim .	2,950	18,250	13,380	8,176	830	1,627	45,213
Kostheim .	1,010	16,783	14,465	9,630	1,022	1,220	44,130
Totals .	15,800	87,628	73,764	49,151	5,907	6,767	239,017
Averages	3,160	17,526	14,753	9,830	1,181	1,353	47,803

[DISCUSSION.

NOTE
Several of the Lines and Sidings and some of the Shoals on the (ways of the various Ports, have been omitted owing to the smallness of the Scales.