such as is used in sampling soils and clays. This consists mainly of two blades arranged to cut a 6-in. hole and so bent as to pick up the material each time. Sufficient amount of handle can be attached to enable a pile of nearly any depth to be thoroughly sampled. In this way uniform sections can be bored into a pile in several places and duplicate samples invariably check, showing that if the materials are put into the mixture, a correct sample of same can be obtained.

The following tests were made on four brands of about 1000 tons each. Four samples were bored from each bin with the sampler as well as a sample being drawn from the mill during the run of the entire lot. The brands being figured to the exact analysis, the slight overrun is evidently due to shrinkage.

	"12½-5" BRAND P ₂ O ₅ K ₂ O	"10-8" BRAND P ₂ O ₅ K ₂ O	"1-8-4" BRAND NH ₃ P ₂ O ₅ K ₂ O	"2-8-10" BRAND NH ₃ P ₂ O ₅ K ₂ O
	12.55 4.96	10.05 7.91	1.15 8.05 4.00	2.18 8.15 10.20
	12.42 5.10	9.92 8.08	0.99 8.18 4.16	2.01 8.10 10.20
	12.48 5.12	9.96 8.10	1.03 8.15 4.06	2.11 8.17 10.01
	12.63 5.00	9.93 8.04	1.13 8.02 4.06	1.96 8.18 10.14
Av. (Bored)	12.52 5.04	9.97 8.03	1.07 8.09 4.07	2.06 8.15 10.13
Mill sample (Not Bored)	11.96 4.66	10.67 7.83	1.10 8.50 3.60	2.16 7.80 10.30

On these "mill" samples it would be necessary to change the formula which would result in incorrect analyses, whereas the bored samples show that the piles actually run about as figured. Bad analyses on bored samples can invariably be traced to faulty mixing in which either wrong amounts were weighed in or the actual materials fail to analyze as figured.

In sampling bagged shipments, we believe that much more reliable information can be obtained as to their analyses by the use of the double tube sampling trier which is inserted into a bag, closed, and withdrawn, giving an exact section of the material therein.

If methods of sampling could be as rigidly enforced in the factory as in the laboratory, we believe that more dependable information would result.

The average factory chemist does not bestir himself sufficiently to see when samples are being drawn correctly and the average superintendent does not realize the importance of the small details in sampling, which have a vital bearing on the plant and its reputation for uniform analyses.

CHEMICAL LABORATORY, F. S. ROYSTER GUANO COMPANY
NORFOLK, VIRGINIA

A NEW SPECTRUM MAP PAPER

By R. P. ANDERSON

Received July 17, 1916

The method of mapping emission spectra which was suggested by Bunsen¹ has proven of value in the course in Opticochemical Methods at Cornell University as an aid in familiarizing the student with comparatively simple emission spectra. Bunsen's method consists in plotting the lines and bands of a spectrum on a millimeter scale, numbered to correspond to the arbitrary scale of the spectroscope. Each line or band is placed at the position on the scale that corresponds to its

position on the scale of the instrument, representing its width and intensity by the width and height, respectively, of the drawing.

The spectrum map paper here described differs from that ordinarily employed in that there is provided above each scale a cross-sectioned area one centimeter in height on which the maps are made, using the heavy line as the base line. The vertical lines of the cross-sectioned area are useful as guides in mapping spectrum lines, while the horizontal lines simplify the comparison of the intensity of lines and bands in different parts of the spectrum.

The spectra that are shown were mapped as an illustration of Bunsen's method as applied to this new map paper. The compounds employed were respectively: lithium carbonate, sodium carbonate, potassium carbonate, rubidium carbonate, caesium alum, calcium chloride, strontium chloride, barium chloride, boric acid, and manganese chloride. The spectra were produced in the usual fashion by introducing the sub-

stances into a Bunsen flame on a platinum wire. In the case of the chlorides of the alkaline earths, where rapidly shifting spectra are first obtained, the maps represent the fairly stable spectra that are produced after a preliminary heating of the chlorides on the wire.

This map paper can also be conveniently employed for the mapping of absorption spectra at different concentrations for the determination of the point of "minimum brightness" of the substance in solution.

The illustration shows a sheet of the spectrum map paper about one-third natural size. This paper is furnished by the Cornell Coöperative Store, Morrill Hall, Ithaca, N. Y., in packages of fifteen sheets, together with three sheets of millimeter cross section paper, at a cost dependent upon the price of paper. Until recently a package was sold for fifteen cents, postage prepaid, with lower prices on ten or more packages.

CORNELL UNIVERSITY, ITHACA, NEW YORK

¹ *Ann. der Phys. und Chem.*, **195** (1863), 10.