must find a thousand purposes for which it will carry its own recommendation. Dr. Kleiner's process was first noticed in June, 1886, and brought into its present practical prominence by Major Ricarde-Seaver, F.R.S.E., who, during some years, has given special scientific attention to the production of aluminum. We are indebted to his courtesy for the opportunity of visiting the works in Farringdon road, and thus giving the first public technical description of this interesting invention. The dynamos used are the Edison-Hopkinson, made by Messrs. Mather & Platt, Manchester, and for electrolytic purposes seem all that can be desired, although not specially built with that object.—*Engineering.*

A PLANT THAT DESTROYS THE TASTE OF SUGAR.

AN EXAMINATION OF THE LEAVES OF GYMNEMA SYLVESTRE.*

GYMNEMA SYLVESTRE (R. Br.) is an asclepiadaceous plant growing in the Deccan peninsula, from Concan to Travancore; it is also met with in Assam, and on the Coromandel coast, and is distributed in the continent of Africa. It is a stout woody climber, with long, slender branches.

The leaves are opposite, entire, from $1\frac{1}{2}$ to 3 inches long, and from 1 to 2 inches broad, elliptic or obovate, acute or cuspidate, rarely cordate at the base, membranous, thinly pubescent on both sides, the upper surface of a darker green than the lower. *Gymnema sylvestre* is mentioned in the non-official list in the Pharmacopœia of India (1868), and in Dr. Dymock's "Materia Medica of Western India." The powdered root has for a long time been known among the Hindus as a remedy for snake bites. In such cases it is applied locally to the part affected, and also taken internally in the form of a decoction. But the most curious circumstance connected with this plant was first noticed by Mr. Edgeworth, who discovered that by chewing some of the leaves it destroyed the power of the tongue to appreciate the taste of sugar. He found that powdered sugar, taken immediately after masticating some of the leaves, tasted like so much sand in his mouth, and this effect lasted for twenty-four hours. Dr. Dymock, reviewing this property, said he was unable entirely to confirm this statement. His experience was that sugar taken into the mouth after chewing the fresh plant had a saltish taste, but was still easily recognizable.

Some authentic leaves were procured by Mr. Lawson from Guindy Park, Madras, who placed them at my disposal for chemical examination. They had a bitterish astringent and slightly acid taste. After chewing one or two leaves, it was proved undoubtedly that sugar had no taste immediately afterward; the saltish taste experienced by others was due to an insufficiency of the leaf being used. Sugar in combination with other compounds in dietetic articles is plainly destroyed as to its taste after using these leaves. In gingerbread, for instance, the pungency of the ginger is alone detected, the rest is tasteless meal; in a sweet orange the taste of the sugar is so suppressed, and that of the citric acid consequently developed, that in eating it resembles a lime in sourness.

Among the several kinds of foods, drugs, and beverages which affect the palate, *gymnema* does not pretend to render them all tasteless; it does not affect pungent and saline things, astringents, and acids. It is limited to apparently two diverse substances, sweets and bitters. It has been noted that sugar taken after the leaf tastes like sand, so I have found that sulphate of quinine taken after a good dose of the leaf tastes like so much chalk. I am not going to propose its use in the administration of nauseous drugs, until the medicinal properties of the *gymnema* have been more studied, otherwise the quantity of the vehicle taken may prove to counteract the effect of the medicines. The experience of several friends as well as my own is that the effect does not last for twenty-four hours as stated, but for only one or two hours; after that time the tongue resumes its appreciation of all that is sweet or bitter.

The powdered leaves were submitted to the action of various solvents, and by this means it was ascertained that the peculiar property of *gymnema* leaves was dissolved out by alcohol, and, as it occurred in the aqueous extract of the residue, it was therefore soluble in water. As benzene and ether took from the leaves certain principles of the same appearance and weight, it was conceived that nothing would be gained by using both solvents; the preliminary extraction was therefore made with ether rectified from water and spirit. The ether extract consisted of chlorophyll and two resins separated by their solubility in alcohol. The resin insoluble in spirit formed the larger portion; it was soluble in chloroform, bisulphide of carbon, and benzene. It was elastic and tenacious, decomposed by warming with nitric acid, the product being precipitated with water; only partially saponified with caustic potash. Sulphuric acid dissolved it in the cold, giving a green solution. It seemed to consist principally of a neutral resin. The resin soluble in spirit was readily saponified with soda, and gave a permanent bluish-green color with sulphuric acid; like the former resin, it was of an acid nature, and left a tingling sensation in the throat.

The alcoholic solution of the leaves was almost entirely soluble in water; in fact, by treating the leaves separately by alcohol and water, 36.37 per cent. organic matter was extracted; by treating the drug with water alone, 36 per cent. was removed. By direct experiment it was found that in the former extract 0.47 per cent. was an acid resin similar to those found in the ether extract. The aqueous solution of the substances soluble in alcohol had a decidedly acid reaction; it gave no coloration with ferric chloride, showing absence of tannin. It was deepened in color with alkalies, but gave a bulky precipitate with sulphuric, nitric, hydrochloric, and acetic acids. It reduced Fehling's solution on boiling, and gave a cloudiness with Nessler, a precipitate with lead acetate, but none with tannin or picric acid. The precipitate caused by sulphuric acid was collected on a filter and washed till it ceased to give a cloudiness with barium chloride. It yielded a greenish powder, insoluble in water, but soluble in alcohol, ether, benzene, and chloroform. With potash, soda, and ammonia it afforded fine red solutions with orange colored froth, but they were both precipitated on the

addition of the mineral acids. It dissolved in concentrated sulphuric and nitric acids with intense red color, but in both mixtures it was destroyed and precipitated by water. It fused at about 60° C. into a blackish brittle mass. Heated in a test tube it gave off fumes of creosote, but no crystals were obtained in a subliming apparatus. Gently ignited, it burned with a bright flame, leaving no ash. It was thrown down as a bulky gray mass by acetate of lead; the lead salt decomposed by sulphureted hydrogen in water left the substance in the reddish evaporated filtrate from the lead sulphide.

The body just described has the characteristics of an organic acid related in some particulars to chrysophanic acid, but having some distinctly peculiar reactions, and possessing the anti-saccharine property ascribed to the leaves. I propose to call it *gymnemic acid*.

Gymnemic acid forms more than 6 per cent. of the constituents of *gymnema* leaves, in combination with a base which has not been isolated. Another organic acid was present in the lead acetate precipitate, which was identified as tartaric acid. The filtrate from the insoluble lead compounds was treated with sulphureted hydrogen gas, and the clear liquor after evaporation was examined for sugar. Glucose was detected in some quantity by its immediate and abundant reduction of Fehling's solution; the sugar examined in a polariscope had a left-handed rotation.

Chloroform agitated with an alkaline solution of the leaf left a crystalline residue of a brownish color; it had a bitter taste, and acted as a sialagogue. With the ordinary alkaloidal reagents it afforded colored precipitates, but was a neutral principle. Its further examination, together with that of *gymnemic acid*, is reserved for further investigation.

The leaves after being exhausted with ether and then alcohol were treated with water. The gum was detected and estimated in the usual manner. A carbohydrate, optically inactive, and, after boiling with acid, reducing Fehling's solution, was found in this extract.

Diluted soda removed a brownish liquid which consisted of albuminous matters only partially soluble in alcoholic and acetic acid. These were not weighed, but calculated by difference.

A solution of 1 per cent. hydrochloric acid was employed to remove the oxalate of calcium. A microscopical examination of the powdered leaves showed a fair sprinkling of the conglomerate crystals or raphides so well known to exist in rhubarb. The dilution of the acid menstruum rendered this process very tedious, so a stronger acid was used and the marc washed with it until ammonia produced no cloudiness. The collected liquors were allowed to deposit, the sediment was then collected on a filter, dried, and weighed; then incinerated and weighed again. The calcium carbonate was calculated into oxalate, and the difference between this and the first weighing was reckoned as pararabin. No oxalic acid was found in a free state.

The ash of *Gymnema sylvestre* is very high, a fact in accordance with the amount of lime salts it contains. Gentle ignition of the air-dried leaves left as much as 11.65 per cent., and about one-half of this was calcium carbonate. One hundred parts contained:

15.41 soluble in water.
78.71 soluble in acid.
5.88 sand and siliceous residue.

The cellulose was estimated by steeping the leaves in sulphuric acid of specific gravity 1.50 for 30 hours, washing, drying, burning, and deducting the ash; this result did not differ materially from the weight of the totally exhausted powder treated with chlorine water.

The following is a tabulated analysis of the powdered and sun-dried leaves:

Ether extract (chlorophyll and resins)	5.51
Alcoholic extract (<i>gymnemic acid</i> , tartaric acid, glucose, neutral bitter principle, resin, etc.)	19.50
Aqueous extract (gum 1.45 per cent., glucose, carbohydrate, and extractive)	16.87
Alkaline extract, by difference (albuminous and coloring matters)	8.15
Acid solution { calcium oxalate	7.64
{ pararabin	2.74
Ash (balance of)	5.69
Cellulose	27.86
Moisture	6.04
	100.00

CELLULOSE.

By R. B. GRIFFIN and A. D. LITTLE.

CELLULOSE is to the paper maker the substance upon which his whole art depends. In its purer form, as cotton or linen fiber, or the product of the different chemical wood pulp processes, it forms the basis of all that he produces, and associated with various chemical modifications of itself it has in the shape of ground wood made possible the present enormous production of cheap printing paper. In view of the great importance thus given to the subject, it is to be regretted that the chemistry of cellulose is as yet in a very imperfect condition. Much is merely hinted at, and much more probably is wholly unknown. In view of the present state of our knowledge, therefore, the writer will only touch upon the theoretical aspects of the subject, confining himself mainly to its well known chemical relations and reactions.

The physical features of the ordinary forms of cellulose are familiar to all paper makers. It is essentially vegetable in its origin, although it is said to have been found in certain of the lower orders of animals, in degenerated human spleen and in the brain. It occurs ordinarily in the shape of plant hairs or fibers, which vary in length and somewhat in other characteristics, as they are obtained from different sources. The cotton hairs appear under the microscope as long ribbons, thickened at the edges and twisting in all directions, while the purified fibers from certain dense woods are so short as to appear to the unaided eye as scarcely more than dust.

The most striking and valuable chemical property of cellulose is its remarkable indifference to nearly all chemical reagents, treatment which would cause the metals or even glass to dissolve having scarcely any effect upon it. It has, however, a powerful attraction for certain salts in solution, and water containing

them may be so filtered through a mass of cellulose as to have the dissolved salts completely removed. This attractive power is so strong in the case of vanadium compounds that cellulose will separate them from solutions containing only one part in a trillion.

Cellulose dissolves in a number of reagents, but in all cases except the one immediately to be mentioned it undergoes chemical change, so that the phenomenon is not one of simple solution. In Schweitzer's reagent, however, cellulose is readily brought into solution, and may subsequently be recovered without change of composition. This reagent is best prepared by dissolving freshly precipitated copper hydrate in strong ammonia. Under its influence cellulose, as in the shape of pure filter paper, softens, swells, and soon passes into a thick, sirupy solution from which, on the addition of acid, it is precipitated in dense flocks. A commercial process for waterproofing paper depends on the action of Schweitzer's reagent, which is allowed to remain in contact with the sheet long enough for the fibers to become superficially softened, in which condition they may be pressed into a continuous mass.

Cellulose belongs to the group of bodies known in chemistry as the carbohydrates, and which comprises in addition the sugars, dextrine, starch, etc. The relationship between these bodies is very close, and is made evident by a large number of reactions. Thus it is possible to form cellulose in the laboratory by the action of certain ferments on ordinary sugar, and it has been shown that in the case of the sugar cane the formation of cellulose is attended by a directly proportional decrease in the amount of sugar present; indeed, it is probable that, speaking generally, the formation of cellulose in living plants is due to the action of ferments on the sugar in the plant.

Strong sulphuric acid dissolves pure and thoroughly dry cellulose, and forms an almost colorless solution, which, on dilution with water and boiling, yields dextrine and glucose. Under the same conditions, starch acts similarly and gives the same products. With rather more dilute acid—one part water, four parts sulphuric acid—cellulose dissolves, and from the solution, on addition of a large amount of water, it is precipitated as amyloid, which dries to a horny mass, which is now attracting considerable attention in the arts. It forms the outer covering of the parchment paper now largely used for tying up the tops of bottles and preserve jars, and which is made by dipping ordinary unsized paper for a few seconds in sulphuric acid diluted with a quarter or more of its bulk of water. The paper is then washed with water containing ammonia, then with pure water, and will be found to have acquired a remarkable toughness and many of the properties of animal parchment. Concentrated solutions of zinc chloride effect similar transformations into amyloid and parchment paper.

The action of chlorine upon cellulose is of the utmost importance to the paper maker, and has been quite carefully studied. When chlorine gas is passed into water containing cellulose in suspension, the cellulose is rapidly oxidized, and the same effect is produced on heating cellulose with a solution of a hypochlorite as bleaching powder. The extreme effect of this treatment is to convert the cellulose into oxycellulose, a substance of very friable nature and containing more oxygen than ordinary cellulose. It is evident therefore that in bleaching cellulose care must be taken that the solution of bleaching powder is not too strong or the bleaching temperature too high. Oxycellulose can also be produced by the continued action of a comparatively small amount of bleach solution. If a mass of fiber should be saturated with the solution, then squeezed nearly dry and allowed to remain in the air for some time, it will be found that the fibers have lost their strength and become brittle through the formation of oxycellulose. The importance of thoroughly removing by washing or otherwise the last traces of chlorine from half stuff becomes self-evident in this connection. This forming of oxycellulose, however, even takes place, though only slowly, in the simple presence of light and air, and is the main cause of the deterioration of paper by age. In cases where resin size or much ground wood is used, this ageing is largely due to the action of the active oxygen or ozone in the air on the resinous and woody matter present.

Hydrocellulose is a body resembling oxycellulose in many properties and which has, with little or no occasion, attracted considerable notice in connection with the pulping of wood by the sulphite processes. Hydrocellulose, although generally retaining the form of the cellulose from which it was derived, is very brittle and easily acted upon by chemical reagents. It is formed by the long-continued action of certain dilute acids, as hydrochloric, at the boiling temperature. Many careful examinations of sulphite fiber have, however, failed to show any sign of this substance.

The action of nitric acid upon cellulose is peculiarly interesting, and has received important applications in the arts. The effect of the moderately strong acid is to form varieties of oxycellulose. As the strength of the acid is increased, however, and particularly when a mixture of nitric and sulphuric acids is employed, the cellulose is converted without change of form into compounds of nitric acid and cellulose, known as gun cotton, pyroxyline, etc. Certain of these nitrates dissolve in a mixture of alcohol and ether, the resulting solution being widely used under the name of collodion by photographers and surgeons. These nitrates explode with great violence under proper conditions, but when wet can be handled with such freedom from danger that gun cotton when manufactured on the large scale is commonly freed from adhering acids by washing in an ordinary rag engine.

Unless carefully made and thoroughly washed, there is great liability that gun cotton will explode spontaneously, and to show how near one may come to living on a volcano without realizing the fact, it is worth mentioning that in the early part of the century a process was employed commercially in France for the manufacture of wood pulp, which consisted in dissolving the incrusting matter of the fiber by treating the chips with strong nitric acid. The process was conducted in great stoneware jars, and yielded quite good pulp for the times, but was finally abandoned on account of cost and difficulty of working. In such a process there was, of course, though unknown at the time, great danger of forming explosive nitrates of cellulose.

By special treatment and incorporation with camphor

* A paper read at a meeting of the Nilgiri Natural History Society, Ootacamund, by David Hooper, F.C.S., March 7, 1887.—*Nature.*

gun cotton is converted into celluloid and zylonite, both of which are now widely used as substitutes for ivory, tortoise shell, coral, etc.

Caustic soda and caustic potash, when in dilute solution, do not readily attack cellulose, even on boiling under considerable pressure. Cotton wool heated to 160° C., with a concentrated solution of caustic potash, dissolves completely, and under the conditions observed in the manufacture of wood pulp by the soda process a portion of the cellulose is dissolved, together with the incrusting matter.

The effects of heat alone upon cellulose are noteworthy. At temperatures between 100° and 160° C. cellulose is slowly decomposed, with gradual elimination of the water with which it was chemically combined. A sample of perfectly pure and dry pulp will therefore slowly continue to lose weight under prolonged heating, and this fact has doubtless given rise to many controversies regarding the dry weight of shipments of wood pulp.

Under the influence of a considerably higher degree of heat than those mentioned cellulose, if protected from the air, decomposes into a variety of acid, tarry, and gaseous products, leaving a residuum of carbon and charcoal.

Cellulose is rapidly acted upon by water at temperatures below 200° C., being converted into dark brown products, mainly insoluble. Wood chips are similarly affected at temperatures below 150° C., becoming, in the presence of water alone, badly burned and brittle.

The decay of cellulose in nature, where it generally occurs associated with other bodies, as woody tissues, is greatly hastened by the action of a ferment occurring in sewage and in fertile soils. Under this action cellulose is rapidly decomposed into carbonic acid and a marsh gas.—*Paper Trade Jour.*

DETERMINATION OF NITROGEN IN COMMERCIAL FERTILIZERS.*

By B. B. ROSS and L. W. WILKINSON.

At a meeting of official agricultural chemists held in Washington, September 1 and 2, 1885, the committee on nitrogen reported that the samples sent out by the committee were so few and meager and the discrepancies so large as to make it inadvisable to recommend any method for the determination of nitrogen for use during the next season, and recommended that the entire report of the last committee be referred, without further action, to the next committee on nitrogen. The new committee, in accordance with the report referred to, sent out other samples during the present year, with specific instructions to be followed in determinations according to the Ruffe method, the one proposed by the committee for adoption by the association. Nitrogen was also determined in the same samples, for the purpose of comparison, by the soda lime and the Kjeldahl methods. As these determinations were made with great care, the results are believed to be of sufficient interest to justify their publication.

The reagents used in the Ruffe method consisted of standard solutions of sulphuric acid and caustic potash, one-fourth normal; soda lime crushed, one-half in form of powder, and one-half granular; sodium hyposulphite, commercial, fused, water-free, and powdered; finely powdered charcoal and flowers of sulphur, equal parts by weight; and cochineal solution as an indicator. The combustion tube was twenty inches in length and one-half inch in diameter.

The samples used for analysis were represented to consist of Nos. 1 and 2, ordinary commercial fertilizers containing nitrogen, No. 3, a rather superior sample of cottonseed meal, and No. 4, a nitrate mixed with sugar.

Careful analysis of the chemicals used in the Ruffe method showed them to contain a small percentage of nitrogen, which is allowed for in the following results:

Results according to the Ruffe Method.

	(a.)	(b.)	(c.)	Average
No. 1. Nitrogen found	1.83½	1.86	1.85	1.8483
No. 2. " " " " " " " " " "	2.15	2.16½	2.15	2.1541
No. 3. " " " " " " " " " "	7.66½	7.57½	7.35	7.53
No. 4. " " " " " " " " " "	3.45	3.39½	3.35	3.3983

Results according to the Method with Soda Lime.

	(a.)	(b.)	(c.)	Average
No. 1. Nitrogen found	1.84	1.85	1.85	1.845
No. 2. " " " " " " " " " "	2.05	2.12½	2.15	2.0875
No. 3. " " " " " " " " " "	7.25	7.27½	7.26	7.2625
No. 4. " " " " " " " " " "	2.10	2.12½	2.10	2.0875

Results according to the Kjeldahl Method.

	(a.)	(b.)	(c.)	Average
No. 1. Nitrogen found	1.85	1.85	1.85	1.85
No. 2. " " " " " " " " " "	2.17½	2.17½	2.17½	2.17½
No. 3. " " " " " " " " " "	7.33	7.33	7.33	7.33
No. 4. " " " " " " " " " "	3.45	3.45	3.45	3.45

From eight to ten hours' digestion with sulphuric acid was required in the Kjeldahl method, and about three-quarters of an hour for distillation, making it long and tedious. No. 4, consisting of sodium nitrate and sugar, yielded totally unreliable results, and is omitted. The quantity of material sent was too small to allow of other determinations.

The above determinations show the uniform and satisfactory results obtained by the Ruffe method, and commend it to the favorable consideration of agricultural chemists especially.

RESIN GAS FOR IRON MAKING.

MR. H. C. FREEMAN, Alto Pass, Illinois, lately referred to an iron melting operation with gas, about thirty years ago, in Newark, New Jersey. Messrs. Bowen had a malleable iron foundry in that city, and, requiring very pure fuel for melting the pig metal (which was Salisbury, Conn., iron), they abandoned coal and substituted gas made from resin, which could then be had for about 50 cents a barrel. This fuel they used for several years, and, I think, up to the time of the war, when the advanced price compelled abandonment. The method of use was extremely simple. At the base

of the furnace was arranged a sheet iron hearth, about four feet wide in front, nearly horizontal, and descending a little under the furnace. A man sat in front of the hearth and fed the resin with his hands, strewing it broadly over the hearth. The resin was broken to the size of one inch diameter and smaller. The downward radiated heat volatilized it.

A NEW METHOD OF MANUFACTURING CYLINDRICAL GLASS OBJECTS.

MR. A. OPPERMANN, of Belgium, has recently patented a new and very ingenious method of manufacturing cylindrical glass objects, of any section whatever—the word cylinder being taken in its widest acceptation, and also designating a solid or hollow prism, and, indeed, even a plane sheet in the special case in which the directrix of the cylinder is reduced to a straight line. The most interesting, or, at least, the most immediate, application is in the manufacture of hollow cylinders of circular section, called "muffs" in the language of the trade, and which, when split lengthwise and spread out in a furnace, give the sheet glass used in windows.

Every one knows the system that has been employed from time immemorial for producing the muff by blowing. In Mr. Oppermann's system, this blowing, with all its preliminaries and its multiple operations, which require numerous and experienced workmen, is entirely done away with. The principle of the method is that of drawing a mass of glass in a vertical direction through the aid of a mould of any form corresponding exactly to the section of the cylinder to be obtained. This mould is immersed in the molten glass, and an upward motion is given to it. The glass, in consequence of its cohesion and of its adherence to the mould, follows the latter in its ascensional motion, and forms a vertical sheet whose base is fixed, while the upper part rises with the mould itself.

The term mould is not exactly accurate; the device should be understood as a solid body—either of metal or refractory earth—whose lower face is a representation of the horizontal section of the cylinder with vertical generatrices.

GLASS DRAWING MACHINE.

Let us suppose a certain quantity of glass of the desired degree of fluidity to be contained in any receptacle whatever, and its free surface to be at rest and perfectly horizontal. If we lower the solid body in question until it touches the molten glass, and enters it to a certain depth, the glass will adhere to the parts that are in contact with it. If the body to whose face the glass adheres be then raised, the glass will be carried along in the ascensional motion, and the portion lifted will cool and solidify, and, performing of itself the office of mould for the rest of the bath, will carry along with it another portion of the glass, and so on, until the vessel is empty.

It will be understood that each point of the face of the mould gives rise to a vertical generatrix of the glass cylinder, and that, on varying the form of the face, cylinders of all forms may be obtained. If the mould touches the surface of the glass in the direction of a straight line, the cylinder will be reduced to a plane, and the operation described will give a sheet of glass. If the face is circular, the product will be a muff.

The principle of drawing has been applied for some time to the manufacture of glass rods and tubes. But the drawing in this case is in a horizontal direction, and is capable of producing nothing but objects of small dimensions.

During the formation of the cylinder, the parts of the glass carried along must, in measure as they leave the mass, cool and harden to the point necessary to allow them to carry along other portions of the glass in their train. Cooling through the surrounding air will sometimes be sufficient, and this is the case with rods and tubes; but Mr. Oppermann prefers artificial cooling through a blowing machine. In the manufacture of a hollow cylinder, he thus has a means of introducing air into the interior of it. In this case the mould is provided with a clack that opens inwardly, in order that the air may freely fill the cylinder in measure with its increase in size. On the contrary, this clack closes as soon as the air has a pressure greater than that of the external atmosphere.

Up till now, it has been a question merely of straight cylinders with an invariable directrix. But the introduction of air regulated at will permits of enlarging or reducing the cylinder that is being formed, to any desired degree—of enlarging it by the admission of compressed air, and of reducing it by the expansion due to the closing of the clack; whence, instead of cylinders with rectilinear generatrices, surfaces of revolution as variable as possible are obtained. Finally, the artificial cooling serves to regulate the thickness of the sides of the cylinder. It will be seen, in fact, that the glass will be less drawn out, and consequently thicker, the more it is cooled, and more drawn out, and consequently thinner, the less it is cooled.

When the operation of drawing is finished, the cylinder will be found fixed at its upper end to the face of the mould, and at its base to the glass remaining in the vessel. It may be detached by any artifice whatever—a hot glass thread, a cutting wheel, or a diamond. Mr. Oppermann's apparatus, however, includes a mechanical device for performing this. It consists of an arm carrying a cutting tool, pressed against the glass by a spring, and fixed upon a circle whose center coincides with the axis of the cylinder. A rotary motion given to the circle suffices to detach the cylinder at the top and bottom.

It now only remains to briefly describe the glass drawing apparatus.

The glass, *a*, held in a molten state in the circular vessel, *b*, provided with a detachable handle, is carried to the machine. The vessel rests upon a fixed platform, *c*. In case its weight, in addition to that of the glass, did not suffice to balance the upward traction resulting from the adhesion of the vitreous material to the mould, it would be fixed by bolts or some other method.

The mould is usually cylindrical in form, and, in order to facilitate the changing of the worn-out parts, is composed of two pieces, *d* and *e*, bolted together. The lower piece, *d*, has an edge which varies in sharpness according as it is desired to obtain a narrower or wider contact with the glass. The upper piece, *e*, is provided with a clack valve, *f*, for the admission of air into the interior of the muff, and receives the extremity of the tube, *g*, that leads the air under pressure into the mould. This tube is fixed to the rod, *h*, which carries the mould. This rod is threaded throughout its entire length, and passes into a vertical nut, *i*, which is fixed to the frame of the apparatus, and which can only revolve. The rotary motion is communicated by a pair of bevel wheels, *j* and *k*, actuated by an inclined shaft, provided with a hand winch, *l*. The cast iron frame, *m*, supports the entire transmission. It will be seen that the nut, on revolving, will move the rod that carries the mould, whence the vertical motion of the latter in one direction or the other.

The air, under pressure, is led into the mould through the movable tube, *g*, and the fixed one, *n*, which carries a cock, *o*, for regulating the supply.

When, on the external cooling of the cylinder, the air designed to effect such cooling issues from the tubulures, *p*, in the circular conduit, *q*, it strikes a movable sheet iron cone, *r*, whose position must be so regulated as to lead refrigerant jets of air upon a zone more or less distant from the molten glass. These jets are directed by radial vanes, *s*. In order to raise or lower the cone, we act upon the iron circle, *t*, which actuates the levers *v*, and, through their intermedium, the cone itself, which is balanced by the counterpoise, *x*. The circular conduit supports the apparatus.

The characteristic part of this invention is the draw-

* Notes of Practical Work in State Laboratory, Auburn, Alabama.