peripheral speed of over 4,665 feet per minute. Although the lifter was simply acting on confined air within the shed, it enabled the machine to rise vertically; but as the steam pressure owing to the small boiler used could not be kept up, the lifting though of a decisive nature could not be maintained more than a few seconds at a time, the machine rising and falling with the fluctuating steam pressure.

These experiments were brought to an end by the boiler exploding. Though not inflicting serious damage to the lifters, the main body of the machine was entirely wrecked. The damage was not repaired, and the experiments are to be continued in London, where arrangements are being concluded for the construction of a second and more perfect machine, in which angle steel will enter largely in its construction in lieu of wood and steel tubing, the latter having been found unsuitable since it is liable to buckle. The ex-

periments with the small engine, however, served to demonstrate that a machine could be constructed capable of lifting itself bodily from the ground in a vertical direction. The fact that with two 40-horse-power steam engines the inventor can secure an upward thrust in excess of 1.5 tons with each lifter, which is more than sufficient to lift the whole structure from the ground and support it in the air, has been conclusively ascertained.

The control of the inclination of the gyropters is very simply effected. At the lower extremity of the vertical shaft of each lifter is a toothed quadrant, with which the shaft engages. By moving this quadrant in either direction from the floor of the car by hand wheel, the gyropters can be inclined either forward or backward, the angle being very slight, but adequate to alter the direction of the upward thrust, so that the resultant thrust tends to give the machine

either a forward or backward motion in a horizontal direction. No preliminary impetus to the machine to overcome its inertia is requisite, and it can start from the ground level, ascent being attained as soon as the speed of the rotary lifters becomes sufficient to give an upward thrust exceeding the downward pull due to gravity.

At Montclair the inventor devised a shed built in two sections and mounted to travel upon a railroad track, each half of which was simply drawn aside, leaving the machine free on the ground. Several suitable sites have been placed at the disposal of the inventor in England, in order to enable him to continue his experiments, while more than one well-known engineering company has volunteered the services of its staff to assist in the mechanical and engineering details. It is anticipated that the building of this second machine will be commenced soon.

ADVANCES IN MECHANICAL ENGINEERING.*

IMPROVEMENTS IN PRIME MOVERS AND CUTTING METALS.

BY PROF. CARL C. THOMAS.

THE past year has seen very few innovations in engineering matters, but in spite of the financial depression, considerable progress has been made in almost all of the important branches now occupying the attention of engineers.

In the field of mechanical engineering probably the most striking development has been that of the larger prime movers, notably the steam turbine and the internal combustion engine. The question is frequently asked, "Will not some one form of prime mover drive out of existence the other forms of engine?" Experience does not point, so far, to the probability of any one or two types of prime mover taking the place of or supplanting all the others. The steam turbine has not driven out the reciprocating steam engine; it has taken its place for certain uses, and the reciprocating engine will probably not regain the position it formerly occupied. However, the inherent qualities of the reciprocating engine are such that it is likely to remain superior to the steam turbine for certain special uses. In the same way the gas engine, while it has taken the place of the steam engine in special cases and will probably retain what it has won for a long time to come, is not so well adapted to the driving of alternate current generators in central stations, and for running many classes of machinery as is the steam turbine. The question as to the probability of hydraulic turbines driving out of use all forms of heat engines may be answered in a somewhat different way: If falling water were available within practicable distance of all places where power is desired, it is probable that it would, in connection with electric apparatus, supplant heat engines for nearly all stationary power purposes, but the fact that water power is not thus universally available assures the continuance of extensive use of heat engines for power development.

The effect of competition for place of first importance among prime movers has been to stimulate improvement of each type rather than to cause any one of the well established forms of engine to be driven out of the market. Each surviving type has been brought to a higher state of perfection than that which it would have reached if it had had the field to itself. It is a question not alone of relative fuel economy, but of general adaptation to specific purposes, reliability of operation, simplicity of parts, and ease of repair. It is natural that the reciprocating steam engine should lead in many of the above points because of the length of time it has been in use; but the steam turbine and the internal-combustion engine are forcing themselves into important places because of their special merits and are now operating machinery in fields where the reciprocating engine formerly held full sway.

The large gas engine of from 500 to 2,000 or more brake horse-power, using as fuel what was formerly the waste gas from blast furnaces, has been applied to operating the rolling mills of steel plants and to the generation of electric energy. Such engines are now coming to be regarded as the rule rather than the exception in steel works, and are displacing the steam driven blowing engines which formerly delivered the hot blast to furnaces for the reduction of iron ores.

Electricity is occupying a more and more important position in steel mills and the governing of gas engines has been improved so materially that central stations in connection with steel mills are being equipped with electric generators, operated by gas en-

gines as prime movers. The difficulty of varying the speed of gas engines within wide limits and of reversing such engines has so far prevented their adoption for direct connection to rolling mills, but gas engines may be used to operate electrical generators, and ingenious systems of electric driving of such mills have come into use and are apparently giving satisfaction in the operation of rolling mills for the production of rails and structural steel.

Large gas engines are also being used for the direct driving of high-pressure pumps and in cases where such pumps are continuously operated, the service seems entirely satisfactory. If there were to be frequent stopping and starting of the pumps, the problem would be much more difficult and perhaps the gas engine would not be capable of handling the work. In this case as in that of the rolling mills, electrical means are resorted to, and motors have been produced which will run with satisfactory regularity at any speed required from zero to the maximum for which the motors are designed.

In the new plant of the Indiana Steel Company at Gary, Indiana, the largest works of their kind in the world, there are to be sixteen blast furnaces producing about 45,000,000 cubic feet of gas per twenty-four hours, equivalent, when used in gas engines, to about 300,000 brake horse-power. Approximately 30 per cent of this gas is taken for heating the stoves supplying the hot blast to the furnaces. About 7½ per cent is used in steam boiler furnaces, 5 per cent is used for small auxiliaries or is lost in the process of cleaning the gas, 12½ per cent operates the gas-driven blowing engines, and 45 per cent supplies the gas-driven electric power station. Each of the sixteen blowing engines consists of a horizontal, twin-tandem gas engine having cylinders 42 inches in diameter by 54 inches stroke, and two direct-driven blowing tubs capable of delivering 30,000 cubic feet of free air per minute against a pressure of 18 pounds per square inch. These blowing engines are so designed that they can be operated at any pressure up to 30 pounds per square inch. The gas and air cylinders of the engines are situated at opposite ends of the main engine frame. Eight of these engines were built by the Westinghouse Machine Company and eight by the Allis-Chalmers Company.

In connection with the works of the Indiana Steel Company is a large central power station, 966 feet long and 105 feet wide, containing forty-two 23-foot bays. The station is advantageously placed as to fuel supply and with regard to minimum lengths of transmission lines to the various departments of the mills which use electric power. In this station there are installed seventeen horizontal, twin-tandem, double-acting gas engines, having a rating of 4,000 horse-power each and connected to generators of 2,000-kilowatt, normal capacity, but capable of carrying continuously 25 to 30 per cent overload. The engines turn at a speed of 83 1/3 revolutions per minute. Fifteen of the engines are designed for coupling to alternating current generators and two to direct current generators. The former are 25 cycle, 3 phase, 6,600-volt machines, while the voltage of the direct-current generators is 250. The engines described above are said to be the largest engines in the world to operate on blast furnace gas.

The occupation of this large field of power development by the gas engine has grown very rapidly during the last year. A heavily capitalized company has been formed in the iron-producing districts of England for the purpose of utilizing the waste gases from blast furnaces and distributing electrical energy to power

users in various parts of England. The hitherto unprecedented scale upon which the United States Steel Corporation has entered on the use of power development by means of gas engines has created great interest in such installations all over the world. At the works of the Illinois Steel Company, South Chicago, are four gas engines of 4,000 horse-power, each direct connected to a 2,500-kilowatt alternating-current generator, and in one of the Carnegie plants, near Pittsburgh, eight similar units are being installed.

The installations mentioned serve to indicate the immense field which gas engines are coming to occupy in one of the world's greatest industries, that of making steel.

The energy developed from blast-furnace gas by means of gas engines may be distributed for power and lighting purposes to distant points as well as used in the operation of the rolling mills in connection with blast furnaces, so that the latter become sources of power, serving various kinds of engineering enterprises.

Aside from blast-furnace gas, the gas produced from coal of various grades, and even from some lignite and peat, offers the most promising solution of the fuel question as applied to internal combustion engines of large size. It is safe to say that the most important work in developing satisfactory producers has been done in Germany, where large plants are in operation using cheap fuel and generating power at a surprisingly low cost. One of the chief lines of improvement during the past year or two has been in the methods used for cleaning the gas after it leaves the producer. When operated with high grade anthracite coal, there is very little tar in the gas coming from the producers, but when the cheaper grades of fuel are used it becomes necessary to employ special means in order to extract tar and dust from the gas. This is done in part by passing the gas through water chambers, or scrubbers, and in some cases by the use of what are called re-circulating producers in which the gas, after having been formed in the upper part of the producer, is led to the bottom of the bed of fuel by an external pipe and is caused to pass upward through the incandescent-fuel in the bottom of the producer, after which it is taken off at a point about half way up the producer.

The application of internal-combustion motors to driving motor cars has undergone rapid development during the past year. No revolutionary discoveries have been made in this field during that time, but improvements in details have been continuous.

A new type of gasoline engine has been developed for motor-car propulsion by the Daimler Company, in which, instead of the usual poppet valves and gear, the inlet and exhaust ports are operated by means of sliding sleeves in which ports are cut. The sleeves are caused to move up and down between the piston and cylinder walls by means of eccentrics carried upon a shaft which is driven by chain gearing from the crank-shaft of the engine. The engine is said to run silently and well, even at low speeds, but it remains to be proved how successful it will be as regards wearing qualities and freedom from difficulties attending complex design. Another advance in automobile engine construction consists in arranging for the circulation of the cooling water on the thermo-siphon principle, with large flow and return pipes, instead of circulating the water by mechanically operated pumps. This change has been made on a number of recently designed engines. The design of automobile engines is continually advancing along lines of greater accessi-

*The Wisconsin Engineer.

bility and simplicity, more positive lubrication, and, in general, greater reliability.

Turning from the subject of internal-combustion engines, the generation of power by means of steam has undergone steady development, principally with regard to the steam turbine. The development has been along two lines: First, improvement in mechanical detail, leading to more simple construction and greater reliability, accompanied by more satisfactory methods of manufacture and the production of certain well-defined types of turbines. The most prominent types in use are, first, the Parsons, or many-stage reaction type; second, the Curtis, several-stage, velocity-compounded impulse type; third, the Rateau, several-stage, impulse type, compounded with respect to pressure only, instead of with respect to both pressure and velocity, as in the Curtis type. Based on the general principles of these three kinds of turbine, a large number of types more or less closely related to these has appeared, within the past six or eight years, each type bearing the name of its inventor.

The second line of improvement has resulted from better understanding on the part of designers of the heat changes that go on within their machines; that is, of the thermodynamics of steam flow in the various types of turbine.

Much remains to be done in steam turbine analysis, both from the mechanical standpoint, and from that of thermodynamics, but already many important improvements have been brought about. Some of these have been, the production of more homogeneous steel for turbine rotors; special material for blades, adapted to withstand the action of rapidly moving steam; such arrangement of parts as will permit of the use of superheated steam of high temperature without undue distortion, and consequent vibration and possible destruction of motive parts; better and more sensitive governing devices; and improvements in methods of supplying oil bearings. Besides these, methods of construction have been adopted in some types of turbine permitting larger working clearances between moving and stationary parts to be used without undue loss of steam leakage through the clearances. Five years ago, the largest steam turbine units built were designed for normal load of about 5,000 kilowatts. Now, units of from 10,000 to 12,000 kilowatts are not uncommon.

At present one of the most promising fields in power development is that in which the reciprocating steam engine and the turbine are combined; the engine using high-pressure steam of from 150 to 200 pounds per square inch by gage and expanding to about atmospheric pressure, the turbine using the exhaust from the engine and expanding it to a vacuum pressure of about one pound absolute, or, in some cases, one-half pound. Combinations of this sort are being used both for stationary power purposes and for the propulsion of vessels. The results are improvement in economy of fuel, in the amount of power developed per unit of weight and space occupied, and, in the case of marine work, the combination gives greater facility in maneuvering vessels, and greater economy at slow speeds than is possible in an all-turbine installation. Some of the largest vessels ever built are at present under construction at Belfast, Ireland, for the White Star Line, to be equipped with this combination system, which is the result of several years' experience in the application of the turbine to marine propulsion. During this time the giant Cunarders "Lusitania" and "Mauretania," with an all-turbine arrangement yielding 65,000 horse-power, and driving the vessels at 25 knots speed, have been in service. They have been remarkably successful considering that they were more or less in the nature of experiments in a hitherto untried field. It is significant that vessels of similar type, designed in the light of experience, are being equipped with the combination system.

With the development of the steam turbine, has come the necessity for measuring the power it delivers. This necessity has brought forth the invention of the torsion-meter. Heretofore, indicated horse-power, calculated by means of diagrams showing the pressure existing in steam-engine cylinders, has been the universally accepted standard for comparing the output of steam engines. A steam turbine cannot be "indicated." It can be tested by means of a brake, and the result is what is known as "brake horse-power." But a brake is difficult to apply to a shaft, under the conditions usually existing, especially on ship board. As is often the case, an investigation begun with one specific object in view yielded two-fold results. That is, Mr. Herman Frahm, of Hamburg, was commissioned to find out why marine engine shafting so often broke under the turning effort put upon it. A determination of the extent of angular distortion of the shafting under known turning efforts was part of the information necessary to his investigation. Having obtained means for measuring this, it was only a step to working the inverse of this problem, namely, if the angle of torsion of a given shaft, the elastic properties of which have been determined by experi-

ment be ascertained by measurement, when turning at a given speed, how much power is being delivered by the turbine or other engine, which is causing the shaft to rotate? As soon as the nature of the problem was recognized, instruments were devised for measuring the angle of torsion of shafting in motion, and such instruments are called torsion meters. Some of them are automatic recording devices, some indicate delivered horse-power directly on a dial, while others depend for their record upon sounds transmitted by the telephone. The results of this invention have been far-reaching. Not only can the power delivered by turbines be measured, but that of reciprocating engines can be equally well determined, and this latter, combined with information as to the indicated horse-power, has enabled engineers to solve the vexed problem as to the mechanical efficiency of large reciprocating steam engines. It had been customary to assume this efficiency at from 85 per cent to 90 per cent, with the emphasis on the 85 per cent. The torsion meter has shown it to be nearly 95 per cent. That is, that a well designed reciprocating steam engine of large size delivers perhaps 94 per cent or 95 per cent of the power given up to it by the steam working in the cylinders, instead of from 85 per cent to 90 per cent, as was formerly assumed. This has been one of the recent great achievements in mechanical engineering.

Another notable improvement has been the development of more satisfactory apparatus for producing superheated steam, for use in turbines and other engines, and resulting in greatly improved economy.

Again, the turbine has called for a better vacuum

points of view of maneuvering and of fuel economy. There exists at present considerable difference of opinion in engineering circles as to whether the producer-engine combination or the engine using liquid fuel will be best adapted to the propulsion of large ships. Of course, the general question as to the practicability of applying internal-combustion engines to large ship propulsion is still open, it cannot be said to be near solution at the present time. For relatively small vessels, up to about 125 or 150 feet long, gasoline engines are being successfully used and are very satisfactory owing to the lightness of the machinery and the readiness with which a boat so fitted can be got under way. It is probable that the use of gasoline engines in marine work will be confined to relatively small ships, the heavier internal-combustion engines using either producer gas, or else the heavier oil fuels, being preferable for large installations aboard ship.

No account of even the most impressive recent improvements in mechanical engineering would be at all comprehensive if it failed to mention the great progress that has been made in the art of cutting metals; or, in other words, in the art of producing high-grade tool steel. A few years ago, one of our greatest steel works, turning out machine-finished products as well as the raw material, was facing the apparent necessity of doubling the size of its buildings and general equipment in order to cope with its growing business. At the critical time, the problem was met in an unexpected manner. Instead of enlarging the works, some bright fellow found a way to make tool steel that would maintain a cutting edge when taking off metal in a lathe or other machine tool at double the rate of speed formerly used. It was thus possible on the same floor-space to turn out about twice the work formerly produced. This improvement, however, could in many cases be taken advantage of only by replacing the machine tool equipment with new and stronger machines. The introduction of what are called "high-speed tool steels" at once became general. The advantage to large as well as small concerns was unquestionable. It has been followed by the appearance of many brands of special steels, each claiming superiority because of certain special properties conducive to the rapid cutting of metals.

There have been many other important developments during the past year or two, such as improvement in steam locomotives, which has undoubtedly been stimulated by the increasing application of electric traction in fields formerly occupied by steam locomotives alone; proposed mono-rail transportation; advance in submarine boat engineering; and the vast array of improvements in electrical engineering.

A NEW IDEA IN AIR COMPRESSION.

By JOSEPH H. HART.

THE accompanying illustration shows a system of air compression which may become useful under certain circumstances. In the engraving, merely the principle is shown, some mechanical improvements being possible of introduction in a commercial apparatus not being indicated. The construction of this device is very simple. It consists of an endless chain of buckets moving over two cog-wheels, the apparatus being almost entirely sunk under water. The buckets on the left-hand side turn their openings downward when moving in the downward direction, and are thus filled with air when they strike the surface of the water. During the downward movement of the buckets the air inside of them is compressed, as indicated by the double lines on the lower buckets on the left-hand side, the pressure on the air depending simply on the depth of the buckets below the surface of the water. When the bucket comes to the lower cog-wheel, it is turned around and the air escapes, being then collected into a hood A where it will be under pressure corresponding to the hydrostatic pressure of the water at the point at this depth below the surface. At the top of the mechanism the water is carried from the surface to the upper level of the wheel, and when the buckets are reversed, the water is dumped, and the buckets again filled with air. The raising of the water from the surface to the place where it leaves the buckets represents one of the losses of the mechanism. This loss remains approximately constant for all conditions, and expressed as a percentage of the total power required, it decreases as the depth of the device, and in consequence the compression increases.—The Mining World.

According to Engineering-Contracting, April 7th, 1909, the record for daily excavation in the central division of the Isthmian Canal was broken February 27th, 1909. On that day 59 shovels excavated 77,064 cubic yards, an average of 1,306 cubic yards per shovel for the eight-hour day. The material excavated was loaded in 2,177 Lidgerwood flats, 352 large western dump cars, and 2,754 small western and Oliver dump cars, a total of 5,283 carloads.

A NEW IDEA IN AIR COMPRESSION.

in the condenser receiving its exhaust steam, and this requirement has been promptly met by the production of condensers very much more efficient than have ever before been constructed.

In certain cases internal-combustion engines and steam turbines are being installed together, in electric power stations, with a view to obtaining cheaper power than is available from either steam or gas engines alone. The heat of the gas-engine exhaust, and that from the cylinder jackets, may be used for heating the feed water for the boilers supplying steam to the turbines. Where the gas engines can be fed with producer gas made from low-grade fuel, or where natural gas is available and cheap, the economy of the gas engine is such as to render it a very desirable element in the power station. But when the cost of gas is high, the advisability of installing gas engines is very questionable. In any event, where the combination system is used, the steam turbines, or else reciprocating engines, are used to take care of variations in load coming on the station, as the latter are very much more easily governed during wide variations of load, than are the internal-combustion engines. The latter are especially suited to carrying constant loads, while a steam turbine will take care of sudden variations from zero load to full load, with very little variation in speed of revolution.

The proposal so often made, to apply producers and internal-combustion engines to the work of ship propulsion, has been tested by the installation on the British ship "Ranger," in use by the Clyde Brigade of the British Naval Volunteers. This vessel has made long cruises, with satisfactory results, from the