potash contained in the solids suspended in the sewage is rendered available.

As to what proportion the resulting manure, if the whole of my scheme were in operation, would be by weight to the cake dealt with, it is not possible to speak with accuracy—it might probably be one-tenth.

At the present day it is fast becoming widely felt that it is the duty of towns to treat their sewage in some way, so that no injury may be caused to health, yet we surely ought not to rest content with processes which yield nothing but refuse. It is now many years since Liebig insisted on the need of maintaining a proper circulation of phosphates and ammonia if we wish our land to remain fertile, and this need, instead of diminishing, shows itself more clearly every day.

PREPARATION OF HYDROGEN.

In the country, when it is a question of getting together the elements of the simplest apparatus and mounting them, all sorts of difficulties have to be surmounted. Retorts, balloons, two-necked bottles, etc., all are unknown in a small village, and it is necessary to set one's wits to work to construct his apparatus for himself.

On trying to construct a hydrogen apparatus always ready to operate, and more easily realized in the country than the elegant laboratory apparatus composed of two bottles united by their lower tubulure, I have devised an arrangement that operates very regularly. I have thought that it might perhaps interest some of the readers of *La Nature*.

I take a common quart glass bottle (the bottom of which bulges inwardly), and, with a quick blow struck with the extremity of an iron rod from the exterior to the interior, I pierce the cone forming the bottom. I fill the bottle with zinc filings, and close the mouth with a cork traversed by a glass tube. Then I take a glass vessel (say a jar such as is used by grocers for olives, etc.), having an opening wide enough to allow the bottle to enter freely. I fill the vessel half full of a mixture of water and sulphuric acid, and when the mixture gets cold, I place the bottle in it. The liquid enters through the aperture in the bottom, the zinc is attacked, and the gas escapes through the tube, and may be collected in a test glass, as shown in the figure.

SIMPLE APPARATUS FOR THE PREPARATION OF HYDROGEN.

After the experiment is finished, I remove the bottle and immerse it two or three times in clean water. The zinc, thus freed of acid, is no longer attacked, and may be preserved for a second or third experiment. If, through any accident, the tube should get obstructed, the pressure of the gas would force the liquid into the vessel, and the production of hydrogen would cease.

If the gas is designed for inflating soap bubbles or small goldbeater's skin balloons (but not rubber ones, since the pressure would be inadequate), it will be necessary to free it of humidity. To this effect, it suffices to fill an ordinary lamp tube with quicklime and close its extremities with perforated corks. One of these corks is traversed by the tube issuing from the bottle, and the other by a tube to which may be adapted either the pipe designed to form soap bubbles or the neck of the balloon to be inflated.—A. Batut.

THE SEPARATION OF ROSIN FROM FATTY ACIDS.

By E. TWITCHELL, Superintendent of the Emery Candle Co., Cincinnati, O.

THE ethylethers of fatty acids, as is well known, are most readily formed by acting on an alcoholic solution of the latter with hydrochloric acid gas, the HCl merely serving to remove the water formed by the combination. This reaction I have found to be practically complete where the alcohol employed is absolute, and the HCl gas is passed to saturation. No other precautions are necessary.

On attempting to etherify rosin acids (common rosin) in the same way, I found that no combination takes place between the alcohol and acid, and that, when the solution is kept cool, the rosin acid is entirely unacted on, and can again be separated by diluting with water and boiling to collect the precipitate.

This important difference suggested a method for separating rosin from fatty acids which, on being practically applied, gave me separations such as I think are impossible by any of the methods now in use.

The analysis may be either gravimetric or volumetric, and depends on the fact that, by the means indicated, all the fatty acids are combined to form ethers which are neutral in alcoholic solution and unacted upon by alkalis in the cold, while the rosin is left as it was, reacts acid in alcoholic solution with phenolphthaleine and combines easily with caustic potash to form a soluble soap. It is, therefore, simply necessary to effect the combination of the fatty acids with alco-

hol, when the rosin acids may be titrated with standard NaOH solution, using phenolphthaleine as indicator, or they may be combined with KOH, and the rosin soap thus formed separated from the unsaponified fatty ethers by extracting with naphtha in a separatory funnel.

The gravimetric method is carried out as follows: Two or three grammes of the mixture of fatty acid and rosin are dissolved in ten times their volume of absolute alcohol in a flask, and dry HCl gas passed through in a moderate stream. The flask is set in a vessel with water to keep it cool. The HCl is rapidly absorbed, and, after about forty-five minutes, the ethers separate, floating on the solution, and no more HCl is absorbed. The flask is removed and allowed to stand a half hour longer to insure a complete combination of the alcohol and fatty acid. It is then diluted with about five times its volume of water and boiled until the acid solution is clear, the ethers, with rosin in solution, floating on the top. To this is added some naphtha, and the whole transferred to a separatory funnel, the flask being washed out with naphtha. The acid solution is then run off and the naphtha solution (which ought to measure about 50 c. c.) washed once with water and then treated in the funnel with a solution of 0.5 gram. KOH and 5 c. c. alcohol in 50 c. c. water and agitated. The rosin is immediately saponified and the two layers separate completely. The solution of rosin soap can then be run off, treated with acid, the rosin collected in any manner desired, dried, and weighed. A second washing of the soap with naphtha is hardly necessary, as very little remains after the first extraction. The naphtha used is 74 deg. gasoline, and for this purpose is much to be preferred to ether.

The first stages of the volumetric method are similar to those of the gravimetric, with the exception that the contents of the flask are washed into the separatory funnel with ether instead of naphtha, and the ether solution in the funnel is then thoroughly washed with water, until the wash water is no longer acid: 50 c. c. alcohol, previously neutralized, are then added and the solution titrated with standard NaOH solution. If the combining equivalent of rosin is known, its percentage may be calculated, or some of the original mixture may also be titrated, when the

difference in NaOH required will correspond to the fatty acids converted into ether.

I have tested this method by a number of experiments, some of which I will here describe. As a first step it was necessary to determine the effect of HCl gas on alcoholic solutions of fatty and of rosin acids separately.

1. Five grms. of distilled fatty acids were dissolved in 50 c. c. absolute alcohol, treated with HCl gas in the manner described, then treated with water, boiled, washed in a separatory funnel, and dried. They yielded 5.451 gram. of ethyl ethers. These ethers were dissolved in neutralized alcohol and titrated with a normal solution of NaOH. They required for neutralization 0.14 c. c. of the solution. This would represent 0.97 per cent. of rosin acid, taking 346 as the combining equivalent of rosin, i. e., the weight of rosin neutralized by 1 c. c. normal alkali = 0.346 gram.

2. Five gram. fatty acids from a low grade tallow were treated in the same way, and required 0.06 c. c. for neutralization = 0.41 per cent. rosin.

These figures, although not indicating a perfect combination, are still very small, and I think can be explained, especially in the first case, by the supposition that there were actually some rosin acids present, natural constituents of the crude fats.

On attempting to use alcohol of 90 per cent. instead of the absolute, I could only succeed in etherifying 92 per cent. of the fatty acids.

3. Five gram. of an average sample of rosin were treated in exactly the same manner as in working with the fatty acids. After diluting with water and boiling the rosin was collected by dissolving in a little ether and found to weigh 4.9382 grms. This was dissolved in alcohol and required 14.27 c. c. of the NaOH solution to neutralize it. Five grms. of the original rosin were titrated and required 14.45 c. c. There has been a slight loss in drying, but no change in the combining weight.

It was found that if the alcoholic solution became heated by the HCl gas, or if the solution was boiled without first diluting with water, the rosin suffered some change and required less NaOH to neutralize it.

Analyses were made of a number of mixtures. In using the volumetric method the mean combining weight of fatty acids was taken at 275, and of rosin 346.

A mixture consisting of 20 per cent. rosin, 80 per cent. f. a. gave, by the volumetric method, 20.36 per cent., 21.40 per cent., and 19.91 per cent. rosin. The same by the gravimetric method: 18.93 per cent. rosin.

A sample of soap said to be made of 100 parts fat to 40 of rosin, and, therefore, containing 28.67 per cent. rosin, assayed by the volumetric method, 73.7 per cent. fatty acid, and by the gravimetric method, 25.7 per cent. rosin.

Unsaponifiable matter in the fat does not affect the process, but can be determined by the volumetric method in one operation, as follows: Two grms. of the original fatty mixture are titrated with normal NaOH solution and saturate a c. c. Two grms. are treated with HCl gas, etc., then titrated and saturate b c. c. Then

$$b \times 0.346 = \text{weight of rosin.}$$

$$a - b \times 0.275 = \text{weight of f. a.}$$

The remainder is unsaponifiable matter.

A mixture of rosin, fatty acid, and paraffine was prepared and analyzed in this manner, with the following results:

	Calculated.	Found.
Rosin.....	21.3	22.6
Fatty acid.....	43.6	42.7
Paraffine.....	35.1	34.7

I have since analyzed a number of samples of soaps and always obtained the rosin distinctly brittle, and, therefore, practically free from fat. This I found to be the case even when the percentage of rosin was so low as 4 or 5 per cent.

In my experiments the caustic soda solution was normal, but a more dilute solution might be used with advantage, as a smaller sample could be taken and the operation considerably hastened.

The figures given have been those actually obtained, without correction for error, such as unsaponifiable matter in the original rosin, which would affect the gravimetric determination. The volumetric method I should prefer in all cases except where an examination of the rosin was desired.—*Journal Analytical and Applied Chemistry*.

PRODUCTION OF HYDROGEN.

By W. B. LEWES, Greenwich, England.

IN the method of producing hydrogen in which steam is passed over red hot iron, the iron, in course of time,

becomes oxidized, and the process stopped, which necessitates the removal of the oxide of iron and the substitution of fresh iron before the process can be continued. This invention is designed to enable hydrogen gas or a mixture of hydrogen and carbon monoxide in this manner to be carried on in an efficient manner and on a commercial scale by apparatus simpler in construction than hitherto used, and in which the iron is made to serve again and again for the decomposition of the steam. The accompanying illustration shows one form of the apparatus, in which A is the producer fitted with tuyeres B. In the center of the producer is placed the retort C, which may be filled with fragments of iron, or, if a mixture of hydrogen and carbon monoxide be wanted, with a mixture of iron and carbonaceous material. D is a steam pipe exposed to the heat of the furnace so that the steam may be superheated, its upper end being connected to a steam generator while its lower end opens into the retort. E is a pipe for placing the interior of the producer in communication with the top of the retort, and F is another pipe for the escape of gases that have been used to reduce the oxide of iron, and which will consist chiefly of steam and carbon dioxide. G represents the pipe for the delivery of the hydrogen. The operation is as follows: The producer is charged with coke or other carbonaceous material, which is lighted at the bottom. The air blast is then turned on until the fuel is raised to a bright red heat, when a little steam is admitted with the air blast, and the resulting hydrogen, carbon monoxide, and nitrogen produced are led from the producer into the retort, the contents of which latter become highly heated, partly by the heat of the gases and partly by the heat transmitted through the sides of the retort. The gases escape by the pipe F. When the iron oxide is reduced to iron, and the required temperature is obtained, the producer gases are then turned off, and steam is sent through the retort from the pipe D, and hydrogen is generated. When the iron becomes oxidized, the oxide can be reduced back to metallic iron by the producer gases, and the operation continued. Claims: In the manufacture of hydrogen by the decomposition of steam by contact with heated iron, and reducing the resulting oxide of iron to the metallic state, for reuse by subjecting it to the action of a reducing gas, utilizing the heat generated by the production of the reducing gas to maintain iron at a temperature at which it will decompose steam and the resultant oxide of iron at a temperature at which it can be reduced by the reducing gas.