time required for producing anesthesia of dentine is the chief objection to the practical use of the method, and this drug may probably reduce the time. It is quite possible that the drug is not sufficiently escharotic to work harm in the dentine, but it would seem desirable to use it with caution till more is known of its effects. With guaiacol and cocain it would be less necessary to use the rubber dam, and it would also be easier, with the escharotic properties eliminated, to produce effects on the gum if it were desired to use the method there. The combination has been used successfully for anesthesia in extraction, implantation, and skin surgery. On mucous membranes the subsequent sloughing is objectionable. On the skin it is said not to produce ill effects.

For bleaching teeth a 25 per cent. aqueous solution of H_2O_2 will prove successful if used as directed for cocain. The cotton in the cavity needs to be kept wet with fresh solution and stronger currents may be used than in living teeth.

When a commercial system is used as the source of power, it should be one that furnishes a steady current. A system subject to large intermittent demands upon it is not satisfactory in this respect. It needs also a well-appointed and well managed central station in order to be successfully used for this purpose; otherwise the irregularities due to imperfect machinery will be disastrous. Any primary or storage battery of sufficient capacity will do well. The manufacturers of the selector have made one to be used with a set of dry batteries that impresses me very favorably. It is certainly a most convenient form of battery, free from the objection of requiring constant care, and much less liable to injury than storage batteries. It is essential that the selector be fitted to go with the particular battery provided.

The most formidable objection to this process for the treatment of sensitive dentine is the time required. On this account, its best field is in the cases of extreme sensitiveness that require so much time and care for their preparation. I anticipate that the result of the general use the process is fast attaining will be the development of improvements which will reduce the time required.

EXPERIMENTS ON THE RUSTING OF INSTRUMENTS IN STERILIZATION BY BOILING.

BY EDMUND ANDREWS, M.D.
CHICAGO.

Every one knows that if steel instruments are sterilized by boiling in pure water, they become covered with spots of rust. It is usual to guard against this by adding to the water 1 per cent. of sodium carbonate. Some surgeons complain that this process gives no uniformity of result, their instruments sometimes coming out bright, and sometimes badly spotted.

As the rusting is a simple chemic process, the results ought always to be the same if the conditions are uniform. The following experiments were made to ascertain the effect of boiling under different conditions. A quantity of thin polished steel plates, each one inch wide and two inches long, were made for me by a cutler. These were washed well in ether, and then soaked in a bath of ether for some hours to remove all oily matter from the surface.

Also two plates of aluminium, each two inches square, were subjected to the tests, and two bright

scalpels, one with an aluminium handle and one with a German silver handle. These scalpels were selected to see if the presence of different metals in the same bath caused any galvanic action at the expense of the steel blades. For the same reason two plates of steel were laid on a plate of zinc and boiled.

Experiment 1. Two plates of steel were boiled twenty minutes in distilled water. They began to rust in two minutes, and in twenty minutes large elongated spots of black rust covered 30 per cent. of the surface.

Experiment 2. Several steel instruments were exposed to a steam bath over boiling water for twenty minutes. They came out much spotted with black rust.

Experiment 3. Two steel plates were boiled in Lake Michigan water, which is purer than ordinary Western well water, but contains small traces of chlorids and sulphates, being slightly "hard." The plates began to rust in two and one-half minutes. In twenty minutes about one-quarter of the surface was covered with small black spots.

Experiment 4. Two steel plates were boiled in water from a country well dug in the boulder drift. It was very "hard" water, owing to the presence of soluble chlorids and sulphates. In twenty minutes they were taken out and only one-twentieth of the surface was rusted, showing that hard water is better than soft for this purpose.

Experiment 5. Two plates were boiled twenty minutes in Lake Michigan water with 1 per cent. of sodium carbonate added. No rust at all.

Experiment 6. Two plates boiled twenty minutes in Lake Michigan water containing 1 per cent. of sodium bicarbonate. Not a particle of rust.

Experiment 7. Two plates boiled twenty minutes in very hard country well water containing 2 per cent. of green soap. Not a particle of rust.

Experiment 8. Two plates boiled twenty minutes in Lake Michigan water with 2 per cent. of green soap. No rust.

Experiment 9. Two plates boiled twenty minutes in Lake Michigan water with 2 per cent. of ordinary toilet soap. No rust.

Experiment 10. Two plates boiled twenty minutes in Lake Michigan water containing 2 per cent. of boric acid. Began to rust in two and one-half minutes. In twenty minutes there were many minute specks of rust.

Experiment 11. Two plates boiled twenty minutes in Lake Michigan water containing 1 per cent. of sodium chlorid. Twelve per cent. of the surface was rusted.

Experiment 12. Two plates boiled twenty minutes in pure Lake Michigan water, lying on a plate of zinc to test the galvanic effect. Twelve per cent. of surface rusted in large spots.

Experiment 13. Two scalpels, one with German silver handle and one with nickel plated handle, were boiled twenty minutes in Lake Michigan water with 2 per cent. of green soap. No rust.

Experiment 14. Plate of aluminium boiled twenty minutes in pure Lake Michigan water. A thin, delicate tarnish appeared on the surface.

Experiment 15. Plate of aluminium boiled twenty minutes in Lake Michigan water containing 1 per cent. of sodium carbonate. Copiously covered with blackish rust.

Experiment 16. Several aluminium articles soaked

in solution of bichlorid of mercury, strength 1 to 2,000. Surfaces marred and injured by the bichlorid.

Experiment 17. Two steel plates were placed in a small covered dish of melted vaselin and set for twenty minutes in a bath of boiling water. Not a particle of rust resulted.

These experiments yield the following conclusions:

1. Hot distilled water and steam rapidly rust steel instruments.

2. One per cent. solutions of soap and sodium carbonate almost perfectly protect steel instruments, provided they are completely immersed in the fluid.

3. If instruments lie in a shallow boiling pan and are not fully covered with the protective fluid, and a cover or towel is laid over them, the portions projecting above the fluid will only get a steam bath and will rapidly rust. This is the accident which perplexes some surgeons, and leads them to think there is no uniformity about the action of protective fluids in preventing rust. The fluids themselves will not cause oxidation, but the steam rising from them will easily corrode steel.

There is one theoretical objection to the use of all these boiling fluids. Educated mechanical engineers say that the heat of boiling water somewhat impairs the temper of cutlery steel. This is no doubt true, yet they are not so badly softened as to prevent us from using them with good effect, and as the boiling seems to be a necessity, we have to put up with the slight injury done to their cutting efficiency.

2520 Prairie Avenue.

SOCIETY PROCEEDINGS.

Physicians' Club of Chicago.

A regular meeting of the Club was held Monday evening, Nov. 30, 1896, at the Victoria Hotel.

Dr. ARTHUR R. REYNOLDS in the Chair.

The subject for discussion was

THE WATER SUPPLY OF CHICAGO.

The Chairman in calling the meeting to order, said: Our subject tonight is "The Water Supply of Chicago." There is no subject in which the members of the medical profession of Chicago are so deeply interested, and there is perhaps no subject in which the taxpayers are so deeply interested, for it is true, or will be true at the close of this century, that the taxpayers of this community will have paid directly or indirectly to maintain the purity of its water supply \$100,000,000 since the foundation of the city.

It has been said that each human being is worth to the State \$5,000. Impure water has been credited with destroying a great many lives, and it has often occurred to me that in this public-health matter, looking toward the preservation and building up of the race, that in order to get the people to understand the importance of the subject, it is necessary for us to reduce the matter to dollars and cents. I can not tell you at this time how many lives have been sacrificed because of bad water and so can not compute the total cost. Our own water supply is sometimes good and sometimes bad. It is a matter of very great interest to Chicago to have the outside world think well of us, because this city is a commercial center and is well known all over the world. Indeed, when we were inviting the world to partake of our hospitality and to attend the Fair, it was one of the bugbears even beyond the Atlantic Ocean, that our water supply was bad and on this account a great many people that would otherwise have come to the Fair remained away. Medical journals across the Atlantic took the matter up and discussed our water supply with a great deal of interest, and pointed out the evils of our water system, while we ourselves had said nothing and have suffered in consequence. If our water is impure we should admit it at once, in order that proper measures may be taken to purify it. To start the ball rolling it gives me very great pleasure to introduce Prof. Carl S. Hallberg of the Chicago College of Pharmacy.

Prof. C. S. HALLBERG spoke to the text: "Water, air and

cleanliness are the chief articles in my pharmacopeia." (Napoleon.) He said: As long as we have at the head of our municipal government men who know nothing about the importance of those matters for which they are engaged, taking care of the public health, we never can expect a better condition than we have at the present time. As for the subject of water; the newspapers have ridiculed the proposition of the Health Department to boil the water regularly every twenty-four or forty-eight hours, and one journal has even suggested that we get an automatic health department that would simply announce to the public every twenty-four hours, "boil the water," and that would be all that is necessary. However much we may ridicule the condition of the water in Chicago, anyone that has any knowledge of the service water in the large cities in this country, particularly in the East and South-east, must agree with the statement that the water of Chicago, however bad, is better than it is in any other large city east of us. It is only in the cities west of us that the water supply is perhaps purer. To consider the best methods of purifying water is a large subject, and I shall only briefly touch upon it, for the reason that there are other gentlemen here who have made water supply a specialty. There are three methods of purifying water:

1. *Filtration.*—Filtration resolves itself into any process which will remove the finely suspended insoluble particles. We may carry that process to such an extent as to also remove whatever microorganisms or organic matter the water may contain. As to whether or not filtration will purify ordinary water, such as our Lake Michigan water, is doubtful. In the first place we must remember that the filtration from the service pipes, that is for domestic or culinary purposes in small quantities is one thing, while the attempt to filter all the water which goes through the service pipes is another thing. It is quite possible to purify water if we attempt to do so in small quantities for domestic purposes, provided we take extreme care, giving it constant and unremitting attention. Filtration, as you doubtless know, is dependent upon the attraction that solid matter has for other solid matter. When we pass a liquid charged with more or less solid matter through a porous solid, such as animal charcoal, which is a mass of minute pores, by capillary attraction the solids, and particularly in this case, organic matter, are attracted and retained in the pores, while the clear water is allowed to pass through. For small operations we might choose various media through which to pass water which will not only rid it of the grosser impurities that it may contain, but will also carry off the microorganisms themselves. But we must remember that just as soon as this particular medium becomes charged to saturation with the insoluble matter, or with microorganisms, from that time on the process can be no more effective, and that is an objection to all forms of filtration of whatever kind; in filters made from sand, charcoal or silicious matter in any form, or burnt loolin, made into cylinders and the water passed through by pressure as in the Chamberlin-Pasteur period, and then their usefulness is at an end. Then, in many instances, the filters may require to be regenerated, burnt out, when they will again be free from organic matter and effective and be used again. In a larger way it is doubtful whether or not, for a city like Chicago, water can be purified by filtration. I might refer here to the conclusions based upon filtering apparatus used in three or four of the largest German rivers, because we have no details from any others, such as the Elbe, Oder, Neckar and Spree. The various cities situated on these rivers, such as Breslau, Berlin, Altona and Stuttgart, have filtering apparatus attached for purifying the water. But it is found by referring to the standard work of Koenig, that there are more impurities in the water served to those cities on the German rivers that have filtering apparatus attached than any other cities which do not have any filtering apparatus. This may not be conclusive testimony, but The Waterworks Technical Society of Germany a couple of years ago, after investigating the matter, reported that it must be remembered that the microorganisms in a filter settle to the bottom of a filter. The manner in which these filters are constructed is to have a depth of from five to six feet of various fineness of sand, gravel and stones. For example, beginning with a layer of fine sand, then coarser sand, then gravel and coarser gravel on top of that and finally pebbles. A bed like that, 300 meters square, representing 90,000 square meters area, would filter about one hundred million gallons of water every twenty-four hours. The bacteria are found to accumulate and to grow under the bed of the filter. In the beginning the water runs through in an impure condition, but after a while a sediment forms and a rather thick impervious coating over the porous bed, which retards mechanical impurities and lessens largely the number of bacteria. However, the question has yet to be solved whether or not a