"The medical referees, who were asked, in 1870, to give their opinion on the estate of Belvidere as a hospital site, while approving of it, stated that its distance from an extensive part of the city would render it necessary that the hospital in Parliamentary Road should be maintained, or that some other hospital, adapted in point of situation for the reception of patients from the northern and western districts, be made available in future. No site could be found within the municipal boundaries, and legal disabilities made it impossible to acquire land for such a purpose outside, until the obstacle was removed by the 'Glasgow Police (Amendment) Act, 1890,' Clause 6 of which enables the town council to acquire hospitals 'either within or without the city.' As soon as the way was thus cleared, the corporation took vigorous action in the matter, and in 1892 obtained power to purchase the lands of Ruchill for the joint purpose of laying out a public park and building a hospital for infectious diseases. In the previous year, the boundaries of the city were extended to include the territory surrounding the hospital, as well as various other suburban areas.

"The site on which the hospital is built was selected, after much consideration, because of its accessibility from numerous districts occupied by an ever-increasing working-class population, and because its altitude confers on it the benefits derivable from as much free air and sunshine as can be obtained in an industrial neighborhood. The adjacency of the public park affords permanent free space on the westward side of the hospital, while the other boundaries are ample enough to prevent the undue encroachment of buildings. It was pointed out in a joint report by the medical officer of health and the city engineer, dated Jan. 28, 1891, before the corporation purchased the site, that the level of the upper part of the ground was above the gravitation delivery of the water supply, and that it would be necessary to provide storage for the service of the hospital. Adequate arrangements for this purpose are installed in the water tower, which forms the most conspicuous feature of the central group of buildings.

"The entrance to the hospital is in Bilsland Drive. No other access is provided, and the discipline of the establishment is thus simplified.

"The hospital includes thirty-four distinct blocks of buildings, the principal of which are sixteen pavilions for the reception of patients. Twelve of these are large pavilions, each having beds for 30 patients, or 360 in all, while the four smaller pavilions will each accommodate 20 patients, or 80 altogether. There is thus provided accommodation for 440 patients, allowing upwards of two thousand cubic feet to each bed.

"Much consideration has been given to the design and general arrangements of these pavilions, particularly in regard to ventilation and sanitary arrangement, and the systems adopted have met with general approval from those specialists who have had the opportunity of examining them.

"The experience gained in the earlier construction of Belvidere Hospital has been invaluable, and all the features susceptible of improvement in that institution have been carefully investigated. The arrangements of other hospitals in different parts of the Kingdom have also been studied, and such details as appeared adaptable have been embodied in the design, with the result that Ruchill Hospital may fairly challenge comparison with any kindred institution at home or abroad.

"Second in interest to the pavilions is the administrative block; a large building, three stories in height, with a frontage of 240 feet, the wing walls extending to 189 feet.

(To be continued.)

A PRACTICAL PHOTOMETRIC METHOD FOR CASE RECORD.

BY G. W. FITZ, M.D., BOSTON.

THE photographic method of recording deformities has been used since dry plate photography first made it available for amateur use. Many, however, have been deterred because the control of the camera presented seemingly insurmountable difficulties, and the expense of development and printing and the difficulties of properly labelling and caring for plates were considerable. To overcome these defects by insuring convenience and accuracy of handling and economy of time, expense and storage, the following method and apparatus have been devised by the writer and carefully tested by long practical use,¹ but are now for the first time described.

The method is briefly as follows:

1. To adjust the focus of the lens for such selected image sizes of the subject as will give the desired ratios of size between subject and image (such as 6=100, 10=100, 14=100, 20=100, etc.) and to mark these foci and the corresponding distances of the subject from the camera on the adjusting part of the camera or lens so that the focus can be instantly secured by merely setting an index to a mark and adjusting the subject's distance by means of a graduated tape or knotted string, and the photograph taken in the exact ratio without any delay for focusing or other adjustment.

2. To make the camera so that it will take three or four photographs of the same individual in different aspects upon the same plate, thereby avoiding confusion in labelling and loss of identity of the several photographs.

3. To photograph with each subject an identifying number which absolutely identifies every photograph.

4. To make a transparent scale based on the ratios of subject size to the image size selected for records, by which the photographic images may be measured as to any dimension, asymmetry or deformity, directly in inches or centimeters, as if one were measuring the subject himself, by the application of the scale to the face of the photograph.

The lens. — Although expensive modern lenses are the most satisfactory, yet a rapid rectilinear lens of the cheaper sort, such as a Darlot, will ordinarily give thoroughly satisfactory results, provided that one does not need to get a large image in a poorly lighted and cramped room.² Unless one is very familiar with the working values of different kinds of lenses, however, it is wisest to test them under the conditions of use before making a choice for purchase.

It is important to use a lens of the longest focus possible in the space available for photographing if the room is short, since it will give a

¹ The first multiple camera, a three-phase and the first automatic labelling device were designed and made in 1888 by the writer for use in photographing the students in the Hemenway Gymnasium, Harvard University, where it has since been in constant use.

² The Darlot with a slip collar permitting adjustment for focus by movement of the lens itself is so convenient for use in this method that it has been adopted for illustration. (See Fig. 4.) Any lens can be fitted to a slip tube which will serve the same purpose and at the same time save the necessity of making the camera box adjustable.

sharper large image of the subject with full aperture than one of shorter focus, and hence permit the shortest exposure. If the distance from the camera to the object is necessarily short and large photographs are desired, it may be necessary to purchase an expensive lens of shorter focus which will work with wide aperture since a cheaper lens may not give satisfactory results when strained in this way. The longer focus

FIG. 1. Projection angles of lenses of focal lengths, 5 in., 9 in., and 13 in., respectively, showing projection of shoulder (a) against anterior posterior vertical mid plane (cd) in photographing a subject 60 in. in height with the camera at mid height. a-b = shoulders, c = top of head. Subject standing with his side to the camera.

lens is also to be preferred for getting a good perspective and the proper relation of projecting parts. This is shown diagrammatically in Fig. 1.

The following table of focal lengths will assist

Focal lengths of lenses.	Distances of object.	Lengths of image of individual 68 in. tall.	Distances ³ of lens to plate.
7 in.	54.6 in.	10 in.	8.0 in.
	66.5 "	8 "	7.8 "
	86.3 "	6 "	7.6 "
	102.2 "	5 "	7.5 "
	126.0 "	4 "	7.4 "
8 "	62.4 "	10 "	9.2 "
	76.0 "	8 "	8.9 "
	98.7 "	6 "	8.7 "
	116.7 "	5 "	8.6 "
	144.0 "	4 "	8.5 "
9 "	70.2 "	10 "	10.3 "
	85.5 "	8 "	10.1 "
	111.0 "	6 "	9.8 "
	131.4 "	5 "	9.7 "
	164.0 "	4 "	9.5 "
10 "	78.0 "	10 "	11.5 "
	95.0 "	8 "	11.2 "
	123.0 "	6 "	10.9 "
	146.0 "	5 "	10.0 "
	180.0 "	4 "	10.6 "
11 "	85.8 "	10 "	12.6 "
	104.5 "	8 "	12.3 "
	135.7 "	6 "	12.0 "
	160.0 "	5 "	11.9 "
	198.0 "	4 "	11.7 "
12 "	93.6 "	10 "	13.8 "
	114.0 "	8 "	13.4 "
	148.0 "	6 "	13.1 "
	175.2 "	5 "	12.9 "
	216.0 "	4 "	12.8 "

Table for determination of required focal lengths of lenses for given room distances and image sizes. — Adapted from P. Brosig. *Am. Ann. Photog.*, 1900, p. 309.

³ These distances must be considered as approximate, owing to variations in lenses.

in deciding upon the lengths of focus of lenses most convenient for given conditions. It gives the distances required for a full length view only, since larger views of parts of the body are taken at less distances and hence do not count in deciding room capability for photographic purposes:

In deciding the question of available room length it is necessary to determine, preferably experimentally, the position for best illumination of the subject and the direction in which the camera must be placed in order to secure a photograph which will give the best modeling of the body. Having determined these two points, position of subject and of camera, the distance between them becomes the "available distance" of our problem and we are in a position to decide what focal length of lens is best adapted to secure good images. It not infrequently happens that only one half or one third of the room length or width can be used and that the camera must be placed so that it will look into the room containing the subject through a doorway from another room.

The multiple camera. — After settling the lens problem it is necessary to determine the range of focal length ("back focus" or distance from flange to ground glass) of the lens for the largest and smallest images required. The box depth, Fig. 2, must be made equal to the shortest back focus when the lens is pushed home into its collar, less the thickness of wood used for the front of the box, the thickness of the slide carrying the lens and the depth of the plate holder to the film surface of the plate. The breadth and height of the camera may either be made large

FIG. 2. Diagrammatic section of a four-phase multiple camera. (1), (2), (3), (4), portions of plate occupied by the successive photographs. (1), (2), etc., pins on lens slide for stopping lens in exact position for corresponding photographs. The plate is 5 x 8 in. lens, Darrlot No. 2. Scale $\frac{1}{4}$ in. = 1 in.

enough to inclose the plate holder or may be made $\frac{1}{4}$ inch smaller each way by fitting the box flush to the edges of the plate holder.

The dimensions with a scale plan of the camera can then be given to a carpenter who will "gang-

saw" the pieces of $\frac{1}{4}$ -inch mahogany together, so as to make a stout and at the same time light box. The front may be fitted with small brass hooks so as to permit easy removal for adjustment of the partitions. The sliding strip of mahogany to which the lens is fastened is best carried between two narrow guide strips of mahogany by means of $\frac{1}{4}$ -inch brass splines and is stopped at the center of each of the four compartments (into which the box is divided) by a spring catch slipping over the end of a pin in the slide. The partitions are of thin blackened wood each carrying a $\frac{3}{4}$ -inch strip of blackened wood, at right angles on the front end to prevent the light from the lens getting into the adjacent compartments. They may be kept in place either by binding nuts on long screw wires which pass through their corners and rest lightly against the sides of the camera box thus uniting the partitions into one easily removable framework, or by pieces of doweling similarly treated. Vertically the partitions themselves should fit loosely so as to remain in place. The screw wire and nuts permit adjustment of the spaces, and the whole may be removed and the entire plate used for one large photograph in a moment's time, the conditions of focus, of course, remaining the same.

is required, it is unnecessary to provide a regular ground glass in case the box used does not have one. Any glass will serve, provided that it is coated with some substance which will make it milky so as to receive the images. Beeswax rubbed on the side of the glass toward the lens, a thin coating of uncooked starch paste dried on, or even better an undeveloped gelatine plate will give a fair image.

The ground glass or its substitute, when used for focusing, should be exactly in the plane of the plate in the plate holder. To obtain this position the plate holder may be used if the central partition is removed, or strips of wood or pasteboard of the requisite thickness may be glued upon the face of the glass itself at the ends.

Adjusting the focal distances. — To prepare for the systematic focusing of the lens, drive three 2-inch wire nails lightly into a strip of wood at $\frac{1}{2}$ -meter intervals and in a vertical position. Place this strip on a table at right angles to the axial line of the camera, and set behind each nail the flame of a Christmas candle with a piece of oiled paper between them, so that the nails will show black on a bright ground. The camera should now be set at such distances from the nails as will give exactly the desired lengths to the images

FIG. 3. Photographs taken with four-phase multiple camera showing utilization of whole plate surface, plumb line for vertical reference, automatic numbering and dating (November, 1903, No. 614) and method of marking back. ($\frac{2}{3}$ full size.)

For use as a multiple camera an ordinary collapsing camera box is not available because of the difficulty of properly providing for the partitions, and for the further reason that on account of the wide aperture of lens used and the required accuracy of image size the focal adjustment must be more accurately made than is possible with the ordinary camera box. It is far better to have the box so made as to be useful for no other purpose and hence to be always instantly available for case photographing.

Since by this method no subsequent focusing

of the meter (or half meter) when focused with full aperture of lens; for this purpose a millimeter scale should be used and repeated trials made until exact coincidence is obtained. When this is accomplished in exact focus, measure and record the distance from the front of the camera box to the middle nail and mark the lens tube⁴ by drawing a sharp knife carefully along the edge of the collar. In this way the image values

⁴ In an ordinary camera these marks can be made upon the bottom portion over which the moving front or rear of the camera passes as is sometimes done for a simple focusing scale, but it is not nearly so satisfactory a method.

and object distances were obtained for the lens positions shown engraved on the lens tube in Fig. 4. It is best to use a magnifying glass to test the sharpness of the focus on the ground glass and to be sure that the line of sight is perpendicular to the glass surface in reading the distances between the nail images, to avoid the errors which may be made if one carelessly measures in the line of emergence of the light itself, as may easily be done if the coating on the glass is too transparent.

FIG. 4. Lens tube graduated for distances of object and sizes of image of one meter. The edge of the collar forms the index set for a distance of 1,900 mm., giving an image of one meter = 140 mm. = 140/1,000 or 14% of size of subject. ($\frac{1}{4}$ natural size.)

A proportional scale for measuring photographs.

—Having prepared the table of image sizes as above, one may construct a universal scale for image measurement as shown in Fig. 5. First draw with the utmost precision as straight base line (*a b*) of the length of the longest meter image (or, for greater exactness, of double that length) and erect a perpendicular (*b c*) at one end exactly equal to the longest meter image length. From the upper end, *c*, of this perpendicular draw as carefully as possible a straight diagonal (*c a*) to the remote end of the base line. If one now draws intermediate perpendiculars touching the base line and the diagonal at distances on the base line proportional to the meter image lengths measured, these lines will give the meter images in position for ready multiple subdivision, since if the first perpendicular be divided into ten equal parts by means of dividers⁶ and diagonals be drawn to each division, all the perpendiculars will be divided to tenths and each division will stand for 100 mm. or one decimeter for its own scale. These may be subsequently divided again into fifths or tenths as shown, thus giving 10 mm. or 1 cm.

This universal scale cannot be used directly on the photographs to advantage, but from it scales similar to Fig. 6 may be made for standard image sizes. For this purpose clear celluloid 20-1,000 to 15-1,000 inch in thickness is best,

⁶ This can be avoided by using the divided ruler or tape when it is 10 cm. or any multiple of it; otherwise by prolonging the base line proportionately it is possible to erect the perpendicular which may be divided by the divisions on the scale.

and the graduations may be scratched with a needle point.

These scales are useful for all measurements on negatives or prints and have proved themselves superior to any of the methods tried by me previous to devising this. They have the great advantage of being instantly adjustable to any part of the body of which the measurements are required. Thus lengths and breadths are readily measured as well as depths of curves, lengths of chords of curves, inclination of the body from a plumb line, deviation of the spine at various levels from the mid-line between cleft of buttocks and the Vertebra Prominens and other measurements which on the human body cannot otherwise be obtained without elaborate apparatus and much expenditure of time.

Method of measuring with the proportional scale.

—The method of applying the scale to a photograph for the measurement of a particular dimension is illustrated in Fig. 5 in which the scale is applied for the measurement of the line *a b*. The end *a* is adjusted to the nearest division of the main scale (in this case 800) which will permit the end *b* to overlap the zero on to the fractional scale. This fractional reading (70) is then added to the main reading (800), giving the total length (870).

In practice the great advantages of this method over that of Oehler,⁸ now rather commonly employed, are that the scale can be so adjusted to the photograph that oblique as well as rectangular measurements can be made, and that the scale may be made to tally with the beginning of any desired measurement, so that fractional parts need to be measured at one end only. The importance of the former of these advantages is quickly realized in practice since few dimensions are strictly horizontal or vertical; of the latter, since it is impossible to so adjust the screen as to make the zero line tally with even one fundamental point or line on the subject. Furthermore, the meshwork of lines in the Oehler method is extremely confusing to one trying to get a comprehensive and accurate impression of the photographed figure. The thread screen is, moreover, very delicate and thereby easily injured and somewhat costly and awkward of adjustment.

This method of measuring photographs by means of a proportional scale can be applied to any photograph whose size ratio to its original is known.

A simple method of making a measuring scale for one distance of the subject when the scale and not an exact size ratio to the subject is required and an ordinary camera is used, is to determine the distance and the focus which will give the size of image desired. This distance is then measured, or an inelastic string of the exact length is provided for use in reproducing it, and the focal point is marked on the focus adjusting part of the camera. A strip of paper or a board

⁸ Zeitsch. f. Orthop. Chir. Bd. II, 1893, p. 169-173. This method is to photograph the subject behind a thread screen whereby the entire surface of the photograph is covered with 2.5 cm. squares formed by the intersection of the black cross threads.

is then graduated with heavy ink markings in either inches or centimeters to a length of from three to five feet. This is photographed at the exact distance of the subject as previously determined. If the negatives are to be used for measurement the scale may be prepared directly from the negative, but if paper prints are to be used it is wiser to make the scale from a print treated in the same manner as the case photographs.

stuck carefully upon a heavy rough surfaced dark photographic mount board cut into pieces of the right size.

The holder is made of sheet metal as shown in Fig. 7 and receives the number cards at the ends. A pin on the back serves to attach the device to the clothing of subject. The holder is coated inside and out with a dead black enamel. To simplify classification by using the same

FIG. 5. Scale plan of proportional image sizes of one meter for all distances of object: for lens "D2." (3 full size.)

This is necessitated by the fact that velox paper, for example, shrinks 1% in all directions when after development it is allowed to dry spontaneously and is not burnished, and other papers behave somewhat similarly depending upon the structure of the paper, the character of the film and the method of treatment. Since the glass support of the negative prevents change of size in its film, it is preferable to use the negative for accurate work, especially as it is also much more economical so to do.

Automatic labeling of negatives.—White-gummed numerals one inch in height are sold in packages of ten each. These are moistened and

number always for each individual it is convenient to date the photographs by adding the proper numbers as is done, for example, in the figure which reads "September, 1902, No. 485." The holder should be six inches long and five series of number cards 0 to 9 are necessary beside the year cards, '02, etc. This will give a complete series up to 999 cases.

Plates or films.—Rolled films are very attractive because of their lightness and small bulk and for the reason that they can be superposed in the developing tray and several developed at once. This apparent advantage is, however, neutralized by the fact of their greater delicacy,

by their greater expense, by the delay in development of the entire roll of twelve or more exposures until all are used and by their change of size in drying.

Plates, however, have one property lacking in all substitutes, that of furnishing a film support which is practically a true plane and of absolute rigidity and unchanging dimensions thus enabling one to measure the image on the negative with perfect confidence in its accurate ratio to the subject photographed.

Plates are more durable than rolled films both when unexposed or exposed and when developed and dried as negatives. They are more readily filed away for reference and when one is sought it is found with little disturbance of the others and can easily be replaced again when it is no longer needed. This is a very important item when one is using photography for case record,

FIG. 6. Transparent measuring scale of celluloid for ratio method: apply scale as shown so that one end of line, as *a-b*, coincides with the cross line whose distance from (0) is just short of its total length, the other end will then extend by the zero line (0), thus giving the fractional excess (70), length *a-b* = 870 mm. ($\frac{1}{2}$ natural size.)

especially when the negative itself is used for study as it should be for greatest accuracy and economy.

Plate holders.—Light, strong plate holders should be selected with special reference to the particular device to be used for retaining them against the end of the camera box and to the ease with which they can be filled and emptied by feeling in the dark room. No plate holder without stout wooden sides should be considered for an instant, since they will not stand the hard usage which may unavoidably come to them. One should try manipulating the sample holder

with the eyes shut,⁷ and unless it can be done quickly and safely without touching the face of the plate except at the edges either in filling or emptying it should be unhesitatingly rejected.

Shutter.—Any shutter may be used, but one of simple construction is most convenient. All

FIG. 7. Holder for date and number cards. Each figure is on a separate slip. (Reads No. 485, September, 1902.)

that is needed is that it should open and shut positively so that the exposure may be perfectly controlled from a distance. Automatic shutters which give measured exposures when released, as the Bausch and Lomb, though excellent, are expensive. It is sometimes convenient to have the rubber tubing long enough to control the shutter from the position of the subject, especially in photographing children.

Exposure.—The ordinary exposure varies from one to six seconds, according to light, diaphragm, subject, etc. It is seldom that light enough can be secured in hospitals or offices to permit a shorter exposure than two seconds, but even in the case of a restless child, this is usually found to be sufficiently short. Six seconds is as long an exposure as is permissible even for older children or adults when standing, since it involves a certain amount of body swaying, which cannot be controlled without a back rest. The use of a rest is objectionable for the reason that it leads to greater or less distortion of the body, in that each subject adjusts himself to the rest and consequently is not in normal posture. For other than standing postures, rests are both less objectionable and less necessary. Too short exposures must be avoided owing to the difficulties of developing the plate.

The length of exposure can be conveniently measured by means of a simple pendulum, consisting of any small weight suspended by a string from some fixed point. The distance from the center of the weight to the point of bending of the string at its upper end should be for a one-second swing 39.1 inches. for a half second, 9.78 inches.

Automatic shutters can be adjusted for the proper exposure and then need no attention except to set and release them at the proper times for each exposure.

Instantaneous photography has small use indoors, owing to the weakness of illumination and consequent difficulty of successfully developing the plate.

Camera stand.—A stand is a not unimportant aid in photographing cases. In emergencies it is possible to use a table or other support but for routine work a good stand is essential. The

⁷ Plates should be handled in the dark except when one is developing them, and then they should be kept as nearly in the dark as possible in order to get the full advantage of the sensitiveness of the film and to avoid the "developing" fog which in very short exposures may seriously diminish the value of the plate.

ordinary folding tripod is useless on a polished floor and is awkward and treacherous in all indoor work; the studio stands are expensive as well as clumsy and take up considerable room. There is, however, now on the market, a stand which in structural design combines the advantages of both in that it has a small folding tripod base which, however, becomes rigid when opened out, a central vertical extension giving elevations, of from two and one-half to five feet, and a tilting top. It is excellent for semi-portable use owing to its lightness, strength and compactness when folded and to the quickness with which it may be adjusted. Its chief disadvantage is its tendency to vibration when the camera is set at a high level, but this it shares with most portable stands. It can be neutralized by leaning a light pole or other object against it, or by wedging, lightly, a brace obliquely from the camera to the floor or wall.⁸

TECHNIC EMPLOYED IN THE LAST ONE HUNDRED LAPAROTOMIES WITH THE VIEW OF RESTRICTING THE EMPLOYMENT OF DRAINAGE.

BY L. J. HAMMOND, M.D., PHILADELPHIA, PA.

EXPERIENCE has so abundantly proven the wonderful power of resistance possessed by the peritoneal cavity that the opinion formerly held universally, that drainage should be employed in about all abdominal operations, has, during the past few years, been to a great extent abandoned by a great number of operators in this country, though by no means has this advancement been universally accepted by foreign surgeons. Not only is drainage employed whenever infected material is present, but is still regarded by some as essential in benign and non-suppurative intra-abdominal growths.

After a painstaking search of the literature covering the past two years in an endeavor to gain the views of various surgeons throughout the world on the subject of drainage in abdominal surgery, I find there is a striking absence of expression of opinion as to its relative merits. Even in those articles bearing on the subject of operative technic, drainage, when employed, in the majority of cases, is dismissed with the simple statement that it was used.

Of the 41 opinions collected, 21 without exception drain in every operation on the abdominal viscera, while the other 20 do not drain at all or limit its use to those cases where accidental puncture of the viscera has occurred or pus has been free in the abdominal cavity.

Those who restrict the employment of drainage are very much more outspoken in their reasons for so doing than are those who continually employ it. For example: Arthur H. N. Lewers, in the sixth edition of his work on *Diseases of Women*, says that Keith's tubes for drainage in abdominal cases are no longer to be recommended, and adds that there can be no doubt that in time,

⁸ The stand is sold under the name "Daisy" for \$2.50 in the photographic stores.

not very long past, drainage has been employed in a needlessly large proportion of cases. He further says that it is rarely necessary, but when it is, sterilized gauze drain answers the purpose well.

F. Milner Blumer, in reporting on Chronic Gastric Ulcer, says, that drainage was not employed by him.

G. A. Moynihan says that he rinses the abdominal cavity thoroughly and drains through both wounds when extravasation has taken place from perforated stomach ulcer, but further says that in fresh cases it is sufficient to close without drainage.

Dr. Robert T. Morris, in discussing complications of stomach surgery, says that the presence of gauze very distinctly has a tendency to keep the patient in a condition of shock. He has given up its use entirely, having found, as he says, it to be practically useless in the present day surgery.

Dr. Hunter Robb says that he has not for seven years used a drainage tube, and a gauze drain is used only when there is an adherent pus sac or the structures cannot be removed completely. He further remarks: "I do not feel altogether sure that even under these circumstances the procedure is always absolutely called for."

Dr. John G. Clark has shown in his report of 1,700 abdominal sections that drainage is not only valueless in a great majority of cases in which it has hitherto been used but that it frequently is productive of harm.

On the other hand, among those who persistently employ it, may be mentioned M. G. Roussel, M. R. Sorel of Havre; Cantlie of London; W. Renner of Brussels; Dr. Robert Lichtenstern of Vienna; Hans Lorenz, Dr. Emerick Ullman, H. Feling of Strassburg; Racovicceanu of Roumania; A. Doederling of Tübingen and others.

Most of those just mentioned use it in cases where there are oozing surfaces from broken adhesions and in the absence, according to their reports, of demonstrable infection.

The one hundred cases that I have used to illustrate the technic employed, with the object of lessening the employment of drainage, were in no way selected but were reported in the order that they presented themselves for operative treatment.

Of these there were 36 cases of localized pus, as follows:

- 16 Appendicitis.
- 8 Pus tubes.
- 2 Cholelithiasis with pyemia of the gall bladder.
- 1 Pericholecystitis.
- 3 Tuberculous suppuration of the mesenteric glands.
- 2 Suppurating fibroids of the uterus.
- 3 Intestinal perforations from typhoid.
- 1 Perforating duodenal ulcer.

Of these 20 were females and 16 males.

Operated in the absence of pus, there were

- 22 Appendicitis.
- 8 Cholelithiasis with sterile gall bladder contents.
- 14 Fibro-myoma of the uterus.
- 2 Chronic gastric ulcers.