Modification of the Micrometer-head, devised by Mr. *Joseph A. Rogers*, Aid U. S. Naval Observatory.

(Communicated by Prof. *J. M. Gilliss*.)

For the determination of declinations, it is sometimes desirable to make repeated bisections of a star with the micrometer of a meridian instrument. To avoid the inconvenience of reading the micrometer after each bisection, to save time required for the observations in right-ascension, and to dispense with use of a lantern and pencil while the star is in the field, a modification of the ordinary micrometer-head has been devised by Mr. *Joseph A. Rogers*, one of the Aids of this Observatory.

Both edges of the micrometer-head are divided into the usual number of parts, marked by figures between the two sets of divisions. Between this head and the milled shaft by which it is turned, and revolving with it upon the same axis, are two other disks of the same diameter but not so broad, separated from it and from each other by narrow and equal spaces.

These disks are divided by lines which extend from edge to edge, every fifth one being distinguished by a small dot.

The corresponding divisions of each disk are in the same line parallel to the axis of the screw, and are thus easily referred to the figures on the head. The divisions of the edge nearest the eye-piece are read from a fixed index-mark in the usual way. To each of the other edges, except that next the milled shaft, an index is adapted, which is attached to one end of a light arm that revolves freely about the axis of the head. The other end of this arm projects a short distance beyond the opposite side of the head. A lever, having a limited motion in the same plane as the index arm,

is so arranged that in one of its positions the projecting end of the arm is held and its revolution prevented, while by moving the lever the index may be released.

A slight degree of friction, obtained by washers of thin steel on this axis, carries the indices round with the head, except when prevented by the levers. The adjustment is such, that when each index is detained by its appropriate lever, all of them and the fixed index have the same reading. By moving one of the levers its index will then be carried round with the head, and will continue to mark the same reading.

The star to be observed is first bisected by the micrometer thread without removing the eye from the telescope or the hand from the milled shaft. The first lever is moved and a second bisection made. The next lever moved, a third bisection made, and so on, for five successive bisections, if so many are desired. The readings may be recorded at leisure, beginning with the index nearest the milled shaft. To restore the indices to their places, the levers are moved partly back, and after a revolution of the head are replaced as at first.

The drawings are of full size and in detail, and a skillful mechanic can so construct the appendage that the additional weight on the micrometer screw will scarcely be appreciable. It has been ordered for the new Transit Circle constructing for the Observatory by Mrs. *Pistor & Martins*.

U. S. Naval Observatory,
Washington, 1864 Aug. 3.

J. M. Gilliss.

Entdeckung eines Cometen.

Schreiben des Herrn Prof. *Donati*, Directors der Sternwarte in Florenz, an den Herausgeber.

J'ai découvert une nouvelle comète, dont j'ai fait les observations suivantes:

1864 Sept. 9, 15^h 56^m 6^s T. m. Florence. α app. $\oslash = 10^h 23^m 17^s 77$, δ app. $\oslash = +35^\circ 21' 32'' 9$
 = 10 15 42 52 = = = 10 23 59,46 = = +35 52 47,0

Très-faible.

Florence, 1864 Sept. 11.

G. B. Donati.

Beobachtungen des Cometen III. 1864, von Herrn Professor *de Gasparis*.

1864 Sept. 11, 16^h 4^m 3^s 0 T. m. Naples. $AR \oslash = \alpha * +6^m 59^s 5$, $\delta \oslash = \delta * +17' 28''$
 12 16 28 8,5 $-3 \ 9,0$ $-4 \ 28$

La première étoile est 339 Weisse. 7ième grandeur.

La deuxième étoile est 551/52 Weisse. 7ième grandeur.

Naples, 1864 Sept. 13.

Annibal de Gasparis.