truer than that by blades, but not so smooth. However, the highest degree of polish is given by clamping down the slab to the reciprocating carriage of the machine, shown by Fig. 22, and subjecting it to the action of the rapidly revolving plate set with amalgams of emery and various metals, iron being used for marble.

For an annual production of 14,000 cubic feet of marble sawn to size, the Traigneaux Quarry only employs thirty hands, all told, except in addition to the five boys who tend the apparatus and give the feed. This process has formed the subject of favorable reports by M. Belpaire, president of the commission as to new processes for the Belgian government, and of M. Trouel, Engineer-in-Chief of Ponts et Chaussées, while it was awarded the first prize of progress at the

amount of current that the generator feeding the circuit is capable of supplying.

A decided advantage is gained in this system of factory construction over the usual method of transmitting all the power by belting and long lines of shafting, by being able to run any small portion of the factory independent of all the rest. For instance, if the work is behind in one department, and it is necessary to work overtime, that particular department of the shop, having a motor of its own, can run without running any of the machinery or shafting in any other part of the building; and thus a great saving of fuel can be effected over the old method, where it would be necessary to run all the shafting throughout the entire building.

provided in this main pipe at each floor, through which the steam may be turned into the heating pipes. The latter are arranged in a manner similar to the "multiple arc" system of electric lighting. A 4 inch pipe extends along each side of the building and connects through the valve to the main exhaust; elbows are provided every seven feet apart, from which run 3 inch pipes across the building, connecting the two 4 inch pipes together. The steam that condenses in these pipes returns to the feed water heater through a smaller pipe, which connects to a spiral tube submerged in the water in the drums. With this arrangement the back pressure on the engine never exceeds four pounds. If for any reason the back pressure should exceed this amount, the valve on the roof opens and relieves it.

The C. & C. electric motors are built with interchangeable parts throughout, all parts being finished to standard gauges and drilled in standard jigs, while pedestals and caps are milled with standard cutters, thus insuring an interchangeability of parts that could be realized in no other way.

The writer hopes in the near future to be able to make efficiency tests of the actual power delivered and the fuel consumed, and also the efficiency of each transforming or transmitting device through the chain. From the practical standpoint the success of the plant has been unqualified. From the time steam was first turned on the engine until the present, not a single stop for repairs has been necessary, and frequently the shops are run fifteen or sixteen hours a day.—*Stevens Indicator.*

LECTURE EXPERIMENTS.*

By PETER T. AUSTEN.

Simple Apparatus for Showing the Formation of Nitrogen Peroxide, N_2O_4 , from Nitric Oxide, N_2O , the Solubility of the Former in Water, the Neutrality of Nitric Oxide, N_2O , and the Acidity of Nitrogen Peroxide, N_2O_4 .

THE following simple form of apparatus has worked very satisfactorily in my lecture room. A large cylinder, best a 1,000 c. c. glass-stoppered graduated cylinder,

der, is fitted with a double-bored rubber stopper, and provided with two glass-stoppered tubes. The tubes should not be over three-sixteenths of an inch internal diameter, and the long one may, if desired, be drawn to a jet about one-eighth of an inch in diameter. The cylinder is filled with water, to which has been added enough litmus solution and a drop of caustic soda (not ammonia) to impart to it a deep blue color. The cylinder is next half filled with nitric oxide, N_2O , which must be passed through a washer filled with a ten per cent. solution of caustic soda, in order to remove all traces of acid and the peroxide, N_2O_4 , which might otherwise pass over and redden the litmus solution. The rubber stopper and tubes are introduced and pushed in tight. This is done in the deep trough in the lecture room, care being taken that the cocks are both open, so that the tubes may be entirely filled with water. After the stopper has been inserted, the cocks are closed and the apparatus lifted out of the water. The colorless nitric oxide, N_2O , and the fact that it does not affect the litmus, are observed.

Holding the cylinder in a vertical position with one hand, the cock of the long tube and the cock of the short tube are successively opened with the other. Air enters through the long tube, while the water flows out through the short one. The water is allowed to flow out until the change of color of the gas is apparent. The cock of the short tube and the cock of the long tube are then successively closed, the cylinder held horizontally, and the water allowed to flow to and fro several times. The red peroxide, N_2O_4 , dissolves in the water, forming nitric and nitrous acids, and the gas becomes colorless, while the blue color of the solution changes to red. The cylinder is now held vertically, and the ends of both the tubes immersed in water.

* Communications from the Chemical Laboratory of Rutgers College.

THE PARIS EXHIBITION—STONE-CUTTING MACHINERY, TRAGNEAUX QUARRY, BELGIUM.

Brussels exhibition last year. The patents are held by the Societe Anonyme Internationale du Fil Helicoidal, Brussels, of which M. Wilmart is managing director.—*The Engineer.*

A MODEL ELECTRICAL MANUFACTORY.

By L. W. SERRELL, Jr., M.E., 1884.

WHILE electric motors have been used for some time past for operating many small manufacturing establishments, there has never, to the writer's knowledge, been installed a factory employing over one hundred men and depending upon electric power alone as a prime mover. Such, however, is the plant the construction of which the writer has recently superintended. This is the new factory of the "C. & C." Electric Motor Co., at 341 Greenwich Street, New York City.

The building is a thoroughly fireproof structure, built entirely of iron and stone. The floors are made of granolithic cement, with a slight slope draining to the center of the side walls to sewer connections, and may be washed down with a hose, or flooded in case of fire, with water taken from a 15,000 gallon tank on the roof. This tank also supplies the water necessary to operate the elevator, and receives its supply from an artesian well under the building. The walls are provided with conduits built in them for the electric wires.

The electric power generating plant is in the basement, and the only possible means of distributing power around the building is through the wires which run out of the dynamo room. As the structure of the building does not allow of the running of belts from floor to floor, dependence is had entirely upon electricity as a motive power.

The power-generating plant consists of a 12 by 12 inch Ball engine, belted direct to a No. 20 Edison dynamo, of 50,000 watts capacity, compound wound for 220 volts; the engine also drives through a countershaft a constant potential and a constant current dynamo used in testing. A central station switchboard is arranged beyond the dynamo, from the "bus" wires, on which are tapped independent circuits to each floor. At present four motors are employed, two of $3\frac{1}{2}$ horse power, one of 2 horse power, and one of 1 horse power; yet these small machines, fixed in out-of-the-way places, furnish power for 22 engine lathes, 8 drill presses of various sizes, 4 milling machines, 2 power presses, several iron planers, besides tapping machines, grindstones, emery wheels, and a 60 inch boring mill, making in all a total of about 45 machine tools.

Power tests made in the engine room, when a full force of men is working in the shops, show a load of 22 horse power on the engine and an electrical output of $13\frac{1}{4}$ horse power on the dynamo. This may seem incredible, but when we remember that every time a machine is shut down the motor is instantly relieved of that amount of work, and takes just so much less current, and the dynamo supplying less current takes less power to drive it, we can more readily see how such figures are not so improbable after all, especially in cases where the shafting load is light.

In actual practice, probably not over half the machines are doing actual work at the same time; thus one man may be setting his work in position while the man at the tool next to him may have his machine in operation doing work. Hence in a carefully laid out shop, with short lengths of shafting, making a light friction load, there may be installed machines requiring, if all were worked at precisely the same instant, nearly double the amount of power represented by the motors installed. This is analogous to the case of an electric light station where the number of lamps placed on a circuit would require, if all were burning at precisely the same instant, more than double the

A diagram of current delivery from the dynamo is given, the ordinates representing the ampere load, and the abscisses the time of day. In early morning and toward evening the curve is much higher, owing to lights being thrown on, but the power curve itself is nearly a straight line. The building is wired for 220 lights, connected two in series, and each floor is provided with a separate switchboard, to which the terminals of the various light circuits are brought. The circuits

are so arranged that the darker portions of the shop may be lighted independently of the other portions.

The building is heated with the exhaust steam from the engine, which exhausts into a 6 inch pipe that runs through the upper part of a large horizontal drum, used as a feed water heater, and thence up to the roof, where it exhausts into the air when not used for heating. The upper end of the exhaust pipe is provided with a check valve which opens when the back pressure reaches a certain amount. Valves are

A cylinder filled to the brim with water is best adapted to this, as it allows the gas cylinder to be held well up so that it may be easily seen by all. The cock of the long tube is now opened, when the water rushes up and spurts up as a fountain, usually striking the head of the cylinder. When the vacuum has been filled by the entering water, the cylinder is lifted up, thus removing the seal from the tubes, the cock of the short tube is opened, which allows more water to flow out and air to enter. The experiment is then repeated as just described. Four to six repetitions can usually be made before the nitric oxide, N_2O , is entirely consumed. The experiment is an unusually effective one.

The apparatus may be made in a simpler and cheaper form by putting in place of the glass stop-cocks on the long tube a four inch piece of soft rubber tube, clamped at the middle by a pinch-cock, and in the short tube a Kronig valve. This form of the apparatus works in every way as well as the other, but is not so elegant.

Experiments with Gaseous Hydriodic Acid.

After some experimenting, I found the following mixture to yield hydriodic acid gas in abundant quantities: In a six ounce flask are placed 20 grammes of iodine, 5 grammes of potassium iodide, 2 grammes of red phosphorus, and 10 c. c. of water. The whole is well mixed by swirling the flask, and then gently heated. As soon as the action begins, the flask is at once thrust under the cold water tap until the violence of the action ceases, which occurs in a few seconds. The mixture at once ceases to evolve the gas, but on heating will evolve a large amount, the evolution ceasing as soon as the heat is removed. It is well to pass the gas through an empty Silliman washer, in order that any of the liquid which may distill over may deposit. As a rule, if the heating is too violent, no distillation will take place till toward the end. Vessels can be easily filled with the gas by displacement, the level of the gas being ascertained by introducing a lighted wax lamp lighter.

Potassium chlorate placed in an iron deflagration spoon and heated to boiling, and introduced into a jar of the gas, takes fire and burns with a large red flame, forming clouds of iodine gas and crystals. The sides of the jar become rapidly coated with a deposit of iodine crystals. The reaction is, of course, simply a flame of oxygen in hydriodic acid.

Magnesium.—I was in hope that magnesium would take the iodine away from hydriodic acid, but it does not. A piece of ribbon, when ignited and in full blaze, was dropped into the bottom of a cylinder filled with the gas. It continued to burn for an instant, and was then extinguished. There was, of course, some dissociation of the hydriodic acid.

Sodium, heated red hot and burning, was introduced into a cylinder of the gas, but behaved like magnesium.

Nitrous oxide.—The experiment is best performed by placing a cylinder of the hydriodic acid gas on a cylinder of the nitrous oxide, drawing the glass covers and allowing the gases to mix. A white cloud forms which gradually becomes reddish. Drops of red liquid collect at the bottom, and soon the tubes become filled with a cloud of minute iodine crystals, which gradually deposit on the sides. The red liquid is a solution of iodine in hydriodic acid, and soon deposits crystals of iodine. The water formed by the reaction dissolves some of the hydriodic acid, and this solution dissolves some of the iodine set free. The liquid gives off ammonia when treated with caustic alkali. The reaction appears to be $N_2O + 12HI = 2NH_4I + H_2O$.

The gradual separation and deposition of the iodine makes an interesting phenomenon. The presence of ammonia in the deposited liquid should be demonstrated.

Nitric acid gas, evolved from a mixture of granulated potassium nitrate and sulphuric acid in a small flask, and allowed to issue from a bent-up glass tip having an orifice of about one-eighth of an inch in diameter, takes fire when introduced into the gas, and burns with a fine red flame tipped with a halo of violet iodine gas and a cloud of minute iodine crystals. The sides of the vessel soon become coated with a deposit of iodine crystals.

Chlorine gas, evolving from the apparatus just described, takes fire when introduced into the hydriodic acid gas, and burns with a fine red flame resembling the preceding phenomenon. The stream of chlorine should be rapid, or else no flame, but only the separation of iodine described by Heumann, will be obtained.

Sulphur dioxide makes an effective experiment, and one which is particularly appropriate in demonstrating a chemical change between gases. The cylinder full of hydriodic acid gas is placed on the one containing sulphur dioxide and the glass covers drawn. The colorless gases mix, flashing out deep red, and the sides of the cylinders are at once covered with a deposit of iodine crystals.—*Am. Chem. Journal*.

NITROGEN FOR LECTURE PURPOSES.

By CHARLES R. C. TICHBORNE, LL.D., F.I.C., etc.

THE best method of preparing nitrogen for lecture experiments, or when required in a pure form, is unquestionably (in my opinion) based upon the decomposition of ammonium nitrite. That process possesses numerous advantages over all the others. It is sufficient to enumerate the simplicity of the reaction, the purity of the product, and the ease with which the experiment is performed. The apparatus required is a retort of the right size and a bent tube.

For the last ten years I have been in the habit at my lectures of falling back upon this method when I came to the subject of the oxygen compounds of nitrogen. The symmetric manner in which this reaction harmonizes with the production of laughing gas is most instructive, and is a special inducement to use it as a lecture illustration. Here we have the production of a molecule of nitrogen by the splitting up of the nitrite, while the nitrate gives us a molecule of the monoxide.

A statement in the article (*Chemical News*, vol. lix., p. 135) runs as follows: "The action of potassium nitrite, when heated in a suitable apparatus in admixture with ammonium chloride, produces when prepared cautiously a moderately pure gas, but, owing to the

inconsistency of the reaction, the same is rendered considerably tedious and unprofitable.

As this is contrary to my experience, I think it desirable to give the *modus operandi* which I have adopted, presuming that if the modifications and precautions which I indicate be strictly carried out, the experiment will turn out satisfactorily.

Ten grms. of ammonium sulphate and ten grms. of sodium nitrite are mixed in a capacious retort with 40 c. c. of glycerin and 60 c. c. of water. The retort should be of the capacity of half a liter, or about 16 ounces. The retort is placed with the neck elevated to an angle of about forty degrees, so that the water may condense and fall back into the retort. A bent tube is fitted with a cork into the neck, and conducts the gas into a wash bottle, or it may be collected at once for general purposes without washing.

100 c. c. of water may be used in place of the mixture of glycerin and water, but it does not seem to work quite so regularly. Heat is applied directly to the retort, and the disengagement of free nitrogen begins at a temperature a few degrees below the boiling point of water. It steadily but rapidly proceeds—the temperature generally rises a few degrees above the boiling point, but after a little time again begins to fall. A gentle but constant heat will, however, keep up the disengagement of gas until the nitrite is all decomposed. It is desirable to slightly increase the heat toward the end of the reaction.

There is nothing specially new in this process, except the substitution of the sulphate for the chloride, and in the determining of the exact conditions under which the experiment may be carried on successfully for class illustrations, or for the purposes of procuring pure nitrogen with the least expenditure of trouble. If the reaction is pushed on very rapidly, ammonia will be evolved, and this phenomenon is most marked when using the chloride in place of the sulphate. If carried on slowly with the sulphate, no ammonia is evolved, but a trace of nitrogen dioxide is produced, which may be easily removed by washing with a dilute solution of permanganate of potassium. By carefully regulating the temperature, almost pure and neutral nitrogen will be evolved.—*Chem. News*.

THE SCIENTIFIC AMERICAN Architects and Builders Edition.

\$2.50 a Year. Single Copies, 25 cts.

This is a Special Edition of the SCIENTIFIC AMERICAN, issued monthly—on the first day of the month. Each number contains about forty large quarto pages, equal to about two hundred ordinary book pages, forming, practically, a large and splendid *Magazine of Architecture*, richly adorned with *elegant plates in colors* and with fine engravings, illustrating the most interesting examples of modern Architectural Construction and allied subjects.

A special feature is the presentation in each number of a variety of the latest and best plans for private residences, city and country, including those of very moderate cost as well as the more expensive. Drawings in perspective and in color are given, together with full Plans, Specifications, Costs, Bills of Estimate, and Sheets of Details.

No other building paper contains so many plans, details, and specifications regularly presented as the SCIENTIFIC AMERICAN. Hundreds of dwellings have already been erected on the various plans we have issued during the past year, and many others are in process of construction.

Architects, Builders, and Owners will find this work valuable in furnishing fresh and useful suggestions. All who contemplate building or improving homes, or erecting structures of any kind, have before them in this work an almost endless series of the latest and best examples from which to make selections, thus saving time and money.

Many other subjects, including Sewerage, Piping, Lighting, Warming, Ventilating, Decorating, Laying out of Grounds, etc., are illustrated. An extensive Compendium of Manufacturers' Announcements is also given, in which the most reliable and approved Building Materials, Goods, Machines, Tools, and Appliances are described and illustrated, with addresses of the makers, etc.

The fullness, richness, cheapness, and convenience of this work have won for it the **Largest Circulation** of any Architectural publication in the world.

A Catalogue of valuable books on Architecture, Building, Carpentry, Masonry, Heating, Warming, Lighting, Ventilation, and all branches of industry pertaining to the art of Building, is supplied free of charge, sent to any address.

MUNN & CO., Publishers,
361 Broadway, New York.

Building Plans and Specifications.

In connection with the publication of the BUILDING EDITION of the SCIENTIFIC AMERICAN, Messrs. Munn & Co. furnish plans and specifications for buildings of every kind, including Churches, Schools, Stores, Dwellings, Carriage Houses, Barns, etc.

In this work they are assisted by able and experienced architects. Full plans, details, and specifications for the various buildings illustrated in this paper can be supplied.

Those who contemplate building, or who wish to alter, improve, extend, or add to existing buildings, whether wings, porches, bay windows, or attic rooms, are invited to communicate with the undersigned. Our work extends to all parts of the country. Estimates, plans, and drawings promptly prepared. Terms moderate. Address

MUNN & CO., 361 BROADWAY, NEW YORK.

THE

Scientific American Supplement.

PUBLISHED WEEKLY.

Terms of Subscription, \$5 a year.

Sent by mail, postage prepaid, to subscribers in any part of the United States or Canada. Six dollars a year, sent, prepaid, to any foreign country.

All the back numbers of THE SUPPLEMENT, from the commencement, January 1, 1876, can be had. Price, 10 cents each.

All the back volumes of THE SUPPLEMENT can likewise be supplied. Two volumes are issued yearly. Price of each volume, \$2.50 stitched in paper, or \$3.50 bound in stiff covers.

COMBINED RATES.—One copy of SCIENTIFIC AMERICAN and one copy of SCIENTIFIC AMERICAN SUPPLEMENT, one year, postpaid, \$7.00.

A liberal discount to booksellers, news agents, and canvassers.

MUNN & CO., Publishers,

361 Broadway, New York, N. Y.

TABLE OF CONTENTS.

	PAGE
I. ARCHÆOLOGY.—The Origin and Manufacture of Playing Cards.—By GEORGE CLULOW.—A most interesting lecture recently delivered before the Society of Arts, in London, giving the history of playing cards and the different methods of manufacturing them used at different epochs, down to and including the present time.	11240
II. CHEMISTRY.—Lecture Experiments.—By PETER T. AUSTEN.—Experiments showing the reactions of different oxides of nitrogen, and also with gaseous hydriodic acid.—1 illustration	11249
Nitrogen for Lecture Purposes.—By CHARLES P. C. TICHBORNE, LL.D.—The production of pure nitrogen from ammonium sulphate and sodium nitrite, with formula and full details of manipulation	11250
III. CIVIL ENGINEERING.—Bridge over the Indus at Sukkur.—A new railway bridge recently completed in India, giving a peculiar modification of the cantilever structure.—1 illustration	11244
Mechanical Quarrying and Stone Cutting.—An interesting review of the machinery in the Traigneux Quarry, in the province of Namur, Belgium, illustrating the application of the continuous wire as well as of other machinery for cutting stone.—24 illustrations	11248
IV. ELECTRICITY.—A Model Electrical Manufactory.—By L. W. SERRELL, JR.—A new factory of the C. & C. Electric Motor Co. in this city described, with a diagram of the current delivery at all periods of the day.—1 illustration	11249
V. MECHANICAL ENGINEERING.—A Three Hundred Horse Power Jonval Turbine.—A large turbine recently constructed in England for use in the Transvaal Gold Fields, adapted for transportation to the South African deserts.—1 illustration	11245
Pumping Machinery, Ancient and Modern.—First installment of a Sibley College lecture.—By Mr. J. F. HOLLOWAY.—Giving an exhaustive review of the direct-acting steam pump.	11245
The Pulsometer.—By Prof. DE VOLSON WOOD.—The Pulsometer described and illustrated, with a mathematical analysis of its work and efficiency.—1 illustration	11244
Water Softening.—By GEORGE E. DAVIS.—A discussion of the proper treatment of water for use in boilers, with a view to the prevention of scale and corrosion by producing a soft deposit.	11247
VI. MEDICAL.—Hypodermic Injections of Quinine in Malaria.—An excellent suggestion for malaria treatment, involving the subcutaneous application of quinine, with formula.	11241
VII. MISCELLANEOUS.—The Catastrophe at Samoa.—A note of the disaster to the German ships, with illustrations of their wreck in the recent hurricane.—2 illustrations	11239
VIII. NAVAL ENGINEERING.—The Structural Strength of Sea-going Torpedo Boat No. 1.—By Lieut. F. J. DRAKE, U. S. Navy.—Commencement of a most elaborate review, with exhaustive calculations of the constants of the new sea-going torpedo boat.—5 illustrations	11242
IX. TECHNOLOGY.—A New Flexible Cloth.—An improved method of making twills, diagonals, and other double-backed cloths, with illustrative diagrams of the arrangement of the warp and weft threads.—3 illustrations	11247

A New Catalogue of Valuable Papers

Contained in SCIENTIFIC AMERICAN SUPPLEMENT during the past ten years, sent free of charge to any address. MUNN & CO., 361 Broadway, New York.

Useful Engineering Books

Manufacturers, Agriculturists, Chemists, Engineers, Mechanics, Builders men of leisure, and professional men, of all classes, need good books in the line of their respective callings. Our post office department permits the transmission of books through the mails at very small cost. A comprehensive catalogue of useful books by different authors, on more than fifty different subjects, has recently been published, for free circulation, at the office of this paper. Subjects classified with names of author. Persons desiring a copy have only to ask for it, and it will be mailed to them. Address,

MUNN & CO., 361 Broadway, New York.

PATENTS.

In connection with the Scientific American, Messrs. MUNN & Co. are solicitors of American and Foreign Patents, have had 42 years' experience, and now have the largest establishment in the world. Patents are obtained on the best terms.

A special notice is made in the Scientific American of all inventions patented through this Agency, with the name and residence of the Patentee. By the immense circulation thus given, public attention is directed to the merits of the new patent, and sales or introduction often easily effected.

Any person who has made a new discovery or invention can ascertain, free of charge, whether a patent can probably be obtained, by writing to MUNN & Co.

We also send free our Hand Book about the Patent Laws, Patents, Caveats, Trade Marks, their costs and how procured. Address

MUNN & CO.,
361 Broadway, New York,

Branch Office, 622 and 624 F St., Washington, D. C.