(Paper No. 2383.)

"Balanced Slide-Valves."

By JOHN CARTER PARK, M. Inst. C.E.

THIS communication is illustrative of various forms of balanced or partly balanced slide-valves, which have been from time to time experimented with on the locomotives in use on the North London Railway, with the dates of their introduction (Plate 7, Figs. 1 to 11).

Figs. 1, $\frac{M}{1}$ (1856), show a form of valve having the steam admitted through the steam-chest cover to the inside of the valve, the steam-chest being relieved of pressure and communicating only with the exhaust; the steam-lap in this case is on the inside, which reduces the size of the valve.

Figs. 2, $\frac{M}{95}$ (1863), show a pair of balanced-valves as applied to a six-wheeled coupled goods engine No. 11, having inside cylinders. Each valve is in three pieces, and works between two parallel faces, the valves being fitted with adjustable wedges to take up the wear. The valves were never tight, and the difficulty of obtaining and maintaining parallel faces when hot was so great that they were taken out after a few weeks' trial.

Figs. 3, $\frac{M}{4}$ (1867), show a valve on Thomas Adams' principle, having a relief-ring fitted to the back of the valve, and working between the cylinder-face and the steam-chest cover. The relief ring is kept up to the cover-face by the spring shown. The valve exhausts the steam through the steam-chest cover, the ordinary exhaust-port being blocked up, and the engine had a very free exhaust; it ran for about six months, but the valve ultimately had to be taken out owing to leakage through the relief-ring.

Figs. 4, $\frac{M}{5}$ (1867), show another form of a pair of Thomas Adams' valves, fitted within a very narrow space to an inside-cylinder engine. These valves had two relief-rings, and ran for some six months; they, however, required too much attention to keep tight, and they had to be replaced by the ordinary valves.

Figs. 5, $\frac{M}{6}$ (1868), represent another valve of cast-iron on Thomas Adams' principle, fitted with one large relief-ring; this valve was

[THE INST. C.E. VOL. XCVIII.]

2 B

applied to a standard passenger outside-cylinder engine, and great trouble was experienced in keeping it tight. The back of the valve, though bored out truly to receive the ring, was not found to be round when hot; the ring used to stick, the packing-ring would not remain tight, and although the leakage was reduced to a minimum, still it increased the consumption of fuel, and the valve was replaced by the old one.

Figs. 6, $\frac{M}{7}$ (1869), are a form of valve designed by the late David Park. It was fitted to an outside-cylinder passenger engine. The novel feature in this valve was that a large portion of the load on the valve was taken by the relief-ring and carried on a steel roller running on a bridge-piece inserted over the exhaust-port. This valve soon gave trouble owing to the wear of the roller, and the seizing of the pin; it was replaced by the old valve after two or three months' trial.

Figs. 7, $\frac{M}{10}$ and $\frac{M}{12}$ (1871), are two views of Outridge's form of balanced-valves fitted to an outside-cylinder engine. The port face is covered by a plate having the steam and exhaust-passages through it, corresponding to those in the cylinder face. The valve works at right-angles to the ordinary face between two port faces, one being adjustable to take up the wear, and the size of the valve is reduced to about one-half the ordinary size. The plate is free to drop away from the cylinder face when steam is shut off to avoid "pumping," and rests against the stud S. The difficulty in obtaining steam-tight parallel faces was again experienced; but after careful adjusting, the valve was sufficiently tight to run, which it did for some months. The reversing-lever was easily handled, with steam at 160 lbs. per square inch full on, and the wear was very slight on the face of the valve; but constant attention was required to keep it tight, and it was replaced by the old valve, there being no saving of fuel.

Figs. 9, M, represent a pair of Dawe's valves tried on an outside-cylinder engine. In this class of valve the relief-frame is connected to the back of an ordinary valve by a flexible steel diaphragm, so that the valve is practically one piece. Owing to the inability of this valve to leave the faces when running without steam, pumping is set up, causing a partial vacuum in the steam-chest; the diaphragm soon failed and took a permanent set, steam blowing through, and finally it cracked round the frame.

Figs. 10, $\frac{M}{9}$ (1873), show a pair of cast-iron balanced slide-valves designed by Mr. Manico, and tried in No. 63, inside-cylinder pas-

senger engine. There were only two parts in this valve, namely, the valve proper, and the relief-plate. The valve was simply a frame, perforated on its inside and outside edges, to give quick admission and release; the relief-plate had duplicate steam-ports on the inside, and was free to leave the valve when steam was shut off, thus avoiding pumping. The valve was in perfect balance, and the reversing-lever was quite free with steam full on. These valves at first gave promise of success; but, after a few weeks, it was found that the relief-plate, although $1\frac{3}{8}$ inch thick, sprang slightly with the pressure, causing the valve to wear hollow and steam to blow through.

Figs. 11, $\frac{M}{74}$ (1886). This form of valve is similar to the valves in use on the Grand Trunk Railway of Canada, except that the valve works vertically instead of horizontally.

It is simply an ordinary valve with packing-strips fitted to the back to work against the inside face of the steam-chest cover; the packings are kept up to the face by twelve spiral springs, and the steam-chest cover is provided with a port to convey the steam to the front end of the chest. The air-valve opens inwards, and prevents a vacuum being formed when running without steam; a hole drilled in the back of the valve puts the space within the area of the packing-strips in communication with the atmosphere. Although carefully fitted, these valves were never tight, and were replaced by the old valves.

The communication is accompanied by eleven tracings, from which Plate 7 has been engraved.

Fig^s 1.

This improvement consists in passing the steam through valve to the cylinder thereby disposing entirely with the pressure of steam on the back of the valve, which will diminish at least 15 per cent the friction on the valve and eccentric gearing. This improvement has also another very important advantage over the old valve, in so much as it disposed very considerably with the loss from radiation, especially in the outside cylinder engines as the steam or valve-chest in the old system is always full of steam and exposed to the cold air whereas the valve chest with this improvement is only filled with the exhaust steam.

Fig^s 2.

Fig^s 3.

Fig^s 4.

Fig^s 5.

Fig^s 6.

Fig^s 7.

Fig^s 8.

Scale, 1 Inch = 1 Foot.

Fig^s 10.

Fig^s 11.

Fig^s 9.