THE ARMORED CRUISER "RURIK."

RUSSIA'S NEW ADDITION TO HER NAVY.

BY PERCIVAL A. HISLAM.

THE armored cruiser "Rurik," which has recently left the works of Messrs. Vickers, Sons & Maxim on acceptance by the Russian naval commission, is the first large vessel to be completed for the Russian navy since the close of the war with Japan. The designs were originally completed before the close of that conflict, but as a result of the lessons of the war they were considerably modified, the principal alterations taking the direction of greater structural strength and protection against underwater attack.

The "Rurik" is 490 feet long between perpendiculars, with a beam of 75 feet and a normal draft of 26 feet, giving a displacement of 15,200 tons. She has a very powerful armament, consisting of four 10-inch guns, 50 calibers long, twin-mounted in barbets fore and aft on the center line. Each of these guns can be worked through 35 degrees of elevation and 5 degrees of depression, while the forward guns can be trained 45 degrees abaft the beam, and the after guns 45 degrees before the beam. There are also eight 8-inch 50-caliber guns, twin-mounted in barbets on the quarters of the ship, having an angle of fire of about 170 deg. For repelling torpedo attack there are twenty 4.7-inch guns of 50 calibers length. Sixteen of these are placed within an armored battery in the center of the ship, separated from each other by specially hardened armor. This battery, being on the upper deck, enables the secondary armament to be placed higher above the waterline than usual. There are four 4.7-inch guns aft, also behind armor, and to counteract the effect of raking fire, three armored bulkheads have been fitted. There are also twelve 47-millimeter, quick-firing guns, and two 18-inch submerged torpedo tubes, one on each bow.

The armament of the ship was subjected to very severe tests, at the instance of the Russian officers who superintended the trials on behalf of the naval

commission. For each caliber of gun mounted in the ship a "test" weapon was specially built, and from each of these there were fired 100 rounds with full charges. Following this, 30 rounds were fired from two of the 10-inch guns, and two of the 8-inch guns, and fifteen from all the others, at varying angles of elevation and training. All the guns are operated by electrical mechanism, and the guaranteed rate of fire is two rounds a minute from the 10-inch, three from the 8-inch, and eight from the 4.7-inch guns, representing an aggregate discharge of 16,384 pounds of metal a minute, of which the 10-inch and 8-inch guns account for 9,184 pounds.

The "Rurik" is, for her size, very efficiently protected. She has a main belt 12 feet deep extending for 270 feet of her length, and this belt is 6 inches thick, the material being Krupp steel. At the bows the thickness is reduced to 4 inches, and at the stern to 3. The central battery of 4.7-inch guns is protected by 3 inches of armor, the strake extending for a length of 200 feet and including all the heavy-gun barbets. These barbets are constructed of 7¼-inch Krupp steel plates, while the walls of the conning towers, of which there are two, are 8 inches thick. There are two protective decks having a total thickness of 4 inches, and the bases of the funnels are protected by armor casings. The whole of the machinery and magazines below the waterline are surrounded by armored walls extending from the main deck, through the protective decks right to the bottom of the ship, and since this is in addition to the usual double skin, the ship is practically armored from the keel to the upper deck.

The machinery of the "Rurik" consists of two sets of four-cylinder quadruple-expansion engines, steam being supplied by twenty-eight Belleville boilers. The latter work at a pressure of 285 pounds to the square

inch, which is reduced to 250 pounds at the engines. There was no full-speed stipulation in the contract, the conditions being that the ship should be able to steam an easy 21 knots with only 75 per cent of her boiler power. This was done for three hours, and then a ten-hour run at full power was made. The results of these and of the other steam trials are shown in the following table:

	Mean of 30 Hours at 12 Knots.	Mean of 90 Hours at 19 Knots.	Mean of 10 Hours at 21 Knots.	Mean of 3 Hours at 21 Knots, with 75% Boiler Power.	Mean of 10 Hours at Full Power.
Steam pressure, pounds per square inch.	196	261	269	273	280
Vacuum, inches.	27.12	27	26	24.8	25.2
Revolutions per minute.	75.6	123.85	138.48	138.3	141.6
Indicated horse-power.	3,039	13,359	19,356	18,953	20,675
Number of boilers in use.	8	21	28	21	28
Air pressure in stokeholds, inches.	0.13	0.3	0.31	0.58	0.36

It will be noticed from the accompanying photographs that the "Rurik" differs considerably in appearance from the British cruisers of the "Indomitable" type. The huge tripod masts are missing, the Russian vessel having only a light signaling mast with a searchlight platform low down. The fire-control stations, which are high up on the masts of the British ships, are comparatively low in the "Rurik." They are constructed of 5-inch armor, and are situated a little fore and aft of the masts. The ship came through all her trials with uniform success, and will be a formidable addition to the Czar's navy. It is probable that she will be the last Russian warship to be built abroad, as the naval commission decided last year that all new ships were to be laid down in home yards.

ELECTROLYSIS AND CORROSION.*

HOW RUSTING IS PRODUCED.

BY ALLERTON S. CUSHMAN.

It is assumed for the purpose of this paper that by corrosion we mean the effects produced on the metals by the combined action of water and oxygen, with or without the stimulus provided by various impurities in the water or in the atmosphere. Few authorities now deny that in this sense of the word corrosion of all metals is simply a matter of electrolysis. It is necessary, however, before proceeding with the discussion to be quite sure that we are all accepting the same definition of electrolysis. The word was first used by Faraday to express the decomposition of compounds by the electric current, but to-day it is used in a wider sense, and electrolytic phenomena are recognized whenever a strip of any ordinary metal is immersed in water. There has unfortunately been a widespread impression that electrolysis, as it applies to the corrosion of metals, can take place only if the electricity, or electrical circuit involved, can be traced to some definite extraneous source. Thus it has come about that engineers, metallurgists and others to whom the causes of deep corrosion and pitting of metals is a matter of anxious inquiry, have wasted much valuable time feeling about with voltmeters and galvanometers in vain efforts to locate and insulate the dangerous intruder. While it is not my present intention to combat the idea that stray, escaped currents play a contributory part in some cases of corrosion, I wish to point out emphatically that corrosion is eternally going on where no extraneous currents can be held responsible for the damage.

In order to understand exactly what is meant it will be necessary to consider briefly the modern physico-chemical explanation of electrolytic solution-tension. It is well known that when a liquid or a solid is heated, some of the molecules pass into the form of vapor or gas, and in any closed space equilibrium is established for a given temperature when the vapor exerts a certain definite pressure. As Nernst, who first gave expression to this phase of the modern theory of solution, puts it: "If, in accordance with

Van't Hoff's theory, we assume that the molecules of a substance in solution exist under a definite pressure, we must ascribe to a dissolving substance in contact with a solvent, similarly a power of expansion, for here also the molecules are driven into a space in which they exist under a certain pressure. It is evident that every substance will pass into solution until the osmotic partial pressure of the molecules in the solution is equal to the solution-tension of the substance."

To use a rough analogy, this is no more complicated than saying that a company of people pressing from one room into another will find themselves in comfortable equilibrium just as soon as the expansive power of the company in the newly occupied space is about equal to that left in the originally overcrowded one. It should be understood, however, that individuals may be passing continually backward and forward between the rooms without essentially disturbing the equilibrium, but if we further assume that some barrier or force prevents a person having once passed into the new room from exerting back-pressure, the stream of new arrivals will continue, to the depletion of the company in the original room. Also precisely the same result would accrue if the individuals pressing into the second room were slowly but constantly being removed by passing down a narrow stairway and thus being removed from the scene of action. Leaving now this rough analogy, whose application, however, will soon be apparent, we may return to Nernst's conception of solution-tension. The metals, probably without a single exception, have the possibility of passing into solution as positive ions, that is to say, as atoms carrying relatively to their mass enormous static charges of positive electricity. Every metal in water has a solution-tension peculiar to itself, provided it is pure, but, as we shall see, this property is enormously modified under most circumstances by a most remarkably small presence of certain impurities. To quote from a well-known text-book, Jones's "Elements of Physical Chemistry"

"If we dip a metal into pure water, let us see what will take place. In consequence of the solution-tension of the metal, some ions will pass into solution. When metallic atoms pass over into ions they must secure positive electricity from some thing. They take it from the metal itself, which thus becomes negative. The solution becomes positive, because of the positive ions that it has received. At the plane of contact of the metal and solution there is formed the so-called electrical double layer, whose existence was much earlier recognized by Helmholtz. The positively charged ions in the solution and the negatively charged metal attract one another and a difference of potential arises. The solution-tension of the metal tends to force more ions into solution, while the electrostatic attraction of the double layer is in opposition to this. Equilibrium is established when the two forces are equal. Since the ions carry such enormous charges, the number that will pass into solution before equilibrium is established is so small that they cannot be detected by any ordinary method."

It is apparent from this, that since under the ordinary conditions of service metals suffer corrosion only by first passing into solution, the corrosion can only be prevented or inhibited either by aiding the resistance to the entrance of more ions into solution or by covering the surface of the metal with a water-proof coating, or by doing both these things at the same time, on the principle that a double barrier is more impregnable than a single one. If we had to deal always with chemically pure 100 per cent metals, which were also perfectly physically constant as to surface conditions, and if natural waters were absolutely pure, the electrical double layer would be sufficient to protect all metals from continuous corrosion. Needless to state, this is not the case. Let us then examine the forces which are operating in the direction of continued corrosion, as an understanding of these may point the way to various methods of throwing against them opposing forces. It is well known that even the purest water that it is possible to pre-

* A paper read before the American Society for Testing Materials.

pare is to some extent dissociated; that is to say, it contains free positively charged hydrogen ions, while ordinary natural water contains very many more free ions than pure water, as the measurement of its electric conductivity serves to show.

When this is the case the entering metallic ions do not have to take their positive charges with them, leaving the metal surface negative, but they now assume the positive charges carried by the hydrogen ions, which immediately pass into the atomic condition and make their exit from the system, as effectually as the individuals in our analogy did by proceeding down the staircase. Relieved of the pressure of the hydrogen ions further dissociation of the water takes place and the action may thus go on continuously, although in the case of most metals it is so exceedingly slow that it is not visible to the eye. The direct result of this action is that the electrical double layer is continually being broken down and if it breaks down at weak spots, which for any reason whatsoever exist on the surface of contact, we shall have corrosion taking place more rapidly at some points than at others and the results will be a pitting effect.

Leaving this phase of the subject for the present, if we inquire which among the common metals have high and which low solution-tensions, we shall find that magnesium, zinc, aluminium, iron, and the like are always negative when in solutions of their own salts. This means that the solution-tension of the metal is always greater than the osmotic pressure of the metal ion in any solution that can be prepared. On the other hand, with such metals as gold, silver, mercury, and copper the metal is usually positive when immersed in a fairly strong solution of its salt, although in very diluted solutions even these metals may appear negative.

Among the metals iron is unique in the fact that its physical characteristics are tremendously modified and changed by the presence of extremely minute quantities of other elements; thus, to mention one well-known instance, the electrical resistance of iron rises rapidly with an extremely small increase in the manganese content. That the surfaces of specimens of iron, when wetted, throw themselves into positive and negative nodes, corrosion taking place more rapidly at the positive poles, has been shown by means of the ferroxy indicator, which was described in a previous paper (Bulletin 30, Office of Public Roads, U. S. Department of Agriculture). It will be interesting now to consider and, if possible, to interpret the facts disclosed by this test, as well as the general subject of rusting of iron, in the light of the modern theories of physical chemistry.

When a strip of ordinary steel is wetted with pure water, iron ions under the pressure of solution-tension pass into solution, but, owing to the uneven electrical condition of the surface, local couples are formed, and the solution is stimulated at the positive poles while it is resisted at the negatives. If no oxygen is present, however, equilibrium is established by the formation of an electrical double layer before any visible damage is done. In other words, the positive iron ions tend to cluster or crowd about the point of their formation where they have inevitably left the metal slightly negative and the continued entrance of more iron into solution is thus resisted. Once admit molecular oxygen to the system, however, and the condition of affairs changes. As is well known, molecular or atmospheric oxygen has the power of oxidizing ferrous ions to the ferric condition, which results in the precipitation by hydrolysis of the insoluble hydrated ferric oxide which is called rust, and its consequent removal from the solution system. As ferric hydroxide tends to migrate to the negative pole the inevitable result is that the clustering ferrous ions are removed, one is tempted to say dragged, away from the entrance, the electrical double layer is destroyed and more and more iron ions stream in as time goes on, only to be in turn removed by oxygen. Thus the damage from pitting slowly but surely proceeds. The conclusion to jump at is that if we must admit water to the surface of iron or steel, it is dangerous to admit oxygen, too. And at this point we find an explanation of some interesting facts that Prof. W. H. Walker is at present studying, and to which he first called my attention; namely, that tannic acid and pyrogallol acid when introduced into boiler water prevent pitting. Since these organic compounds fix the dissolved oxygen in the water, there is but little left over to attack the ferrous ions.

Since oxygen undoubtedly plays such an important part in the corrosion of iron, how, it may be asked, are we to find an explanation of the now widely known fact that such strong oxidizing agents as chromic acid and its salts prevent the corrosion of iron. The paradox seems the greater when we proceed to the consideration of this phase of the subject directly after having pointed out that a strong reducing agent like pyrogallol acid produces the same result. In order to understand the subject better, we must review what is known about the so-called passive state into which certain metals may be put, and here again I shall quote from Jones's "Physical Chemistry":

"It has long been known that when certain of the metals are subjected to special kinds of treatment they no longer have the properties that they usually possess. As early as 1790 Kier observed that when iron is dipped in nitric acid having a specific gravity of 1.45 it becomes passive, i. e., it is no longer attacked by dilute nitric acid. Further, it no longer has the power to precipitate metallic copper from a solution of a copper salt.

"Other strong oxidizing agents, such as chromic acid, also render the iron passive. The same result is frequently obtained when iron is made the anode in electrolysis.

"A number of metals other than iron can be rendered passive. We should mention especially chromium, copper, cobalt, and nickel.

"A number of attempts have been made to explain the passivity of the metals. Faraday and Schonbein explained the passivity in the case of iron, as due to the formation of a layer of oxide on the surface of the metal. This was natural when we consider that iron is rendered passive by strong oxidizing agents and loses its passivity when heated in a reducing gas.

"The oxide layer theory of passivity is now regarded as untenable, since the passive state has been brought about under conditions where oxidation is impossible; and, further, has been destroyed under conditions where any layer of oxide would not be disturbed.

"The same fate has befallen the theory that passivity is due to the formation of a protective layer of gas over the surface of the metal. The two views of passivity that have acquired the greatest prominence are those of Finkelstein and Hittorf. According to the former, active iron is bivalent and passive iron trivalent. This conclusion was based upon the difference in potential between iron electrodes and the iron salt in which they were immersed. The potential difference depends upon whether the iron salt is in the ferrous or in the ferric condition.

"Hittorf also points out that in the case of chromium the passive condition corresponds to the highest valence, and the active to the lower valence. He thinks that we have to do with two allotropic modifications of the elements, one of which is active and the other not."

If Finkelstein and Hittorf are correct, and the experimental work appears to justify their conclusions, the action of chromic acid and its salts in preventing the corrosion when present in sufficient concentration is very simply explained. Passive trivalent iron does not pass into solution and ionize and the reaction which produces oxidation cannot proceed. The second theory, however, which holds that the protection afforded by chromic acid is due to a polarization effect, and that the metallic surface is actually plated with ionic oxygen, is still very widely held in spite of the opinion advanced in the above quotation. Moreover, the polarization theory explains other effects which have been observed in the course of recent investigation along these lines, carried on independently by W. H. Walker and by myself. In my own laboratory it was observed that in making ferroxy mounts an indentation, scratch, or wound of any kind on the surface of the steel invariably became positive to its surrounding area, and thus formed a center of corrosion. If this had occurred only upon mill specimens, which carried a coat of scale or blue oxide, the explanation would be simple, but the fact is, if a freshly polished steel mirror receives a cut or wound before immersion, the marked place comes out in blue and corrosion naturally takes place more rapidly at the positive spots.

The fact thus brought out by experimental investigation has a direct bearing upon the results of observation in practice. I am informed by Commander Parks of the U. S. Navy Department that it has been known for a long time that indentations or injuries on the water surfaces of boilers always become centers of corrosion and pitting. It is certain that inspection should be very thorough in regard to this point, where resistance to corrosion is a matter of prime importance. It is a question whether the smoothing up and actual polishing of surfaces would not in the long run repay the trouble and expense. There are times when a sound boiler tube is of vastly more importance than a polished gun barrel.

It would seem from the facts brought out by the ferroxy test that the polarization effects which take place on the surfaces of iron or steel are determined by a number of widely different causes which may be classified as electrical, chemical, and mechanical. It seems probable that the surfaces of steel which are subject to the condensation moisture of the atmosphere are always in a certain state of electrical strain and polarity. Any change produced on the surface by cutting, stressing, or straining upsets the equilibrium, with the result that certain surface points are depolarized. The ferroxy tests show that in the very large majority of cases the positive spots once formed remain positive and so corrosion proceeds steadily to the formation of destructive pit holes.

As has been pointed out in previous papers, the purer and more homogeneous, chemically speaking, the

iron or steel, the less liable is the metal to suffer from localized rusting leading to pitting; but besides the important bearing which this chemical homogeneity has upon the problem, we now see that the physical and mechanical condition of the surface is of the greatest importance. It is undoubtedly true, as Burgess and Walker have shown, that the rapidity of corrosion is modified by the condition of strain that the metal may be under, and this, as has been pointed out, is undoubtedly due to the changes set up in the electrical state or condition of polarity on the surface of the metal. Again, the presence and distribution of mill scale on the surface is a modifying factor, as has been shown by Walker in an exceedingly interesting experiment.

All these factors must be taken into consideration when attacking this interesting and intricate subject, but I should wish to urge upon metallurgists the prime importance of studying the effects of the usual metallic impurities which accompany nearly all forms of merchantable iron and steel. Already many metallurgists are agreeing that the use of manganese in steel making has been overdone, and they are seeking to reduce the manganese content to the lowest practicable quantity. It was new to me until a few months ago, and I think must have been overlooked by many other workers along these lines, that impure metallic manganese, when in a fairly finely divided condition, is soluble in water, decomposing it with a rapid evolution of hydrogen. Since this is the case it is not surprising, if even slight segregation has taken place in manganiferous steel, that the polarization effects would be modified and increased.

Another interesting experiment shows that certain metals can be so mixed as to give off a very rapid evolution of hydrogen when brought in contact with cold water. I have studied the action of water on a number of combinations of metals by mixing them together in the form of powders and then compressing the mixtures in a die into tablets under a pressure of 50,000 pounds to the square inch. The amount of hydrogen given off and collected in a given time by equal weights of these compressed tablets when acted on by cold water is distinctly modified and determined by the electrolytic effects which are produced. Metallic magnesium is stated in the text-books on the authority of Liebig, Bunsen, and others, not to decompose cold water, but we have not as yet encountered a sample of magnesium that did not vigorously give off bubbles of hydrogen in cold water. An interesting experiment can be shown in which tablets made from pure aluminium and pure zinc are placed in cold water side by side with a compressed alloy of the two. The first two tablets are not visibly attacked by the water, while the hydrogen comes from the alloy with all the vigor exhibited by an effervescent salt.

It is safe to state that the tendency of metallic impurities to produce electrolytic effects on the active surfaces of the various industrial metals, has not received the attention that the problem demands.

As I stated last year, there are two distinct lines along which progress may be made in combating the damage done by corrosion. One is a metallurgical and the other a paint problem. It is sufficient to state here that the evident palliative measure of applying a first or prime coat containing a substance which prevents corrosion by inhibiting electrolysis gives great promise for future experimental work.

It has been frequently shown that alkalis inhibit corrosion while acids stimulate it, for reasons which have been discussed in recent publications. It would be well worth trying whether trenching with lime would not furnish protection to steel pipe lines that have been reported as giving trouble. Although the electrolytic theory of the corrosion of the metals may not have met with universal acceptance, it is difficult to see how it can be rejected in view of the evidence that has been brought forward by recent workers in this field. But whether it survives or not, like other good theories, it will serve a purpose in suggesting methods of overcoming existing difficulties.

A new form of portable telephone apparatus has been lately devised by a German company. It is intended to be used specially for connecting with the telephone wires which are mounted upon the same poles as the wires of power lines from electric stations, and in order to avoid accidents which might be occasioned by the high-tension current of the power lines, the new telephone apparatus is insulated so that it can be used with great security in the presence of 10,000-volt wires which run on the same poles. At the same time the conversation is very clear even at great distances. The apparatus, which is compact and easily handled, consists of a telephone mounted in a rain-proof casing and adapted to be set up on a special tripod which gives a ground connection and is made of light steel tubes. For making the connection from the telephone to the overhead wire there is mounted a long pole which is made in six sections of ash wood. In this way the telephone can be connected at any point along the line and without any risk.