A FRENCH STEAM BREWERY.

SEEING the constant increase that is taking place in the consumption of beer, and the great competition that exists among manufacturers of it, every invention that is capable of reducing the prime cost can be only well received by brewers. It is from this standpoint that we think it our duty to publish a description of a new system that has been invented and patented by Mr. A. Girard, of Paris.

This improved brewery, which is simple in construction, and necessitates neither masonry foundations nor brick furnaces, and occupies but little space, permits, as compared with the ordinary type, of a great saving being effected in the cost of the first establishment, as well as in fuel and manual labor. The system is adapted for the manufacture of all kinds of beer, whatever be the method of maceration (infusion or decoction) and the mode of fermentation (high or low) that are adopted. The inventor has sought to obtain these multiple advantages by operating with steam.

As shown in the accompanying plate, which represents a complete plant according to Mr. Girard's system, all the ap-

paratus rest on the floor without any foundation. An iron frame, which is supported by cast iron columns, serves as a seat for the coppers. A light platform, that runs along the various apparatus, facilitates such manipulations as putting in hops, etc., closing the vessels, maneuvering the cocks, etc. To the extreme right of this series of apparatus is a tubular, inextensible boiler (A), such as Mr. Girard's house has made a specialty of. Any other boiler, however, can be used just as well, although the vertical style, by reason of the small space that it requires, appears to be best adapted for breweries. The steam boiler employed in the present case is easy to run and keep in repair, is brought quickly to the requisite pressure, and requires no masonry furnace. The fireplace being in the interior, a simple jacket serves to prevent the loss of heat through radiation and thus diminishes the output of fuel.

bottom, there is a second man-hole, closed by a screw plate, to allow of the removal of the malt and the cleaning of the interior. The apparatus is provided with a safety-valve, and a pressure-gauge whose metallic rod (without mercury) enters the vessel. Externally there is a dial-plate with figures large enough to be read from a distance. Finally, there is a glass window in the side to allow the operation that is going on within to be watched.

This saccharifier is tested and registered, at the time of its construction, to resist a pressure of 2 kilogrammes per square meter, corresponding to a temperature of 133° C. The double bottom, which receives the live steam, is, like the generator, registered at 7 kilos, corresponding to a temperature of 170° C.

To the left of the saccharifier stands a second cylindrical vessel, D, that serves for the manufacture of beer. This vessel, which is the one in which the hops are boiled with the wort, is, like the apparatus just described, provided with a thermometer, pressure-gauge, water-level, sight-hole, etc. At its side stands a similar vessel, E, called the hot water or small beer vat. The total capacity of these two vessels, D

perform these different maneuvers, and to attend to all the operations. Finally, it is of interest to add that, by means of these apparatus, two brewings per day may be effected.

Description of the Plate.—A. Steam generator. B. Feed-water reservoir. C. Mash-tun. D. Hop copper. E. Hot water or small-beer copper. F. Pipe that connects the coppers. G. Pressure pipe for transferring and elevating the products. H. Steam pipe connecting the double bottoms. J. Pipe that leads the condensed steam to B. K. Level of the liquids. L. Man-holes. M. Pressure gauge. T. Thermometer. R. Sight holes.—*Revue Industrielle.*

THE IRIIDIUM INDUSTRY.*

By WM. L. DUDLEY, Cincinnati, O.

It is my desire to call attention to a new industry which was started about four years ago, through the discovery by Mr. John Holland, a resident of this city, of methods suitable for working the metal iridium. This metal has been known since the year 1803, having been discovered by Smithson

FRENCH STEAM BREWING PLANT.

and E, is equal to that of the saccharifier. The role of the hot water vessel, E, is not limited to the heating of water for steeping, but has a still more important object.

In fact, by the aid of blow-off cocks in the bottoms, and through the pressure exerted by the steam when the upper cocks of the vessels are opened, the contents of the various apparatus can be transferred from one to the other respectively. It follows that after the malt has been moistened from the hot water vat, the latter may serve to boil and hop small beer, while the stout beer is boiling in the first copper. In this way the two qualities of beer that usually result from all brewings may be obtained very economically.

The apparatus under consideration permits, as we have said, of the use of all modes of brewing, and of performing the operations with the greatest cleanness. Nothing is easier than to gradually reach the requisite temperature through steam heating. The thermometer is merely consulted, and, according to its indications, the opening of the heating cock is regulated. In order to obtain a sweet beer that contains much dextrine and little alcohol, the heating is arrested at 65°; if the beverage is to contain much alcohol, the heat is carried to 70°; and, if a very alcoholic, light, and digestible beer be desired, the heat is carried to 80°.

As regards facility of manipulation, it is well to remark that the difficult and delicate operation of maceration in brewing by infusion is here much simplified. The transparent glass in the side of the mash-tun or saccharifier permits, in fact, of all the transformations of the mash being watched, and the thermometer gives the most accurate indications as to the temperature of the interior. Owing to these means of control, it is easy to avoid, during the progress of the work, irregularities that might interfere with the saccharification, reduce the yield of malt, interfere with the perfect clarification of the wort and beer, and alter the delicious aroma of the malt sugar.

The operations once finished, the steam and boiling water that are always present in sufficient quantity allow the vessels and pipes to be readily cleaned. It requires but one man to

Tennant while investigating the metallic residue which remained when platinum ores were dissolved in aqua regia. The metal is classed among the rare metals, as it is not found in large quantities, although it is quite widely distributed geographically. It is found in California, Oregon, Russia, East India, Borneo, South America, Canada, Australia, and in certain parts of France, Germany, and Spain. The principal sources of supply of the metal are Russia and California; it is nearly always found with either platinum or gold, is extracted from those ores as a by-product, and is always found in small grains or fine powder, the largest pieces being about the size of a grain of rice. In nature it is generally alloyed with other metals, and the two metals with which it is most commonly alloyed are platinum and osmium; the platinum alloy is called platinum-iridium, and the osmium alloy osmium-iridium or iridosmine. The grains of platinum-iridium are sometimes found as small cubes with rounded edges, while the iridosmine usually exists in the form of flat irregular grains and occasionally as hexagonal prisms. The supply of metal which is derived from Russia is generally obtained from the platinum mines which are situated in the Ural Mountains; while in California it is found principally in placer gold-washings. The ores of iridium are a source of great annoyance when mixed with gold-dust on account of its specific gravity, which is about 19.3, being nearly the same as that of gold. Consequently, it is impossible to separate the gold from the iridium by the process of washing; the separation may, however, be made either by the amalgamation of the gold (as neither iridium nor its ores combine with mercury), or by dissolving out the gold in aqua regia.

In the mints these metals are frequently separated by melting the gold-dust and allowing the molten mass to remain in the crucible for some time, during which the iridium slowly settles to the bottom, as it does not alloy with the gold under such circumstances. The gold is then poured off from

* Read at the Cincinnati meeting, American Institute of Mining Engineers, Feb., 1884.

the top, and the dregs in the bottom of the crucible are found to contain the greater quantity of the iridium. The gold contained in the dregs is then dissolved, and the iridium is found in the residue.

In Russia it is contrary to the law to possess or deal in iridium ore, and consequently the government takes possession of all the ore which is mined or extracted from the platinum ores in that country, and it is stored in the vaults of the Royal Mint. The reason for the law is, that some years ago the Russian government found that speculators in gold-dust would sometimes add iridium to it (which often escaped detection by the officials of the mint), for the purpose of increasing its weight. On attempting to work this gold they found the fine particles of iridium distributed through the ingots; on rolling the ingots into sheet, these individual grains or particles produced indentations in their steel rolls; and in striking out the coins the dies were marred and defaced, thus causing considerable loss to the government. In order to prevent this species of fraud, the government passed a law prohibiting persons from handling the metal in any way, and compelling its immediate surrender.

For a number of years experimenters have endeavored to melt the iridosmine or iridium, in order to utilize it in the arts for such purposes as could with advantage employ a metal of its wonderful properties; but until lately success has been only partial.

I may here briefly describe the properties of the metal itself. Iridium possesses a white luster, resembling that of steel; its hardness is about equal to that of the ruby; in the cold it is quite brittle, but at a white heat it is somewhat malleable. It is one of the heaviest of metals, having a specific gravity of 22.38. When heated in the air to a red heat the metal is very slowly oxidized; but upon raising the temperature to about 1,000° C., it parts with its oxygen, and hence at a high heat (above 1,000° C.) it is not oxidized. It is insoluble in all single acids, but is very slightly soluble in aqua regia after being heated in the state of fine powder for many hours. In a massive state, however, aqua regia does not attack it.

In attempting to fuse iridium heretofore, it has been found by experimenters that the best results that could be obtained were by means of the oxyhydrogen or electric furnace, but that with either of these means of fusion they could only work a very small quantity of the metal at a time, and obtain a globule of very small size. Previous to the present time iridium has had substantially but one use (with the exception of alloying with platinum), viz., for pointing gold pens. The iridium point is commonly called "diamond point" upon a gold pen, and it consists simply of a small grain of iridosmine which has been selected for the purpose, and soldered to the tip of the pen. These are selected by first removing from the ore, with a magnet, the magnetic oxide of iron which always accompanies it, and then dissolving out, by means of acids, the other impurities which may be present; the ore is then washed with water, dried and sifted in order to remove the fine dust, and the sifted ore is then ready for the selection of points. This is done by an operator, who rolls the grains of iridium around with a needle point, examining them under a magnifying glass, and selecting those which are solid, compact, and of the proper size and shape. These points are usually selected in three grades, small, medium, and large, depending upon the size of the pen for which they are intended to be used. The grain of iridium having been soldered on to the end of the pen, it is sawed in two (which makes the two nibs of the pen), and ground up to the proper shape.

About four years ago Mr. John Holland, the well known gold pen manufacturer, found it necessary to have pieces of iridium larger than those generally found in nature for the purpose of making points for the Mackinnon stylographic pen. After many experiments he found that by heating the ore in a Hessian crucible to a white heat and adding to it phosphorus, and continuing the heating for a few minutes, he could obtain a perfect fusion of the metal, which could be poured out and cast into almost any desired shape. This material was found on physical examination to be about as hard as the natural grains of iridium; and in fact seemed to have all the properties of the metal itself. On chemical analysis it was found that the metal fused with phosphorus contained, according to two determinations, 7.52 per cent. and 7.74 per cent. of phosphorus. At this stage of the discovery we became acquainted with it, and began experiments with the intention of putting the product to some practical use in the arts. It was found that the presence of phosphorus rendered the metal quite readily fusible at a white heat, but this, of course, was an obstacle in the way of its use for electrical purposes. Desiring, therefore, to remove the phosphorus, we found by experimenting that by heating the metal in a bed of lime the phosphorus could be completely removed. In this operation, the metal is first heated in an ordinary furnace to a white heat, and finally, after no more phosphorus makes its appearance, it is removed and placed in an electric furnace with a lime crucible, and there heated until the last traces of phosphorus are removed; the metal which then remains will resist as much heat without fusion as the native metal.

In mechanical applications, where the metal is not subject to great heat, it is melted with phosphorus and cast into the shape desired, and then ground or worked as the application may require. The first application to which it was put was for the manufacture of the Mackinnon pen-points. For this purpose, the metal, after being fused, is removed from the furnace and poured between two slabs of iron, which are kept apart the desired distance so as to make a sheet of iridium of the thickness required. The metal is poured, as I have said, between these plates, and the plates are brought suddenly together, on the plan of a closed ingot with a hinge, so that as the metal cools it is subjected to pressure, which closes the pores and makes a very compact casting. The slabs for the Mackinnon pen-points are about one thirty-second of an inch in thickness, and are broken up into small irregular pieces, which are soldered on a strip of brass and ground down to a flat surface by means of a copper-lap. The copper-lap consists of a plate of copper, about one-half inch in thickness and eight inches in diameter, fixed on a spindle which is made to revolve from eight hundred to a thousand revolutions per minute; the copper of which the lap is composed is wrought copper, well annealed, and consequently very soft. In order to grind with it, corundum or diamond dust is mixed with oil and applied to the flat surface of the lap by means of a flat steel instrument, upon which pressure is applied in order to force the corundum or diamond dust into the copper, thereby making a cutting surface. The iridium to be ground is held against this sharp surface of the lap, and the corundum or diamond dust gradually cuts the metal away. As the cutting material wears from the copper-lap, another application of the corundum and diamond dust is made by means of the steel instrument described; this operation is continued until the grinding is complete. After the slabs

are ground to a surface they are then drilled. In the drilling operation, the iridium is first countersunk by means of a diamond drill, consisting of an upright spindle suitably fixed in a frame so as to revolve freely; the bottom of the spindle holds a small rod of brass, to the lower end of which is set a white diamond-splint. This drill is made to revolve about nine hundred revolutions per minute. The iridium is held up against the diamond with a light pressure, and the diamond gradually makes a conical hole or countersink. After countersinking the iridium, it is finally pierced by means of a copper drill, which consists of a piece of soft copper wire, which is filed down to a point and set in a drill similar to that in which the diamond is placed, but this drill makes about thirty-five hundred revolutions per minute. Corundum or diamond dust and oil is put into the countersink opening in the iridium, and then it is held up against the piece of revolving copper. The diamond dust or corundum, embedding itself in the copper, acts as a cutting surface, and finally accomplishes the drilling of the hole. The holes having been drilled in the pieces of iridium which were soldered to the brass, the brass is finally dissolved from the iridium by means of nitric acid; and then we have irregular-shaped pieces of iridium, pierced with holes. These pieces of iridium are then soldered in proper position to the end of the Mackinnon pen, fitting into the opening of which there is a valve consisting of an iridium-pointed wire. The iridium is then ground to the proper shape on the outside by means of a copper-lap, consisting of three or more copper cylinders on a common spindle, making about three thousand revolutions per minute.

The operation of sawing iridium is carried on by means of a copper disk from four to eight inches in diameter, made of soft thin-sheet copper, held between two clamps, placed on a spindle revolving at the rate of about twenty-five hundred revolutions per minute. This sheet of copper revolves in a box which contains corundum or diamond dust and cotton-seed oil. The cotton-seed oil with the cutting material adheres to the periphery of the saw, and as the saw comes in contact with a piece of iridium it gradually does the work. Cotton seed oil is preferred for this purpose to any other oil, on account of its viscosity.

I may mention briefly some of the uses to which iridium has been applied. First, I will refer to the draw-plate for drawing wire. There are at present, besides the iridium draw-plate, the ordinary steel-plate which is used for drawing heavy wire, and the ruby plate, which is used in drawing gold and silver wires, where it is desirable to have them of uniform thickness. The iridium plate is made somewhat similar to the ruby plate, consisting of a piece of iridium which has been countersunk and drilled in the usual way to the size of the hole required, and set in a brass plate, where it is firmly held by a bushing. This plate is now coming into use, and is rapidly taking the place of the ruby plate, being equal to the ruby in hardness and much more durable, since it is less liable to break or chip by rough handling or heating.

Iridium knives are made for fine scales and balances, the bearing edge of which consists of iridium, soldered firmly to a brass body. These are rapidly taking the place of the agate for fine chemical balances, and there seems to be no reason why they should not have even a more extended use, since they are superior to the agate in that they take a finer edge and thereby make a more delicate balance, and are not so liable to crack or break. They are now being used altogether by Mr. Henry Troemner, of Philadelphia, the well-known scale manufacturer, for the purpose of adjusting his weights for all of his scales.

Hypodermic needles for physicians' and surgeons' use are now made of gold and tipped with iridium, in place of the old steel pointed ones, which are liable to rust or corrode if not properly taken care of. The iridium being hard will take a good edge, and is not subject to corrosion, as is steel.

Styluses for manifold writing are also being made with iridium points, having decided advantages over either steel or agate. Iridium points are also being applied to surveyors' and engineers' instruments, and in all places, in fact, where hardness, durability, and non-corrosibility are required. For all the above uses the iridium alloyed by fusion with phosphorus is employed.

Some years ago experiments were made in order to apply this metal to the electric light. We found that an iridium electrode used upon the negative of an arc-light would keep its shape and resist the heat, provided the positive carbon which was used with it was not allowed to strike or fall too heavily upon the iridium negative. Since the metal at a white heat becomes malleable, a continual pounding or striking would gradually beat the negative out of shape. The iridium negatives are made by setting a piece of dephosphorized iridium in the end of a brass rod about six inches long and nine-sixteenths of an inch in diameter. The length of the iridium is about half an inch, ground conical in shape. It was found that the brass, being only half an inch from the arc, would resist the action of the heat; but in some cases where the lamp flamed the brass was liable to undergo partial fusion; and in such cases it was found desirable to put a thimble or cap of platinum over the end of the brass and just below the iridium, the platinum thimble being about half an inch long.

One of the most important applications of iridium which has yet been made is to the electrical contact-points of telegraphic apparatus. These contact-points consist of pieces of copper wire tipped with iridium, which are set in the instrument just as platinum points are set. These contacts will outlive many platinum contacts; are not subject to oxidation or sticking, as are the platinum ones; and all that is necessary in order to clean them when they become dirty is to pass over their surface an emery file or a piece of fine emery-paper. These contacts have been thoroughly tested by various eminent electricians and also by long continued use, and the advantages herein stated have been in every case fully demonstrated.

In the past three years we have been experimenting on methods of plating with iridium, and about one year ago we succeeded in obtaining a bright reguline deposit of iridium on base metals. This deposit resembles the natural metal, being quite hard and resisting the action of acids. There were many difficulties encountered in accomplishing this result, on account of the power of the metal to resist the action of the solvents; but we have succeeded in obtaining a solution which gradually attacks an anode of iridium, and it is hoped in a short time that all the minor practical difficulties will be overcome in the plating of articles on a commercial scale. So far we have been thoroughly testing our results, and do not feel prepared to place our work before the public until it is perfect in all its details.

For the anode in electro-plating we use iridium which has been fused with phosphorus. It contains 5 per cent. of phosphorus, which does no damage. Of course, in working

out a problem of this nature, it takes several years to ascertain all the causes of disturbance; but we have not yet attributed any trouble to the phosphorus in the solution. We have made many experiments with alloys of iridium, but have practically failed to get an anode of them which would readily dissolve; but we find that the anode of fused iridium gradually dissolves, and yet not fast enough to keep the solution replenished, without the addition, now and then, of some of the pure salt, the amount depending upon the kind of solution employed. The same thing is necessary in silver and in nickel plating. Theoretically, the anode should dissolve and keep the solution up to the proper strength. In practice, that is never the case.

The solution is made by dissolving the iridium first with chlorine and sodium chloride. The iridium or iridosmine is mixed with common salt, placed in a tube, and heated to redness. Chlorine gas is then allowed to flow slowly through the tube for several hours, at the end of which time most of the iridium will have combined with the salt and chlorine to form the double chloride of iridium and sodium, which rapidly dissolves in water. From this solution we can obtain any salt of iridium which we desire. In plating with the metal, we find that a solution, very slightly acidified with sulphuric acids, gives the best results practically, although neutral or alkaline solutions work very well.

Ordinary silver solder is used in soldering iridium to other metals. Soft solder will solder the metal as well, but we seldom use it, since it is not as durable.

As to the supply of the metal, we find it, like a good many other metals, widely distributed—in Canada, and many parts of the United States, in France, and a great many European countries, and, as I have said, the largest supply has heretofore been in Russia.

There are some parties in Hamburg who deal in the ore, and we get most of it from them. We get from three to four hundred ounces annually from the United States government. We do not get more, for the reason that the mints will not knowingly buy gold-dust which contains any iridium. They examine the dust very carefully, but, in spite of their care, they get a little.

PHOTOS IN INK.

By SAMUEL C. RILEY.

In using the velvet roller no particular precautions are needed, but the roller should carry enough ink of moderate thickness, consisting of pure olive oil and litho. transfer ink thoroughly incorporated. The greatest advantages accrue from first rolling the collotype plate with the velvet roller, covering the whole plate with a thin uniform coating, and immediately rolling the plate with a leather roller sparingly covered with the same ink as used on the velvet roller. Any amount of brilliancy can thus be obtained (provided the negative is perfect), always remembering that a little sharp rolling clears the whites effectively. I have repeatedly seen collotype plates that could not be inked up with the leather roller by itself (owing to the plate being dried badly), which gave perfect impressions after having been inked lightly all over with the velvet roller, the plate being cleared with a few gentle rolls with the leather roller.

To make a collotype plate that will give perfect impressions, proceed as follows:

First, the substratum for the plate. Take 1 ounce of ordinary dinner ale, 6 or 8 drops of silicate of soda, and well shake into a froth in a bottle, stand it by for twenty minutes, then filter. Take a clean glass plate (patent plate is best), and with a camel's hair brush go over one side of the plate; set on end to dry. When dry, go over the plate again, letting it dry this time the other way up. When again dry, let a gentle stream run on it for thirty seconds, then again dry on end. When again dry, you may coat with the following solution: 44 grains Nelson's ordinary gelatine soaked for quarter of an hour in cold water, then heated in the oven till all is melted. Then pour into it the following hot solution:

Water..... ½ ounce.
Bichromate of ammonium..... 6 grains.

Well mix and filter. On no account let the solution get to boiling point. Take an 8 by 5 plate with the dried substratum on it, and flow over it ½ an ounce of the hot gelatine solution; place at once on the leveled glass in the drying box. It should dry in two hours, and is ready for instant use. Expose under an ordinary negative for an hour, then wash in cold water for 1½ hours, and dry in the open air, which takes from 4 to 6 hours, according to the weather. When dry, damp with very weak glycerine and water, allow the moisture to slightly evaporate, roll as above mentioned, and take impression off at once.

The drying box is as under: 20 inches high, 12 inches square, the leveling glass about 6 inches from the top of the box, three sheets of loose blotting paper lying on it for the plate to rest on, a piece of iron (say) 6 by 4 by 3 heated in the fire, and placed 6 inches under the leveling glass. There should be at least three or four holes at the bottom sides of the box, and three at the top, to promote a good draught. The heat in the box should be about 120° F.—*Photo. News.*

HOW TO MAKE PHOTO PRINTING BLOCKS.

THE Pretsch method, described by Mr. Ryley and given in the *Photo. News*, is as follows: The nitrate of silver need not be added, and by "fine glue" must be understood such a gelatine as that of Coignet. Mr. Ryley says:

1. I dissolve 1 ounce of fine glue in 3 ounces of distilled water, and to 1 ounce of this solution I add 30 grains of nitrate of silver, previously dissolved in ½ ounce of distilled water; to the other 2 ounces of glue solution I add 2 ounces of a saturated solution of bichromate of potass, and while warm I add to it the nitrate of silver and mix well.

2. I level a glass plate, and pour over it as much of the above solution as will when quite dry form a film about the thickness of thin writing paper.

3. I now expose the plate to sunlight under a glass positive for about three hours, or until all the details of the picture appear when viewed by transmitted light.

4. I then wash it under water until those parts of the picture which are the least acted on by light become granulated, which is caused by a peculiar contraction of the film; the superfluous moisture must then be removed by blotting-paper.

5. You may use a negative instead of a positive, but your exposure must not be more than half the time, and you will still have a positive result and the grains of your film will be much finer. And now let me remark that in this granulation lies the whole secret of the process; and yet, strange to say, not one word can you find respecting it in the specification,