THE NEWCOMEN ENGINE.

By MR. HENRY DAVEY, *Member of Council.*

A great deal has been written on the Steam-Engine generally, but the author has not met with any connected record of the invention and construction of the first steam-engine—the Atmospheric Engine of Newcomen. Unfortunately it does not appear that much detailed information is available; but the author has been able to bring together some facts, which, with the aid of appendices contributed by others, and with some illustrations of the engine itself, may be found to form a useful contribution to place on record in the Proceedings of the Institution. There are not many examples of the engine now in existence; and when they are consigned to the scrap heap, that receptacle of great efforts of the past, all will perhaps be forgotten.

Towards the end of the seventeenth century, philosophers and mathematicians searched for a new method of obtaining motive power. Mining was an important industry, requiring in most cases a new power, in order that the mines might be worked to greater depths. Water-power where available was often insufficient; and manual and animal power were altogether too small and too expensive for working any but shallow mines. Deep mining was and is possible only with pumping machinery. Water-wheels were used for working pumps. The construction of the common pump was known. Papin had proposed to transmit power by means of pistons moving in cylinders and acted on by the atmosphere, a vacuum having been formed under the pistons by the explosion of gunpowder; and he even hinted that it might be done by steam. It was claimed for Papin that he invented

the steam-engine, because in 1685, in one of his letters, he illustrated what was known of the properties of steam, by saying that if water were put in the bottom of a cylinder under a piston, and the cylinder were put on a fire, the water would evaporate and raise the piston; and that if, after the piston had been raised, the cylinder were removed from the fire and cooled, the steam would condense and the piston would descend; but this was only an illustration of common knowledge. Sir Samuel Morland had, in 1683, stated * that steam occupied about two thousand times the space of the water from which it was produced; and had made some calculations as to the powers to be obtained from different sized cylinders, but had suggested no practical mode of operation. Experiments to determine the density of steam were made by John Payne in 1741, published in the *Philosophical Transactions*, vol. xli, page 821. As the result of these he concluded that one cubic inch of water formed 4,000 cubic inches of steam. Beighton calculated, from an experiment with the Griff engine, the second Newcomen engine erected, that the specific volume of steam was 2,893. The properties of steam were probably no better known to philosophers than to the ordinary observer who had seen the lid of a kettle dance under pressure, or steam issue from the spout. The only practical application of steam was made by Savery, who, in 1696, described his invention in a pamphlet entitled "*The Miner's Friend*."† Savery's engine was a pistonless steam-pump—in fact, the pulsometer of to-day without its automatic action. It remained for Newcomen to combine the bits of common knowledge in his mind for inventing the steam-engine. He was a blacksmith, probably accustomed to invent methods of construction in the prosecution of his art. At that time mechanics were more self-reliant than they are now. He knew from experience what a lever was, a pump, a piston, a cylinder, a boiler; and he knew that the atmosphere had pressure, and that steam possessed a far greater volume

* See Tredgold's "Steam Engine," 1853.

† "*The Miner's Friend*" was published in 1696; and a dialogue in answer to objections in 1699, and both together in 1702. Savery's Patent is dated 1698, or two years after the publication of "*The Miner's Friend*." See R. Stuart's "*Descriptive History of the Steam-Engine*."

than the water which produced it. It did not require much more than common knowledge and observation to realise that. To produce the steam-engine from such known facts required invention. Philosophers probably conceived what might be done; but Newcomen had the advantage of seeing what could be done, and he did it. The engine when produced was imperfect; but defects became obvious to the designers and constructors of steam-engines, and the want of perfection at the present day is not from want of theory, but because of practical limitations and the want of practical invention. The theory of the steam-engine has followed its application, which is the natural order of things. Ascertained facts form the best foundation of theory. Watt's invention of the separate condenser was founded comparatively on no greater theoretical knowledge than Newcomen's invention of the engine itself. Watt was probably a better educated man than Newcomen; but no knowledge superior to that possessed by many others was necessary for the invention of the separate condenser. Watt roughly ascertained the specific volume of steam, and so did Morland, and the makers of Newcomen's engines, incorrectly. It was also given with even greater inaccuracy in a text-book edited by Dr. Brewster;* but quantitative results did not determine either invention. There are so-called inventions which are nothing more than obvious combinations of mechanism, but inventors such as Newcomen and Watt are pioneers who discover and occupy the country, whilst the theorists are surveyors who follow to measure it up.

At this distance of time it is difficult to appreciate the inventive power required to produce the atmospheric engine from the crude ideas of Papin and others. It appears, from papers in possession of the Royal Society, that Dr. Hooke had demonstrated the impracticability of Papin's scheme, and, in a letter addressed to Newcomen, had advised him not to attempt to make a machine on that principle: adding however, "Could Papin make a speedy vacuum under your second

* "Ferguson's Lectures on Mechanics, &c.," by Dr. Brewster, 1806. In this book the specific volume of steam is given as 14,000. Emerson, in "The Principles of Mechanics and the General Laws of Motion," 1758, gives it as 13,340.

piston, your work is done."* A great deal of controversy hangs about this, as about many things historical; and little is to be gained by minute research into disputed claims. What we do with certainty know is that, with the common knowledge existing, and with the mechanical contrivances available, Newcomen alone succeeded in making a workable engine.

In 1698, Thomas Savery, of London, obtained a patent for raising water by the elasticity of steam.† It is stated in many popular histories that in 1705 Thomas Newcomen and John Cawley, of Dartmouth, in Devonshire, and Thomas Savery, of London, secured a patent for "Condensing the steam introduced under a piston, and producing a reciprocating motion by attaching it to a lever," but no record of such a patent exists in the Patent Office. Stuart gives a list of patents commencing with 1698, and in that list is one said to have been granted in 1705. Dr. Pole, author of "The Cornish Engine," had a search made at the Patent Office, and no such record could be found. It is possible that Savery's patent was thought to cover Newcomen's invention, as Savery was associated with Newcomen.‡ This was sixty-four years before Watt invented his separate condenser. Very little is known of Newcomen. It is recorded that he was a blacksmith or ironmonger residing at Dartmouth, and that he was employed by Savery to do some work in connection with his water-raising engines. In this way he had some experience in the condensation of steam.§

* See R. Stuart's "Descriptive History of the Steam Engine," 1824.

† Savery was born at Shilstone, near Modbury, in Devonshire, in 1650; died in London in May 1715.

‡ See Appendices I and II, from which it appears that there is every reason to believe Newcomen had no patent, and that his invention was supposed to be covered by Savery's patent of 1698, and that the latter was kept in force for thirty-five years, the original patent having been extended for twenty-one years.

§ Newcomen was born at Dartmouth about the middle of the 17th century, and died in London in 1729. It is stated in Haydn's "Dictionary of Dates" that at the time of his death he was in London, trying to secure a patent. A sketch of the house in Dartmouth, occupied by Newcomen when he invented the steam engine, is shown in a pamphlet published in 1869 for Mr. Thomas Lidstone of Dartmouth.

Newcomen appears to have conceived the idea of using a piston for giving motion to pumps. He became associated with John Calley or Cawley, a glazier of Dartmouth, probably for business reasons. His connection with Savery was doubtless because of Savery's patent for condensing steam for raising water. He must however have been a good mechanic, because the construction of such an engine at a time when there was no previous experience or data to guide him was a task of no ordinary magnitude. He could not get workmen skilful enough to do his work, till, erecting an engine near Dudley in 1712, he secured the assistance of mechanics from Birmingham.*

In this age of mechanical developments we wonder at the slow progress made in early times, till we realise the condition of society, and the apathy with which all things technical and scientific were regarded by the public generally. That ignorance and prejudice are well illustrated by the following extract from the preface to a book published in 1758, entitled "The Principles of Mechanics," by W. Emerson, a copy of which was kindly lent to the author by Mr. H. W. Pearson, of Bristol:—

"I might have given the cuts of many more machines, but perhaps what I have already done may be thought too much in such a nation as this, where natural knowledge wants due encouragement, and where no Mecaenas appears to patronize and protect it, and where arts and sciences hang, as it were, in suspense whether they shall stand or fall, and where public spirit and English generosity are just expiring. This decline of arts and sciences is wholly or in a great measure owing to the ambition and most extreme avarice of the present age, where men, not being able to lift their eyes above this earth, think nothing worth their care but raking together the dross it affords, striving, like the toad, who shall die with the most earth in his paws. The duller part of mankind are entirely engaged in the pursuit of filthy lucre, and the brighter sort are wholly devoted to low, trifling, and often barbarous diversions. In such momentous concerns as these, it is no wonder

* See Appendix X. (page 695).

if arts and sciences flag, and natural knowledge meets with nothing but contempt, and Minerva gives place to Pluto. And indeed, if the general temper and disposition of men had been the same in all ages, as it is in this, I am in doubt whether we had ever had any such things as a mill to grind us corn for bread, or a pump to draw us water. It is a trifling excuse for men of exalted station to urge that they are unacquainted with such arts or sciences. For learning has always been esteemed to be under the peculiar care and superintendency of the great, who ought to protect and encourage both that, and the professors of it, or else arts and sciences can never flourish. And as the encouragement of these evidently tends to the benefit of mankind and the promoting of the public good, nothing can excuse so gross a neglect or such a manifest disregard as they show for the happiness of their fellow-creatures. The industrious students have only the fatigue, whilst all the world reaps the advantage of their labours."

The Newcomen engine was soon brought into use; for in 1712 Newcomen, through the acquaintance of Mr. Potter, of Bromsgrove, erected an engine near Dudley Castle for Mr. Back, of Wolverhampton. The cylinder of this engine was surrounded with water. The piston was packed and had a water seal. It is reported that by accident a hole in the piston admitted water into the cylinder, and the condensation thereby became so rapid, compared with that produced by cooling the cylinder from the outside, that the engine worked much quicker. This may or may not be correct; but it is certain that, by accident or design, the first improvement in the engine was condensation by injection in the cylinder. It appears that the second engine was erected at the Griff Colliery, near Nuneaton, in 1715. It had a 22-inch cylinder. At this time the cocks and valves were all worked by hand; but automatic devices were soon introduced. The first appears to be that for actuating the injection-cock by means of a buoy in a pipe connected to the cylinder. Desaguliers thus describes the apparatus: "They used to work with a buoy in the cylinder enclosed in a pipe, which buoy rose when the steam was strong, and opened the injection and made the stroke." It is said that a boy,

Humphrey Potter,* added a catch or "scoggan"† which was caught by a pin upon the plug-rod from the beam; and by this means the speed of the engine was increased from 8 or 10 to 15 strokes per minute.

Thomas Barney's engraving of the engine‡ erected in 1712 near Dudley Castle, was made in 1719, and contains the plug-frame and tumbling-weight device attributed to the invention of Beighton in 1718. It is possible that the tumbling-weight had just been added for actuating the steam-valve. The injection-valve is released by the buoy, said by Desaguliers to have been enclosed in a pipe attached to the cylinder, but here shown in a pipe attached to the boiler. The scoggan is also shown, and it is clear that the only thing Humphrey Potter added, if he added anything, was a cord for causing the plug-frame to actuate the scoggan, instead of the float doing it. The engraving shows such an addition, but the story of Humphrey Potter is discredited.

The scoggan appears in Belidor's illustration, § also in Stuart's illustration (Fig. 19, page 73, second edition, 1824), which is said by Stuart to be Beighton's gear with improved details. It also appears in the York engine, Plate 21, and the engine, Plate 23. Emerson says, "In some engines there is a catch held by a chain fixed to the great beam, and this catch holds the injection-cock lever or eff|| from falling back and opening the cold-water cock, till the rising of the beam pulls the catch up by the chain, and then the eff falls."

* It is curious to observe that the first engine was erected for Mr. Back through the influence of Mr. Potter of Bromsgrove. Mr. W. G. Norris writes that John and Abraham Potter were engineers in Durham, and erected an engine for Mr. Andrew Wauchope in Midlothian in or about 1725. See also Bald's "View of the Coal Trade of Scotland," pp. 18, &c., for a full account of this engine. He prints the contract in full, giving many interesting details.

† To scog is said to be a Yorkshire term meaning to skulk—"Mechanic's Magazine," p. 154; Stuart, p. 66. In Celtic Scotch "sgog" or "sgogan" is a fool or idler. In modern Scotch "scogie" is a kitchen drudge. In Barney's engraving the word is spelt "scoggen."

‡ Proceedings 1883, Plate 87, and page 623.

§ "Architecture Hydraulique," Paris, 1739.

|| So called from its resemblance to the letter F.

In all the earliest engines the "eduction pipe" or drain pipe from the cylinder was arranged with sufficient fall to prevent the hot-well water from returning to the cylinder when the vacuum was formed. It terminated below the water level of the hot-well. In later engines it was shortened, and a non-return valve was placed on the end, which was turned up in the hot-well, and in this way had a water seal.

The next improvement consisted of the plug frame, invented by Henry Beighton, who erected an engine at Newcastle-on-Tyne in 1718, in which a rod suspended from the beam actuated what was called the hand-gear. This contrivance, with some slight modification, remained till Watt's time.

In Plate 16 is reproduced from Pryce's "Mineralogia Cornubiensis," by William Pryce of Redruth, published in 1778, an illustration of the Newcomen engine of that day. Also a section of the Bullen Garden Mine, near Camborne, in Cornwall, Fig. 12, Plate 24, showing the application of two atmospheric engines for enabling the mine to be worked to a greater depth than was possible with only the water wheels in use.

In 1758 Emerson described in detail the Newcomen engine of that day. The description is so excellent that it is here reproduced, omitting the letters of reference to an accompanying engraving; the description is clear enough without the engraving. It will be observed that the dimensions are given of an engine and pumps, and the reported consumption of coal; neither the water pumped nor the consumption of coal can be correct.

Description of the Engine.

"The fire-engine to raise water has a great beam or lever, about 24 feet long, 2 feet deep at least, and near 2 feet broad. It lies through the end wall of the engine house, and moves round a centre upon an iron axis. The steam cylinder is of iron, 40 inches diameter or more, and 8 or 9 feet long, the piston sustained by the chain. The fire-place is underground. The boiler is 12-feet diameter, which communicates with the cylinder by a hole and throat-pipe 6 or

8 inches diameter. The boiler is of iron, and covered over close with lead; in this the water is boiled to raise steam. The regulator being a plate within the boiler which opens and shuts the hole of communication, this is fixed on an axis coming through the boiler, on which axis is fixed a horizontal piece called the spanner, so that moving the spanner forward and back moves the plate over the hole and back again. There is a horizontal rod of iron movable about a joint, and a piece of iron with several claws called the wye, moving about an axis in a fixed frame. The claw is cloven, and between the two parts passes the end of the spanner with two knobs to keep it in its place. There is the working-beam or plug-frame, in which is a slit, through which the claws pass and are kept there by a pin going between them. There is a leaden pipe called the injection-pipe, carrying cold water from the cistern into the cylinder, and turned up at the end within the cylinder. To the injection-cock is fixed an iron rod lying horizontal. The end goes through a slit in the end of another piece, and on the end is a knob screwed on to keep it in place. There is a piece of iron with several claws called the 'eff,' movable about an axis. The claw goes through the slit in the plug frame, and is kept there by the two pins; the claw goes over the piece. As the piece is moved back and forward, the injection cock opens and shuts. There are several holes in the plug frame that by shifting the pins serve to set the pieces higher or lower as occasion requires. There is the snifting clack balanced by a weight and opening outwards, to let out the air in the cylinder at the descent of the piston. In some engines a pipe goes from it to convey the steam out of the house. There is a leaden pipe called the sinking pipe or *eduction pipe* going from the cylinder to the hot-well; it is turned up at the end, and has a valve opening upwards; this carries away the water thrown in by the cold-water pipe or injection pipe. There is the feeding pipe, going from the hot-well to the boiler, to supply it with water by a cock opening at pleasure. There are two gauge pipes with cocks, one reaching a little under the surface of the water in the boiler, the other a little short of it. By opening these cocks, it is known when there is water enough in the boiler, for one 'cock will give steam and the other

water ; they stand in a plate which may be opened for a man to go into the boiler to clean or mend it. There is the puppet-clack or safety-valve ; from this a wire comes through a small hole, to which is fixed a thread going over a pulley, with a small weight at it ; the weight on the clack is about a pound for every square inch. There is a steam-pipe going from the clack out of the house. When the steam in the boiler is too strong, it lifts up the puppet-clack and goes into the steam-pipe, by which it is conveyed away ; otherwise the boiler would burst. There is a pipe carrying water from the cistern into the cylinder to cover the piston to a good depth ; also a cock opening to any wideness that the water may run in a due quantity ; and a hole to let it out through a pipe into the hot-well, when there is too much. There is a force pump, with a bucket and clack, and two valves opening upwards. This pump is closed at the top, and being wrought by a lever it brings water out of a pit into a cistern for supplying condensing water. There are speers (spears), which work in wooden pumps within the pit. The cylinder is supported by strong beams going through the engine-house. There is the first floor and the upper floor. At the end of the beam there are two pins, which strike against two springs of wood, fixed to two timbers or spring beams lying on each side of the great lever ; these pins serve to stop the beam, and hinder the piston from coming too low in the cylinder.

“When the engine is to be set to work, the water in the boiler must be made to boil so long till the steam is strong enough, which is known by opening the gauge-cocks. Then the inlet hole is opened by moving the spanner by hand ; then the steam is let into the cylinder which lets that end of the beam rise up ; this raises the working beam or plug-frame and moves the eff, which moves and opens the cold-water cock ; at the same time is moved the wye, and shuts the inlet steam-hole. The injection-cock being opened, the cold water rushing into the cylinder is thrown up against the piston, and descending in small drops condenses the hot rarefied steam, and makes a vacuum under the piston. Consequently the weight of the atmosphere pressing upon the piston brings down the inner end, which raises the other end, which works the pumps. As the inner end descends, the working plug-frame descends, and moving the eff and

the wye shuts the cold-water cock and opens the hole inlet for steam, and the steam goes into the cylinder, which takes off the pressure of the atmosphere, and the outer end descends by the weight of the speers and the inner end ascends as before, which opens the injection cock and shuts the steam inlet. So by the motion of the beam up and down the cock and holes shut and open alternately; and by this means of condensing and rarefying the steam by turns within the cylinder, the lever or beam constantly moves up and down, by which motion the water is drawn up by the pumps, and delivered into troughs within the pit, and carried away by drifts or levels. At the same time the motion of the beam works the cold-water pumps, and raises water into the injection-water cistern.

"When the engine is to cease working, pins are taken out of the plug-frame, and the cold-water cock is kept close shut while the inner end is up.

"The diameter of the pumps within the pit is about 8 or 9 inches, and the bores of the pumps where the speers work should be made wide at the top, for if they be straight more time is required to make a stroke, and the barrels are in danger of bursting. Likewise, if water is to be raised from a greater depth at one lift, the pumps will be in danger of bursting; therefore it is better to make two or three lifts, placing cisterns to receive the water.

"The speers or rods that work in the pumps, consisting of several lengths, are joined thus:—each piece has a stud and hole, which are made to fit; and the studs of one being put close into the holes of the other, and an iron collar drove upon them to the middle, they are then firmly fixed together.

"There is never made a perfect vacuum in a cylinder; for as soon as the elastic force of the steam within is sufficiently diminished, the piston begins to descend. The vacuum is such that about 8 lbs. presses upon every square inch of the piston, or in some engines not above 6 lbs. This engine will make thirteen or fourteen strokes in a minute, and makes a 6-foot stroke; but the larger the boiler is, the faster she will work.

"A cubic inch of water in this engine will make 13,340 cubic inches of steam, which therefore is fifteen times rarer than common

air. But its elastic force within the boiler is never stronger or weaker than common air; if stronger it would force the water out of the feeding pipe. This engine will deliver 300 hogsheads of water in an hour to the height of 60 fathoms. She consumes about thirty bushels of coal in twelve hours. In some engines there is a different contrivance to open and shut the regulator, which is performed thus:—As a beam ascends, it turns the wye about its axis, causing a weight to fall and strike a smart blow on a pin, and shuts the regulator. And when the beam descends, a similar action opens the regulator. There is a cord fixed at the top of the wye to hinder it from going too far on each side; likewise for opening and shutting the injection-cock, instead of the pieces described. Some engines have quadrant wheels with teeth, which, moving one, the other opens or shuts the cock of the injection pipe.*

“In some engines there is a catch held by a chain fixed to the great beam, and this catch holds the injection-cock lever or eff from falling back and opening the cold-water cock, till the rising of the beam pulls the catch up by the chain, and then the eff falls.”

This last is the contrivance said to have been invented by Humphrey Potter, applied to the working of a buoy for opening and closing the cocks. The story probably arose from calling the cock-buoy “cock-boy.” The contrivance is embodied in the Cornish engine gear. From the above description, written twenty-nine years after Newcomen’s death, it is evident that the atmospheric engine was largely in use. The writer of it speaks of some engines differing from others in details. Engines were at work in most of the mining districts of England. In this year (1758) many engines were at work in Cornwall; and it appears that in that county Newcomen erected an engine in 1720, or two years after Beighton’s invention of the hand-gear. It is said that his first engine in Cornwall was erected in 1814, but there are no definite records. In 1769 Smeaton computed the duty of fifteen engines in the Newcastle district, and

* This is the Beighton gear or tumbling-weight device, Plate 16. From the above description it is clear that the plug-frame was in use without Beighton’s device, and probably before it.

one year later made note of eighteen large engines in Cornwall, eight of which had cylinders 60 to 70 inches diameter.

A calculation of the Cylinder and Pumps of the Fire-Engines.

"If it be required to make an engine to draw any given number of hogsheads of water in an hour from f fathoms deep, to make any number of strokes in a minute by a 6-foot stroke, find the ale gallons to be drawn at one stroke, which is easily found from the number of strokes being given.

"Let g = number of ale gallons to be drawn at one stroke.

„ p = pump's diameter (in inches).

„ c = cylinder's diameter (in inches).

Then $p = \sqrt{5g}$;

and supposing the pressure of the atmosphere on an inch of the piston to be 7 lbs.,

$$\text{then } c = p \sqrt{\frac{2 \cdot 614 f}{7}} = \sqrt{\frac{13 \cdot 07 f g}{7}}.$$

"Note, if instead of 7 lbs. you suppose the pressure of the atmosphere to be 1 lb., and instead of a 6-foot stroke to make an r feet stroke; then $p = \sqrt{\frac{6}{r} \times 5g}$, and $c = \sqrt{\frac{6}{r} \times \frac{13 \cdot 07 f g}{1}}.$ "

The author has here arranged the events in connection with the subject in their chronological order; and it is interesting to observe that, though Watt had finished his labours in Cornwall in 1800, bringing the duty of his engines up to 20 millions, yet, between 1810 and 1821, three Newcomen engines were erected at the Farme Colliery in Scotland; particulars of these engines are given in Appendix III (page 681). In those days the want of knowledge of what others had done formed a great bar to progress. By the publication of what has been accomplished, and by the knowledge thereby imparted, the progress of mechanical science and arts has been hastened during the last fifty years as much as by the theoretical teaching of schools.

The Newcomen Engine.

Events in chronological order:—

1696. Description of Savery's Fire Engine, published under the title of "The Miner's Friend."
1698. Thomas Savery, of London, obtained a patent for raising water by the elasticity of steam. His engine had no piston.
1702. Savery's "Miner's Friend" was republished. Savery's advertisement in "Post Man," 19–21 March, notified that his engine might be seen at work "at his workhouse in Salisbury Court, London." This advertisement was reproduced in "Notes and Queries," 27 January 1900 (9th series v. 64).*
1712. Newcomen erected an engine near Dudley Castle for Mr. Back of Wolverhampton. It had a water-jacket around the cylinder for condensing the steam; but afterwards injection in the cylinder was adopted. All valves were worked by hand.
- 1712 to 1718. A buoy was used to give automatic action to the injection-cock.
1714. A Newcomen engine is said to have been erected at Wheal Vor, near Breage, in Cornwall; and another at Ludgvan in 1720.
1715. Savery died in London.
1717. 29 December.—Calley (or Cawley) died whilst erecting an engine at or near Ansthorpe, Yorkshire. This is from the burial register of Whitkirk. See Farey's "Steam Engine," p. 155.*
1718. Beighton invented the "hand-gear." The steel-yard safety-valve was introduced; also the snifting valve, and the shortened eduction-pipe with its non-return valve. All the essential features of the perfected engine were now present.
1720. Newcomen went into Cornwall and erected an engine at Wheal Fortune, St. Day. Another engine on the same model was erected at Pool Mine, Carn Brea, in 1746.

* These and some other notes have been contributed by Mr. Richard B. Prosser.

1721. An advertisement appeared in the "Daily Courant," 24 July 1721, beginning "Whereas an engine to raise water by Fire, commonly called Savery's engine . . .," and inviting attention to a new form of engine. The above was printed in "Notes and Queries," 27 January 1900 (9th series v. 64). *See also* "Notes and Queries," 17 February 1900, for a communication from J. E. Hodgkin.*
1725. Joseph Hornblower erected an engine at Wheal Rose, Truro; a second engine was erected at Wheal Busy, Chasewater; and a third at Polgooth, near St. Austell.
- 8 April.—Steam engine at work at Tipton, Staffordshire. [On this day the son of John Hilditch, "Manager of y^e Fire Engine at Tipton," was baptised in the Parish Church of Bilston.—"The Engineer," 11 Nov., 1898.] *
1729. Newcomen died in London.
1733. 24 July.—Savery's patent expired, having been in existence for 35 years.
1758. Many engines at work in Cornwall, one at Herland, near Gwinear, having a 70-inch cylinder. Emerson describes in detail in his "Principles of Mechanics" the Newcomen engines as then used.
1767. Smeaton first turned his attention to the atmospheric engine.
1769. Smeaton computed the duty of fifteen engines in the Newcastle-on-Tyne district, and found the average duty to be 5.59 millions of foot-lbs. per bushel or 84 lbs. of coal.†
- 5 January.—Watt's first patent.
1770. Smeaton made note of eighteen large engines in Cornwall, eight of which had cylinders from 60 to 70 inches diameter.

* These and some other notes have been contributed by Mr. Richard B. Prosser.

† The bushel was taken as 84 lbs. in Savery's time, and continued until Watt adopted 94 lbs. The duty of steam-engines continued to be calculated on 94 lbs. until 1856, when the Cornish engineers adopted the cwt. (112 lbs.) *See* Davey on "Pumping Machinery," page 20.

1772. Smeaton made improvements in details, not altering the general construction, and succeeded in obtaining a duty of 9·5 millions.
1775. Smeaton erected a Newcomen engine at Chasewater in Cornwall, the steam cylinder 72 inches diameter. Water load $7\frac{3}{4}$ lbs. per square inch. Lift of pumps 360 feet. This engine was altered by Watt to his system.
1776. Watt corresponded with Smeaton, and claimed 21·6 millions duty for his engines. Smeaton, after making experiments with Watt's engines, laid it down as a general rule that the Watt engines did double the duty of the Newcomen.
1777. Watt erected three more of his engines in Cornwall, his first having been erected the previous year. In these engines the load on the piston was increased from the 8 lbs. per square inch in the Newcomen to 11 or 12 lbs. in the Watt engines.
1778. Smeaton found that a Watt engine at the Birmingham Canal* did a duty of 18 millions, and one at the Hull Waterworks 18·5 millions. Two engines at Poldice, St. Day, were found to do a duty of 7 millions on one bushel of coal.
1781. 25 Oct.—Watt's second patent.
1800. Watt finished his labour in Cornwall, having raised the duty of his engines to 20 millions of foot-lbs. per bushel (94 lbs.) of coal. In 1798 the 70-inch engine at Herland, near Gwinear, was reported as giving a duty 27 millions. It was probably the best which at that time had ever been erected, and was under the care of William Murdock, who had the general charge for Boulton and Watt of their engines in Cornwall.
1810. A Newcomen engine was erected at the Farme Colliery, Rutherglen, near Glasgow, for winding and pumping; in 1820 another was added for winding; and in 1821 a third having a 60-inch cylinder for pumping.

* A drawing of almost the first Watt engine for the Birmingham Canal was illustrated in "The Engineer," 15th July 1898. This is now erected in the yard at Ocker Hill, near Wednesbury.

Newcomen had associated with him Cawley, a plumber and glazier; and it will be observed that the pipes of the engines were at first made of lead with plumber's joints. In the early days the steam cylinders only were obtained from iron-founders, and the other parts of the engine were built by local blacksmiths, carpenters, and plumbers, under the direction of an engineer.

The engine cylinder was at first fixed on a boiler of haystack form; but the vibration of the working so loosened the joints that it was found advisable to secure the cylinder to strong wooden beams above the boiler. At a later date the cylinder was fixed on a separate foundation by the side of the boiler, and as time went on iron pipes were substituted for lead, and the wagon-boiler was introduced to take the place of the haystack.

Among the first erectors of the Newcomen engine were the Hornblowers in Cornwall. Newcomen visited Mr. Potter, of Bromsgrove, and erected the engine near Dudley Castle in 1712. This is the historical engine in which injection in the cylinder was first used. In the vicinity lived Joseph Hornblower, an engineer who became acquainted with Newcomen's engine, and who was sent for into Cornwall about 1720 to 1725 to erect an atmospheric engine at Wheal Rose near Truro. It may be interesting here to observe on the authority of Cyrus Redding, a great grandson of Joseph Hornblower, and author of "Yesterday and To-day," &c., that the Newcomen engine was not such a simple machine as to require the attention only of boys, as stated in popular histories, but that it required the united exertion of three men to start.

A second engine it appears was erected by Hornblower at Wheal Busy or Chasewater Mine. A third at Polgooth near St. Austell. Joseph Hornblower then left the county, and his son Jonathan came down and erected his first engine at Wheal Virgin, St. Day, about 1743. The fourth son of Joseph was Jonathan Carter, the inventor of the compound engine* and the double-beat steam-valves, who died at Penryn in 1815.

* Proceedings 1862, page 243.

From 1720 to 1740 few engines were erected in Cornwall, because of the high duty on sea-borne coal. In 1741 an Act of Parliament was passed for the remission of the duty on coal used for fire-engines for draining tin and copper mines in the county of Cornwall.* The effect of the passing of this Act was that by the year 1758 many engines had been brought into use; one engine at Herland had a 70-inch cylinder.

Rotative Atmospheric Engines.—It appears that attempts were made as early as 1768 to produce a rotative motion from a Newcomen engine; but it was not till about 1780 that it was successfully accomplished by the use of the crank.

It does not appear that any attempt was made, before Watt's separate condenser was invented, to reduce the cooling effect of the injection-water in the cylinder by effecting the condensation in a small vessel attached to the cylinder. It is evident however from Plate 28 that, after Watt's patent, Newcomen engines were made with separate condensers without air-pumps, the air being discharged through a snifting-valve. Such condensers were known as "pickle-pots," and are shown clearly in both illustrations.

In Fig. 23, Plate 30, will be found a sketch of the "pickle-pot" condenser. Such condensers are indicated in both engines, Plate 28, and were operated without air-pumps, as already described. It is more than probable that such condensers were not known till after Watt's invention of the separate condenser, and that they were applied to improve the economy of the Newcomen engine and to evade Watt's patent.

In Fig. 27, Plate 30, will also be found a diagram constructed by the author to indicate the economy of fuel resulting from various improvements commencing with the earliest engines of Newcomen. A diagram above also indicates the increase in steam pressure corresponding to the increased economy.

* The Act referred to is the 14th Geo. II., Cap. xli., and intitled:—An Act for granting to His Majesty the sum of one million out of the sinking fund, and for applying other sums therein mentioned for the service of the year 1741; and for allowing a Draw-back of the Duties upon Coals used in Fire Engines for drawing Tin and Copper mines in the County of Cornwall, &c. . . .

The steam-engine has held its own as a prime mover for two centuries. The gas-engine has now become a more efficient heat engine, and a powerful competitor, and electricity has become an economical transmitter of power.

Heat, electricity, and mechanical work are mutually convertible. The time may come when heat may be converted into electric current with as little loss as that involved in the conversion of electric current into mechanical work; when that time comes, the heat efficiency of the prime mover will exceed that of the gas-engine in a greater degree than the gas-engine has exceeded that of the steam-engine.

The Paper is illustrated by Plates 16-30, and is accompanied by the following ten Appendices:—

- Appendix I. Mr. W. G. NORRIS.
- II. Sir FREDERICK BRAMWELL.
- III. Mr. HENRY DAVEY.
- IV. Mr. H. W. PEARSON.
- V. Mr. JOHN H. CRABTREE.
- VI. Mr. W. E. HIPKINS.
- VII. MESSRS. THORNEWILL and WARHAM.
- VIII. Mr. W. B. COLLIS.
- IX. Mr. HUGH S. DUNN.
- X. INSTITUTION NOTES.

APPENDIX I.

By MR. W. G. NORRIS,* *Member*, OF COALBROOKDALE.

Among the miscellaneous articles in the Works stores at Coalbrookdale at Midsummer, in 1718, was a brass fire-engine valued

* Mr. Norris has also contributed a list of large cylinders and other castings, &c., supplied to colliery owners and others between the years 1732 and 1792, which is invaluable as a means of tracing the dates of erection of many large engines during the eighteenth century.

at £7 3s. This is not likely to have been a utensil such as is now known by the same designation ; but probably was a model of the newly introduced machine, which was then beginning to make itself widely known under that name.

No record has been preserved of direct communication between Thomas Newcomen with his partner John Cawley and Coalbrookdale, if any took place ; and the name which is first found associated with "Fire-Engine" work in the account books at Coalbrookdale is that of Stanier Parrot of Coventry, as though he were at the time at Coalbrookdale. In December and March 1718, some castings and "pipes 6 inches bore" were charged to him for "ye fire-engine."

Thomas Newcomen however had in some previous year (about 1715), erected one of his engines for Sir Robert Newdigate at Griff Colliery, near Nuneaton ; and Stanier Parrot, resident at Coventry, and evidently also interested in adjacent coalworks, may be assumed to have made acquaintance with Newcomen and with his invention and its results. There are particulars in print* of the difficulties connected with the erection of this first engine at Griff, and also of the economic advantages of one or other of these early engines.

Evidently it was not difficult to obtain wrought-iron for the rods and links connecting the wooden beam with the cast-iron articles ; and the work must have been done by local mechanics to suit each particular engine at the time of its erection. For years the necessary cast-iron articles only were supplied from Coalbrookdale ; and also it was not until the middle of the century that boilers came to be made entirely of wrought-iron, when "engine plates," or small plates hammered at a "plating forge," feebly made their appearance.

The earliest entry of a set of castings for an engine is in October 1724, when there were sent to the order of Richard Beech, of

* Stuart's "Historical Account," etc. Desaguliers' "Experimental Philosophy," Vol. 2, 1734.

Walton near Stone, to "Harding beyond Chester," now known as Hawarden—

		£.	s.	d.
1 Cillinder and Bottom	25 0 10 @ 32/6 =	40	15	5
1 Pistern	1 1 21 @ 32/6 =	1	17	7
2 Brass Pipes and Brass to s ^d Pistern .	1 1 4 @ 14d. =	8	8	0
A parcel of Wrought Iron Screwpins.	0 0 40 @ 9d. =	1	10	0
Carriage of Do. to Harding		3	16	0
		<u>£56</u>	<u>7</u>	<u>0</u>

In 1725 there are entered :—

Aug. Stanier Parrot of Coventry.

1 Cillinder, 1 Bottom, 1 Pistern and 4 Pipes weighing 74 1 11 @ 32/6 =
£120 16s. 4d.

Oct. Sir Richard Newdigate of Griff.

1 Cillinder, 1 Bottom, 1 Pistern with 3 Pieces to go round it, and 3 Pit
Barrels (for pump) 51 3 25 @ 32/6 = £84 9s. 1d.

From this period there followed a continuous demand for sets of these castings, with working barrels and pipes for pump work; the cylinders and castings increasing in dimensions and weight. Unhappily the volumes of "the Journal" account books for the years 1749-65 and 1771-78 are missing, so that a complete list of the cylinders made and sent away up to 1800 cannot be prepared.

The only reference that can be traced to a patent connected with this engine work occurs in a letter from Richard Ford to Thomas Goldney, of Bristol, both partners in the concern, under date 26 March 1733, * "and as y^e patent for y^e Fire Engine is about expiring, that business will consequently more increase."

There is no evidence in the books of difficulty in making the castings. With the increase in the size of the cylinders an important practical difficulty connected with the boring began to be experienced from the frequent breakage of the boring bars. It was desired in 1734 by the managing partner, Richard Ford, to have for this purpose "a wrought-iron spindle, 12 feet long and full 3 inches in

* Savery's patent dated July 1698 (extended for 21 years) expired 25th July 1733.

diameter; one end to be left square for 18 inches, and y^e other end to be left square for 6 inches, and the remaining 10 feet to be left round, but to be as true as may be, and to be made of right tuff iron and right sound." This was ordered from an anchor-smith in Bristol, and supplied at a cost of £26 10s. in September 1734. Another was obtained in 1745, $5 \cdot 8 \cdot 15$ @ 8d. per lb. = £21 19s. 4d.

The motive power for the blowing apparatus for the blast furnaces, and for any machinery, in the works at Coalbrookdale was the water from the brook running through the valley in its course to the Severn, which necessarily was a variable supply. In order to utilise the limited quantity in the drier periods, it was decided in 1743 by the then acting partner, the second Abraham Darby, to erect an engine for pumping back the water after it had passed over two or more water-wheels, up into the reservoir from which it had first issued, and to make it proceed on its course of labour again. The difference in level through which the water was raised was about 120 feet. The dimensions of the cylinder and of the pumps have not been preserved. The total cost, as upheld in the year's accounts for 1745, appears to have been for—

	£.	s.	d.
Cylinder, Working Barrels and Cast Iron Articles	307	18	7
Brass Work and Lead	108	14	1
Plate Iron and Bricks	70	15	8
The Oak Regulating Beam	10	15	0
Various Labour in and with the Erection and the Pit	356	0	3
	<u>£854</u>	<u>3</u>	<u>7</u>

Similar engines for the same object were subsequently erected at the other works belonging to the concern at Horsehay in 1754, with cylinders 10 feet by $47\frac{3}{4}$ inches, and in 1756 with cylinders 10 feet by 60 inches; and at Ketley about the same years with the same sizes of cylinders. With the Coalbrookdale engine the experiment was made of using spelter in place of brass for the working barrel of the pump, either entirely or as lining for an iron pipe. A second working barrel of the same size was sent with some engine work into Cornwall, but was quickly returned. The size of the working

barrel was 9 feet long by $8\frac{1}{4}$ inches diameter, and the weight of spelter in each was 8 cwt.

The application of a pumping-engine to return water for recurring use by a water-wheel was subsequently adopted at several furnaces in England and Scotland, because of the advantage of a continuous blast upon the furnace.

From 1755 to 1765 James Brindley was frequently at Coalbrookdale. He superintended about 1756 the preparation of castings for an engine for Mr. Broade of Fenton near Stoke-on-Trent, but there is no record of experiments with wood for cylinders: * experiments which seem hardly probable, having regard to the experience already acquired with both steam and iron; but probably experiments were largely made with casing the cylinder, condensation, and steam pressure. He obtained a patent for an arrangement of boiler to be made largely of cast-iron, upon which several experiments were made by the Coalbrookdale concern, but without satisfactory results. At last, in 1762, it was treated as old iron. He also superintended the castings for a larger engine sent to Newcastle-on-Tyne for the Walker Coal Co. in 1763. The cylinder was $10\frac{1}{2}$ feet by 74 inches, and was said to be the largest that had been sent into that district. It is stated also that the "bore was turned perfectly round and well polished," and "the whole a complete and noble piece of work."

The accurate boring of the large cylinders was still a source of anxiety. In 1751 a note is made against a "Journal" entry:—"The 54-inch cylinder for Lord Ward having been examined, was found to be true and exactly bored, viz., within $\frac{1}{8}$ -inch in all the working part." Afterwards, in 1776, James Watt wrote † to James Smeaton: "Mr. Wilkinson has improved the art of boring cylinders, so that I promise upon a 72-inch cylinder being not

* See "Lives of Engineers—Brindley," by Dr. Smiles.

† See Farey's "History of the Steam Engine." Mr. John Wilkinson, of Bersham, near Wrexham, contrived about 1775 a new machine for more accurately boring the insides of cylinders. A straight bar was fixed in the axis of the cylinder, which was made to revolve slowly round it, while a sliding cutter was caused to travel along the central stationary bar.

further distant from absolute truth than the thickness of a thin sixpence in the worst part."

After 1750, notices of "engine plates," or "boiler plates," are more frequent. They were all hammered under a "Plating" hammer from slabs or moulds. They seldom exceeded half a cwt. each. It was not until after 1790 that boiler plates, about 4 feet by 8 inches by $\frac{1}{2}$ inch were rolled at the Coalbrookdale Co.'s works at Horsehay: and no other works in Shropshire then made them.

With the improvements in boilers consequent on the use of wrought-iron boiler plates, the greater efficiency and economy of the steam-engines conformable to the designs of James Watt were becoming generally acknowledged. In 1780, Matthew Boulton visited Coalbrookdale, in order to confer with the Coalbrookdale partners upon the requirement for steam-engines for Cornwall, on which Boulton and Watt had reports from their own agents. One of the results was that the Coalbrookdale partners decided to supersede the Newcomen engines in use at the works at Coalbrookdale and at Ketley, by engines on the plans of James Watt. It was found that the Newcomen engine in Coalbrookdale consumed 12 tons of small coal, valued at 2s. 6d. per ton, beyond what would be required for every 10,000 strokes by a Watt engine having a cylinder 66 inches in diameter and 11 feet long, making 9 strokes a minute. It was agreed, therefore, in 1781 to pay to Boulton and Watt one-third of the estimated saving in fuel upon this basis, or 10s. for every 10,000 strokes, as recorded by a mechanical counter, during the unexpired period of the term of Watt's renewed patent.

The difficulty and extreme delay involved in sending such large castings into the North of England, all being forwarded to Bristol and thence shipped to London and often transhipped, had led to the cessation of business with the North.

At that time there were sixteen large engines at work in connection with the coal works and furnaces of the Coalbrookdale concern at Ketley, Dawley, Madeley, and Coalbrookdale, chiefly for pumping.

The enlargement of the cylinder bottom, and the addition of a "hot well," appear to have been improvements which were made

upon the earlier castings for the engine; but experiments were also made upon the expansion or extended use of the steam by means of two cylinders. Arising partly from these experiments Jonathan Hornblower, of Penryn, obtained a patent for an engine somewhat of this arrangement in 1781.* Similar experiments led to the patent in 1790 of Adam Heslop, who was then engaged at the Ketley Branch of the Coalbrookdale concern, for the application of two cylinders, one hot and the other cold. A pumping-engine to Heslop's designs † was made in 1791-2 and sent to Workington, where it worked for years at one of Lord Lonsdale's collieries. In 1878 an engine of this kind but arranged chiefly for winding, supposed to be the last, was presented to the Commissioners of Patents by Lord Lonsdale, and was erected at the Patent Museum. The notice of this donation in the "Times" of 24th May 1879 led to a letter from W. R. Anstice of the Madeley Wood Co., saying "that they still have three of the same description at work; they had five, and had had eight." One continued to work at a coal pit until 1890. The last of the single-cylinder Newcomen engines continued to work a helve in one of the Coalbrookdale Co.'s forges until 1879, when it gave place to a steam-hammer. A photograph of a winding engine built at Coalbrookdale about 1790 is shown in Plate 17,

The engines completed at Coalbrookdale must have been adapted in some manner to rotative action at least by 1780; but no detail drawings or descriptions are preserved there. Small engines working with cranks for coal winding were in frequent sale by 1790. Several office drawings of various designs made previous to 1800, which had been the property of William Reynolds, of the Ketley Branch of the Coalbrookdale concern, were sent to London in 1879; but recent enquiries at the Patent Office Library and at the Board of Education at South Kensington have failed to discover their present owners.

In Farey's "History of the Steam Engine," 1827, and in Stuart's "Descriptive Anecdotes of Steam Engines," 1829, are engravings

* Proceedings 1862, page 243.

† See also H. A. Fletcher on the Heslop Engine, Proceedings, 1879, page 85.

representing Newcomen and other engines; also in the Transactions of the Chesterfield and Derbyshire Institution of Engineers, Vol. IX, 1881-2, p. 37, is given an illustrated description of the Atmospheric Engine at Handley Wood, built by the Coalbrookdale Iron Co. in 1776.

APPENDIX II.

By SIR FREDERICK BRAMWELL, BART., *Past-President.*

The writer wishes to draw attention to the details of Newcomen engines given in Belidor's "Architecture Hydraulique," published in Paris in 1739, in which a description of Newcomen's engine occurs on page 309 of the first part, illustrated by three extremely good engravings. These have not been referred to by the author, although he has quoted so fully from Emerson's book.

In his own investigations * as to the inventions of Newcomen, the writer found that Newcomen never took out a patent,† probably because he joined forces with Savery, and the terms of Savery's patent of 1698 were wide enough to cover Newcomen's invention.‡ A recent examination of the official lists of patents from the beginning of 1617 to 1852 shows neither the name of Newcomen nor that of Cawley. He has however found three patents in the name of Thomas Savery, one of which is of 1698, above referred to. The year 1705, quoted by Mr. Davey (page 658) from Stuart, was the year wherein only a single patent was taken out, and that was by a gentleman of the name of Lydall for separating gold and silver from tin.

* Life of Watt in "The Dictionary of National Biography."

† Mr. Norris writes (page 675) that, as contemporary evidence in the belief of the grant of a patent, may be quoted an extract from a letter from Richard Ford of Coalbrookdale to Thomas Goldney of Bristol, both partners in the Coalbrookdale concern, under date 26 March 1733, "And as y^e patent for y^e Fire Engine is about expiring, that business will consequently more increase."

‡ See also Transactions, British Association, 1877, Mechanical Science Section, page 217.

APPENDIX III.

By MR. HENRY DAVEY, *Member of Council.**Newcomen Engines at the Farme Colliery, Rutherglen, near Glasgow.*

Plate 18.

The Newcomen engines at the Farme Colliery were three in number. The first was erected in 1810. In its present state it is illustrated in Plate 18 by photographs and drawing, together with indicator diagrams taken from it. It has a 42-inch cylinder with a stroke of 5 feet 8 inches, and has worked almost constantly since it was put up, being employed in winding coal. One rope draws from a depth of 30 fathoms, the other from a depth of 44 fathoms. Until recently, it also pumped water from a depth of 23 fathoms with an 8-inch bucket pump. It drew from 150 to 200 tons per day, and pumped for four or five hours in the twenty-four, on a consumption of 34 cwts. of "dross" coal per twenty-four hours.

In 1820 was erected another winding engine; and in 1821 a pumping engine, having a 60-inch cylinder, with a stroke of 7 feet. It worked three set of pumps. In the top set the pump was 20 fathoms deep, with 15½-inch bucket; the second set was 30 fathoms below, with a 12-inch bucket; and the bottom set was 20 fathoms lower, with 10-inch bucket: making 70 fathoms total lift. Steam was supplied by two haystack boilers, 30 feet and 25 feet in diameter; the pressure of steam was 2½ to 3 lbs. on the square inch. The piston was made as an ordinary air-pump bucket, and was packed with the old hemp ropes that had been used in the pit. A head of water 12 inches deep was always kept above it, so as to prevent air leaks. The engine worked night and day, driving two pumps, and sometimes three when they were hard pressed with water in the pits. Wood blocks were bolted to the beam to regulate the stroke. They were covered with old ropes to deaden the shock of the beam coming down, should the engine-man happen to give her a little extra steam.

The winding engine erected in 1810 is still working; it was constructed by John McIntyre, who made his own patterns, and

obtained the castings from the Camlachie Foundry, three or four miles away. The two other engines were taken down in 1888.

APPENDIX IV.

BY MR. H. W. PEARSON, *Member, OF BRISTOL.*

The writer having offered to the Institution in 1901 a description of the Ashton Vale Newcomen Engine, the Council considered it would form an interesting contribution to the history of the subject; and Mr. Davey having offered to compile a general history of the Newcomen engine, the writer trusts the following short account of some early illustrations of pumping and winding engines, which in most cases have come directly under his notice, will be of some service to the Members of the Institution, and of sufficient interest to form a pleasing link between the past and the present. The existing developments, and the perfection to which the steam-engine and pump have been brought, will perhaps make the retrospect a still more interesting and instructive comparison in the study of their history, more especially in connection with mechanical works. The earlier and more ancient examples of steam as a power for working pumps and driving machinery were referred to by the writer in a pamphlet, published in 1896, entitled "The Creation and Development of the Steam-Engine," which is in the Institution Library.

*Newcomen Engine at Ashton Vale Iron Works, Bristol.**

Plates 19 and 20.

The earliest instance of a pumping engine for colliery purposes, which has come under the writer's notice, is the Newcomen engine at the South Liberty Colliery of the Ashton Vale Iron Company,

* Compiled by the writer from particulars taken by him from the engine itself at the South Liberty Colliery in 1895, at which date the engine was in regular work. It has since been dismantled in 1900. There is at South Kensington a photograph of this engine, taken many years ago, when it was in a more perfect condition than it was in 1895.

near Bristol. According to common statements Thomas Newcomen, of Devonshire, invented in 1705 the first successful cylinder and piston engines; and this example is considered one of the early large engines built by him, possibly about 1746-60.* The drawing in Plate 19 shows the general arrangement of the engine, and has been prepared from a sketch the writer had made in September 1895, when he had occasion to take some particulars on the spot for illustrating this old relic. The drawing, together with the three photographs, Plate 20,† conveys a good idea of the rude though successful working structure of Newcomen's age, with its open-topped cylinder and trussed oak beam having arch-heads at the ends. The cylinder was 5 feet 6 inches diameter, and being 10 feet long had clearance enough to allow of working 8-foot stroke if required. The piston was packed with rope ends, and loaded with pig-iron to help to balance the indoor stroke; and was worked with a covering of water on the top, so that, if the packing was not quite tight, only water leaked through and helped to maintain the vacuum. The valves fitted to the cylinders consisted of a circular lift steam-valve, for admitting steam during the outdoor stroke; a slide-valve B for admitting injection water to condense the steam for forming the vacuum; and a flap valve C, kept closed by a weighted lever, for the escape of the injection and condensed water at the end of the indoor stroke. The Newcomen engine was utterly dependent on manual working of the valves, until that egregious youth Humphrey Potter devised self-acting catches whereby the working beam was made to perform the opening and closing of the valve.‡ This led to the introduction of the plug frame, fitted with catches to act on the valve

* Mr. W. G. Norris writes that he has little doubt the castings for this engine were made at Coalbrookdale about the year 1760, or perhaps a few years earlier; no castings so large could have been obtained much earlier than that date.

† Mr. W. G. Norris writes, in reference to these illustrations, that there must have been renovation in the early years of the last century, as the large adjusting screws on the arch-head at the pump end of the beam in Fig. 7, Plate 20, cannot have been of the same date as the cylinder.

‡ This story is quite discredited.—H. D.

levers—first put on a Newcastle engine by Henry Beighton in 1718.* The engine was at first supplied with steam from a haystack boiler, but latterly from the boilers working the winding engine; the steam was passed into a receiver through a reducing valve by which the pressure was brought down to $2\frac{1}{2}$ lbs. to the square inch before entering the cylinder. The beam was built of oak timber trussed with rods, 24 feet long and 4 feet deep, and had V-shaped gudgeons of cast-iron bolted on it in the form of a collar, which rocked in cast-iron plumber blocks. Its weight with the gudgeons, trusses, &c., was about 5 tons. The engine made from ten to eleven double strokes per minute.

The pumps, which were three in number, were bucket lifts, and 9 inches in diameter, and were worked from the end of the beam by chains secured to the beam, and passing over the wooden arch-head at outer end of beam and thence down to the pump-rods, which were of wood, bolted together with side straps. The pumps were in three lifts, delivering one into another from the bottom of the shaft, which was 700 feet deep. There was a jack-pump J attached to the inner end of beam, which lifted water into a cistern on the beam floor for supplying the injection water to the cylinder. A vacuum was formed on the under side of the piston by the admission of steam during the outdoor stroke, which was then condensed by the admission of injection water; and the top of cylinder being open to the atmosphere, the atmospheric pressure on top of piston caused it to descend with an energy proportional to the perfection of the vacuum formed, thereby producing the indoor stroke, which lifted the pump rods and buckets at the outer end of the beam, and so raised the water from the bottom of the shaft. The outdoor or descending stroke of the pumps was made chiefly by the weight of the rods, &c.; and thus the double stroke was completed.

No indicator diagrams had ever been taken from the cylinder until the writer took some in 1895, for which purpose the cylinder had to be drilled and indicator connections and gear fitted. Fig. 5,

* "Imperial Cyclopædia of Machinery," by W. Johnson, 1852.

Plate 19, represents the indicator diagram, showing the amount of vacuum to be between 9 and 10 lbs. At a speed of 10 strokes per minute this diagram gives about 52 horse-power. The old driver seen in Fig. 6, Plate 20, near the gudgeon blocks, worked the engine up to the time of its being dismantled in 1900, and had driven it since he was a boy. His father and grandfather had worked it before him. No records could be obtained of the cost of the engine, neither was the writer able to gather any information as to who made the castings or erected the engine. He searched for a date on the cylinder and other parts of the engine, but could find no evidence of it. The gear for actuating the steam-valve and injection-valve was almost identical with that shown in the illustrations of the earliest engines: in confirmation of which the writer consulted an old book called "The Principles of Mechanics and the General Laws of Motion," by Emerson, published in 1758, kindly lent to him by Mr. T. Bush, of Bath, formerly of the firm Messrs. Bush and De Soyres of Bristol; this he has shown to Mr. Davey. Mr. W. G. Norris believes that a second edition of this book was published some years later.

Engine at Buffery Old Colliery, near Stourbridge.

Fig. 15, Plate 26.

Mr. E. B. Marten, of Stourbridge, has lent the writer some sketches of early examples of open-topped cylinder engines of the Newcomen kind, which were worked in the neighbourhood of Stourbridge. These sketches* are from a collection of Mr. W. B. Collis, of Stourbridge, and are from the pen of the engineman who drove the engines, named William Patrick, whose father and grandfather had worked them before him.

"A Scribble of the Buffery old Pumping 'Engine," Fig. 15, Plate 26, drawn from memory in 1878, illustrates the Newcomen atmospheric engine, and shows the old haystack boiler with its

* See also Appendix VIII (page 691).

steam connections, and the admission of steam controlled by the levers worked from the tappet on the plug-rod from the beam. The engine as shown had a Watt condenser. There are also shown the jack-pump and hot-well tank, dealing with the injection water after it had done its work in the cylinder in forming the vacuum to give the indoor stroke. The outdoor stroke was made by the weight of the pump-rods, as in other instances of this class of engine. The oak trussed and tied beam, with quadrant ends and chain connections to pump and piston-rods, was similar to those previously described in connection with the engines of the Newcomen period.

Atmospheric Winding Engine, near Stourbridge.*

Fig. 16, Plate 26.

The other illustration is of a curious old atmospheric winding engine of the same kind as the one just described, with the exception that the quadrant ends to the beam were dispensed with; the couplings for the piston-rod and for the connecting-rod to the flywheel and crank-shaft were formed by a gudgeon or pin working in a sort of gudgeon block attached to the ends of the wooden beam, which was doubtless in two slabs, with a space between them to allow of the oscillation of the piston-rod and connecting-rod at the beam ends. An interesting note was made by the draughtsman, Mr. Patrick, stating that this is a representation of the atmospheric winding engine worked by him when he was ten years old in the year 1814; it was drawn by him in 1878 from memory. Several engines of somewhat similar description were to be seen working in Shropshire and South Staffordshire up to 1850.

York Water Works Pumping Engine.

Plate 21.

On occasion of being consulted by the York Water Company, in a visit to their works the writer came across an early illustration of

* See Indicator Diagrams, Plate 27.

their "Fire Engine," which is here reproduced by the kindness of Sir Jos. Sykes Rymer, the Chairman, and Mr. Humphreys, the engineer; Plate 21 is a copy of the original working drawing, reduced to one quarter the size of the original.

The action of this engine, it will be seen, is almost identical with that of the Ashton Vale Newcomen Engine previously described. The engine was designed by Smeaton, and erected in 1784. It was 18 horse-power, and raised 16 gallons of water per stroke, and could work up to 18 strokes per minute, and appeared to be used from 7 to 8 hours each day. The cylinder was placed immediately over the centre of the boiler, and the steam admitted at the bottom of the cylinder, the admission being regulated by the cataract; diameter of the steam-supply pipe 5 inches. The diameter of the cylinder was 27 inches, and its total length was 8 feet 3 inches. The length of the stroke was 6 feet; length of beam $23\frac{1}{2}$ feet, with quadrant ends. Two pumps, one 9 inches and the other $7\frac{1}{2}$ inches diameter. The rising main from the larger pump to the reservoir on the top of the tower was of flanged iron, and that from the smaller pump delivered into the reservoir through wooden pipes. The lift was about 70 feet. The supply pipe from the reservoir to the city was 7 inches diameter. A wooden overflow pipe was fixed for returning the water into the well below, in which the pumps were situated. A tell-tale worked by a float was placed in the engine-room, for showing the depth of water in the reservoir. The boiler was haystack; the body was made of copper, 9 feet 3 inches diameter at its broadest part, and 7 feet at the bottom, the crown was of iron-plate; total depth 8 feet 6 inches. For the most part the cataract appeared to have been adjusted to eleven strokes per minute.

An interesting trial of the engine was made by Smeaton in August 1785, and is recorded in Table 1 (page 688).

TABLE 1.

Date.	Number of Trial.		Strokes counted.	Length of Strokes.	Total Time of counted Strokes.		Weight of Coals.	Time of Consumption.	Reduced Strokes per minute.	Metts used per hour. †	Hogsheads raised per hour.	Hogsheads raised per mett.	
1785. 24 Aug.	1	10	6	ft.	min.	sec.	stone. lbs.	hour. min.					
	1	10	6		1	3	11 4½	0 44	9 ⁵ / ₁₀	1 ²⁸ / ₁₀₀	328 ³ / ₁₀	256 ⁵ / ₁₀	{ Slack.* Cataract.
	2	10	6		1	3	12 5¾	0 56½	9 ⁵ / ₁₀	1 ¹⁰ / ₁₀₀	328 ³ / ₁₀	298 ⁵ / ₁₀	{ Coals. Cataract.
	3	13	6		1	2	11 6	0 46¼	12 ⁶ / ₁₀	1 ²⁴ / ₁₀₀	442 ⁵ / ₁₀	356 ⁹ / ₁₀	{ Coals. Self- worked.

* Same as Slack.

† Mett, or measure, is believed by Mr. Humphreys, the present engineer of the York Water Works to mean a bushel, one bushel of coals weighing 84 lbs.

APPENDIX V.

BY MR. JOHN H. CRABTREE, OF OLDHAM.

Newcomen Pumping Engine at Bardsley, near Ashton-under-Lyne.

Plate 22.

This engine, in a ruined condition, is still to be seen at Bardsley, near Ashton-under-Lyne, and was used for pumping water out of a coal mine there. It had a wooden beam with metal bracings, and is said to be of very early date. It had a cylinder, open at the top, about 28 inches in diameter, with a stroke of about 6 feet. The steam entered the cylinder at the bottom, and the condensation was effected by the injection of cold water into the cylinder. There was no separate condenser. The engine passed out of use about 1830. It pumped water from the "Camel" mine, which was 70 yards deep. The boiler was of the "wagon" pattern, and was placed in front of the beam-bed of the engine.*

* A Photograph of this engine is in South Kensington Museum.

APPENDIX VI.

BY MR. W. E. HIPKINS, *Member, OF BIRMINGHAM.*

The drawing reproduced in Plate 23 represents a Newcomen mine-engine, but the writer has no knowledge at what mine it was worked. James Watt visited various mines for the purpose of making hand sketches and taking particulars of the engines and coal consumption, for enabling him to send in a report pointing out the saving to be effected by adopting his own plan of engine in lieu of the atmospheric. When the law cases with Hornblower, Bull, and other later infringers of Watt's patents, were proceeding, most of the sketches were properly drawn out with a view to their production in evidence; and the drawing in Plate 23, dated 1826, was taken from a portfolio containing all these drawings in question, and is doubtless made from one of James Watt's sketches of a much earlier date, probably about 1796. This drawing represents a modern Newcomen engine arranged to work on the injection principle, the external cylinder or water-jacket having been discarded. In the position shown the engine is at rest, the weight of pump-rod U having drawn the outer end of the working beam R down, thereby bringing the piston up to the top of the cylinder. The manipulation necessary in working the engine was the alternate opening and closing of two valves; the regulating or steam valve M and the condensing or injection valve H. When the piston reached the top of the cylinder, M had to be closed and H opened; and on reaching the bottom M had to be opened, and H closed.

In starting * the engine from its position of rest shown in the drawing, the regulating valve M was opened, and the steam admitted was at first condensed by contact with the cold cylinder. After a short time however, the cylinder acquired the temperature of the steam, which then ceased to be condensed, and became mixed with the air that previously filled the cylinder. The steam and heated air, having a greater force than the atmospheric pressure, opened the

* With trifling verbal modifications this paragraph is reproduced from "The Steam Engine," by Dr. Dionysius Lardner, seventh edition, 1840, pages 69-70.

blowing or snifting valve V, which was placed at the end of a small pipe at the bottom of the cylinder, and opened outwards. From the snift the steam and air rushed out in a continuous stream until all the air had been expelled, and the cylinder was filled with pure steam. This process was called blowing the engine, preparatory to starting it. When it was about to be started, the engine-man closed the regulating valve M, and thereby stopped the supply of steam from the boiler. At the same time he opened the injection valve H, whereby a jet of cold water was thrown up into the cylinder. This immediately condensed the steam contained in the cylinder, and produced a vacuum. The atmosphere could not enter the snift valve V, because it opened outwards, so that no air could enter to destroy the vacuum. The atmospheric pressure above the piston now took effect, and forced it down in the cylinder. The descent being completed, the engine-man closed the condensing valve H, and opened again the regulating M. By this means he stopped the play of the jet within the cylinder, and admitted fresh steam from the boiler. The first effect of the steam was to expel the condensing water and condensed steam, collected in the bottom of the cylinder, through the eduction pipe N, containing a valve (called the eduction valve) which opened outwards; the pipe led down to the hot cistern, into which the water was therefore discharged. When the steam admitted through M ceased to be condensed, it balanced the atmospheric pressure above the piston, and thus permitted the latter to be drawn up to the top of the cylinder by the weight of the pump-rod U. The ascent of the piston was also assisted by the circumstance of the steam being somewhat stronger than the atmosphere.

APPENDIX VII.

By MESSRS. THORNEWILL AND WARHAM, OF BURTON-ON-TRENT.

Basset Atmospheric Engine, Denby Colliery, near Derby.

The atmospheric engine photographed in Fig. 13, Plate 24,* was erected in the position shown in 1817, but had been working

* See also "Engineering," 1887, page 285.

previously at another pit. It ran until 25th April 1886, working 24 hours a day in winter and 9 or 10 hours a day in summer, and in the opinion of the present colliery manager at Denby it was at that time working remarkably well and economically.

The stroke of the piston was 3 feet 3 inches, diameter of the cylinder 2 feet 2 inches, and stroke of the pump 3 feet. There were two lifts of buckets, each 7 inches diameter, with a lift of 42 yards, the total depth of the pit being 84 yards. The engine worked at 22 strokes a minute, and the safety-valve was loaded to a pressure of 2 lbs. per square inch.

Plate 25 shows a photograph and drawing of an Atmospheric Rotary Pumping Engine, made at the "Moira Furnaces" in 1821.

APPENDIX VIII.

BY MR. W. B. COLLIS, OF STOURBRIDGE.

Communicated through Mr. E. B. Marten, Member.

The writer sent to the Institution a number of sketches of old engines, made from memory by Mr. William Patrick (pages 685-6). From these have been selected for illustration Plates 26 and 28, on account of their being Mr. Patrick's personal recollections of definite engines of the atmospheric class.

Mr. Patrick was foreman over the colliery engine-men, some twelve in number, at Messrs. Cochrane and Co.'s Woodside Collieries between the years 1854-60, and came at that time under the writer's direction. When he left Woodside he went to Middlesbrough, and subsequently returned to Dudley. The writer believes the whole of his sketches are from memory. None of them relates either to the present Buffery pumping engine or to the atmospheric winding engine, now being worked by the Mines Drainage Commissioners in the Old Hill district. The writer was informed that the former of these was

erected in 1801, and the latter some thirty years later. He re-started them both, and put them to work about 1874. The pumping-engine works with about 12 lbs. steam pressure, and has an air-pump and condenser. The air-pump is on the outer end of the beam. The engine has no valve between the boiler and the closed top of the steam cylinder. The steam-pressure on the top of the piston with the vacuum on the underside is sufficient to raise the pump-rods and water. When the vacuum is destroyed by the admission of a small whiff of steam, the weight of the rods overpowers the steam, and drives it back into the boiler. The atmospheric (open-topped) engine receives the injection (condensing) water in the bottom of the cylinder, whence it escapes through a "pickle-pot" vessel beneath, similar to that shown on Fig. 20, Plate 28, provided with a "sinker," or self-acting flap-valve opening outwards. The writer has had to alter both engines by introducing equilibrium valves in place of the original mushroom valves, which had become too heavy for handling, on account of the use of a higher steam-pressure than that for which they were designed; but the principles of the engines remain the same.

APPENDIX IX.

By MR. HUGH S. DUNN, *Member,*

OF THE CAPRINGTON COLLIERY, NEAR KILMARNOCK.

The writer draws attention to the description and illustration * of a pumping-engine set up at Caprington in 1806 (Plate 29), which, according to the late Mr. Bryan Donkin, was a Newcomen engine.† A short description of it has also been published in a recent number of the Transactions of the Institution of Mining Engineers.

* See also South Kensington Museum.

† See "The Engineer," 15 July, 1898, p. 65, illustrated p. 57

Notes on a Newcomen Engine at Caprington Colliery, Ayrshire.

Plate 29.

This engine, erected at Caprington Colliery in the year 1806, is understood to have been built at Carron Iron Works in Stirlingshire, sometime between 1770 and 1780; it continued at work until July 1901, pumping from a pit, the exact distance from the surface of the water in the sump to the lip of the discharge being 165 feet 8 inches. As originally erected at Caprington Colliery the engine had the usual wooden beam with cast-iron gudgeons, and a rocker or cradle on each end. The pumps were worked at one end by a chain fastened to the upper end of the cradle or rocker, and the piston-rod was connected to the other end of the beam in the same manner. The cradles served the purpose of a parallel motion. About the year 1837 the wooden beam, having shown signs of distress, was removed, and a cast-iron beam with cast-iron gudgeons was substituted, and was fitted with a Watt parallel motion at each end. At the same time the original boiler, which was spherical, was removed, and an egg-ended boiler was substituted. These were the only alterations made on the engine during the ninety-five years it worked at Caprington Colliery. The engine is of the usual kind, made on the Newcomen principle. The cylinder is $30\frac{1}{2}$ inches internal diameter, and about 8 feet long. The working stroke however is only 4 feet 6 inches to 5 feet. The excess length of cylinder is necessary, owing to the lower part of it being used as a condenser, and also because there is no crank to regulate the stroke, which constantly varies with the least change of either steam or atmospheric pressure, or with the condition of the pump bucket. The steam is admitted to the cylinder at just over atmospheric pressure by a plain plate-and-pin valve, worked by a rod passing through an ordinary stuffing-box. The valve-rod is actuated by the tappet gear through a series of rods and levers, worked direct from the beam. The water for condensation is admitted at the bottom of the cylinder, also by a plate-and-pin valve similarly worked; but here the valve-rod passes through

the side of the water valve-chest, and is kept tight by a cramp arrangement, which presses a collar on the valve-rod against a small brass collar screwed into the side of the water valve-chest. The condensed steam and the condensing water are discharged through an eduction port in the bottom of the cylinder, which is practically the sole-plate of the engine. The discharge or eduction pipe, fitted with a hinged non-return valve, is immersed in a cast-iron tank or hot-well filled with water, which effectually secures the engine against taking in air at the discharge valve. From this hot-well the feed-water flows into the boiler by gravity, being regulated by a float which opens the feed-valve according as water is required in the boiler. The cycle of the engine is as follows:—The pump-rods being heavier than the piston and other attachments at the cylinder end of the beam, the piston is always kept at the top end of the cylinder when the engine is stopped. To start the engine, the steam-valve is opened, and the steam allowed to blow through for a few seconds; it is then closed, and the injection-valve opened; this produces a partial vacuum, and the piston will move down perhaps a few inches. The water is then at once shut off, and the same process is repeated until the air is entirely expelled from the cylinder, and the engine continues to work full stroke. Every time the steam-valve is opened, the water which was admitted during the previous stroke is expelled by the steam; and as soon as the cold water is admitted, the vacuum is formed, and the non-return eduction-valve closes. The piston is well worth study, as showing how the difficulties of construction were got over in those early engineering times. The body is of cast iron, and is fastened to the piston-rod by an old form of splice-joint secured by a collar-ring and cottar-pin, Fig. 22, Plate 29. To prevent leakage of air into the cylinder, the piston was packed round the flange with old rope or junk, over which were placed quadrant-shaped weights to hold the junk down. A jet of water was always kept running upon the piston, to prevent air from passing. The pump-rods were made of red pine, 4 inches square, jointed with malleable iron plates, 7 feet long by 3 inches by $\frac{3}{8}$ inch; and were carried down the pump pipes to the working barrel, which

was 9 inches in diameter. The stroke of the pump was equal to the stroke of the piston. The piston usually made from 11 to 13 strokes per minute. The water for condensation, and for keeping the piston covered was supplied from the jack-head tank, which was about 5 feet by 3 feet by 3 feet, and was kept full of water by the jack-head pump, which was an ordinary bucket-pump 4 inches diameter, making half the stroke of the engine piston. The spherical boiler was 8 feet 4 inches in diameter. The under half was made of malleable iron plates $\frac{3}{8}$ inch thick; the top half was cast iron. Each half had a flange about 4 inches broad for fastening them together, which was done with $\frac{3}{4}$ -inch bolts spaced about 9 inches apart. The joint was made with gasket and white lead, and the outside stemmed with cast-iron turnings and sal-ammoniac. The whole of the engine castings are cold-blast iron; each casting has a number and its weight cut on it with a diamond-pointed chisel. The cylinder has cut on it

No. 31935

1—6—3—0

CARRON

The engine is to be erected by the Corporation of Kilmarnock in the Dick Museum.

APPENDIX X.

Additional Notes by the Secretary.

In connection with a Paper read before the Institution in November 1883, by Mr. E. A. Cowper, on "The Inventions of James Watt," an illustration (Plate 87, described on page 623) shows "The Steam Engine near Dudley Castle, Invented by Capt. Savery and Mr. Newcomen. Erected by ye later, 1712." *See ante*, page 661.

A reproduction of the original engraving of this engine may also be seen in "The Engineer," 28 November 1879.

A short Paper on "Thos. Newcomen's Steam-Engine," by Thomas Lidstone, was read at the British Association in 1877 (*see* page 680); and a pamphlet "Some account of the Residence of the Inventor of

the Steam-Engine" was published (2nd edition) in 1869 by the same author.

In a series of articles published in "The Engineer" during 1880, on "Pumping Engines at Staveley, Old and New," will be found, on page 84, a full-page drawing of an Atmospheric Engine with separate condenser, built at Coalbrookdale in 1776.

An interesting model of the Newcomen engine, as known in 1720, may be seen at work in the South Kensington Museum. This was exhibited at the Meeting.

Discussion.

The PRESIDENT said he was sure that the Meeting might congratulate Mr. Henry Davey upon the great success of his labours in bringing the history of the Newcomen engine so vividly before them; and they might also congratulate themselves upon having listened to so interesting a lecture. He thought that at this stage of the proceedings formal thanks might be given to the Lecturer and others, so that the whole of the evening might not be taken up by expressions of praise, but that the remainder might be spent in dealing with critical remarks or questions for obtaining information. He would therefore ask them to indicate their agreement with him when he proposed that their best thanks should be given to Mr. Davey for his Lecture and for his Paper, and also to those gentlemen who had made contributions to that Paper, of either drawings or supplemental Papers, namely:—Sir Frederick Bramwell; Mr. W. B. Collis; Mr. John H. Crabtree; Mr. Hugh S. Dunn; Mr. W. E. Hipkins; Mr. E. B. Marten; Mr. W. G. Norris; Mr. H. W. Pearson; Messrs. Thornewill and Warham; and the Board of Education, whose Senior Keeper of the Science Museum, Mr. W. I. Last, had so kindly arranged for the exhibition of the working model of the Newcomen Engine shown at the Meeting.

The vote of thanks was given by the Meeting with much applause.

Mr. VAUGHAN PENDRED said that the admirable Lecture which they had just heard appeared to him to present a suitable occasion for calling attention to the work that had been done by their predecessors. He was afraid that in the present day there was some tendency among younger members of the profession to underrate what was done by the pioneers of the profession. On coming into the hall he mentioned this matter to Mr. Davey, who said that in olden times a man had had not only to invent, but he had to invent something which could be made. The speaker did not think that engineers of the present day thoroughly realised the difficulties with which men like Newcomen and others had to contend. A keen controversy raged between Watt and Trevithick in their work. Trevithick advocated high-pressure, and Watt low-pressure, and he thought that it was quite possible that either of them would have killed the other if he could have got the chance, and it was perhaps as well that James Watt, who was rather a delicate man, never came in contact with Trevithick. Mr. Pendred then read an extract from the "Life of Trevithick," containing the Recollections of the late Captain Charles Thomas,* Manager of Dolcoath Mine, in which a brief description was given of Captain Trevithick's large high-pressure steam-puffer pumping engine, erected about 1814 at the Herland Mine, and worked at about 150 lbs. pressure (Vol. 2, pages 74-75). He, Mr. Pendred, thought they would agree with him that there was a large amount of courage in a man who could do this with the boilers of that day, which were made with rope yarn between the lap of the boiler plates to make the seams tight (page 78). Mr. Pendred quoted also from pages 90, 91 and 395,† which he thought illustrated very clearly the principles on which the men worked who made England what she was to-day. He also thought that, if a selection were made amongst the best of those present, having technical education and skill of all kinds, they would not be able to deal as successfully as their predecessors with the

* "Life of Trevithick," by Francis Trevithick. Published by E. and F. N. Spon, London, 1872.

† *Ibid.*

(Mr. Vaughan Pendred.)

materials and men available 100 years ago. There was an old saying which possibly a great many of them had heard, that the difference between an amateur and a regular workman was that the amateur would attempt to do anything with hardly any tools at all, whereas the workman was entirely helpless unless he had the precise tools he thought necessary. All of the early engineers must have been, in the first sense, amateurs. He thought that Newcomen, producing an engine such as they had heard described, was a man whose reputation should live through all time.

Mr. HENRY LEA, Member of Council, said that as a Birmingham man he had been considerably cheered up by the reference to Newcomen's obtaining the assistance of mechanics from Birmingham. In 1712 Birmingham was the only place apparently in which Newcomen could get two or three good mechanics to help him to build his engines. He might mention that in Birmingham, up to within quite recently, there was an old beam-engine at Cliffords' Rolling Mill, in Fazeley Street, with a cylinder of about 4 feet in diameter, and with a 9 or 10-foot stroke. That engine had a wooden beam built up of baulks of timber, and a wooden connecting-rod. It drove that rolling mill for about ten hours a day for ninety-five years, and the cost of repairs was almost nil. He had taken some diagrams from it and worked out the coal consumption per day, and, as far as he could recollect—it was some eight or nine years ago—it worked out at about 7 lbs. of engine slack per indicated horse-power. The users of that engine wanted to know whether it would pay them to take it out and put a more modern one in, and he reckoned that, with the cost of taking it out and putting in a new engine and new high-pressure boilers, it would be simply change for sixpence. As they would not get more than 10 per cent. reward for their labour, and as the saving in coal would not pay this 10 per cent., there was no financial reason for making the change; and the engine remained, and he believed was there to this day, but he understood the old wooden beam had been taken out and an iron one put in. It was most curious to hear this engine at work; it creaked like an old cane-bottomed chair. One would think it would all come to grief, but it had stood for close

upon 100 years and did its duty well. He did not think that they sufficiently realised the difficulties that Newcomen and Boulton and Watt experienced in the old days in making engines of the size that they did. When one considered these people making cylinders 66 inches in diameter and with a 10-foot stroke, in the days when there were no lathes to bore them with, it made one appreciate very much the perseverance with which they went to work.

He had once looked through the old correspondence between Boulton and Watt, and through Watt's old drawings, and had come across a letter from Boulton to Watt, when Boulton was making the Watt engines at Soho, and Watt was still working in Edinburgh. "My dear friend, congratulate me," he said; "I have just succeeded in making a cylinder" (for some engine) "nowhere more than a quarter of an inch out of truth." Of course Boulton had no lathe to bore out such a cylinder. It was 4 feet in diameter, and had a 10-foot stroke. The cylinder was laid on its side in the yard, and a block of lead, about 2 or 3 cwt., was cast inside it; to this was added about a bucketful of emery and oil. Then two gangs of men pulled this block backwards and forwards, by means of chains, until they had scoured the cylinder smooth. The cylinder was then turned round a little on the ground, and another portion was scoured smooth. When one considered the means which they had for this purpose, he thought it was really a matter of much congratulation that they had produced a cylinder 4 feet in diameter and 10-foot stroke "nowhere more than a quarter of an inch out of truth."

Mr. MARK ROBINSON, Member of Council, drew this conclusion from the Paper: that it was a great pity that ancient and historical engineering records were allowed to fall into ruin and dilapidation. In any other country in the world he felt sure the Government would think it its duty to secure such relics. He went down with Mr. Davey a few months ago to see the old engine at Bardsley, illustrated on Plate 22. It was lamentable to see its neglected state. When they came back, he wrote to the owner of the property on which it was standing and begged to be allowed to

(Mr. Mark Robinson.)

remove it, adding that his Company would be delighted to remove it, together with the stone column which carried the beam, and to re-erect it without any cost to the owners. He proposed to give an undertaking that the engine should be properly taken care of, and that, if at any future time his Company desired to give it up, it should be available for the purposes of a museum. It was probably the oldest steam-engine in the world, and enough of it was still left to form a most interesting relic, yet he could not even get an answer, so little interest was taken in preserving that old relic. If any of the Members who were present, who had it in their power to influence people who had the control of such relics, would endeavour to get more attention paid to them by museum authorities, and would persuade them to put in claims for such relics, he felt sure that a very useful result would have followed from the reading of Mr. Davey's delightful Paper.

While upon ancient curiosities, he wished to point out that the open-top cylinder had come much nearer to their own day than he fancied many people were aware, for about thirty-five years ago he travelled on a steamer, which used to run between Jersey and St. Malo, with oscillating cylinders open at the top; they had no cover of any kind, and one saw the pistons moving up and down—pressed down, of course, by atmospheric pressure alone.

The PRESIDENT said he would now call upon Mr. Davey to conclude the Meeting with any remarks he might wish to make. He had shown how slowly improvements travelled a century ago from one end of the country to the other. In those days there were no such societies as this Institution; and he did not think it would take very long now to find out such a difference in economy between the Boulton and Watt engine and that of Newcomen, and to disseminate the knowledge from one end of the country to the other.

Mr. DAVEY said that he did not know that he could say very much in reply to the questions which had been raised. He was sure they could not realise the difficulties of the situation at the time

when Newcomen set to work to make a steam-engine. He might mention that the first cylinders were made of brass. At that time cylinders of iron could not be cast sufficiently good and true. He had seen a copy of the invoice of the engine erected for Mr. Wauchope in Midlothian only a few years after the first Newcomen engine. The cylinder was made of brass somewhere near London. It was then put on board ship and sent to Scotland. Engines were, at that time, designed by Newcomen, and by engineers such as Hornblower and others, who went into the neighbourhood where the engines were required to find the materials for building them. The pipes at first were made of lead, and the wrought-iron work was made at local blacksmiths' shops.

He had listened with very much interest to the account Mr. Pendred had read of the starting of Trevithick's "pole" engine.* His (Mr. Davey's) father was present on the occasion of the first starting of that engine and had given him very graphic descriptions of what took place. Captain Dick (Richard Trevithick) was there with a crowbar which he inserted under a prop beneath the crosshead to make the plunger start. Then he called out to a man to come and hit the end of the crowbar with a sledge-hammer.

Referring to the lip round the outlet in the bottom of cylinders, Figs. 23 and 24, Plate 30, it was interesting to notice that in some later engines the bottoms of the cylinders were dished and brought down to a cone for the water to tumble into. The steam-valve was moved from underneath the cylinder to the side so that the discharge of the injection water did not at all interfere with the steam inlet. It was quite clear that the Newcomen engine was not ignorantly made. All those little points received consideration, and it was not the want of knowing what should be done as much as knowing how to do it. Therein lay the great difficulty. There was very often as much invention in being able to utilise the materials for the purpose for which they were required, as in the design of the mechanism itself.

* *Life of Trevithick*, Vol. 2, page 78.

Communications.

Mr. ARTHUR TITLEY wrote that he thought all members interested in early mechanical matters would be grateful to Mr. Davey for collecting under one head so many facts and illustrations relating to steam-engine history. Francis Trevithick, in the life of his celebrated father, had recorded, among many other such facts, the existence in 1830, near Camborne, of the remains of what was known as the old moor-stone boiler. This was a floor about 12 feet square of granite blocks which, in the recollection of people then living, had walls several feet in height; and members of a previous generation were known to have taken a contract to cut out the copper pipes, &c., from it. He also recorded that cotter bolts and screw bolts were used to hold such blocks together. The only available iron in Cornwall in the middle of the 18th century was bar, up to 2 inches square, and all weights were carried between the mines and sea-ports on the pack-saddle. This seemed to point to an intimate connection between granite and boiler-making, but in precisely what manner it was hard now to say. The engine illustrated by Pryce, Plate 16, was described as the one purchased and re-erected by Richard Trevithick, Senior, at Bullen Garden (Dolcoath) in 1775 at a cost of £2,040. This engine was of great interest, as it remained for years at Dolcoath in competition with a Boulton and Watt engine, and also with one built by Richard Trevithick, the younger, who ultimately added to it a cylinder cover and plunger air and feed-pumps, retaining the timber beam and "horses' heads." It then (in 1812) took steam from his earliest cylindrical (Cornish) boilers, so that this engine, probably one of the Newcomen's own construction, survived to take part in the first practical experiments with high pressures.

Hornblower's valve, as illustrated by Tredgold, although double seated, gave only a single passage for steam, Fig. 28 (page 703), the present forms being probably much later. Tredgold also illustrated a modification of Hornblower's valve which had a cylindrical packing instead of the upper seat, Fig. 29 (page 703).

Mr. John Greene, Mining Manager to the Lilleshall Company, Shropshire, informed the writer that up to ten years ago they had had an atmospheric engine at work, and it was only broken up for scrap about three years since. It was used at their "Lawn" Pumping Station as a "Man Engine." It had to be "handled" and the levers set in motion at each stroke. It had, of course, an open-top cylinder, and was used about once a week to raise and lower the men employed in repairs and examination of the pumping shaft, the rope used being of thick round hemp 3 inches in diameter. The pit was 400 yards deep.

FIG. 28.—*Hornblower's Valve.* FIG. 29.—*Modification.*

Professor W. CAWTHORNE UNWIN wrote that he thought Mr. Davey was a little hasty in calling the "pickle-pot" a "separate" condenser. It was not separate, being always open to the cylinder; and, as it increased the surface cooled during exhaust and reheated during admission, he would think it decreased rather than increased the efficiency. It looked merely like the arrangement of a draughtsman. There was a working drawing of a Newcomen engine in Smeaton's Reports.

Mr. DAVEY wrote in reply to the communications that he thought Professor Unwin had failed to realize the difference in the mode and conditions of working of the engine with the "pickle-pot" and without it. There was no doubt whatever that the "pickle-pot" had been added to reduce the fuel consumption of the engine. The engine without the "pickle-pot" might have water covering the bottom of the cylinder at the time of opening the steam-valve, and the incoming steam would come into contact with water having an exposed surface equal to the area of the

(Mr. Davey.)

cylinder. In the "pickle-pot" the water surface would be reduced to about one-fourth, and the total surface of metal exposed alternately to water and steam would also be reduced.

The great economy of the Watt condenser arose more *from the mode of removing the water and air from the condenser* than from the use of a separate vessel. The cooling effect of the condenser on the cylinder was nearly as much with the Watt as with the "pickle-pot." In the "pickle-pot," as in the Newcomen cylinder, the air and water were removed by direct contact of steam with the water, involving great condensation in the operation; but, in the Watt condenser, the work was done by an air-pump. The early Watt condensers were constantly open to one end of the cylinder, and in all double-acting engines the condenser was practically constantly open to one end or the other. No doubt the "pickle-pot" reduced the condensation due to the removal of the injection water. There would also be more cooling of the cylinder from direct contact of injection water than from contact of a mixture of steam and air at the same temperature. The economy might not have been very great.

Many letters had been received with reference to the existence of old engines, showing how great an interest was taken in the subject; but it had not been possible to make use of the information offered without unduly extending the limits, and going beyond the title, of the Paper.

Fig. 1. Newcomen Steam Fire Engine.

From "A Treatise on Minerals, Mines, and Mining," by Wm. Pryce, folio, 1778, p. 160.

Appendix I.

Fig. 2. *Colliery Winding Engine, Coalbrookdale.*
Made about 1790. Boilers much later.

Appendix III.

Fig. 3. *Newcomen Winding Engine at the Farme Colliery, Rutherglen.
Erected 1810. Still working.*

Fig. 4. Newcomen Engine at Ashton Vale Iron Works, Bristol.

From a Sketch made in September, 1895. Erected about 1746-60. Dismounted 1900.

Fig. 5. Indicator Diagram taken from above Engine, 27th May, 1895.

Dia. of Cyl. 5' 6"
Stroke 6' 0" about
No. of Strokes per min. 10.

Boiler Pressure 23 lbs.
Vacuum Gauge, none fixed.
Time 3 p.m.

Fig. 7. Side View of Pump End of Beam.

Fig. 8. Top of Cylinder.

Fig. 6. Beam and Driver.

Appendix IV.

Fig. 9.
Section of the Fire Engine for
supplying the City of York with
water.

Designed by J. Smeaton, 1784.
Original Working Drawing, reduced 1-4th.

0 5 10 15 20 Feet

Fig. 10. *Newcomen Pumping Engine, Bardsley, near Ashton-under-Lyne.*

Out of use 1830.

The following three Views are from recent Photographs.

Appendix VI.

Fig. 11. *Newcomen Mine Engine.**From a Drawing dated 12th January, 1826.*

A. Cylinder.	H. Injection Pipe and Valve.	P. Injection Pump.
B. Piston.	I. Injection.	Q. Piston Chain.
C. Piston Stems.	K. Boiler.	R. Working Beam.
D. The Cup.	L. Steam Pipe.	S. Plugtree which opens and shuts
E. To pour water on piston.	M. Regulator Valve.	Regulator and Injection cocks.
F. Overflow pipe from ditto.	N. Eduction Pipe.	T. Gudgeon of Beam.
G. Injection Cistern.	O. Its Valve.	U. Pump Rod.
		V. Snift.

Fig. 12. Parallel Section of Bullen Garden Mine, near Camborne.

From "A Treatise on Minerals, Mines, and Mining," by Wm. Pryce,
folio, 1778, p. 172.

Appendix VII.

Fig. 13. Basset Atmospheric Engine, Denby Colliery, near Derby.

Erected 1817 in position shown, but had been working previously at another pit.
Dismounted 25th April, 1886.

Fig. 14. Atmospheric Pumping Engine, made at the "Moira Furnaces," 1821. Max. boiler press. 4 lbs.

Appendix VIII. (Described in Appendix IV.)

Figs. 15, 16, 19 & 20 are from memory drawings by Mr. Wm. Patrick.

Fig. 15. *The Buffery Old Pumping Engine, near Stourbridge.*

(Being a Newcomen Engine with Watt's separate condenser added).

*Reproduced
¾ths. original.*

Fig. 16. *Atmospheric Winding Engine, near Stourbridge.
Working in 1814.*

¾ths. original.

Indicator Diagrams, taken 8th Dec., 1903.

at Windmill End, near Netherton, Dudley, from Newcomen Winding Engine
with "Pickle-pot" Condenser.

(Similar to Engine, Fig. 16, Plate 26.)

Fig. 17. Valves worked by hand.

Fig. 18. Valves worked by self-acting tappet.

Dia. of Cyl., 28½ ins.

Length of Stroke, 5 feet.

Mean Pressure, 6·8 lbs. per sq. in.

Revs. per min., 30.

I.H.P., 19·7.

Appendix VIII.

Fig. 19. "Pickle-pot" Atmospheric Engine of 16 H.P. Working in 1814.
 Reproduced $\frac{1}{3}$ rd. original.

Fig. 20. "Pickle-pot" Atmospheric Engine. Winding from 6 pits.
 Bore of Cyl. 28". Stroke 4 feet. $\frac{1}{3}$ rd. original.

Appendix IX.

Fig. 21. *Newcomen Engine at Caprington Colliery.*

Fig. 22. *Two views of the Piston for above Engine.*

Explanatory Diagrams.

Fig. 23.
"Pickle-pot."

Fig. 24. Sketch illustrating the Newcomen Engine before it was made automatic, 1712-1718.

Fig. 25. Illustration of the "Buoy" and the "Scrogan" in the Newcomen Engine. 97

Fig. 26.

Illustration of the "Cataract" substituted for the "Buoy" in Modern Engines.

Fig. 27. Pumping Engines.