to their places ; this is a very important precaution, as the flanches of the wheels are apt to catch the points of the plate rails, and thus to throw the engines and carriages off the line.

“A drawing and description of a new Lewis.” By Henry Robertson (Glasgow.)

New form
of Lewis.

The proposed Lewis consists of two pieces of iron, whereof each is a bent lever connected at a joint by a strong bolt. When the upper, or longer arms are drawn together, by the tension of the lifting chain, the under, or shorter arms, inserted into the hole, are forced against the sides, and by properly increasing the proportion of the upper to the under arm, any necessary power may be given to the instrument.

The advantages of this Lewis, as compared with those composed of three pieces, as usually constructed, are, that it can be inserted into and removed from the hole in less time ; it adapts itself to the form of the hole, all fitting and plugging with slips of iron being unnecessary ; and by exerting its pressure directly against the sides of the hole, it is less liable to chip off the edges and to endanger the falling of the stone.

“Experiments on the strength of various kinds of American Woods, exposed to a transverse strain.”* By Lieut. Denison, R.E., Assoc. Inst. C.E.

Strength
of Timber.

These experiments were principally undertaken, with the view of establishing some common standard of comparison between the woods in general use in America and in England. Some of the results corroborate, in a remarkable degree, the experiments made by Mr. Barlow upon wood of the same nature ; but of very different scantling, and under different circumstances.

The results are given in a series of tables, and the calculations are according to the formulæ given by Mr. Barlow.

March 7, 1837.

The PRESIDENT in the Chair.

“Account of a Machine for cleaning and deepening small rivers, in use on the Little Stour River, Kent.”† By W. B. Hays, Assoc. Inst. C. E.

* Vide Trans. Inst. C.E., vol. ii., page 15.

† Ibid. page 181.