NOTES ON ENGLISH CHEMICAL MANUFACTURES.

By S. CABOT, JR.

To give an account of the chemical advance, even during a few years, in a great country like England, is no easy task, if only in a sketchy and superficial manner. Nevertheless, having had very good opportunities of seeing some of the newest processes in use in England and Scotland, I propose to run through my note-books for the benefit of your readers, leaving out many particulars which would not be interesting to any but specialists, and many which are parallel to our American methods.

MANUFACTURE OF SULPHURIC ACID.

Sulphuric acid seems to be the starting point of almost all the larger chemical industries, therefore we will begin with that. The pure acid is made exclusively from sulphur. In the best chemical works (for instance, Mr. Riley's of Accrington, near Manchester), the sulphur is supplied through a hopper at the top of the furnace, the nitre and strong nitrous vitriol being also let into a cast-iron pan in the exit flue by means of another hopper.

The nitrous fumes are removed from the chamber gases, at the end of the set of chambers, by the use of a Gay-Lussac tower. Vastly the larger portion of the sulphuric acid made in England is, however, obtained by the combustion of pyrites. In addition to the much smaller first cost of sulphur thus obtained, it is in this case possible to use the Glover's towers, which cause a great saving in fuel. The principle of the Glover's tower is well known, but I will describe them as I saw several in England. They are towers made of acid-proof stone joined together by grooving the edge and then inserting a rubber rod; at the corners these rods are slit, and one is run through the other. The whole is bolted together outside with iron rods. These towers are from 30 to 40 or 50 feet high, and are filled with some acid-proof brick. At the top are two tanks, one containing chamber-acid, and the other nitrous vitriol from the Gay-Lussac tower. These acids are allowed to flow together down through the tower, while the hot sulphurous acid from the pyrites burners rises up in the opposite direction and carrying some water as steam, and much nitrous acid goes forward into the chambers. Many attempts have been made to use the Glover's tower where sulphur was burned. The reason of failure is that, as Professor Kopp once told the writer, sulphur can never be raised to the temperature obtained by burning pyrites, as it is volatile at a much lower temperature. The acid as it comes out of the towers is not far from 55° or 60° B $\acute{e}$, and may be concentrated in glass or platinum stills as is done in this country.

THE LEBLANC SODA PROCESS.

The greater part by far of this acid is, however, used for the decomposition of salt in the Leblanc soda process.

This decomposition of salt is done in hemispherical cast-iron pans, which are connected with absorbing towers constructed much like the Glover's towers, but filled with coke. These pans are separated by a sliding door with a muffle furnace, into which the mass is shoved while still quite liquid, and this muffle is connected with another condensing tower in which a less pure hydrochloric acid is obtained.

There is, however, a new method of accomplishing the decomposition of salt, patented by Hargreaves & Robinson. The process is, briefly, to pass a mixture of air, sulphurous acid, and steam, through salt in a porous condition, obtained by moistening it and then drying and breaking it up to the required size. This has the obvious advantage of doing away with the sulphuric acid chambers entirely.

The operation is performed in immense cast-iron chests heated on the outside with coal fires, and the gas from pyrites burners is put in at the bottom of one with an excess of air and some steam; it is then taken in at the top of a second one, and so on; this is, of course, changed about as one after the other of the chests is discharged.

The hydrochloric acid is very strong; indeed Mr. Hargreaves told me, in showing me the condensing apparatus, that in the first pipes it was stronger than by the ordinary method.

The sulphate of soda formed seems to be of good quality, and manufacturers are looking with much interest to see the result obtained by several large establishments running on this plan.

The salt in its porous condition is thought to act catalytically, causing the sulphurous acid (SO $_2$) and oxygen from the air to form (SO $_3$), which, however, would not occur without the presence of steam to form (H $_2$ SO $_4$) sulphuric acid, which in turn reacts on the salt to form (Na $_2$ SO $_4$) sulphate of soda and (2HCl) hydrochloric acid.

In the preceding paragraphs I disposed, rather summarily perhaps, of the various methods of manufacturing sulphate of soda and muriatic acid. I now propose to take up the various products of the latter acid and give a sketchy account of the methods in use in England for the manufacture of chlorine and chloride of lime.

CHLORINE BY WELDON'S PROCESS.

The two prominent, almost universal, methods of producing chlorine are by the Weldon and the Deacon processes. The Weldon process is properly only a method of regenerating the oxide of manganese from the chloride of manganese, formed by the action of the muriatic acid on natural binoxide of manganese.

By far the larger portion of the chlorine manufactured in England is produced under Weldon's patent, 101,600,000 kilograms, or over two hundred million pounds of chloride of lime, having been put on the market during the year 1874 to 1875 in England alone.

I had the good fortune to make the acquaintance of Mr. Weldon, and with him made an excursion of a day to some of the large works at St. Helen's, near Manchester, in one of which I saw his process in operation to great advantage.

The native binoxide of manganese is decomposed in large sandstone chests with muriatic acid; to assist the operation steam is introduced through a small (earthenware) pipe. The chloride of manganese is run into a large stone reservoir while still hot. Here it is treated with a sufficient quantity of finely powdered limestone to neutralize all excess of acid; this throws down any iron that is present as the carbonate of the peroxide. The clear liquor is then pumped up into tanks where it is mixed with an excess of hydrate of lime. It is then warmed to 55° or 75° Cent., and then a powerful blast of air is blown through pipes which open in fine jets at the bottom. The protoxide of manganese is hereby oxidized to the binoxide which unites with the lime to a feebly combined acid manganate of the composition, CaMnO $_3$ H $_2$ MnO $_3$, or Ca $\left\{ \begin{array}{l} \text{MnO}_3 \\ \text{H}_2 \end{array} \right\}$ (MnO $_3$) $_2$. This compound is a brownish black paste

which sinks to the bottom while a clear solution of calcic chloride remains above it. This calcic chloride is sometimes treated with sulphuric acid to obtain precipitated calcic sulphate (Paris white) for papermakers, etc. The sediment of bi-manganate of lime is run direct into the chests of sandstone in which it is treated with its equivalent quantity of muriatic acid. It is, however, in a state of exceedingly fine division, and therefore requires less heat to produce the reaction. The calcium of the compound (bi-manganate of lime) requires, however, two equivalents of muriatic acid, lost in the chloride of calcium, which is usually run away for the benefit of the fishes.

It is evident from examining the above formula that not only two equivalents of muriatic acid are lost on the calcium, but four more are lost on the chloride of manganese (afterwards changed to chloride of calcium by the addition of lime). In an attempt to avoid these losses Mr. Weldon has invented and patented another process, which I will only briefly notice, as it has not as yet proved a success in a commercial sense, I believe.

In place of lime in the regeneration of the chloride of manganese, he proposes magnesia (MgO). The solution of MgCl $_2$ (chloride of magnesium) with suspended bi-manganate of magnesia, is evaporated. As it approaches dryness muriatic acid is given off, which is condensed for further use; then a stream of air is let in and the mass is roasted in a muffle, whereupon the manganate of magnesia reacts on the chloride of magnesia and gives chlorine (mixed with air). After roasting with an excess of air, the mass becomes changed to manganate of magnesia. This is treated with aqueous muriatic acid, whereby chlorine and a mixture of chlorides of manganese and magnesia are produced, which latter mixture is treated as before. Theoretically this process is subject to no loss of chlorine, but there are many practically important obstacles to its success—the difficulty of evaporating chloride of magnesium without destroying the vessel containing it, etc. Both of Weldon's processes are at a glance nothing but indirect methods of decomposing hydrochloric acid by means of the oxygen of the air. We now come to a direct method of accomplishing the same result. This we see exemplified in Deacon's chlorine process.

DEACON'S CHLORINE PROCESS.

This process I had the good fortune to see in Deacon's own works. It depends upon the decomposition of hydrochloric acid at high temperatures by the oxygen of the air in the presence of a salt of copper. The gas from the converting furnaces mixed with air is passed through chambers heated outside to between 400° to 500° Cent., and filled with earthenware balls moistened with a solution of sulphate of copper. The mixture is decomposed according to the following reaction:

The mixture of nitrogen, chlorine, and steam, is cooled, whereby the steam is condensed, then washed with water to remove any excess of acid which has not been decomposed, and then passed into the lime-chambers, which must have a large surface on account of the dilution of the chlorine by nitrogen and air.

The great drawbacks to this process are, first, the quantity of hydrochloric acid (HCl) left undecomposed; second, the great dilution of the chlorine. The consequence is, that most large works—Deacon's own, for instance—use both the Weldon and the Deacon process. It appears to me that the two might be combined to advantage by passing the gas from the Deacon converter through a tower filled with native manganite in lumps, and regenerating the chloride of manganese formed by the action of the muriatic acid left undecomposed in the converters by the Weldon process.

There is one other process, in use at Tennant's works in Glasgow—in use at the time I was there, at least—wherein the manganese liquor was precipitated boiling hot, and under some pressure, with powdered limestone. The precipitated carbonate of manganese was then heated on trays in ovens with a supply of air which changed the manganous carbonate to manganic oxide, with the evolution of carbonic acid. This process, however, has not been introduced into the newer portion of Tennant's works, in which Weldon's process has been substituted.

At Tennant's, also, a part of the chlorine was produced by acting on a mixture of salt and nitrate of soda with sulphuric acid. The mixture of chlorine and nitrous acid was passed through strong sulphuric acid, which absorbed the nitrous gas, while the chlorine passed forward to the lime-chambers. The nitrous vitriol was used in the Gay-Lussac towers.—*American Chemist.*

MANUFACTURE OF ORCHIL EXTRACT AND PASTE.

ACCORDING to the process of Saroz and Chognard (French patent) the lichens are macerated for a quarter of an hour in water, to which a little hydrate of lime has been added, and are then heated in a closed vessel to 100° to 120° by the introduction of steam at a tension of several atmospheres. The duration of the heating as well as the temperature are modified according to the kind of lichens made use of. The purpose of this heating is the rapid and complete conversion of the lichen acids into orcein. The clear liquid is then separated from the undissolved woody matter by a filter, a hydro-extractor, or a press, and concentrated by evaporation. It is then mixed with ammonia, and put in a tightly-fitting vessel of iron or wood, into which oxygen is conducted. The formation of orcein is thus more rapid than on the common procedure, in which the extract is left to the action of the atmosphere. The oxygen prepared by the process of Tessié du Motay enters at the bottom of the vessel by means of a perforated tube: the portion not absorbed is conducted away by a second pipe passing through the lid, and may be reserved for a second operation. The evaporating ammonia escapes through the same pipe, and is absorbed in water with a view to its being re-utilized. When the oxidation is complete, and the liquid contains an excess of ammonia, it is driven off by exposure to the air or by a gentle heat. To prepare orchil paste, the above-described extract, after concentration and mixture with ammonia, is thickened with a quantity of extracted lichens, and treated with oxygen. The closed vessel is provided with a mechanical agitator. When the oxidation is complete the paste is allowed to stand for some days exposed to the air, with occasional agitation.

PHOSPHINE (PH $_3$).

THE only method of obtaining absolutely pure phosphine is by the decomposition of phosphonium iodide by water, which yields PH $_3$ and HI, but very pure phosphine may be obtained by the action of sodic ethylate on P in alcoholic solution. The evolution of gas commences on warming slightly, and will continue regular for some days. From a strong alcohol solution the excess of hydrogen rarely amounts to more than 1½ per cent.

Aqueous and alcoholic solutions of ammonia (nitride) produce, when digested with phosphorus, mere traces of phosphine, only either at the ordinary temperature or the boiling-point.

Clear phosphorus immersed in strong alcoholic ammonia and exposed to light (direct sunlight when that could be obtained) for a period of nearly six months, yielded only a very small amount of gas containing a trace of phosphine merely, a white crystalline deposit forming on the sides of the glass vessel in very small quantity. (It appears to be only white phosphorus.) Similar formation of crystals was noticed by Commaile.

A smaller amount of similar looking white crystals mixed with red phosphorus formed on the sides of a flask containing aqueous ammonia to which phosphorus had been added.

Glycerin does not prevent the formation of the spontaneously inflammable gas when added to the aqueous potash solution used for generating it; even strong glycerin with only 1 to 2 per cent water when treated with potash and phosphorus gives off the spontaneously igniting gas at the ordinary temperature slowly.—*Chemical News.*

PLASTIC SULPHUR.

It may perhaps be interesting to know that plastic sulphur may be formed at the ordinary temperature. When sulphuretted hydrogen is passed into water containing iodide in suspension, hydric iodide is formed and retained in solution, and a mass of sulphur is formed which may be drawn out into threads, and behaves in all respects like the plastic sulphur formed in the usual way by heat.

The whole of the sulphur is not in the plastic state, there being some ordinary precipitated sulphur intermixed.

The color is light red, due to iodine or probably a sulphur iodide.—*Chemical News.*

DETECTION AND DETERMINATION OF MAGENTA AND ARSENIC IN WINES ARTIFICIALLY COLORED.

By M. C. HUSSON.

THE author places a few drachms of the suspected wine in a phial, and adds a little ammonia, when the mixture turns a dirty green. He then steepes in the liquid a thread of white woollen yarn, withdraws it when saturated, places it vertically, and allows a drop of vinegar to flow along it. If the color of the wine is natural, as the drop advances the wool returns to its original whiteness, but if the wine has been sophisticated with magenta it is dyed of a rose, deeper or paler. He has also examined the physiological action of magenta free from arsenic, and finds that, though not a violent poison, it produces some morbid phenomena. In a state of chemical purity he considers that its use would not occasion any great inconvenience.

RHODEINE, A NEW REACTION OF ANILINE.

By M. E. JACQUEMIN.

THE author having mentioned that the hypochlorites of lime and soda cease to indicate the presence of aniline in solutions containing less than 1 centigram. in 500 c.c. of water, shows that if after adding the test solution of hypochlorite to these dilute solutions there be further added a few drops of dilute sulphide of ammonium (1 part to 30 of water) a splendid rose coloration appears. In this manner 1 part of aniline may be detected in 250,000 of water. He gives the name rhodeine to the coloring matter thus generated. No other oxidizing agent can be substituted for the hypochlorites, and no color is obtained if a sulphite or hyposulphite is used instead of a sulphide. Diphenylamin and toluydin similarly treated produce no such reaction.

ACTION OF SULPHUR UPON PARAFFINS.

By S. CABOT, JR.

HOPING to obtain a sulphur compound of the normal paraffins which might be decomposed with oxide of lead to an oxide, and perhaps be of use in the candle industry, I took for an experiment some pure heptan, C $_7$ H $_{16}$, prepared by Professor Schorlemmer, of Manchester, from petroleum. This was heated in a flask with a large excess of sulphur. The flask was connected with a return tube cooled with water to prevent the heptan from distilling off and being lost. After five or six hours' heating, this mass began to change in color, and volumes of sulphuretted hydrogen were given off. By continuing the heating the paraffin was almost entirely decomposed. The remainder was examined and proved to contain no organic sulphur compound. The smell was very offensive, but not more so than the combined perfume of H $_2$ S and heptan (petroleum spirit) would produce. The excess of C $_7$ H $_{16}$ was distilled off, and the solid residue was examined by dissolving the sulphur with bisulphide of carbon, which left a black powdery precipitate of carbon. Another portion was heated in a small retort until all the sulphur was distilled off; a black pulverulent residue of carbon was left.

From this experiment it is seen that sulphur at high temperatures decomposes heptan, forming H $_2$ S and carbon. This, I have no question, is the case with all the other members of the group, and I therefore shall not attempt the formation of a sulphur compound of the heavier and solid paraffins.—*American Chemist.*

COMBUSTION OF THE DIAMOND.

By R. BLINDOW.

THE diamond is placed on a piece of magnesium ribbon, and this on a small bit of clay, and then the whole introduced into a combustion tube. Oxygen is passed through the tube until all the air has been driven out, and that part of the tube at which the diamond is situated is heated. The magnesium takes fire, and the diamond itself also burns slowly. The vapors formed are conducted into lime-water.