the bridge, with the exception of the two rest piers for the draw, which are swung 14 degrees to the west, to bring them in line with the current of the river. Pier No. 1, the east abutment, was built by open cofferdam construction on rock at an elevation of 4.4 feet.

Excavation for piers Nos. 2, 3, and 4 was carried on by the open cofferdam construction, and in the case of pier No. 3 a depth of —32.0 feet was reached. From the bottom of the excavations piles were driven to solid rock. In the case of No. 2 pier, 294 piles were driven until their points were at a depth of —77.0 feet. Piers Nos. 3 and 4 each rest upon 390 piles driven until the points reached an average depth of —110.0 and —88.0 feet respectively. Piers Nos. 5 to 16 inclusive were built on pneumatic caissons at depths of from —22.3 to —87.6 feet.

Work was started upon the piers in the summer of 1904, but not much river work was done until the ice went out in 1905. The last masonry was laid on the fender pier December 16, 1905.

The fender at the draw is built of piles with a granite pier at the north end, and a timber crib filled with stone at the south end. The granite pier rests upon a caisson sunk to a depth of —44.8 feet, while the crib rests on the river bottom dredged to a depth of —30.5 feet.

Erection of the steel work was begun August 10, 1905, and finished May 22, 1906. The draw span was erected on falsework over the fender, and swung into position May 19, 1906.

Industrial Alcohol.

Dr. Wiley, of the United States Department of Agriculture, in his conclusions on industrial alcohol, points out that the manufacture of alcohol on a very small scale is not likely to prove profitable. Experience has shown that attempts to manufacture sugar and other substances of a similar character on a small scale cannot compete with similar manufacturing industries on a large scale. Furthermore, any still for the distillation of spirits must be registered and conducted under the supervision of the internal revenue officers; and though no regulations on the subject exist, the rules in regard to output practically result in fixing the minimum size of a registered still as one making from 7 to 10 proof gallons per day. It is thus seen that it will not be practicable for the farmer to operate a still on a small scale under present conditions. Moreover, the still can only be shut down by an internal revenue officer, and thus it would not be practicable to conduct a

abundant, technical methods of manufacture improved, and the method of utilizing the industrial alcohol better understood. Our people should not, however, be disappointed should many years elapse before the magnitude of the product used for industrial purposes reaches the figure already attained by Germany and some of the other European nations.

Of the raw materials which can be utilized for the manufacture of alcohol, Indian corn is by far the most abundant and the most promising source at the present time. The average price of potatoes must be very much decreased before raw material of this kind can come into competition with Indian corn as a

THE BOW OF THE "SUEVIC" ON THE WAYS

source of alcohol. Promising sources which are not now utilized for the manufacture of alcohol in this country are the potato, the sweet potato, the yam, sorghum, molasses from the sugar-cane and beet-sugar factories, and the Indian-corn stalk. Waste materials of other manufacturing industries, such as those related to fruits and vegetables, may incidentally be utilized for manufacturing purposes, but could not of themselves become independent sources of profitable industrial alcohol.

An Aeroplane Prize Offered by the Auto.

The offer by the SCIENTIFIC AMERICAN of an aeroplane trophy has caused much interest in Europe—so much that our esteemed Paris contemporary, Auto,

THE LAUNCH OF THE BOW OF THE "SUEVIC."

BY HAROLD J. SHEPSTONE.

A launch of unusual interest was that accomplished at the shipyards of Messrs. Harland & Wolff at Belfast, when the new fore end of the White Star liner "Suevic" took the water. It will be recalled that this steamer went on the Stag Rock at the Lizard on the Cornish coast on March 17 last. The Stag Rock is one of the most, if not the most dangerous place around the British Isles, and it was considered by the majority of experts that the vessel would be a total loss; but after a careful examination, the owners and builders, along with the Liverpool Salvage Association, came to the conclusion that the greater part of the vessel might be saved by cutting her in two.

This operation was successfully performed with dynamite and gelignite. The after portion was drawn clear of the rocks sixteen days after the wreck, the "Suevic's" own engines assisting the tug by working full speed astern. This after portion, containing the engines, boilers, etc., the most valuable part of the ship, was towed to Southampton, the engines assisting in the steering by means of the twin screws, and it is now at the Trafalgar graving dock at that port. The old bow was hopelessly lost on the rocks, and is to-day entirely submerged.

It was decided at the time of the wreck to build a new fore end and fit it to the saved portion of the wreck. This work was intrusted to her original builders, Messrs. Harland & Wolff. The new portion, with deck houses, captain's bridge, masts, etc., complete, extends from the stem to the bulkhead aft of No. 3 hold, i. e., the fourth bulkhead from the stem, and it has a total length of about 212

feet. It was virtually this half of a ship that was launched and towed to Southampton. It is to be placed in the same dock where the after portion now is, when the two will be connected together and the ship made as good as when she originally left the builder's. There have been cases where ships have been joined together in this way, though they have been much smaller boats than the "Suevic." The "Suevic" is a twin-screw steamer of 12,500 tons, and was one of the five vessels specially designed and built for the White Star Australian trade. She was originally launched on December 8, 1900.

Artificial Sapphires.

An analysis of a number of the imitation sapphires that have been flowing into this country from Paris

AFTER SECTION OF THE "SUEVIC," TO WHICH THE NEW BOW WILL JOIN.

THE NEW BOW OF THE "SUEVIC" TAKING THE WATER. THE BOW IS 212 FEET LONG.

small still in a desultory manner. The still must be constructed as prescribed by law and the process conducted in all its details according to the regulations of the internal revenue. It is evident that the farmer must be content with producing the raw materials and that he cannot look forward to becoming a practical distiller.

The benefits which are to accrue from the use of industrial alcohol free of tax have probably been overestimated by the people at large, and especially by the farmers, but that material benefits will accrue is not a subject of doubt. These benefits will come, not suddenly but slowly, as agricultural products are more

has followed the example and offers a cup for aeroplanes. The idea is a simultaneous race, and the machine which covers the longest distance to be declared the winner. All the flyers would be assembled at the start, and would commence the race at a given signal. Judges would observe the distances for the finish, and two chronometers would take the total time for each machine. There would also be a number of judges placed along the course so as to see the probable point from which the flight took place. It is probable that the leading aeroplanes will be entered in the event, and it will certainly be novel to see the flyers drawn up in line.

was made recently by Prof. Alfred J. Moses, of Columbia University. He states that artificial stones contain more than 99 per cent of oxide of aluminium; the remainder being silica and coloring matter. True sapphires are composed of 97 per cent oxide of aluminium, 2 per cent iron oxide, and the remainder silica, etc. Physical differences are also marked, the artificial stones having a hardness of 8 as against 9 of the natural. The density of the former is also low, 3.62, compared with 3.97 in the latter. In color both stones have practically the same basic blue, but the artificial gem does not exhibit the same high degree of dichroism shown by the natural product.