GRADUATES' ASSOCIATION.

DEEP WELL PUMPING MACHINERY.*

By MR. W. PERCY GAUVAIN, *Graduate, OF LONDON.*

Wells are, and have been for many centuries, an important means of water supply for large districts, and it may be interesting to go briefly through the methods which have been adopted for raising water from them. All the first methods employed were by winding, for although pumps were in use to a small extent, they were made of wood, and unable to hold water with a greater head than a few feet. Wooden winches were employed, the water being drawn up in small buckets. At present there are numbers of such wells scattered about the country, supplying hamlets or groups of houses situated at so great a distance from the nearest town that it would be impossible to connect them with the town supply. Windmills were largely employed in driving two and three-throw pumps, and are still used in certain districts and in country houses; but, as their action is uncertain, it is usual to adopt a small oil-engine, or some such motor, as a standby.

The earliest type of steam-engine that was successfully applied to raising water (other than the Newcomen) was the Cornish engine, which was first used to drain the tin mines in Cornwall. Engines used for deep well pumping may be divided into two classes:—

- (1) Rotative.
- (2) Non-Rotative.

the non-rotative class being subdivided into:—

- (2 a) Cornish.
- (2 b) Those other than Cornish.

* This Paper, read on 9th March 1903, has been selected by the Council for publication.

Rotative.—A large variety of different types of rotative engines have been used. A very common type is the overhead beam-engine. It is cumbersome, the first cost is heavy, and it is subject to the disadvantage open to all classes of rotative engines employed in deep well pumping, namely, that there is no distinct pause at the end of the stroke, which is so essential to the efficient and economical working of the pump-valves. Even though a large fly-wheel be employed, it is impossible to run such engines very slowly, such as can be done with the Cornish engine and the Davey engine described below. Gas- and oil-engines are usually employed to drive three-throw pumps. The speed has to be reduced, and the gearing involved not only reduces the mechanical efficiency, but makes the upkeep very heavy. Where small quantities of water have to be dealt with however, the upkeep is probably less than that of a steam plant, the reduction being in labour cost, rather than in fuel. Electric motors are also used to drive well pumps, and in this case also a certain amount of power is lost in gearing.

Cornish.—For those who are not conversant with this type of engine, it will be advisable to explain upon what principle it works. The engine has to lift the pump-rods (which are of timber, usually pitch-pine) and then let them fall by their own weight and force up the water. In the case of an engine forcing into the mains and having no pump-rods, a balance weight or weighted plunger is used. The mode of working is as follows:—Suppose the steam-piston to be at the top of its stroke. Steam is admitted at the top of the cylinder and the piston moves downwards, raising the pump-rods and drawing into the pump a charge of water. Steam is cut off at about one-quarter to one-third stroke, the piston continuing its stroke, partly by the expansive force of the steam and partly by the momentum of the pump-rods. At the end of the stroke, the equilibrium valve opens, allowing the steam, which was at the top of the piston, to come round underneath it, putting the piston in equilibrium. The pump-rods then fall by their own weight, forcing water up by means of the plunger. The pumps-rods should be at least 20 per cent. heavier than the water load, but in many

cases they far exceed this, the extra weight having to be counterbalanced by balance bobs. Before the end of the stroke is reached the equilibrium valve is closed, thereby cushioning steam in the top of the cylinder and bringing the rods gradually to rest. The exhaust- and steam-valves now open, the exhaust-valve remaining open nearly the whole of the stroke. The Cornish engine takes advantage of the momentum of the pump-rods to enable it to use steam expansively; in fact, the pump-rods are to it what a fly-wheel is to a rotative engine.

The energy stored up in the pump-rods is expressed by the formula $\frac{W V^2}{2 g}$, where W is the weight of the moving parts, V the velocity in feet per second, and $g = 32.2$. It will be seen, therefore, that the degree of expansion depends on (1) the weight of the moving parts, and (2) the velocity which they attain; and as the weight is constant for a given engine, any increase in the degree of expansion employed increases the value of V . For the purpose of expansive working the speed of a Cornish engine during the steam stroke (that is, when it is lifting the pump-rods) is about twice the speed of the water stroke; and for this reason the suction-pipes and valves should be large, generally two suction-valves and one delivery-valve being employed. The Cornish engine employed as a mining engine is usually more economical than when it is used for waterworks purposes, for the reason that as a mining engine the weight of the pump-rods usually far exceeds the water load, whilst the balance weight on a waterworks engine is very little in excess of the load on the plunger. There is a limit however to the number of expansions, for increasing the weight and the velocity of the moving parts puts greater stresses on the rods and connections, so that steam of a higher pressure than about 40 lbs. cannot be used effectively. The consumption of steam by a high-class Cornish engine is about 26 to 30 lbs. per I.H.P. hour, and the duty about 60 million foot-lbs.

Non-Rotative Engines other than Cornish.—Of non-rotative engines for deep-well pumping, probably the best known type is the Davey high-duty engine. The following is a description of such an

engine which was erected at the Hooton pumping station of the West Cheshire Waterworks in 1901, the author being present during the whole time of erection. Two boreholes were sunk 22 feet apart and to a depth of 450 and 500 feet respectively. For the first 200 feet they were 30 inches diameter, and from there onward 18 inches diameter, it being decided to place the pumps at a depth of 200 feet from the surface. The engine had to lift water from the boreholes into a sump in the bottom of the engine-house, from which sump the force-pump drew and forced the water into the mains against a head of about 400 feet. Running at 15 double-strokes per minute, equivalent to a piston speed of 150 feet, 2,160,000 gallons had to be pumped per 24 hours.

The engine, Fig. 1, Plate 39, is of the horizontal compound tandem type, having cylinders 30 inches and 56 inches diameter by 5 feet stroke, actuating a pair of single-acting borehole pumps and a double-acting force-pump. From the engine crosshead two timber rods go to the first pump quadrant, where they couple on at the bottom and from thence a single timber rod goes to the second pump quadrant. These rods are made of pitch-pine, and are strapped the whole length with mild steel plates. Timber is much better than steel for this purpose, there being no vibration such as would occur in steel rods of a great length. The piston-rod is continued through the low-pressure back cover, and is cottered on to the pump-rod of the force-pump. Both high- and low-pressure cylinders are steam-jacketed on the bodies and on the covers, the jacket space on the bodies being about 1 inch. The steam for supplying the steam-jackets is taken from the boiler side of the engine stop-valve, so that the engine can be thoroughly warmed up before starting. Jacket steam passes first round the high-pressure cylinder body, and from thence to the two high-pressure covers and to the receiver. The receiver is an enlarged steam-pipe in which is placed a copper coil, the effect of the jacket steam passing through this coil being to superheat slightly the steam on its way to the low-pressure cylinder. The jacket steam then passes round the low-pressure cylinder and the two covers. All cylinder jackets and covers are connected to steam traps.

In an engine of this type some special governing arrangement has to be adopted, otherwise it would be impossible to obtain a constant stroke; sometimes the pistons might be striking the cylinder covers and at other times the stroke might be several inches short, owing to a variety of circumstances, such as rise and fall of steam-pressure, pump-valves sticking, etc. It is of great importance that a full stroke should be made every time, for if the stroke is two or three inches short at each end, the clearance volume is thereby greatly increased. In small duplex pumps such as are used for boiler feeding, the bringing to rest of the piston at the end of the stroke is performed by means of a double steam-port which enables the piston to cushion steam. These pumps, however, have no pretence to economy, and, being of small size, would do little or no damage if the covers were struck occasionally; but in the case of a large engine a heavy bump might be a very serious matter. To overcome these difficulties the differential valve-gear was invented by Mr. Henry Davey.

At first sight the action of the gear may perhaps be a little difficult to follow. The following explanation should, however, make it clear. The gear is a small engine which is run at a definite speed, and which is used to open the valves of the main engine; the main engine itself closes its own valves. The motion given to the valves is thus a differential one, made up of a definite motion from the gear and a varying motion from the main engine, so that the engine automatically adjusts its own cut-off. For example, if the engine is very heavily loaded the gear will open the valves, and the engine will move off slowly and cut off late in the stroke; if, on the other hand, it is lightly loaded as soon as the gear starts opening the valves, the engine starts off and commences closing them, overtakes the gear and cuts off early. In the case of the engine racing, for example, if a pipe bursts and the load is suddenly thrown off, the engine starts off at a high velocity and overtakes the gear, so that the valves are closed soon after they commence to open.

The usual form of differential gear is that in which a steam cylinder, controlled by a cataract, works the engine-valves. In the case of the Hooton engine, however, the gear was worked by water-

pressure derived from the force-pump of the engine. This also has a great advantage, for in the case of the pressure falling by reason of a burst pipe, the gear ceases working. Both high and low-pressure cylinders have slide-valves, on the backs of which work Meyer expansion-plates. The cut-off can be adjusted whilst the engine is in motion, in the case of the high-pressure cylinder from 0.3 to 0.7, and in the low-pressure from 0.3 to 0.9. The main slide-valves receive their motion from the gear through a rocking-shaft, and the expansion-valves through a similar rocking-shaft worked from one of the pump quadrants. Both valves move in the same direction, and the faster the engine goes the earlier the expansion-valve cuts off. The gear consists of a subsidiary double-acting cylinder; the valve controlling admission of water to this cylinder is of special type, and is itself worked by a second and smaller cylinder known as the pausing cylinder. This cylinder, as its name implies, regulates the amount of pause the engine makes at the end of its stroke. The valve controlling admission of water to this cylinder is worked from the engine. By throttling the supply of water to this cylinder it can be arranged that its piston takes several seconds to complete its stroke, so that the valve which admits water to the subsidiary cylinder is not opened till two or three seconds after the engine has reached the end of its stroke. Consequently the engine pauses, as the main valves are not open. The amount of pause given to the engine can be regulated to a nicety by means of this cylinder. Allowing a pumping-engine to pause at the end of its stroke is very beneficial; it enables the valves to fall to their seats by their own weight instead of being forced down, the wear and tear on the beats being much less. This, of course, is impossible in a rotative engine, and the valves of pumps driven by that type of engine require renewing more frequently than in the non-rotative type.

In the high-pressure steam ports are placed two Corliss valves receiving their motion from the engine, the object of these valves being to close the port before the engine gets to the end of its stroke and thereby cushion steam. These are capable of adjustment whilst the engine is running, from three-quarters to nineteen-

twentieths of the stroke. The exhaust steam, after leaving the low-pressure cylinder, passes through a feed-water heater, through which water, on its way to the boiler, passes. The condenser is of an open type standing in the sump into which the borehole pumps deliver, and contains 530 square feet of cooling surface. There are two single-acting air-pumps driven from one of the pump quadrants.

Pumps.—The borehole pumps receive the engine motion by means of quadrants or compensating levers. The pump-rods not being of sufficient weight to allow of an early cut-off (as in the case of the Cornish engine), a compensating method was devised. The pumps are connected to the engine in such a way that, as the engine advances in its stroke, it gains a mechanical advantage over the pumps, or, in other words, the pump resistance gets less as it proceeds in its stroke; Fig. 2 illustrates this. Let A B C D be the pump

FIG. 2.

resistance and C E F G D the resultant engine diagram, then A D E C B is the pump resistance when the compensating levers are used, the momentum of the moving parts of the engine and pumps being sufficient to equate the two diagrams. By this means it is possible to cut off early in the stroke, and a great economy is thereby effected. In Fig. 3 (page 894) the author shows energy-diagrams of various classes of engines. The rectangle represents the pump resistance, whilst the curve is that of engine pressures. The percentage of excess work at the beginning of the stroke is given in each case.

The pumps are of the single-acting bucket type, the pump-rods working inside the raising main. The action is as follows:—On the

upstroke the bucket draws in a charge of water through the suction valve, at the same time delivering water over the top of the well; on the down, which is the idle stroke, the suction valve is closed, the bucket coming back to its position for the working stroke, water passing up through its valve. During the idle stroke it is possible to ascertain if the suction valve is holding water, and as the bucket has to be drawn before the suction valve can be got at, it (the

FIG. 3. *Energy-Diagrams.*

Non-Rotative Pumping Engines.

Variation per cent. from Actual Engines.

<i>Compound Forcing Engine.</i>	<i>Cornish Mining Engine.</i>	<i>Cornish Waterworks Engine.</i>
<i>Steam Pressure 70 lbs.</i>	<i>Steam Pressure 45 lbs.</i>	<i>Steam Pressure 32 lbs.</i>
<i>15.4 per cent.</i>	<i>26 per cent.</i>	<i>21.1 per cent.</i>

Cylinder Ratios 1 : 3.3.

No. of Expansions 5.

No. of Expansions 3.5.

Cut-off in H.P. Cylinder $\frac{1}{4}$.

Total number of Expansions 6.6.

bucket) can be examined at the same time. The rising main consists of a number of mild steel lap-welded pipes, 18 inches diameter and $\frac{3}{8}$ -inch thick, in 15 feet lengths, having wrought-iron flanges screwed on and riveted through. Fig. 4 shows a section of one of the pipes, and illustrates the methods of attaching the flanges and making the joints. The working barrel and clack piece, which are of cast-iron, are attached to the pipes by a screwed joint. A steam-winch is supplied, which makes the operation of lowering in the pumps quite a simple matter. The suction pipe is first put into the borehole, and clamps somewhat similar to those used by smiths are placed round it, supporting it at the borehole mouth. The working barrel and clack piece are next lifted up by the winch and screwed on to the

suction pipe. The winch then lifts the whole lot slightly, enabling the men to free the clamps. The working barrel clack piece and suction pipe are next lowered into the borehole and the clamps fixed near the top of the working barrel. Then another pipe is added, and so on. To the top pipe is screwed an iron casting which rests upon, and is bolted down to, a second casting firmly bedded in concrete. In this position the rising main and working barrel hang. The suction valve is then lowered down to its seat. The valve, Fig. 5, Plate 40, is of the double-beat type, having gutta-percha beats.

It will be noticed that a long weight is cotteder on to the valve-spindle. This is necessary in order to keep the valve from lifting

FIG. 4.

on the suction stroke. In some cases taper seatings have been used, but these are troublesome, as the valve seating gets firmly bedded in, and difficulty is experienced in drawing it. It will be observed that the ribs on the valve are cast at an angle. This is done so that the water impinges on them, and causes the valve to revolve and continually bed itself on to its beats.

The fishing tackle used for lowering in the suction valve is also shown in Fig. 5, Plate 40. It is of a very simple construction and most effective in "fishing" for the valve when it is required to put in new beats or for other causes. The valve spindle is made with a mushroom head under which the wings of the tackle grip. Fig. 6,

Plate 40 is a drawing of the bucket, which has a double-beat valve similar to the suction valve. The bucket packing consists of gutta-percha rings of stout section. Three or four small holes about $\frac{1}{4}$ inch diameter are drilled on the top of the bucket, so that the pressure of water gets to the back of the rings and makes a tight joint. The first rod is cottered on to the bucket spindle and is then lowered, the method adopted being the same as with the pipes, clamps being used. The rods are of steel 4 inches diameter and in 20-foot lengths. At the end of each rod a guide is cottered, which consists of a cast-steel wheel, Fig. 6, and is made about 1 inch less in diameter than the pipes. There is no thrust on the rods, all the work being done on the upstroke; on the downstroke the rods simply fall by their own weight, but in the case of the bucket sticking and the weight of the rods being insufficient to overcome the friction, the engine then having to help them, the guides would stay the rods very materially. The pump quadrants are connected to the pump crossheads by two steel connecting-rods. The pins on the quadrants to which these connecting-rods are attached are prolonged about 10 inches each side, and are made to act as bumpers. In the event of the engine overstepping its stroke, these pins come on to buffers and prevent the pistons striking the covers. The buffers consist of blocks of hard wood about 7 inches deep, lying on top of about 3 inches of indiarubber. There are similar buffers in the engine slide-bars for the slippers to bump against.

In starting this engine great difficulty was experienced, owing to the large amount of sand which found its way into the boreholes. Sand was pumped in such large quantities that it had to be ladled away as soon as it rose to the surface, and finally it was decided to stop, as the sump in which the borehole pumps delivered became so full of sand that nearly all the rows of condenser tubes were covered and the vacuum fell away. The rods and bucket of one borehole were drawn, and after some difficulty the suction-valve also, but when it came to drawing the suction-valve of the second borehole, it was found that the mushroom head was completely covered with sand by about 12 inches, the sand in the 200 feet of water having settled. The fishing tackle was tried several times but without

avail, and it looked very much as though the tubes would have to be drawn, when it was decided to try the effect of putting a small pipe down the tubes with water under pressure. A 1-inch wrought-iron pipe was connected to the mains under a pressure of about 150 feet, and then led down the tubes. It had the effect of stirring up the sand which gradually rose and flowed over the top with the water. After running several hours enough sand was cleared away to enable the fishing tackle to grip the mushroom head, and the suction-valve was drawn.

The valves of the force pump are of the same type as those described, the piston being 17 inches diameter and double acting.

By-passes are provided, making connections from above to below the delivery valves, and above to below the suction valves. By means of these by-passes the engine can be moved over, provided there is pressure on the main, the force-pump acting as a power cylinder. The engine can also be run with only one borehole pump in action, or the force pump single-acting, or any such combination, by the adjustment of the expansion plates, which is a very simple matter. This is extremely important, for in the case of a breakdown, one set of pumps can be run whilst the other is being repaired. This type of engine can be run dead slow, and the pause may be as long as ten to fifteen seconds; running at a slow speed the steam consumption is not much more than at the normal, for steam is not throttled, the piston speed during each stroke being the same.

Unfortunately the author is unable to give any results as to the steam consumption of this engine, as at the time of writing this Paper no trial had been carried out. A similar type of engine, but working with a steam pressure of only 70 lbs. per square inch, gave a duty of 124 millions on a ten to one evaporation, the steam consumption per I.H.P. being 15.6 lbs. and the mechanical efficiency 87 per cent.

Taking into consideration the fact that the steam pressure used was only 70 lbs. per square inch, the above result is extremely good. It will be noticed also that the mechanical efficiency is high. The Hooton engine may reasonably be expected to give an even better result, as the steam pressure in this case is 100 lbs. per square inch,

and various improvements, all tending to reduce steam consumption, have been added.

It would take too long to go into the various classes of pumps and pump valves used for deep wells, but the engine and pumps already described may be taken as an example of the best practice of the day.

The Paper is illustrated by Plates 39 and 40, and by 3 Figs. in the letterpress.

Fig. 1. *High-Duty Differential Pumping Engine (Davey), West Cheshire Water Works, Hooton.*

Fig. 5. Suction Valve and Fishing Tackle.

Fig. 6. Bucket and Guide.