DISCUSSION.

THE PRESIDENT:—The paper is now before the INSTITUTE for discussion.

DR. LOUIS BELL:—It strikes me that the most important proposition which Mr. Steinmetz has made is in calling attention to the facts regarding the imperfection of the ordinary sine wave computations in dealing with some phenomena which we encounter in those cases having combined capacity and inductance as in long lines. Again and again we find evidence in long line work of the existence of the higher harmonics. I think more and more in a practical way it is being forced on our attention that the variations from the sine waves make themselves felt in a very striking way. I firmly believe that by recognizing these variations in the treatment of the subject by complex quantities and bringing them into the summation so as to deal at least approximately with the conditions, thus bringing the analysis to bear on that one point, we shall be able to clear up a great many things now unexplained, and also very possibly to lick into shape the practice of dealing with currents containing harmonic factors so that we shall be able to understand more clearly what the conditions of minor resonance are and how to correct them. It is this phase of the matter which is most important. We are constantly running in practice against these variations from the sine wave.

PROF. THOMSON:—I think Dr. Bell has hit the nail on the head in regard to this paper. He has voiced my opinion in regard to it. We are constantly striking things which appear to us anomalies. We measure the capacity of a condenser by an alternating current, we find that the result is all wrong, we can't get any consistent results. And such things we are meeting constantly, and Mr. Steinmetz himself is constantly meeting them I know on a large scale. This work of Mr. Steinmetz gives us a method of getting at an understanding and predicting results where formerly we had to experiment and take our chances.

THE PRESIDENT:—The excellent paper before us marks an important step in the development of the vector analysis of alternating-current phenomena. Hitherto we have been compelled to limit the use of vectors to electromotive and magnetomotive forces, and their offspring currents and fluxes, and exclude activities. Mr. Steinmetz shows, however, that by adopting a separate vector plane for power we may also represent it by a vector having real and imaginary components corresponding to the real and wattless components. The advantages of this means of representing power are considerable, and we have only to take care not to confuse the plane of single frequency in which we draw our forces and currents, with the plane of double-frequency in which we draw our powers. The two planes must be kept

distinct in the mind and the algebraic laws they follow are also distinct.

PROF. W. E. GOLDSBOROUGH:—I should like to say a word as coming from our universities to express how much we are indebted to Mr. Steinmetz for giving us a method, differing from the older methods we have used, which enables us to place before our students in a much more simple form many of the problems in electrical engineering. It is rather startling to the student at first to find that complex quantities admit of so direct and simple an application, but he is always charmed with the result. I doubt if Mr. Steinmetz fully appreciates the effect of his work in modifying the curricula of our American schools of electrical engineering; and in connection with this paper as in connection with the other valuable papers which he has given us I am glad to express the sentiment of our gratitude to him.

PROF. C. A. ADAMS, JR.:—I wish to add one more word of gratitude for Mr. Steinmetz's valuable addition to his very valuable work along this line. I wish also to emphasize what Dr. Bell has said in regard to the practical importance of this subject of harmonics. Problems are continually arising in practice where they play a very active part, and this is not only true in long distance transmission lines, but also in the underground alternating current distribution in our large cities, particularly in Boston where the amount of such distribution is very considerable. Even in the case of the comparatively small fluctuations of the arc lighting current, there are strong indications of trouble from the same source.

MR. T. J. JOHNSTON:—I am not competent to criticize Mr. Steinmetz's paper, for like the famous Scotch joke, I have followed it with difficulty, but it seems to me that there is an error in the induction motor curves; taking Figs. 1, 2 and 3, the percentage of synchronism is given, for example, as one-tenth of one per cent., whereas it should be ten per cent.; in other words all of these figures are given one-one-hundredth of what they should be; I think Mr. Steinmetz will corroborate that.

Some time ago Mr. Steinmetz explained to me in a general way the fact that the general alternating wave contained only odd harmonics, that is, as generated by dynamo and motor. I do not know whether that is so in relation to all alternating current apparatus, for example, the transformal and induction regulator; that is, I do not know whether there are even frequencies introduced into the wave by apparatus other than rotating armatures. I would like to have Mr. Steinmetz say whether that is true or not.

THE PRESIDENT:—I would like to call attention to a point of terminology which may be important in the future and which ought to be cleared up. There is no doubt about the point in the paper, because the meaning is clearly defined. The term "torque" is used with a meaning which seems misleading, at

least to those who may not have the definition before them. It is stated to be the product of the E. M. F. into the quadrature component of secondary current. But this product is not a "torque" or "moment" but is a "power" or "activity," and it is defined as the power which the torque develops at synchronous speed. Now a torque cannot be both a torque and a power, because the one is a moment of a force about an axis and the other is a rate of working. Further on in the paper the "torque proper" is defined as this so-called synchronous torque divided by an angular velocity and by the number of poles. Surely it would be better to retain the term "torque" for this its usual meaning, and use some such term as "synchronous power" for the activity of the torque at synchronism.

MR. STEINMETZ:—Taking up the last question first, I appreciate that it is undesirable to denote by the same name two quantities of different dimensions. I was obliged, however, to introduce the definition of torque in synchronous watts as the only one suitable for general theoretical discussions, by its independence of individual conditions of the apparatus, as number of poles, frequency, etc.

In synchronous watts, torque has as definite a meaning as power in watts. To avoid the objection of the different dimension from torque as usually given in foot pounds, the value $T = e^2 a^1$, etc., may be divided by the frequency: $T_0 = \frac{e^2 a^1}{N}$ as indeed is implied by "synchronous" watts, or a new name may be invented for the quantity $T = e^2 a^1$ if anybody can suggest a suitable name.

The lettering on Figs. 1 and 2 is obviously a misprint which will be corrected, it should read "in fractions" and not "in per centages."

I would like to draw your attention to one curious and somewhat unexpected feature regarding the effect of higher harmonics of E. M. F. on the current input of the condenser.

The current input, and thus the apparent capacity of a condenser, when supplied by a wave of E. M. F., containing higher harmonics, is independent of the magnitude of the higher harmonics, provided that the resistance between generator and condenser is negligible, and depends upon the existence of these harmonics only. Thus a quintuple harmonic of 25% of the fundamental will send neither more nor less current into a condenser at the same effective terminal voltage than a quintuple harmonic of 5% or less, at negligible resistance.

The only effect of the magnitude of higher harmonics is that the resistance which is negligible with a higher harmonic of 25% of the fundamental, may not be negligible with a higher harmonic of 5%, or in other words the lower the amplitude of the higher harmonics the lesser resistance is sufficient to suppress their effect on the condenser.

DR. BELL:—In this matter of torque, I must beg of Mr. Stein-

metz out of kindness to the profession not to invent a new name. We have now not a deficit but a plethora of new names and I think that a little clearer explanation would avoid what I should style a real calamity.

In respect to this matter of harmonics, one quickly realizes that when it comes to a matter of resonance, when there is true resonance, mechanical or of any other sort the original amplitude of the wave of energy does not make very much difference. It is the resistance to the propagation of the vibrations, whatever they may be, that determines the magnitude of resonance. So while it seems queer that a small fifth harmonic should raise the very deuce with the capacity of a condenser, we should remember that this condition expresses a general physical fact not at all confined to electrical problems.

PROF. H. J. RYAN:—May I say in answer to the gentleman who spoke of the even harmonics that the positive and negative magnetic flux must always have the same value. The E. M. F. values will therefore be alike and such values can therefore always be made up of components and the fundamental and the odd numbers of harmonics. The even numbers would represent a state of affairs in which the flux positive and negative would not be the same.

PROF. E. THOMSON:—There is just one point about the production of the even harmonics. We could provide for them without doubt by making a single conductor travel in front of magnetic poles of different width, say the north poles of a certain width and the south a greater or less width, and a single conductor would thus operate to produce the ordinary wave containing even harmonics.

MR. T. J. JOHNSTON:—We may take a vibrating string in music and split the vibration so that there will be two nodes, making the string vibrate in three parts, giving the third harmonic. Take another string and split that into two parts, giving rise to the second harmonic or octave, and the vibrations may be so mingled as to sound in the same wave both the second and third harmonics.

What I want to know is, is there anything analogous to that in the alternating circuit; by which, for example, by power from the outside a second harmonic may be introduced into that circuit, so that a second and third harmonic will flow in the same wave?

DR. SAMUEL SHELDON:—In instrumental music the duration of the different tones is represented by notes of different lengths as eighths, sixteenths and halves. There is also the tempo mark, and yet if we take a classic and place it in the hands of an inexperienced performer, although the directions on the printed page are followed perfectly, the resulting music is in no wise of the same character as if played by an artist. The difference between the performances of the two, the artist and the unskilled

performer, is largely a question of allowance in time. There is a subdivision of the different time intervals far below the limits which are represented on the printed music. These subdivisions are readily detected by the ear. In the question of alternating currents of course any problem could be easily solved were it not for phase differences. If we knew the instantaneous values of current, E. M. F., torque, etc., in a number of small successive time intervals we could solve without the use of any complex quantities. However, the difference between the ordinary person and the artist I think is well represented here to-day and I would like to add my word in appreciation of the artist who has presented this paper to us and who seems to perceive these little time intervals by self-consciousness.

PROF. GOLDSBOROUGH:—There is one matter which, so far, I believe, has not been touched upon, which is the use of complex quantities in connection with the design of electrical machinery. If we have harmonics in our circuits they are usually developed in the station generator. We know that whenever we use an iron-clad armature we get harmonics. If we follow the type of the smooth core armature it is possible to produce what is practically a pure sine wave. Now, as every introduction of inductance into the circuit, whether it be from transformers or induction motors or even from changes in the flux densities used in the iron of the alternator, modifies the character of the wave, it also modifies the amplitudes of the harmonics which are component parts of the wave, and there is presented a series of mutually related phenomena the treatment of which is very difficult. I think, therefore, that this paper which Mr. Steinmetz has brought out, showing us how we can apply complex quantities to the analyzation of problems involving harmonics, is a contribution of great value. In other words, by being able to analyze our generators properly, in the process of design, and thereby pre-determining the exact character of their regulation, we will be better able to adapt them to the needs for which they are built, and cut off in the development of the machines the undesirable qualities which cause trouble.

[COMMUNICATED AFTER ADJOURNMENT BY DUGALD C. JACKSON.]

Mr. Steinmetz makes a very interesting expansion, in this paper of his "symbolic" method of representing alternating waves, and the paper is undoubtedly a valuable contribution to the literature of the subject. It is pleasing to find Mr. Steinmetz bringing his analysis into more rational paths, as his apparent disregard in the past, of the imaginary or wattless component of the power vector must have led many students to question the generality and truth of his methods.

Even now, Mr. Steinmetz uses in Part I of the paper, what appears to me an unnatural treatment of the power vector, and I