maps, and with a telephone, of which the wire wound around one of the two cables that attached the balloon to the windlass of the carriage.

The balloonists then let go the equatorial ropes and grasped the maneuvering ones, by means of which they hauled the balloon to the carriage to which it was attached. The engineer at once set the steam engine in motion, the windlass revolved, and the balloon ascended to a height of 80 meters, and was kept at that altitude.

The double door of the inclosure was opened. "Forward, march!" exclaimed Captain Aaron; and the carriage, drawn by six powerful horses, and containing three artillery chiefs, then started, preceded by a wagon provided with a strong pulley at its extremity. —*Le Monde Illustré*.

LACEY'S SEA ANCHOR AND OIL DISTRIBUTOR.

UNDER the provisions of the English Merchant Shipping (life saving appliances) Act, 1888, all vessels are required to carry sea anchors and oil distributors in their life boats. Messrs. Manwell & Glen, 8 Great Winchester Street, London, E. C., are introducing a combination sea anchor and oil distributor, invented by Mr. R. G. Lacey, which we illustrate below, Fig. 1 showing it as attached to the thwart, and Fig. 2 when opened. The apparatus consists of a square of stout rot-proof canvas, A, attached at the top to a stout spar, B, and weighted by a galvanized iron rod sewn into the canvas at F F. At C is a pocket containing a flat copper vessel, secured by a lacing up, D. This constitutes the

FIG. 1.—VIEW SHOWING METHOD OF ATTACHMENT TO THWART.

FIG. 2.—APPARATUS WHEN OPENED.

IMPROVED SEA ANCHOR AND OIL DISTRIBUTOR.

oil holder and distributor. At G G are screw plugs, which, when unscrewed, allow the oil to escape slowly, and as it flows out it is replaced by water entering a similar orifice at H. E E are eyes for stretching the anchor on the spar and for suspending the apparatus to the thwart, and K K are toggles for gathering up the canvas and bridles when the anchor is not being used. The spar, B, is proportioned so that it floats the entire anchor, including the copper vessel filled with oil or water and the iron rod which acts as a sinker.

In using the anchor the boat rope is taken through the thimble, L, in the upper bridle, and is then fastened to M in the lower bridle. By attaching another smaller line to the thimble, L, the anchor can be readily tripped at any time, it being only necessary to haul upon the smaller line and slack out the boat rope, and this feature of the invention is of considerable importance. —*Industries*.

FERROID, A NEW ARTIFICIAL STONE.

By HERMAN POOLE, Member of the Civil Engineers' Club of Cleveland.

FERROID, as its name suggests, is like iron—in color, expansion and many other properties—and contains proportions of that metal varying from 25 to 33 per cent. It is a compound, partly chemical and partly mechanical, of the elements of iron, sulphur and silicon, with more or less foreign matters; and from the union of these elements a material is obtained having

some properties of each of its constituents, besides others possessed by neither.

It is mainly a super-saturated solution of iron in the sulphur, with the silica acting as a binder and hardener. The form of the crystals is entirely different from that of sulphur or iron in any of their states, and the melting point is midway between that of its constituents.

Before mentioning any of the uses it may be well to give a succinct account of some of its physical and chemical properties, as by so doing a fuller comprehension of such uses and applications will be possible.

Color.—The usual color is that of a dark slate. This color is lighter on a fractured or coarsely tooled surface and much darker on a polished or varnished one. It then approaches black or plumbago color. Being thus of a dark color naturally, attempts to make light tints are futile, but many colors of a medium tint are possible, besides the darker ones. The pigments used must be of a kind not affected by the action of sulphur; of such nature are the earthy pigments which work well, although, being of weak tinctorial power, large proportions are needed.

Imitations of the color of various kinds of brick and sandstone have been successfully made, also the various mauves, dark drabs, slates, dark greens, etc. These tints and the natural one being of the neutral kind harmonize well in combinations and can be used to produce very pleasing effects.

Hardness.—The hardness is comparable with stone and brick, and is about that of ordinary bluestone. It is quite tough for the class of material, being capable of working under hammer and chisel, drill, or even

the strength of the common cements in use, as few of them ever equal the strength of the stones they are used to bind.

It shows no tendency to bend under pressure, and breaks with a columnar fracture.

Adhesion.—It is very adhesive to anything that presents points of contact and to many substances which are nearly smooth. It will adhere to glass and glazed surfaces while hot. The force of adhesion to brick, stone, wood or iron is that of several hundred pounds to the inch; to cast iron, the strongest of any.

This adhesion to cast iron is shown in the case of a conical cast iron plug being cemented with ferroid in a ring of cast iron. The thickness of the cement varied from one-half to one inch and the diameter of the plug was six inches. A force of 150,000 pounds was applied without starting it or even showing any signs of compression.

This adhesion is manifested also under transverse or shearing strains in brick and stone joints. In the case where ferroid was used as a cement for pavement blocks one of the stones was broken by a sledge hammer in futile attempts to drive it through.

In another instance, thirty-two ordinary bricks were cemented together side by side, and supporting the two end bricks on props, a weight of 150 pounds was held up at the middle. The whole was then supported while the end brick was cemented to a wall, and on taking away the supports the line not only remained unbroken, but the deviation from perpendicular to the wall was hardly appreciable.

Although ordinary liquids have no adhesion to a smooth ferroid surface, viscid, oily substances adhere well and can be spread smoothly. The surface thus becomes available for many applications needing oil paints, in fact, it forms one of the best surfaces for oil painting and many times has been used for such purposes—a fine, smooth painting being the result. In many of the uses in a large scale this property becomes convenient, as lettering or painting of more or less of the surface is often desirable, in some cases indispensable.

Porosity.—Having a solid, uniform, homogeneous texture, water or other liquids, and even air or gases, have no passage into or through it. The thickness of one sixteenth of an inch has repelled a pressure of twenty pounds of water. A polished surface presents a firm front like polished steel to all attempts of liquid penetration, and one on which they get no hold, and through which a pressure of 300 pounds to the inch has been unable to force them. This applies to steam pressure as well as air pressure, a force of 80 pounds steam with its accompanying temperature having been successfully sustained.

Weight.—The specific gravity is about 2.6, being thus one fourth as heavy as lead or one third as heavy as iron.

Ordinary sandstone will float on melted ferroid, although it becomes nearly submerged when all the air is expelled from its pores. The weight varies a little with change of composition, but it is safe to estimate 1 cubic foot as 170 pounds, 1 cubic inch as 0.1 pound, 1 flour barrel full as 600 pounds.

Action of Heat.—It is a very poor conductor of heat, the thickness of $\frac{1}{4}$ inch being sufficient to protect the hand from danger of burning from the melted ferroid, or even from a temperature of 400°. This property is also shown in the use of the material in taking casts from the moulds.

It melts at about 300°, and melts very slowly at first, requiring a low fire. This is owing to its low conducting power. When melting it is necessary to keep it well stirred, especially at first. Later on an occasional stir will suffice. At the first application of heat no softening occurs until the melting point is reached. Then it melts to a thin liquid, nearly as thin as water, and remains so if the heat is not increased. On increasing the heat a gradual thickening is noticed, until finally it becomes as thick as mortar, or even thicker, and can be stirred only with difficulty. If, now, it be allowed to cool, a gradual thinning occurs until the former watery consistency is attained. This it keeps until solidification.

While solidifying, the whole mass becomes a conglomeration of feathery, leaf-like crystals intricately woven together. This crystal structure is entirely different from the sulphur crystal, and undoubtedly is the cause of the high tensile strength. On cooling, a gradual contraction takes place, as with cast iron, until the whole mass is nearly solid. Then a slight expansion occurs, followed by a small contraction as it gets cold.

The expansion seems to be occasioned by the whole mass assuming the crystalline form, and the subsequent contraction is that due to the general law of expansion and contraction. The contraction after setting is about that of cast iron, slightly less.

Action of Electricity.—Being a non-conductor of heat, it would be supposed to act in a like manner toward electricity, and such is found to be the case. Tests made with bars of ferroid 14" long, $1\frac{1}{2}$ " wide and $\frac{3}{4}$ " thick showed a resistance of ∞ , ∞ and 125,000,000 ohms. This test was made after the bars had been soaked in water for 36 hours. These tests place it in the front rank among insulators, along with vulcanite, shellac, etc.; in fact, places it ahead of them.

Action of Air, etc.—Gases having no apparent adhesion to ferroid surface, if smooth, have no action on it, and pieces exposed to the action of the weather for several years have shown no diminution of polish. The effect of ordinary climatic changes is not to disintegrate it, as for this it is necessary for moisture and its winter form of frost to penetrate the mass. This it cannot do, and consequently has no effect beyond a blurring of the polish, which is readily removed with wiping. Rain striking it glances off as from an oiled surface. Usually, the capillary attraction of water in a vessel of ferroid is exerted in the negative direction, as with mercury in glass, the meniscus being reversed.

Mixtures.—Ferroid can be mixed with almost anything which is dry. Any of the earthy materials, sand, gravel, rubble, clay, lime, brick dust, dried earth, etc., work in well. Some of them seem to have no effect on the strength, unless used in very large proportions.

It is capable of uniting very large proportions of sand or gravel without sensible diminution of strength. The earthy or fine materials weaken it more.

Asphalt, tar, sulphur, and like materials can be in-

incorporated with it, some needing more care than others. The resulting mixture is between the elements in properties, and some of these mixtures are very valuable. With tallow and fatty matter no mixture can be had.

Applications.—As may be readily supposed from the above recital of the properties of ferroïd, the applications are numerous and valuable. A few only will be mentioned.

First. Let us consider it as a material capable of melting, and hence of being cast in a mould.

This is possible with almost any kind of a mould, moulds of glue, plaster, wood, stone, and metal having been used. Moulds of sand may be used, but it is not ordinarily desirable, as the surface is very rough, and owing to the tenacity with which the sand is held, it is very destructive to tools used in dressing.

Ferroïd is probably the only hard substance which can be melted and poured into a glue mould without spoiling it. This has been done repeatedly and with complicated forms. The action is peculiar. Of course, the glue melts with the heat of the ferroïd, but before this occurs a thin skin of solidified ferroïd has been formed on the surface of the mould, which, by its strength, prevents the liquid mass from breaking through, and by its low conduction prevents the glue from melting quickly. The glue is hence held in place and melts very slowly, and by the time the glue is melted soft, the ferroïd is set and hard enough to bear its whole weight and keep the glue in place. On cooling, the glue recasts itself on the ferroïd, and when quite cold it may be stripped off as good as new.

With plaster moulds and also with wooden ones care must be taken to avoid air bubbles, or blow holes, as these become magnified in the cast, owing to the expansion of the air under heat. This does not apply so forcibly to metal moulds, as they are generally comparatively smooth.

With all moulds except those which are highly polished the use of some greasy or waxy material is necessary, owing to the strong adhesiveness. Paraffine wax or heavy lubricating oil seems to answer the purpose best. Only enough need be used to prevent contact, as more would blur the impression. In some cases plumbago or facing may be used, either alone or supplementary to the wax or oil. Even with highly polished surfaces it is well to have a very thin film of oil, which is best obtained by lightly wiping over with an imperfectly oiled rag.

In making hollow casts some provision must be made to remove the core from contact with the solid ferroïd before the contraction sets in. In conical or conoid moulds this is easily effected by withdrawing the core slightly—an inch or so being sufficient. With other forms collapsible cores must be used.

When making casts it is usually advisable to heat the mass above the melting point, with brisk stirring. Then remove the vessel and let it gradually cool down till of the proper consistence for pouring.

It must be remembered that whatever form is made it can be used over and over again, as remelting does not deteriorate but rather improves it. All broken pieces are as good for remelting as new material.

Among small objects may be mentioned the numerous statuettes, vases, medallions, picture frames, etc., to be found in our drawing rooms, and *insulators* for telegraphic or other electric wires. These latter may be cast smooth or with thread, either inside or outside or both, and being hard cool, not acted on by the elements or chemicals and of high resistance, may be used to advantage in all places where an opaque insulator is admissible. One was tested in the office of the Western Union Telegraph Company, at New York City, by being placed in water, the inside being dry. A force of 10,000,000 ohms was needed to pass the current through the sides, which were $\frac{1}{8}$ " thick in thinnest part.

Mugs, Pitchers, Cocks, Tubes, etc., which are in constant use in chemical works, may be made of ferroïd and do good service.

Battery Tops for closed cells and the numerous other places where vulcanite or its equivalents are used can be supplied with ferroïd at a decided reduction in cost, but no reduction in insulation.

Among larger castings may be mentioned *pipes* for sewage or other purposes. It is eminently adapted for this use, requiring no skilled labor at the ordinarily difficult pieces and being capable of ornamentation in any way desired at no extra trouble in casting. As soon as the form is out of the mould it is ready for shipping and no delay in preparing, drying and firing is needed. The pipes are not porous and may be had polished if needed. They have no honeycomb structure and small bubbles due to defective moulds never extend into the body of the pipe. They can be cast in the ordinary or special shapes readily and are always of uniform strength.

Chimney Tops have been used in several instances and cost much less than any made from stone. They answer well and are very durable. The temperature at the top of an ordinary house chimney never reaches anything like the melting point of the ferroïd. They may be made of very artistic forms as readily as of simple ones.

For black boards a very decided advantage over slate is obtained in price. They always have grit enough and do not get gummy. They can be put up much thinner than slate ones. They wear as long as the school house.

Billiard Table Tops are cast with smooth top and bottom, and require no polishing. They resist the usage well and cost much less than slate.

Sanitary Appliances, such as water closets, urinals, basins, bath tubs and the like, have been made and possess many advantages. They are clean, almost self-purifying. They are not porous and furnish no foothold for disease germs. They are cheap.

Vats and Tubs.—Can be used for any purpose, water, chemicals or electro plating. They may be made with or without holes or taps and can be changed as desired, holes being easily stopped up or drilled out.

Architectural Forms.—Caps, cornices, sills, keystones, corners, bricks, whole arches, in fact, or columns may be made, either in moulds or *in situ* if needed.

Many other forms could be mentioned that will readily suggest themselves to a practical man.

Core makers, having intricate cores to make, have

occasionally availed themselves of ferroïd by making a model of the core in wax, wood or plaster and pouring ferroïd over it. A mould is thus made which will outlast many of the ordinary wooden ones.

Occasionally blow holes or sand holes are found in cast iron, and in some instances to save breaking the casting these holes were filled with ferroïd. In one instance, in a trip hammer block after being painted over, it not only did not show, but six months' wear did not loosen it.

Second. Having considered the applications depending on its melting, let us now consider some which come from its adhesive properties in addition.

In this connection attention is at once drawn to its immense advantages as a building material for concrete, etc., any kind of stone, any kind of gravel may be used and it will unite them so firmly that in many instances the stones themselves will break before leaving the cement. Of course, any application of concrete of any other kind can be filled by this with the proviso that the materials used and the surfaces applied be dry at the time of the applications. Once thoroughly united, no water or moisture will ever get in, and hence no crumbling from such cause.

A very large amount of filling in the shape of sand or broken stone and gravel may be used without weakening the mass, as it seems that only ferroïd enough to unite the stones firmly together is needed, no especially large body of cement being required.

Any desired form may be given the concrete by means of suitable moulds and it may be moulded into blocks or used as a continuous mass *in situ*.

Culverts and Bridge Foundations may be cited among the numerous applications of this concrete and the surface imparted to them may be rendered perfectly smooth, thus lessening the friction of the water, and in the case of culverts enabling a small cross section to be used. They are as strong and durable as stone, and have no attraction for moss germs or other vegetable growths, which have a tendency to choke up the openings.

Another form of concrete is that used in making floors for stables, breweries, chemical works or other places requiring a strong, hard, durable, impervious floor, not affected by heat or cold, rain or shine, steam, moisture or ordinary chemicals.

The same or analogous composition used for floors may be used as a facing for walls. There are many cases where a wall has been laid with ordinary mortar or cement, and the water on the outside persists in going in or the inside persists in going out through the wall. An application of ferroïd made plastic with a large quantity of sand will remedy this. If the surface of the wall can be made dry or approximately so the ferroïd will stick to it, and once on no further trouble will be had from water on either side. In this way leaky cisterns, vats, chimneys and other brick work may be rendered tight. It will stick to wood, but not as firmly as to brick or sandstone.

As a simple cement, it has been applied to joints of sewer pipe and some kinds of water pipe with success. In one instance, a line of water pipe had 300 pounds of water turned on in fifteen minutes from the time of pouring the joints and no leak discovered; of course with ordinary kind of ferroïd no calked joints can be made. With iron pipe uniform success has not been attained, but this will probably be had with a better understanding of the material, and how to use it.

It has been used as cement for bricks in many places. Its strong adhesion to this class of material was shown above. The outside course of ordinary chimneys has been laid with it, and in the case of that portion projecting above the roof very good results have been attained, especially in locations where strong winds tend to overturn them.

Allied to this class of structures may be mentioned towers of brick erected for chemical purposes, for which it is well adapted by its strength, absence of pores and resistance to chemical action.

Underground cisterns, vats, cellar walls, and the like, when laid with it have the advantage of its strength, and eminently its non-absorbing properties.

Several thousand yards of stone pavements have been laid using ferroïd as a cementing material, and after several years' use but slight wear can be noticed. Its high melting point added to its not softening under that temperature gives it a very decided advantage over other substances used for such purposes. It does not get brittle by cold. It is non-absorbent, germ destroying, clean and durable.

It requires a force of 400 pounds to the inch of surface contact to shear a stone out of its bed, and in many cases efforts to drive one out with a sledge hammer have resulted in fracturing the stone, but notwithstanding it. As it wears a little faster than the stone, a good foothold is always possible for the horses.

RESULTS OF TESTS MADE.

The majority of these tests were made at the testing department of Fairbanks & Co., New York City. Some of the others were made with Riehle & Co.'s machines.

No.	Composition.	Kind.	Pounds per in.
1.	Ferroïd.....	Compression.	9,073
2.	1 ferroïd, 3 sand.....	"	11,303
3.	1 ferroïd, 3 sand, 6 stone chips.....	" (sideways.)	3,756
4.	Ferroïd.....	Iron ring compression.	15,000
5.	Ferroïd.....	Tensile.	750-1,000
6.	1 ferroïd, 3 sand.....	"	850
7.	1 ferroïd, 1 asbestos.....	"	1,050
8.	Ferroïd.....	Transverse.	1,322
9.	Ferroïd.....	Adhesion to iron.	526
10.	Ferroïd.....	" stone.	431
11.	Ferroïd.....	" brick.	420
12.	Ferroïd.....	Pressure (steam).	75
13.	Exposed to action of gas in main.	No action on the ferroïd.	
14.	Boiled in dilute sulphuric acid.	No action.	
15.	Boiled in muriatic acid.	No action.	
16.	Boiled—mixture of soap suds, niter, and soda.	No action.	
17.	Electrical resistance		125,000,000 ohms.

—*Jour. of the Association of Engineering Societies.*

THE FOOD OF MAN IN RELATION TO HEALTH AND LONGEVITY, IN THE LIGHT OF COMPARATIVE DIETETICS.

By FRANK WOODBURY, M.D.

THE old puzzle, "Is it better for a man to have a dinner and no appetite, or an appetite and no dinner?" is still unsolved. In another shape it reappears in the familiar nursery question, "Is it better to be a beggar by day, and at night dream of being a king, or to be an actual king, and every night be pursued by dreams

of beggary?" In this case the verdict is usually rendered in favor of the enjoyment of the substance of royalty rather than dependence for happiness upon the shadowy stuff that dreams are made of. This problem, however, or one analogous to it, is actually presented by civilized man in comparison with uncivilized races, or the lower animals. The latter are blessed with appetite, good digestion, and an uncertain supply of food, while highly civilized man, with abundant food, eats with little appetite, and oftentimes lacks the digestive power to easily and comfortably dispose of the food with which the art of the cook has succeeded in seducing his palate. Where the greatest luxury prevails, the so-called culinary art reaches its highest development, and gastronomy becomes a science. Here also the question, "how to get an appetite for the dinner," often becomes more pressing than "how to obtain the means to satisfy hunger and support life."

Such conditions and customs are not favorable for determining what is the best diet of man. If we wish to ascertain his most natural food, we must go to communities in which greater simplicity of life prevails, and where occupations impose conditions less obnoxious to physiological laws than those pursued in large cities. Here we may find the finest developments of bone and brawn, and also discover how with simple food good digestion may wait on appetite and health on both.

Comparative dietetics, or that department of comparative physiology which considers the problems arising in connection with the food supply of the lower animals and their relations to those of man, has shed much light upon the physiology of digestion and nutrition, and can also render valuable aid in solving still unsettled questions. Comparative anatomy and comparative physiology have thrown side lights upon many obscure problems in human anatomy and physiology, which, without their assistance, would have remained unelucidated. In a similar manner, comparative dietetics may be made to contribute important information which will most materially advance human dietetics, and assist in selecting now articles of food and in defining more clearly the requirements of a suitable dietary for man.

In general terms it may be said that the presence of life is conditioned upon the exercise of the functions of absorption and assimilation of various food materials.

When a living organism is under normal conditions, these functions maintain its physical integrity, and enable it to go through its cycle of development in accordance with its physiological law. When they have finally discontinued their operations, the organism perishes.

By the presence or absence of these functions, therefore, we can easily distinguish between organic and inorganic substances, a distinction by the way which has been made since the earliest times. All living substances, during their period of existence, therefore demand regular supplies of food material in form and character suitable for absorption and assimilation.

Among the lowest forms of life, we observe the greatest simplicity in this respect. Indeed, the rule is that only one kind of food or pabulum will support the organism and permit its growth. Thus we have well known forms of micro-organisms that develop only in certain chemical solutions, such as the *micrococcus ureæ*, causing the ammoniacal fermentation of urine, the *micrococcus* of mucoid wine fermentation, the *micrococcus* causing phosphorescence in putrid meat and fish; the *bacterium lactis*, causing lactic acid fermentation in milk, and the *bacterium aceti*, associated with acetic acid fermentation. Advancing in the scale we find nearly every variety of vegetable product accompanied by a parasite to which it affords the appropriate food.

Even the higher animals in their natural state have a very limited variety of articles from which to select, and which affords them all the nourishment needed for their growth. In a state of domestication, the effects of different kinds and of greater variety of foods have been carefully studied both physiologically and economically, and biological science has been enriched by the results of innumerable investigations, since Boussingault first opened this important field of investigation. At the present time stock raisers know how to feed so as to produce fat, or on the other hand so as to increase muscle and bone. Special traits of form or color may thus be cultivated, and in fact, according to Darwin, all the existing varieties of domestic animals are the result of man's controlling agency, especially in the direction of methodical selection and feeding.

These facts are common knowledge, but they demonstrate the far-reaching and important relations of food, and are suggestive in regard to the diet of man.

One distinguishing feature by which the dietetic problem in man differs widely from that of the lower animals is the absence in the latter of the gastronomical element. The animal eats its appropriate food with relish, and as long as it thrives seeks no change from year to year and from generation to generation. Man, on the contrary, in his civilized state, demands an extended dietary, and tires of even the most wholesome and appetizing articles, even acquiring disgust for them, if too long continued. The anecdote of "*toujours perdrix*" is here very much to the point. We observe, however, that the animals nearest to man, living upon comparatively few articles of food, are very rarely troubled by anything like indigestion. It may be added that in drink they are still more restricted, and after weaning are limited to cold water. The contrast on the score of health between them and the lords of creation is not in favor of the latter. Possibly a hint may here be found which will suggest the cause of the difference.

Man in his uncivilized state resembles the lower animals in the poverty of his dietary and, under favorable conditions, in his physical health. Travelers who have visited tropical Africa state that the native tribes along the Congo exhibit some of the finest specimens of human development that they have ever seen. This may be partly due to the extinction of the unfit, which is a necessary result of their hand-to-hand conflict with nature, but it is also partly attributable to the simplicity of their diet, and also to their constant open air life and physical training.