Discussion.

Mr. Wolfe
Barry.

Mr. J. WOLFE BARRY, C.B., President, thought this was the first time a Paper had been read before the Institution on the application of electricity to such mechanical contrivances as lifts and cranes, and it appeared to mark an era of considerable interest. The application of hydraulic power to lifts and cranes had been so universal for so many years, and had been so extremely successful, that it would be very interesting to have some definite comparison both of first cost and of the cost of working between hydraulic and electrical gear. He was sure that to many members, who had to advise on the application of power to large enterprises, the matter dealt with in the Paper would be found of great interest. He might mention that only recently, in Paris, he had seen a hydraulic lift being taken out of an hotel and an electric lift substituted; and he was told it was by no means a solitary instance. He thought the members would find plenty of food for discussion in the Paper, and he would be only speaking their sentiments when he offered a hearty vote of thanks to the Author for having brought the subject before them in so able a manner.

Mr. Adamson.

Mr. DANIEL ADAMSON, of Hyde, remarked that for lifts, Messrs. Joseph Adamson and Company had been accustomed to use a shunt-wound motor with additional series coils, as mentioned by the Author; but it was found that when high speeds were required, the conditions of running the motor with additional series coils were such that a varying load gave a variation in the speed, which affected the momentum of the moving cage, so that when it was stopped it travelled further, against the resistance of the brake, sometimes than others, and missed the landing. He had overcome that difficulty by arranging the automatic switch to cut out the series coils after cutting out the resistance; thus the motor ran at a fairly constant speed after starting. With regard to travelling cranes, the three-motor type had been preferred, the series motor being always used, on account of its greater starting-power, and also its characteristic—which was an advantage in that case—of running faster under lighter loads. It also enabled the change of gear, for giving a higher speed with lighter loads, to be dispensed with. In connection with the lifts, the arrange-

ment they had used for cutting out the resistance was to connect Mr Adamson. the sliding-switch with some moving portion of the mechanism, so that as the motor started it gradually cut out the resistance. This was found to work well, and was much simpler than either of the arrangements mentioned in the Paper. As to choice between single and separate motor-cranes, his opinion was, he thought, confirmed by practice in the United States, where greater attention appeared to be paid to the matter than in England. On the occasion of his last visit, he noticed that Messrs. Sellers of Philadelphia, who had first advocated the one-motor crane, had begun to make cranes of the three-motor type. He did not hear of any makers of three-motor cranes commencing to make a single-motor crane. The principal reason for preferring the three-motor crane was the reduced wear and tear on the mechanical portion, owing to the fact that, even when the crane was nominally in use, there was a considerable amount of idle time, as, for instance, when adjusting the chains. During those intervals, when the crane was not actually hoisting or travelling, with the three-motor crane the mechanism was at a stand-still; whereas in the single-motor crane, or in any other type of power-driven crane, some portion of the mechanism was running, and there was thus wear and tear, varying with the type of crane. The maintenance of clutches and such arrangements for mechanically controlling power was very costly. He called to mind an example of a steam-driven crane, in a girder-yard in which the square cross-shaft was used to transmit some of the motions, which lasted 11 weeks, so that four were required in the year. Another advantage of the three-motor crane was that, each motor being fitted with starting resistance, the man working it was able to start very gradually; and, in case he wanted to travel only a small distance, that was a great advantage; with other kinds of power-driven cranes it was much more difficult to travel a short distance and stop again with precision. Cases also arose in which the motion was required to run slowly for a short time, as when drawing patterns. That was not so easily effected with a clutch or strap-driven crane. The switches of their first three-motor crane had lasted just two years, at the end of which time they were taken down to be refaced and replaced. Progress had since been made, and no doubt the switches now made embodied considerable improvements, but how much was a matter for time to prove. The only results given by the Author had reference to tests of a crane of an unusual type. He noticed that the efficiency came out quite as high as in some of the tests he had made 12 months ago, with five over-

Mr. Adamson. head travellers. In those cranes the speed-reduction between the motor and the hoisting barrel was effected by means of three sets of spur-gear, two of those sets having machine-cut teeth; whereas in the arrangement shown in the Paper, Figs. 6, Plate 1, the motion was transmitted through a worm-wheel, a bevil gear, and two sets of spur-gear. This should not be such an efficient arrangement as the three sets of spur-gear mentioned; yet the efficiency appeared as high as he had obtained. His tests, however, had been made when the cranes were comparatively new, and possibly better results could be obtained now. Still, his experience, judging from other tests he had seen, was that the efficiencies stated were high. He would ask the Author to give details as to the method of taking the measurements, and also as to the care taken to see that the instruments were accurate.

Mr. Ellington. Mr. E. B. ELLINGTON thought that, notwithstanding the progress of the past 15 or 16 years, in its application to hoisting, electricity was, as he had pointed out in 1881,¹ subject to the same defects as steam, gas, and compressed air.

FIG. 9.
DIAGRAM OF THE
DIRECT-ACTING
LIFT.

When electricity or any of the other powers were applied to lifting, dependence had to be placed, first upon the brake, secondly on gearing, and thirdly on various controlling mechanisms. All those things were avoided by the use of hydraulic power. A simple valve sufficed to control all the motions; no brake was required, and practically no gear. A diagrammatic illustration of a complete hydraulic lift, the ram, the cylinder, and the supply-pipe, was given in Fig. 9. The whole machine might be said to be a modification of the supply-pipe. That apparatus, with the addition of a simple valve, controlled in the ordinary way, formed as perfect a type of lifting machine as it was possible to conceive. The only objection the Author had stated to the use of the hydraulic lift was that it was not economical. That type of lift, Fig. 9, was necessarily an uneconomical machine. Not only did it require the same power for a light load as for a heavy load, but, from the nature of the case, the useful load was only a small proportion of the total load. That was the perfect type of lift from the mechanical point of view, apart from economy. The

¹ Proceedings of the Institution of Mechanical Engineers, 1882, p. 122.

next step was the introduction of multiplying gear. *Fig. 10* Mr. Ellington. showed the ram and the cylinder, and, with the addition of the cage, a suspended lift, in which the chains or ropes were introduced. In that machine, the ideal simplicity of the first type was departed from and its relative economy increased. The economy of that second type of lift was limited by the fact that it required the same power to raise a light load as it did to raise a full load. To that extent he agreed with the Author. From the earliest times, nearly 50 years ago, when introduced by Lord Armstrong, it was seen, however, that greater economy might in many cases be advantageously obtained by dividing the rams into two, three, or more, by suitable mechanism. In the two machines he had described there was a condition of things which was *sui generis*—altogether different from the application of any other power to lifting. But it was not necessary to use those types of lifts when employing hydraulic power. A hydraulic engine could be used and fitted with the Hastie gear which automatically adjusted the throw of the crank when there was almost perfect adjustment of the hydraulic power used to the load. But, although a greater economy was secured, a more or less complicated mechanism was introduced. No brake or other controlling details had been introduced, but the machine had been complicated. But it was not necessary to use a hydraulic engine at all; in a properly adjusted turbine perfect control was secured, as well as economy resulting from the adjustment of the power used to the load lifted, but the troublesome and often dangerous details necessary when using steam, gas and electricity, such as had been depicted in the Paper, had to be resorted to. There was no controlling power apart from the brake. Owing to their great simplicity a large number of the first type of lifts he had described, *Fig. 9*, were in use. They, no doubt, would continue to be employed where practicable for all lifts of only 10 feet to 20 feet, notwithstanding their relative large consumption of power. He now wished to consider in more detail the question of economy. In the

Fig. 10.

DIAGRAM OF THE SUSPENDED LIFT.

Mr. Ellington. Paper to which he had alluded, particulars would be found of a trial of a lift which was commensurable with the Otis electric lift. The load lifted in that case was 886 lbs., with 790 lbs. pressure on the square inch. The multiplying power was 10 to 1, the height of the lift being 71 feet 8 inches, so that it was not so economical as it would be if it had been made for a height of 36 feet as given in the Table. The quantity of water used would be 6 gallons for the 72 feet, and 3 gallons for the 36 feet. Using for the purpose of discussion electric units, units of energy, it would be found that the cost of 3 gallons at 4*d.* per unit, the standard taken by the Author, worked out at 0·078*d.* for each double journey. This cost was lower than the lowest cost of the electric lift, even when there was no work being done by the lift up or down; the figures were 0·082*d.* as against 0·078*d.*, notwithstanding the fact that there was an increased load in the hydraulic lift of over 2 cwt. If the load were reduced to the 648 lbs. mentioned in the Table, by reducing the area of the rams by the amount required, with an efficiency of 100 per cent. for the additional 2 cwt., the quantity would be $2\frac{3}{4}$ gallons, and the cost would be 0·071*d.* As a rule, lifts were not worked with a full load or the full height. If they ascended with a full load, they did not descend full, but generally with only the attendant. Therefore a proper comparison was to take the lift, worked at half-load up, and down with the attendant two-thirds of the height. Under those circumstances, using the Author's Table, he found that the cost would be 0·072*d.* in the case of the electric lift; and that the cost of the hydraulic lift, the particulars of which he had given, was 0·048*d.*, or 18 watt-hours, and 12 watt-hours respectively, a difference of 50 per cent. It was true that a simple hydraulic lift took exactly the same power at all loads, but it took with a full load less than the electric lift with the lightest load, according to the Table. There was nothing in the question of economy, because the hydraulic machine was so extraordinarily economical at full load that the work could not be done more cheaply at any load. So economical an electrical machine was not available, even with the advantage due to the fact that there was no variation of power according to the load in the hydraulic lift. If mechanism was introduced which would reduce the work done in proportion to the load, there would be still further economy in the use of hydraulic power. With regard to the cut-out resistances, he might mention that a year or two ago he had examined some electric lifts in Berlin, where there were a great many at work on the electric mains, and he was much struck

by the peculiar action, which at first he could not account for. Mr. Ellington. For instance, a lift hoisting about 10 cwt. worked well with a load of three persons under the action of the pulling of the rope by the attendant; but with full load it was several seconds after the rope was put into the position for lifting before the lift moved. That was very dangerous, and he hoped that the matter would be fully explained. As far as he could see from the Paper, that difficulty existed in the machines described, viz., that the current could not be applied directly, but time must be given. There was an automatic cut-out arrangement, which took a certain time while the current was being switched on, and that was liable to lead to accidents. When passengers entered a machine, expecting it to move on and it did not, the first thing they did was to try and get out. At the Allgemeine Elektrizität Gesellschaft's works also, where everything was done by electricity, and three-phase motors were used, he was shown the traveller going about 120 feet, lifting four or five times. He was asked to work it, that he might see how easily it was manipulated. He started to work it as he would any other crane or any hydraulic crane, but the machine broke down and failed to move. He was informed that he must apply the current much more quietly, and had to wait 5 minutes before it was put to rights again, and the same difficulty of control was experienced. He thought the proper application of electricity to the purposes of lifting was indicated by what he had said as to the necessity of complication when endeavouring to realize high economy. There were many cases in which hydraulic power was supplied by hydraulic engines. When a hydraulic engine or a turbine was used, it was a fair question whether electricity or hydraulic power was the better. He thought there was confusion in the Paper as to the terms "travelling crane," and "traveller." He understood by a "traveller" what the Author had described as a "travelling crane," moving a long distance. For "travellers" he believed electricity was the proper power to use. In timber-yards he thought it was the best kind of apparatus that could be used. The fact was that electricity was splendid for traction, but where energy was required for lifting only, hydraulic power was better.

Mr. F. S. COURTNEY thought that for a lift of short stroke, Mr. Courtney. where hydraulic power was available, it should be used; but for a long stroke electric power had advantages. In the starting of an electric lift there was a large increase of current beyond that necessary when once the lift was running, and this became a con-

Mr. Courtney, siderable factor in short journeys. In Appendix I, taking the tests of this electric lift as representative of any other electric lift under similar conditions, he found that with full load the starting current was 13 amperes, while the running current was $11\frac{1}{2}$ amperes; with a light load the starting current was 11 amperes, and the running current 7 amperes. With so short a stroke as only $26\frac{1}{2}$ feet, the larger current at starting told materially on the mean current used for the complete journey, whereas with a longer stroke the percentage of increase due to starting was materially diminished. With the electric lift there was the advantage that the amount of current varied in proportion to the work to be done, and this, with varying loads, was a strong point in favour of electric power. There were differential hydraulic lifts, which gave greater economy in water-consumption than the single-acting lift; but they began to lose somewhat in efficiency, and they also required more attention. The question then arose whether the attention necessary for a differential hydraulic lift was materially less than that in an electric lift; he did not consider that this was so. The electric lift certainly could be made to work under perfect control. With shunt-wound motors, with a series starting-coil, they started smoothly, and they could be regulated to stop at the landing-stages without jerks, so that in that respect they could compare with the best hydraulic lifts. There was in the electric lift a high-speed dynamo, and care was necessary in the reduction of the gearing to render it sufficiently noiseless to be placed in positions where it had frequently to be placed, such as in the centre of a staircase and the like. With ordinary gearing it was difficult to do away with the noise, but with worm-gearing this might be done effectively. He did not agree with the Author that it was difficult to have worm-gear running without vibration, as there were lifts with worm-gear which were running without any vibration in the cages, and working quite smoothly. The question of ball-bearings had been alluded to by the Author for small lifts; where the load on them was light a very high efficiency could be derived from them. But there was very much greater difficulty in getting the balls evenly tempered and absolutely to gauge, than there was in making a true running path. He would venture to sacrifice the little difference of efficiency that there might be between a good thrust-bearing and a ball-bearing for larger lifts, in order to get the greater simplicity in the thrust-bearing. Their extreme adaptability to standardizing also commended electric lifts from a manufacturer's point of view. The length of stroke did not enter

into the element, so far as driving gear was concerned. The motor Mr. Courtney. had simply to be run so much longer, and the increased length of stroke was obtained; whereas with the hydraulic lift it became necessary either to increase the length of stroke of the ram or increase the number of multiplying sheaves. It was essential in an electric lift that the controlling arrangements should be precise, and it should be possible to stop the lift absolutely at its proper level; because if they did not, and stopped a little short of the landing-stage and had to start again, that excess of current, which was unavoidable at each time of starting, recurred. Those were points which only had to be realized to be mastered, and in practice there was little difficulty in controlling the lift so that it could stop precisely where required. With regard to the electric crane described in the Paper, that was an adjunct to an existing crane, and therefore there was more gearing about it than would have been the case had it been a complete design, and its efficiency was to a certain extent sacrificed. In his own works there were two electric cranes, one of 15 tons, and another of 20 tons, which had been running regularly 9 years and 8 years, and worked without the slightest trouble either in the electrical or mechanical parts.

Mr. T. D. HOLLICK observed that the gear for which he was Mr. Hollick. responsible, a view of which the Author had thrown upon the screen, gave, when used on electric cranes, much higher results than those of the crane described in the Paper. The crane which had been exhibited had an efficiency of 74 per cent., as compared with 53 per cent. It was tested under ordinary conditions; the weight of the hook had not been subtracted and there was about 150 feet of wiring. Those results had been obtained, not by increasing the electrical efficiency of the motor, but by increasing the efficiency of the gearing—the mechanical arrangement between the motor and the load. With regard to lifts, the Author's tests showed an efficiency of about 20 per cent. or 25 per cent., and that the cost per ton raised 36·5 feet was 1·015*d.*, the price of the current being 4*d.* per unit. That was a high cost per ton, but he would expect to find a high price when the efficiency of the lift was considered. In the case of the lift the losses probably took place between the motor and the load. With regard to the efficiencies of the cranes, the crane described in the Paper lifted 20 tons 15 feet per minute, whereas the crane which had an efficiency of 74 per cent. lifted 6 tons 15 feet per minute. The motors in each case ran at about the same speed, and the load was raised at about the same speed; therefore there was the same reduction of speed

Mr. Hollick. between the motors and the load. He thought the Author would have secured a higher efficiency had he used his arrangement in that position. The current capable of raising 6 tons 15 feet per minute was about 31 amperes; there was no rush of current at starting, as had been mentioned by some of the speakers. The variation during the run was about 2 amperes, probably due to inequalities in the gearing, the spur-gearing, the rope or barrel, but there was not a large jump at starting. The recording ampere-meter was checked with an ordinary meter, and the results gave about 74 per cent. efficiency. He did not agree that electric cranes were inferior to hydraulic cranes, on the three grounds of efficiency, simplicity, and finality. In the matter of efficiency, the hydraulic cranes and lifts had about the same efficiency as those mentioned by the Author, which would be about 50 per cent. With regard to the 74 per cent. efficiency, that, he thought, was a fair average test, though higher efficiencies had been obtained. It was taken in the ordinary way of work and exceeded that of the hydraulic cranes. The question of simplicity, however, was more difficult to deal with; it appeared to be more a matter of opinion. If there were switches with resistance and such complications, it followed that the apparatus appeared complex. But he thought that if a shunt-wound motor, with a simple mechanical gear like that which he had arranged, were compared with an ordinary hydraulic arrangement, say with a series of cylinders in order to increase the efficiency at the smaller load, it would be found that the simplicity was in favour of the electric gear. It should be remembered that in all those matters people had become used to hydraulic cranes; they had been in use for perhaps 40 years, while, on the other hand, electric cranes were new. He already knew many instances in which employers had become used to the electric cranes. The cases in which they had not become used to them were generally those in which the cranes were not applied properly, or the switching arrangements were complex. In the crane he had referred to, the switching arrangement was most simple. Anyone could switch it on, and it was impossible to fail. In regard to finality, he did not think there was such a thing, especially in the case of machines having an efficiency of only 50 per cent.

Mr. Walker. Mr. F. W. WALKER thought the simplicity of hydraulic machinery was even greater than had been pointed out by Mr. Ellington; and he did not think the direct-acting hydraulic hoist would be more wasteful than an electric one. It was assumed by Mr. Ellington that the direct-acting hydraulic hoist would only

be a ram and table or cage—the ram working in a cylinder; Mr. Walker. therefore the ram would have to lift the moving parts before it lifted the load. If the electric hoist was allowed a wire-rope or chain, he wished to know why a hydraulic hoist might not be allowed the same privilege. He submitted that if the hydraulic hoist with a direct-acting ram had wire-ropes from the top of the cage, or from the corners of the cage, connected with balance-weights, such a direct-acting hoist could be made to work more economically than an electric hoist. His firm were in the habit of making coal-tips, where 20-ton wagons were continually lifted, not with the expense of water necessary to lift a 20-ton coal wagon, in addition to the weight of the moving parts; but the moving parts, either by hydraulic cylinders in constant communication with the accumulator, or by balance-weights in connection with wire-ropes or chains, were balanced within about 2 tons of the total load to be lifted; therefore the hydraulic power only had to lift the actual coal, the wagons being a constant quantity. It was not fair to compare the two things, unless on parallel lines, and he submitted that if the hydraulic hoist was allowed to have a wire-rope, and then to add its own power in its own way, it was simply a plain cylinder and a ram, which was not only worked much more safely and simply, but more economically than any power which could be applied to it by an electric motor. The jiggers referred to by Mr. Ellington consisted of a cylinder which did not require attention, a ram and a gland. In addition there were two pins, one at the top and the other at the bottom, with a number of sheaves working on them. In machinery of that kind, the smallness of the number of working parts was of immense value, not only because it made the machine work better, but also because it made it easier to keep in repair. The fact that it could be controlled and worked by much cheaper labour was an additional advantage of hydraulic machinery. He thought results as to the question of relative economy would be of great value, because economy, first in capital outlay, secondly in maintenance, and thirdly in working, was of primary importance. He hoped that some manufacturer of electrical plant would give the Institution the benefit of his experience and state not in electrical terms, but in plain old-fashioned horse-power or foot-pounds, how much it cost to generate the power, and how much was lost when it was used. In dealing with such a question, which was influencing large dock- and railway-companies in the consideration of the machinery they were to employ, that subject should be settled

Mr. Walker. once and for all. How much did the power cost to produce, and how much was produced and then wasted? He thought it would be generally admitted that if electrical power was to be utilized in large installations such as docks and railways, it must be used in some way by which it could be stored. He thought it would be impossible to drive direct the machinery at the Bute or the Barry Docks, or at the North Western, or the Midland, or any other large railway company's works. In one dock at one minute there would be twenty coal-tips working as hard as they could, and the next minute perhaps, when the dinner-signal was given, hundreds of horse-power suddenly disappeared. He should like to know what an electrical engine would do with this power? A hydraulic engine put it into the accumulator and used it after dinner. He did not know what an electric engine would do with it; was it to stop instantaneously? Was the man always there ready to stop it, and what was going to happen if some industrious tipper went on working and still required power to work the machinery? That was the great problem which should be dealt with clearly and distinctly. With regard to accumulators, he did not think that the value of the hydraulic accumulator, indeed, its absolute necessity on a dock, was generally understood. In some docks there might be pumping-engines with 1,000 HP. continually at work; but in addition to that there would be hydraulic accumulators in all parts of the dock, storing many thousands of HP. which, when twenty coal-tips and fifty capstans and thirty cranes and the dock-gate machinery all required to be moved at the same time, would be supplied by those accumulators. He wished to know whether there was any arrangement by which electrical machinery could accomplish the same results. As to the general working, he should like to ask if it did not require much more skilful labour to keep it in order, and if it did not cost very much more, also if the difficulty of working it either slowly or quickly at pleasure was not much greater? Could an electric crane be worked when picking up the loads slowly, and when it had felt the load let it shoot up at 300 feet a minute? Could the operator lower it at no cost, or was it necessary to work the machinery? When lowering, had the operator only to let loose the handle in order to stop it? That was all that was necessary with a hydraulic arrangement. Could all that be done with equal simplicity in the case of an electrical motor?

Mr. Unwin. Mr. P. I. UNWIN desired to refer to results as to the working cost of passenger and goods lifts, and of machines similar to those used in hotels, warehouses, private houses, and other high build-

ings, in London and other great cities. Hydraulic lifts had been Mr. Unwin. well known for many years, and they had been brought to a high pitch of excellence. The safety gear had been perfected, and, although no such thing as finality was possible, he did not think that much improvement could be expected in the future. The advantage of electric lifts was, as the Author had stated, that power was used in proportion to the load. With the hydraulic lift it was necessary to fill the cylinder whether the load was light or heavy; but with the electric lift the current was in proportion to the number of persons carried. To give an instance, the Otis Elevator Company had been asked two years ago to design a machine for a large establishment in London to carry a given load, possibly 1,000 lbs., to a height of 70 feet, at a certain speed. It was found that the current to drive the electric lift at $4\frac{1}{2}$ d. per unit would cost between £19 and £20 per annum; and that a hydraulic elevator under similar conditions, with a similar load and lift and doing similar work, would cost £47 per annum. The electric lift had then been decided upon, and the anticipations had been amply confirmed by results. The accounts for current for the first few months were at the rate of between £20 and £22 per annum, and at present, although the number of trips had increased from two hundred to three hundred per day, and although the loads had increased, the average cost of current was about £24 or £26 per annum. The Otis Company had made in past years a great many more hydraulic than electric elevators. They were compelled to place the best article before their employers, and if they were tied down to low cost of maintenance, they would advise electric instead of hydraulic lifts. As to the question of reliability, a hydraulic lift was simple, but an electric lift was equally simple, the switch-gear being the only part open to criticism on the score of complication. With regard to the question of initial cost of lifts, it was difficult to give exact figures, because every case had to be separately considered, as it depended upon different conditions. He might say that electric lifts for high buildings were as a rule between 10 per cent. and 15 per cent. more expensive in first cost than hydraulic lifts, depending on the height. The 10 per cent. or 15 per cent., whichever it might be, when capitalized, was saved over and over again in the difference in the cost of working. Taking an ordinary load of 800 lbs. or 900 lbs., twelve trips could be made with an electric machine against six with a hydraulic machine.

Mr. W. H. PREECE, C.B., Vice-President, said Mr. Walker, with Mr. Preece. considerable boldness, had called upon the electrical-plant manufac-

Mr. Preece, turers to support the facts which had been given in favour of electricity as applied to lifts and cranes. He was a considerable electrical user, and had early seen that electricity, if it possessed any merits, had the merit that it was particularly adapted for application to the very simple mechanical operation of lifting weights to a certain height. As soon as he had had the chance, he had applied electricity to working lifts, to which purpose he had considerable experience in the application of hydraulics. The great merit of electricity was, that it could be applied where it was wanted, that it could be used when, and only when, it was required; there was no waste in the meantime, and it could be stored quite as well as hydraulic power. He had, at the Post-Office at Leeds, three lifts worked by electricity. One was a short lift, only used for lifting parcel-baskets, bags, mails, etc. It made three hundred trips a day, and its height was only 12 feet 2 inches. The other two lifts had a run of 52 feet. He had made careful and accurate experiments upon those lifts, on the same system as that adopted by the Author. In the Table on p. 35 would be found the load, the travel, the time, the power, the energy, and the cost of working. Those engineers who loved the horse-power, and did not understand the Watt, would find both in that Table, so that both the old and the modern engineer could gratify their feelings in regard to the unit which each used and understood. In Leeds the cost of working each lift was almost exactly £7 per annum, and there were three lifts working there at a total cost for twelve months of £22 14s. 8d. He had also sent out to the Cape of Good Hope two lifts for use in the General Post Office there. They had been very carefully measured and tested, and their total efficiency worked out at about 40 per cent. In other words, the electric motors worked with an efficiency of over 80 per cent., and the gearing of the lifts themselves had rather a lower efficiency. At the General Post Office in London there were several hydraulic lifts, which were very largely used. Their average load amounted to six persons per trip, and the average number of trips was two hundred and twenty-eight loaded trips, the total number of trips being much more; 4,560 gallons of water per day were used, being received from the London Hydraulic Company. One was a ram lift, and another a suspended lift, similar to that suggested by Mr. Walker. The ram lift cost £123 10s. per annum, and the suspended lift £94 per annum. The height of the lifts was 84 feet in the General Post Office, as against 51 feet at Leeds; and the average load in the General Post Office was higher than the average load at the Post Office in Leeds. The

Mr. Preece.

TESTS OF THE ELECTRIC LIFTS AT THE POST OFFICE, LEEDS.

No. of Test . . .	Lift No. 1. ¹						Lift No. 2. ²						Lift No. 3. ²					
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
E.M.F. constant 105 volts.	Direction	up	down	up	down	up	down	up	down	up	down	up	down	up	down	up	down	down
	Load, lbs.	0	0	448	448	896	896	0	0	448	448	896	896	0	0	448	448	896
	Travel, ft.	12	12	12	12	12	12	51	51	51	51	51	51	52	52	52	52	52
	Time per trip, secs.	19	19	17	17	19	17	37	39	38	38	40	35	38	41	38	40	38
Average current, amps.	..	..	..	..	..	..	..	..	..	..	..	..	..	..	..	..	..	..
	Average current, amps.	3	15	13	10	21	5	10	28	15	17	28	8	3	27	15	26	5
	Duration of current, secs.	19	19	17	17	19	17	37	39	38	38	40	35	38	41	38	40	38
	Energy per trip, watt-hours	1.66	8.31	6.44	4.95	11.63	2.47	10.7	31.8	16.61	18.6	32.6	8.1	3.3	32.2	16.61	18.6	30.3
Cost per single trip at 14d. per unit.	.0025	.0125	.0096	.0074	.0174	.0037	.0160	.0477	.0249	.0279	.0489	.0121	.0049	.0483	.0249	.0279	.0454	.0082
	Cost per double trip at 14d. per unit.	0.01495		0.0170		0.0211		0.0637		0.0528		0.0610		0.0532		0.0528		0.0536
	Average current from meter reading, amps.	3	15	13	10	21	5	10	28	15	17	28	8	3	27	15	26	5
	Average speed, feet per minute	37.9	37.9	42.3	42.3	37.9	42.3	82.7	78.4	80.5	80.5	76.5	87.4	82.1	76.1	82.1	82.1	78.0

¹ Platform, 5 feet 8 inches x 7 feet 6 inches, constructed to carry 15 cwt. Balance weight = cage plus 4 cwt.

² Cage, 2 feet 10 inches x 3 feet 6 inches, constructed to carry 8 cwt. Balance weight = cage plus 4 cwt.

Mr. Preece. mean cost per lift for equal loads and equal heights worked out, for the hydraulic lifts £35 a year, and for electric lifts £7 a year ; so that, from actual experience, the cost of working an electric lift against a hydraulic lift was in the instance given as 1 to 5. The electric power was developed on the premises. With regard to speed, Mr. Ellington had suggested that the electric lift was slow. The average speed very nearly approached 2 feet per second in the electric lifts. A rate of 300 feet per minute was not comfortable travelling ; 2 feet per second was fairly comfortable, and he believed the average was rather below 1 foot per second ; so that with regard to speed he did not think any comparison could be drawn, since they were equal. In regard to staff, it was only the difference between a skilled mechanic and a skilled electrician ; his experience was that a skilled electrician required less training than a skilled mechanic. With regard to storage, he would say that whatever could be done with a hydraulic accumulator could be done with an electric accumulator. He knew many places where nearly two-thirds of the work of the electric-lighting station was performed by energy stored in accumulators. Many people thought of electric accumulators of to-day as accumulators which existed 10 or 12 years ago, but he could assure them that the electric accumulator of the present day was as different from the electric accumulator of the past, as the water accumulator of to-day was compared with the rough machinery used in the last century. He thought the Table showed that electricity as a motive power applied to lifts and cranes, was not to be brushed aside with old-fashioned notions.

Mr. Ravenshaw.

Mr. RAVENSHAW, in reply, considered the efficiencies given in the Paper for the electric crane were low rather than high. He had known electrical cranes which had given higher efficiencies, but the case in point was a special one. It was a large crane, and power was lost in the gearing. The loss in the electrical part was 10 per cent. at full load, and in the gearing about 40 per cent. There was a very heavy chain barrel, and a large weight of chain down the vertical girder which had to be balanced by a heavy hook. In the crane mentioned there was a switch, Fig. 6, Plate 1, by which the motor could be started very gently. He had not advocated either the three motors or the single motor. He thought the three motors in many cases could be used with great advantage ; but there was the disadvantage that it was possible to apply an inordinately large current, which responded very rapidly, and caused damage. The instruments were all carefully calibrated after the tests, and the results were the average of a great number

of readings. He had not advocated electrical over hydraulic lifts, Mr. Raven-shaw. because he was certain that hydraulic power would not entirely give place to electricity. A hydraulic lift was certainly very simple, especially when there was a single ram. Mr. Ellington complained that the lift he had ridden in in Berlin did not start immediately, that it lagged and hesitated. Possibly it was a lift made by a German firm, and of which he had recently seen the mechanism. It had an escapement gear, and passengers had to wait till the escapement ran half way down before the lift would start. He believed the escapement did not reach the bottom at all. With regard to jerking, he had himself gone up and down a hydraulic lift which had caused him great concern. It sometimes went very fast and sometimes very slow; sometimes it could not be stopped, then it was suddenly reversed, and there was a great jerk. He had spoken to the makers on the subject, and they said that it was the fault of the man who worked the lift. A new man was then employed, and the jerking did not now take place. This showed that care had to be taken in working hydraulic apparatus. He had ridden in many English electric lifts, and as a rule they worked very steadily. The rope could be pulled right down to the bottom, and it started smoothly. As to the small number of working parts; the electric lift gear, Figs. 1-3, Plate 1, showed only two working parts, namely, an armature and worm-wheel. In the lift gear shown there was a second guide-wheel, but many lifts had not that. In the jigger lift there were more than two working parts. As to being able to apply a large amount of power, that was done every day in the case of electric railways. He did not think there was any difficulty in that respect, with heavy fly-wheels and automatic expansion-gear, especially with the accumulators now being used. With regard to the cost of transmitting power by electricity, generating plant for electricity cost about 25 per cent. more than for hydraulics, the engines and boilers required being the same. Where overhead wires could be used, the cost of the electrical conductors was much less than that of hydraulic pipes; but where underground conductors were used, the cost was about the same. The increased cost of electric motors and gear was about 25 per cent. greater where a short travel was required; but for hauling-engines, where a rotary motion was necessary, he did not think there was much difference. He had experience of a great many plants on both systems, and had based his figures on practice. As to repairs, electricity had a great advantage over hydraulic power as it was not affected by frost. He had fitted hydraulic cranes with

Mr. Raven-shaw. electric wires to heat the pipes and cylinders to prevent freezing, and had effected a saving of nearly £100 a year in repairs per crane in consequence. With properly constructed electric motors the repairs and maintenance did not exceed 5 per cent. per annum. As to cost of working, in a typical plant where the power was transmitted over an area of, say, 1 square mile, the losses were approximately as follows:—In dynamos 8 per cent., in cables 8 per cent., in motors 10 per cent. under varying loads, or a total loss of 24 per cent. The engines could be taken to deliver power to the dynamos at a cost of £8 per brake HP. per annum, so that the power would cost £10·5 per brake HP. per annum at the motor-shaft. Electric motors were remarkably well suited for travelling cranes, and could be arranged so simply that they could be very easily adapted to existing machines. This application was an extremely important one, and a large number of square shaft and rope-driven cranes had been adapted to work by electricity in the last few years.

Correspondence.

Mr. Aspinall. Mr. JOHN A. F. ASPINALL remarked that in the erecting shop at Horwich good illustrations were afforded of the advantages of driving overhead cranes with electric motors instead of ropes. There were twenty 30-ton cranes in this shop, driven in pairs, with a single rope $1\frac{3}{8}$ inch in diameter, 600 feet long, weighing $3\frac{1}{2}$ cwt. and running at a speed of 3,880 feet per minute. Each of the ten ropes with their pulleys absorbed 15·5 HP. The energy required to lift a 46-ton engine with two cranes was only 16·4 HP. including internal friction. The ropes had been dispensed with and a single motor fitted to each crane with most advantageous results. Another application of electricity to lifting work was shown by an arrangement he had had introduced in the Victoria (Manchester) Station of the Lancashire and Yorkshire Railway for the transmission of parcels from point to point. The arrangement was unique and, he believed, the first of its kind. It had been running for 2 years and lifted baskets containing 8 cwt. of parcels, and, when high enough, ran with them at about 8 miles an hour. It covered about 100 miles a week, lifted about five hundred or six hundred baskets of parcels, and had consumed on the average 45 B.T. units of electricity in the same time. The current was taken from the electric-lighting circuit and passed from one rail through the machine, returning through to the second rail.