(Paper No. 2895.)

“Plant for the Treatment of Trades Waste.”

By WILLIAM NAYLOR, Assoc. M. Inst. C.E.

SINCE the issue in 1874 of the Reports of the Rivers Pollution Commission of 1868, the Treatment of Trades Waste has become of much greater importance on account of the increase of the population and of the growth of industry, together with the more general demand for pure air and water and better hygienic surroundings. The Local Government Act of 1888, by which the County Councils were empowered to administer the Rivers Pollution Prevention Act of 1876, has, in no small measure, contributed to the outcry against the pollution of watercourses by domestic and trades waste; for many of the local authorities empowered with the administration of that Act have been great defaulters, and hence its provisions have not been fully enforced.

Three joint committees of County Councils and County Boroughs, namely, the Mersey and Irwell, the Ribble, and the West Riding, have been formed by a provisional order of the Local Government Board for the purpose of cleansing rivers from objectionable matter. The Manchester Ship Canal is already largely polluted by solid matters brought down the Irwell from the Lancashire manufacturing towns; while the estuary of the Ribble, which is being channelled by means of training-walls, stands in need of protection from pollution by solids from the upper reaches. In an estuary so large as that of the Ribble, liquid pollution will have little effect upon the composition of the water, but the solid pollution not only causes obstruction, but has a stiffening or coagulating action upon the sand of the river. This hardened sand is almost immovable by natural scour.

The following analyses of specimens dried at 100° C. show the difference in composition between the bed of the river in the estuary of the Ribble, the bed upstream, and the mud on the bottom of the Salford dock of the Manchester Ship Canal:—

Sample.	Organic Matter.	Silica and Insoluble Matter.	Carbonate of Lime.	Oxide of Iron.	Alumina and other Metallic Oxides.
	Per Cent.	Per Cent.	Per Cent.	Per Cent.	Per Cent.
Ribble bottom in estuary . .	3·0	96·6	0·4	trace	..
Ribble mud at Walton Bridge	9·8	67·7	12·9	5·1	4·5
Salford-Dock bottom . . .	14·0	77·5	3·6	4·0	0·9

The effect of pollution from manufactories in the second and third of these samples is shown by the high percentage of organic matter and salts of lime and of the metals. The proportion of the silicious matters is higher and of the soluble salts lower in the Ship Canal sludge, owing probably to the acid nature of many of the waste-liquors from factories. In the Ribble, most of the liquors are alkaline, the paper-making industry accounting for the greater part of the pollution.

The forms of pollution may be divided into those from (1) calico and woollen bleaching, dyeing, and printing, (2) paper making, (3) tanning, (4) alkali and soap making, and (5) the galvanizing of iron.

Calico and Woollen Bleaching.—The object of the calico bleacher is to remove as much of the foreign matter as possible from the woven fabric. This consists of the natural resinous, fatty, waxy, colouring and albuminous matter, and that introduced in the sizing of the warps, as well as adventitious dust, dirt and grease. In order to note exactly the extent of pollution caused by each of the several steps in the process of bleaching, samples were obtained and examined by the Author from the Brinscall Bleach and Print Works in January, 1893, with the results shown in the Table, p. 390. It will be seen that the refuse from bleachworks consists principally of liquors holding in solution and suspension starch, lime, greasy and resinous matters, soluble soaps and soluble salts of lime and soda, etc.—mixed with the waste from dyeing and calico-printing operations. The principal polluting agents in calico-printing are: albumen, caseine, china clay, pipe clay, dextrine, glue, gluten, glycerine, gum senegal, gum tragacanth, molasses, lead sulphate, potato starch, salep, shellac in borax, sugar, wheat flour, wheat starch, zinc chloride and zinc nitrate. In addition, therefore, to the contents of the waste liquors from bleachworks generally, are added waste liquors from the dye-becks and the thickenings washed out in calico printing.

Nature of Sample.	Parts per 100,000.							Parts per 100.		Relative Volume.
	Dissolved Solids.		Total Dissolved Solids.	Suspended Solids.		Total Sus- pended Solids.	Total Solids.	Acid- ity. Nor- mal NaHO re- quired.	Alka- linity. Nor- mal H ₂ SO ₄ re- quired.	
	Mineral.	Volatile.		Mineral.	Organic.					
Water-supply from reser- voir . . .	8.0	10.3	18.3	Nil	Nil	Nil	18.3	Neut	ral.	Gallons.
First wash (or steep) . . .	42.9	145.1	188.0	16.4	55.9	72.3	260.3	0.2	..	20,000
Spent lime from kier . . .	134.3	613.8	748.1	9.0	105.0	114.0	862.1	..	1.4	1,600
Wash out of lime kier . . .	22.8	25.7	48.5	6.8	9.7	16.5	65.0	..	0.3	20,000
First (or grey) sour . . .	288.9	131.4	420.3	8.8	55.9	64.7	485.0	32.7	..	1,600
Wash out of grey sour . . .	42.7	22.0	64.7	3.4	10.7	14.1	78.8	1.5	..	10,000
Spent ash liquor (soda) . . .	802.1	556.4	1,358.5	{ taken with dis- solved solids }			1,358.5	..	10.1	1,400
Wash out of ash kier . . .	30.7	20.2	50.9	3.0	9.0	12.0	62.9	..	2.0	20,000
Spent "chemic". . .	114.3	29.8	144.1	8.6	11.5	20.1	164.2	..	0.3	1,600
Second (or white) sour . . .	126.5	47.5	174.0	1.2	7.1	8.3	182.3	10.9	..	1,600
Wash out of white sour . . .	8.2	12.1	20.3	2.9	11.2	14.1	34.4	0.3	..	20,000

The objectionable matters in the waste liquors may be either in suspension or in solution. The plant now generally in use for dealing with these liquors may be divided into (1) settling-tanks, to permit of the subsidence of the suspended matter and the precipitation of as much as possible of the dissolved matter, as well as the oxidation by aeration or other means of the remaining portion of the organic matter and the removal of colouring matter; and (2) filters for the further separation of the dissolved and colouring matters by oxidation or other means. The plant shown in Figs. 1 and 2, Plate 7, was designed and set up by the Author at the works of Messrs. John Stanning and Sons, Leyland, Lancashire, and has been in successful operation since January, 1894. The liquors for treatment, dye and bleach mixed, as well as all wash-waters, enter the precipitation-tanks along the carrier from the works after admixture with milk of lime and alumina-ferrie as precipitants. A dense precipitate of sulphate of lime and aluminium hydrate is immediately formed in the carrier, and the

whole then travels to the first precipitation-tank, which has a division down the centre. About 90 per cent. of the precipitate falls in these two tanks, which are emptied about once per week, the larger tanks being allowed to run for a fortnight or more. The precipitate of aluminium hydrate forms to some extent an insoluble lake with some of the colouring matter, and so clarifies the liquor of dye colorations apart from the deposition of suspended matter. The tops of the divisional walls are formed into carriers with the forward edge about $\frac{1}{2}$ inch lower than the rear, and having a top course of splay bricks for the lips. By this means any forward tank can be missed and the liquors may be passed on by the side carrier running the whole length of the tanks; thus any one, two or three of the four tanks can be used simultaneously, while the fourth is being cleared of sludge. The best results are, however, obtained from continuous flow, due probably to the important fact that the suspended matter in dye and bleach liquor aggregates during slight agitation; although, on standing either in bottles or in tanks for a short time, considerable deposition of the solids and colouring matter takes place apart from any chemical action of the precipitants. The top liquor is conducted away by floating arms, and the sludge is raised by a Shone ejector, into which it gravitates. The tank walls are 3 feet thick, of solid brickwork in cement mortar, and the floors are of 12-inch concrete throughout. The volume of liquor treated per day is 500,000 gallons, that being the capacity of the precipitation-tanks. The precipitated liquors are generally allowed to run into the river direct, but if required for further use they flow into the storage reservoir, Figs. 2. In the latter case they are lifted from the sump A on to the cinder filters, which deliver the water clear and sparkling, and fit for any of the finest bleachwork or delicate shades of dyeing and washing, etc., into the clear-water tanks. Thence pipes convey it from a well to the various departments of the works. The filter-beds are about 5 feet deep, the filtering medium being furnace clinker of various thicknesses. They have not sufficient area to filter 500,000 gallons per day, as it is only necessary to make up a short supply of water from other sources. Should the present water-supply become inadequate, the filter-beds will be enlarged for the treatment of the whole of the flow for use again in the works. The analyses (p. 392) show that the dissolved solids are largely eliminated by the cinder filters.

The quantity of precipitant used is 466 lbs. per day, or $6\frac{1}{2}$ grains per gallon of alumina-ferrie. About 10 tons or 12 tons of cloth are bleached per day, the cloth, reckoned dry, showing on! the

average 10 per cent. of size to be abstracted in the process. This amounts to 1.1 ton per day of dry, or 22 tons of wet sludge, the whole reckoned as in suspension and the sludge containing 95 per cent. of water. But to this must be added $1\frac{1}{4}$ ton of starch, lime, soda and other matters passing from the works to the tanks as waste, making a total of 47 tons of wet sludge per day. Of this only 33 tons are retained as sludge, the remainder passing away in solution in the liquors. The wet sludge is lifted by the ejector to a height of 17 feet and is delivered into earth drying-pits, from which it is carted away when dry. The ejector has a capacity of 100 gallons, and the air-compressor has 6-inch steam- and air-cylinders, with a 9-inch stroke. Working at a steam-pressure of about 50 lbs. per square inch, it is capable of dealing with 100 tons of wet sludge in twelve hours. Tested on the 21st November, 1894, the steam-cylinder of the air-compressor indicated 1.75 HP. with a pressure of 10 lbs. per square inch in the air-receiver, and a piston-speed of 150 feet per minute. The diagram taken at the same time from the air-cylinder indicated 1.1 HP., the steam-cylinder running with a light load of 0.76 HP. The compressor was working two hours and twenty-seven minutes, and ejected 11,800 gallons, or 63.2 tons, of sludge.

The following analyses of samples drawn during a period of six hours, at intervals of fifteen minutes, expressed in parts per 100,000, show the effect of the treatment:—

Description of Sample.	Dissolved Solids.			Suspended Solids.			Total Solids.			Remarks.
	Volatile.	Mineral.	Total.	Organic.	Mineral.	Total.	Mineral.	Organic.	Total.	
Raw liquor . . .	44	86	130	24	12 ¹	36	98	68	166	<div>Highly discoloured.</div> <div>Clear.</div> <div>Clear and sparkling.</div>
Tank „ . . .	40	92	132	..	..	..	92	40	132	
Filtered „ . . .	10	56	66	..	..	..	56	10	66	

The composition of the mineral dissolved solids in each case was:—

	Common Salt.	Silica.	Sulphate of Lime.	Chloride of Lime.	Sulphate of Iron.	Sulphate of Alumina.	Alumina.	Oxide of Iron.	Carbonate of Lime.
Raw liquor . . .	36.3	15.8	13.2	8.9	7.3	3.5	3.1	..	..
Tank „ . . .	34.1	..	45.3	6.1	..	..	2.8	3.0	1.6
Filtered „ . . .	14.5	14.4	21.8	..	0.56	..	trace	trace	4.7

¹ Composed of 11 parts of carbonate of lime and 1 part of oxide of iron.

It will be seen that although precipitation removes all the suspended solids, no difference is perceptible in the amount of dissolved solids. The raw liquids entering the tanks are discoloured, muddy, and contain suspended matter. They emerge from them clear, but little different so far as dissolved solids are concerned. The filtered liquor, however, is considerably improved, both as regards suspended and dissolved solids, containing only 46 grains of solids per gallon. The sludge, when dried at a temperature of 212° F., gives the following analysis:—

	Per Cent.
Organic matter	19·6
Silica, &c.	38·5
Calcium carbonate	31·4
Alumina	3·2
Ferric oxide	7·3
	<hr/>
	100·0
	<hr/>

The calorific power of the organic matter present is so low that the sludge is valueless as a fuel, for when placed in a calorimeter tube with a fusion-mixture it will not ignite but is converted into a liquid mass. When powdered and thrown on a boiler-furnace it gives for a few minutes a lambent blue flame with little heat, and then settles into a solid mass of clinker, which it is almost impossible to fire in ordinary furnaces. As a manure also it is valueless, the percentage of phosphates and ammonia being exceedingly low. If burnt to a clinker, it might be used for mortar-making, but other substances equally good can be obtained at a cheaper rate.

A series of precipitation-tanks, similar to those shown in Fig. 1, have been put into operation at Messrs. Fox's Woollen Mill, Wellington, Somerset. The supernatant liquor is, however, raised by pumps, owing to the levels not being suitable for it to be siphoned off by floats. As much more soap also is used, these liquors are treated separately and the soap is recovered.

Soap is formed by the combination of a fatty acid with a base, which may be an alkali, an alkaline earth, or a mineral. The fatty acids of a soap may again be separated and recovered, either by treating it with an acid which has a greater affinity for the base than for the fatty acids, in which case the latter are liberated; or by treating it with a second base, such as lime, which has a greater affinity for the fatty acids than has the base already combined with them, when a second soap will be formed, which, if insoluble in water, can be collected as a precipitate.

The first of these methods is that in use at the Wellington mill. The soap-liquors are conducted into six acidifying tanks, along with sufficient acid to liberate the fats, which on separation are drained on sawdust filters. Later they are taken off and purified by distillation for use again. The resultant or mother liquor from these acidifying tanks is pumped into the intermediate storage-tanks for further precipitation and settlement, after which it gravitates into the precipitation-tanks proper, and is treated with the general waste liquors by alumina-ferrie. The volume of liquor treated per day is about 600,000 gallons, and the tanks have a capacity of 300,000 gallons. Average samples of the liquor were taken during three or four days in January, 1895, and the effect of the treatment, expressed in parts per 100,000, is shown in the following Table:—

Nature of Sample.	Dissolved Solids.			Suspended Solids.			Gross Solids.		
	Mineral.	Volatile.	Total.	Mineral.	Volatile.	Total.	Mineral.	Volatile.	Total.
Raw liquor	46	18	64	18	8	26	64	26	90
Treated liquor	24	12	36	2	..	2	24	14	38

The raw soap-liquors contained, on an average, about 500 parts in 100,000 of solids, of which the fats averaged 150 to 250 parts, but in the treated soap-liquors no fats were present. The sludge, which is lifted from the wells on to cinder filters, amounts to about 10 tons per day, and the precipitant to 392 lbs. per day, or $4\frac{1}{2}$ grains per gallon. The sludge gives the following analysis:—

	Per Cent.
Moisture	76·40
Sand and silicious matter	14·50
Organic matter	3·98
Lime as CaO	1·39
Alumina as Al_2O_3	0·60
Ferric oxide	0·52
Sulphuric anhydride	0·34
Combined chlorine	0·02
Carbonic acid	1·56
Soda, &c.	0·69
	<hr/> 100·00 <hr/>

The Mather-Platt method of treating bleachers' and dyers' waste, adopted at Messrs. Rylands and Sons' Bleach Works, Chorley, is shown in Figs. 3 and 4. There are four tanks, at the bottom of which is laid a series of aeration pipes M, through which air is drawn by means of a steam injector. The precipitant is also blown in by a series of pipes L about 1 foot above the aeration pipes, so that the sludge is not disturbed when it is added. After the addition of the precipitant, the contents of the tanks are blown up for some minutes into a seething mass, and are afterwards allowed to settle. The precipitants are mixed in wooden tanks, shown on the divisional walls, with water drawn through the dilution pipe K and agitated by air also introduced by the injector. The sludge runs from each of the four tanks into a chamber shown in the sections AA and BB, from which it is lifted by a centrifugal pump.

In filters, the decolorization of dyers' wastes is probably not effected so much by oxidation as by the actual abstraction of the colouring matter. The filtering medium abstracts the colouring matter, as evidenced by the satisfactory results obtained so far as this point is concerned with a filter of straw, and also by the complete change of colour of the filtering media in all dyers' filters, as well as by the falling off in decolorizing efficiency after continued use. On the other hand, in precipitation-tanks the decolorization is more probably due to the presence of iron or aluminium hydrates liberated from the precipitant, which form an insoluble lake with the colouring matter. The amount of decolorization which followed the use of precipitants of iron and alumina without aeration for twenty minutes, has been shown by the Author's experiments to be much greater than that which ensued from three or four hours' aeration without precipitants.

The principal advantages of the aeration system are: The exceedingly quick and intimate admixture of the precipitants and liquors under treatment; the accuracy and ease with which precipitants can be used, and the results gauged as regards alkalinity, acidity or neutrality; and the reduction in the amount of precipitant used owing to the admixture of sludge already precipitated. With regard to the latter, it is certain that all finely divided precipitates are caused to aggregate by violent agitation; and, so far as the Author has been able to observe, the rapidity of aggregation is in direct proportion to the amount of precipitate present, the degree of agitation being constant. This is exemplified in the

case of a finely divided precipitate of calcium oxalate or barium sulphate, which aggregates on aeration or boiling; as is also the case with turbid argillaceous water, which will settle quite clear on agitation with a small quantity of sand. The same phenomenon is also noticeable if the liquor containing the precipitate be allowed to pass through a series of U-tubes. Aggregation takes place principally when the liquor is rising, and this in some measure accounts for the efficiency of the Candy tank, Figs. 5.

At various works where this system has been adopted, both alumina-ferric and lime, and copperas and lime, have been tried; but for bleachers' waste only, copperas and lime give better results than alumina-ferric and lime. The results obtained during an extended trial of the system in March, 1895, are given in the following Table, expressed in parts per 100,000 :—

Nature of Sample.	Dissolved Solids.			Suspended Solids.			Total Solids.			Remarks.
	Mineral.	Volatile.	Total.	Mineral.	Volatile.	Total.	Mineral.	Volatile.	Total.	
Raw liquor . .	52	20	72	..	10	10	52	30	82	{Reddish-black colour.
" " after treatment . . }	76	24	100	..	..	..	76	24	100	Colourless.

The amount of precipitant used varies with the liquor to be treated, but in this case 300 lbs. of lime and 300 lbs. of copperas were required per 100,000 gallons.

The two cases mentioned are exemplary of waste arising from the heavy bleaching of goods containing a considerable amount of size, say 20 per cent. or 30 per cent. Cloth, however, woven for purposes of printing (and yarn also) generally contains considerably less than this amount, between 8 per cent. to 12 per cent.; and therefore the refuse liquors are cleaner, on account of a smaller weight per ton of matter to be abstracted and a smaller weight of reagents used in the abstraction. The washing waters are nevertheless as voluminous as in heavy bleaching, owing to the finish required, the resulting waste being comparatively clean—containing about 10 parts to 20 parts per 100,000 of suspended solids and 50 parts to 60 parts of dissolved solids. Experiments made with the filtration of this class of liquor show, that the dissolved solids are only slightly affected when less than 50 parts

or 60 parts per 100,000; and, as these are principally unobjectionable mineral matter, it is doubtful whether further treatment than the interception of the suspended solids is necessary. The filters were 6 feet thick, and were first thoroughly washed. The following Table shows the result of filtration on the dissolved matter in bleach waste, expressed in parts per 100,000 :—

Initially.	After Filtration through Sand.		After Filtration through Cinders.	
	500 Gallons per Square Yard in 24 Hours.	200 Gallons per Square Yard in 24 Hours.	500 Gallons per Square Yard in 24 Hours.	200 Gallons per Square Yard in 24 Hours.
130	{ Filters choked	{ Filters choked	85	69
70	59	48	63	57
40	34	30	36	32

The desired elimination of the suspended matter can be effected more cheaply by a subsidence- or a precipitation-tank than by filters, which, with any appreciable amount of suspended matters, require frequent washing. For this purpose the Candy self-cleansing tank has proved itself to be well adapted. It is better fitted for liquors containing small percentages of suspended matter than are the horizontal tanks generally in use. That shown in Figs. 5 is fed at the bottom by down-pipes A, the inlets being laid at semi-tangents B, to avoid the disturbance of sludge already deposited. The liquors ascending to the surface pass away in thin films, void of suspended matter, along the channels C laid about $\frac{1}{2}$ inch below the outlet.

The Ives tank has a cone-shaped bottom, the sludge being pumped from the apex, under the liquor. It is found, however, that only the sludge immediately above the suction-pipe is drawn out, the greater portion of it remaining on the sides. The Candy tank has a flat bottom from which the sludge is siphoned off by a perforated pipe D moved over the surface by a winch. The sludge is delivered about 2 feet below the water-level and is of a satisfactory consistency. The following results have been obtained with this tank. The number of gallons treated was 100,000, the time occupied being twelve hours, and 6 grains per gallon alumina ferric being used as precipitant.

BEFORE TREATMENT.						AFTER TREATMENT.					
Dissolved Solids.			Suspended Solids.			Dissolved Solids.			Suspended Solids.		
Mineral.	Volatile.	Total.	Mineral.	Organic.	Total.	Mineral.	Volatile.	Total.	Mineral.	Organic.	Total.
43·1	35·1	78·2	3·6	15·8	19·4	50·6	21·3	71·9			
38·2	21·9	60·1	4·7	20·6	25·3	42·7	18·6	61·3			
44·3	41·7	86·0	3·2	13·9	17·1	47·3	33·3	80·6	..	2·0	2·0

At the works of the Pincroft Dyeing and Printing Company, at Adlington, Lancashire, the waste liquors containing indigo in solution are passed into precipitation-tanks, receiving on the way between 10 grains and 15 grains per gallon of calcium hydrate. The precipitated indigo is raised by an injector from the bottom of the tanks, and is blown into the dye-vats for use again. All other liquors, such as aniline-dye liquors, etc., used in the works, are treated in separate tanks, the precipitants being lime and ferric chloride. The raw indigo liquors before treatment contained, on the 17th January, 1895, 0·4 part of indigotine per 100,000, or 4 lbs. per 100,000 gallons. They are then of a deep blue colour, but after precipitation are clear and transparent, containing a reasonable amount of dissolved solids with little objectionable organic matter. Results of examination of liquors from the Pincroft Dye Works, expressed in parts per 100,000, are given in the following Table:—

Nature of Sample.	Dissolved Solids.			Suspended Solids.			Gross Solids.			Indigo-tine.
	Mineral.	Volatile.	Total.	Mineral.	Organic.	Total.	Mineral.	Volatile.	Total.	
Indigo waste before treatment	90	34	124	16	30	46	106	64	170	0·4
Indigo waste after treatment	84	30	114	3	1	4	87	31	118	..

Wool-washing Waste.—In the washing and scouring of wool a quantity of fat or grease is liberated, for which a special process

of treatment is required. The object of scouring wool is to remove natural impurities, such as yolk, dirt, oil, etc., and to leave a clean surface for dyeing. The wool contains large quantities of potash salts which may be recovered before scouring.

At the works of Messrs. Thomas Biggart, of Dalry, Ayrshire, the recovery of the grease and potash from the liquor produced in scouring the wool is effected in the following manner. The suds from the first bowl, containing about nine-tenths of the grease and potash, after standing about twelve hours to ensure deposition of the sand, are evaporated in a pan until the liquid assumes the consistency of syrup. It is then cooled on shallow iron trays, the grease, which collects at the top, being removed at intervals. The semi-liquid residue, containing the potash and organic matter, is calcined in a brick oven, the heat being used to assist in the evaporation. A crude carbonate of potash is produced in the calcining chamber, which, after being completely carbonated, is boiled to dissolve out the potash salt. It is then concentrated to 100° Twaddell at 212° F., and the sulphate and chloride of potassium crystallizes out on cooling. The quantity of fuel required is about 1 ton for 1,500 gallons; the carbonate of potash can be sold at £16 10s. per ton, and the grease, when boiled with vitriol, at £60 per ton.

In France and Belgium, and occasionally in England, the potash is extracted from the wool before it is scoured with soap. In a recent type of machine, that of Mr. Emile Richard-Lagerie, of Roubaix, the wool, in a series of tanks with distributors and automatic valves, is subjected successively to the action of liquors of diminishing strengths, the last being clear water for rinsing. The liquor, after having passed through the wool, is pumped for re-distribution into tanks until, on obtaining a density of 1.07, it is evaporated and calcined into carbonate of potash. Each machine is capable of dealing with about 8 tons of wool per twenty-four hours. The furnaces consume 1 cwt. of fuel per cwt. of potash salt produced.

The grease is extracted from the suds at the works of Messrs. Alf. Matte and Company, of Roubaix, by a mechanical process of "battage," without the aid of chemicals. The suds are, by means of a rotary-agitator, beaten into a froth, which carries to the surface the insoluble fats. This greasy lather is skimmed off into conduits by a mechanical scraper as it is produced, and is then forced by steam extractors into wooden tanks, in which it is heated to 140° F. Sulphuric acid, in the ratio of 1 lb. to 100 gallons, is then added to clarify it. The acidulated water is decanted and

used to assist in the clarifying, and the magma is passed into open filters of rough canvas. It is then pressed in screw-presses and disposed of as manure, the grease being clarified with sulphuric acid. After the "battage" treatment, the water is allowed to flow into the sewer without further purification.

Paper-Works Waste.—Paper manufactories contribute largely to the pollution of rivers. The effluents are always more or less foul, depending upon the material in hand, and, of course, upon the particular point of time in the washing process, the machines running generally about an hour or two hours. Analyses expressed in parts per 100,000 of the washing-machine waste liquors, taken on the 9th March, 1893, from Messrs. Dimmocks' works, Darwen, are given in the following Table:—

Nature of Sample.	Dissolved Solids.		Total Dissolved Solids.	Suspended Solids.		Total Suspended Solids.	Total Solids.
	Mineral.	Volatile.		Mineral.	Organic.		
Samples from beating- and washing-engines taken every five minutes and mixed	152·2	110·5	262·7	32·1	63·9	96·0	358·7
Samples from breaking- and washing-machines taken every five minutes and washed	18·6	18·3	36·9	8·1	29·8	37·9	74·8

These effluents are, at least in so far as treatment is concerned, subject to the same remarks as bleachers' uncoloured effluent. Upon being mixed with iron sulphate and lime, deposition of solids takes place quickly, and a clear supernatant fluid is obtained. If such treatment and the recovery of soda is adopted, the matter for consideration is reduced to the most economical form of precipitation-tank and filter if necessary.

At Messrs. Peebles' Whiteash Mill, Church, Lancashire, a successful plant is in operation. The whole of the liquors for treatment gravitate to two reception and primary settling-tanks of 9,437 gallons and 9,650 gallons capacity respectively. The overflow from these tanks is conducted to a well, 6 feet deep, having a capacity of 5,000 gallons. From this it is pumped a height of 70 feet to two sets of precipitation-tanks, the first set each 24 feet by 20 feet by 4 feet deep, their combined capacity being 36,000 gallons. The second set is divided into six tanks, each of which is 19 feet 6 inches by 11 feet 5 inches by 5 feet deep, having a

combined capacity of 41,700 gallons. The total capacity, therefore, of the precipitation-tanks is 77,700 gallons, or nearly one day's flow. The tanks are of brickwork with concrete bottoms, and the waste liquors are treated with lime and alumina-ferrie as precipitants. After settlement the top liquor is passed through cinder filters, 3 feet deep, of varying grades. The filters are herring-boned with 6-inch drains, and 3-inch branches, the former of which conduct the effluent to the river. On the date of the trial of which the following Table shows the results, in parts per 100,000, the cinder filters had been affected by frost, and were therefore supplemented by a sand filter which relieved them of a large portion of the work. The cinders, too, of the regular filter were fresh from the furnaces, and therefore gave up some soluble matter to the tank effluent, counterbalancing that abstracted.

Nature of Sample.	Dissolved Solids.			Suspended Solids.			Gross Solids.			Remarks.
	Mineral.	Volatile.	Total.	Mineral.	Volatile.	Total.	Volatile.	Mineral.	Total.	
Raw liquor . . .	200	46	246	72	104	176	150	272	422	Turbid.
Tank „ . . .	154	48	202	14	8	22	56	168	224	Fairly clear.
Cinder-filter liquor	154	50	204	14	6	20	56	168	224	Clear.
Sand-filter „	152	44	196	..	..	..	44	152	196	{Bright and colourless.

The composition of the mineral solids in each case was:—

—	Silica.	Lime as CaO.	Chlorine.	Sulphuric Anhydride.	Alumina.	Carbonic Acid, Soda, &c.
Raw liquor . . .	24.3	101.3	61.2	51.4	29.3	4.5
Tank „ . . .	1.9	60.3	36.8	54.8	6.8	7.4
Cinder-filter liquor	1.5	42.3	28.3	43.0	4.9	48.0
Sand-filter „	..	28.2	35.0	60.0	..	28.8

The samples were drawn at intervals of two and a half hours. The amount of sludge produced in the precipitation-tanks was 17 tons per day on an average of 28 days, 95.0 per cent. and 98.0 per cent. of moisture being contained in it. This is reduced

[THE INST. C.E. VOL. CXXIII.]

2 D

by sludge-presses to about $3\frac{1}{2}$ tons per day, the composition of the pressed sludge being—

	Per Cent.
Water	71·50
Sand and silicious matter	5·81
Organic matter	12·74
Lime as CaO	2·45
Alumina as Al_2O_3	2·01
Ferric oxide	0·55
Sulphuric anhydride	0·47
Combined chlorine	0·11
Carbonic acid	2·22
Soda, &c.	2·14
	<hr/> 100·00 <hr/>

As this sludge contains a considerable amount of fibre it is used again, after being washed, for the manufacture of the coarser brown or shop papers. Since the introduction of imported wood pulp as fibre for making paper, the volumes of waste liquors from paper-works generally have been so largely reduced that several attempts have been made to deliver the reduced volume into town sewers. This, however, is undesirable, since the salts of lime, as well as the silicious suspended matter, are liable to be deposited in the form of an incrustation on any small projection in the sewer, and so to eventually block up the sewer, or at any rate to materially diminish its sectional area.

Tannery Waste.—Waste liquors from tanneries form probably the worst manufacturing pollution, containing as they do so much organic putrescent matter which cannot be precipitated by ordinary means, if at all. They are in reality strong sewage, and must be treated as such. So far as the prevention of river-pollution is concerned, such waste is best disposed of by the local authority's sewer. Ratepayers generally, however, are averse to being taxed for the treatment of waste which they do not produce. But in towns where tanning is the staple industry, the community at large should be prepared to make concessions to a trade upon which it exists either directly or indirectly. In other towns, however, where tanning is an isolated industry, reasonable objection is often taken to sewer connections, and in such cases the manufacturers are compelled to adopt the best known means for purifying the waste.

The plant in use at the works of Messrs. W. and J. Sagar, of Colne, forms a good example. It consists of two series of tanks and filters, the first set of tanks receiving the washings of hides,

and refuse from pure shop and bran fermentation. The liquor passes from them, after settlement through fibre screens, to a second series of precipitation-tanks, and is then passed through oxidizing filters to the river. A second series of tanks receives the waste liquors from the lime-pits through the delivery-pipe of a pump; and, after settlement has taken place, it is filtered on specially prepared layers of earth and ashes, formed to contain as much air as possible for oxidation. The effect of this treatment is fairly satisfactory, though it is perhaps not the best process of sewage purification. Various experiments have been made by the Author, the results of which show that the oxidation of organic matter in tannery waste as in sewage is an exceedingly slow biological process which cannot be advantageously hurried. Only a fixed amount can be oxidised by a certain organism under the best conditions. The result of the treatment at Messrs. Sagar's works is generally the total reduction of the suspended solids and about 30 per cent. of the dissolved solids. The albumenoid ammonia in the liquors is also reduced about 40 per cent., but the nature of the raw liquors varies so continually that any figures for less than a month's trial are likely to be misleading.

Alkali-Works Refuse.—By the careful supervision of the inspectors under the Alkali-Works Regulation Act, pollution from this source has now almost ceased. The yellow liquors containing sulphides from the vat waste are treated in most cases by the Chance sulphur-recovery process. But there are many thousands of tons of old vat waste, tipped in various parts of the country, still draining unoxidized sulphides into watercourses. Apart from the Chance sulphur-recovery process, various expedients have been adopted for the treatment of this waste. In a typical plant, the liquors are pumped from subterranean channels and delivered on to a filter of iron oxide. The sulphides are oxidized to a certain extent, and any precipitate formed is caught in two successive precipitation-tanks; while the traces of sulphide still unoxidized are dealt with eventually in the second oxide filter, together with any matter which may remain in suspension after passing through the two precipitation-tanks.

Where large volumes have to be dealt with, so causing the choking of filters, the liquor is treated with a ferric salt which oxidizes the sulphides, and is afterwards filtered through sand or gravel.

Samples taken on the 19th January, 1895, before and after passing through the filter, gave 3·84 parts and 0·64 part per

100,000 of sulphuretted hydrogen respectively. Other samples taken before and after this date gave similar results.

The Galvanizing of Iron.—Before iron sheets will take the zinc from the molten bath, their surfaces must be free from iron oxide and from any adventitious dust and grease. The removal of such matters is accomplished in a bath of sulphuric or hydrochloric acid which gradually becomes saturated with iron salts. Before, however, the point of neutrality is reached, the action of the acid is so slow that it becomes more economical to discard it and to employ fresh rather than to use it further. Local authorities rightly refuse to admit the liquid into common sewers, owing to its action on the cement joints, and to the large amount of lime necessary for the precipitation of the iron at the outfall works. If allowed to pass into rivers directly, or thence through outfall sewers without treatment, it has an injurious effect upon animal and vegetable life, in addition to producing an objectionable deposit of ferric oxide on the banks and beds of rivers.

Where sulphuric acid is used and the waste therefore consists of a solution of ferrous sulphate, a process of neutralisation is adopted, similar to the Weldon process for manganese dioxide recovery; viz., lime is added which forms sulphate of lime with the acid radical, and so sets free iron oxide which in some cases is collected and used as a pigment. Where hydrochloric acid is used and the "waste" is a strong solution of ferric chloride, the Turner recovery process,¹ which has been in successful operation about four years at Messrs. Walker Brothers' galvanizing works, Walsall, gives much better results. The plant consists of a dish-shaped receptacle or pot into which the liquid is run. This is placed before a coke fire, the heat given off gradually concentrating it and causing a continual deposition of the soluble ferric chloride. This is extracted through a hand-hole and is placed in a space between the fire and the dish-shaped receptacle, where it is decomposed by heat into chlorine and ferric oxide. The chlorine passing over the bridge with the draught, comes in contact with the steam rising from the waste, and forms hydrochloric acid, which is conducted to a tower and condensed for use again. The iron oxide is of some value as fettling for puddling-furnaces, yielding a few shillings per ton. The two furnaces at Messrs. Walker Brothers' works together treat 1,000 gallons of waste per day, yielding about 300 to 350 gallons per day of 75 per cent. commercial strength (29° Twaddell). Its

¹ "Industries," vol. x., 1891, p. 163.

actual strength is not a reliable indication of its acidity, owing to the ferric chloride it contains, due to particles of iron oxide which pass over it in the draught and are dissolved by and come down with it. This, however, is no drawback to the system, as its elimination forms part of the cycle. An average sample of the acid contained 8·8 per cent. by weight of ferric chloride; and 10 parts by volume of the acid required for neutralisation contained 62·5 parts of normal alkali, its specific gravity being 1·115, or 23° Twaddell. The ferric oxide contained 97·6 per cent. of black magnetic oxide and 2 per cent. of carbon and ash. About 1 cwt. of the oxide is produced daily, and about 4 tons of coke are used every week. The ferric chloride in crystallising out in the pot, does not always sink to the bottom immediately, but forms a scum on the surface, which, owing to the high temperature, is, to a certain extent, decomposed in the pot. A sample extracted from the surface contained—

	Per Cent.
Ferric chloride	53·40
Ferric oxide	20·14
Moisture	22·21
Carbon and insoluble matter	4·01

Two men are required to attend to the plant, one being on duty during the day and the other at night. The average cost of recovery is about 8s. per ton.

The Paper is accompanied by ten sheets of tracings, from which Plate 7 has been prepared.

Figs: 3.

Fig: 4.

Figs: 5:

Figs: 2.

Scale for Figs. 4 & 5 $\frac{1}{2}$ inch to 1 Foot

Figure 1. A schematic diagram of the experimental setup. The subject is seated in a chair, viewing a screen displaying a target. The target is a vertical line with a horizontal bar at the top. The subject's hand is positioned at the bottom of the target. The distance between the subject's hand and the target is 10 cm. The target is 10 cm high and 10 cm wide. The subject is instructed to move their hand to the top of the target. The distance between the subject's hand and the target is 10 cm. The target is 10 cm high and 10 cm wide. The subject is instructed to move their hand to the top of the target.