The traveler on its last trip to the main pier, placing the upper member of the north anchor arm, November, 1914

Placing one half of the main link, connecting the cantilever and anchor arm top chords, at the top of the main post, 350 feet above the water level

The north anchor and cantilever arms, completed November, 1915

Showing the enormous size of the details at the middle or "K" joints

Diagram showing members are erected

Ten huge members connecting to the main shoe center

The "flying bridge" being moved out to its second position

The New Quebec Bridge

Progress of Erection of the World's Longest Cantilever Span

By A. Meyers

Status of the bridge last November when work was halted for the winter season. Work is now proceeding on the south side to receive the center span next September

Work is now proceeding on the south side to receive the center span next September

The north cantilever arm and the south anchor arm in the process of erection. Note the "flying bridge" supporting the last placed section of the bottom chord

The traveler, having finished the placing of the shoes on the main pier, is laying the bottom chords of the anchor arm on the outside staging

ON the 12th of November, 1915, when the last member of the north cantilever arm was put in place, the third season's work in connection with the erection of the superstructure of the new Quebec Bridge was brought to a satisfactory close.

The season of 1915 was remarkable on account of the great amount of tonnage handled, the rapidity of erection, and the clock-like regularity of the advancement of the work. Except at times, from the inclemency of the weather and high wind, there was practically no unforeseen delay of any consequence, and the work progressed according to schedule in a manner that attested to the careful and well thought out plans.

During this, the third season's work the tonnage erected, amounting approximately to 30,000 tons, was over twice as much as that put in place during the seasons of 1913 and 1914 combined.

During the summer of 1913 the approach spans on the north shore from the abutments to the anchor pier were fully erected by means of a derrick car. These spans were erected partly on wooden and steel falsework and the longer spans partly cantilever. The last supports for the longer approach spans were at the first panel point past the center on the side nearest the anchor pier. Here they rested on sandjacks on top of the steel bents. When the spans were completely erected they were lowered onto their shoes on the anchor pier by means of these sandjacks.

During the fall of 1913 and the following winter the 1,000-ton traveler, standing over 200 ft. high, carrying two electric traveling cranes capable of lifting 110 tons each, and four 70-ft. 30-ton derrick booms, was erected just back of the north abutment. This traveler was completely finished by May, 1914, and one week later it was moved over the approach spans to its first position over the anchor pier. The approach spans had previously been equipped with special brackets carrying a special line of outside stringers for supporting the traveler track, and also at several points had been reinforced to carry this excessively heavy concentration.

From its position over the anchor pier the traveler, on May 21, 1914, began its work of erecting the falsework and superstructure of the north anchor and cantilever arms, which it finished, as stated above, on November 12, 1915, consuming in actual working time some fourteen months, during which time it erected, including falsework and bridge material, approximately 35,000 tons of steel.

The traveler on the first trip out to the main pier erected the inside staging which carried the main bridge floor material and extra lines of girders for the traveler track, and also erected the outside staging which supported the main trusses, sway and lateral bracing of the anchor arm.

This work was completed early in July, and on the

The shoes being erected, the bottom chord, some pieces of which weighed over 100 tons, with its lateral bracing was next laid from the main pier to the anchor pier.

The traveler was then brought back to the main pier and commenced the placing of the web members below the middle or "K" joints. This work was finished by November 18th, and the traveler started on its last trip to the main pier, completing the erection of the upper portions of the trusses and sway bracing except the last two panels next the main pier.

The work on the north anchor arm for the season was then brought to a close—December 3, 1914.

The work on the south shore during the season of 1914 consisted of the erection of the south approach

Diagrammatic view of the bridge

Note the suspended center span

18th of that month the erection of the main shoes on the north main pier was begun. Each of these shoes weighed about 450 tons, and was shipped in sections weighing up to 50 tons. The lower story is made up of four steel castings, each casting weighing about 40 tons. The middle and top stories are made up of four webs running 9 inches thick in places, spaced to correspond to the webs of the bottom chords, compression diagonals and main post. These webs are reinforced and supported by heavy cross diaphragms, spaced about two feet centers. Extreme care was taken to insure a perfect bearing on the bridge seats for these shoes, and in placing them exceptional precautions were taken to see that they were properly aligned.

span, the mode of erection being similar to that followed for the north shore approach spans, as described above. Also about two thirds of the south shore traveler were erected before the close of the season.

In connection with the erection of the anchor arms, after the bottom chord had been completely riveted up in a straight line, it was jacked down to a curve sufficient to bring the top chord panel points about one inch closer together than the normal shop lengths of the eyebars demanded. This was accomplished by slotting the pinholes in the eyebars 1/2 inch in the direction opposite to the bearing surface. The pinholes at the upper ends of the main tension diagonals were slotted 2 inches in a similar manner. The purpose of this

camber was to avoid as far as possible any difficulty that might arise in driving the huge pins used for connecting the main members.

Work on the north shore was resumed in the spring of 1915—about the middle of April. The erection of the anchor arm was completed, and on May 3rd the placing of the main posts was begun. Each post, standing 310 ft. high, weighing approximately 1,000 tons, was shipped in 27 pieces. The two were assembled simultaneously, and the work of erection was completed by May 31st. The outside dimensions of these main posts are about 10 ft. by 10 ft., and although there were six full horizontal field splices in each post, the final distance, center to center of end pins, was as nearly accurate and the bearing surfaces of the pins as nearly horizontal as it was possible to measure.

In the erection of the cantilever arm, which was begun on June 9th, the panels are completed as the traveler advances, the final bracing for each panel being put in by the rear booms of the traveler. On account of the large section and the length, the bottom chords are fully spliced twice between the main panel points. This necessitated that they be supported while the different parts were being assembled and lined up on what is known as a "flying bridge." This "flying bridge" is attached at the shore end by a pin driven through a temporary bracket which is bolted to the bottom flange of the chords already placed and the front end is tied back to the compression diagonals by means of yoking girders and links. The adjusting of the chord for riveting and driving of pins connecting the chords to the tension verticals was made by means of jacks placed on this bridge. As each panel was completed the bridge was taken up by the cranes of the traveler and moved ahead to its new position.

The operating schedule for each panel of the cantilever arm was approximately as follows:

With the traveler standing with its front legs at a main panel point, the "flying bridge" was moved forward into position; the first panel section of the lower chord placed with its portion of the bottom lateral

(Concluded on page 490)

Six-30
\$1195

ON the street the Moon Six-30 "stands out". It's not just a plain automobile. You notice it—for its size—its beauty of line—its individuality—and the kind of people you see in it. From top to tires, it looks—and acts—and lasts—like a high-priced car.

Six-30, 5 passenger, fully equipped \$1195
Six-44, 7 passenger, fully equipped \$1475

Write for large folder, describing and illustrating Moon cars.

MOON MOTOR CAR CO.
ST. LOUIS, U. S. A.

How Manufacturers Can INCREASE THEIR BUSINESS

Read Carefully Every Week the CLASSIFIED ADVERTISING COLUMN in the
SCIENTIFIC AMERICAN

Some week you will be likely to find an inquiry for something that you manufacture or deal in. A prompt reply may bring an order.

Watch It Carefully

Klaxons say "Supper Time" on big ranch in Peru

THE sound of Klaxon automobile horns is music to the ear of ranch hands in Peru. It means time to stop work and come in for supper.

The big ranches there stretch out for miles. A way was needed to summon the hands. A steam whistle was impractical—it was a difficult problem—until one day one of the ranchers heard a Klaxon on an automobile in Lima.

He bought several and put them on posts a mile apart—all over his ranch. Now it is simply a question of pressing a button. The men in the fields hear the Klaxons. In they come.

600,000 automobilists depend on this same Klaxon carrying power to herald their approach around the turns of

country roads; and in the noisy traffic of city streets.

The Klaxon is so universally used among motorists that the word "Klaxon" has come to mean "auto horn"—and many horns which are not Klaxons are sold as Klaxons to unsuspecting motorists. To be sure, look for—and find—the Klaxon name-plate.

There is a Klaxon for every kind and size of automobile—for trucks, motorcycles, motor-boats—from the Haod Klaxon at \$4 to the large Klaxon at \$20. Klaxons are made only by the Lovell-McConnell Mfg. Co. of Newark, N. J.

LIFT THE HOOD AND SEE IF THE HORN ON YOUR CAR BEARS THE KLAXON NAME-PLATE.

This nameplate is
your protection
against substitution

enemy's line in the direction of the Lone House.

Second Battalion, as reserve, will follow behind the center. I will be with the reserve.

[The first of this series of War Games began with the issue of March 11th. A war map in colors, covering the terrain of these War Games, was published in the issue of March 25th. Copies of this map may be had for 10 cents each.—EDITOR.]

Cartridge Cases of Steel

(Concluded from page 478)

The present American service rifle develops a chamber pressure of about 50,000 pounds per square inch. The German Mauser goes nearly to 60,000. Because of the rimless case used and the form of the bolthead, the case is not solidly supported during firing, but it is free to flow out around the bolthead when the pressure gets high enough to make brass flow.

In the American service rifle, when the pressure gets up beyond 60,000 pounds per square inch, the first sign of trouble is the dropping of primers from the cases, caused by the shell flowing sideways around the head and enlarging the primer pocket. Sometimes this allows gas to get into the bolt mechanism and blow the striker to full cock. A number of riflemen, holding their heads close to the firing pin and wearing glasses, have had their glasses broken by the sudden rearward thrust of the firing pin from the escaping gas.

Still higher pressures rupture the brass case at the groove or cannelure, and this may blow open the rifle if the gas gets out at the right spot to lift off the top of the receiver and release the top locking lug of the bolt cylinder. The first sign of too high pressure, as I say, is the flowing or stretching sideways of the brass case at the head. However, rimmed cases, solidly supported by most carefully machined blocks, extending all round the rim and not allowing the brass to flow in any direction, have stood chamber pressures of 80,000 pounds per square inch. This is an impossible form of construction with the rimless case of the modern military rifle, and the necessary tolerance allowed in economical machine manufacture.

So much stronger is the locking mechanism of the modern rifle, and so easy is it to make this still stronger if necessary, like the interrupted screw form of bolt-head used on the Canadian Ross rifle, that we may say that the brass case is the weak point of the modern rifle. Both from the standpoint of economy and of strength the steel cartridge case would be desirable if we can make steel function through the draw presses with the facility of the brass cup. The very fact of the ductility of the brass in the draw press is what makes the same brass yield to high powder pressures. It is evident that if we are to gain ground in this department, add strength to the case, we must be prepared to machine some material or other which is also less amenable to the blandishments of the press. Steel is immensely more economical than brass, which is largely copper. The economy may disappear if the speed of machines has to be cut down and the wear on the tools becomes excessive and the reloading of the cases becomes impractical through the rust, and corrosion through powder residue.

But regardless of the economical side of the argument, if we add strength to the rifle and permit of still higher pressures and ergo higher velocity, steel cases would be worth while. And, if through some such calamity as has befallen Germany, the supply of copper is cut off, then making cartridge cases out of steel is greatly to be desired even though no other advantage be gained than that of an unlimited supply of raw material.

Some years ago there came reports of German and French experiments with steel for cartridge cases, while I have before me samples of cases of this material made experimentally by Sir Charles Ross, of the Canadian national rifle factory. Nearly a year ago, the Ordnance Department of the United States Army undertook the manufacture of steel cartridge cases, doubtless actuated by the consideration I have mentioned, the pos-

sible shortage of copper or spelter in case of war. The manufacture of the cases was never put on a regular basis, but enough were made on the regular machines set out for the manufacture of the brass cases, to demonstrate that the steel cartridge case is entirely practical. One is led to wonder whether Germany has not found the process practicable or whether her shortage of copper is not so great as it is reported to be.

At the American Frankford Arsenal of the Army they made both steel service rifle cases and the clips to hold the five cases together as they are issued to troops. The Chief of Ordnance of the Army reports as to this work:

"Two thicknesses of sheet steel were used, the steel being planished on both sides. The cups were made without difficulty on draw presses, using the same punches and dies as are used for cartridge brass. Annealing after each operation was essential, and special precautions had to be taken to prevent scaling, by annealing in boxes packed with iron filings. The ordinary speeds of machine were used as it was not desired to make any extensive changes, but this resulted in considerable loss on account of scratching by the dies.

"For permanent manufacture the speeds would undoubtedly have to be very much diminished. Great care had to be taken with the lubricant, only the very best quality giving good results.

"As might be expected, a number of modifications in the amount of the annealing were experimented with. The earlier cases were defective in that there was a swelling of the head sufficient to cause leaks. Experiments were conducted only far enough to determine the practicability of the process and to overcome evident defects in order that the department might have the necessary knowledge to quickly undertake the manufacture in quantity, if desired."

Sample cases from Frankford, before me, show work of the highest quality, the cases being as uniform in wall thickness and head as the best made brass cases. The lightness of these cases is noticeable as compared to cases of brass, for the same rifle.

Steel cases would of course offer some difficulties outside of those of manufacturing. A protective coating of some sort would seem essential to prevent rust from perspiration from the bodies of the soldiers, and from the rain and dew to which soldiers are exposed. Their behavior in a rifle is still a matter of conjecture, but extraction should be easier and there should be less chance for the occasional clean rupture of the case in the chamber of the machine gun, leaving the forward part in the gun and putting that piece effectively out of commission until it is removed with a special tool.

It is not at all improbable that the Germans have not found practical what the Frankford Arsenal has been able to do without much trouble. The German never yet has equaled the quality of the ammunition turned out from this Government arsenal, and the German never has turned out powder equal to the latest product of the American Du Pont Co., the progressive burning variety. Despite his painstaking thoroughness, it is not the Teuton alone who makes improvements in war material.

The New Quebec Bridge

(Concluded from page 481)

bracing, followed by the lower sections of the compression diagonals with their sway bracing. The sub-tension diagonal was then erected and the pins connecting it to the compression diagonal and the main "K" point were driven. The sub-post carrying the floorbeam and the floorbeam itself were next placed and the floor system from the main panel point to the sub-panel point laid. The traveler was then advanced until the front legs rested over the sub-panel point. In this position the second panel section of the lower chord was placed on the "flying bridge." The upper halves of the compression diagonals with their sway bracing were next erected, followed by the portal and vertical post sway bracing in the panel to

What Tungsten filament did for electricity, and the Welsbach Mantel for gas, Rice's Gloss Mill White does for daylight. Treating ceilings and walls with Rice's Gloss Mill White increases daylight from 19% to 36%—saves half to three quarters of an hour of the time you otherwise burn artificial lights.

RICE'S GLOSS MILL WHITE

is an oil paint made by a special process discovered and owned exclusively by the makers. There is no substitute. It is the only oil paint giving a glossy tile-like finish at no more expense than lead and oil paint. It is as clean as it is bright—can be washed like a piece of white china. Sanitary.

By the Rice Method, it can be applied over old cold water paint. Over 3,000 plants have proved Rice's the most efficient finish for ceilings and walls. Repeated tests have shown without a single exception that Rice's remains whiter longer than any others. Users are protected by the Rice Guarantee.

On Concrete Surfaces—On inside concrete, Rice's Granolith makes the best possible primer for a second coat of Rice's Gloss Mill White—giving a tile-like finish at no more expense than lead and oil paint.

RICE'S GRANOLITH

Write for our booklet—
"More Light"

U. S. Gutta Percha Paint Co.
23 Dudley St., Providence, R. I.

A few of the 3,000 plants in which Rice's is used

General Fire Extinguisher Co.
Pierce Arrow Motor Car Co.
Northwestern Knitting Co.
United Shoe Machinery Co.
Waltham Watch Co.
"Huyler's"
Jenckes Spinning Co.
Pacific Coast Syrup Co.
Winchester Repeating Arms Co.
Eastman Kodak Co.
Gillette Safety Razor Co.
Cluett, Peabody & Co.
Merrell-Soule Co.
Colt's Fire Arms Co.
Royal Typewriter Co.
Hyatt Roller Bearing Co.
Hudson Motor Car Co.
Newark Public Service Corp.
Remington Typewriter Works

the rear of the traveler. The main tension diagonal with field splices completely riveted up was then hoisted into position and the pins driven. This was followed by the tension vertical, the vertical compression post and the supporting trusses with top chord eyebars in the order named. The top chord pins at the shore end of the panel were then driven, and the last truss pin connection was made by jacking up the bottom chord from the "flying bridge" and driving the pin connecting the tension vertical at the "K" joint. The erection of the sway bracing for the tension vertical, the floorbeam connecting to the tension vertical, and the floor system from the sub-panel point to the main panel point followed immediately. The traveler was then moved out into position to repeat the operation for the next panel.

The work done on the south shore during the season of 1915 was as follows:

The south shore traveler was completed by June 1st. The inside staging was then taken down on the north shore, transferred to the south shore, and re-erected, together with separate outside staging for the south shore anchor arm trusses. The placing of this material was completed by July 9th, when the erection of the main shoes was begun, followed by truss material in the same sequence as described above for the north shore.

Profiting by the experience gained on the north shore, very much better time was made in erecting this material, a saving of some six weeks being effected. The anchor arm trusses, together with the main post and links at the top of the main post, were completely erected by the end of the first week of November, 1915. The inside falsework was then removed and sent back to the shops at Rockfield, P. Q., to be remodeled for use in the erection of the suspended span in 1916 at Sillery Cove—about three miles below the bridge site.

The suspended span, 640 ft. long by 88 ft. wide, weighing in the condition of floating in approximately 5,000 tons, will be erected on falsework and raised on six scows 32 ft. by 160 ft., having a draft, when carrying a load, of about 8 ft. The span will then be floated to the bridge site, where it will be hoisted into position by means of eight 1,000-ton hydraulic jacks, placed in pairs on jacking girders at each cantilever corner, together with plate hoisting links. Each operation of these jacks will lift the span about 2 ft. Altogether, the span will have to be hoisted vertically about 130 ft. The time consumed in this operation is not expected to exceed twenty-four hours.

If nothing interferes with the schedule mapped out, it is expected that the south cantilever arm will be completed and ready to receive the suspended span about the end of September, 1916, when, after many years of effort, this great steel bridge—the largest in the world, and the last link in the National Transcontinental Railway System between the Atlantic and Pacific Oceans—will have been finished.

The Problem of Gasoline Supply

(Concluded from page 466)

It is said that one concern spends more than \$150,000 each year collecting and tabulating statistics relating to the production, distribution and consumption of petroleum and its products in the United States alone. If the statistics are of sufficient importance to justify their collection and tabulation by a private concern, does it not indicate a field in which the Government should seek to supply all parties engaged with corresponding information? Such a service would be of interest not only to the industries themselves but also to the country as a whole.

The only hope for the speedy reduction in the high prices of gasoline, according to Van H. Manning, the director of the Bureau of Mines, Department of the Interior, lies in the immediate development of the so-called Rittman cracking process and similar processes. He declares that the prevailing prices may not only continue for some time but will undoubtedly reach higher levels before there is any permanent relief. He points to the fact

Stanley Core Box Plane

For making circular core boxes. The sides of the Plane are at right angles, consequently the point of the Plane will always cut on the circumference of the circle when the sides rest on the edges of the cut. It will make tapered core boxes as well as straight ones.

As furnished, it will work semi-circles up to 5 in. in diameter. Extra sections at slight additional cost, enable the Plane to work semi-circles up to 10 in. in diameter.

Price as Illustrated—\$4.40

If you are unable to procure this tool from your dealer write us direct.

Address

STANLEY RULE & LEVEL CO.
NEW BRITAIN, CONN. U.S.A.

How much power for a dollar?

And then, how to get more power for each dollar—that's the big question that remained unanswered in thousands of plants until they secured the

Bessemer Oil Engine

(Awarded Gold Medal Panama-Pacific Exposition)

This wonderful power producer operates on cheap crude and fuel oils. In dependability of service it cannot be surpassed, no matter what power you use. In economy of operation, no other method except water power in some instances has ever equalled the Bessemer Oil Engine.

If you are open to conviction that your power costs might be reduced, ask for catalogue.

Our complete line: Fuel Oil Engines from 15 to 185 H. P. Gas Engines, 5 to 350 H. P. Kerosene Engines, 2 to 8 H. P.

The Bessemer Gas Engine Co.
14 York Street Grove City, Pa.
Bessemer Engines Running Today
in Sixteen Thousand Power Plants

Keen Tools Cut Hard Work in Half

In big machine shops and manual training schools where sharp tools are the rule, there is an established preference for

These oilstones cut faster and hold their shape longer than any others. When properly oiled, they will not glaze and they are so tough that even dropping won't break them. After years of service the rubbing surface is even and that means square edged chisels and plane bits. When you want an oilstone of proven merit

Pick a Pike

Every tool user should own a copy of "How to Sharpen." This little manual tells how to get a keen edge quick and is a reliable guide on the proper selection and care of oilstones. It is sent without cost to you.

Write for it today.

PIKE MANUFACTURING CO.
6 Main Street, Pike, N. H.

that the oil companies, in competition to supply the United States Government for the next fiscal year, have offered gasoline at 31½ cents a gallon for the whole year, and argues from this that, if the United States, using vast quantities of gasoline, is compelled to pay this much, the private consumer will have to pay much more. Furthermore, Mr. Manning says that with a rate of production the same as in 1915 the crude oil supply of the United States, from which we are getting our present supply of gasoline, will be exhausted in 27 years.

"And what is still more important to the situation, present indications forecast a decreased production of gasoline from crude oil for 1916 rather than an increased production. The daily production of crude oil for February in the Mid-Continent field, which produces 75 per cent of our refinable crude oil, was 40,000 barrels less than the average daily production for 1915, and 20,000 barrels less per day than the average production in 1914, and this is in the face of a strong incentive to find new fields given by the rising market of the past six months, which has culminated in record high prices for that field of \$1.55 per barrel for the crude, with, in some cases, a premium exceeding 40 cents per barrel.

"The demand for gasoline has outstripped the demand for all other petroleum products with the result that these other products, amounting to about 75 per cent of the production, are being sold for less than the cost of production. In other words, 25 per cent of the production, consisting chiefly of gasoline, must pay all costs in addition to the amount that is lost in marketing the remaining 75 per cent.

"We are exporting at the present time 20 per cent of our entire production of crude petroleum, including 16 per cent of our gasoline production. We are burning 25 per cent of our petroleum under boilers, which is a shameful and criminal waste of precious natural resources, and we are using another 20 per cent of our crude petroleum inefficiently in competition with coal as in the manufacture of artificial gas. Three fourths of the entire amount of artificial gas in this country is made from petroleum. This gas could be made from coal, except that the gas manufacturers are able to make it at less cost from petroleum, owing to the lower cost of oil as against coal. It is needless to say that petroleum should not be used for this purpose.

"The solution of the problem is conservation—our petroleum resources being put to their proper uses. Let us stop this wasteful foolishness of burning petroleum under boilers and the use of crude oil in the making of artificial gas. If by means of cracking processes, such as the Rittman process, our kerosene and fuel oils, which we have been using in competition with coal and selling for less than the cost of production, can be converted into gasoline, the present production of crude petroleum would be more than ample to supply our present demands for gasoline. Not only that, but the general adoption of these processes would result in extending the life of our petroleum deposits, based on present demands, from 27 years to more than 100 years, at the same time reducing and stabilizing the cost of gasoline to the consumer and preventing the rapid fluctuations in price. Ten different refineries are now installing the Rittman process and more companies are considering doing so. This is but a drop in the bucket, but the situation is hopeful.

"The importance of petroleum cannot be measured by dollars and cents. Figures cannot convey an idea of the dependence of many industries upon petroleum products of one kind or another. Lubricating oils, all of which come from petroleum, are absolutely necessary to our very existence. It has been computed that the machinery of the nation requires approximately one gallon of lubricating oil to each 300 horse-power per day, roughly speaking. Every automobile built but adds to the demand for lubricating oil; every ship launched, every car, every locomotive, must be supplied with lubricants, and petroleum is the only known source of supply. To-day we are burn-

The Thing Worth While

For thirty-five years the simplifying and perfecting of photography has been the big aim, the thing considered most worth while, the ideal in the Kodak factories. And each measure of success has made further successes possible. Each success has broadened the foundation, has given more in experience and in facilities, with which to work.

Along with the experience that comes to a well trained and efficient organization of long standing the Kodak organization has also the advantages of its own Research Laboratory, one of the largest and best equipped in the world. And this laboratory is not merely a building of brick and mortar to house the instruments of precision. It is a miniature factory where actual manufacturing on a small scale, can and does supplement in a practical way the work of the experimenter. Its staff is composed of scientific specialists whose work has developed along photographic lines. Its work is basic, far reaching. It has already done much for and in the future will do more for a scientific knowledge of photography.

The "Know how" that comes from long experience, the practical application of scientific knowledge, an organization in which honest workmanship has become a habit, in which nothing is left to guess work, a manufacturing plant that provides in a big way for accuracy and efficiency, this is the force that, under intelligent and masterful superintendence, has wrought the marked superiority in Kodak Products.

If it isn't an Eastman, it isn't a Kodak.

EASTMAN KODAK COMPANY, ROCHESTER, N. Y., *The Kodak City.*