As an example of the use of the equation suppose it is desired to know which of two coals, A or B, is the more economical, the prices and analyses being as follows:

	A	B
Cost per long ton.....	\$ 3.00	\$ 3.50
Per cent water.....	4.25	3.50
Per cent dry ash.....	10.25	8.00
B. t. u. per pound dry coal.....	13,500	13,900

Taking 8 as the standard ash we obtain by substitution in (5) \$0.1044 for A and \$0.1167 for B as the relative costs per 1,000,000 B. t. u. A is therefore the cheaper coal and the extra price of B is greater than is justified by its better quality.

The chart for the solution of these equations is 30 inches square. It is divided by a horizontal and a vertical line into four quadrants. On the horizontal axis to the right of the vertical axis is indicated the price per long ton, a , from \$2.00 to \$4.40 by \$0.01 (scale, $\frac{1}{16}$ in. = \$0.01). The vertical line above the horizontal represents the cost per long ton dry coal, c (same scale), but the values are not indicated. In the first quadrant are diagonal lines representing percentages of water from 0 to 12 and are plotted according to Equation 1. Any two points are plotted for each line. Zero per cent water is of course the diagonal of the square, and the others are above it.

Distances along the horizontal axis to the left of the vertical axis represent the cost per long ton of dry coal corrected for ash, f (same scale as before), but the values are not indicated. In the second quadrant are diagonal lines representing the difference between the percentage of dry ash and the standard ash. In the cut the standard ash is taken as 8 per cent and is so marked, the others being the actual percentages of dry ash. These lines are plotted according to Equation 2 for positive values of $(d - e)$ and by Equation 3 for negative values of $(d - e)$. The standard ash, 8 per cent dry ash in the chart, is, of course, the diagonal of the square. The others are parallel and range from $e - d = 4$ (in the chart 4 per cent ash) to $d - e = 19$ (in the chart 27 per cent ash).

On the vertical line below the horizontal are indicated the cost per million B. t. u. from \$0.060 to \$0.180 (scale $\frac{1}{8}$ in. = \$0.001). In the third quadrant are diagonal lines representing the dry B. t. u. from 10,000 to 15,000. They are plotted according to Equation 4.

This chart is framed with a thick glass plate with bevelled edges such that the wooden frame comes just level with the face of the glass. It is then fastened to the wall and used in the following manner: A T-square with the head against the left side of the frame is laid along the horizontal axis and the point corresponding to the price per ton of the coal in question is marked upon it or indicated by holding the thumb nail at the point. This point is then projected vertically upward by raising the square until the point intersects the line corresponding to the per cent of water. Without moving the square the point in the third quadrant where it intersects the line representing the difference between the ash and the standard ash

(or in the chart the per cent ash) is marked. This point is projected vertically downward by lowering the square until it intersects the line representing the B. t. u. The point where the edge of the square intersects the vertical axis indicates the cost per million B. t. u. Fractions of per cents, etc., are easily estimated and even when this is done the result obtained can always be checked by \$0.0004 or less.

ATLANTIC SUGAR REFINERIES, LTD.
ST. JOHN, NEW BRUNSWICK, CANADA

A THERMOSTAT OR CONSTANT-TEMPERATURE CABINET FOR THE FLOUR-TESTING LABORATORY

By C. H. BAILEY

Received October 11, 1915

The making of yeast-leavened bread is a biochemical process, involving the use of living cells in the production of the gases of fermentation. The CO_2 which expands the dough is derived from certain sugars by the action of the yeast enzyme, zymase. The activity of this enzyme, or group of enzymes, is influenced by several factors, one of the most important of which is temperature. Aberson¹ found that 2.7 times as much sugar was fermented by yeast at 28° as at 18°. The other ferments in the dough, including the natural enzymes of the flour, and those due to the presence of bacteria and fungi, are similarly affected by temperature variations.

It is evident therefore that in making comparative tests involving the use of living yeast cells, the control of the temperature is an important item. This may be eliminated as a variable by the use of suitable thermostats or constant temperature chambers. Many laboratories are making flour tests, which embody yeast-fermentation, without adequate means for the production of maintenance of the proper temperature. Chambers or cabinets are in use which are not uniformly heated. Electric lamps are frequently used as the heating element in a manner which precludes uniform heating unless fans are employed for the circulation of the air. Usually no provision is made for the automatic control of temperature, which may fluctuate within rather wide limits, depending upon the vigilance of the operator, and the facilities which are afforded for varying the heat supplied.

Since this laboratory has had occasion to conduct a number of investigations requiring the use of a thermostat for dough fermentation, our attention was turned to the construction of an adequate device for this purpose. It was desired to make this of a type which would not only be capable of the proper control, but which could be duplicated at a reasonable cost, and operated by a person without much knowledge of physics. The thermostat when completed proved so satisfactory for this purpose that it is believed a description of it, and a statement of the reasons governing the style of construction adopted, might be of interest to others engaged in a similar line of work.

The electrical heating element offers marked ad-

¹ Aberson, *Rec. trav. chim. Pays-Bas*, **22** (1903), 100. Cited by Euler, "General Chemistry of the Enzymes," translated by Pope, p. 241, New York, 1912.

FIG. I—CABINET IN USE

vantages over other possible sources of heat. It is clean, dependable, easy of operation and control, and involves no serious risks of shock or fire if properly constructed and installed. This method of heating was accordingly adopted. Neither this nor any other heating system, where an accurate control is necessary, can be made entirely fool-proof. Some knowledge of the properties of electricity is desirable to secure the best results. This is especially true if the specifications and details of construction given in this paper are to be departed from. While all the work of making and installing the heating elements in the cabinet in this laboratory was done by the writer, the services of an electrician may be necessary when one is not familiar with such work, or where certain shop facilities are not available.

The cabinet was made with sufficient space for conducting 24 baking tests simultaneously if used from

FIG. II—FACE OF CABINET

both sides. One face is provided with twelve doors, and the other has a "piano-box back" which can be removed in one piece and a face having twelve doors substituted. If the work of the laboratory is voluminous enough to justify it, doors may be provided on both faces at the outset. Where the cabinet can be used only from one side, the back may be glued on. A depth of 18 inches permits of setting two ordinary fermentation vessels or baking-pans one behind the other. This depth can be reduced if the cabinet is used only from one face. Any reduction in the cubical contents of the cabinet must necessarily be accompanied by an increase in the length of wire used in the heating element.

The doors were made 8 in. wide $\times$ 10 in. high, with panes of glass 5 $\times$ 7 in. Where the space is limited, the width of the doors may possibly be reduced 1 in. each, thus shortening a cabinet of this capacity 6 in. The 8-in. door is more desirable, as it reduces the liability of striking dishes and pans when introducing or removing them. Small doors are preferable to fewer large doors because of the reduced exposure when the doors are opened to introduce or remove the vessels. A space of 5 in. between the upper and lower rows of doors was provided so that the heating coils between shelves would not be too close to the doughs on either side of them.

The inside of the box is virtually an undivided space. The two shelves were made by bending the ends of $\frac{3}{16}$ -in. iron rods at right angles and inserting the bent ends into holes provided in cleats screwed to the inside of the box. These rods were placed at distances of $1\frac{1}{2}$ in. from center to center. The cleats were located so that they serve as stops for the doors, as shown in Fig. III.

FIG. III
DETAIL
OF
CROSS-SECTION

The electrical heating elements were made by winding No. 20 Advance resistance wire around a $\frac{1}{4}$ in. iron rod. Coils wound in this manner possess sufficient resiliency to eliminate any considerable sagging and to take up the expansion on heating. The wire was manufactured by the Driver-Harris Wire Co., of Harrison, N. J., and has a rated resistance of 287 ohms per 1000 ft. For use on a 220-volt current, 20 coils, each 15 ft. long, were suspended beneath the lower shelf, and 10 coils, each 10 ft. long, beneath the upper shelf. The coils were supported by porcelain knobs at a distance of $3\frac{1}{2}$ in. below the shelves in each instance. The end coils under the lower shelf parallel the end of the box at a distance of 2 in., while the other coils of this set zigzag back and forth across the box, the knobs to which they are attached being 6 in. apart. The end coils of the upper set parallel the end of the box at a distance of 3 in., and the porcelain knobs are 13 in. apart. These knobs should be attached by the cabinet maker while the cabinet is in course of construction. The scheme of attachment is shown in Fig. IV.

This method of distributing the heating elements has been found to give reasonably uniform temperatures in all parts of the box. Uniform heating cannot be effected when the coils (or lamps if used) are all beneath the lower shelf of a two- or three-shelf cabinet, and there is no provision for air circulation by fans. The 400 ft. of wire has a resistance of 115 ohms, and since the 30 coils are in series, a current of 1.9 amperes is drawn on 220 volts. This furnishes more heat than is necessary to maintain the air in the cabinet at from 28 to 32° C. when the air of the room is 22° C. The

current is accordingly flowing only part of the time when the thermostat is used under these conditions. The cabinet may be employed for other lines of investigation at higher temperatures, which would be

FIG. IV—METHOD OF ATTACHING HEATING COILS

impossible were it wired for use at only one temperature. If desired for dough fermentation exclusively, at the temperatures mentioned above (28 to 32°C . or 82.4 to 89.6°F .) from 600 to 700 feet of wire should be used instead of 400 feet. This should be distributed between the upper and lower sets in the same proportions as given for the 400 -foot coil, *viz.*, 25 per cent above and 75 per cent below.

The temperature of the air in the box is controlled by a thermoregulator. For this purpose the device manufactured by the Apparatus and Specialty Company of Lansing, Michigan, has been found quite satisfactory.¹ If the heating elements were in series with the thermoregulator the contact points of the latter would be rapidly destroyed. A circuit-breaking device or relay switch was accordingly devised, the magnets of which are in series with the thermoregulator. Two 16 -candle-power carbon lamps in series are used as resistance to reduce the current which flows through the thermoregulator and relay magnet series. The current which passes to the heating elements is broken

FIG. V
DIAGRAM OF WIRING

through carbon contacts in the relay. These contacts are moved in one direction by a spring, and in the other by the electromagnets. The general scheme of the wiring system is shown in Fig. V. The thermostat

¹ Since writing this paper the No. 5 thermoregulator with condenser manufactured by the Chicago Surgical and Electrical Company has been tested and found satisfactory for use in this thermostat. It costs $\$10.00$, and since no relay and carbon lamps are required when it is employed, the cost of the complete thermostat is reduced by $\$5.80$. The wiring system is also simplified.

thus arranged does not vary more than 0.5°C . if properly adjusted.

The heat-regulating system may be rendered more efficient by having a variable external resistance or rheostat in series with the heating elements. While not essential, this can be employed to reduce the number of makes and breaks occurring in the thermostat. A little experience with a thermostat enables one to judge of the proper additional resistance to insert by means of the rheostat when the surrounding air temperature is known. A rheostat of this kind can be purchased for about $\$8.00$, while a satisfactory one may be constructed by anyone with mechanical ingenuity for $\$4.00$ or even less.

The cost of the completed thermostat is shown below. The cabinet in this laboratory was built of clear cypress, although white pine could possibly be used at a slightly reduced price. It was finished inside and outside with white enamel paint. The figures represent only the price of the materials. A rheostat is not included, as this is a non-essential though desirable accessory. The cost of winding and installing the heating elements is omitted as this would vary with the efficiency of the person employed. About 4 hours were required to wind and install the coils and make the electrical connections described in this paper.

COST OF COMPLETED THERMOSTAT

Cabinet.....	\$40.00
1.25 lbs. No. 20 advance resistance wire.....	1.88
Thermoregulator.....	7.00
Circuit breaker or relay.....	8.50
2 16-c. p. carbon lamps.....	0.30
1 15-ampere knife switch with fuses.....	0.75
25 feet No. 14 insulated copper wire.....	0.25
3 doz. split porcelain knobs.....	0.75
TOTAL.....	\$59.43

The writer does not claim that the features of this cabinet possess any marked originality. The ideas expressed in its construction were gained from several sources. The device as finally assembled possesses a serviceability that is outstanding, however. It gives added value to tests conducted by empirical methods, as any fermentation or baking test must be. No laboratory concerned with such work can long afford to be without a uniformly heated, automatically controlled device of this character which can be obtained at such a reasonable cost.

CEREAL AND FLOUR LABORATORY
DIVISION OF AGRICULTURAL CHEMISTRY
MINNESOTA AGRICULTURAL EXPERIMENT STATION

NOTE ON THE RESULTS OF ANALYSES ON FERTILIZER SAMPLES TAKEN WITH DIFFERENT STYLES OF SAMPLERS¹

By F. B. CARPENTER

Received October 20, 1916

Having noticed the low results in ammonia on samples of fertilizer taken with the ordinary half round sampling tube, on goods which we had every reason to believe contained the guaranteed percentage of ammonia, an experiment was made to determine the

¹ Presented at the 53rd Meeting of the American Chemical Society, New York City, September 25 to 30, 1916.