WORM GEAR.

By F. W. LANCHESTER, M. INST. C. E.
(MEMBER OF COUNCIL.)

Introductory.

THE main interest that attaches to worm gear from the point of view of the Automobile Engineer is its application to the rear axle transmission of a motor car. Worm gear and screw gear, it is true, are applied to some small extent to accessory purposes, such, for example, as the driving of the valve gear or the magneto in the engine, or the steering motion transmission on the chassis, but these applications are of quite secondary importance.

Since the main function of the axle transmission is to transmit power with the smallest possible loss, the question of efficiency becomes one of first, and in fact is of vital, importance.

In the present paper the high efficiency power transmission worm gear will be the main subject of discussion, but for purposes of comparison and as illustrating points of importance, screw gear and motion transmitting worm gear will not be excluded.

Power transmitting worm gear for motor car use requires to comply with two main conditions: (1) it must give an efficiency comparable, if not equal or superior, to the efficiency of the alternative types of gear, i.e., bevel or chain; (2) it must be of less weight and size than, or approximately the same weight and size as, a bevel gear of equal horse-power capacity. It is unnecessary to mention *silence* as a third condition, since this is the point on which worm gear is notoriously beyond reproach.

Compared to other forms of gearing on the score of efficiency, modern worm gear is well able to hold its own; the efficiency of chain gear is variously given as from 93 per cent to 97 per cent, and bevel gear according to the tests of M. Faroux* has an efficiency of

* *L'Auto*, Nov. 1912. A comparison of results given by M. Faroux for a parallel worm and a bevel gear is shown plotted in Fig. 1, accompanied by a

89 per cent; this is probably too low an estimate. Samples of Lanchester worm gear taken from stock at the Daimler Works showed efficiencies varying from 95 per cent to 97 per cent, as tested and certified by the National Physical Laboratory.

On the score of weight and compactness the Lanchester worm gear does not compare unfavourably with bevel gear; the size and weight of a rear axle for a given duty is approximately the same for both types of gear.

1. Lanchester worm. Nat. Phys. Lab. Report.
2. Bevel. (Faroux.)
3. Parallel worm. (Faroux.)

FIG. 1.

Apart from considerations of the load carried, the efficiency of worm gear or screw gear is a function of the worm angle.[†] Neglecting journal and thrust friction, or including such bearing friction in the total reckoning of tooth friction (we may refer to the combined friction as the *effective* friction), the best efficiency is

curve representing the Lanchester worm from the Nat. Phys. Lab. Report. The author is of opinion that both curves representing M. Faroux' results are too low.

[†] The angle made by the worm spiral to a plane normal to the worm axis.

reached when the worm angle is 45 degrees *minus half the effective angle of friction*.

When the efficiency is high it is convenient to remember that the efficiency at this maximum condition, is approximately $1 - 2\mu$ where μ is the coefficient.

Thus, if $\mu = 0.02$ the efficiency is $1 - 0.04 = 0.96$, or 96 per cent. The subject is discussed more fully in the body of the paper.

The *maximum load* that can be transmitted by any gear pair depends mainly upon the type of worm or screw gear employed. It depends, in fact, upon what tooth pressure the gear will stand without expelling the lubricant from between the engaged surfaces or without crushing or distortion of the materials employed. It will be shown later that in some cases the limit is not the oil film, but rather the hardness of the materials of which the worm and wheel are constructed.

There is some confusion as to terms in connection with worm gear. The term itself generally accepted in this country is possibly a misnomer. Alternative terms sometimes used are *screw gear*, *skew gear*, *helical gear*, etc. In the present paper the term *screw gear* is used to denote gear in which the teeth of the two component elements are true parallel screws; the term *parallel worm gear* to denote worm gear in which one element only (the smaller element) is a true parallel screw, and in which the wheel is of the hollowed form; and *hollow worm gear* for the type in which both elements have hollowed faces, that is, the type commonly known as Hindley gear. There is a fourth type, in which the wheel is a true screw gearing into a hollow-faced worm. This type does not come under discussion.

Historical.

The history of the application of worm gear to the main transmission, that is to say to the back axle, of the motor car, is in fact the whole history of the worm drive that is of interest to the present day Automobile Engineer.

The author, after a careful examination of the problem, designed and built in 1896 a special machine for the production of gear of the hollow or Hindley type (Brit. Patent 13433 of 1897), and fitted up his first car with worm gear the following year. At that time the Hindley worm was a known text-book device and was probably in use somewhere, but the author had at that time neither seen nor heard of a worm gear of the Hindley type in successful operation.

The only case of prior use of a worm transmission of any kind in road automobiles known to the author, is that of an electric vehicle exhibited in London (at the Stanley Show) in 1896; it is not known whether the said vehicle was ever put to run on the road.

Prior to the advent of the petrol car (and more generally the road automobile) it is well known that tram cars had been successfully propelled by worm gear, notably in Germany*; the author lays no claim broadly to the introduction of worm gear for locomotive purposes.

From the date of the fitting of the first worm gear transmission in 1897, every Lanchester car built has without exception been fitted with worm gear, and until about five years ago the whole of the said gear had been produced by the one original experimental machine. Since that date (about 1907), new and improved machines have been designed and constructed, and in addition to the enlarged worm gear plant at the Lanchester Works, a complete plant has been laid down at the Daimler Works, with an output capacity of one million horse-power per annum.

A Lanchester worm gear plant has also been established at the works of the Warner Gear Company of Indiana (who hold the American rights), which is capable of dealing with the present demand in the U.S.A. and Canada.

At the present time there are many competitors in the field; in almost every case the alternative offered is the true screw or parallel worm. The parallel worm has been able to find a certain number of advocates, but the present tests appear to show that it is inferior to the Hindley type (as exemplified in the Lanchester gear) both in efficiency and load capacity.

The author makes the assertion without fear of contradiction, that the present position of worm gear in its application to the automobile is the definite outcome of the uninterrupted success of the Lanchester worm gear during what may be termed its probationary period, when applied exclusively to the Lanchester car, and its subsequent adoption by some of the leading firms in this country.

One of the obstacles that beset the introduction of worm gear some twelve or so years ago, was the then existing prejudice on the score of efficiency. The Lanchester worm gear of to-day shows an efficiency of from 95 per cent to 97 per cent under varying conditions. (*Vide* National Physical Laboratory Report, Appendix I.)

* Reckenzaun.

The Lanchester worm gear of 1899 was cut by the same methods on the same type of machine from materials to approximately the same specification, yet Mr. Worby Beaumont,* in his book on the Motor Car, assessed the mechanical efficiency of the Lanchester Car at 31·9 per cent, a most palpable mistake, but nevertheless one which doubtless misled a great number of readers. Actual determinations of the gear efficiency made before the advent of the new testing machine from the actual gear, gave 94 per cent as the efficiency of the gear in question, with a possible error of 2 per cent plus or minus.

Probably the most recent development of importance in connection with worm gears is the new method of testing introduced in the machine built to the author's design by the Daimler Company, Ltd., and described in the present paper. By means of this machine, efficiency tests can be made with a degree of accuracy not hitherto obtainable—the average error is probably less than one-tenth of 1 per cent, the National Physical Laboratory (the results of whose tests are given in Appendix I.) certifying the accuracy as definitely within one-fifth of 1 per cent from the truth.

The importance of rapid and accurate measurement of efficiency can scarcely be overrated; minute differences in the physical condition of the tooth surfaces, or in the extent of the tooth clearance, or in the character of the lubricant are detected, and the effect or efficiency determined, with speed and certainty, and so the introduction of greater refinements is rendered possible; without doubt even higher efficiencies will in the near future be reached.

Controlling Factors in the Proportions and Design.

The determination of the appropriate design of worm gear for any given duty is one that, like every other problem in engineering, depends upon the conditions that are given. In some cases the

* In the paper as issued before the meeting, Mr. Beaumont was incorrectly quoted by the author as giving the efficiency of the transmission at 37 per cent. This statement, to which Mr. Beaumont has taken exception in the discussion, has been revised as above to correspond actually with the text of Mr. Beaumont's work. The author's original figure of 37 per cent was based on the figures now given after making a reasonable deduction to allow for other losses of power. The point at issue is not, however, one merely concerning a few per cent one way or the other; it rather involves the fundamental question of what can be properly termed *mechanical efficiency*; in the author's opinion this term is improperly used by Mr. Beaumont in connection with the figure above cited.

ratio of the transmission is a determining factor, it being essential to make some definite speed reduction ; in other cases considerable latitude may exist as to the ratio of gear that may be employed, the external conditions, i.e., the revolution speed of the motor or some member of the transmission drive, being variable. In most cases it is the torque or horse-power to be transmitted that mainly determines the size and standard of the gear to be employed. In the application of worm gear to an automobile the most important variable factor is the *weight of the vehicle*. The road wheel diameter varies comparatively little on any given class of car, otherwise it would be more accurate to say that the main variable is the *torque on the driving axle*. The fact that the road wheels in common use vary but little in diameter means that the torque on the rear axle for a given road duty is approximately proportional to the weight of the machine. It is quite true that one of the important factors in the resistance of an automobile is wind reaction, but the *maximum load* on the transmission is determined by the resistance on heavy gradients where the speed is insufficient to render windage of importance. On the lower gears the torque transmitted by the worm due to gradient alone is considerably greater than the torque required to overcome the combined resistance of gradient and windage on the higher gears. A more important fact is probably that in actual road usage the high-powered car is not habitually driven on the level against wind resistance materially faster than a low or moderately powered machine.

A very interesting point arises in considering the influence of speed from the present aspect ; it will be seen on examination of the curves of efficiency (N.P.L. report) that, as a general rule, efficiency is one or two per cent lower at very low worm speeds than at worm speeds of 800 to 1,200 revs. per minute (Fig. 2) ; this not only means that the loss of power is greater, and therefore the heat generated on the worm teeth is greater, per revolution of the worm, but it also means (which is really more important) that the lubrication film is thinning down considerably. If in two comparative cases we suppose the given motor car to be climbing a steep hill, in one case on its direct gear with a comparatively high velocity, and in the other case on its low gear at a comparatively low velocity and therefore transmitting considerably less horse-power, the worm may be under less severe conditions at high speed in spite of the fact that the horse-power transmitted is greater ; consequently we have the paradoxical fact in the application of worm gear to the

motor car that in two cars of the same weight a given worm gear will stand up as well or better in the case of a high-powered machine than in the case of a low-powered machine. This result, which follows almost logically from the tests conducted by the representative of the National Physical Laboratory at the Daimler Works, has long been known to the author as a matter of experience, and the reason has been fully appreciated, but it has only been since the new Daimler testing machine has been built that it has been possible to put so unexpected a fact definitely on record. The practical conclusion had been reached

FIG. 2.

previously as the result of experience gained in applying the same standards of worm gear from year to year to successively more powerfully engined cars. It was found that whereas an engine of higher power gave no trouble at all, some attention was needed when the weight of the car was increased. During the last ten years, during which period car weights have gradually increased (principally owing to the demand for luxurious body work), it has become increasingly necessary to pay attention to the quality of the bronze and the hardening of the worm.

In considering the design of worm gear for a motor car, whether it be a pleasure vehicle or a commercial vehicle, we are thus led to

the conclusion that the main factor in determining the size of the worm gear is the torque on the driven axle. Now, if it is proposed to propel any given vehicle with an engine of specified horse-power, we know that the said horse-power may be obtained by large cylinders and slow revolution speed, or smaller cylinders with a higher revolution speed; it is evident, therefore, that we require ready means of comparing the power transmission capacity of worm gears of given centres, under conditions of constant *driven* torque and variable speed reduction ratio. In the present connection it may be pointed out that in certain cases (especially where noise is unimportant) a gear may be used between the motor and worm shafts, in place of the direct drive, in order to accommodate a worm standard that might otherwise be unsuitable.

FIG. 3.

It is evident that the safe torque on the low speed shaft, which we may for the purposes of the present paper assume to be the driven shaft, will depend very much for given centres of worm and wheel upon the ratio employed. We know from what has already been said that it is desirable to use an angle of about 45 degrees at the top of the worm wheel teeth, that is, in the bottom of the teeth in the worm neck. This means that the diameter ratios of worm and wheel at the bottom of the worm teeth should be approximately those of an ordinary pair of spur gears designed to the same ratio. A second factor in the present connection is the question of tooth pressures; we know that the load limit on the teeth of a worm gear is in the main a measure of the projected area of the worm wheel teeth, this area being determined by the depth of the tooth

and the width of the tooth, both of which quantities are tied down by the diameters of worm and wheel. In Fig. 3 we have three diagrammatic drawings (a), (b), and (c), representing gears of ratios respectively 10 to 1, 4 to 1 and equal; the tooth load which these gears will be capable of taking will be given by the shaded areas, and the torque on the driven member will in each case be proportional to this area multiplied by the radius R ; from the relative figures for the respective gears laid out in the drawing we see that the torque transmitting capacity of the gear is least for the big ratios, that is, in motor car phraseology, for the low gears, and greatest for the high gears. We may represent the torque capacity for the centres given roughly by the curve as in Fig. 3 (d).^{*} We can refer to this torque curve when we wish to know what capacity a given gear will have or conversely what gear centres it is necessary to select for any given vehicle. Thus, the selection of a suitable gear is reduced to four factors, the weight of the vehicle and the diameter of the driving wheels on the one hand, and the centres of the gears and the torque curve, which we are able to obtain (as shown in Fig. 3), on the other; it is thus quite a simple matter to specify the proportions of the worm gear required for any given duty.[†]

In the design of different types of gearing, whether worm gear or spur gear in any of its varieties, the important factors differ considerably according to the type of gear employed, and even according to the ratios required; thus in spur gearing the strength of the teeth is a very important factor; in power transmitting worm gears (for certain reasons which will be understood later) the strength of the teeth needs rarely if ever to be considered; designs which fulfil the other necessary conditions are usually found to possess ample strength from the point of view of possible tooth breakage. Again, in spur gearing the pitch diameters, or, in the case of involute gears, the rolling circles, require to be selected exactly in the ratio of the transmission, and no departure is permissible; in worm or screw gear, on the other hand, no such rigid condition exists, and the angle of the gear teeth

^{*} The curve shown in Fig. 3 (d) would evidently return to zero if continued to the lower (worm wheel) axis: it would therefore be a round topped curve as suggested by the dotted line. The assumption of a 60 degree angle for all ratios is evidently a rough and ready rule and obviously at fault.

[†] It is frequently found that a further factor (i.e., road clearance) requires to be taken into account.

may be selected to accommodate any diameters required. For given gear centres the gear ratio is a function of two variables, namely, the size ratio of the blanks and the tooth angle, whereas in the ordinary spur gear, the one variable alone determines the gear ratio.

In designing or laying out worm gear, the use for which it is required is one of the most important factors in imposing limitations to the proportions that may be adopted. Thus, for a motion transmitting worm gear where mechanical efficiency is of no importance, the only limitation is that the tooth pitch on the driving member should not be too steep—it must make an angle to the axis

FIG. 4.

greater than the *effective* angle of friction. When it is desired that the gear should be self-locking, that is to say, “*irreversible*,” the tooth angle itself must be less than the effective angle of friction; but assuming efficiency to be unimportant, within this angle it may be as small as we please. When the conditions require that the gear shall be self-locking, and at the same time it is important that the efficiency shall be as high as possible, the angle of the worm tooth must be less than the angle of friction, but should be made as near to the angle of friction as practicable. Under these circumstances the maximum limit of efficiency is 50 per cent. When a worm or screw gear is required essentially for power transmission, the angle of the worm must be made about 40 degrees if the highest

efficiency is to be obtained. The efficiency for different worm angles is given by the equation

$$\frac{\tan \theta}{\tan (\theta + \mu)}$$

where θ = worm angle and μ = effective co-efficient of friction.*

The efficiency appropriate to different angles in accordance with this equation is given in Figs. 4 and 5, in which ordinates represent efficiency and abscissae the cotangent of angles; the actual angle values are also figured. In Fig. 6 this curve is given transformed to correspond to a gear example on the left of the figure. In view

FIG. 5.

of the fact that the angle of tooth in a screw or worm gear is not constant at different points of the tooth, we must always consider that we are using a certain portion of the efficiency curve shown in Fig. 6, and it must be our object in designing to utilise the highest part of the said curve. It will be noted that an error on the side of making the worm angle small, penalises the efficiency far less than departure in the opposite direction.

The question of the variability of the angle discussed in the preceding paragraph in the case of the worm gear, relates not only to the variations at different heights of the tooth, as in the case of the screw gear, but also to variations due to the hollow form of

* The angle of friction in circular measure as employed in the equations.

face, and in estimating the expected efficiency of any gear it is necessary to consider the total range of angle presented by the gear teeth.

The need for high tooth angle, otherwise termed quick pitch, necessitated by considerations of efficiency, has in itself a certain accidental influence on the tooth form; thus, in the hollow type of worm gear as exemplified in the Lanchester gear, the quick pitch would result in "undercut" if the tooth face angle itself (that is to say, the angle the faces of the teeth make to each other) is not designed to give the necessary relief. If such undercut were to exist, it would prevent the gears being put into mesh, or if by any

FIG. 6.

mysterious process they were initially created in mesh, it would be impossible to separate them. In practice, the need for avoiding undercut requires, in order to take full advantage of the useful permissible length of worm, that the tooth angle should be made approximately the ordinary standard Whitworth "V." The angle adopted by the author in all his gears is a slope of one in two.

In discussing the difference that exists between the ordinary parallel worm gear or screw gear and worm gear of the Hindley or Lanchester type, the main characteristic feature has been mentioned that both worm and wheel faces are hollow; this, however, does not fully define the difference, there is a more essential feature than the hollowness of the tooth face. Referring to Fig. 7, two diagrammatic mid-sections are shown, one of the parallel worm and the other of a worm of the hollow type, and in the latter it will be seen that the form of screw instead of being compounded of simultaneous axial and rotational motion, as in the ordi-

mary screw, has two rotational components, one about the axis

FIG. 7.

of the worm and the other about the axis of the wheel, the ratio of the two corresponding to the ratio of the gear. In

FIG. 8.

studying these figures it will at once be realized that where in the parallel worm A the surfaces of the worm and wheel

teeth require to be of rolling form as in spur gearing, in the case B considerations of this kind do not concern the designer, the tooth form may be made anything convenient, since they follow geometrically the same path. In Fig. 8 this is illustrated by showing a tooth of impossible and fantastic form; such a tooth, it is evident, would be possible except that, as drawn, the undercut difficulty would exist—the gears could not be put together or taken apart. This fundamental difference between the two types of gear must always be remembered in considering the questions of tooth form, etc. of the Hindley and Lanchester type.

It may be noted, in referring to the sections of the present paper entitled “*Generating and Cutting*,” that the method of cutting

FIG. 9.

FIG. 10.

follows the geometry of the gear as above described; that is to say, in generating, the worm cutter or hob rotates about the worm wheel axis, while the worm blank is rotated about its own axis just as is the case in the inverse operation.

If the worm wheel were represented by its plane of symmetry alone, that is to say, if the worm wheel be considered as quite a thin sheet or lamina of metal, this method of generating or cutting a worm gear would result in perfect contact along the radial width of the driving tooth during the whole period of the engagement. Since, however, the worm wheel must of necessity possess substantial thickness, there will be a certain incompatibility between the worm and the wheel due to the changes of angle of the worm tooth owing to the greater diameter of the worm at its extremities.* This is the main fact that renders it undesirable

* In the parallel type of worm gear the “incompatibility” of worm and wheel faces is far greater, due to other quite well known causes.

to use in practice more than a very moderate length of worm. In the Lanchester gear the length of worm used is such that the variation of diameter from the neck of the worm to its largest part is about 7 or 8 per cent of the total. Fig. 9 illustrates the proportions commonly figured in text-books as the Hindley worm, and Fig. 10 the proportions adopted by the author. In the Lanchester method of cutting, special precautions are taken to avoid the above-named incompatibility of tooth angle, the result of these special methods being to distribute the wear over the whole width of the

FIG. 11.

tooth face of the worm wheel, it being found practicable to utilise in this way an arc or worm wheel tooth subtending about 60 degrees of the worm axis.

It is these two quantities, the length of the worm and the arc subtended by the wheel, that determine the tooth angle required to avoid undercut. So long as the ordinary proportions are adhered to, the tooth form in Fig. 11 is found to give the necessary clearance.

In selecting the tooth form from the efficiency diagram, much depends upon whether the designer has an entirely free hand. It is undesirable from the manufacturing point of view to make a

large number of but slightly differing blank sizes. It is found convenient from the works standpoint to cover a group of two, three or more gear ratios by one size of blank. When the designer has *carte blanche*, it is, as already stated, found to be a good rule to give the bottom of the tooth of the worm an angle of about 45 degrees, and in arranging a number of gears to be cut from one standard size of blank, it is convenient and good practice to adopt 45 degrees for the highest gear ratio. As an example, the 6 inch centre Daimler-Lanchester series may be cited in which

FIG. 12.

one standard of blank is adopted for various ratios as tabulated below ; in this case the highest gears, i.e., 10/31 and 10/33 are of rather steeper pitch than the 45 degrees laid down.

10/31	49 deg.
10/33	47 deg.
9/32	45 deg.
9/34	43 deg.
8/33	39 deg.
8/35	37 deg.

It will be noted that in considering the torque transmission capacity of these different gears, the torque transmission is settled by the standard blank, and so, where it is desired to avoid wide centres, it is good practice to design a worm with rather a less angle than theory requires in order to keep up the size of the worm blank; in other words a slight sacrifice is made in the efficiency in order to permit of the required load being carried. For omnibuses and commercial vehicles it is the author's practice to adopt this compromise; it will be seen on reference to Figs. 3 and 6 how comparatively small a sacrifice of efficiency is necessary in order to gain largely in the torque capacity of the gear.

In ordinary screw gear the two component parts, the driving and driven elements, are symmetrical both as to design and method of manufacture. The correct basis of tooth form for a pair of screw gears is a section taken at right angles to the teeth. On such a section the two pitch lines or rolling circles (the base circles in the case of involute teeth) appear as ellipses, the point of engagement being at the extremities of their respective minor axes, Fig. 12. At the point of engagement the ellipses may be approximated by arcs of circles, and the cutter used for generating the teeth must be selected appropriate to these circular arcs, and otherwise as if they are required to cut a pair of gears represented by the two circles in question, with a fictitious number of teeth to correspond.

In ordinary parallel worm gear the component gears are not symmetrical either in design or in any other respect; the worm is commonly produced on the same basis as if required for an ordinary screw gear and the counterpart of the worm, that is to say, a duplicate of the same, furnished with cutting teeth, is used as a hob for forming the teeth in the wheel, this being sometimes first gashed on the milling machine. According to another system the worm is treated as a rack, the form of worm tooth being a simple "V," and the wheel is hobbled from a counterpart cutter as above described. The latter method is practically speaking as good as the former in all cases where the worm pitch is small, as in motion transmission gear, owing to the fact that the longitudinal section of the worm itself does not give a tooth form materially different from a section at right angles to its teeth; in other words a section at right angles to the teeth of a fine pitch screw gives a tangent circle of so great a radius that it is legitimate to treat the tooth form as a rack tooth. In power transmission worm gear, however, where the mean tooth angle is approximately 40 degrees the assumption of a rack form.

of worm tooth cannot be accurate ; this method of generating has, however, come into fairly common use amongst the advocates of the parallel worm transmission ; we must presume from the fair measure of success achieved that the resulting wheel form of tooth is one appropriate to the rack section, and that the disadvantage of designing the tooth form on incorrect assumption is not in practice a serious matter.

In the hollow (or "hour glass") type of worm, as in the Hindley and Lanchester gear, the conditions theoretically are such as are consistent with symmetrical treatment ; thus, if we consider the particular case of an equal transmission (that is to say, a one to one ratio) there seems no reason why the gears should not possess perfect skew symmetry about their pitch point ; in other words, in a number of such sets of gear there appears to be no reason why, from a purely theoretical standpoint, worms and wheels should not be mutually interchangeable. It is less easy to define, however, what kind of tooth form would be required to bring this condition about, and it is still more difficult to define the tooth form for cases where the ratio of the drive is not equal, that is, where the worm and wheel contain different numbers of teeth. It is perhaps even more important that if we knew the tooth form, that is to say, if we could formulate a theory which would treat worm and wheel for all cases on a symmetrical footing, we might be no nearer producing the required form of tooth in the machine shops. In practice it is necessary to begin with a tool of some kind that can be made according to a definite simple geometrical plan, that is to say, a tool with a cutting edge of some definite form in some definite position, such as can be laid out on the drawing board and afterwards produced in the tool room. From such a tool it is next necessary to produce either the worm or the wheel, and from the form of worm or wheel so produced, to develop a hob by which the counter-part gear is cut ; there seems to be no possibility of evading some such procedure, and given that this is the case, it is evident at once that we are unable to treat the problem symmetrically. The difference between the author's system of generating worm gear and previous methods depends in the main upon the special line of procedure by which the master tools are initiated, and in the worm-cutting machine and tool outfit which are employed in carrying the method into effect.

The maximum horse power that can be transmitted through a pair of gears of given design depends upon the pressure that can

be safely transmitted between the teeth. In an ordinary journal bearing, the transmission of pressure, and the limiting pressure that may be used, have a more or less definite meaning; thus in the case of a plain bearing the pressure so specified means definitely the mean pressure on the oil film. In the case of worm gear, however, it is necessary to make use of a convention in speaking of the tooth pressure, since we do not know the precise area over which

FIG. 13.

the re-action at any instant is distributed. It has been the custom of the author for many years to express the force transmitted by the teeth as a *pressure per square inch on the projected area of the worm wheel teeth*; thus Fig. 13 represents a standard six-inch centre motor car gear, and the shaded area represents the projected area of the teeth on which as a convention the load is supposed to be distributed. On this basis worm gear cut according to the author's

system will carry easily one ton per square inch, and is good for an overload of two or three times that amount, in fact a load of two tons per square inch may be looked upon as a safe load, inasmuch as the gears will run satisfactorily with such a load for an indefinite period. Taking a car and passengers weighing two tons gross on a one in twelve gradient, we have roughly a traction resistance with allowance for road resistance of 0.2 ton which represents on the worm teeth a force of 0.8 ton on a projected area of approximately half an inch, that is to say, 1.6 tons to the inch; the gear in question will work quite satisfactorily and will show no signs of distress under these conditions.

It is difficult to form directly any estimate of what such so-called pressures mean when considered as transmitted through the actual surface of proximate contact; it is at least remarkable that pressures of this magnitude should be carried, even on the assumption that the load is distributed over the whole surface without breaking the oil film, since far less pressures are considered extreme loads on ordinary journal bearings. When, however, it is considered that the actual area in contact, or rather the actual area of the oil film under pressure, at any instant must be many times less than the total projected area of the tooth, the matter becomes more amazing. The best estimate of the actual load carried is obtainable from the behaviour of the bronze under extreme duty. It is found that in the case of a full load of a heavy Limousine, nearly three tons total weight, the bronze will slowly yield, unless of more than fifty tons crushing strength (Brinell test); and the manner of a failure of this kind denotes that the bronze has slowly yielded by a kind of spinning action to the pressure applied. The precise symptom of failure from over-load is that after some 5,000 to 10,000 miles running, the teeth will be found to have increased in height, owing to the pressure on their face, so that they bottom on the worm teeth. If under these conditions they are put in a lathe and cropped they will run for another considerable period before showing the same trouble again. It is evident from these observations that the pressure transmitted from the worm to the wheel is *of the order of* fifty tons per square inch, and we might consequently conclude that metallic contact *must* be taking place. However, efficiency tests at heavy loads show clearly that the oil film is still intact and as perfect as ever. Efficiencies at extreme loads still reach 96 per cent or thereabouts, corresponding to a co-effi-

cient of friction of only two per cent. It is quite evident, therefore, that the oil film is, under these conditions, still intact, and supporting a pressure sufficient to crush the bronze itself. This is certainly an astonishing result. It means that the pressures transmitted by an oil film under the conditions in which a lubricant is used in worm gearing are about one hundred times as great as are deemed good practice in the lubrication of a plain journal. Such results appear to call for thorough investigation of the circumstances under which lubricants are commonly employed in journal bearings; there seems no final or fundamental reason why improvement of a revolutionary character might not be effected in journal design, in view of the enormous pressure and low co-efficient of friction shown possible by a modern worm gear. The above result is, in the author's opinion, due mainly to his special method of generating and cutting; under test (as elsewhere pointed out) the Lanchester gear shows marked advantages under heavy loads over the parallel type. The chief theoretical point involved is concerned in the manner in which lubricated surfaces sweep across each other in their engagement period; endeavour was made in the Lanchester worm to cause the lubricated surfaces to take the form of an elongate strip or line *moving broad-side on* so that the oil squeezed out from the region under pressure at any instant takes its place at the point where the pressure is about to be applied. There seems no doubt that the abnormally high loads carried by lubricated surfaces in worm gear in general, and by the Lanchester gear in particular, are only carried on account of this oil chasing action. In aeronautical phraseology the load is carried in the Lanchester gear on an oil film of great "aspect ratio."

The Lanchester Worm—Generating and Cutting.

It has already been pointed out that the problem of cutting worm gear of the hollow worm or Hindley type cannot be treated on a symmetrical basis.

In the Lanchester gear the actual worms and wheels are each hobbled on a special machine, the subject of Letters Patent, No. 13433, 1897; Figs. 14 and 15. In this machine the cutter head and blank are both positively rotated, the machine being fitted with change gear wheels to give the ratio desired. The hobs or cutters are generated initially on the same machine as that on which the gears are finally cut. The process is essentially un-

symmetrical, the worm form being first generated by a single tooth or fork cutter shewn in Fig. 14, and the form so prepared then gashed in a milling machine, backed off, and "corrected" to form the master hob of which the actual working tools are copies.

From the master hob so obtained a counterpart blank in tool steel is cut which is similarly gashed and backed off, the cutter so produced being likewise only employed for the production of working tools. The original pair of master cutters is never used except for the production of working cutters.

In the case of standards for which it is anticipated large quantities may be required, the original cutters are termed the grand master cutters, and are only used for the production of master cutters,

FIG. 14.

FIG. 15.

which in turn are employed only for making working cutters; the interchangeability of the gears is thus ensured. Generally speaking this elaboration is scarcely necessary in view of the fact that one pair of master cutters may be made responsible for at least 50,000 pairs of gears without serious inaccuracy being introduced. Each set of working cutters is good for from 1,000 to 2,000 sets of gear.

The actual machine is one of the most elementary simplicity; its design was very carefully considered with a view to the avoidance of all sliding surfaces or adjustments of a nature liable to introduce backlash. The machine consists essentially of two parallel spindles, A and B (Figs. 14 and 15), connected by change gear, an ordinary spur train of gearing being employed, and a third spindle, C, driven

by fine pitch screw or worm gear from the spindle A, and mounted in a swivelling frame, D, whose motion is concentric with the spindle, A, and by means of whose motion the cutter head E is fed towards the spindle B. This feed motion is operated by gravity, the swivelling frame, D, being loaded by a suspended weight, F, consisting of about half a ton of slab weights. The feed is controlled by means of a screw acting permissively, the screw allowing the weight to descend gradually until an independent stop is reached, which is set to give the required depth of cut. This gravity type of feed mechanism has many advantages: firstly, it is entirely free from backlash, and chattering is almost unknown; secondly, the stopping of the feed does not involve the accurate throwing out of the feed mechanism, and the depth of cut, regulated by the separate screw-adjusted stop, is absolutely certain, and probably accurate to the ten-thousandth of an inch; thirdly, it is entirely unaffected by wear.

The action of the machine is the same whether used for initiating or reproducing its own tools or for cutting the worm or the wheel, the tools and blank having been set up and the depth stop set, and the swivelling frame raised to clear the work, the machine is set to work and is automatic in its action till the cut is completed. In the roughing and finishing of a gear, whether worm or wheel, three settings are necessary, and where quantities are concerned and the supply of material is available it is convenient to arrange three machines to work in a gang, namely, roughing, rough finishing, and finishing. It is always possible, but not usually to be recommended, to dispense with the rough finishing and complete the job at two settings.

Owing to the fact that during the cut the swivelling frame D has angular motion about the driving spindle A, a certain amount of inaccuracy is introduced into its motion; it is with a view to reducing this inaccuracy that the driving worm is made of comparatively fine pitch. The motion does not result in any inaccuracy of the gear, owing to the fact that the angularity of the teeth is such that the cutter clears itself as it advances deeper and deeper into the work, but it is necessary to reduce the error of motion to the least conveniently possible to avoid having an unnecessarily great contained angle of tooth face. In the case of a worm whose tooth angle is insufficient, the fouling of the entering cut leaves its mark in a quite self-evident manner at one of the extremities of the worm; a slight foul of this kind, though generally avoided, is of no real importance as affecting the efficiency or durability of the gear.

The Testing of Worm Gear.

The most important direction in which it is desirable to test worm gear is to determine its efficiency under various conditions of load and speed. Where the efficiency of any piece of mechanism is high, such tests, to be of any real service, must be carried out with a very great degree of accuracy. Thus, where an efficiency of 97 per cent or thereabouts (as in a well designed worm transmission) is obtained, it is useless to employ methods having an error of 1 per cent more or less. Any such error may be legitimately looked upon as a 33 per cent error in the measurement of the power wasted in transmission. If the tests are to tell us anything of a nature useful to the engineer in the improvement of his methods of generating, or to enlighten him as to the best conditions under which worm gear is to be employed, he must be able to detect with certainty variations in the amount of power lost of a far less magnitude than this. It might, in fact, be said that unless the *loss of power* can be determined to within about 5 per cent, the method of test must be looked upon as unsatisfactory. Thus, taking 96 per cent as a good average worm gear efficiency, the loss of power is 4 per cent, and the determination should be within an error of one-fifth of 1 per cent. This is the degree of accuracy obtained as certified by the Director of the National Physical Laboratory by the new Daimler-Lanchester testing machine.

The machine itself is described in Appendices I. and II. to the present paper. It will suffice to say here that in principle the new machine is an instrument for the direct comparative measurement of two torques acting about axes at right angles, or more generally about axes making any angle with each other, but unsuited to cases where the torque axes approach the parallel. It is evident that in any gear transmission where there is no slip the efficiency is given by the ratio of the torques of the driving and driven elements divided by the gear ratio (or multiplied by the gear ratio if it is expressed in the inverse form). Thus, if the efficiency were perfect the torque ratio and gear ratio would be identical; or if, for example, the efficiency were 0.5, the torque of the driven element would be 0.5 of what it would be on the basis of perfect efficiency.

In the Daimler testing machine the gear box containing the gear under test is mounted on double gymbals and the power input and output are taken by universally jointed shafts; for any given conditions of running it is found that there is a neutral axis about which

the torque is zero; this is at right angles to the plane of the resultant torque, and is determined by the adjustment of a sliding jockey knife edge. This knife edge and the centre of the double gymbal mounting define the line of zero torque, and when the floating system is in equilibrium the position of the knife edge gives the torque reading required. At every reading the machine is brought to its zero position about both co-ordinate axes; it is steadied by appropriately arranged dash-pots. The power transmitted by the gear is restored to the driving shaft through the medium of a bevel gear and slipping belt.

Full lines represent $2\frac{1}{2}$ tons per square inch mean distributed tooth load.
Dotted lines represent 1 ton per square inch.

FIG. 16.

The *total torque* transmitted is in every case measured immediately before the *torque ratio* is read and gives the measure of the total power transmitted; any error that may creep in between the times of reading the transmission torque to determine the horse power and reading the torque ratio to determine efficiency owing to changes in the external conditions, such as the slip factor of the belt, is of no importance owing to the fact that the changes of efficiency for such small changes of load or speed as are liable to occur are quite negligible.

Many facts of considerable importance both to the designer and to the user have been elucidated by the recent tests by the new method. Not the least important of these is the marked difference in behaviour that is found to exist between the ordinary parallel type of worm and that of the Hindley type, i.e., the Lanchester gear on which the majority of the tests were made. These tests confirm some previous roughly made tests carried out by the ordinary methods by the Daimler Company at the time they first adopted the worm drive on their rear axle. Summarized it appears that at the best the parallel worm can scarcely reach the efficiencies shown as a regular thing by the Lanchester gear; at the worst the efficiency of the parallel gear falls 3 or 4 per cent lower, this being particularly the case at heavy loads. It would appear that the oil film begins to break down in the case of the parallel worm at loads that the Lanchester sustains without loss of efficiency. The comparative behaviour of the Lanchester and the parallel worm is illustrated typically by the two curves given in Fig. 16.* The upper pair of curves relate to the Lanchester gears, the lower pair to gear of the parallel type.

A second fact brought out by these tests is, that the loss of efficiency at reduced speeds is far less than previously supposed; at the lowest useful motor car speeds it rarely falls much below 94 per cent, and it is *quite* exceptional to record efficiencies below 93 per cent.

A third fact brought out is the great variation in efficiency due to differences in the lubricant employed, and the individual character of the diagrams or curves obtained when different lubricants are submitted to test. This is clearly exemplified in the curves given in Fig. 17. The two upper curves are typical of oils of animal or vegetable origin. The lower curves represent results obtained from mineral oils. The main conclusions to be drawn (apart from indications as to the suitability of the lubricant) are—(1) That in general, mineral oils are inferior to animal or vegetable oils; (2) that the viscosity of the oil is little or no guide in the selection of an oil for the purpose in question; one might almost as well try to judge the value of beer or any other beverage by the viscosi-

* This applies to the actual cases of parallel worm tested; the author cannot vouch for other makes of worm, though there seems no reason to suppose that the results would be materially different.

meter; (3) that the efficiency may be lowered by the presence of too much lubricant in the gear box.

A fourth fact brought out is that the best efficiencies are obtained with a certain perceptible tooth clearance; the said best clearance in an ordinary motor car gear appears to be about $1/64$ in. (somewhat less than half a millimeter).

Full lines represent $2\frac{1}{2}$ tons per square inch mean distributed tooth load.

Dotted lines represent 1 ton per square inch.

FIG. 17.

A fifth fact of importance is that in the Lanchester gear the efficiency is best with quite heavy loading; there is virtually no falling off in efficiency due to overloading—at least unless carried far beyond the point at which the bronze slowly yields.

Lastly, it may be noted that the heavier loads are carried with the best results at high speeds of revolution.

APPENDIX I.

REPORT ON THE EFFICIENCY OF DAIMLER-LANCHESTER WORM GEARS TESTED FOR MESSRS. THE DAIMLER MOTOR CO., LTD., OF COVENTRY, BY THE NATIONAL PHYSICAL LABORATORY.

THESE gears were cut by Messrs. The Daimler Motor Company, Limited, on Mr. Lanchester's patented principle, designed to give constant velocity ratio at all points of contact of worm and wheel and at the same time give a thread on both worm and wheel of sufficient strength to stand heavy loading.

The tests were carried out at the Company's works at Coventry in a special machine made for the purpose and used by the Company for experimental work.

A diagrammatic sketch of the apparatus (Fig. 18) is appended to this report. The worm box A is mounted on ball bearings so as to have freedom of motion about the axis of the driving shaft (XX) and the axis of the driven shaft (YY). The driving and driven shafts are connected to the worm shaft and wheel shaft in the box by means of universal joints so arranged that any turning moment about either axis is eliminated when the box is in the balanced condition. An arm is attached to the box in the direction of the XX axis but the balance weight is not attached to this directly but to a bar fixed at right angles to the arm in a direction parallel to the YY axis and 24 inches therefrom. The balance weight is adjustable along this bar. The box was first balanced in both directions without the balance weight and the torque in the driven shaft obtained by noting the balance weight lifted at the 24 inch radius. The torque on the driven arm was then balanced by sliding the weight along the bar until the box was balanced

about axis XX. If W is the balance weight and S the distance along the bar from the arm,

$W \times 24 = \text{torque of driven shaft.}$

$W \times S = \text{,, ,, driving shaft.}$

and if there were no friction $W \times S / W \times 24 = r$, the gear ratio. To overcome the friction $W S$ has to be increased to $W S^1$, and S/S^1 will then be the efficiency ($= e$). $e = 24 \times r / S^1$. It must be

FIG. 18.

noted that the shift of the point of application of the load is not large. For example, if $r = \frac{1}{4}$, $S = 6$ in., and with 90 per cent efficiency $S^1 = 6.67$ in., so that 0.67 in. corresponds to a change in efficiency of 10 per cent. The efficiency measured during the tests varied from 93 to 97 per cent, and for the gear given above, S^1 would vary from 6.452 in. to 6.186 in. In actual work a variation of 0.01 in. from the mean position would make the box turn in one direction or the other about axis XX, and consequently

the determinations of the efficiency are probably correct to 0·2 per cent, which is sufficient for practical purposes.

Referring to the diagram (Fig. 18), the drive is taken by means of shaft B to a bevel box (C) with the large wheel driving the pinion, and the shaft D carries a pulley from which a belt E is taken, tending to drive the driving shaft at a slightly higher rate than the driving belt F. By altering the tension in this belt the pressure between worm and wheel, and therefore the torque, could be adjusted to any desired value, while the driving belt only had to supply the mechanical losses in the apparatus. The apparatus was driven by a four-cylinder petrol motor, hand controlled to give the speed required, which varied from 400 to 1,500 revs. per minute of the driving shaft. The speed was observed by a tachometer driven from the driving shaft, and this was checked and found to be reading 0·8 per cent too low, a correction of this amount being applied to its readings. The gears tested were left hand worms with the worm running in an oil bath under the wheel. The temperature was observed by means of a thermometer fixed in the top of the case and with the bulb in close proximity to the top of the worm wheel so that the lubricant was thrown off the wheel on to the bulb of the thermometer. This probably gives a fair indication of the working temperature except in the case of low speeds when the oil did not appear to be thrown off with sufficient velocity to keep the bulb covered. The lubricant used was a mixture of non-mineral oils, and its viscosity after the tests of the second and third gears (Series B and Series C) was determined.

Particulars of Gears.

The gears were of the same overall dimensions.

Steel worm, diameter at throat $3\frac{1}{2}$ in.

Phosphor bronze wheel, diameter 9-3/8 in., width $1\frac{1}{2}$ in.

Depth of thread, 7/16 in.

Series A tests were made on the 8/33 gear.

Series B „ „ 8/35 gear.

Series C „ „ 9/34 gear.

The 8/33 gear had been run in the machine about 40 hours on previous tests, equivalent to about 1,000 miles of running in actual use.

The 8/35 gear was run for 8 hours in the machine before these tests were made, equivalent to about 200 miles in actual use.

The 9/34 gear had been run for considerably longer than the others, probably equivalent to 2,000 miles of actual running.

The oil removed from the gear box after Series A tests was examined in the Company's chemical laboratory and found to contain a small quantity of carbonaceous material and a trace of iron, but no copper. The presence of the iron may be due to slight abrasion of the worm or the ball bearings, or it may be scale from the body of the casing. The oil removed after Series B and Series C tests was examined at the National Physical Laboratory and its viscosity determined at three temperatures.

Viscosity of Oil.

Series B.		Series C.	
Temp.	Viscosity.*	Temp.	Viscosity.*
30° C.	250	30° C.	245
60° C.	88.5	60° C.	90.5
90° C.	50.5	90° C.	53

That used in Series B tests showed a small amount of carbonaceous material and iron and a very small amount of copper.

The oil used in Series C tests showed traces of carbonaceous material and copper and a very small amount of iron.

The results of the tests are given in the following tables.

TABLE I.

TESTS AT NORMAL TEMPERATURES AT VARYING PRESSURES AND SPEEDS.
8/33 GEAR, B. TYPE, LEFT HAND.

Series.	No. of Test.	Speed of Worm Shaft.	Calculated Horse Power.	Temperature.	Efficiency.	Torque on Driven Shaft.	Pressure on Thread.
A. (a).	1	r.p.m. 1522	31.5	° C. 34	per cent. 95.4	ft.-lb. 449	lb. 1205
	9	1542	31.9	35	95.4		
	2	1310	27.1	34	95.1		
	3	1023	21.2	33	95.2		
	4	801	16.6	32	95.4		
	5	696	14.4	35	95.1		
	6	595	12.3	38	94.8		
	7	504	10.4	37	94.4		
	8	383	7.9	34	93.9		

* By Redwood's Viscosimeter (time of outflow of 50 cc. in seconds).

TABLE I.—*continued.*

Series.	No. of Test.	Speed of Worm Shaft.	Calculated Horse Power.	Temperature.	Efficiency.	Torque on Driven Shaft.	Pressure on Thread.
		r.p.m.		° C.	per cent.	ft.-lb.	lb.
A. (b).	1	1532	45.6	36	95.7	645	1733
	9	1522	45.3	38	95.7		
	2	1315	39.1	37	95.4		
	3	998	29.7	36	95.2		
	4	806	24.0	36	95.4		
	5	716	21.3	36	95.3		
	6	605	18.0	36	95.0		
	7	494	14.7	35	94.5		
A. (c).	8	408	12.1	34	94.0	841	2258
	1	1532	59.4	44	95.8		
	9	1512	59.8	44	95.5		
	2	1310	50.8	44	95.5		
	8	1015	39.4	41	95.5		
	7	835	32.4	41	95.4		
	6	711	27.6	42	95.1		
	5	600	23.3	42	95.1		
A. (d).	4	489	19.0	42	94.8	1037	2786
	3	403	15.6	40	93.8		
	1	1512	72.4	47	95.5		
	9	1532	73.3	50	95.7		
	2	1310	62.7	47	95.5		
	3	1008	48.2	47	95.5		
	4	791	37.9	47	95.4		
	5	711	34.0	47	95.2		
A. (e).	6	595	28.5	48	94.8	449	1205
	7	574	24.6	47	94.6		
A. (f).	8	373	17.8	47	93.7	254	682
	1	1527	31.6	46	95.7		
	2	413	8.6	41	94.5		
	1	1497	17.5	35	93.5		
	9	1532	17.9	33	93.9		
	2	1315	15.4	33	93.5		
	3	1013	11.9	32	93.5		
	4	796	9.3	31	93.5		
A. (j).	5	701	8.2	30	93.7	449	1205
	6	585	6.8	30	93.6		
	7	499	5.8	30	93.5		
	8	418	4.9	30	93.6		
	1	1522	31.5	41	95.1		
	2	595	12.3	37	94.8		
	3	393	8.1	35	93.9		

TABLE II.

8/35 GEAR, B TYPE, LEFT HAND. TESTS AT VARYING SPEEDS AND LOADS.

Series.	No. of Test.	Speed of Worm Shaft.	Calculated Horse Power.	Temperature.	Efficiency.	Torque on Driven Shaft.	Pressure on Thread.
		r.p.m.		° C.	per cent.	ft.-lb.	lb.
B. (a).	1	1532	29.8	38	95.7	447	1200
	9	1512	29.4	38	95.6		
	2	1310	25.5	37	95.7		
	3	1003	19.5	35	96.8		
	10	1013	19.6	37	96.8		
	4	791	15.4	35	95.6		
	5	711	13.8	35	95.4		
	6	600	11.7	35	95.1		
	7	509	9.9	35	95.0		
	8	418	8.1	33	94.6		
B. (b).	1	1512	42.3	37	96.2	643	1727
	5	1512	42.3	37	96.0		
	2	1013	28.4	37	95.7		
	3	711	19.9	37	95.4		
	4	413	11.6	33	95.1		
B. (c).	1	1532	69.0	45	95.6	1035	2780
	5	1532	69.0	47	95.9		
	2	986	44.4	45	95.4		
	3	716	32.2	46	95.2		
	4	398	17.9	40	93.1		
B. (d).	1	1527	29.7	44	95.4	447	1200
	5	1532	29.8	37	95.4		
	2	1003	19.5	39	95.9		
	3	716	13.9	37	95.7		
	4	398	7.7	35	94.8		

TABLE III.

9/34 GEAR, B TYPE, LEFT HAND. TESTS AT VARYING SPEEDS AND LOADS.

Series.	No. of Test.	Speed of Worm Shaft.	Calculated Horse Power.	Temperature.		Efficiency.	Torque on Driven Shaft.	Pressure on Thread.
				° C.	per cent.			
C. (a).	1	1512	34.0	33	96.0	447	1200	
	5	1532	34.5	37	96.0			
	2	1003	22.6	33	96.3			
	3	706	15.9	35	95.7			
	4	393	8.9	30	95.2			
C. (b).	1	1527	49.5	37	96.6	643	1727	
	5	1512	49.0	37	96.3			
	2	1003	32.5	37	96.1			
	3	706	22.9	37	95.8			
	4	403	13.1	31	95.0			
C. (c).	1	1527	79.6	40	96.6	1035	2780	
	5	1532	79.9	41	96.8			
	2	1008	52.5	40	96.3			
	3	701	36.6	41	96.1			
	4	403	21.0	36	95.0			
C. (d).	1	1532	34.5	38	95.7	447	1200	
	5	1512	34.0	36	95.8			
	2	1028	23.2	37	95.7			
	3	706	15.9	36	95.2			
	4	413	9.3	32	95.1			

TABLE IV.

Series.	No. of Test.	Speed of Worm Shaft.	Calculated Horse Power.	Temperature.	Efficiency.	Torque on Driven Shaft.	Pressure on Thread.
A. (g).		r.p.m.		" C.	per cent.	ft.-lb.	lb.
	1	1542	31.9	54	94.9	449	1205
	2	1018	21.1	56	95.1		
	3	711	14.7	57	95.1		
	4	403	8.3	50	93.5		
A. (h).	1	1517	45.2	84	94.3	645	1733
	4	1517	45.2	86	94.4		
	2	1003	29.9	82	94.8		
	3	706	21.0	66	94.2		
	5	393	11.7	73	92.8		
A. (i).	1	1532	73.3	98	94.0	1037	2786
	5	1542	73.8	94	94.7		
	2	988	47.3	96	93.7		
	3	676	32.3	100	93.7		
	4	413	19.8	83	92.8		

TABLE V.
EFFECT OF RISE OF TEMPERATURE ON EFFICIENCY.

Approximate Speed of Worm Shaft.	Torque on Driven Shaft.	Pressure on Teeth.	Efficiency at	
revs. per min.	ft.-lb.	lb.	30°—40° per cent.	50°—60° per cent.
1500	449	1205	95.4	94.9
1000	"	"	95.2	95.1
700	"	"	95.1	95.1
400	"	"	93.9	93.5
1500	645	1733	95.7	94.35
1000	"	"	95.2	94.8
700	"	"	95.3	94.2
400	"	"	94.0	92.8
1500	1037	2786	95.6	94.35
1000	"	"	95.5	93.7
700	"	"	95.2	93.7
400	"	"	93.7	92.8

TABLE VI.

EFFECT OF PRESSURE ON TEETH ON EFFICIENCY AT 30°—40° C.

Gear.	Pressure on Teeth.	Efficiency at			400 r.p.m.
		1500 r.p.m.	1000 r.p.m.	700 r.p.m.	
8/33		per cent.	per cent.	per cent.	per cent.
	682	93·7	93·5	93·7	93·6
	1205	95·4	95·2	95·1	93·9
	1733	95·7	95·2	95·3	94·0
	2258	95·65	95·5	95·1	93·8
8/35	2786	95·6	95·5	95·2	93·7
	1200	95·65	96·8	95·4	94·6
	1727	96·1	95·7	95·4	95·1
	2780	95·75	95·4	95·2	93·1
9/34	1200	96·0	96·3	95·7	95·2
	1727	96·45	96·1	95·8	95·0
	2780	96·7	96·3	96·1	95·0

TABLE VII.

SHOWING THE EFFECT OF THE PREVIOUS HISTORY OF THE GEAR ON THE EFFICIENCY.

TORQUE ABOUT 450 FT.-LB. PRESSURE ON TEETH ABOUT 1200 LB.

Gear.	Speed. r.p.m.	1st Test.	Efficiency.	
			After Higher Loading.	After High Temperature Running.
8/33	1500	per cent.		
	400	95·4	95·7	95·1
8/35		93·9	94·5	93·9
	1500	95·65	95·4	
	1000	96·8	95·9	
	700	95·4	95·7	
9/34	400	94·6	94·8	
	1500	96·0	95·75	
	1000	96·3	95·7	
	700	95·7	95·2	
	400	95·2	95·1	

The efficiency of the worm gear itself should depend entirely on the condition of the oil film between the worm and wheel, and the value should remain sensibly constant as long as this film is perfect. The values obtained in these tests, however, are to a certain extent varied by the journal and thrust friction losses in the worm shaft, and do not depend alone on the friction of the gear. The fall in efficiency of the gear at slow speeds is in every case noticeable, and may in part be due to the reduction in the quantity of oil carried round by the worm. The fall in efficiency is also noticeable when the pressure on the teeth is small, and the reason for these lower values may be looked for in the journal friction and churning action of the worm and wheel in the lubricant, both of which losses do not vary as the pressure.

A fall due to rise of temperature is also apparent, but this is much smaller than would be expected with the thin lubricant used. In the worst case it amounts to 1.3 per cent, although the temperature of oil was sometimes 100° C. The conclusion to be drawn from these tests is that the efficiency of the gears lies between 93 and 97 per cent under all circumstances, and taking the normal running speed of the worm at 1,000 revs. per minute the efficiency of the gears lies between 95 and 97 per cent, only falling slightly below the lower figure when the temperature approaches 100° C. The effect of the previous history of the gear is shown in Table VII.

This table indicates that running at higher pressure sometimes increases the efficiency and sometimes decreases it, the difference obtained being probably caused by the difference in condition of the gears owing to the different amounts of running they had had.

High temperature running appears to lower the efficiency on the temperature becoming normal, but it is probable that the original condition of the oil film would soon be re-established and the efficiency become normal again.

Curves are appended (pp. 253 - 255) showing the efficiency at different loads and speeds, and also the effect of temperature and pressure on the efficiency.

The general slope of the efficiency-speed curves is similar with different loads for the 8/33 gear except for the very light load (Series Ae), where the efficiency is lower and nearly constant. The curves for the 8/35 and 9/34 gears are similar in shape as a rule, but there is a rather remarkable exception in the case of the 8/35 gear with a pressure of 1,200 lb. on the teeth which is shown on

Curve 3. The rise in efficiency at 1,000 revs. per minute is most marked, and the observation was repeated and found to be quite correct. This gear shows a very considerable drop at the end of the high pressure curve (2,780 lb.), and it would appear that the load was too heavy for the gear in its present condition. It will be remembered that this gear had not had nearly as much running as the other two. The gear was run at 1,200 lb. tooth pressure after this test, and the efficiency was lower than before, but the peak at 1,000 revs. per minute still appears. This is shown in Curve 8.

The curves connecting temperature and efficiency show a similarity in all cases, there being no case of a rise of efficiency with an increase in temperature. This would seem to show that the viscosity of the oil was most suitable at fairly low temperatures. The table of viscosity, however, shows a very considerable variation with temperature, and the alteration in efficiency is in no way comparable with the change in viscosity.

The pressure efficiency curves indicate that the efficiency is very nearly constant except when the pressure is very small.

(Signed) R. T. GLAZEBROOK.
Director.

November 4th, 1912.

CURVE 1.

Series.	Curve.	Gear.	Pressure on Teeth.
A (a)	—	8/33	1205 lb.
A (b)	- - - - -	8/33	1733 lb.
A (c)		8/33	2285 lb.

CURVE 2.

Series.	Curve.	Gear.	Pressure on Teeth.
A (d)	—	8/33	2785 lb.
A (e)	- - - - -	8/33	682 lb.

CURVE 3.

Series.	Curve.	Gear.	Pressure on Teeth.
B (a)	—	8/35	1200 lb.
B (b)	- - - - -	8/35	1727 lb.
B (c)		8/35	2780 lb.

CURVE 4.

Series.	Curve.	Gear.	Pressure on Teeth.
C (a)	—	9/34	1200 lb.
C (b)	- - - - -	9/34	1727 lb.
C (c)		9/34	2780 lb.

TESTS ON DAIMLER-LANCHESTER WORM GEARS.

CURVES OF EFFICIENCY.

CURVE 5.

CURVE 6.

CURVE 7.

CURVE 8.

CURVES 5, 6 and 7.

Speed of Worm Shaft :

1500 R.P.M.	—————
1000 „	-----
700 „	
400 „	

CURVE 8.

First Test —————

After High Loading -----

TESTS ON DAIMLER-LANCHESTER WORM GEARS.

TEMPERATURE EFFICIENCY CURVES AND EFFECT OF HIGH LOADING.

CURVES 9, 10 and 11.

Speed of Worm Shaft :

1500 R.P.M.	—————
1000 „	- - - - -
700 „	
400 „	- . - . - .

TESTS ON DAIMLER-LANCHESTER WORM GEARS. LOAD-EFFICIENCY CURVES.

APPENDIX II.

The general description of the machine has been given in Appendix I. as embodied in the report of the National Physical Laboratory. Fig. 19, Fig. 20, Plate XII, and Fig. 21, Plate XIII, will serve to make clear the method of construction and details of the more important parts of the apparatus. The letters of reference which accompany Fig. 19 are self-explanatory. Figs.

FIG. 19.

A. Worm Gear Case.	F. Dial.
B. Ball Bearings carrying case allowing movement in Cradle.	G. Rod carrying weight.
C. Cradle, consisting of two circular disks coupled by bridges.	H. Antifriction Rollers.
D. Cross Knife Edge.	K. Balance Arm, with knife edge on upper face.
E. Adjusting Wheel.	W. Weights.

22 and 23 show the Lanchester gear-cutting machine from photographs taken of different processes in the course of execution. Fig. 22, Plate XIV, represents the initial process of generating a worm, and Fig. 23, Plate XV, represents in the left-hand machine the hobbing of a worm, and that of a wheel in the machine on the right-hand. Fig. 24, Plate XVI, illustrates a sample of the output as representing three of the standard types of gear manufacture.

APPENDIX III.

—◆—

J. L. MILLIGAN, B.Sc., Member.

The following graphic method of dealing with the lay out of spiral or worm gearing has been evolved with a view to minimising the time and labour necessary, and is presented in a form in which it is readily applicable to any set of conditions that may arise in the ordinary course of practical design. In its main features this method (although worked out independently by the author of the present Appendix) is identical with that previously developed and published by Messrs. R. E. Flanders and F. J. Bostock.* Such differences as exist are quite unimportant, and consist merely of detail additions.

The principal particulars of a pair of spiral or worm gears are :—

- D = Diameter of wheel.
- d = Diameter of worm.
- P = Normal pitch.
- θ = Angle of teeth to wheel axis.
- S = $(D + d)/2$ centre distances.
- N = Number of teeth in wheel.
- n = Number of teeth in worm.
- L = Axial lead of wheel teeth.
- l = Axial lead of worm teeth.
- E = Diameter of equivalent circle to wheel.
- e = Diameter of equivalent circle to worm.
- ϕ_1 = Efficiency when worm drives.
- ϕ_2 = Efficiency when wheel drives.

Fig. 25 shows the elementary relations between the quantities, $AB = 2S$; $AC = D$; $BC = d$; $CE = (NP)/\pi$; $CD = (n\phi)/\pi$. Angle $ABO = \theta$ $\tan QOX = \text{gear ratio} = n/N$.

An instrument has been constructed (Fig. 27) consisting of an "L"-shaped frame $\frac{1}{8}$ in. thick screwed to the board, and a rule to the

* Compare Machinery, Oct., 1908, and Machinery Reference Book, No. 29.

underside of which pins $\frac{1}{2}$ in. diameter, $\frac{1}{16}$ in. high are clipped so

FIG. 25.

that the centre of the pin is under the edge of the rule, and by a mark on the pin the centres of the pins may be adjusted to $AB = 2S$.

FIG. 26.

The lines OX and OY are then parallel to the frame at a distance equal to the radius of the pin.

If the centres and ratio are fixed, and d must be as near a given size as possible, then the pins are set to $= AB$. A point C is marked, $CB = d$. OQ is drawn, $\tan QOX = \text{ratio}$, and the rule is moved until C lies on OQ . CD is drawn and measured to see if the pitch is accurate for the cutters required, and trial is made by varying centres, diameters, pitch or ratio till a suitable gear is found.

FIG. 27.

The diagram can then be extended as Fig. 26 drawing CF normal to AB and FL and GH .

$CF = L/\eta$ and $CG = l/\eta$, which gives suitable change gears for milling. $AL = E$; $BH = e$.

The cutter for the wheel is one suitable for a spur gear of diameter $= E$, and the cutter for the worm is one suitable for a spur gear of diameter $= e$. If these equivalent circles be set out touching each other as in Fig. 28, and the addendum circles drawn, the common chord BV gives the width normal to the teeth of the two gears; if

BV is set off on Fig. 26, then BW = width of worm and VH' = width of wheels.

FIG. 28.

If BP is drawn with $PBA = \alpha$ = angle of friction, and AZ is drawn with angle ZAB = angle of friction, then if lines TR and JN are drawn $SR/TR = \phi_1$ and $JM/JN = \phi_2$.

APPENDIX IV.

LIST OF FIRMS USING WORM DRIVE.

(ARRANGED IN ORDER OF DATE.)

FIRM.	Date of Adoption.	Type.
LANCHESTER MOTOR Co.....	1897	Lanchester.
DENNIS BROS.	1904	Parallel.
NEW ENGINE Co.	1905	Parallel.
ARGYLLS, LTD.	Commercial Vehicles, 1906.	Parallel.
DAIMLER MOTOR Co., LTD. ..	1907	Parallel.*
THAMES IRONWORKS Co.....	1907	Parallel.
PHENIX MOTORS, LTD.	1908	Parallel.
VULCAN MOTOR AND ENG. Co..	1908	Parallel.
DAIMLER MOTOR Co., LTD. ..	July, 1909	Lanchester.
SIDDELEY DEASY Co.	October, 1909	Lanchester.
STANDARD MOTOR Co.	November, 1909	Parallel.
ARGYLLS, LTD.	Pleasure Cars, 1909.	
TURNER PETROL CARS, LTD. ..	1909	Parallel.
WOLSELEY TOOL AND MOTOR CAR Co.	1909	Parallel.
BELSIZE MOTORS, LTD.	June, 1910	Parallel.
BAGULEY CARS, LTD.	August, 1911	Parallel.
HUMBER, LTD.....	1911	Parallel.
SHEFFIELD SIMPLEX, LTD.	1912	Lanchester.

* The parallel worm was only employed by the Daimler Co. in the gear box of their chain driven cars.

THE DISCUSSION.

Mr. W. WORBY BEAUMONT, in opening the discussion, said: I understand that Mr. Lanchester has made some allusion to myself in a paragraph on p. 219, and as he has shown in his paper that he is one who has a very great admiration for extreme accuracy, and has also shown that even one-fifth of 1 per cent may, if confirmed by the National Physical Laboratory, be of importance, I am rather surprised to find on that page a paragraph which, as to accuracy, is more like that to be found in another House in Westminster, where some of the statements have been characterised as terminological inexactitudes. I would like to ask Mr. Lanchester where, in the book of mine to which he refers, he finds any mention whatever by me of an efficiency of worm gearing of 37 per cent. I do not think he can point to anything of the kind, but I must state that in that book it mentions the results of the trials of a certain vehicle to which the judges, of whom I was one, awarded the gold medal, not so much because of what it did, as because of what it promised; that was a worm-driven vehicle. There is in my book a reference to the efficiency of the whole gearing, of the whole transmission from the engine to the ground, and that is given as 33·4 per cent on the actual trials referred to, and as 41·6 per cent if certain allowances were made as to speed on the hill trials on which the measurements were made, and which formed the basis of comparative performance of the competing vehicles. I think, therefore, that as Mr. Lanchester has assigned to me an assessment of 37 per cent, which I never gave, he will either withdraw that statement he has put in the paper, or explain how it is that he has got these figures. In any case, I may say that I have no such notion as 37 per cent for any such gear as that to which Mr. Lanchester referred, and inasmuch as I am responsible for the character, at all events, of construction of vehicles that run about $1\frac{1}{2}$ million miles a week, it is quite certain I should not recommend something which had an efficiency of only about 37 per cent. I therefore merely wish to explain that it is by some error in looking at the pages of the book to which Mr. Lanchester refers that he has himself compounded and ascribed to me an estimate of 37 per cent for his worm or anybody else's worm gear.

Professor H. S. HELE-SHAW: I will commence by pointing out that Mr. Lanchester's paper may be divided into two parts, one of which deals with the efficiency of different kinds of worm gear amongst themselves, and the other raises the question generally as to the relative efficiency of worm gear as against the two other chief kinds of drive and bevel wheel. I wish to speak chiefly on the question of the relative efficiencies and questions arising out of different kinds of worm gear, but I would first remark that I quite feel with Mr. Lanchester that it is necessary to make some distinction in the nomenclature of worm gear. He has suggested the very good term "hollow" worm gear as against the parallel worm gear. I think, however, that the use of the term "hollow-face" will lead to a certain amount of confusion. We all realise that a parallel worm is one in which, in section, the top and bottom lines are parallel, and that the hollow worm gear more or less fits the contour of the worm wheel. The objection I have, and Mr. Lanchester, I hope, will say a word on this point, is to the use of the word "face." I think that the word "face" is always used to denote the sides of the teeth in contact, and Mr. Lanchester has used the word himself later on in that sense, on p. 234, where he says that "The precise symptom of failure from over-load is that after some 5,000 to 10,000 miles running, the teeth will be found to have increased in height, owing to the pressure on their face, so that they bottom on the worm teeth."

Coming to the gear itself, it may be said that the two forms of worm gear respectively represent Mr. Lanchester's system and that of most of the other makers. I have been looking this matter up, and find that nearly all other makers adopt the parallel worm. The author of an article on the Hindley or hollow form has given certain disadvantages, but it is by actual tests that we must ultimately decide such questions, and hence the value of the testing machine devised by Mr. Lanchester. I do not think anyone could understand from the illustrations the nature of that machine; it must be seen to be appreciated, and I hope members will have an opportunity of paying a visit to Coventry and seeing it in operation, as I have done; I consider it is one of the most ingenious testing machines I have ever seen. The machine is important, because the ordinary ways of testing a worm alone would not reveal the minute differences of efficiency.

Coming now to the actual efficiency obtained, this seems to be really a question of the proper use of the film of oil. In fact, the

(Professor H. S. Hele-Shaw.)

important part which the film of oil is playing to-day in modern machines can be partly realised if we remember how we depend on forced lubrication to-day. The success of the turbine depends upon it. Without a system of efficient forced lubrication away go the turbines of our men-of-war, because they could not run efficiently and satisfactorily without that system of floating on the film instead of trusting to luck whether there is an interposed film or not. Here, by a happy coincidence, is a case where the film is so drawn in by the machine that it is able to stand a pressure of 50 tons per sq. in. I think the reason for this is something to do

FIG. 29.

with the fact that these films of oil can be kept in place much better with a hollow worm than it seems to me possible with the parallel worm. It goes through the tooth, and is spread over a much larger portion of the circumference. Perhaps this was at the bottom of Mr. Lanchester's mind when he started making this form of gear.

The next point to be noted is that a higher efficiency is obtained with higher speed, which I do not think was to be expected. I have some diagrams (Figs. 29 and 30) of results of tests on worm gear for electrical transmission given by me in some Cantor lectures before the

Society of Arts 26 years ago, long before anyone thought about motor cars as practical, and they show an efficiency of over 95 per cent, though in some respects they are not quite correct. These tests also showed that the efficiencies rise as the speed goes up from 300 to 900 revs. per min. The errors referred to were due to the fact that different pressures were used at different speeds, and the curve went the wrong way. Against these I have plotted curves from Professor Goodman's modern results in his recent work on applied mechanics, and they show the same effect, namely, that the higher the speeds the higher the efficiencies, and

FIG. 30.

an angle of 45 degrees gave about the best results, Mr. Lanchester's angles of working being, generally speaking, from 39 degrees to 49 degrees. Here again increased speed gives increased efficiency, because the higher the speed the more the film is dragged in, and the better it acts.

Mr. Lanchester has given a word of warning at the end of the paper as to overdoing lubrication. On p. 241, the third conclusion says, "That the efficiency may be lowered by the presence of too much lubricant in the gear-box." Why? Not because of the lubricant that gets on to the film, but because, as I have found, there is a whirling in the box at high speed and a churning of

(Professor H. S. Hele-Shaw.)

the oil, and we all know that viscous resistance varies as the square of the velocity, and I suppose that this churning action is really at the bottom of this reduction of efficiency. In the same Cantor lectures I called attention to the fact that Mr. Wicksteed had made tests of a worm gear for a big testing machine, and he found the efficiency was not a loss of 3 per cent, but a total of 3 per cent, that is a loss of 97 per cent. One satisfaction is that such a gear could not run backwards and cause an accident, but it only shows the extreme possibilities of bad workmanship.

In conclusion, I would like to make a remark generally, that with regard to the comparison between the screw, the bevel and the chain, there is no doubt that people working at one particular subject, such as Mr. Lanchester at the worm, and other people at the bevel, are bound more or less to believe in the respective mechanisms they are handling, because they can see the improvement they get. I think I may say, however, that the bevel has replaced the chain drive, and I do not think I shall be in great danger of being contradicted if I say the worm appears to be replacing the bevel, notwithstanding the great improvements in the bevel. Perhaps a day may come when both bevel and worm and all other kinds of transmission to the axle will be replaced in turn.

Mr. E. G. BEAUMONT: There is no doubt that the author has had an uphill fight, and that he is largely responsible for the success which has now been achieved with worm gear, and he, of course, would be the last to fail to recognise that others have also had a good deal to do with its development. Listening to the paper, one point has occurred to me upon which Mr. Lanchester can probably enlighten us a little more. He has stated on p. 232 that a considerable degree of success has been achieved by the users of the parallel worm, and on p. 240 he summarises the differences between the efficiency of the parallel worm and that of his own type, showing that under heavy load conditions these differences may be in the neighbourhood of 3 or 4 per cent. He also refers on p. 235 to the marked advantages of his worm under heavy loads. I should like to know what percentage of the limiting load of his worm gear will the parallel worm stand before showing signs of breaking down. We can all understand that failure probably follows very rapidly when that limit is reached. We have now a definite statement of the difference of efficiency of the two types,

and there can be no question of the accuracy of the results published in this paper, but we have no definite statements as to the relative capacities of the worms, from which we might judge the different dimensions necessary to secure what may be termed a working compromise with the parallel type, if it is to be encouraged at all. It may be of interest to the members of the Institution to know that the parallel type of worm gear is being used by the London General Omnibus Company in their vehicles, which are making a weekly mileage of about $1\frac{1}{2}$ million miles, and that I am given to understand that that worm has undergone a period of use of 20,000 miles successfully, which shows that at all events the parallel worm can be used and give good results. From my own external observation of the two types which are now running in London, namely, the "B" type of the London General Omnibus Company, and the Daimler buses, which I believe have Mr. Lanchester's worm, there is no apparent difference in the sizes of the axle casings, so that in that particular example, which is an instance of the application of worm gear to very heavy service, it has not been found necessary, apparently, to give any appreciable increase of size to the parallel worm.

Prof. Hele-Shaw has touched on the question of different types of gear to be used as the final transmission in motor vehicles, but I may, perhaps, add one remark to his, namely, that it is not alone a question of efficiency which determines the type of gear to be used. I think the first requirements are reliability and durability. Efficiency of transmission might, perhaps, be put third, and while realising the extreme niceness of working and the high degree of efficiency obtainable with worm gearing, I think it is also correct to say that it is a more sensitive gear; it will not stand the abuse which a bevel gear, for instance, may be expected to stand. It is dependent on good lubrication, and a bevel gear might be expected to "stand up" under conditions of less intelligent use where the worm gear would fail. On the question of the efficiency of the two types of gear, that is to say, the worm gear and the bevel gear, there still seems to be a difference of opinion, and Mr. Lanchester, in opening his paper, quoted the result of some tests by M. Faroux, showing an efficiency of 89 per cent, but he was obviously uncertain about them himself, and thought they were too low. I do not know whether a comparatively recent test given in "Science Abstracts" for October, 1912, p. 479, paragraph 1043, which is an abstract from the proceedings of

(Mr. E. G. Beaumont.)

the American Society of Mechanical Engineers, is known to Mr. Lanchester. It describes a method of testing which seems to have been a careful one, and it also gives two results which the members may be interested to hear. I will only read one paragraph which says: "Tests are described on three forms of worm gear and a bevel gear, the apparatus being arranged in the following sequence:—an electromotor driving, through an automobile gear case, a Kenerson's transmission dynamometer which drives through the worm and worm wheel an Alden brake. The worm is immersed in an oil bath containing about five quarts of oil, and the temperature variation during a run is observed. At the commencement the temperature increase is rather rapid and irregular; towards the attainment of the steady state the increase is less rapid, much as in a B-H magnetic curve. The efficiencies increase with the power transmitted; with the worm running at 880 revs. per min. and its wheel at 198 revs. per min. and transmitting 31·17, 40·92, and 49·26 h.p., the worm gear efficiency is 92·4 per cent, 94·4 per cent, and 97·9 per cent respectively. The bevel gear used for purposes of comparison has a ratio of 14 to 52, and an efficiency of 94·2, 95·1 and 98·9 per cent at 30, 40 and 50 h.p. respectively." That reverses the result shown on Mr. Lanchester's diagram, and shows the bevel gear as 1 per cent higher in efficiency than the worm gear. Whether that can be considered reliable or not I do not know. In one part of the paper the author says that only one case of prior use was known to him, and he refers to the electrical vehicle shown at the Stanley Show in about 1896, but he did not know whether it had ever run. This was a vehicle designed by Mr. Carl Oppermann, and all the figures showed that the efficiency of that early gear was at least 90 per cent. That is a good many years ago now, and I have since had an opportunity of referring to these figures.

I do not suppose it is a matter of general interest to the members that there should be a difference of opinion between Mr. Worby Beaumont and Mr. Lanchester, but if I can assist Mr. Lanchester at all to relieve his paper of the disfigurement of inaccuracy which appears in it I shall be pleased to do so. Reading the part of the book referred to as impartially as I can, it seems to me that there can be no question whatever that Mr. Lanchester has stated the figure without reference to the preceding or succeeding parts of the chapter in which the figure referred to occurs. Mr. Lanchester has already amended that statement, which appears in

paragraph 6, and pointed out that it was not a statement with regard to worm efficiency, but a statement with regard to the transmission efficiency of the vehicle. I would also like to remind him that the figures given are not figures of gear efficiency, but are deduced, as plainly stated, in comparison of performance of vehicles in a hill-climb, and I would only refer Mr. Lanchester to the first paragraph of that chapter and to the last paragraph, and to paragraphs which appear on pages 379 and 383. Mr. Lanchester suggested in his reply to Mr. Worby Beaumont that he assumed that the difference between the efficiency he expected and the efficiency of the transmission gear referred to would be accounted for by the fact that his engine, on the very low gear ratio employed, was only working at, I think he said, four-tenths of its power, and that that explained the low figure published. I would remind Mr. Lanchester that that is recognised in the chapter referred to, and on p. 383 there is a reference to at least one of the vehicles, Mr. Lanchester's being that referred to, which was known to be "cutting out," and had there been a different gradation of gear there would have been a better result as regards performance on the hill.

Mr. CARL OPPERMANN: Mr. Lanchester was good enough to mention the fact that some years ago he saw an electrical vehicle fitted with a worm drive which I had designed and exhibited at one of the exhibitions, and he also stated that he did not know whether that vehicle ran. It ran for some considerable time, and I may say that I made many other vehicles with worm drive. In all cases I used the parallel worm. I may tell you that the difficulties which I met with in the early experiments were due to the fact that we could not buy the well-made ball-bearings or ball races which can be purchased now. I had to make them myself, and, of course, I did not make them as they ought to be made. Nevertheless, I made some very careful practical tests in 1904, with a view to comparing the relative efficiency of the chain drive, the bevel drive and the worm drive. I constructed a vehicle, and as this vehicle was electrically driven, it was of course quite easy to make a perfect record of the amount of energy which the gear consumed. I made the back axles for the different drives interchangeable, so that I could make the tests under the same conditions as nearly as possible, so that after making the test with the bevel drive I replaced the back axle by a worm drive, and then with the chain drive, and there

(Mr. Carl Oppermann.)

was no appreciable difference in the net results between any of those various systems. I cannot find the papers relating to the exact efficiency, but Mr. Beaumont was good enough to mention that it was 90 per cent, but I cannot be sure of that. The amount of current and electrical energy together consumed in all three cases was practically identical. The only difficulty that I noticed in the case of the worm drive was that the vehicle appeared to be a little more sluggish in starting, and I think that can be explained by the fact that the film of oil drained away when the vehicle had been standing, and as soon as it began to move it picked up the oil, and the difficulty was got over. With regard to the necessity of having the best material and the most suitable material, I am now making a worm gear, and I am using drop forged phosphor bronze wheels. It seems to me that the difference between the texture of a casting of phosphor bronze and that of a phosphor bronze forging is so great as to be noticeable whilst it is being machined, and I think that it will be worth the extra expense. Mr. Lanchester mentioned the fact that on one or two occasions he noted that the phosphor bronze material had been squeezed out, or rolled out, I think, was the expression he used; and he also mentioned, if I understood him correctly, that he did not think that was due to any fault in the lubricating system. Personally, I think he has made a mistake, and I really think that the reason why that metal got pushed out of place was owing to the fact that there was an appreciable rise in the temperature, because I had a similar experience, and it seems to me that, comparatively speaking, a few degrees increase in the temperature of phosphor bronze makes it semi-plastic, and it gets rolled out. I remember, some years ago, seeing one of Parson's turbines which had broken down: the points of the phosphor bronze blades, which were 14 B.W.G., and I think, $\frac{5}{8}$ in. wide, had melted into lumps. As a further example of the difference which a rise of temperature makes in the nature of metal, I remember a case in the early days when I used one big ball as a thrust, and this ball got flattened out like a bullet. The temperature did not appear to have risen beyond a blue, which would be, perhaps, about 500 or 600° F. I am somewhat disappointed that Mr. Lanchester, in his very interesting paper, has not told us the best way of housing a worm, because it seems to me that the way in which the worm is housed is responsible for the efficiency.

Prof. A. SHARP: I do not quite follow Prof. Hele-Shaw in

his elucidation of the action of the oil film. In fact, I thought his reference to the thrust bearing of a marine turbine was rather an unhappy one, because when I was an apprentice in marine engineering 70 lb. per sq. in. was regarded as the absolute limit to be put on a thrust bearing.

Prof. HELE-SHAW: I meant by a number of separate surfaces. I do not wish Prof. Sharp to argue against a point I did not make. I did not mean to multiply the surfaces.

Prof. SHARP: With regard to the oil film, comparing the Lanchester worm with the parallel worm, I think that, from the mode in which the Lanchester worm is generated, there is one great geometric difference between the two surfaces in nominal contact. In a cross section of the Lanchester worm and wheel there is always a definite line of contact down the centre of the plane of the wheel, and from the mode in which the first generating tool cuts the worm, and the worm-cutting tool in turn cuts the wheel, there is bound to be a line of contact from side to side. It is difficult to form an idea of the effective surface of contact across the face of a tooth, but from the above considerations we may imagine the effective surface supported by the active oil film to be bounded by curves resembling two pairs of hyperbolas giving a large area sufficient to transmit the heavy pressures referred to. In the parallel worm, on the other hand, the nominal contact is a single curved line, so that the actual surface effectively supported by the oil film must be extremely narrow, of much smaller area than that bounded in the Lanchester worm and wheel.

Mr. L. A. LEGROS: In the paper which Mr. Lanchester has given us there is a great amount of valuable information in respect to both the methods of manufacture and the efficiency of the resultant product. It is worth noting in connection with the latter result that in the discussion on a paper read before the Institution of Civil Engineers by the Hon. R. C. Parsons in December, 1884,* Mr. W. Wilkinson described a steam tramway engine fitted with worm gear (the illustration shows a straight worm) and oil-bath, and he stated that although failure had been foretold for his departure from ordinary locomotive methods yet "A gradient of 1 in 70, which was considered slight in tramway practice, would propel the worm round by the force of gravity."

* Proc. Inst. C. E., Vol. LXXIX., p. 157 *et seq.*

(Mr. L. A. Legros.)

The worm used was made of Siemens steel and apparently the worm wheel was of phosphor bronze. It is evident that even in this early application the efficiency must have been high.

In a paper on Transmission, read by the author before the Institution in 1910, he had pointed out the necessity for obtaining uniform angular velocity in the details of the transmission gear. In the case of spur and bevel gears this can be obtained by generating the gears in a machine of the planing machine type, spur gears being generated in the Fellows gear shaper while bevel gears are generated in the Bilgram or in the Gleason gear shaper. In both these cases the axes of the two gears are in the same plane, whereas in the case of worm gears they are not. It is, however, quite possible to conceive that the worm and wheel, instead of rolling together on pitch cylinders, as in the case of spur gears, or on pitch cones, as in the case of bevels, should roll together on pitch hyperboloidal surfaces, and that the form of such gears would be that of the hollow worm and hollow worm wheel. Mr. Lanchester has pointed out that it is not essential to the obtaining of uniform angular velocity from the gear that the form of the teeth should be symmetrical; in fact, he states that his process is essentially unsymmetrical; it is the cutting machine which produces the correctly formed counterpart to work with the arbitrarily selected worm. It would, however, be of interest to know, should the problem of worm gear design be still further elaborated, whether an even better result could not be obtained by generating the master worm on a machine which produced it by planing a tooth form symmetrical to the hyperboloidal pitch surface generated by the rotation of a line about an axis not lying in the same plane with it.

I would like to ask Mr. Lanchester a question with regard to the worms and worm wheels generated by his process. If the worm (or the wheel) be reversed by turning through two right angles and put to work in this position, will the worm and worm wheel work equally well together? If not, is there any special method adopted for enabling those responsible for erection to know which way round to put the worm and worm wheel in gear? The chances of putting the two together as generated and with one face transposed respectively are equal if either worm or worm wheel, or both, are symmetrical in other respects, but in many cases the design may so determine matters that only one way of assembling is possible.

Mr. C. E. DAVIS: I am interested in the problem from the commercial standpoint, and I felt that in entering into a problem of this sort with a view to the possible introduction of the worm gear drive into America, it was desirable to get into touch with the people who had produced a worm gear drive which everyone admits has not been excelled. I believe I am on safe ground when I state that there are others who claim that they can do practically as well, while none have claimed that they can do better, and I felt that it was desirable for the American market that we should start with a product and a method of production of that product as far in advance in the study of the subject as possible; hence our action in securing for the American trade the Lanchester worm gear drive. We have been watching with a great deal of interest the introduction of the worm gear drive on motor cars in the United States, though many of the American engineers and manufacturers have not done so, possibly partly from the fact that there has been a very careful refinement on the bevel drive, and partly that with many of the manufacturers over there a change from one design to another means the introduction of an element from the commercial side that has made it necessary for them to take more time in its introduction than would otherwise be the case. To-day, however, nearly all the leading manufacturers in the United States are studying the problem of introducing worm gear drive, and very careful tests are being made. In order to show what has been done in America, one test of which I am cognisant was made with the Lanchester drive in order to see what the mechanism would stand up against on American roads. A car was taken on a Monday morning from New York and driven to Chicago, a distance of about 940 miles, and got there on Thursday. It left on the return trip on Friday, taking a different route, and reached New York somewhere in the neighbourhood of Monday morning. It left again the following day and reached Chicago again on Thursday. It made that trip six times, over six different routes, without any trouble, without any difficulty as to lubrication, and without any apparent wear. That is one reason why manufacturers in the United States have taken the line that until they were sure that there was nothing as good as the Lanchester worm drive they would not definitely adopt any particular type. Possibly the largest adaptation of worm drive has been made by the Pierce-Arrow Co., in connection with their large truck. That is of the parallel type of worm gear. At

LANCHESTER.

S

(Mr. C. E. Davis.)

the present time they are investigating and testing out other types of worm gear. Inasmuch as I represent parties interested in America, I should very much like to find out whether anyone has found anything that is at all better as a worm gear than the Lanchester type. I also want to know whether there is any reason why the worm drive shall not become, as I believe it is going to be, the silent, efficient drive for the motor car of the future.

Mr. L. H. HOUNSFIELD: I once tested a worm drive, and I see on reference to an old note book that I found the efficiency 30·7 per cent maximum, and it even went down to 11 per cent at light loads. Of course, the worm gear I had tested was not intended for automobile transmission. I think it was a good thing for the Lanchester Motor Company that I was not awarding the medals in the trials. So far as abuse of worm gear is concerned, I happen to be connected with some vehicles which seem to have received the worst abuse imaginable; out of the back axle cases of these worm-driven vehicles I have taken balls, hexagon nuts and pieces of bolts, and one could hardly be distinguished from the other. The worm itself, however, was practically unscratched on these occasions, and as a rule the worm wheel was badly scratched, that is all; and it was still fit for more work when the odd parts had been removed. My last point is that I want the author to tell us what oil we should use for lubricating worm gear. I have had so much trouble in obtaining a satisfactory lubricant.

Mr. H. W. STANER: I think we are all particularly grateful to the author for having published these figures, because really we have never had any definite figures before as to the efficiency of the worm drive, more particularly of the hollow worm drive, and I only hope it will be regarded in the light of a challenge, because I think we should all like to see similar tests made with bevel gearing. There is no doubt that there is a very general impression that the worm gear is bad at acceleration, but the author's tests show that any possible improvement must be approximately between 93 per cent and the highest possible minimum, so that it does not allow a very wide margin. Nevertheless, there is that impression, and as a rule there is no smoke without fire, and if we could only get some equally good tests with bevel gears we could at least have some figures to go on. Of course, there is still the old reproach for the worm that it has not yet shown its ability to make a world's record. If it did so, it would be at least a proof, and some people would prefer these

records to highly scientific tests. I am not running these scientific tests down, but the fact remains that the worm has not distinguished itself in the direction I have indicated, but it has shown such a high efficiency at the high loads that there really appears to be no reason why it should not do so, because even on the assumption that its efficiency is low at starting it does not really matter in a record, unless its starting efficiency is very much lower than these tests show, and we know that cannot be the case. With regard to the lubrication of gearing generally, and worm gearing in particular, I would like to ask Mr. Lanchester whether, in regard to the churning of the lubricant, he has ever made any lubrication experiments on the road with an accelerometer. Tests with the Wimperis accelerometer show how the efficiency falls on the first speed if there is either a needless quantity of oil or a very thick lubricant. Of course, we all know with hill climbs, and similar feats where efficiency is studied, that the minimum quantity of oil is used, but the bad effect of a surplus is quite distinctly visible on an accelerometer, and it bears out the point that both Mr. Lanchester and Prof. Hele-Shaw mention as to the undesirability of carrying more lubricant than necessary. My point in bringing this up is rather to advocate the desirability of a more definite and scientifically regulated system of lubrication than we have now for the gear, in other words, something more or less like we have for engine lubrication. In conclusion, I would like to point out one interesting adaptation of the screw gear which works very well in practice, and that is in the steering gear of certain cars where screw gear is used on the column, and the nut is simply cast round it, and that has been a very successful steering indeed, although, I suppose, according to theory, it should scarcely have been used. Nevertheless, the bearing surface has been so ample that the soft metal of the nut gives no trouble for long periods. My excuse for mentioning this is that the author himself departed a little from the driving worm, and has incidentally referred to its other uses on the motor car.

The PRESIDENT: I do not think that the author laid quite enough stress in his paper on all the advantages of the worm, one of which, especially for commercial purposes, where the speed of the vehicle is comparatively low, is the fact that a single reduction at one step in the transmission is quite practicable. A reduction of as much as 1 in 12 or 1 in 14 can be obtained, as

(The President.)

Mr. Lanchester, of course, is fully aware, but he did not state it in his paper. I think myself that this interesting feature of the worm being less efficient at low speeds might perhaps be cleared up by saying that the film of oil is squeezed out at the lower speed. With a certain pressure it takes a certain time to squeeze out, and when the surfaces are moving rapidly over one another the oil film has not time to squeeze out before the area of contact has completely changed, but when the speed is comparatively slow the oil is squeezed out from between those parts of the surfaces which are still under pressure, and so they become dry. I think there may be something in this theory. That would also account for the fact that these high pressures cannot be used with ordinary plain bearings where the surfaces are always in contact, instead of as with the worm receiving a fresh bath of oil on both surfaces at each revolution. Another point that Mr. Lanchester mentioned was the difficulty of calculating the amount of surface actually under pressure at any instant. It occurred to me that Prof. Coker's method of using transparent models of the parts in conjunction with polarised light might be of assistance in that direction. There would have to be one turn of the worm simply, otherwise the light would not get through. There would be other practical difficulties in carrying out the experiment, but I think these could probably be overcome by those who have had practical experience with this method.

The author has not said very much about the use of worm gear for engine auxiliary drives, such as for magnetos or for cam shafts. The reversals of stress from the magneto armature, and the effect of the reaction of the valve springs transmitted through the tappets to the cams, often cause serious knocking with plain spur gears, and it is very much intensified with the worm or spiral gear. First of all the teeth are at such an angle that the back lash in the direction of rotation is greater than the tooth clearance in the direction normal to the teeth, being nearly half as much again with a 45 degrees worm; and then again, if there is any end play in the shafts, and very often the lay shafts are not too well provided with proper thrust bearings, the back lash is still further increased. If a worm gear is used for driving cams, sleeves or magnetos, ball bearing thrusts of ample dimensions are an absolute necessity, and it is well to provide some means for their adjustment to take up the end play, as with 45 degrees worm gear the back lash will be proportionate to

the sum of the amount of end play in both driving and driven shafts. The question of tooth clearance as causing back lash is not so important with worm gear in the main transmission; the reversals are more infrequent there, the drive is comparatively elastic, and the parts are heavier, so that there is not the same effect. I should like to say, in conclusion, that I have had a worm-driven car for two years, and I have found it absolutely silent, and both with the engine driving the car and when coasting it is extremely free running, more so than I had expected.

Mr. F. W. LANCHESTER, in replying on the discussion, said: Mr. Worby Beaumont complains, perhaps with some reason, that I have quoted him as having given the efficiency of worm gear as 37 per cent, and points out that he neither agrees with, nor is responsible for this estimate. In point of fact, the estimate in question though not quoted from Mr. Beaumont's book, is based on Mr. Beaumont's statement, p. 619, that the mechanical efficiency of the Lanchester car is 31·9, the author of the paper having made what he believes to be a reasonable and proper allowance for other losses. There appears to be no doubt as to Mr. Beaumont's meaning, inasmuch as in the same paragraph the following statement appears:— "There can be no doubt that, firstly, the motor which is air-cooled is less than 8 h.p. on a long, heavy pull; that a good deal of power is absorbed by the fan; and that the efficiency of the transmission is not what was hoped from it."

Whether or not the 37 per cent given is a fair or reasonable interpretation of Mr. Beaumont's estimate is not, however, of great importance, the author's objection to Mr. Beaumont's work being not a question of a few per cent of efficiency one way or the other, but the whole misconception of what constitutes *mechanical efficiency*, on which Mr. Beaumont's estimates, both on p. 384 and on p. 619 of his book (1st edition, 1900), are based.

Professor Hele-Shaw has raised a point of terminology, exception being taken to the use of the words "hollow face" as applied to a worm of the Hindley type. I myself am not thoroughly satisfied with the term "hollow," because it suggests a kind of egg-shell worm, a sort of worm made of thin material, and the idea of the modified term "hollow face" was to emphasise that it was the hollow or "*saddle*" form of the surface. I quite agree with Professor Hele-Shaw that this is open to quite as serious objection, possibly more so, since the term "face" usually means the face of the tooth, and some

(Mr. F. W. Lanchester.)

confusion arises if it is used for the face of the blank. The term "hour glass" has been suggested, but as the function of the hour glass is to pass a stream of sand, it does not seem to be singularly appropriate. Possibly the "diabolo worm" would be a more apt descriptive title.

Professor HELE-SHAW: Why not concave?

Mr. LANCHESTER: It is convex the other way!

With regard to more important matters (not that I wish to belittle the objection, but facts are ever more important than words), Professor Hele-Shaw raises an objection to the Hindley type of worm on account of the accuracy of the alinement which is necessary. It appears to amount to this, in the ordinary parallel worm accuracy of alinement in one direction is necessary, and in the Hindley or diabolo worm we have to take care of the accuracy of alinement in another direction as well, so that we require to be a little bit more precise than before. There may be some slight difficulty encountered in the shops if the need for this co-ordinate alinement is not realised, but when understood there is no difficulty whatever in getting it carried out.

I have to thank Professor Hele-Shaw for his kind remarks on the new testing machine. If, as he suggests, any of the members of the Institution desire to visit Coventry to inspect the worm testing machine I shall be most happy to do all I can to make such a visit interesting, and I think I may definitely promise to have some exhibition tests conducted in their presence if members will notify the Secretary of the Institution and he will give me due notice.

I will now discuss the point raised by Professor Hele-Shaw as to the permanence of the film of oil, and the reasons why so high an intensity of loading can be sustained. When I designed the gear and method of cutting (about fifteen years ago), the question of improved lubrication was very carefully dealt with by a method involving principles that had not at that time been seriously applied or exploited.

Referring to Fig. 31, take a load supported on a surface, which we will, for the purpose of discussion, suppose to be an ellipse of elongate form, and let us assume that in one case this ellipse moves in the direction of its major axis as in Fig. 31, positions *a*, *b*, *c*, and in another case let it be assumed to move in the direction of its minor axis, its successive positions being 1, 2 and 3.

Now, in the first case, if the load supported is considerable, the oil will be squeezed out mainly in the region marked *e, e, e*, and *f, f, f*, and when the motion is longitudinal as in *a, b, c* the oil will be speedily squeezed from between the surface and metallic contact will result. If, on the other hand, the motion is broadside on, as in positions 1, 2 and 3, the pressure is continually being exerted on a region to which the oil has just previously been squeezed, and so the surface continually floats on an oil film instead of sinking through it. When the pressures are comparatively light, this action is not important, because the oil is never squeezed from between the surfaces, and the oil film has the power of insinuating itself between the surfaces and holding them apart up to moderate pressures. When, however, pressures exceeding half a ton to one ton per square inch are encountered, there is no longer any question of the oil film being maintained of its own

FIG. 31.

initiative, and it is for pressures of above this magnitude that this "squeegee" action becomes important.

In the Lanchester worm gear the whole system of generating and cutting is based on the need of maintaining the pressure surface in broadside motion. *Theoretically*, in the Lanchester worm the contact takes the form of a line running more or less radially from the root to the top of the tooth, and this line sweeps the tooth of the worm wheel from end to end twice, that is, one complete return journey during each engagement. In practice this line of contact becomes an area of proximate contact and elongate form, and its motion is in the main at right angles to its major axis, thus, as the location of the pressure area changes the oil in the region of pressure is squeezed out, and in endeavouring to escape, finds itself where a fraction of a second later it is again in the pressure region, and so the cushion of oil on which

(Mr. F. W. Lanchester.)

the two surfaces float is being continuously renewed. In the paper attention has been called to the partial analogy that exists between this behaviour of an oil film and that of the air supporting a flying machine. The analogy becomes more striking if we suppose an aerofoil skimming very close to the surface of the ground, in this case there is a static pressure region beneath the aerofoil to which much of the support is due, and when the thickness of the air layer becomes very thin (as in theory we may suppose it to gradually become as thin as we please) the problem approaches that of support by air lubrication, and the effect under discussion becomes identical with that well known as due to "*aspect-ratio*" in the problem of flight.*

Professor Hele-Shaw called attention to and exhibited certain diagrams (Figs. 29 and 30) given in his Cantor lectures of twenty-six years ago. It is difficult to attach much importance to the diagrams exhibited, the curves are erratic, and one can only feel that, having apparently reached over 97 per cent with the curve on a very steep up grade, it was a pity the curves were not carried just one step further, 100 per cent would certainly have been exceeded. My feeling is that the diagram in question has quite unintentionally managed to suggest a lie that nobody would care to tell.

I think Professor Hele-Shaw's explanation of the reason that a large quantity of oil diminishes efficiency is perfectly correct. It is the churning action. When there is enough oil for lubrication purposes and more is added the added oil becomes an impediment to the movement of the parts, and so efficiency falls.

Professor Hele-Shaw suggests that some day the whole of the worm and bevel gear as at present used will be placed on the scrap heap, and will have given place to a superior method of transmission (hydraulic of some kind, the exact medium is not mentioned). This is an interesting, if somewhat remote, sugges-

* In my "Aerial Flight" (Constable), Vol. I., in article 112, the question of the partial static support of an aeroplane is discussed and dealt with on a scientific footing, the proportions of the load supported statically and dynamically being clearly separated by the hypothetical conception of a fluid prismatic column. In case of flight at an altitude the proportion of the load supported statically becomes negligible, but at low altitude, as when starting or alighting, there is without question a certain proportion of the weight directly transmitted by the trapped pressure region. It is legitimate in such a case to regard the air as acting as a lubricant to whatever extent the load is statically sustained.

tion; if an overall efficiency of 95 per cent or 96 per cent can some day be obtained by hydraulic transmission, Professor Hele-Shaw's prophesy will have a very good chance of being fulfilled; however, we may rest assured that there is still a long and honourable future in store for mechanical transmission gear.

In response to the requests which were made during the course of the discussion, I have added an Appendix I., the Report of the National Physical Laboratory, which gives an account of the theory and mechanical construction of the testing machine, and some further illustrations and description in Appendix II. Here, I will confine myself for the moment to pointing out that as a matter of convenience the efficiency is not read direct but as an inverse quantity, a table being prepared to give the efficiency corresponding to the reading. I may also say that this machine is quite capable of being designed to test the efficiency of gear whose axes are at an angle other than a right angle. The right angle is much the simplest, considered theoretically, because the torque about the one axis has no resultant about the other; if the worm or wheel axes are at an acute or obtuse angle instead of at right angles the torque values are best laid out as a vector diagram and a graphic solution obtained.

I will now pass to the remarks of Mr. E. G. Beaumont. Mr. Beaumont has asked a question as to the percentage of loading a parallel worm would stand compared with the diabolo type. In Figure 16, the thick lines represent a load of $2\frac{1}{2}$ tons per sq. in., and the broken lines 1 ton per sq. in. If instead of plotting for these definite values $2\frac{1}{2}$ tons and 1 ton tooth load against variable revolution speed we plot load against efficiency for given values of revolution speed, we find that up to a certain load the two efficiency curves (Lanchester and parallel) keep fairly close together, but when a certain load is reached the parallel curve drops away and the Lanchester curve goes on for some considerable further distance before it shows any fall. On the question of the omnibus worm gear, there were and are certain political reasons for making the centres the same, *absolutely the same* in the Daimler bus as in the existing L. G. O. "B" type of bus.* Beyond this, the same standard of worm gear is adopted by the Daimler Company for their heavier commercial vehicles. The modern street omnibus is a light-weight vehicle,

* Since giving this reply, I have ascertained that the Lanchester-Daimler worm gear is standing up far better than the parallel type.

(Mr. F. W. Lanchester.)

weighing $3\frac{1}{2}$ tons, carrying $2\frac{1}{2}$ tons of passengers, or 6 tons in all. The question of the initial tool outfit cost is a serious matter, and it is necessary to avoid embarking on too many standards. Mr. Beaumont, I think, gave it as his opinion that a worm gear would not stand as much abuse as a bevel gear. My reply to that is that taking the word "abuse" in its ordinary accepted sense (and in its derivative sense), I do not think it is necessary in a civilised country for a motor vehicle to stand abuse; so long as it is made to stand *use* it is sufficient; however, I have seen some shamefully treated gear, both bevel and worm, and I think that the worm is quite able to hold its own.

Mr. Beaumont has kindly mentioned the tests summarised in "Science Abstracts" from a report of the proceedings of the American Society of Mechanical Engineers. I had already seen the test in question, and I believe I am right in saying that the method of testing is by a torsion dynamometer on the input shaft, and an ordinary dynamometer brake on the output shaft. I am open to correction, but I believe that is the matter referred to.

The method of test is one which cannot compare for accuracy with the method of direct torque comparison employed in the present investigations. The results when plotted are so irregular as to render it certain that the limit of inaccuracy is of the order of 2 per cent or 3 per cent; it may be taken as quite a fortuitous circumstance that none of the efficiencies exceeded 100 per cent. I decided after studying them carefully that they were quite unreliable. A plotting is given in Fig. 42, p. 299 (A), and a plotting of one of the National Physical Laboratory curves is shown at (B) for comparison. The vertical extensions from the observation loci given in Fig. 43, p. 300, indicate the probable degree of inaccuracy. Comment is needless.

Mr. Beaumont rightly states that reliability and durability are of equal importance with efficiency or even greater. In these respects the Lanchester gear has fully established its reputation. It is, in fact, the only gear that can claim a fifteen years' history in its application to the automobile; there are many worm gears still running in the same rear axles to which they were fitted more than ten years ago at a time when the Lanchester was the only worm driven car and the parallel worm was unrepresented in automobile practice. Reliability and durability have been established past question, hence the prominent place given to efficiency in the present paper.

Mr. Beaumont speaks from personal knowledge of the Opperman worm gear, and it is exceedingly interesting to hear that at that early period (1896) an efficiency in excess of 90 per cent had been obtained.

I do not understand Mr. Beaumont's reference to a "disfigurement of inaccuracy" that appears in this paper. If there is a disfigurement of that kind I shall be very pleased to correct it. If I understand the matter aright, Mr. E. G. Beaumont objects to the figure cited in the present paper, namely, 37 per cent, as representing the estimate of Mr. Worby Beaumont of worm gear efficiency, on the grounds that the figure in question is not correctly quoted from his book. This is true; the actual figures given in Mr. Beaumont's book are 33·4, p. 384, and 31·9 per cent, p. 619, as the total mechanical efficiency of the vehicle on two hill climbing tests. The figure given by me, 37 per cent, was based on the latter of the figures cited above (31·9 per cent) with a reasonable allowance for other losses. This should have been explained. Mr. Worby Beaumont's so called "mechanical efficiency" is not in reality mechanical efficiency at all, and has no relation thereto. Granted that Mr. Beaumont is entitled to raise an objection on the ground stated, the main point is still untouched. There are passages on the subject which have not been referred to by Mr. E. G. Beaumont: on p. 619 it is, for example, given that the low efficiency (so called) is in part attributable to the fact that the "efficiency of transmission was not what was hoped of it."

Mr. E. G. BEAUMONT: It refers you back to the earlier trial.

Mr. LANCHESTER: It may or may not, but I have since dealt with it in preparing the paper for press. Whatever ground there may be for complaint is due to the fact that the paper has been very much condensed.

Mr. BEAUMONT: It refers to 1901, when, as is stated in the book, very little data was available, and very little was known on the subject.

Mr. LANCHESTER: That is the main point of my argument; Mr. W. Beaumont's calculation is founded on entirely insufficient data.*

I have been very much interested in hearing from Mr. Oppermann an account of his early work in connection with worm gear, especially so as my own recollections of what he had done were

* (*An explanatory note has since been inserted.*—ED.)

(Mr. F. W. Lanchester.)

somewhat hazy. I have fully appreciated the difficulties mentioned by Mr. Oppermann in connection with ball bearings; in my own early cars, built about 1896 and 1897, I had to design and construct the whole of the ball bearings necessary, in fact the ball bearings used on the 10/12 h.p. Lanchester car commercially manufactured in 1900 were all home-made, it was only subsequent to this date that ball bearings as we know them to-day became articles of commerce. I think the tests made in 1904 by Mr. Oppermann, from which he appears to have reached the conclusion that the worm, the bevel and the chain give approximately equal efficiency, are of considerable interest; I am not acquainted with any direct comparative tests that had been made elsewhere at that date. On the question of sluggishness of the worm at starting, it is of interest to point out that where (as is the case in an electric vehicle) the horse power is low, the slightly lower efficiencies of worm gear at low speeds might easily be noticed, but this is an effect which it is scarcely possible to observe in an ordinary petrol car owing to the fact that when the worm speed is low the car is usually being driven on one of its lower gears. Under these conditions the torque available is in excess of what the road wheels will transmit, and so the limit of acceleration is determined by the skidding of the road wheels rather than by the driving torque available on the road wheel axles. On the question of the efficiency of the Oppermann worm gear, I note that Mr. Oppermann is not quite prepared to vouch for the 90 per cent mentioned by Mr. Beaumont. I should not, however, consider the figure in question improbable, although speaking from memory, I believe the angle of the Oppermann worm was considerably less than that now known to give the highest efficiency; as far as my recollection serves me, the angle employed by Mr. Oppermann was about 30 degrees, but as I believe I only saw the gear in question once, and that about fifteen years ago, this estimate may be entirely at fault. However that may be, I am glad that some permanent record has been made of the work done by Mr. Oppermann. On the question of the bronze being squeezed or spun out, I am sure my explanation is correct; there is ample evidence that it was not a temperature effect at all. The bronze showed no evidence of over-heating, and the conditions were such that there is no possibility that the matter can be explained on that basis. I have seen worm gears which have never been lubricated and which have suffered from overheating,

even to the extent of the complete disintegration of the alloy of the worm wheel and the separation of lumps of almost pure tin. I have seen things that came quite as a surprise in that direction, but the action under discussion is an entirely different matter.

Mr. Oppermann expresses regret that the question of mounting or housing worm gear has not been touched upon. The housing of worm gear, if usefully or adequately dealt with, would require far more space than could possibly have been devoted to it in the present paper.

Prof. Archibald Sharp mentions that when he was apprenticed in marine engineering 70 lb. per square inch was regarded as the absolute limit to be put on a thrust bearing. It is evident that thrust bearings in which such pressures cannot be exceeded cannot be really adapted to take pressure at all, in view of the fact that the pressure on journals is frequently carried as high as 800 lb. per square inch, and in such cases on the connecting rod heads pressures of even 1,200 lb. or more are commonly met with. However, all these pressures pale into insignificance compared with those carried on the contact surfaces of worm gear. The difficulty is to actually express the pressures carried on worm wheel teeth; it has been pointed out that if we assume the pressure to be distributed uniformly over the tooth face, the intensity of pressure that can be carried is already higher than we are accustomed to in other branches of engineering, but since we know that the actual force is transmitted by a very small fraction of the total tooth area at a time, we realise definitely that the actual pressure on the proximate contact surface is many times greater than anything with which we are familiar in ordinary lubricated thrust or journal bearing experience. As pointed out in the paper, I know of no better method of estimating the actual pressure than by the fact that it appears to be at least equal to the crushing strength of the bronze. It seems to me that in the design of thrust surfaces, journals, etc., we engineers must have missed something, and I have a feeling that some revolutionary work has to be done in the design of lubricated journals. As confirming that view, I have recently heard of a thrust shaft bearing in which the thrust is taken by very narrow radial strips of hard steel, and in that case the pressure on their surfaces was enormously greater than anything previously employed. I think I have already dealt with Prof. Sharp's main question on the oil film matter.

(Mr. F. W. Lanchester.)

Mr. Legros raises one or two points and makes suggestions of considerable interest in connection with worm gear. In brief his suggestion is that, just as ordinary spur gear is geometrically related to rolling pitch cylinders, or bevel gear based on pitch cones, so worm gear should be founded on pitch hyperboloidal surfaces, the tooth form being produced by planing, and so the problem of the hollow or Hindley type worm would be capable of symmetrical treatment. I think the main difficulty in carrying out this suggestion is due to the fact that the tooth could strictly speaking only be planed on its pitch line. There is also the difficulty that it is impossible to make any independent selection of the tooth angle when once the pitch ratio is specified, and so, if efficiency is a matter of importance, or if the exigencies of design impose any particular restrictions on diameter, the method becomes inapplicable. Consider, for instance, the case of any two given neck diameters; now, since the gears have to work together, the hyperboloidal surfaces are defined, the external neck radius of the hyperbola of the one blank being identical with the radius of circular mid-section of the other blank. Under these circumstances the angle of the common generating line is defined, and the ratio of the gear also is defined, so that if the particular ratio or angle does not happen to suit the designer it may be impossible to construct the worm gear required by the suggested method. After considering questions of this kind in all their bearings, the conclusion seems inevitable that the problem is to be treated on an unsymmetrical basis. Mr. Legros asks a question as to the end for end symmetry of the worm gear constructed by the method described in the paper. If the work is executed with sufficient care there is no reason why a worm should not be reversed end for end, that is to say, there is no intentional want of symmetry in the gear in this respect. It is, however, found far preferable to mount the gears in their correct end for end position, and all worms and worm wheels are clearly marked and instructions are issued to avoid any mistakes being made.

I was very much interested in hearing from Mr. C. E. Davis of the trial of the Lanchester worm in the States. This must have been a very instructive test; we have, it appears, run a Lanchester worm over six different routes from New York to Chicago and back. Are we justified in the presumption that one Lanchester worm has worn out about 12,000 miles of American highway?

Mr. C. E. DAVIS: If it will stand that it has great durability.

Mr. LANCHESTER: At least it appears to have had to take a new route every time.

Mr. DAVIS: It was desired to try every type of road that we have.

Mr. LANCHESTER: Mr. L. H. Hounsfield tells us that he has himself tested a worm gear and found the efficiency 30·7 per cent, and that it went down to 11 per cent at light loads. Evidently this was a fine pitch motion-transmitting worm not fitted with anti-friction bearings. It is very candid of Mr. Hounsfield to say all that he does on this point, but he was certainly not the only engineer in this country that would have made a grave mistake if he had been called upon to give an opinion on power transmission worm gear at the date in question. It really is scarcely fair to use the same term for the worm gear that is to be seen on a hand crane as that used for the propulsion of motor vehicles, and an opinion based on the study of worm gear of this type would evidently require to be entirely revised where a well designed power transmission gear is in question. Mr. Hounsfield mentions having found an assortment of nuts, balls, etc., in a worm gear box without the worm showing serious injury. I have myself seen strange objects removed from a worm gear case, varying from a shifting spanner to a solid silver spoon, without any permanent injury having been done.

Mr. Hounsfield also asks for information on the subject of a suitable lubricant for worm gear; at the present time the lubricant has to be selected to suit the circumstances, and I am afraid that up to the present the results brought out by the recent test have had but little influence in practice. Circumstances governing the class of lubricant includes such questions as liability to leakage as affected by the viscosity of the oil; liability to leakage standing as affected by the power of the oil to solidify when cold, relative importance of obtaining highest possible efficiency, etc. There is no doubt where circumstances permit an oil such as castor oil, lard oil or sperm oil give the better results.

Mr. H. W. Staner raises the question as to why no world's records have been made with the worm gear, that is to say, he points out that no actual track or road records have hitherto been undertaken by the worm propelled vehicles. The probable explanation is that hitherto the worm has been adopted by firms whose immediate object was to obtain silence and smoothness of running, and so the racing side of the business, so to speak, has

(Mr. F. W. Lanchester.)

been neglected. However, from a business point of view the absence of a world's record is certainly an omission that it will be worth while repairing in the future.

Replying further to Mr. Staner, I cannot say that I have made any special experiments with an accelerometer to show the effect of using highly viscous lubricants; there is no doubt, however, but that results could be obtained by that method. The screw gearing referred to by Mr. Staner as having been used for steering gear, in which a screw is used and a nut cast round it in white metal, is not a type of gear that one would describe as a worm gear in the sense of the present paper.

In conclusion, Mr. Browne (President) has kindly called my attention to the fact that I have omitted to state one of the claims that may be urged in favour of worm gear, namely, the possibility of making a single reduction at one step of greater ratio than practicable in any other form of gear; the reductions mentioned by Mr. Browne, 12-1 and 14-1, are quite possible reductions obtainable by worm gearing. For reductions of this magnitude it is, however, not always possible to design for maximum efficiency owing to the fact that the worm becomes very small in relation to the wheel diameter, and so for carrying given torque the centres have to be wider than would be otherwise desirable. Alternatively, a certain amount of efficiency may be sacrificed and the worm diameter not reduced to the full extent; in this manner it is possible to work with a more compact design of gear, but the efficiency must suffer in some degree. It would appear, however, that where the worm gear is employed of a ratio that obviates a double reduction, the efficiency permissible may be legitimately compared with the efficiency of a double train of gearing of another type.

With regard to Mr. Browne's suggestion that experiments might be made with a transparent wheel, according to Professor Coker's method, I have not considered this seriously. I do not think the method would be altogether applicable, but if it should be found possible to make worms and wheels of a transparent material that would in any way resemble bronze and hard steel some information might be gained by the examination of the interference rings surrounding the region of contact, using ordinary (not polarised) light. Whether information of this sort, when obtained, would be of any value or not I cannot say; it would appear to be more of academic interest than anything else.

I quite agree with Mr. Browne that there are many cases where worm gears, or rather screw gears, are applied to auxiliary purposes on an automobile, both in the motor and on the chassis; in the motor for such purposes as valve gear, and magneto driving in which there are reversals of stress. I think a worm gear of the Lanchester type, if it were worth making for the purpose, would be preferable to parallel gear, because there is a good deal more oil cushioning on these reversals than with screw gear in which, practically speaking, there is only nominally point contact. In practice the best way out of the difficulty is to put some constant resistance on the same axle. For instance, by arranging a cross shaft on the engine with the circulating pump at one end and the magneto at the other; the constant resistance thus applied prevents the chattering of the gears. Alternatively, a flywheel may be fitted on the magneto to minimise the snatching action.

COMMUNICATED.

Mr. C. A. BRANSTON wrote: Will Mr. Lanchester tell us something about the fourth type of worm gear mentioned in his paper—the true screw gearing into a hollow ground worm? What are the peculiarities, advantages and disadvantages of its use and of its manufacture?

I would also ask the author if he is able to explain the phenomenon of a worm of the hollow type emitting a humming noise when running? Wishing to lower the gear ratio of my six-cylinder Lanchester car, I had it altered by the makers from 9/34 to 8/35. After the alterations, the back axle emitted a distinct hum, the loudness of which varied with the *torque* transmitted, while the *pitch remained practically constant at all speeds*.

On the subject of the history of the Hindley worm, I give below a passage from a paper on "The Graduation of Astronomical Instruments," read before the Royal Society on Nov. 17th, 1785, by John Smeaton,* the civil engineer and architect of the third Eddystone lighthouse.

" . . . On the first interview, he (Hindley) showed me not only his general set of tools, but his *engine*, at that time furnished with a dividing plate, with a great variety of numbers for cutting the teeth of clock wheels, etc., and also, for more nice and curious purposes, furnished with a wheel of about thirteen inches diameter, very stout and strong, and cut into 360 teeth, to which was applied an endless screw, adapted thereto. The threads of this screw were not formed upon a cylindric surface, but upon a solid whose sides were terminated by arches of circles. The whole length contained fifteen threads, and as every thread (on the side next the wheel) pointed towards the centre thereof the whole fifteen were in contact together; and had been so ground with the wheel, that, to my great astonishment, I found the screw would turn round with the utmost freedom, interlocked with the teeth of the wheel, and would draw the wheel round without any shake or sticking, or the least sensation of inequality. . . . He told me

* Phil. Trans., Vol. LXXVI., p. 19.

that the screw was cut by the rotation of the point of a tool, carried upon a strong arm, at the distance of the radius of the wheel from the centre of motion, which arm was carried forward by the wheel itself, and the wheel was put forward by an endless screw, formed upon a cylinder to a proper size of thread, cut by his chock lathe; he showed me also this chock lathe, and the method employed to make the threads of the screw *equiangular* with the axis, that is, to free the screw from what workmen term *drunkenness*; and also showed me how, by the single screw of his lathe, he could cut, by means of wheel-work, screws of every necessary degree of fineness (and, by taking out a wheel, could cut a left-handed screw of the very same degree of fineness); by which means he was able not only to adapt his plain screw to the size of the teeth of his wheel, but also to prevent any 'drunkenness' that otherwise the curved screw would be subject to in consequence of being produced from the plain one; . . ."

I may, perhaps, add in conclusion that Henry Hindley was a clockmaker of York; he was born in 1701 and died in 1770; it was in the autumn of 1741 that Smeaton made his acquaintance and saw the mechanism described above, and which had then, according to the latter, not yet been in use for many years.

Mr. H. KERR THOMAS wrote: Mr. Lanchester states that accurate tests show the parallel worm to be inferior to the Hindley type both in efficiency and load capacity. He has evidently overlooked the long series of tests carried out by Prof. Kennerson of the Worcester Polytechnic at the factory of Messrs. Brown and Sharpe Manufacturing Company, Providence, R.I., where exactly the opposite result was obtained. It would appear that since two trained observers arrive at precisely opposite conclusions in respect of the two kinds of gears, each giving to the other kind of gear an advantage of about 1 to $1\frac{1}{2}$ per cent, it is reasonable to suppose that the efficiencies if taken over a sufficiently long number of examples would be equal. Moreover, if the subject be treated from a purely theoretical standpoint, the two *are* equal, and the actual experience of a large number of users who employ a parallel type of worm shows that perfectly consistent and satisfactory results are daily obtained from it.

The author points out that having regard to the fact that the worm wheel must be of substantial thickness, it renders it undesirable in practice to use more than a very moderate length of worm with the Lanchester gear. I will substitute for the author's

(Mr. H. Kerr Thomas.)

word "worm" the word "hob." If Mr. Lanchester's hob be extended lengthwise to embrace more of the worm wheel, it will be found that it does not cut a Lanchester worm but a Hindley worm wheel, which is flat on the top of the teeth. In other words, when a worm wheel is generated with a hob, *either the worm or the wheel must be parallel, the other being hollow*. Mr. Lanchester's ingenious compromise between the two forms is, in my opinion, of doubtful advantage, although I fully admit it has given entirely satisfactory results.

Coming next to the question of tooth pressures, I cannot follow the author's reasoning when he refers to the wear which takes place on a worm wheel by the lengthening of the teeth. I agree that this does occur, but Mr. Lanchester first assumes that the bronze has a hardness of 50 tons by the Brinell test, and then, having observed that the teeth after 10,000 miles of wear have lengthened, he assumes that the working pressure was 50 tons. Mr. Lanchester, it would seem, has overlooked the lengthening effected on the teeth by the spinning action of the worm, and also the "peaning" effect of innumerable repeated but relatively light blows which will tend to cause the metal to flow. It is quite a simple matter, however, to calculate the actual pressure between the surfaces of the worm and the wheel, and it can be shown that this pressure is expressed by the equation

$$p = \sqrt{(T \cot \alpha \tan (\psi/2))^2 + (T/\sin \alpha)^2}$$

where α = pitch angle;

T = torque in lb. at pitch line;

ψ = normal included thread angle.

I agree with Mr. Lanchester, however, that even on this basis the wearing pressures permissible in worm gear are amazingly high, and I think he has hit upon the only explanation when he refers to the crowding of the oil in advance of the line of contact, which virtually produces a volume of oil under considerable pressure, which is capable of supporting momentarily an immensely high load.

Mr. Lanchester's method of testing efficiencies as exemplified in his new machine appears to be wholly admirable, and it is to be hoped that very extended use may be made of this with other gears than those examined by the National Physical Laboratory.

Mr. FRANCIS J. BOSTOCK wrote: (1) I agree with Mr. Lanchester that good worm gearing is quite as efficient as either bevel or

chain transmission, but I certainly do not agree that the hollow type worm, known in different parts of the world as Hindley, Globoid, Hour Glass, Lanchester, etc., is more efficient than an equally well designed and manufactured parallel worm.

(2) The Lanchester worm gears taken from stock and showing efficiencies of 95 per cent to 97 per cent are very good, but no better than efficiencies of similar gears with the parallel worm. The high efficiency of parallel worm gear has been demonstrated by numerous authentic tests, notably those by Mr. F. Berry, The Oerlikon Co., Switzerland, and Brown and Sharpe, America, recently described in the Proceedings of the Society of American Mechanical Engineers. Years ago, when even in its transition stage from a motion transformer to a power transmitter, the efficiencies varied up to 95 per cent. Since then the subject has been more understood, and the machines and methods have been vastly improved.

(3) Mr. Lanchester states "the present position of worm gear is the definite outcome of the uninterrupted success of the Lanchester worm gear." I do not agree; I think my firm, Messrs. David Brown & Son, have had a great deal to do with this, and they have probably devoted more time and spent more money on this particular form of gear than any other firm, and to-day I believe they have the largest plant in the world for dealing with it. While Mr. Lanchester has been devoting his time to automobile gear, they have, in addition, been manufacturing it for every conceivable purpose, and in sizes up to those weighing, with casing, 30 tons, efficiencies as high as 98 per cent being frequently attained when conditions are favourable, as is generally the case in automobile transmission. My firm's experiments have proved over and over again that with correctly designed and accurately made gears for automobile transmission, these high efficiencies are regularly obtained.

(4) Some time ago, in order to ascertain the efficiency of a worm driven back axle as a unit, David Brown & Sons, Ltd., made a series of tests on a chassis in the course of erection, by replacing the cardan shaft with an Amsler torsional dynamometer, locking the differential, jacking up the chassis, and applying a special Prony brake to one of the rear wheels (see Fig. 32, Plate XVII.). The resulting efficiencies at the different speeds and loads varied between 94 per cent and 96 per cent. This result included the loss in friction by the universal joint, the journal

(Mr. Francis J. Bostock.)

and thrust races, felt washers for oil retaining, the air resistance of the spokes and felloes of the wheels—in fact, the conditions were, as nearly as possible, those actually obtaining on the road, and I must call attention to the fact that this parallel worm and wheel had been assembled exactly as they came from the machines, without any previous running. This proves conclusively that the parallel type is now manufactured by my firm with such a degree of accuracy, that it attains this high efficiency right at the very commencement, whilst I notice that in the Daimler tests, in one case at least, the gears were previously run for a period equivalent to a distance of 2,000 miles, and that actual test extended over a period of five minutes only, whereas, to obtain any really valuable data, each test should have been extended over several hours. The tests carried out by Mr. F. B. Waterman, of the Brown & Sharpe Co., U.S.A., and referred to above, gave efficiencies for the parallel type worm up to 97·9 per cent.

(5) I had previously noted that the Warner Gear Co., of Indiana, U.S.A., has adopted the Lanchester type of worm gear, but I was also aware that the largest back axle manufacturers in the world had been studying this question for the past three years. Their engineers had investigated all the various types represented by the leading firms, including the design, the manufacture and testing, both on the road and on the bench. On their return to America, and after comparing notes, they decided that the parallel type of worm was by far the most suitable. They could not agree that either type could claim the advantage as regards efficiency, but they were unanimous in that the parallel type alone presented a thorough manufacturing proposition. The outcome of it all is that the initial complete plant, with a guaranteed output of 1,000 sets per week to commence with, is being made in Huddersfield by David Brown & Sons, Ltd., for the “D.B.S.” type, and according to their design and practice.

(6) It has been stated that the Lanchester type would probably carry a higher load than the parallel type, and that a greater area of contact can be obtained by virtue of the worm wrapping round the wheel; if this be so, why does Mr. Lanchester, in all the gears, at any rate, that I have seen, provide such a narrow wheel and so short a worm? Why is not the full advantage taken by making the worm longer and the wheel wider? I believe if this were done, the inherent defects or evils, called by Mr. Lanchester

"incompatibility," or commonly known as "interference," would make this type of gear an impossible one. If my contention is true, and I certainly think it is, these errors must exist to a smaller degree in a short worm and narrow wheel, as even with this short worm Mr. Lanchester speaks of having to make certain corrections.

(7) It seems to me that the diagram showing the mid-section of the hollow worm can only be correct if "the worm wheel be considered as quite a thin sheet or lamina of metal"; since, however, the worm wheel must of necessity possess substantial thickness, the incompatibility mentioned above will prevent such a contact immediately we endeavour "to distribute the wear over the whole width of the tooth face of the worm wheel," so that this ideal condition is not realised in practice. I have examined a number of them, but in none have I been able to make them agree with the diagram. With a correctly made parallel type contacts are made both along the linear and the normal, as shown in Figs. 33 and 34, Plate XVIII.

(8) I consider that there is a serious drawback to the Lanchester type, in the difficulty of setting the worm and wheel in correct alinement in the two ways, and I am led to understand that none of these gears are strictly interchangeable, but that a special packing washer has to be made to suit every individual axle.

(9) This difficulty in setting must be accentuated in running, by the rise in temperature, which will cause mal-alinement; hence the contact between the worm and wheel cannot remain the same; whereas, with the parallel type, such increase in temperature has no corresponding disadvantage.

(10) The question of cost of production appears at first sight to be in favour of the Lanchester, on account of the short worm and narrow wheel, and consequent saving of material; in addition, I believe the Daimler Company limit themselves to comparatively few ratios, thus saving considerably on tools, but against this, they seem almost invariably to supply a worm having a splined bore, leaving their clients to make the castellated shaft, which in all shops is by no means a cheap production. The fewness of the ratios manufactured on this principle is perhaps owing to the fact mentioned by Mr. Lanchester, that each size requires 4 master hobs and 6 working ones.

(11) The parallel type of hob as made by my firm represents a sound manufacturing proposition, without any lengthy processes,

(Mr. Francis J. Bostock.)

and an entirely machine finished job, whereas, with the hollow type, the processes are costly and lengthy, and it seems that the teeth would have to be backed off by hand. It does not seem possible for a fitter to give an accurately filed hob, such as can be obtained from a machine.

(12) I was pleased to observe Mr. Lanchester's adoption of the writer's method of graphically obtaining the pitch diameters for a pair of gears for a given ratio at fixed centres, as shown in the diagram appended to the paper, and as also described in *Machinery* reference book on "Spiral Gearing."

(13) The involute system of gearing owes its existence in shop practice entirely to its being generated from a straight line system; Fig. 35, Plate XIX., shows a section of one of our worms, wherein a straight-sided tooth form is to be seen, and its corresponding cutter, which has a rounded tooth form. The profile of this cutter is generated by means of a patented universal tool, which gives the correct cutter profile for any worm thread, of any lead, pressure angle, or pitch, up to 8 in. diameter. A cutter when so made is used in a worm milling machine, one of which is shown in Fig. 36, Plate XIX., which Messrs. David Brown & Sons, Ltd., have designed, and now manufacture at their works to meet this class of gear cutting.

(14) To my mind, one of the first conditions of a manufacturing proposition is that there shall be an easy and accurate way of measuring for interchangeability. Mr. Lanchester has not mentioned interchangeability, which is absolutely essential; a hob after once being sharpened does not cut quite the same form again. It would be interesting to hear how Mr. Lanchester detects such an error, and how he avoids it. With our special system of reamer hobs this grinding has practically no effect whatsoever, and immediately the effective pitch diameter is reduced more than a few thousandths, the hob is rejected. Figs. 37 and 38, Plate XX., show a "DBS" worm and wheel testing machine, wherein the worm in one case is being tested for the diameter of pitch line, and in the other for the angle of the tooth face.

(15) By means of other measuring instruments on similar lines, my firm are able to so correctly gauge a worm and wheel that they are manufactured as independent units, and not tried together until they are absolutely finished, as shown in Fig. 39, Plate XXI. This system ensures perfect interchangeability. We have prac-

tically discarded the usual gear tooth method of measuring for interchangeability, as it is wanting in accuracy.

(16) I am entirely in accord with Mr. Lanchester when he says that "minute differences in the physical condition of the tooth make a difference in the efficiency," and I know well that the minutest error in the tooth shape will make a far greater difference in the efficiency. It is universally recognised in engineering practice, that all important work must be rectified after hardening; a worm that has not been rectified cannot possibly compare with one that has had its thread accurately ground. From a careful study of the "Hindley" type of worm, I am compelled to conclude that the grinding of its thread is an extremely difficult job; in fact, it seems that its very nature prohibits such an operation, especially when accuracy is the all-important factor. This, to the mind of all engineers, presents a difference between the two systems which is of vital importance.

(17) My firm have for a long while considered it absolutely necessary to grind the worm threads, and for that purpose have designed and built automatic machines specially for the grinding operation; Fig. 40, Plate XXI., shows a front view of one of them. The abrasive wheel has its profile automatically formed by a patented generating tool, whilst the machine is entirely automatic in all its functions, and the worm to be ground is supported on fixed centres, under exactly the same conditions as for the grinding of its cylindrical parts. Our aim and procedure in manufacture is to obtain a worm as perfect as possible before hardening, and simply to rectify the distortion due to hardening which takes place even after most elaborate precautions.

(18) Reverting to the hobs for the cutting of the worms and wheels, I fully appreciate the work done by Mr. Lanchester in this direction, and the difficulties he has had to contend with, such as the tearing away of the tooth face, especially when endeavouring to cut a nickel or a nickel-chrome steel worm. Can Mr. Lanchester now supply worms of the latter material, made solid with the shaft, which we find are nearly always asked for?

(19) The method of cutting the wheels of the parallel type is different from that of cutting the hollow type in that the former are "fed through" whilst the latter are "fed into." It is the former way that gives such a nice and accurate finish to the "DBS" worms. Fig. 41, Plate XXII., shows one of the patented worm wheel generators, specially designed for automobile gears.

(Mr. Francis J. Bostock.)

I cannot understand any hesitancy on the part of automobile-manufacturers with regard to the adoption of worm gearing.

The amount of time and study that Mr. Lanchester has devoted to this subject deserves the thanks of all engineers, and the motoring public generally, and no one appreciates the work he has done more than myself, and I hope that the remarks that I have made will be taken in the spirit intended, but at the same time I cannot help expressing my regret that the tests were not of sufficient duration to give such valuable data as might have been obtained.

In reply to the written communications, Mr. LANCHESTER wrote: I am unable to give Mr. Branston much information as to the fourth type of worm gear briefly mentioned on p. 217 of my paper; it is a type with which I have had no personal experience. From a theoretical point of view it may be considered as identical with the parallel worm type of gear in which the worm has become bigger and of higher tooth number than the wheel. I believe Messrs. Brown and Sharpe have adopted this type of gear in certain applications.

I do not identify the humming noise mentioned by Mr. Branston from his description; it would certainly appear to be something abnormal that a pitch note emitted by a gear of any kind should be independent of the speed.

The information Mr. Branston gives, cited from the Phil. Trans. 1785, is very interesting, and I am very pleased indeed to see this reference from the original work of Henry Hindley take its place in the correspondence on my paper. I am sure our Institution have to thank Mr. Branston for digging up this little bit of history, it is most appropriate to the occasion.

Mr. Kerr Thomas says that I have overlooked the long series of tests carried out by Professor Kennerson at the factory of Messrs. Browne and Sharpe Manufacturing Company. I may state once and for all that I have not overlooked these tests, though I do not mention them in my paper. Mr. E. G. Beaumont in the discussion has already called my attention to the omission and he has briefly cited the results of Prof. Kennerson's tests. My reason for ignoring the tests in question is that, in spite of all the care that is said to have been taken, the experimental results show such divergence amongst themselves, and there is so much internal evidence of inaccuracy, that if I had cited them

it would have been to throw doubt on their accuracy. As, however, the matter has been raised, the following comments will not be out of place.

The method used for the determination of efficiency, as given in Prof. Kennerson's paper, namely, a transmission dynamometer and an Alden brake, is not one that, it appears, can be relied upon within 2 per cent or 3 per cent. In support of this contention, I would first call attention to the variations of the transmission dynamometer reading in the Table on p. 10 of the reprint (p. 1332 of the Proceedings of the American Society of Mechanical Engineers). In this table the dynamometer measurements are

FIG. 42.

given as an average of three readings, and in the five cases tabulated these readings vary amongst themselves 1 per cent, 1 per cent, 2 per cent, 1 per cent, and $1\frac{1}{2}$ per cent respectively; in addition to this there is the error of the brake reading, which probably is an amount of about the same magnitude, so that the variations may possibly range over 4 per cent, i.e., plus or minus 2 per cent from the correct readings. This is the kind of error which is very commonly met with in such combined brake and dynamometer readings. It is possible that Mr. Waterman, who is apparently responsible for the experimental work, might be inclined indignantly to repudiate any such possible degree of inaccuracy.

(Mr. Lanchester.)

Let us refer to the plottings of the actual experiments as given. Firstly, we find that the plottings, p. 13, of the reprint do not in every case quite agree with the Tables, p. 11. However, the disagreement, such as it is, may be ignored. I have elected in Figs. 42 and 43 to replot from the actual figures. In Fig. 42, Curve A, these plottings are shown as relating to Table I., which happens to be a worm gear of the Brown and Sharpe type. In this diagram I have connected up the observations by straight lines as in Prof. Kennerson's paper, and it will be seen that if these curves were correct the efficiency at 63 h.p. is 95 per cent, at 67 h.p. it

FIG. 43.

is 97.7, and it is evident that, unless something very sudden happens to the curve at this point, at 70 h.p. we have entered the region of perpetual motion, the efficiency being about 110 per cent! Of course it will be argued that the curve will not go on rising in this way, but evidently something sudden must happen to it very soon, and altogether it is a grossly improbable curve.

To compare with this curve I have given on the same diagram a series of observations taken on the Daimler-Lanchester testing machine at approximately the same worm tooth velocity, Curve B. The horse-power scale has been altered in the ratio required on the basis of worm gear centres to render the two sets of observations comparable. It will be seen that the observations in question are reasonably consistent with one another, and suggest a curve of

a rational form; that is to say, a curve in which there is a tendency to approximate a maximum efficiency value over a certain range of horse-power. If, as in Fig. 43, Curve E, each observation in Curve B, Fig. 42, be represented by a short vertical line giving the maximum possible error of observation as certified by the National Physical Laboratory (that is, roughly, plus or minus a fifth of 1 per cent), a smooth curve can be drawn as shown that is probably as near the truth as it is humanly possible to be. It is quite certain from the whole of the experiments conducted by the N. P. L. that worm efficiencies do not jump up and down like a "jack-in-the-box"; variations doubtless occur, but not such as shown in line (A), Fig. 42, or such as would be necessary to continue this line for higher horse-power than that actually tested. Beyond this, it is definitely established that in general character these efficiency curves are curves convex upwards like a trajectory. If we adopt the same method of vertical lines, giving limiting values of errors of observations (Fig. 43) in the case of the Brown and Sharpe worm, as in the case of the Lanchester, we find that with a 2 per cent error (plus or minus) as anticipated above, it is just possible to draw an inclined straight line C without going outside the limits, and in order to give a curve of anything like probable form one has to assume that some of the observations on which Mr. Bostock, of Messrs. David Brown & Sons, is relying had an error of nearly 3 per cent. In Fig. 43 such a curve is given (D), and the dotted extensions of the vertical error lines are shown to indicate a 3 per cent observation error.

As a general proposition, where a curve is actually a smooth curve, it is always possible to estimate the magnitude of the errors by drawing lines through the highest and lowest observed points, provided that sufficient observations exist. In the case of the plottings in Prof. Kennerson's tests, sufficient observations do not exist for this method alone to be employed, but I think that any unprejudiced person studying the paper in question and examining the plottings given in Figs. 42 and 43, will agree that the suggested lines C or D have every probability of being more accurate than the line A in Fig. 42.

One wonders, having got so far as to have plotted the line A up to 67 h.p. and 97.7 per cent efficiency, and if the experimenter believed in his results, why he did not carry his experiments a few horse-power higher to see what becomes of this ambitious curve.

(Mr. Lanchester.)

I candidly do not understand Mr. Kerr Thomas when he says that if the subject be treated from a purely theoretical standpoint the two efficiencies* are equal. Mr. Kerr Thomas does not give the particular theoretical standpoint from which he treats the subject, so that in the present discussion I am only able to say that in any theoretical treatment of the subject with which I am acquainted, the materials on which to calculate the relative efficiencies of the hollow type or the parallel type of worm gear are entirely lacking. One factor in the efficiency of a worm gear is the coefficient of friction between the worm and the wheel teeth, and all depends, other things being equal, upon the perfection of the film of lubricant; now since it is manifest that the perfection of this film depends upon the conformability of the surfaces, it is quite clear that where the geometry of these differs materially we may expect to have corresponding differences of efficiency; how any rational theory can deny such self-evident a fact I am unable to conceive.

Some of Mr. Kerr Thomas's remarks appear to be directed to show that the Lanchester worm is not a Hindley worm, and not being a Hindley worm it is a compromise, the advantage of which is doubtful. I do not follow Mr. Thomas at all.

Mr. Thomas gives a wonderful equation by which he states "it is quite a simple matter to calculate the actual pressure between the surfaces of the worm and the wheel." It appears to me that Mr. Thomas is confusing his terms; his equation might, if it were correct (which I do not think it is), give the actual *force* between the teeth, but in order to know the *pressure*, one must know the area of surface of the teeth on which this force is at any instant distributed. For example, if the force is distributed over the whole of one tooth face in the Lanchester gear, the pressure works out as from one ton to two or three tons the square inch (compare p. 234 of the paper); as stated this is the conventional basis on which the preliminary calculation of the Lanchester worm gear is based. In any worm gear the actual surface in contact is extremely difficult to estimate, as the effective surface of contact is a small area of the worm face over which the oil film is able to transmit pressure between the two surfaces; obviously this is not a defined area but one in which the pressure will be highest in a small central region and less nearer the edges. I am amazed to

* Hollow and parallel types of worm.

find Mr. Thomas falling into so hopeless a confusion of terms. He does not seem to appreciate the fact that it is the very spinning action of the worm to which he makes reference, and, to use his own words, 'the peaning effect of an innumerable number of repeated but relatively light blows' that I have already referred to in my paper as the cause of the ultimate failure of the worm wheel teeth under overload conditions. In my paper (p. 234) I say "*and the manner of a failure of this kind denotes that the bronze has slowly yielded by a kind of spinning action to the pressure applied.*" Evidently Mr. Thomas has not carefully read my paper. I may further point out that the local pressure required to spin or pean out bronze of 50 tons crushing limit (Brinell test) is a quantity approaching or comparable to 50 tons per square inch, for so long as the elastic limit of the bronze is nowhere exceeded it will not suffer permanent deformation. If Mr. Thomas will refer to my paper he will find, on the same page: "It is evident from these observations that the pressure transmitted from the worm to the wheel is *of the order of 50 tons per square inch*"; in view of the words italicised, Mr. Thomas's criticism appears to be entirely without foundation.*

In order to facilitate a reply to Mr. Bostock's communication and for the purposes of reference, I have numbered the paragraphs consecutively.

(1) and (2) Mr. Bostock, in these paragraphs, states that he does not agree that the hollow type worm has a higher efficiency than the parallel type. I had not the intention of making a sweeping statement that such is the case, and in view of the fact that I have not tested the parallel gears of every make extant, I should not be entitled to formulate such a result definitely; the experimental evidence, however, does point to the higher efficiency of the hollow type worm, and Mr. Bostock brings forward no evidence in support of his contention.

(3) In paragraph (3) Mr. Bostock, quoting from my paper, objects to my statement that "*the present position of worm gear is the definite outcome of the uninterrupted success of the Lan- chester worm gear*"; he says that he does not agree. Mr. Bostock

* As Mr. Kerr Thomas' conception of such quantities of pressure and force appears from his communication to be different from those which have currency on this side of the Atlantic, I would point out that the term "pressure" is definitely used in my paper to denote force per unit area, just as, for example, density is mass per unit volume.

(Mr. Lanchester.)

adds: "I think my firm (David Brown & Sons) have had a great deal to do with this, and they have probably devoted more time and spent more money on this particular form of gear than any other firm." I can only meet Mr. Bostock and Messrs. David Brown & Sons with facts. The Lanchester worm gear was applied to the Lanchester car in 1897, it has been applied to every Lanchester car built since that date as a matter of continued engineering and business development. *Eight years* after this date (in 1905) the only cars employing the worm gear besides the Lanchester were the Dennis and the N.E.C. When the Dennis first appeared (I believe in 1904) the success of the Lanchester gear was actually quoted to a supposed prospective purchaser by a Dennis salesman as justifying the use of a worm drive. The N.E.C. appear to have adopted the worm drive at the same time as other features too obviously resembling the Lanchester car to leave much doubt. About 1907 worm gear was introduced to the Wolseley Company by Mr. Max. Lawrence, who makes no secret of the fact that the general proportions of the parallel worm gear adopted were founded on Lanchester practice with which he had become familiar when Works Manager to the Lanchester Company. More recently, from 1909-1910, the Daimler Company adopted the Lanchester gear for the whole of their output. The Napier, on worm driven cars built by them, also adopted Lanchester gear. The Deasy also adopted the Lanchester gear about the same time as the Daimler Company. The above facts, I think, are sufficient to establish my claim.

As far as I am aware, Messrs. David Brown & Sons, on whose behalf it appears Mr. Bostock writes, did not come seriously into the arena till within the last five or six years.

In paragraph (4), it is interesting to note that Messrs. David Brown & Sons have been obtaining results of 94 to 96 per cent as the efficiency of their gears. The weak point, however, in these tests is the somewhat crude apparatus used; there appears to be no question that such apparatus as used and illustrated, Figs. 37 and 38, Plate XX., cannot be relied upon to give results much within 1 per cent or 2 per cent of the truth; it does not appear to be in any way superior to the testing appliance used by Prof. Kennerson. In the latter part of this paragraph it is difficult to understand Mr. Bostock's argument; it appears to be roughly this, that if the Daimler test has been made after "running in" equivalent to 2,000 road miles at load, it is a

great virtue of his D.B.S. gear to have given its results without being previously run in at all; if, on the other hand, the Daimler tests had been made without the 2,000 miles running in, then presumably the criticism that the actual tests only lasted five minutes would have been held by Mr. Bostock to render them worthless. It is difficult to say much in reply to this kind of discussion. If Mr. Bostock wishes to suggest that the National Physical Laboratory tests are delusive on account of the shortness of their duration, then he entirely deceives himself.

The tests referred to by Mr. Bostock as giving 96.9 per cent are, I think, those referred to in other parts of the discussion; the supposed efficiency quoted is merely one of the peak points in an inaccurately plotted diagram, in other words, a freak reading probably 2 per cent higher than the actual figure.*

If, in paragraph (5), Mr. Bostock is referring to the Timken Roller Bearing Company, I can only reply that a representative of the said company interviewed the writer at the Daimler works and expressed great regret that we had already made over our rights in America to the Warner Gear Company; if my surmise is correct, I do not think Mr. Bostock is entitled to write in a manner inferring that this company gave their preference voluntarily to the D.B.S. type.

(6) I candidly do not know what Mr. Bostock is driving at; he appears to have had a quarrel with the hollow worm because it is not what it doesn't pretend to be.

(7) I am again completely at a loss to follow Mr. Bostock's argument. He seems to be trying to tell me that the things that I have done are not possible; if that is his intention he certainly goes out of his way to disguise a pretty compliment.

In paragraph (8) it would appear that Mr. Bostock is not acquainted with what is known as an *accommodation piece* in an assemblage of interchangeable units; it often happens that in the mounting or assembling of any group of parts the use of an accommodation piece, such as a washer of variable thickness, will allow commercial limits to be used where otherwise an altogether too high a degree of accuracy for shop practice would be needed. In the present case the washer referred to by Mr. Bostock is not employed with the object of compensating for any want of interchangeability in the worm itself, but is required

* Compare pp. 299, 300, Figs. 42 and 43.

(Mr. Lanchester.)

owing to the accumulation of smaller tolerance errors, mainly due to the want of interchangeability of ball bearings; as manufactured the makers of ball bearings will not guarantee a very high degree of accuracy.

The difficulties suggested in Mr. Bostock's paragraph (9) have not, in an experience of fifteen years, been found to exist in practice.

Replying to paragraph (10), the system of mounting parts on splined shafts, which was mainly introduced in the automobile world by the author of the present paper (having been used on every Lanchester car turned out since 1900), is actually the cheapest form of mounting. The number of ratios and standards employed by the Daimler Company are supplied to meet every reasonable demand.

(12) I believe I have to acknowledge Mr. Bostock's priority as to the graphic method of obtaining pitch diameters, etc., which in my paper I attributed to Mr. Milligan; I will say, however, that although Mr. Bostock has undoubted priority both as to the method and publication, I am quite satisfied that Mr. Milligan worked the method out independently. Since the receipt of Mr. Bostock's communication, full acknowledgment has been made in the text of the Appendix III.

(13) In reply to paragraphs (13), (14) and (15), perusal of my paper will, I think, satisfy any reader that interchangeability is obtained in the case of the Lanchester gear by the standardization and reproduction of the working tools from the master set. In practice there has never been any difficulty on this score.

Paragraph (16) may sound all right but is actually wrong. In worm gear a high polish of the tooth is more important than an absolute ground surface, at least this is the result of the author's experience.

Paragraph (17) appears to require no comment; the particulars of the D.B.S. worm machine are interesting.

In reply to paragraph (18), the Daimler Company, who have the most complete plant for cutting the Lanchester gear, can supply worm gear solid with the shaft, but it is certainly not the best practice. No demand has, in my experience, arisen for chrome nickel steel worms.

Fig. 20.

FIG. 21.

FIG. 22.

Fig. 23.

Fig. 24.

Bus and Commercial Vehicle Type.
 $7\frac{3}{4}$ in. centres.

Touring Car Type.
6 in. centres.

Light Car Type.
120 mm. centres.

FIG. 32.—Chassis, with Brake for testing Worm Gear efficiency.

FIG. 34.—Normal Contact of Worm and Wheel.

FIG. 33.—Linear Contact of Worm and Wheel.

FIG. 36 —“D.B.S.” Patent Worm Milling Machine.

WORM GEAR.

Plate XIX

FIG. 35.—“D.B.S.” Parallel Worm and Cutter.

FIG. 37.—Testing Worm for Pitch Diameter.

FIG. 38.—Testing Worm for Face Angle.

FIG. 39.—Testing Worm and Wheel.

FIG. 40.—“D. B. S.” Patent Worm Grinding Machine.

FIG. 41.—“D. B. S.” Patent Worm Wheel Generator.