The Sunken Battle-cruiser "Seydlitz"

IF the future visitor to Scapa Flow did not know what had happened to the interned German fleet in that remote harbor, he might be excused for supposing that the monstrous thing which projects above the water, as shown in our illustration, was a submarine of vast proportions. As a matter of fact it is the bottom, or rather one-third of the bottom, of the famous German battle-cruiser "Seydlitz," which took part in the running fight of Dogger Bank and, later, in the great Battle of Jutland.

Some of the wrecked ships sank on a fairly even keel, as did the "Hindenburg"; others, like the "Seydlitz," turned over and settled on their sides. This view shows that the ship turned turtle to starboard, leaving the port side and about one-third of the bottom exposed. The dark object astern is a blade of the port wing propeller, the "Seydlitz" being driven by turbines, acting on four shafts, whose horse-power ranged from 90,000 to a maximum of about 100,000.

The "Seydlitz" was built at Hamburg, in 1913. She was 656 feet long; 93½ feet broad; her displacement was 25,000 tons; and her speed was about 27.5 knots. She was heavily punished and set on fire in the Dogger Bank fight, and was severely handled by gunfire at Jutland.

Many people were surprised that such big ships could have been sunk so quickly; but if we consider the great number and large size of the openings from the interior of the ship to the sea below sea-level, the problem becomes simple.

Referring to the photograph, the long dark object at the turn of the bilge is the bilge keel, put there to prevent rolling. Below it is one of the docking keels, and the two oblong openings astern of the latter are the two intakes for the two port turbine condensers. There are two more of these on the opposite side of the center of the ship. The inflow of water is controlled by large valves.

Copyright, Underwood & Underwood

German battle-cruiser "Seydlitz," as she lies at Scapa Flow

Now, since these openings are fully 30 feet below the surface, there must be a pressure of nearly a ton per square foot upon the valves. In preparing to sink the ships, all that would be necessary would be to take out a section of pipe between the inlet valves and the condensers. On opening the Kingston valves, as they are called, the water would rush into the engine rooms of the "Seydlitz" under a pressure, as noted above, of nearly a ton per square foot.

But there are many other pipes, inlet or outlet, opening through the bottom or side of the ship; and if all of these were opened in such a way as to permit a free inflow and if the watertight doors and other connections through the bulkheads, such as piping, etc., were left open, it would not take long to put the largest ship down.

The "Tennessee" of 28,000 horse-power requires two 28-inch main injection valves to control the intake of water for her condensers. The "Seydlitz," with 90,000 to 100,000 horse-power would require over three times that capacity, and the opening of these valves alone would suffice to sink the ship in a brief space of time, if the water-tight doors leading to the engine rooms were open.

If it is doubtful if any extensive salvage operations will be carried out. Because of the differences in guns, shells, motive power, and miscellaneous gear and machinery, the ships would not match with those of any navy, and it is probable that the great cost of salvage operations in that remote and inhospitable spot would outweigh the value of the recovered vessels—if indeed they can be salvaged at all.

A Naval Land Gun That Can Fire from the Track at a Moment's Notice

By C. L. McCrea

IT will be remembered that when the heavy German long-range guns were bombarding the Allies on the western front last year, the Navy Bureau of Ordnance took some of the 14-inch 50-

caliber guns from our battleships and placed them on railway mounts, sending them abroad and getting them into action several months before the signing of the armistice. These guns were described in the SCIENTIFIC AMERICAN of February 8th, 1919. They were the only American made and operated heavy guns that fired against the Germans.

The original Navy gun car for mounting the monster 14-inch Navy gun, which weighs in the neighborhood of 95 tons, was a car 88 feet long, mounted on 24 wheels, and weighing, complete with the gun, about 275 tons. It was designed to allow the gun to fire directly from the rails at angles of elevation up to 15 degrees. When firing at higher angles of elevation, a pit was dug and a foundation of structural steel and timbers provided on which the gun car rested, so that while firing the gun became a fixed land mount.

The foundation was prepared in advance of the arrival of the gun car, a day's time being required for all preparations. The gun itself could, however, be moved from its foundation and made ready for transportation in a few minutes. On many occasions when the Huns were retreating, however, a big gun capable of firing 20 to 30 miles directly from the rails on a few moments' notice, without any preliminary preparation of the tracks, etc., would have been invaluable in destroying German troop trains, supply stations, etc. Neither the Americans nor the Allies had such a gun. Even the newest models and designs of French and American-French railway guns required special preparation of the railroad track before they could be fired—it was necessary to

(Continued on page 98)

The gun, 58 ft. 4 ins. long, weighs 95 tons. The gun, slide, elevating gear etc., weigh 160 tons. The girders supporting gun are 10 ft. deep by 94 ft. long and weigh 80 tons. The car and gun complete weigh 320 tons. Length of car, 130 ft. Maximum range of gun, 30 miles.
Naval 14-inch railroad gun that can fire from the rails at a moment's notice

Williams' "Agrippa" Turning-Tool Holders "The Holders That Hold"

WILLIAMS' "Agrippa" Tool Holders offer unusual variety of types and sizes for all regular machining operations.

In Turning-tools, the Set Screw Pattern is designed for those using cutters made of steel which has been hammered, or rolled, with a greater variation in size than is common to usual mill practice.

The Cam Pattern, for cutters of accurate size, provides greater strength and reliability than any other type of cutter-fastening.

Both patterns are illustrated above; both are made with right and left hand offset and straight shanks.

These tools measure up to the high standard of Williams' Superior Drop-Forgings and are unexcelled in quality and efficiency. They are absolutely dependable and are unconditionally guaranteed.

May we send you a copy of our Machinists' Tools Booklet?

J. H. WILLIAMS & CO.
"The Drop-Forging People"

Western Office and Warehouse:
28 So. Clinton Street
Chicago, Ill.

General Offices:
28 Richards Street
Brooklyn, N. Y.

BUBBLING FOUNTAINS FOR ATTACHMENT TO MUNICIPAL SUPPLY

Unequaled
Keith Bubbler
Unless otherwise
specified.

This cut shows our No. 604—75 lbs. of ice—cork insulation—15 1/2 coils of 1-2 in. brass tubing No. 22 Gauge. Thorough workmanship—selected materials—tested and adopted by those whose judgment is unquestioned.

Our lines include: Sanitary Wash Bowls (in Batteries), Bubbling Fountains (plain and ice cooled), Metal Lockers, Metal Stock and Pattern Storage Racks, Metal Shelving, Metal Cabinets, Vault Fixtures, Soda Kettles (40 and 60 gallons), Metal Stools and Chairs, Water Mixers, Work Benches, Bench Legs, Full line of Plumbing Fixtures, etc.

Many types and sizes. May have coil on bottom as well as on sides. Tasty—convenient—and efficient. Very attractive appearance.

Olive brown baked enamel finish—Pure white vitreous cast iron enameled bowl. Fittings—nickel-plated. Wastes above or below the floor.

Send for list of users

Many thousand in use

Send for catalogue

The Best is the Cheapest

M&Eco
Metal Equipment
For Shop And Factory

Works and mail address
Framingham, Mass.
186 Federal Street
Boston, Mass.

Manufacturing Equipment and Engineering Co

ICE
COOLED

Fig.
604

The Hook that Holds

Here is POWERSTEEL TRUCKLINE with patented Snaffle Hook. Attaches instantly and cannot loosen. Combined with famous Yellow Strand Wire Rope, it makes a truckline that's dependable under the heaviest strains. Also made with plain hook. Retail, east of Rockies, at \$11.30 with plain hooks; \$12.75 with Snaffle Hooks.

BASLINE AUTOWLINE is a smaller line for passenger cars. At dealers, \$5.80 east of Rockies. POWERSTEEL AUTOWLOCK foils car and tire thief. At dealers, \$2.35 east of Rockies.

BRODERICK & BASCOM ROPE CO., ST. LOUIS
NEW YORK
Manufacturers of Celebrated Yellow Strand Wire
Rope—Now Helping in World Reconstruction

**POWERSTEEL
TRUCKLINE**

A Naval Land Gun

(Continued from page 91)

place heavy reinforcing girders on the roadbed to absorb the shock of firing, as the guns were mounted without any provision for absorbing the recoil and lessening the reaction on the gun girders and the roadbed. Many thought and frankly stated it was impossible to design a gun that would fire at maximum elevation directly from a railroad track and be ready in any emergency.

As usual in the war, the man who said it couldn't be done was interrupted by the man who was doing it. Designs for a new monster gun car were commenced by the Bureau of Ordnance at the Naval Gun Factory in September, 1918, were completed in record time and a number of the cars themselves were under construction when the armistice was signed. Two of these cars were so far along when the armistice was signed that it was found more economical to go ahead and complete them than to cancel the orders. Had the war continued, they would all have been finished long before this, but with the slowing down of work on war material, it took some months longer than originally scheduled to erect them. The first of these cars was exhibited to the public at the Master Car Builders' Convention, held in Atlantic City, N. J., June 18th to 25th, 1919, it being regarded as a masterpiece of car building.

This new railway gun car mounts a 14-inch, 50-caliber naval rifle which can fire at any elevation up to 45 degrees with a corresponding maximum range of 53,000 yards, or about 30 miles. The gun is supported between two enormous bridge girders, 94 feet long and 10 feet high, and weighing 40 tons each, the complete girder unit weighing 80 tons. Two massive steel plates fitted to the inner sides of the girders carry the 95-ton gun with its slide and recoil mechanism.

The 14-inch, 50-caliber gun is 50 x 14 inches or 700 inches long. This is equal to 58 1/3 feet, and in order to balance the gun when in the slide which holds it, the axis of the trunnions is placed 17 feet from the breech. On firing, the gun recoils in its slide a distance of 44 inches, so that a clear space of about 21 feet in rear of the trunnions is necessary to enable the gun to fire. To give the gun an elevation of 45 degrees and allow for necessary clearance the trunnions must therefore be located about 16 feet above the rails. The top of the gun when horizontal then comes about 19 feet above the rails.

Now French tunnels are only 14 feet high (American tunnels are slightly higher). The Navy designers had to find a way of getting a 19-foot car through a 14-foot hole. They solved the problem by making the gun literally "crawl into its shell" when it has to travel over the railroads, crawling out again when it stops at the firing point.

The method of accomplishing this is as follows: The gun, its slide, elevating gear and the supporting plates, castings and braces are built into a single unit weighing some 160 tons and held by guides on the inner sides of the girders. When traveling, the entire unit is housed between the girders. In order to fire, the 160-ton unit is pushed up along the guides, at an angle of 45 degrees, for a distance of about seven feet by hydraulic power, and then locked into position by two heavy lugs. This raises the trunnions a vertical distance of about five feet. To change from traveling to firing position takes about six minutes' time. Power for raising the gun is supplied by a gasoline-engine-driven hydraulic pump located under the forward end of the gun car, where it cannot be struck by fragments of enemy shells when the gun is in action.

All the structural framework on the top of the gun girder at the breech of the gun is readily detachable so that nothing projects above the top of the girder when the gun is in traveling position, except the recoil cylinders of the gun slide.

LEGAL NOTICES

PATENTS

IF YOU HAVE AN INVENTION which you wish to patent you can write fully and freely to Munn & Co. for advice in regard to the best way of obtaining protection. Please send sketches or a model of your invention and a description of the device, explaining its operation.

All communications are strictly confidential. Our vast practice, extending over a period of seventy years, enables us in many cases to advise in regard to patentability without any expense to the client. Our Handbook on Patents is sent free on request. This explains our methods, terms, etc., in regard to Patents, Trade Marks, Foreign Patents, etc.

SCIENTIFIC AMERICAN

contains Patent Office Notes. Decisions of interest to inventors—and particulars of recently patented inventions.

MUNN & CO., SOLICITORS OF PATENTS
626 Woolworth Bldg., NEW YORK and 625 F Street, WASHINGTON, D. C.
801 Tower Bldg., CHICAGO, ILL.

Annual Subscription Rates

Scientific American Publications

Scientific American (established 1845) one year \$5.00
Scientific American Supplement (established 1876) one year 5.00

Postage prepaid in United States and possessions, Mexico, Cuba and Panama

Foreign Postage

Scientific American \$1.50 per year additional.
Scientific American Supplement \$1.00 per year additional.

Canadian Postage

Scientific American 75c per year additional.
Scientific American Supplement 50c per year additional.

The combined subscription rates and rates to foreign countries, including Canada, will be furnished upon application

Remit by postal or express money order, bank draft or check

Classified Advertisements

Advertising in this column is \$1.00 a line. No less than four nor more than 12 lines accepted. Count seven words to the line. All orders must be accompanied by a remittance.

METALS WANTED

FOR THE HIGHEST PRICES send us scrap platinum in any form, mercury, magnets, points, ores and amalgams, watches, false teeth, diamonds—anything valuable. Goods returned if our price is not O. K. Ohio Smelting & Refining Company, 224 Lennox Building, Cleveland, Ohio.

BUSINESS OPPORTUNITIES

SUBSTANTIAL Manufacturing Corporation wants capable men to establish branch and manage salesmen. \$300 to \$1500 necessary. Will allow expenses to Baltimore as explained. Address, Treasurer, 416 N. Howard St., Baltimore, Md.

WANTED

THE exclusive manufacturing rights of some machine, device, or article in the metal line—patented or otherwise, by one of the most completely equipped manufacturing plants in Indiana. Address: W. M. F.—P. O. Box No. 263, Bedford, Indiana.

INVENTIONS

HAVE you a practical invention to sell outright or place on royalty? Send details to Adam Fisher Mfg. Co., 78, St. Louis, Mo.

SOLVINE BOILER PRESERVER

Warranted, without reserve, to remove boiler scale prevent pitting and scale formation. Pamphlet on request. Money back guarantee. SOLVINE MFG. CO. Jersey City, N. J.

ICE MACHINES

Corliss Engines, Brewers and Bottlers' Machinery

The VILTER MFG. CO.

899 Clinton Street Milwaukee, Wis.

THE BRIDGEPORT CHAIN CO.
Specialists in Small Wire Shapes & Flat Stampings
Bridgeport, Conn.

A 96-PAGE CATALOGUE OF

Scientific and Technical Books

listing 2500 titles on 500 subjects, may be secured by addressing

**SCIENTIFIC AMERICAN
PUBLISHING CO.**

Woolworth Bldg., New York

A detachable armor plate cab will be provided for protecting the gun from enemy shell-fire if it is found that the guns are to operate on land against objectives as did the original U. S. Naval Railway Batteries.

An air compressor for supplying compressed air to the gun, for closing the breech, assisting in bringing the gun back to battery after firing, and for the ejection of powder gases after each shot, and a winch are located over the front trucks.

Completely equipped, the gun car weighs about 320 tons. It is supported on two pairs of 20-wheeled trucks, making a total of 40 wheels. Although over 130 feet long, it can travel any railroad, around any curve or on any bridge over which a standard freight locomotive is able to pass.

In operation, this gun will be provided with at least one ammunition car which will be coupled directly to the gun car. The 1,400-pound shells and the 400-pound powder charges will then be rolled on a monorail car from the ammunition car to the gun car, and will be picked up and loaded directly into the gun. The gun will be loaded with the muzzle slightly depressed in order to facilitate seating of the shell. Elevating will be done by hand, wheels being provided on either side of the gun car for this purpose. The gun is so well balanced that one man can easily elevate it.

Although the war is over, and they are now not needed for shooting up "Hun" railroad lines and fortifications, these guns will be extremely valuable for coast defense. Should an enemy appear off either of our coasts, word can be flashed to the commanding officer of one of these traveling land batteries, and the gun can start as soon as a locomotive can be hooked to it. It can make the transcontinental trip in a week's time. The gun will fire from curved sidings placed at points of vantage along the coast. Its fire will be at least as accurate as any from an enemy ship, and will by far outrange the guns of any ship now afloat. These same 14-inch guns have proved, during long operation in France, that they are the most accurate long-range guns in the world, and that, with proper airplane observation of their shooting, they can readily reach and demolish their target.

Does Plate Glass Fade?

SEVERAL years ago a contract was taken to supply a vertical installation of prisms in a store front of a haberdasher in the main business thoroughfare of Indianapolis, Ind. To install the prisms properly it was found necessary to cut off five feet from the top part of the plate glass, which had been in position for a number of years and exposed to the sun's rays during much of the time.

After the prisms had been installed the five-foot piece of plate glass salvaged was thoroughly cleaned and polished and consigned to stock for resale. In the course of time this salvage piece of glass was sold, to be used in a front window of a new residence in one of the principal streets in the fashionable residence section. The house was completed and the owner, having taken possession, was thoroughly enjoying the sensations of the new home, when the family began to receive telephone calls of a rather puzzling and perplexing nature, asking the price and how quickly delivery could be effected in various quantities of *Shirts Made to Order*. A certain wag in the community called up the owner, complaining that he, the owner, had made a mistake in building a shirt factory in that neighborhood, and that if he persisted in operating a factory in his residence, in all fairness and consideration to his new neighbors, he should at least remove all advertising from his front window.

The daughter of the house becoming thoroughly aggravated and annoyed at what she presumed was a practical joke of some sort, proceeded to make an investi-

gation on her own account, which resulted in the writer being requested to call at the house. He was greeted at the front door by Mr. Owner and asked whether the plate glass furnished was really first grade or second handed? To the reply that, from a close inspection at that moment, it was a beautifully polished high grade piece of plate, and to all appearances, absolutely without blemish, he assumed a peculiar knowing smile and asked me to walk down the street with him a short distance; turning abruptly at perhaps fifty paces, he asked me to look at the window. To my astonishment plainly legible at the particular angle, at which we stood, were the words: JOHN DOE—SHIRTS MADE TO ORDER.

What seemed to be a phenomenon was easily explained. Previous to the plate glass being removed from the show window of the haberdasher, there had been pasted white enameled letters, "*John Doe—Shirts Made to Order*." These letters being subjected to the direct rays of the sun for a period of years had prevented the fading of the glass (originally green) to a clear white as was the case with that portion which was not immediately back of the opaque enameled letters. The unfaded portion consequently stood out in contrast in its original green, but was not discernable, except at a certain angle.

How Do Rats Carry Eggs?

THIS is a mystery enacted, in one form or another, annually on thousands of farms, and sometimes even in city homes. The housewife has an accumulation of eggs ready to go to market. They partially fill a wooden crock, set on a box in the cellar. One evening the contents are intact; the next day they have vanished, with not a sign to indicate where or how they have gone.

Or maybe the farm-boy has a hen setting on 15 eggs, in a box high up from the floor. He finds the hen off after several days, and casually counts the eggs. Two are gone. Critically examining the nesting materials, he finds no indication that the hen has broken the eggs. The following day he finds a third egg vanished, the second day, two others gone. Then, suddenly, the trusted broody hen leaves her nest, "broken up." Rats? It doesn't seem possible, yet the farm-boy knows the explanation really is rats. They have been practicing such magic in the poultry-house for generations.

How do rats carry eggs? Some time ago the query was put to the most famous of all American naturalists, John Burroughs. He admitted that he didn't know. He had heard an explanation, current among farmers, but he couldn't say that it was the correct one.

The mystery of how rats carry eggs is unsolved "officially" after hundreds of years of conjecture. That eggs disappearing are borne off by rats is proved clearly enough by the discovery of whole, uncracked eggs beneath floors, in partitions, and other hiding places. In farming communities various theories are advanced and every now and then some one actually claims to have seen the rats at work. These eye-witnesses of a most unusual thing say the rat holds the egg between chin and forefeet, or hugged tightly between the forefeet; that he tumbles off elevations deftly protecting the egg as he falls; that usually there is a crowd of rats about to drag the egg rat, lying on its back, by the tail across the floor to the hole.

Others say the rat carries the egg, held between folds of skin under the chin, without assistance. The general testimony, however, would explain such a conflict of opinion. It is agreed that rats work in gangs when egg-carrying, and that it is difficult to determine from a distance exactly what they are doing among themselves. It is said there is always much squealing, but whether because some are getting hurt, or by contrast are hugely enjoying themselves, is not indicated.

Better Than Sawtooth —Costs Less

The wider the building, the less satisfactory is a sawtooth roof. Every object under it has a light side and a shadow side. The glare when facing the sash is so harsh that workers are placed with their backs to it where possible.

Ventilation is also poor, as very little fresh air reaches the central area. Substitute for the sawtooth a

Pond Truss

PATENTED
THE ROOF THAT VENTILATES

and an actually smaller sash area will give better lighting, because the light enters from all directions, hence glare and harsh contrasts are avoided.

Ventilation is effective also, because the roof tends directly to draw air to the center.

For general manufacturing the roof need not be high. If the building is very wide two or more Pond Trusses may be used, with inlets for air and light at low points in the roof between them.

We invented the Pond Truss to get maximum results from POND CONTINUOUS SASH. It is patented: we license its use where Lupton Products are used in the same building.

Our Service Department will gladly co-operate with your architect or engineer. We design every Pond Truss roof to fit the special requirements of the case.

Write for booklet, "Air, Light and Efficiency"

DAVID LUPTON'S SONS COMPANY

Clearfield & Weikel Sts.

Philadelphia, Pa.

Makers of modern equipment for daylighting and natural ventilation
Canadian Mfrs: The A. B. ORMSBY CO., LTD., Toronto

The illustrations show main manufacturing building of Dayton-Wright Airplane Co. Messrs. Schenck & Williams, Architects; A. R. O. Kressler, Plant Engineer.

Size 270x1000 feet. Will eventually be 870 feet wide. Roof has two Pond Trusses, with Pond A frames between Pond Continuous Sash used in all roof openings

Pond Continuous Sash for Pond Truss, sawtooths, monitors and side walls

Pond Operating Device for long lines of sash
Lupton Rolled Steel Skylight

Lupton Steel Sash
Pivoted Factory Type
Counterbalanced Type
Counterweighted Type
Lupton Steel Partition and Doors

Lupton

INVESTMENT VALUE

Monarch Lathes

Quantity production of a high class machine tool has made possible the low price of MONARCH Lathes. Made up to 30 in. swing. Every one guaranteed to give satisfaction to the purchaser. There is a Monarch lathe to meet your needs. Write for a catalog.

The Monarch Machine Tool Co.

America's Largest Lathe Builders

103 Oak Street

Sidney, Ohio

insure maximum safety and minimum cost in safeguarding electrical circuits against the fire and accident hazards of overloads and short circuits. An inexpensive "Drop Out" Renewal Link restores a blown Economy Fuse to its original efficiency. The Economy is a pioneer renewable fuse. As compared with the use of one-time fuses, it cuts annual fuse maintenance costs approximately 80 per cent.

ECONOMY FUSE & MFG. CO.

Chicago, U. S. A.
Sole manufacturers of "ARKLESS" the Non-Renewable Fuse with the 100% Guaranteed Indicator.
Economy Fuses are also made in Canada at Montreal