An illustration of the use of rubber gloves and safety shields by a lineman working among many wires on a corner pole. Lack of these precautions has resulted in loss of life, and the use of these safeguards should be made mandatory in work of this character.

Accident Prevention*

By James B. Douglas

Accident Prevention Means the Avoidance of Untold Misery, Greater Efficiency, and a Better Feeling Among Workingmen and Their Employers

A sledge found in actual use. A badly mushroomed head will be noted, in addition to the splintered handle. Such tools are extremely dangerous, not only to those using them, but to persons near by, for the handle may break and permit the head to fly and do injury.

WORKMEN'S compensation laws are now in operation in many of our States. Twenty-six either have these laws in operation or their preliminary bills pending, and

*An amplified revision of an illustrated talk on accident prevention in certain public utilities presented at the Public Policy Meeting of the Thirty-sixth Annual Convention of the National Electric Light Association, Chicago, June 4th, 1913. Copyright 1913, by United Gas Improvement Co.

to this fact much of the progress in accident prevention is actually due,—because every law or bill provides for compensation to an injured employee regardless of the person at fault. In addition to the good done by these laws in the prevention field, they also mean a welcome decrease in misunderstanding and litigation between employer and employee, as the schedules of compensation are specific and automatic.

As a rule, it may be said that it is not the failure of machinery or apparatus that swells the accident total, nor is it the obscure electrical or mechanical hazard, but it is the seemingly endless number of simple and apparently trivial hazards or practices, easily recognized by one *not daily on the premises*, that causes the most suffering and loss.

First Aid is important in its place, but treatment of

In many yards, ladders made simply of a pair of "two by threes" with cross strips nailed on as rungs, are in common use. The one shown, with the rungs set in and nailed, is probably as safe as a ladder of this kind can be made, but in climbing it in the manner shown, the workman has pulled a weak rung and is in danger of a nasty fall. The rungs should be mortised into the standards, instead of being nailed on as shown.

The safe method of climbing ladders. With the hands grasping the standards of the ladder illustrated, there is no danger of the rungs pulling out and throwing the workman. This and the preceding photograph were taken near a coal wharf, and it will be noticed that the workman is alive to more than one phase of the safety question. He wears goggles to avoid the danger accompanying flying coal dust and grit.

An ordinary coal trestle over which is drawn a train of loaded cars. A little farther to the right, the trestle runs over a busy public highway. It will be noted that several large pieces of coal have dropped from the cars to the edges of the trestle work and are liable to fall on the workmen below. This hazard can be overcome only by constant watchfulness, to see that the cars are not overloaded, and that the trestle and platforms are kept clear.

Here is seen a picture of a shovel, a rake and an oil can, grouped for the purpose. The shovel lies as shovels are frequently found on floors—in position to do serious injury. It may readily be appreciated how an employee running or walking carelessly might run directly into the broad edge of a shovel, which is at times as sharp as a knife. The rake introduces a liability of the teeth running into an employee's foot.

An emery wheel so guarded by an adjustable glass plate as to intercept flying emery, and thus avoid eye injuries. The iron wheel guard or hood, designed to protect workmen should the wheel burst, will also be noted. In addition the use of goggles is recommended. Reports of the number of injuries prevented by goggles are so numerous that there can be no doubt as to their value.

A particularly dangerous steam line outlet in front of a boiler. The outlet was about five feet above the floor and so placed that, should the valve be turned on, the escaping steam or hot water might scald a workman. An outlet of this sort should be arranged so as to discharge vertically, and under all circumstances be in a position to permit easy accessibility to it at all times.

An ordinary telegraph and lighting pole, to which permanent steps have been so fastened that it is a comparatively easy matter for a boy to climb them as shown. In one case, a boy climbed a pole similarly stepped, and was electrocuted. Sockets into which spikes or bolts may be inserted by the linemen in the exercise of their duty, may be used in place of steps up to sufficient height.

A manhole cover constituting a common tripping hazard. The tripping hazard, however, is not the only one. Owing to the size of the ring, the foot of an employee walking along, particularly at night, might become wedged in the ring and broken. The cover is just at the entrance to a building. The ring, of course, should be countersunk so as to drop level with the cover, in which case any mishap could be plainly avoided.

Wheelbarrows so stored that the handles may strike a passing employee in the groin. It merely suggests more careful storage, but telling workmen to be cautious and to take advantage of the safety methods provided will by itself accomplish little in the way of preventing accidents. The great desideratum is to educate an employee to be alive to even the slightest danger surrounding him—and to be careful.

Band saw not fully guarded. That part exposed to the greatest danger of breaking is immediately above the work, and it is a comparatively simple matter to fit a piece of channel iron, attached to the frame, directly over the saw in such a manner as to cover it almost completely and still not interfere with the work. A similar piece may be fitted to the back, so that in shifting work there will be no danger of striking the running saw and knocking it off the wheels.

this character should not be allowed to overshadow the vastly more important work of Accident Prevention. Thorough preventive measures will make first aid unnecessary.

In spite of the constant endeavors of workers in this field to bring the subject of safety effectively before employes by means of talks and demonstrations, the difficulty seems to have been to draw it to their attention in forms which they can understand and readily use, and it is this need that this little book is, in a measure, intended to fill. Though this material has been designed for the use of superintendents, the nature of the conditions to which attention is drawn is such that the illustrations should prove of value to foremen and employees in general, who, it is hoped, will thoroughly familiarize themselves with the hazards indicated, in order that they may promptly recognize any similar hazards within their own territory.

The illustrations are taken from a collection used in the form of lantern slides, which have been found, along with motion pictures, to be the best way to bring the

various risks impressively home to neglectful employees.

While we all, of course, desire to prevent accidents from a humanitarian viewpoint, the consideration being an economical one as well, we should ever bear in mind that an accident avoided means money saved, efficiency undisturbed, production uninterrupted.

Inherent in all men is a tendency to carelessness which, in many hazardous occupations, reaches a point where familiarity with the risk occasions a sort of contempt that only too often results disastrously.

When thought is given to the innumerable activities of everyday life, it is remarkable how little the average man seems to think or care about the hazards surrounding him on every side. As a rule he does not see how they can affect him. Even where a man has witnessed an accident due to carelessness, the lesson is shortlived at best. He may have his own ideas as to who or what was to blame for the mishap, and, thinking that he will not repeat the mistake, becomes possessed by a feeling of security and self-sufficiency which at times results in the happening of the very

accident for which he should have been prepared through the experience of his fellow-man.

Merely telling workmen to be careful and to take advantage of the safety devices provided will by itself accomplish but little in the way of preventing accidents. Warnings too often repeated and insufficiently varied, lose much of their effectiveness, no matter how attractively worded, but in using the experience of others and applying the lesson directly, the workmen become awakened to the fact that they are the greatest losers through preventable accidents.

It is said that a burnt child dreads fire, but it seems absurd for a man to wait for an accident to happen to him before he takes measures against its recurrence. A man differs from a child in that his mind is developed to such a point that he should profit by the mistakes of others without the necessity of personal experience entering into the question.

It is clear therefore that the great desideratum in accident prevention is that of educating the employees to be alive to the danger surrounding them, and to take

The engineer was actually seen as shown, wiping the face of a pulley carrying a large belt from an engine to a blower, while the belt was running at high speed. A mere slip, or the catching of a strand of waste in the running belt, might carry the employee's hand around the pulley, and cause the instant loss of an arm, if not of a life. The belt was guarded and instructions given how to handle.

Two types of hammers; the ordinary carpenter's, and the newer style with scored face. The statement has been made by one company that during a period of nine months, four workmen lost an eye each, due to nails flying when struck on a slant by the ordinary smooth-faced carpenter's hammer in rough work, and that since adopting the indented-head style, the hazard has well been eliminated.

At times sections of tin or corrugated iron are used to cover small openings and depressions in yards. As shown, these strips in time become buckled and raised at the edges, thereby presenting a mean hazard, particularly where employees are engaged in night work. If the obstruction is low, tripping may result only in a fall, yet even this may turn out seriously.

Hazard accompanying the standing of clinker bars, etc., against walls, pipes, or in similar locations. This workman was injured by a bar falling from the position shown. If these tools are not placed in racks, it is well to lay them flat, close to walls, where they will not cause persons to trip, or to stand them between short guide bars extending out from the wall, well above the floor.

A conveyer and crusher beside a gas house. On the side of the boxed-in conveyer is a ladder, used at times while the crusher is in operation. The hopper directing fuel into the crusher is immediately under the ladder and no guard is provided to prevent a person falling directly into the moving crusher rolls, should he slip from the ladder. The hazard presented by exposed gearing has been overlooked.

A guard, or shield, platform (indicated by the white line at the top of the hopper) to prevent a person, should he slip off the ladder, from falling into the hopper. The gearing, indicated by the arrow, has been inclosed. An employee while working around the hopper of another crusher, in some way got his arm caught in the rolls, and sustained permanent injury.

care of themselves—to be careful. The very nature of the struggle for the survival of the fittest arouses in men a selfishness of which full advantage must be taken in order that the desired results in accident prevention may be achieved. Taking any given number of hazards, a certain proportion will, without fail result unfavorably to the man taking the chances. The odds from the outset being against the man who puts himself in a position where there is a liability of injury, no one can afford to take the risk

It has been well said that *Accident Prevention Saves Misery and Money*. Until within the last few years this twofold saving has not been appreciated, and in striving to increase outputs and sales, the avoidance of accidents has been overlooked as one of the factors reducing the cost of operation. Employers at times have been slow to awaken to the fact that most of the many simple accidents could have been avoided, and have not seemed to consider seriously the great double saving to be effected through prevention. As has been indicated, efforts have been directed mostly towards reducing costs and increasing sales, with little, and at times, apparently, no regard for the saving coincident with intelligently directed work in the prevention field. It surely pays to concentrate on prevention; the *safe* way is the *progressive* way of protecting both employee and employer. A catastrophe avoided may mean lives saved and receivership averted.

An accident removes from his place, for the time being, the man his employer considers most capable in the line of work at which he is engaged. If it were not so, this man would not be holding his position. Through an injury the employer loses his services, and must replace him, temporarily at least, with a man lacking his experience and those qualities which earned him his place. Such an interruption cannot fail to show its effect on the efficiency of the plant; it disturbs the productive power and brings suffering into the family of the injured.

From any viewpoint, leaving out of consideration the humanitarian aspect of the question, the industrial loss is such as to warrant the most thorough precautions to prevent accidents, not only on the part of the employer, but of his employees as well. Accident prevention assures each workman that his normal industrial longevity will not be curtailed through the medium of preventable accidents.

To accomplish this result, the whole-hearted co-operation of employer and employees is necessary. The welfare and freedom of mind that follow the thoughtful and careful attention paid by employer and employees to the prevention of accidents, to a large extent determine the efficiency of the working force of a plant. The employer should give every consideration to suggestions that might improve the working conditions, while on the other hand every employee should consider himself an inspector for his employer in the line of work at which he is engaged. He should feel it his duty to report to his superiors any defect in materials, methods or men that may come to his attention. Every workman should realize that his own freedom from injury depends on the care exercised by him and his fellow

employees, and that their safety mostly rests with themselves.

It has been variously estimated that from 30% to 50% of industrial accidents are preventable. Certain lines of endeavor include operations from which danger can never be entirely eliminated, but in all cases, carefulness brings its own reward in a marked decrease in the number of accidents, and in a reduction of the seriousness of such as may not altogether be avoided.

Presentable accidents may be classified under the following heads:

- First: Use of a wrong method by the workman.
- Second: Carelessness by the workman of his own safety and that of his fellow employees.
- Third: Defective or unguarded machinery, tools, appliances, etc.

By far the largest number of accidents falls into the first two classes. Only care on the part of the workmen as a class will reduce the number of accidents due to these causes. The suffering and loss of time caused by accidents surely warrant the exercise of the greatest degree of care on the part of the men in the prosecution of their work, and call for their heartiest co-operation with their employers in the endeavor to prevent, and to reduce the number of, accidents.

The following illustrations of conditions, which actually have, or at any time might have, caused serious accidents, have been secured from various widely scattered sources, and many of them have formed the basis of several talks on Safety and Accident Prevention Work.

Doubtless each reader can, from his own experience, recall at least one instance of sad loss and heavy cost due to accident. When it is realized that this loss might have been avoided, we find ourselves among those anxious to seize the first opportunity to join in and throw telling efforts into the great and good cause of Prevention.

In 737 cases, at least one day's time was lost. The total time lost was 4602 days, or, on the basis of 300 working days, nearly 16 years. The average loss of time in cases where at least one day's time was lost was 6 2-3 days, practically a working week.

Of the entire number of accidents, 2,200 about 65% resulted in a loss of time that amounted only to that necessary for the proper medical attention. On the other hand, in many cases the employee was assigned to other work not necessitating the use of the injured member. However, in all cases, the suffering, inconvenience and interference with the regular line of work were so great, and so many of the accidents could have been avoided by the slightest of precautions, that these figures furnish a powerful argument in favor of the *value of care*.

In numerous instances, the prompt and efficient administration of first-aid treatment alleviated the pain and suffering to such an extent that the time lost was almost negligible, but in all minor injuries, the danger of infection through lack of attention to the wounds is so great that no one can afford to take chances.

An analysis of over 2,000 miscellaneous accidents to *employees* shows them to have been due to the following:

CAUSES OF ACCIDENTS.

	Number.	Percentage.
Falling objects.....	113	5.1%
Flying objects, cinders, dust, splashing solder, etc.....	138	6.3%
Protruding objects or materials....	250	11.4%
Hanging or swinging objects or materials.....	39	1.8%
Stepping on or being caught by projecting nails, broken glass, etc.	138	6.3%
Machinery in normal operation....	126	5.7%
Defects, or lack of guards, on machinery.....	10	.5%
Elevators, hoisting apparatus, etc..	33	1.5%
Handling materials.....	276	12.5%
Slipping, tripping or falling.....	282	12.8%
Electric shock.....	12	.5%
Falling in or through openings.....	4	.2%
Handtools used by injured.....	322	14.6%
Tools used by fellow employees....	26	1.2%
Hot objects or materials.....	186	8.5%
Leaking gas, sickness, etc.....	8	3.6%
Miscellaneous.....	165	7.5%
	2200	100.0%

The injuries resulting from these accidents were as follows:—

EFFECTS OF ACCIDENTS.

	Number.	Percentage.
Fractures or sprains of		
Arms, hands or fingers.....	58	2.6%
Legs, feet or toes.....	32	1.5%
Bones of body and head.....	26	1.2%
Eye injuries or strain.....	180	8.2%
Lacerations or contusions		
Head.....	64	2.9%
Face.....	59	2.7%
Body.....	66	3.0%
Arms.....	69	3.1%
Hands.....	273	12.4%
Fingers.....	638	29.0%
Legs.....	144	6.5%
Feet.....	150	6.8%
Toes.....	25	1.1%
General.....	66	3.0%
Strains or ruptures.....	63	2.9%
Illness.....	80	3.6%
Burns of		
Body.....	20	.9%
Face.....	25	1.2%
Limbs.....	162	7.4%
	2200	100.0%

Tree-planting Societies in Norway.—The once rapidly dwindling forests along the coast of Norway are being made to flourish again by the vigorous efforts of a large number of three-planting societies. During the past 13 years these societies have set out more than 36 million young trees. In the two counties of North and South Bergenhuus alone there are 144 tree-planting societies, which last year planted 2,276,000 trees.

SCIENTIFIC AMERICAN SUPPLEMENT

Copyright 1913 by Munn & Co., Inc.

VOLUME LXXVI
NUMBER 1971

NEW YORK, OCTOBER 11, 1913

[10 CENTS A COPY
\$ 5.00 A YEAR]

A constantly increasing number of persons owe their lives to the use of this apparatus, which has been remarkably successful in gas and electric accidents, as well as in other cases involving suspended animation. The company has installed pulmotors in accessible positions at its various works.

In a store room were found heavy sledges on top of bins ten feet from the floor, which was caused to vibrate constantly by machinery. On the right will be noticed several projecting chisels which could easily be pushed back, and so stored that there would be no danger to the head of a passing employee.

Sketch of a simple device for preventing injuries to elevator operators. The guard plate engages the operator's foot, and either returns it to the platform of the ascending elevator, or gives him sufficient warning to withdraw it himself, and thus prevents crushing. Grievous injuries have been sustained where this hazard has not been taken care of.

A simple hazard which resulted in a fractured foot is shown here. It consists of a short section of bent pipe which may have been placed at one time to mark the limit of an oxide bed. In this instance an employee's foot was caught and injured in the manner shown.

This picture was taken to show how employees trip over tools lying on operating floors. When thought is given to the innumerable activities of everyday life, it is remarkable how little the average man seems to think or care about the hazards surrounding him on every side.

An ugly hazard. As will be noted, the valve stem is at eye-level. The workman was photographed in the act of passing down stairs. His right foot is on the landing of the stairs, which he is facing, and which are not shown in the picture.

Picture taken to show the occasion for a guard within a guard at times. In this instance, an employee came out of the building on which the lamp is located, holding, and looking at, a chisel he was about to sharpen, and inadvertently walked through the open gateway. He unawares stepped into the separator and was scalded. Both wells are now guarded.

An exposed handle on the cover of a well, illustrating how easily an accident might occur. Under the circumstances, a fractured foot or kneecap is imminent. It is, of course, a matter of no expense to countersink the cover so that the handle will drop into, or fall flat with, the lid when not in use. A mishap under these conditions is the result of an undue feeling of security and self-sufficiency.

An exhaust pipe projecting through a window in an engine-room out into a passageway. The danger of being scalded by steam or hot water ejected from this pipe was made all the more serious by the fact that the engine was run intermittently. In an instance in which an exhaust pipe was placed somewhat lower than the one shown here, a boy's leg was scalded by the steam as he passed by.

ACCIDENT PREVENTION.—[See page 232.]

Copyright, 1913, by United Gas Improvement Co.